# ACR — The Arc Compute Rate

## OpenAPI 3.1.0 · endpoint reference

## Where to send it

| host | chain | serves |
|---|---|---|
| `https://acr-api-1fto.onrender.com` | Arc testnet (5042002) | **start here** — all 50 routes, and a faucet, so nothing costs real money |
| `https://acr-probe-free.onrender.com` | Arc mainnet (5042) | all 50 routes, reading real mainnet state. Holds no signing key |
| `https://acr-api-mainnet.onrender.com` | Arc mainnet (5042) | 44 of 50: `/par` and `/operator/*` answer 404 until its image is rebuilt |

## Paid endpoints (x402-gated) · 6

`GET /compute/{label}` — Compute

`GET /curve/{index_id}` — Curve

`GET /prints` — Prints

`GET /prints/{index_id}` — Print One

`GET /seller-scores/{index_id}` — Seller Scores

`GET /vol/{index_id}` — Vol

## Free endpoints (no payment required) · 42

`GET /` — Root
`GET /agent/challenge` — Agent Challenge
`GET /agent/info` — Agent Info
`GET /agent/whoami` — Agent Whoami
`GET /armor/info` — Armor Info
`POST /demo/attack/start` — Demo Attack Start
`GET /demo/attack/status` — Demo Attack Status
`POST /demo/buyer/start` — Demo Buyer Start
`GET /demo/buyer/status` — Demo Buyer Status
`POST /desk/challenge` — Desk Challenge
`POST /desk/faucet` — Desk Faucet
`POST /desk/limits` — Desk Limits
`POST /desk/pass/claim` — Desk Pass Claim

*Rendered by `scripts/gen_openapi_doc.py` from `app.openapi()` — 48 routes; 9 operator routes omitted on purpose. `make openapi-doc-check` fails when this is stale.*