

ACR — The Arc Compute Rate

OpenAPI 3.1.0 · endpoint reference

Live spec: `https://acr-api-mainnet.onrender.com/openapi.json`

Catalog: `https://acr-api-mainnet.onrender.com/marketplace/catalog`

Index endpoints: **\$0.0001 USDC per request**, x402 `exact` scheme,

Circle Gateway (GatewayWalletBatched), network `eip155:5042` (Arc mainnet).

Fleet sellers (`/compute/{label}`) price per unit; the catalog carries each one's terms.

Agent-to-agent calls may present an `AGENT-CARD` (see `GET /agent/challenge`);
carded tape reads pass Google Cloud Model Armor in both directions (`GET /armor/info`).

Paid endpoints (x402-gated) · 6

GET /compute/{label} — Compute

GET /curve/{index_id} — Curve

GET /prints — Prints

GET /prints/{index_id} — Print One

GET /seller-scores/{index_id} — Seller Scores

GET /vol/{index_id} — Vol

Free endpoints (no payment required) · 37

GET / — Root

GET /agent/challenge — Agent Challenge

GET /agent/info — Agent Info

GET /agent/whoami — Agent Whoami

GET /armor/info — Armor Info

POST /demo/attack/start — Demo Attack Start

GET /demo/attack/status — Demo Attack Status

POST /demo/buyer/start — Demo Buyer Start

GET /demo/buyer/status — Demo Buyer Status

POST /desk/challenge — Desk Challenge

POST /desk/faucet — Desk Faucet

POST /desk/limits — Desk Limits

POST /desk/pass/claim — Desk Pass Claim

*Rendered by `scripts/gen_openapi_doc.py` from `app.openapi()` — 43 routes;
2 operator routes omitted on purpose. `make openapi-doc-check` fails when this is
stale.*