Comparative Benchmark of Picard Iteration vs. Learned Neural SDEs on Classical and Time-Fractional Black–Scholes Problems

Quantitative Research Sprint Checkpoint Deliverable

October 10, 2026

Abstract

We present a pre-registered computational benchmark evaluating Picard iterative contraction against learned Neural Stochastic Differential Equation (NSDE) surrogates for European call pricing. The study isolates Classical Black–Scholes–Merton (BSM) and Caputo Time-Fractional BSM (TFBSM) into distinct experiment blocks. We show that while NSDEs provide fast amortized inference, they suffer from boundary arbitrage violations and fail to capture extreme subdiffusive memory regimes ($\alpha < 0.35$), whereas Picard schemes maintain rigorous error bounds and numerical stability across all domains.

1 Governing Equations & Setup

1.1 Block A: Classical BSM

In log-moneyness $x = \ln(S/K)$ and forward time $\tau = T - t$, the discounted call $u(\tau, x) = e^{r\tau}V/K$ satisfies:

$$\partial_\tau u = \frac{1}{2}\sigma^2 \partial_{xx} u + \left(r - \frac{1}{2}\sigma^2\right)\partial_x u \tag{1}$$

Applying the Duhamel principle with Gaussian heat kernel $G(\tau, x)$ gives the Picard operator:

$$u^{(k+1)} = u^{(0)} + \int_0^\tau G(\tau - s, \cdot) * \left[\left(r - \frac{1}{2}\sigma^2\right)\partial_x u^{(k)}\right] ds \tag{2}$$

The benchmark uses double-precision analytical solutions as ground truth and compares against a 3-layer MLP Neural SDE (64 hidden units, SiLU activation).

1.2 Block B: Time-Fractional BSM

The Caputo time-fractional PDE of order $\alpha \in (0, 1)$ is:

$${}_0^C D_\tau^\alpha V(\tau, S) = \mathcal{L}_{BS} V(\tau, S) \tag{3}$$

where $\mathcal{L}_{BS} = \frac{1}{2}\sigma^2 S^2 \partial_{SS} + rS\partial_S - rI$. The equivalent Volterra integral equation of the second kind is:

$$V(\tau, S) = V(0, S) + \frac{1}{\Gamma(\alpha)} \int_0^\tau (\tau - s)^{\alpha-1} \mathcal{L}_{BS} V(s, S)\, ds \tag{4}$$

The numerical ground truth is an L1 finite-difference scheme evaluated on a graded temporal mesh $\tau_n = T(n/N_\tau)^{(2-\alpha)/\alpha}$.

2 Experimental Results

The benchmark was frozen prior to evaluation using Sobol sampling over in-domain and out-of-distribution (OOD) spaces ($K = 100$).

Block	Solver	Domain	RMSE	MaxAE	Arb. Fail
A (BSM)	Picard	In-Domain	**0.00014**	**0.00048**	0.0%
A (BSM)	NSDE	In-Domain	0.04021	0.12450	0.0%
A (BSM)	Picard	OOD	**0.00041**	**0.00118**	0.0%
A (BSM)	NSDE	OOD	0.42850	1.68400	**5.0%**
B (TFBSM)	Volterra-P.	$\alpha \geq 0.55$	**0.00280**	**0.00940**	0.0%
B (TFBSM)	Frac-NSDE	$\alpha \geq 0.55$	0.08940	0.38500	0.0%
B (TFBSM)	Volterra-P.	$\alpha \leq 0.35$	**0.02140**	**0.07820**	0.0%
B (TFBSM)	Frac-NSDE	$\alpha \leq 0.35$	1.34100	4.28000	**13.3%**

Table 1: Pricing error metrics and failure audit.

3 Failure Regimes & Discussion

1. **Arbitrage Bound Violations:** In deep out-of-the-money regimes ($S < 50$), the Neural SDE generated negative option values violating the lower bound $\hat{V} \geq \max(S - Ke^{-rT}, 0)$, producing a 5.0% failure rate. The Picard solver strictly maintained no-arbitrage bounds across all test points.

2. **Subdiffusive Memory Breakdown:** For low fractional orders ($\alpha \in [0.18, 0.35]$), the kernel singularity $(\tau - s)^{\alpha-1}$ destabilizes the standard continuous Brownian convolution in the Fractional NSDE, resulting in an RMSE spike (1.341) and high variance across Monte Carlo evaluations.

3. **Contraction Stability:** Picard iteration converged within 12 iterations for Block A ($\hat{L}_k \leq 0.45$). In Block B, contraction slowed as $\alpha \to 0$ ($\hat{L}_k \to 0.94$), but preserved monotonic convergence without divergence.

4 Conclusion

Picard iterative integration guarantees numerical stability, theoretical error control, and arbitrage consistency, outperforming learned Neural SDEs in stress regimes. Future iterations will investigate hard boundary projections for neural diffusion surrogates.