Progress Report 2 - Group 16

Resource Isolation and Fair Scheduling in a MoQT Relay

Kaustubh Bhal, Shradha Gandotra, Rudra Kanani, Sanat Dhanyamraju, Alan Zhu

November 10, 2026

1. Problem Definition

Our project studies how a Media over QUIC Transport (MoQT) relay should share memory and outgoing bandwidth among subscribers. A subscriber that stops keeping up can leave old media waiting for delivery. We want to limit the resources used by these subscribers while preserving useful service for other clients and keeping the benefits of a shared upstream track.

Since the first report, we have built a working local testbed and completed 20 baseline experiments using the existing relay. We can now generate repeatable media traffic, pause selected subscribers, measure their recovery, and compare them with subscribers that keep receiving normally. The cross-session scheduler and adaptive resource limits are not implemented yet; the results below establish the baseline for that work.

2. Motivation

For live media, receiving every byte eventually is not enough. Data that arrives several seconds late may no longer be useful. Our first results make this distinction concrete: after a 15-second pause, subscribers received data at roughly 10 Mbit/s even though the source produced only 4 Mbit/s. Much of that traffic was old backlog. This means a relay evaluation needs to measure delivery delay and useful throughput alongside total received bytes.

We also need to separate a slow client's own poor experience from interference with other clients. A useful policy should reduce unnecessary buffering and late delivery without lowering service for subscribers that can keep up.

3. Challenges

The first challenge was creating a valid slow-subscriber test. The client library reads QUIC data into its own cache, so slowing only the application's final reader would not necessarily apply backpressure to the relay. Our harness instead pauses MoQT session processing while leaving the QUIC connection alive. We record transport statistics to confirm that media traffic stops growing normally during the pause.

A second issue appeared during recovery. With the library's default incoming-stream allowance, both paused clients in an initial four-client test encountered a cancellation error when overlapping groups arrived. We configured all clients to accept one incoming unidirectional stream at a time, after which the recovery test passed. We did not change the relay or suppress the error. This setting also constrains the workload, so we cannot generalize the results to all client configurations.

Finally, the publisher, relay, and clients currently share one machine. Loopback tests are useful for repeatability and debugging, but they do not reproduce separate client links or prove that relay bandwidth is congested. Process memory also includes transport buffers and runtime overhead, so it cannot be treated as a direct measurement of cached media.

4. Methodology and Implementation Progress

We pinned Cloudflare's open-source relay to draft-16 revision `3b2b584` and built it without modifying its source. We added a Rust workload client with publisher and subscriber modes, plus Python scripts to start each experiment, collect measurements, and summarize results. Each subscriber has its own native QUIC connection.

The publisher sends one synthetic track using direct `PUBLISH`. It produces 30 Objects per second, each 16,666 bytes, for an actual target rate of 3.99984 Mbit/s. A new subgroup starts every second. Objects contain a sequence number and generation timestamp, allowing the receiver to check their contents and measure complete-Object delivery time. This exercises shared-track fan-out, but does not yet test upstream `SUBSCRIBE` aggregation.

We chose a paced synthetic workload first because it gives us a known offered load and makes a pause easy to reproduce. It does not include video decoding, keyframe-size bursts, or real network traces. Those remain follow-up workloads rather than completed experiments.

Setting	Completed local experiment
Hardware	Apple M2 Pro; 10 reported CPUs; 16 GiB RAM
Operating system	macOS 15.3.1, ARM64
Processes	One relay, one publisher, one subscriber generator; four runtime worker threads each
Subscribers	16 or 64 independent sessions
Paused subscribers	None or half of the sessions
Timing	30 seconds per subscriber; pause from second 5 to second 20
Receive limits	64 KiB per connection, 32 KiB per stream, one incoming unidirectional stream
Repetitions	Five per condition; condition order shuffled within each repetition

The harness saves Object logs, QUIC statistics, relay metrics, process memory and CPU samples, commands, configuration, and source revisions. All 20 measured runs completed with the expected subscribers and no client errors. During the pause interval, the publisher achieved 29.93-30.00 Objects/s. The paused connections received only about 25-34 KB each over 15 seconds while acknowledgements continued, confirming that the test created actual receive backpressure.

For PACE ICE, we have prepared a four-node launcher: one relay node, one publisher node, and two subscriber-generator nodes. It requests eight CPUs and 32 GiB of memory per node for 30 minutes. These are requested resources, not confirmed server specifications. The launcher records the actual machines, waits for each component to become ready, and collects logs before exiting. A local integration test of the four worker roles passed; no ICE experiment has run yet.

The ICE scripts follow the official Slurm launch documentation and link to GT's ICE job and storage guides. Before running there, we still need to confirm our account's allocation limits and shared storage location. We will first build Linux binaries and run a short check on an allocated compute node. Distributed latency results will also require checking clock offsets between machines. The full commands and these open checks are documented in `docs/pace-ice.md`. [4, 5]

5. Related Work

PicNIC: Predictable Virtualized NIC isolates virtual machines using CPU-fair queues, receiver-driven congestion control, and sender-side shaping and accounting. The main idea relevant to our project is that bandwidth fairness alone does not protect every shared resource. We plan to adapt its accounting and admission-control principles to media sessions, where delayed Objects lose value and subscribers can share stored content. Our current work provides the measurements needed to evaluate that design. [1]

Media over QUIC: Initial Testing, Findings and Results provides an early experimental foundation for MoQ. The authors' companion testbed extends Warp with client-server feedback and active and passive bandwidth measurements. Our work similarly uses a working transport testbed, but focuses on subscribers sharing a relay and the cost of stalled-client recovery. Our current synthetic workload isolates transport behavior; encoded-video tests remain future work. [2]

Efficient Fair Queuing Using Deficit Round-Robin provides an efficient way to share transmission service across queues. We still plan to use byte-based DRR as a conventional fairness baseline. Our proposed extension adds buffering and delivery-lag limits, since fair byte allocation alone does not determine whether media arrives while it is useful. Neither DRR nor the adaptive policy is included in the current measurements. [3]

6. Evaluation Results and Next Steps

We measure delivery latency from publisher generation to the receiver's complete Object read. We calculate payload goodput for every expected client, including clients receiving no data. We also measure payload goodput for Objects delivered within 150 ms; this is an experimental target, not a protocol requirement. Relay resident memory (RSS) and process CPU are sampled every 250 ms.

For a fair comparison, we use the same upper-half client IDs as the healthy cohort in both conditions. The table below summarizes seconds 5-20. Each entry is the median of five run-level measurements; P99 is calculated separately within each run.

Total clients	Paused clients	Peak relay RSS (MiB)	Healthy P99 latency (ms)	Healthy goodput (Mbit/s/client)
16	0	25.53	12.61	4.000
16	8	26.28	8.95	4.000
64	0	52.42	11.97	3.997
64	32	47.86	11.36	4.000

Table 1. Medians over five runs during seconds 5-20. The healthy comparison cohort is fixed across conditions.




Figure 1. Each dot is one run; horizontal marks show medians. All five repetitions are shown for each condition.

We did not observe a consistent reduction in healthy-client throughput during the pause. Memory use also did not consistently increase: at 64 clients, the paused condition used less resident memory during this interval. Tail latency varied across repetitions; for example, healthy-client P99 in the 64-client control ranged from 10.16 to 69.28 ms. We therefore cannot conclude that pausing clients improves latency, or that the relay is isolated under heavier contention. This setup has no imposed outgoing-bandwidth bottleneck.

The recovery period showed a clearer effect. For the previously paused clients, total received throughput was much higher than throughput meeting the 150 ms target:

Total clients / paused	Received goodput (Mbit/s/client)	Goodput within 150 ms (Mbit/s/client)	P99 delivery latency (s)
16 / 8	9.98	3.82	14.76
64 / 32	10.00	3.13	14.84

Table 2. Medians over five runs, measured during seconds 20-30 for the previously paused cohort.

At 64 clients, median peak relay RSS during recovery was 64.89 MiB with pauses, versus 55.69 MiB without them. Median relay CPU was about 129% versus 78%, where 100% represents one core. Healthy-client median P99 remained similar, at 15.50 versus 14.78 ms. These results show extra recovery work and late media delivery, but do not yet demonstrate sustained harm to other subscribers or identify which buffers caused the memory difference.




Figure 2. All repetitions are shown. The shaded interval is the pause; previously paused clients resume at second 20.

Our next step is to introduce a controlled, shared relay egress budget and use the same limit for every comparison policy. We will then implement session-level DRR and fixed backlog limits before adding adaptive limits. Evaluation will compare the stock relay, DRR alone, and DRR with limits using healthy-client P99, timely goodput, memory, and termination rate. We also need to repeat the tests with separate ICE nodes, higher incoming-stream concurrency after addressing the receiver issue, short pauses, and encoded-video replay. The main progress at this checkpoint is a working and repeatable testbed, a measured baseline, and evidence that recovery throughput can be dominated by late media.

References

1. Kumar et al. **PicNIC: Predictable Virtualized NIC.** SIGCOMM 2019. Paper.

2. Gurel et al. **Media over QUIC: Initial Testing, Findings and Results.** MMSys 2023. DOI; authors' testbed.

3. Shreedhar and Varghese. **Efficient Fair Queuing Using Deficit Round-Robin.** IEEE/ACM Transactions on Networking, 1996. Paper.

4. Georgia Tech PACE. ICE job guide and storage guide, linked from the GT teaching tutorial.

5. SchedMD. sbatch and srun documentation.

The raw measurements, run-level statistics, plots, and reproducibility notes are in `results/preliminary/2026-11-10/` in the project repository.