Practical 05 Configure DHCP in Packet Tracer.

Step 1: Take one server and 9 end devices such as PC or laptop & one router. and set proper connections among them.



Step 2: apply DHCP on the router. The commands in sequence are as follows.



Step 3: Configure all pc as follows.(Select from Static to DHCP)


Simulation Panel
Event List
Vis. Time(sec) Last Device At Device Type Info
0.000 -- PC2 ICMP
0.001 PC2 Switch0 ICMP
0.002 Switch0 PC3 ICMP
0.003 PC3 Switch0 ICMP
0.004 Switch0 PC2 ICMP
0.940 -- Switch0 STP
Reset Simulation
Constant Delay
Captured to: 0.940 s
Play Controls
Back
Auto Capture / Play
Capture / Forward
Event List Filters - Visible Events
ACL Filter, ARP, BGP, CDP, DHCP, DHCPv6, DNS, DTP, EIGRP, EIGRPv6, FTP, H.323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IPSec, ISAKMP, LACP, NDP, NETFLOW, NTP, OSPF, OSPFv6, PAgP, POP3, PTP, RADIUS, REP, RIP, RIPng, RTP, SCCP, SMTP, SNMP, SSH, STP, SYSLOG, TACACS, TCP, TFTP, Telnet, UDP, VTP
Edit Filters
Show All/None
6:30:00
Event List
Simulation
Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit
Successful PC2 PC3 ICMP 0.000 N 0 (ed
Activate Windows
Go to Settings to activate Windows.