

A Short and Incomplete Introduction to Python

Part 5: File I/O and string processing

Riccardo Murri <riccardo.murri@uzh.ch>,
Sergio Maffioletti <sergio.maffioletti@uzh.ch>
S3IT: Services and Support for Science IT,
University of Zurich

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

File I/O

Code for processing a text file usually looks like this:

```
with open(filename, 'r') as stream:  
    # prepare for processing  
    for line in stream:  
        # process each line
```

File I/O

```
with open(filename, 'r') as stream:  
    # prepare for processing  
    for line in stream:  
        # process each line
```

The **open**(path, mode) function opens the file located at path and returns a “file object” that can be used for reading and/or writing.

Mode is one of 'r', 'w' or 'a' for reading, writing (truncates on open), appending. You can add a '+' character to enable read+write (other effects being the same).

File I/O

```
with open(filename, 'r') as stream:
    # prepare for processing
    for line in stream:
        # process each line
```

This is equivalent to `stream = open(...)` but in addition *closes* the file when the code in the `with`-block is done.

There are many more uses of the `with` statement besides automatically closing files, check out <https://jeffknupp.com/blog/2016/03/07/python-with-context-managers/>

File I/O

```
with open(filename, 'r') as stream:  
    # prepare for processing  
    for line in stream:  
        # process each line
```

A for-loop can be used to process all lines in a file, as if the file were a list.

More on File I/O

The `.read()` method can be used to read the *whole* contents of a file in one go as a single string:

```
>>> s = stream.read()
```

Method `.readlines()` returns a list of all lines in the file:

```
>>> L = stream.readlines()
```

Reference: <http://docs.python.org/library/stdtypes.html#file-objects>

Type conversions

`str(x)` Converts the argument x to a string; for numbers, the base 10 representation is used.

`int(x)` Converts its argument x (a number or a string) to an integer; if x is a floating-point literal, decimal digits are truncated.

`float(x)` Converts its argument x (a number or a string) to a floating-point number.

Exercise 5.A: Write a function `load_data(filename)` that reads a file containing one integer number per line, and return a list of the integer values.

Test it with the `values.txt` file:

```
>>> load_data('values.dat')  
[299850, 299740, 299900, 300070, 299930]
```

Operations on strings, I

`s.capitalize()`, `s.lower()`, `s.upper()`

Return a *copy* of the string capitalized / turned all lowercase / turned all uppercase.

`s.split(t)`

Split `s` at every occurrence of `t` and return a list of parts. If `t` is omitted, split on whitespace.

`s.startswith(t)`, `s.endswith(t)`

Return `True` if `t` is the initial/final substring of `s`.

Reference: <http://docs.python.org/library/stdtypes.html#string-methods>

Operations on strings, II

`s.replace(old, new)`

Return a *copy* of string `s` with all occurrences of substring `old` replaced by `new`.

`s.lstrip()`, `s.rstrip()`, `s.strip()`

Return a *copy* of the string with the leading (resp. trailing, resp. leading *and* trailing) whitespace removed.

Reference: <http://docs.python.org/library/stdtypes.html#string-methods>

Filesystem operations, I

These functions are available from the `os` module.

`os.getcwd()`, `os.chdir(path)`

Return the path to the current working directory / Change the current working directory to `path`.

`os.listdir(dir)`

Return list of entries in directory `dir` (omitting `'.'` and `'..'`)

`os.makedirs(path)`

Create a directory; no-op if the directory already exists. Creates all the intermediate-level directories needed to contain the leaf.

`os.rename(old, new)`

Rename a file or directory from `old` to `new`.

Reference: <http://docs.python.org/library/os.html>

Filesystem operations, II

These functions are available from the `os.path` module.

`os.path.exists(path)`, `os.path.isdir(path)`,
`os.path.isfile(path)`

Return `True` if `path` exists / is a directory / is a regular file.

`os.path.basename(path)`, `os.path.dirname(path)`

Return the base name (the part after the last `'/'` character) or the directory name (the part before the last `/` character).

`os.path.abspath(path)`

Make `path` absolute (i.e., start with a `/`).

Reference: <http://docs.python.org/library/os.path.html>