

# A Short and Incomplete Introduction to Python

## Part 6: Exception handling

**Riccardo Murri** <riccardo.murri@uzh.ch>,  
Sergio Maffioletti <sergio.maffioletti@uzh.ch>  
S3IT: Services and Support for Science IT,  
University of Zurich

# Exception handling

# Exceptions

“Exceptions” is the name given in Python to error conditions.

You can write code that intercepts some error conditions and reacts appropriately.

*See also:* <http://docs.python.org/library/exceptions.html>

## What does an exception look like?

```
>>> stream.write('foo')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
IOError: File not open for writing
```

## What does an exception look like?

```
>>> stream.write('foo')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
IOError: File not open for writing
```

This is the exception *message*: it is supposed to be read by the (human) user.

## What does an exception look like?

```
>>> stream.write('foo')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
IOError: File not open for writing
```

This is the exception *class name*; it is used for catching exceptions (syntax in the next slide).

```
try:
    # code that might raise an exception
except SomeException:
    # handle some exception
except AnotherException as ex:
    # the actual Exception instance
    # is available as variable 'ex'
finally:
    # performed on exit in any case
```

The optional **finally** clause is executed on exit from the **try** or **except** block in *any* case.

Reference: [http://docs.python.org/reference/compound\\_stmts.html#try](http://docs.python.org/reference/compound_stmts.html#try)

# Raising exceptions in your code

Use the **raise** statement with an `Exception` instance:

```
if an_error_occurred:  
    raise RuntimeError("Spider sense is tingling.")
```



**Exercise 6.A:** Try loading file `values2.txt` with the `load_data()` function from Exercise 4.A – what exception does Python raise?

Edit the `load_data()` function into a `load_data2()` that *ignores* any line that does not contain an integer number.

Bonus points if you can write `load_data2()` so that it has exactly the same output of `load_data()`, i.e. minimize the number of rejected input lines.