

Exp: 11b Simulate RIP using CISCO Packet Tracer

28/9/26

Aim:-

To simulate RIP using CISCO Packet Tracer.

Procedure:-

- * Create the topology with 3 routers and 2 PCs.
- * Connect the device using suitable cables
- * Assign the given IP address to both PCs.
- * Configure FastEthernet and serial interface of all routers
- * Enable interface using no shutdown
- * Set clock rate 64000 and bandwidth 64 on DCE serial interface.
- * Enable RIP on all routers using router rip.
- * Add directly connected networks using the network command.
- * Test connectivity using ping 20.0.0.2
- * Use tracer 20.0.0.2 to verify the selected route
- * Disconnect the direct Router 0 - Router 2 link and use tracer again to verify RIP selects the alternate route.

PC0 - Command Prompt (ping)

```
C:\> ping 20.0.0.2

Pinging 20.0.0.2 with 32 bytes of data:
Reply from 20.0.0.2: bytes=32 time=1ms TTL=126
Reply from 20.0.0.2: bytes=32 time=1ms TTL=126
Reply from 20.0.0.2: bytes=32 time=1ms TTL=126
Reply from 20.0.0.2: bytes=32 time=1ms TTL=126

Ping statistics for 20.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\> tracert 20.0.0.2
Tracing route to 20.0.0.2 over a maximum of 30 hops:
  0  1 ms    1 ms    1 ms   10.0.0.1
  1  2 ms    2 ms    2 ms  192.168.1.253
  2  3 ms    3 ms    3 ms   20.0.0.2

Trace complete.

C:\>
```

Result

✓ RIP successfully configured and dynamic routing between PC0 and PC1 was Verified.