

# 1 Types

## 1.1 Primitives

Primitive types are types that do not have fields. Instead, they merely have values. These can take the form:

- **void**: a type representing a the return type of a function that does not return a value. It has no enumerated values and variables of type **void** cannot be created.
- **number**: a numeric type. This includes both integers and floating point numbers. Calculations internally are handled using high precision, large numbers.
- **character**: a character type. This is basically an integer that will be shown as a character.
- **bool**: a boolean type. **true** or **false**.
- **type**: a type type. This type is the type of the *values* (not types!) **number**, **type**, **array of string**.

## 1.2 Defined types

Defined types are the types of structures with fields. These fields can be themselves defined types or primitives.

## 1.3 Compound types

Compound types are types that take other types as arguments, similar to Haskell's type constructors. A common example is **array** which can only be declared as **array of T**, where **T** is the type stored in the array. Compound types are always defined types, because types are fields.

# 2 Variables

Although variables without prefixes would normally be beneficial in a natural-like language like 4l++, they could possibly cause ambiguity with Arbitrary Syntax Functions. Therefore, all variables must start with the underscore character **\_**. The other restriction is that variable names cannot contain spaces or start with a number or **'**.

## 3 Expressions

### 3.1 Literals

Literals are expressions that are hard-coded into the code. They take one of four forms.

### 3.2 Numeric Literals

These must start with a digit, a plus sign, a minus sign, or a period.

### 3.3 Boolean Literals

Either `true` or `false`.

### 3.4 Character and String Literals

These must start and end with a single quote `'`. What is in between is interpreted as a string. To use an actual single quote mark, use `\'`. Standard escapes can also be used. Determining the type of a string falls into three cases.

- `''`: This is automatically a string literal representing an empty string.
- A single character: depending on the context, this is interpreted as a string or character.
- Multiple characters: always a string.

#### 3.4.1 Examples

- `2, -56543234565, 41, -.02345654321, 12.:` Numeric literals.
- `''', '1', '\r', '\n', '\t', '\0123'`: Character literals
- `'', '\'\', '41++'`: String literals.

### 3.5 Algebraic Expressions

Algebraic Expression	Type
=	a = a -> bool
>	number > number -> bool and char > char -> bool
<	number < number -> bool and char < char -> bool
>=	number >= number -> bool and char >= char -> bool
<=	number <= number -> bool and char <= char -> bool
+	number + number -> number and char + char -> char and char + number -> number
-	number - number -> number and char - char -> char and char - number -> number
*	number * number = number
/	number / number = number <sup>1</sup>
//	number // number = number <sup>2</sup>
%	number % number = number <sup>3</sup>

### 3.6 Function Expressions

Any function call of a non-void returning function can be used as an expression.

### 3.7 The Role of Parentheses

While 4l++ is designed to be a English-like language, it is often very difficult to tease out syntactical ambiguity without parentheses. Therefore, in 4l++, parentheses must surround any value that is not a single word or string literal.

## 4 Statements

There are a limited number of valid statement forms. All start with a capital letter and end with a period.

### 4.1 Definition

#### 4.1.1 Declaration

A minimal declaration simply provides a variable with a name and associates it with a type.

**Define** a[n] <type> called <name>.

---

<sup>1</sup>this is standard division. 11/2 = 5.5

<sup>2</sup>this is floor division. 11/2 = 5, 1.5 / 1 = 1, -1.5 / 1.2 = -1

<sup>3</sup>remainder

### 4.1.2 Field Initialization

A variable can also have its fields initialized. It can also be directly set to a value by using the special field `value`.

```
Define a[n] <type> called <name> with a[n] <field1> of <value1>,
a[n] <field2> of <value2>, and a[n] <field3> of <value3>.
```

Commas and `and` are all technically unnecessary, but included to insure readability. Similarly, `a` and `an` are equivalent but both are included to avoid statements like `Define a integer called x`.

### 4.1.3 Examples

```
Define an integer called _x. Define a string called _name
with a value of '41++'. Define a matrix called _M with a
width of 3 and a height of 2. Define a matrix called _M2
with a value of _M.
```

## 4.2 Assignment

Assignment comes in two forms, value assignment and field assignment.

```
Set the <field> of <name> to <value>.
```

## 4.3 Function Calls

Any function call can be a statement in one of these two ways.

- Run <non-void function expression>.
- <Void expression>.

# 5 Control Flow

## 5.1 If

The syntax of If is as follows.

```
If <expression>: <Statement executed in case of expression>.
```

An Otherwise block can also be appended.

```
If <expression>: <Statement executed in case of expression>;
otherwise: <Statement executed otherwise>.
```

## 5.2 While

The syntax of While is as follows.

```
While <expression>: <Statement>.
```

### 5.3 Statement Concatenation

Notice that control flow statements above only take a single statement as an argument. However, having to define a procedure for every small set of instructions would be difficult. Instead, we can use the following syntax to convert multiple statements into a single one:

```
<First statement>; <Second statement>; <Third statement>.
```

## 6 Functions

### 6.1 Declaration

A function is declared as follows:

```
Define a function called <function expression> that takes  
a[n] <type1> called <field1>, a[n] <type2> called <field2>,  
and a[n] <type3> called <field3>[ and outputs a <return type>].
```

Where, in the function expression, variable names are enumerated as they appear in the type declarations later. Note that the function expression doesn't actually have a defined syntax. For example, this is a valid declaration:

```
Define a function is_n prime that takes a number called _n  
and outputs a bool.
```

Note that if `and outputs a <return type>` is omitted, then the return type defaults to `void`.

### 6.2 Body

The body consists of statements, in which any variables that are made cannot be used outside the function.

### 6.3 Conclusion

A function return is declared as follows.

```
Exit the function[ and output <output>].
```

Note that the output must be omitted if the return type is `void` because `void` has no values.

## 7 Structures

A structure is declared as follows:

```
Define a structure called <structure expression>; which contains  
a[n] <type1> called <field1>, a[n] <type2> called <field2>,  
and a[n] <type3> called <field3>.
```

The structure expression may contain variables, whose `type` is automatically `type`. A concrete example is probably best in this situation.

```
Define a structure called _k maps to _v; which contains an  
_k called key and a _v called value.
```

This defines an entry structure that can be later defined as follows.

```
Define a (number maps to number) entry with a key of 2 and  
a value of 2.
```

Note the use of types to replace `_a` and `_b`.