

# 1 Types

## 1.1 Primitives

Primitive types are types that do not have fields. Instead, they merely have values. These can take the form:

- **void**: a type representing a the return type of a function that does not return a value. It has no enumerated values and variables of type **void** cannot be created.
- **number**: a numeric type. This includes both integers and floating point numbers. Calculations internally are handled using high precision, large numbers.
- **character**: a character type. This is basically an integer that will be shown as a character.
- **bool**: a boolean type. **true** or **false**.
- **type**: a type type. This type is the type of the *values* (not types!) **number**, **type**, **array of string**.

## 1.2 Defined types

Defined types are the types of structures with fields. These fields can be themselves defined types or primitives.

## 1.3 Compound types

Compound types are types that take other types as arguments, similar to Haskell's type constructors. A common example is **array** which can only be declared as **array of T**, where T is the type stored in the array. Compound types are always defined types, because types are fields.

# 2 Variables

Although variables without prefixes would normally be beneficial in a natural-like language like 41++, they could possibly cause ambiguity with Arbitrary Syntax Functions. Therefore, all variables must start with the underscore character `_`. The other restriction is that variable names cannot contain spaces or start with a number or `'`.

# 3 Functions

## 3.1 Declaration

A function is declared as follows:

Define a function called `<function expression>` that takes  
a[n] `<type1>` called `<field1>`, a[n] `<type2>` called `<field2>`,  
and a[n] `<type3>` called `<field3>`[ and outputs a `<return type>`].

Where, in the function expression, variable names are enumerated as they appear in the type declarations later. Note that the function expression doesn't actually have a defined syntax. For example, this is a valid declaration:

Define a function is `_n` prime that takes a number called `_n`  
and outputs a `bool`.

Note that if `and outputs a <return type>` is omitted, then the return type defaults to `void`.

## 3.2 Body

The body consists of statements, in which any variables that are made cannot be used outside the function.

## 3.3 Conclusion

A function return is declared as follows.

Exit the function[ and output `<output>`].

Note that the output must be omitted if the return type is `void` because `void` has no values.

# 4 Structures

## 4.1 Declaration

A structure is declared as follows:

Define a structure called `<structure expression>`; which contains  
a[n] `<type1>` called `<field1>`, a[n] `<type2>` called `<field2>`,  
and a[n] `<type3>` called `<field3>`.

The structure expression may contain variables, whose `type` is automatically `type`. A concrete example is probably best in this situation.

Define a structure called `_k` mapped to `_v`; which contains  
an `_k` called `key` and a `_v` called `value`.

This defines an entry structure that can be later defined as follows.

Define a (number mapped to number) entry with a key of 2 and  
a value of 2.

Note the use of defined types to replace `_a` and `_b`.

## 4.2 Field Access

Field access is simple, taking the following syntax.

```
the <field> of <structure>
```

## 4.3 Arrays

Arrays are, in a sense, a primitive structure. To declare an array, the following syntax is used:

```
Define a[n] array of <type> called <name> with a size of <size>.
```

Array access and definition are treated as if defined as such, with one definition for every type <T> in existence.

```
Define a function called the _n th element of _array that
takes a number called n and an (array of <T>) called array
and outputs a <T>.
```

```
Define a function called Set the _n th element of _array to
_value that takes a number called n, an (array of <T>) called
array, and a <T> called _value.
```

Note: Technically, three different functions are defined, with two replacing `th` with `rd` and `st`, to prevent expressions such as `the 2 th element of _array1`.

# 5 Expressions

## 5.1 Literals

Literals are expressions that are hard-coded into the code. They take one of four forms.

## 5.2 Numeric Literals

These must start with a digit, a plus sign, a minus sign, or a period.

## 5.3 Boolean Literals

Either `true` or `false`.

## 5.4 Character and String Literals

These must start and end with a single quote `'`. What is in between is interpreted as a string. To use an actual single quote mark, use `\'`. Standard escapes can also be used. Determining the type of a string falls into three cases.

- `''`: This is automatically a string literal representing an empty string.
- A single character: depending on the context, this is interpreted as a string or character.
- Multiple characters: always a string.

#### 5.4.1 Examples

- `2, -56543234565, 41, -.02345654321, 12.:` Numeric literals.
- `''`, `'1'`, `'\r'`, `'\n'`, `'\t'`, `'\0123'`: Character literals
- `''`, `'\''`, `'41++'`: String literals.

### 5.5 Algebraic Expressions

Algebraic Expression	Type
<code>=</code>	<code>a = a -&gt; bool</code>
<code>&gt;</code>	<code>number &gt; number -&gt; bool</code> and <code>char &gt; char -&gt; bool</code>
<code>&lt;</code>	<code>number &lt; number -&gt; bool</code> and <code>char &lt; char -&gt; bool</code>
<code>&gt;=</code>	<code>number &gt;= number -&gt; bool</code> and <code>char &gt;= char -&gt; bool</code>
<code>&lt;=</code>	<code>number &lt;= number -&gt; bool</code> and <code>char &lt;= char -&gt; bool</code>
<code>+</code>	<code>number + number -&gt; number</code> and <code>char + char -&gt; char</code> and <code>char + number -&gt; number</code>
<code>-</code>	<code>number - number -&gt; number</code> and <code>char - char -&gt; char</code> and <code>char - number -&gt; number</code>
<code>*</code>	<code>number * number = number</code>
<code>/</code>	<code>number / number = number</code> <sup>1</sup>
<code>//</code>	<code>number // number = number</code> <sup>2</sup>
<code>%</code>	<code>number % number = number</code> <sup>3</sup>

### 5.6 Function Expressions

Any function call of a non-void returning function can be used as an expression. This includes structure and array access functions.

### 5.7 The Role of Parentheses

While `41++` is designed to be a English-like language, it is often very difficult to tease out syntactical ambiguity without parentheses. Therefore, in `41++`, parentheses must surround any value that is not a single word or string literal.

<sup>1</sup>this is standard division. `11/2 = 5.5`

<sup>2</sup>this is floor division. `11/2 = 5`, `1.5 / 1 = 1`, `-1.5 / 1.2 = -1`

<sup>3</sup>remainder

## 6 Statements

There are a limited number of valid statement forms. All start with a capital letter and end with a period.

### 6.1 Definition

#### 6.1.1 Declaration

A minimal declaration simply provides a variable with a name and associates it with a type.

```
Define a[n] <type> called <name>.
```

#### 6.1.2 Field Initialization

A variable can also have its fields initialized. It can also be directly set to a value by using the special field value.

```
Define a[n] <type> called <name> with a[n] <field1> of <value1>,  
a[n] <field2> of <value2>, and a[n] <field3> of <value3>.
```

Commas and **and** are all technically unnecessary, but included to insure readability. Similarly, **a** and **an** are equivalent but both are included to avoid statements like `Define a integer called x.`

#### 6.1.3 Examples

```
Define an integer called _x. Define a string called _name  
with a value of '41++'. Define a matrix called _M with a  
width of 3 and a height of 2. Define a matrix called _M2  
with a value of _M.
```

### 6.2 Assignment

Assignment comes in two forms, value assignment and field assignment.

```
Set the <field> of <name> to <value>.
```

### 6.3 Function Calls

Any function call can be a statement in one of these two ways.

- Run <non-void function expression>.
- <Void expression>.

## 7 Control Flow

### 7.1 If

The syntax of If is as follows.

```
If <expression>: <Statement executed in case of expression>.
```

An Otherwise block can also be appended.

```
If <expression>: <Statement executed in case of expression>;  
otherwise: <Statement executed otherwise>.
```

### 7.2 While

The syntax of While is as follows.

```
While <expression>: <Statement>.
```

### 7.3 Statement Concatenation

Notice that control flow statements above only take a single statement as an argument. However, having to define a procedure for every small set of instructions would be difficult. Instead, we can use the following syntax to convert multiple statements into a single one:

```
<First statement>; <Second statement>; <Third statement>.
```