

GE23131-Programming Using C-2024

Quiz navigation



[Show one page at a time](#)

[Finish review](#)

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 26 October 2024, 1:00 PM
Duration	58 days 4 hours

Question **1**

Correct

Marked out of
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false
Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d%d",&a,&b);
6     c=a%10;
7     d=b%10;
8     if(c==d)
9         printf("true");
10    else
11        printf("false");
12    return 0;
13 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, *n*, perform the following conditional actions:

- If *n* is odd, print Weird
- If *n* is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If *n* is even and in the inclusive range of **6** to **20**, print **Weird**
- If *n* is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not *n* is weird.

A single line containing a positive integer, ***n***.

Constraints

· $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2!=0)
7
8         printf("Weird");
9
10
11     else if((a>=2)&&(a<=5))
12
13         printf("Not Weird");
14
15     else if((a>=6)&&(a<=20))
16
17         printf("Weird");
18
19     else if(a>=20)
20
21         printf("Not Weird");
22     else
23         printf("0");
24
25     return 0;
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 [Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main ()
3  {
4      int a,b,c;
5      scanf("%d%d%d",&a,&b,&c);
6      if((a*a+b*b==c*c) || (a*a+c*c==b*b) || (b*b+c*c==a*a))
7          printf("yes");
8      else
9          printf("no");
10     return 0;
11 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review