

Rajalakshmi Engineering College

Name: kavin v
Email: 240701242@rajalakshmi.edu.in
Roll no: 240701242
Phone: 8248033180
Branch: REC
Department: I CSE FC
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_MCQ_Updated

Attempt : 1
Total Mark : 20
Marks Obtained : 11

Section 1 : MCQ

1. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head_ref: Pointer to Pointer of node)

```
temp = NULL  
current = *head_ref
```

```
While current is not NULL  
temp = current->prev  
current->prev = current->next  
current->next = temp
```

```
        current = current->prev;
    End While

    If temp is not NULL
        *head_ref = temp->prev;
    End If
End Procedure
```

Answer

Status : Skipped

Marks : 0/1

2. What will be the output of the following program?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};
```

```
int main() {
    struct Node* head = NULL;
    struct Node* tail = NULL;
    for (int i = 0; i < 5; i++) {
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
        temp->data = i + 1;
        temp->prev = tail;
        temp->next = NULL;
        if (tail != NULL) {
            tail->next = temp;
        } else {
            head = temp;
        }
        tail = temp;
    }
    struct Node* current = head;
```

```
while (current != NULL) {  
    printf("%d ", current->data);  
    current = current->next;  
}  
return 0;  
}
```

Answer

1 2 3 4 5

Status : Correct

Marks : 1/1

3. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

```
Define Structure Node  
    data: Integer  
    prev: Pointer to Node  
    next: Pointer to Node  
End Define
```

```
Define Structure TwoWayLinkedList  
    head: Pointer to Node  
    tail: Pointer to Node  
End Define
```

Answer

Status : Skipped

Marks : 0/1

4. What is a memory-efficient double-linked list?

Answer

Each node has only one pointer to traverse the list back and forth

Status : Wrong

Marks : 0/1

5. Which code snippet correctly deletes a node with a given value from a

doubly linked list?

```
void deleteNode(Node** head_ref, Node* del_node) {  
    if (*head_ref == NULL || del_node == NULL) {  
        return;  
    }  
    if (*head_ref == del_node) {  
        *head_ref = del_node->next;  
    }  
    if (del_node->next != NULL) {  
        del_node->next->prev = del_node->prev;  
    }  
    if (del_node->prev != NULL) {  
        del_node->prev->next = del_node->next;  
    }  
    free(del_node);  
}
```

Answer

Deletes the node at a given position in a doubly linked list.

Status : Wrong

Marks : 0/1

6. What is the correct way to add a node at the beginning of a doubly linked list?

Answer

```
void addFirst(int data){&nbsp;Node* newNode = new Node(data);&nbsp;head-&gt;next = newNode;&nbsp;newNode-&gt;prev = head;&nbsp;head = newNode;}
```

Status : Wrong

Marks : 0/1

7. How many pointers does a node in a doubly linked list have?

Answer

2

Status : Correct

Marks : 1/1

8. Which of the following is false about a doubly linked list?

Answer

Implementing a doubly linked list is easier than singly linked list

Status : Correct

Marks : 1/1

9. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
newNode->data = value;  
newNode->next = NULL;  
newNode->prev = NULL;
```

Answer

Inserts a new node at the beginning of a doubly linked list

Status : Wrong

Marks : 0/1

10. What happens if we insert a node at the beginning of a doubly linked list?

Answer

The next pointer of the new node is NULL

Status : Wrong

Marks : 0/1

11. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

Answer

The node will become the new head

Status : Correct

Marks : 1/1

12. Which pointer helps in traversing a doubly linked list in reverse order?

Answer

prev

Status : Correct

Marks : 1/1

13. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;  
    struct Node *Fwd;  
    struct Node *Bwd;  
};
```

Answer

Status : Skipped

Marks : 0/1

14. What is the main advantage of a two-way linked list over a one-way linked list?

Answer

Two-way linked lists allow for traversal in both directions.

Status : Correct

Marks : 1/1

15. How do you delete a node from the middle of a doubly linked list?

Answer

All of the mentioned options

Status : Correct

Marks : 1/1

16. What will be the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};
```

```
int main() {
    struct Node* head = NULL;
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
    temp->data = 2;
    temp->next = NULL;
    temp->prev = NULL;
    head = temp;
    printf("%d\n", head->data);
    free(temp);
    return 0;
}
```

Answer

2

Status : Correct

Marks : 1/1

17. Which of the following statements correctly creates a new node for a doubly linked list?

Answer

```
struct Node newNode = (struct Node*) malloc(sizeof(struct Node));
```

Status : Wrong

Marks : 0/1

18. Which of the following is true about the last node in a doubly linked list?

Answer

Its next pointer is NULL

Status : Correct

Marks : 1/1

19. Which of the following information is stored in a doubly-linked list's nodes?

Answer

All of the mentioned options

Status : Correct

Marks : 1/1

20. How do you reverse a doubly linked list?

Answer

By swapping the next and previous pointers of each node

Status : Correct

Marks : 1/1