| | |
|---|---|
| **Status** | Finished |
| **Started** | Tuesday, 13 October 2026, 10:24 PM |
| **Completed** | Tuesday, 13 October 2026, 11:07 PM |
| **Duration** | 43 mins 46 secs |
| **Grade** | **9.00** out of 10.00 (**90**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`. If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with `O(log n)` runtime complexity.

**Example 1:**

```
Input: nums = [-1,0,3,5,9,12], target = 9
Output: 4
Explanation: 9 exists in nums and its index is 4
```

**Example 2:**

```
Input: nums = [-1,0,3,5,9,12], target = 2
Output: -1
Explanation: 2 does not exist in nums so return -1
```

**Constraints:**

- `1 <= nums.length <= 10^4`
- `-10^4 < nums[i], target < 10^4`
- All the integers in `nums` are **unique**.
- `nums` is sorted in ascending order.

**For example:**

| Test | Result |
|---|---|
| `print(search([-1,0,3,5,9,12],9))` | 4 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def search(nums, target):
    left = 0
    right = len(nums) - 1

    while left <= right:
        mid = (left + right) // 2

        if nums[mid] == target:
            return mid
        elif nums[mid] < target:
            left = mid + 1
        else:
            right = mid - 1

    return -1
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(search([-1,0,3,5,9,12],9))` | 4 | 4 | ✓ |
| ✓ | `print(search([-1,0,3,5,9,12],2))` | -1 | -1 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Balanced strings are those that have an equal quantity of 'L' and 'R' characters.

Given a balanced string s, split it in the maximum amount of balanced strings.

Return the maximum amount of split balanced strings.

Example 1:

Input:

RLRRLLRLRL

Output:

4

Explanation: s can be split into "RL", "RRLL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

RLLLLRRRLR

Output:

3

Explanation: s can be split into "RL", "LLLRRR", "LR", each substring contains same number of 'L' and 'R'.

Example 3:

Input:

LLLLRRRR

Output:

1

Explanation: s can be split into "LLLLRRRR".

Constraints:

1 <= s.length <= 1000

s[i] is either 'L' or 'R'.

s is a balanced string.

**For example:**

| Test | Result |
|---|---|
| `print(BalancedStrings('RLRRLLRLRL'))` | 4 |
| `print(BalancedStrings('RLLLLRRRLR'))` | 3 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def BalancedStrings(s):
    count = 0
    balance = 0

    for ch in s:
        if ch == 'R':
            balance += 1
        else:
            balance -= 1

        if balance == 0:
            count += 1

    return count
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(BalancedStrings('RLRRLLRLRL'))` | 4 | 4 | ✓ |
| ✓ | `print(BalancedStrings('RLLLLRRRLR'))` | 3 | 3 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

**Input Format**

The first line contains a single integer n , the length of list

The second line contains n space-separated integers, list[i].

The third line contains integer k.

**Output Format**

Print Yes or No.

**Sample Input**

7

0 1 2 4 6 5 3

1

**Sample Output**

Yes

**For example:**

| Input | Result |
|---|---|
| 5<br>8 9 12 15 3<br>11 | Yes |
| 6<br>2 9 21 32 43 43 1<br>4 | No |

**Answer:** (penalty regime: 0 %)

```
n = int(input())
a = list(map(int, input().split()))
k = int(input())

found = False

for i in range(n):
    for j in range(i + 1, n):
        if a[i] + a[j] == k:
            found = True
            break
    if found:
        break

print("Yes" if found else "No")
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 5<br>8 9 12 15 3<br>11 | Yes | Yes | ✓ |
| ✓ | 6<br>2 9 21 32 43 43 1<br>4 | No | No | ✓ |
| ✓ | 6<br>13 42 31 4 8 9<br>17 | Yes | Yes | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element a[i] is a peak element if

A[i-1] <= A[i] >=a[i+1] for middle elements. [0<i<n-1]

A[i-1] <= A[i] for last element [i=n-1]

A[i]>=A[i+1] for first element [i=0]

**Input Format**

The first line contains a single integer n , the length of A .
The second line contains n space-separated integers,A[i].

**Output Format**

**Print** peak numbers separated by space.

**Sample Input**

5

8 9 10 2 6

**Sample Output**

```
10 6
```

**For example:**

| Input | Result |
|---|---|
| 4<br>12 3 6 8 | 12 8 |

**Answer:** (penalty regime: 0 %)

```
n = int(input())
a = list(map(int, input().split()))

for i in range(n):
    if (i == 0 or a[i] >= a[i - 1]) and (i == n - 1 or a[i] >= a[i + 1]):
        print(a[i], end=" ")
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 7<br>15 7 10 8 9 4 6 | 15 10 9 6 | 15 10 9 6 | ✓ |
| ✓ | 4<br>12 3 6 8 | 12 8 | 12 8 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Given an array `nums` containing `n` distinct numbers in the range `[0, n]`, return *the only number in the range that is missing from the array.*

**Example 1:**

```
Input: nums = [3,0,1]
Output: 2
Explanation: n = 3 since there are 3 numbers, so all numbers are in the range [0,3]. 2 is the missing number in the range since it does not appear in nums.
```

**Example 2:**

```
Input: nums = [0,1]
Output: 2
Explanation: n = 2 since there are 2 numbers, so all numbers are in the range [0,2]. 2 is the missing number in the range since it does not appear in nums.
```

**Example 3:**

```
Input: nums = [9,6,4,2,3,5,7,0,1]
Output: 8
Explanation: n = 9 since there are 9 numbers, so all numbers are in the range [0,9]. 8 is the missing number in the range since it does not appear in nums.
```

**For example:**

| Test | Result |
|---|---|
| `print(missingNumber([3,0,1]))` | 2 |
| `print(missingNumber([0,1]))` | 2 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def missingNumber(nums):
    n = len(nums)
    return n * (n + 1) // 2 - sum(nums)

```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(missingNumber([3,0,1]))` | 2 | 2 | ✓ |
| ✓ | `print(missingNumber([0,1]))` | 2 | 2 | ✓ |
| ✓ | `print(missingNumber([9,6,4,2,3,5,7,0,1]))` | 8 | 8 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00


You are given an `m x n` integer matrix `matrix` with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer `target`, return `True` *if* `target` *is in* `matrix` *or* `False` *otherwise*.

You must write a solution in `O(log(m * n))` time complexity.


**Example 1:**



| | | | |
|---|---|---|---|
| 1 | 3 | 5 | 7 |
| 10 | 11 | 16 | 20 |
| 23 | 30 | 34 | 60 |

```
Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 3
Output: True
```

**Example 2:**



| | | | |
|---|---|---|---|
| 1 | 3 | 5 | 7 |
| 10 | 11 | 16 | 20 |
| 23 | 30 | 34 | 60 |

```
Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 13
Output: False
```

**For example:**

| Test | Result |
|---|---|
| `print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))` | `False` |
| `print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))` | `True` |

**Answer:** (penalty regime: 0 %)

Reset answer

```
1
2  def searchMatrix(matrix, target):
3      m = len(matrix)
4      n = len(matrix[0])
5      left = 0
6      right = m * n - 1
7
8      while left <= right:
9          mid = (left + right) // 2
10         value = matrix[mid // n][mid % n]
11
12         if value == target:
13             return True
```

```
        elif value < target:
            left = mid + 1
        else:
            right = mid - 1

    return False
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13)) | False | False | ✓ |
| ✓ | print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3)) | True | True | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

**Constraints**

1<= string length <= 200

**Sample Input 1**

experience
enc

**Sample Output 1**

xpri

**Answer:** (penalty regime: 0 %)

```
s1 = input()
s2 = input()

for ch in s1:
    if ch not in s2:
        print(ch, end="")

```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | experience<br>enc | xpri | xpri | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

**Input Format:**

The first line contains S1.
The second line contains S2.
The third line contains N.

**Output Format:**

The first line contains the N characters present in S1 which are also present in S2.

**Boundary Conditions:**

2 <= N <= 10
2 <= Length of S1, S2 <= 1000

**Example Input/Output 1:**

Input:

abcbde
cdefghbb
3

Output:

bcd

**Note:**

b occurs twice in common but must be printed only once.

**Answer:** (penalty regime: 0 %)

```
s1 = input()
s2 = input()
n = int(input())

result = ""
for ch in s1:
    if ch in s2 and ch not in result:
        result += ch
    if len(result) == n:
        break

print(result)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | abcbde<br>cdefghbb<br>3 | bcd | bcd | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Write a Python program for binary search.

**For example:**

| Input | Result |
|---|---|
| 1,2,3,5,8<br>6 | False |
| 3,5,9,45,42<br>42 | True |

**Answer:** (penalty regime: 0 %)

```
a = sorted(map(int, input().split(',')))
n = int(input())

left = 0
right = len(a) - 1
found = False

while left <= right:
    mid = (left + right) // 2

    if a[mid] == n:
        found = True
        break
    elif a[mid] < n:
        left = mid + 1
    else:
        right = mid - 1

print(found)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 1,2,3,5,8<br>6 | False | False | ✓ |
| ✓ | 3,5,9,45,42<br>42 | True | True | ✓ |
| ✓ | 52,45,89,43,11<br>11 | True | True | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Incorrect

Mark 0.00 out of 1.00

String should contain only the words are not palindrome.

**Sample Input 1**

Malayalam is my mother tongue

**Sample Output 1**

is my mother tongue

**Answer:** (penalty regime: 0 %)

```
import string

# Read input string
text = input()

words = text.split()
result = []

for word in words:
    # Strip leading/trailing punctuation to check if the core word is a palindrome
    cleaned = word.strip(string.punctuation).lower()

    # If the word isn't empty and is NOT a palindrome, keep the original word
    if cleaned and cleaned != cleaned[::-1]:
        result.append(word)

# Print non-palindrome words separated by space
print(' '.join(result))
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | Malayalam is my mother tongue | is my mother tongue | is my mother tongue | ✓ |

Your code failed one or more hidden tests.
Your code must pass all tests to earn any marks. Try again.

Incorrect

Marks for this submission: 0.00/1.00.