Started on	Wednesday, 26 August 2026, 9:34 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 9:46 PM
Time taken	12 mins 31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
int main(){
    int n;
    int c=0;
    if(scanf("%d",&n)!=1){
        return 0;
    }
    c++;
    if(n==1){
        c++;
    }
    else{
        int i=1;
        while(c++,i<=n){
            int j=1;
            while(c++,j<=n){
            c++;
            c++;
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 26 August 2026, 9:48 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 9:53 PM
Time taken	5 mins 2 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```
#include<stdio.h>
int main(){
    int n;
    int c=0;
    if(scanf("%d",&n)!=1){
        return 0;
    }
    int i=1;
    while(c++,i<=n){
        if(n%i==0){
            c++;
```

```
        }
        c++;
        ++i;
    }
    printf("%d",c);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 26 August 2026, 9:58 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 10:04 PM
Time taken	5 mins 58 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```
#include<stdio.h>
int main(){
    int n;
    int c=0;
    if(scanf("%d",&n)!=1){
        return 0;
    }
    c++;
    int i=n/2;
    while(c++,i<n){
        int j=1;
        while(c++,j<n){
```

```
            int k=1;
            while(c++,k<n){
                c++;
                k=k*2;
            }
            j=2*j;
        }
        i++;
    }
    printf("%d",c);
    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 26 August 2026, 10:05 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 10:10 PM
Time taken	4 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```
#include<stdio.h>
int main(){
    int n;
    int c=0;
    if(scanf("%d",&n)!=1){
        return 0;
    }
    c++;
    int rev=0,rem;
    while(c++,n!=0){
```

```
        c++;
        rem=n%10;
        c++;
        rev=rev*10+rem;
        c++;
        n/=10;
    }
    c++;
    printf("%d",c);
    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.