Started on	Wednesday, 9 September 2026, 11:11 PM
State	Finished
Completed on	Wednesday, 9 September 2026, 11:16 PM
Time taken	4 mins 42 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
#include<stdlib.h>
int cmp(const void *a,const void *b)
{
    return *(int*)a-*(int*)b;
}
int main(){
    int n,a[100],b[100],s=0;
    scanf("%d",&n);
    for(int i =0;i<n;i++)
        scanf("%d",&a[i]);
    for(int i=0;i<n;i++)
        scanf("%d",&b[i]);
    qsort(a,n,sizeof(int),cmp);
    qsort(b,n,sizeof(int),cmp);
    for(int i=0;i<n;i++)
        s+=a[i]*b[n-1-i];
    printf("%d",s);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.