



Symbol	Description
	Electrical power-24 VDC
	Hydraulic pilot pressure
	Valve opened
	Valve closed
	Valve active-opened/closed
	Component active

Function	Position	205	210	215	220	222	225	226	227	230	235	240	245	250	260	261	270	275	280-284	290	295
Normal operation	PITCH TO STOP																				
Pressure holding-Normal operation																					
Parking mode																					
Pressure holding accu.side:parking mode																					
Pressure holding cyl. A-side:parking mode																					
Pressure holding cyl. B-side:parking mode																					
Emergency shutdown																					
Emergency shutdown-speed control																					
Pressure holding-Emergency shutdown																					
System pressurerelease																					
Pressure measuring																					

Nacelle Mode : Command RUN then change DP

Hub Mode : Discharge Accumulators - Valve 222
Open Needle Valve - Valve 447

Press RESET then
PITCH TO STOP or
PULSE TO STOP



E	1	25.06.2003	CV	Pos. 255, 270, 275 changed	D5, B6, B8			
D	1	31.03.2003	CV	Pos. 222 added, G1/2-->G1/4	E5, C5			
C	1	11.03.2003	CV	Pos. 255 --> Ø1	C4			
B	1	04.02.2003	CV	Orifice added	D5			
Kunde/customer: NEG Micon A/S				<div><div><div>Rexroth</div><div>Bosch Group</div></div><div><div>Dette hydraulikdiagram er blevet udarbejdet ud fra tekniske data gjort tilgængelige for os. Bosch Rexroth A/S påtager sig intet systemansvar alene på baggrund af dette diagram.</div><div>This hydraulic circuit was created from technical data made available to ourselves. Bosch Rexroth A/S does not accept any system responsibility only on the basis of this circuit.</div></div></div>				
Kunde-nr./customer no.:								
Tilbuds.-nr./quotation no.:								
Ordre-nr./order no.:								
Afd./depart.	Document: HS			Pitchcontrol NM72C/1500 & NM82C/1650		Bl./sheet: 1		
Project	Dato/date	Navn/name						
Tegn./DWN	13.12.2002	CV		Pitchcontrolblock		af/of: 1		
Kontr./CHK				Industrial Hydraulics	Skala/ scale	Format/ size	Tegnings-nr./drawing no.	Indeks
Bearb./WRK					-	A3	HS-036-A693-3-E	
Godk./APP								
Lign. tegn./sim. dwg.:				Erst./replaces:			Ændringsnotat/change note:	