Status	Finished
Started	Tuesday, 20 October 2026, 5:39 PM
Completed	Tuesday, 20 October 2026, 5:43 PM
Duration	4 mins 31 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and write, w+ is for append only

b. r+ is for read and write without truncating, w+ is for read and write with truncating ✓

c. r+ is for read and append, w+ is for read and write

d. r+ is for binary read and write, w+ is for text read and write

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **2**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open("c:\\scores.txt", "rw")

b. outfile = open(file = "c:\\scores.txt", "w")

c. outfile = open(file = "c:\scores.txt", "w")

d. outfile = open("c:\\scores.txt", "a") ✓

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **3**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. finish()

b. end()

c. close() ✓

d. terminate()

The correct answer is: close()

Question **4**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

- a. The buffer size for the file operations ✓
- b. The encoding of the file
- c. The access mode of the file
- d. The file's read/write position

The correct answer is: The buffer size for the file operations

Question **5**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

- a. file.is_closed()
- b. file.closed()
- c. file.closed ✓
- d. file.isclosed()

The correct answer is: file.closed

Question **6**

Correct

Mark 1.00 out of 1.00

How can you read a file line by line efficiently in Python?

- a. Using the readline() method
- b. Using a for loop ✓
- c. Using the read() method
- d. Using the readlines() method

The correct answer is: Using a for loop

Question **7**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer to beginning of the file
- b. move the file pointer five characters ahead from the current position ✓
- c. move the file pointer five characters behind from the current position
- d. moves the file pointer to the end of a file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **8**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. null

b. garbage

c. 0 ✓

d. 1

e. 2

The correct answer is:
0

Question **9**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints the entire content of the file ✓

b. Prints each line of the file

c. Prints an error message

d. Prints the first 10 characters of the file

The correct answer is: Prints the entire content of the file

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

a. readline() ✓

b. readlines(1)

c. read(1)

d. line()

The correct answer is: readline()

Question **11**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. • Move file pointer five characters ahead from the current position. ✓

b. • Move file pointer five characters behind from the current position.

c. Move file pointer five characters ahead from the beginning

d. • Move file pointer five characters behind ahead from the end of a file.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. a
b. r
c. r+ ✓
d. w

The correct answer is: r+

Question **13**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. An empty string ✓
b. EOFError
c. 0
d. None

The correct answer is: An empty string

Question **14**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. read()
b. readlist()
c. readline()
d. readlines() ✓

The correct answer is: readlines()

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open(file = “c:\\scores.txt”, “w”)

b. outfile = open(file = “c:\scores.txt”, “w”)

c. outfile = open(“c:\scores.txt”, “w”)

d. outfile = open(“c:\\scores.txt”, “w”) ✓

The correct answer is:
outfile = open(“c:\\scores.txt”, “w”)