

Website Integration API Documentation

Version: 1.0

Base URL: `https://api-demo.popxcrm.com/v1/api/leads`

Authentication: All endpoints require the `X-API-Key` header.

Note to integration team: Contact the CRM administrator to obtain your `X-API-Key` value. Keep this key server-side and never expose it in client-side JavaScript.

Authentication

Every request must include the following HTTP header:

```
X-API-Key: <your-api-key>
```

Requests missing or providing an invalid key will receive:

```
HTTP 401 Unauthorized
{
  "action": "error",
  "message": "Unauthorized"
}
```

Rate Limiting

The inquiry submission endpoint is limited to **10 requests per 10 minutes per IP address**.

When exceeded:

HTTP 429 Too Many Requests

```
{
  "action": "error",
  "message": "Too many requests. Please try again later."
}
```

Endpoints

1. Submit Lead Inquiry

Receives a contact/inquiry form submission from the website and creates a new lead in the CRM.

POST /v1/api/leads/website-inquiry/

Headers:

Header	Value
Content-Type	application/json
X-API-Key	<your-api-key>

Request Body:

Field	Type	Required	Description
name	string	☒ Yes	Full name of the enquirer
phone	string	☒ Yes	Phone number (7–15 digits, optional + and spaces)
email	string	No	Email address
message	string	No	Enquiry message or notes
property_id	string	No	Encoded property/unit ID from the Get Properties endpoint
location	string	No	Location or area of interest

Field	Type	Required	Description
<code>budget_range</code>	string	No	Free-text budget description (e.g. <code>"50L - 1Cr"</code>)
<code>preferred_visit_date</code>	string	No	Preferred site visit date. Accepted formats: <code>YYYY-MM-DD</code> or <code>MM/DD/YYYY</code>

Example Request:

```
POST /v1/api/leads/website-inquiry/
X-API-Key: your-api-key-here
Content-Type: application/json

{
  "name": "John Doe",
  "phone": "+91 98765 43210",
  "email": "john@example.com",
  "message": "Interested in 3BHK apartments",
  "property_id": "TmZhZGFzZGFzZA==",
  "location": "Kochi",
  "budget_range": "50L - 1Cr",
  "preferred_visit_date": "2026-05-10"
}
```

Success Response:

```
HTTP 201 Created
{
  "action": "success",
  "message": "Thank you! We will contact you soon."
}
```

Validation Error Response:

```
HTTP 400 Bad Request
{
```

```

    "action": "error",
    "message": {
      "phone": "Phone number is required"
    }
  }
}

```

Possible validation messages:

Field	Message
name	"Name is required"
phone	"Phone number is required"
phone	"Invalid phone number"
email	"Invalid email address"

2. Get Properties

Returns the list of active properties/units so the website enquiry form can show a property selector dropdown.

```
GET /v1/api/leads/website-products/
```

Headers:

Header	Value
X-API-Key	<your-api-key>

Response:

```

HTTP 200 OK
{
  "action": "success",
  "data": [
    {
      "id": "TmZhZGFzZGFzZA==",
      "name": "Sunrise Apartments – Block A",

```

```

        "code": "SA-BLK-A"
      },
      {
        "id": "QWxwaGFUb3d1cg==",
        "name": "Alpha Tower – 3BHK",
        "code": "AT-3BHK"
      }
    ]
  }

```

Response Fields:

Field	Type	Description
<code>id</code>	string	Encoded property ID — pass this as <code>property_id</code> in the inquiry endpoint
<code>name</code>	string	Display name of the property/unit
<code>code</code>	string	Short code for the property (may be empty)

3. Get Budget Ranges

Returns the list of predefined budget range options configured in the CRM, for use in a budget dropdown on the enquiry form.

```
GET /v1/api/leads/website-budget-ranges/
```

Headers:

Header	Value
X-API-Key	<code><your-api-key></code>

Response:

```

HTTP 200 OK
{
  "action": "success",
  "data": [

```

```

{
  "id": "QnVkZ2V0UmFuZ2Ux",
  "label": "Under 50 Lakhs",
  "budget_min": null,
  "budget_max": 5000000.0
},
{
  "id": "QnVkZ2V0UmFuZ2Uy",
  "label": "50 Lakhs – 1 Crore",
  "budget_min": 5000000.0,
  "budget_max": 10000000.0
},
{
  "id": "QnVkZ2V0UmFuZ2Uz",
  "label": "Above 1 Crore",
  "budget_min": 10000000.0,
  "budget_max": null
}
]
}

```

Response Fields:

Field	Type	Description
<code>id</code>	string	Encoded budget range ID
<code>label</code>	string	Human-readable label to display
<code>budget_min</code>	number null	Minimum budget value in base currency
<code>budget_max</code>	number null	Maximum budget value in base currency

Common Error Responses

HTTP Status	<code>action</code>	Cause
400	<code>error</code>	Missing required fields or invalid format
401	<code>error</code>	Missing or invalid <code>X-API-Key</code>

HTTP Status	action	Cause
405	error	Wrong HTTP method used
429	error	Rate limit exceeded (10 req / 10 min per IP)
500	error	Server-side error — contact CRM support

Recommended Integration Flow

- On page load
 - GET /website-products/ → populate property dropdown
 - GET /website-budget-ranges/ → populate budget dropdown
- On form submit
 - POST /website-inquiry/ → submit lead with selected values
 - On success → show thank-you message
 - On error → display field-level validation messages to user

Notes

- All `id` values returned by the GET endpoints are **opaque encoded strings**. Do not attempt to decode or modify them — pass them as-is to the inquiry endpoint.
- The `property_id` field in the inquiry payload is optional. If the user does not select a property, simply omit the field.
- The `budget_range` field accepts free text if you do not use the budget ranges dropdown (e.g. `"50L - 1Cr"`). If you use the budget ranges dropdown, you may pass the `label` value from endpoint 3 in this field.
- Dates must be in `YYYY-MM-DD` or `MM/DD/YYYY` format. Invalid dates are silently ignored — the lead is still created without a visit date.

For API key provisioning or integration support, contact the CRM team.