Wi-Fi network traffic analysis

"Wifi traffic analyzer" *Generated by LeapSpace*

Wi-Fi Traffic Analyzers at a Glance

Key Findings Table

Topic	Key finding	Deployment / population context	Citations
Definition	A Wi-Fi traffic analyzer is fundamentally a passive 802.11 frame-capture tool operating in monitor mode/RFMON to observe wireless traffic rather than inject it.	WLAN monitoring, research, troubleshooting	[1] [2] [3]
Capture pipeline	Analyzer effectiveness depends on adapter chipset, driver, and firmware support, plus channel handling strategy such as channel sweeping across 2.4 GHz and 5 GHz.	Commodity and research capture systems	[1] [2] [3] [4]
Frame usage	Management, control, and data frames serve different analytic roles: management for association/roaming, control for ACK/RTS/CTS and retransmission behavior, data for payload-bearing communication and some classification tasks.	Protocol analysis, client/AP behavior reconstruction, traffic classification	[5] [6] [7] [8] [9] [10] [11]
Reconstruction quality	No single monitor reliably sees all traffic; higher-quality analysis often requires multi-monitor merging, missed-packet inference, and completeness checks based on MAC sequence numbers and beacon timing.	Campus/testbed trace reconstruction	[12] [13] [14]

Topic	Key finding	Deployment / population context	Citations
Operational value	Wi-Fi analyzers are useful because they expose PHY/MAC events such as retransmissions, ACKs, CRC errors, collisions, and channel occupancy that SNMP or AP syslog may miss.	Enterprise, lab, operational WLAN troubleshooting	[15] [16] [17] [18]
Security use	Analyzers support malicious-frame detection, rogue AP discovery, WPS attack detection from traffic flow alone, and ML-based attack analytics.	WIDS, rogue AP monitoring, campus datasets	[19] [20] [21] [22] [23] [24] [25]
Encryption limits	Under WPA2/WPA3 and modern high-throughput WLANs, payload inspection becomes less useful, so analysis shifts toward metadata such as timing, size, RSSI, sequence behavior, and occupancy.	Encrypted traffic, dense deployments, 5/6 GHz environments	[26] [27] [28] [29] [30] [31]
Tool comparison evidence	The supplied evidence supports general comparisons, but not a robust head-to-head benchmark across Wireshark, Kismet, Aircrack-based tools, and commercial analyzers on identical workloads.	Tool evaluation literature	[32] [33] [34] [35]

Direct Answer

A Wi-Fi traffic analyzer is a passive wireless-monitoring tool that captures 802.11 frames in monitor mode, decodes management/control/data traffic, and uses those traces to support troubleshooting, performance analysis, and security monitoring in WLANs [1] [2] [3]. Its strongest practical value is visibility into MAC/PHY behavior—such as retries, ACKs, collisions, roaming, and channel use—that ordinary controller logs, SNMP polling, or syslog often do not reveal well [15] [16] [17]. Its main limitations are incomplete capture from single sensors, losses caused by channel hopping or dense environments, and reduced payload visibility under WPA2/WPA3 encryption [12] [14] [26] [27] [36].

Taken together, the literature suggests that the most capable modern analyzer workflow is not just "packet sniffing"; it combines multi-radio or multi-monitor capture, frame-level quality validation, and metadata-based analytics for encrypted traffic [12] [13] [28].
Confidence level: High - consistent findings across capture, reconstruction, operations, and security studies [1] [12] [17] [26].

Study Scope

This report covers academic and technical findings from approximately 2005-2025 on Wi-Fi/802.11 traffic analyzers, including monitor-mode capture, frame decoding, trace reconstruction, WLAN troubleshooting, intrusion detection, rogue AP detection, encrypted-traffic analysis, and limited tool-comparison evidence [4] [12] [17] [22] [26]. Methods represented include passive packet capture, multi-monitor trace merging, observational WLAN measurement, security analytics, and ML-based metadata classification [12] [24] [37] [38].

Assumptions & Limitations

- The supplied evidence supports a strong conceptual account of what Wi-Fi analyzers do, but not a standardized same-workload benchmark across Wireshark, Kismet, Aircrack-based tools, and commercial analyzers [33] [34].
- WPA3-specific evaluation and standardized false-positive/false-negative reporting for Wi-Fi security analyzers remain limited in the supplied studies [27] [39] [40].
- Some papers rely heavily on management/control frames, while others deliberately use only data or non-payload statistics; this is a task-dependent tradeoff, not a resolved consensus on one best method [7] [10] [26] [41].
- Campus and enterprise results are present, but the evidence is thinner for consumer/home networks and for 802.11ax/6 GHz dense deployments under unified evaluation protocols [30] [38] [42].

Suggested Further Research

- Build standardized cross-tool benchmarks covering open-source and commercial analyzers under the same channel, density, and mobility conditions [33] [34].
- Evaluate analyzer fidelity explicitly in 802.11ax/6 GHz, beamforming, and high-density enterprise settings [29] [30].
- Improve validation methods for session/flow reconstruction, especially attribution correctness and timing fidelity in real deployments [13] [43].
- Report reproducible security metrics beyond headline accuracy/AUC, especially false positives, false negatives, and cross-environment generalization [24] [25] [39].
- Develop privacy-preserving analyzers that retain troubleshooting utility while minimizing exposure of user-identifiable traffic patterns [19] [31].

Full Report

Foundational Context

A Wi-Fi traffic analyzer operates on IEEE 802.11 wireless frames, not just on higher-layer IP packets. The key implication is that it can observe wireless-specific events that often disappear once traffic is viewed only after it traverses an access point or controller, including management exchanges, MAC retransmissions, ACK behavior, and channel-access control patterns [5] [6] [17]. This makes the analyzer distinct from ordinary wired packet capture or controller telemetry [15] [16].

The literature consistently distinguishes three frame classes. **Management frames** are used for supervision tasks such as association and roaming inference; **control frames** expose medium-access functions such as ACK/RTS/CTS; and **data frames** carry payload-bearing communication and are often the basis for application or device classification studies [5] [6] [8] [9]. This classification is foundational because different analyzer use cases depend on different subsets of frames [7] [10] [41].

A second foundational point is methodological: wireless capture is inherently incomplete from a single vantage point. Sensor placement, channel selection, driver behavior, packet drops, and clock alignment all affect what is actually observed [13] [14]. As a result, “what the analyzer shows” is partly a property of the capture architecture, not just the decoder software [4] [12].
Confidence level: High - directly supported by multiple methodological studies [12] [13] [14].

What a Wi-Fi Traffic Analyzer Is

The supplied literature describes Wi-Fi analyzers as passive packet-capture systems operating in RFMON/monitor mode, typically dependent on supported chipsets, drivers, and firmware [1] [2] [3]. Functionally, they resemble wireless-adapted sniffers: they observe nearby 802.11 activity, decode frames, and provide statistics or visualizations for diagnostics, measurement, or security analysis [2] [34].

Their uses extend beyond simple packet listing. Open-source 802.11 management-frame analysis can support malicious-frame identification and privacy-preserving research workflows [19]. Tools such as WiPal and WScout were introduced to manipulate, merge, visualize, and compute statistics on large 802.11 traces, showing that analyzers are often part of a broader measurement pipeline rather than standalone GUI applications [37].

Why they matter in research and operations is consistent across the sources: they offer direct wireless-side observability. Large-scale measurements use them to characterize frame mix, temporal traffic behavior, protocol efficiency, application mix, and anomalies in real WLANs [20] [38]. Traffic models also show that Wi-Fi traffic can differ substantially from wired traffic, including multimodal interarrival and pacing effects, which strengthens the case for wireless-specific analysis rather than simply extrapolating from Ethernet observations [44].
Confidence level: High - the definition and research role are stable across sources [1] [37] [38].

Capture Pipeline and 802.11 Frame Decoding

Monitor mode, drivers, and channel handling

Monitor-mode capture availability depends on the network adapter's hardware and software stack, especially chipset, firmware, and driver support; Linux/Unix-like environments are commonly associated with such support in the supplied findings [1] [2] [3]. Capture systems may use a driver-linked acquisition layer and periodically sweep channels across 2.4 GHz and 5 GHz to enlarge observational coverage [4].

That broader channel coverage comes with a cost. Channel hopping can miss traffic, and WIDS studies show that hopping systems may lose visibility even if some adjacent-channel capture is still possible in certain cases [36]. This means there is a direct tradeoff between **breadth** of monitored spectrum and **completeness** of packet capture on any single channel [4] [36].

Frame types and how analyzers use them

The literature is clear that analyzers do not use all frames in the same way. Management frames are central for association and roaming analysis; control frames expose access-control behavior such as ACK and RTS/CTS; and data frames support payload-aware communication analysis [5] [6] [8] [9].

For client and AP behavior reconstruction, studies rely heavily on management and control signals including probe requests, deauthentication frames, group-ID management frames, channel-sounding frames, and ACK/BlockAck sequences [7] [8] [41] [45]. These allow inference of associations, user grouping, transmission rates, MIMO behavior, and sounding overhead without depending solely on payloads [41] [45].

However, a contrasting research strand deliberately filters out management/control traffic and uses only data frames or other limited features for encrypted-traffic or device-identification tasks [10] [11] [46]. Taken together, these findings suggest a task-dependent tradeoff: frame-rich analysis offers greater protocol observability, while frame-minimal analysis may be more robust when encryption or sparse capture limits semantic decoding [7] [10] [26].
Confidence level: High - the distinction is explicit and recurrent across the capture literature [5] [7] [10].

Decoding to higher layers

At least some analyzers can decode captured traces upward into MAC, IP, TCP, and HTTP views after first collecting lower-layer details such as frame transmissions, acknowledgements, CRC errors, collisions, and retransmissions [17]. This is operationally important because it enables cross-layer troubleshooting: wireless anomalies can be linked to higher-layer symptoms like application stalls or transport inefficiency [17] [47].

Traffic Reconstruction and Measurement Quality

A major theme in the evidence is that traffic reconstruction quality is a first-order concern. Wit is a direct example: it merges multiple monitor traces, infers packets missed by all monitors, and estimates whether each packet reached its destination; evaluations with real traces and simulations found substantial improvement over the original incomplete traces [12].

Other work focuses less on reconstruction algorithms and more on validation metrics. One fidelity study evaluates merged or independent traces through **trace completeness** and **clock accuracy**, using packet sequence numbers to detect drops and access-point beacon intervals to estimate timestamp accuracy [13]. A wireless-side tracing study compares three completeness-estimation methods and finds MAC-layer sequence numbers to be the most accurate estimator, while also reporting miss rates and CRC errors as indicators shaped by sensor placement [14].

A campus longitudinal study shows the common practice of preprocessing raw Wi-Fi observations into connection sessions for behavioral analysis, though the supplied abstract does not provide explicit validation metrics for the reconstruction itself [43]. This is a useful reminder that sessionization is often analytically necessary, but not always equally well validated in the literature [13] [43].

Taken together, these findings suggest that analyzer output should be interpreted as a measured-and-reconstructed representation of WLAN activity, not as a perfect transcript [12] [14]. For practical deployments, this implies that multi-monitor collection and explicit fidelity checks are not optional extras when high-confidence interpretation is needed [12] [13].
Confidence level: High - multiple sources converge on incompleteness and validation methods [12] [13] [14].

Performance Monitoring and Troubleshooting Uses

Operational WLAN studies value analyzers because they expose transmission events that conventional management telemetry often misses. Compared with SNMP polling and AP syslog, wireless analyzers offer near-instantaneous PHY/MAC visibility and can reveal retransmissions and related transmission events more directly [15] [16]. Experimental troubleshooting setups also capture transmissions, ACKs, CRC errors, collisions, and retransmissions while simultaneously decoding traces for protocol-level analysis [17].

This visibility supports several troubleshooting tasks:

- **Airtime and contention analysis** through collision, retransmission, and ACK patterns [17].
- **Cross-layer diagnosis** by combining wireless events with network/application observations, as shown in AP-and-endpoint capture studies of streaming behavior [47].
- **Channel occupancy and utilization monitoring** by identifying active channels with analyzer tools and, when data-frame capture is hard, estimating channel load from control-frame metrics [18] [48].

The evidence also indicates that Wi-Fi behavior varies materially by environment. Large-scale measurements report differences in protocol efficiency, frame delivery, application mix, and migration toward newer Wi-Fi variants [38]. Enterprise or warehouse-like conditions with heavier traffic and mobility are associated with increased packet drops and latency, indicating more unstable behavior under dense conditions [42]. Analytical traffic modeling likewise finds wireless traffic patterns that differ from wired norms, including pacing effects and multimodal interarrival behavior [44].

The practical implication is that a Wi-Fi traffic analyzer is especially useful when the problem is "wireless-specific" rather than merely "IP connectivity-related" [17] [44].
Confidence level: High - operational value is directly evidenced across troubleshooting and measurement studies [15] [17] [38].

Security Analytics, Tool Comparisons, and Limits

Intrusion detection and rogue AP discovery

The supplied evidence shows analyzers are used in wireless intrusion detection and anomaly monitoring. A wireless monitoring framework for IEEE 802.11 captures detailed PHY/MAC information and supports detection of malicious traffic, excessive retransmissions, and protocol/security anomalies from a wireless vantage point [20]. Open-source management-frame analysis tools also support identification of malicious frames [19].

For rogue AP discovery, one cited approach stores captured wireless traffic on a centralized server but depends on manual switching between normal and sniffing modes, reducing autonomy [22]. A separate frame-based study reports that rogue AP traces are heavily dominated by beacon frames with some deauthentication traffic, while legitimate APs exhibit a different frame mix including more EAPOL, suggesting that frame-distribution profiling can help distinguish malicious from benign APs [23].

Traffic-flow-only analysis can also detect WPS attacks on WPA/WPA2 routers without deep packet inspection, demonstrating that some wireless attack detection remains feasible even when payload access is restricted [21].

ML and non-payload security analytics

Recent work increasingly uses non-payload or mixed features. One 2016 campus study used simple statistical non-payload features from 2.4 TB of traffic and reported over 90% accuracy for identifying potential malicious domains [49]. An AWID3-based 2022 study comparing 802.11-specific and non-802.11 features reported up to 96.7% AUC for application-layer attacks without feature optimization [24]. Another 2022 AWID-based study found Random Forest and Decision Tree to perform best on flooding, impersonation, and injection attacks, though the supplied abstract does not provide exact percentages [25].

A broader pattern emerges: security analytics are moving toward metadata, timing, and statistical learning because encryption and modern WLAN complexity reduce the usefulness of payload-centric inspection [24] [26] [27].
Confidence level: Medium - the trend is well supported, but benchmarking quality is uneven and often lacks standardized reporting [24] [39] [40].

Tool comparisons

The strongest comparative evidence in the supplied material is partial rather than comprehensive. Wireshark is positioned as a detailed packet capture and inspection tool, and one benchmark reports a 98.5% packet-capture rate with 2.67 ms latency, albeit with higher CPU and memory use [32] [33] [35]. Survey-style discussion describes Wi-Fi analyzers more broadly as spectrum-scanning tools for mapping nearby networks, channels, and signal strength, but without rigorous same-workload benchmark numbers [34].

Critically, the supplied evidence does **not** provide validated direct benchmark results for Kismet or Aircrack-based tools on channel-hopping loss, multi-channel capture, overhead, or dense 802.11ax/6 GHz deployments [34]. Therefore, the honest conclusion is that the literature here supports qualitative comparison categories, not a defensible ranking across those tool families [33] [34].

Limits Under Encryption, Density, and Newer WLAN Conditions

Encrypted traffic reduces access to content-based features, forcing analyzers toward flow size, timing, and connection-pattern features that remain only partially accessible without payload visibility [26]. More broadly, current analyzers are described as limited by scalability, real-time processing demands, and adaptability to new encryption protocols, which pushes evaluations toward metadata-based approaches [27] [28].

Dense and high-throughput WLANs add another layer of difficulty. Under heavy enterprise traffic and mobility, packet drops and latency increase [42]. In high-throughput scenarios, per-frame rate and size differences matter, so accurate inference requires separate uplink/downlink analysis plus consideration of density, signal quality, collision probability, and frame error rate [29] [50]. Passive data-frame monitoring may become impractical enough that control-frame-based channel-load estimation is preferred because legacy-format control frames remain easier to capture [48].

For 5 GHz and 6 GHz environments, broadband or SDR sensing can detect activity, but bursty load-dependent behavior fluctuates over millisecond scales; low-rate sensing often has to rely on averaging or buffering, yielding coarse exposure or activity trends rather than packet-level detail [30]. Passive monitoring also has limited spatial precision and depends on devices having Wi-Fi enabled, though it can still support coarse flow analysis and meta-information extraction [51].

Inferred: Taken together, these findings imply a design shift from classic payload analyzers toward hybrid telemetry platforms that combine packet capture, control-frame estimation, and metadata-based inference [12] [28] [48].
Confidence level: Medium - the direction is strongly suggested by the sources, but the hybrid architecture itself is a synthesis rather than a directly evaluated single system [27] [30].

Practical Guidance for Use

Based on the supplied evidence, a practical Wi-Fi traffic analyzer workflow should prioritize:

1. **Correct capture architecture**: use supported monitor-mode hardware/drivers and avoid assuming a single radio is complete [1] [12].
2. **Frame-aware analysis**: include management/control frames for roaming, retries, and airtime diagnosis; use data-only approaches when encryption or the task demands it [7] [10].
3. **Fidelity validation**: check completeness with sequence numbers and timing with beacon intervals when trace quality matters [13] [14].
4. **Cross-layer troubleshooting**: connect PHY/MAC symptoms to higher-layer behavior rather than relying on controller logs alone [17] [47].
5. **Metadata-centric security analytics** for encrypted environments, while treating headline ML accuracy cautiously if false-positive/false-negative reporting is absent [24] [26] [39].

Conclusion

The literature portrays the Wi-Fi traffic analyzer as a passive 802.11 capture-and-decoding system whose distinctive value lies in direct visibility into wireless MAC/PHY behavior [1] [17]. The strongest evidence supports its use for troubleshooting, measurement, and security monitoring when management/control/data frames are interpreted in a task-aware way [7] [15] [20]. At the same time, its limits are persistent: no single sensor sees everything, channel handling trades off coverage and fidelity, and encryption increasingly shifts useful analysis from payloads to metadata and side-channel features [12] [26] [36].

The field's main unresolved needs are standardized tool benchmarking, stronger validation in modern 802.11ax/6 GHz settings, and more reproducible reporting for security analytics [30] [34] [39].
Overall confidence level: High - the core definition, use cases, and limitations are consistent across multiple independent strands of the supplied evidence [1] [12] [17] [26].

References

1. Jia, Yunjian, Zhou, Zhenyu, Chen, Fei, (...), Mumtaz, Shahid (2016) A Non-Intrusive Cyber Physical Social Sensing Solution to People Behavior Tracking: Mechanism, Prototype, and Field Experiments. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s17010143

2. Wright, Craig (2008) Auditing and Security with Wireless Technologies. *The IT Regulatory and Standards Compliance Handbook*. https://doi.org/10.1016/B978-1-59749-266-9.00012-6
3. Petre, Andreea-Cristina, Chilipirea, Cristian, Baratchi, Mitra, (...), van Steen, Maarten (2017) WiFi Tracking of Pedestrian Behavior. *Smart Sensors Networks*. https://doi.org/10.1016/B978-0-12-809859-2.00018-8
4. Vega-Barbas, Mario, Álvarez-Campana, Manuel, Rivera, Diego, (...), Berrocal, Julio (2021) AFOROS: A Low-Cost Wi-Fi-Based Monitoring System for Estimating Occupancy of Public Spaces. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s21113863
5. Redondi, A.E.C., Cesana, M. (2018) Building up knowledge through passive WiFi probes. *Computer Communications*. https://doi.org/10.1016/j.comcom.2017.12.012
6. Bicakci, K., Tavli, B. (2009) Denial-of-Service attacks and countermeasures in IEEE 802.11 wireless networks. *Computer Standards and Interfaces*. https://doi.org/10.1016/j.csi.2008.09.038
7. Schauer, L. (2018) Wi-fi tracking threatens users' privacy in fingerprinting techniques. *Geographical and Fingerprinting Data for Positioning and Navigation Systems: Challenges, Experiences and Technology Roadmap*. https://doi.org/10.1016/B978-0-12-813189-3.00002-2
8. Amoordon, A., Deniau, V., Fleury, A., Gransart, C. (2022) A single supervised learning model to detect fake access points, frequency sweeping jamming and deauthentication attacks in IEEE 802.11 networks. *Machine Learning with Applications*. https://doi.org/10.1016/j.mlwa.2022.100389
9. Toulson, Rob (2025) Further Aspects of the IoT. *Fast and Effective Embedded Systems Design*. https://doi.org/10.1016/B978-0-323-95197-5.00013-9
10. https://www.sciencedirect.com/science/article/pii/S236441682400132X
11. Pathmaperuma, Madushi H., Rahulamathavan, Yogachandran, Dogan, Safak, Kondoz, Ahmet M. (2022) Deep Learning for Encrypted Traffic Classification and Unknown Data Detection. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s22197643
12. Mahajan, R., Rodrig, M., Wetherall, D., Zahorjan, J. (2006) Analyzing the MAC-level behavior of wireless networks in the wild. *Computer Communication Review*. https://doi.org/10.1145/1151659.1159923
13. Schulman, A., Levin, D., Spring, N. (2008) On the fidelity of 802.11 packet traces. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*. https://doi.org/10.1007/978-3-540-79232-1_14
14. Mahanti, A., Arlitt, M., Williamson, C. (2007) Assessing the completeness of wireless-side tracing mechanisms. *2007 IEEE International Symposium on a World of Wireless, Mobile and Multimedia Networks, WOWMOM*. https://doi.org/10.1109/WOWMOM.2007.4351786
15. Takahashi, D., Xiao, Y., Zhang, Y., (...), Chen, H.-H. (2010) IEEE 802.11 user fingerprinting and its applications for intrusion detection. *Computers and Mathematics with Applications*. https://doi.org/10.1016/j.camwa.2010.01.002

16. Jia, Yunjian, Zhou, Zhenyu, Chen, Fei, (...), Mumtaz, Shahid (2016) A Non-Intrusive Cyber Physical Social Sensing Solution to People Behavior Tracking: Mechanism, Prototype, and Field Experiments. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s17010143
17. Bai, G., Oladosu, K., Williamson, C. (2007) Performance benchmarking of wireless Web servers. *Ad Hoc Networks*. https://doi.org/10.1016/j.adhoc.2006.01.001
18. Joseph, W., Pareit, D., Vermeeren, G., (...), Moerman, I. (2013) Determination of the duty cycle of WLAN for realistic radio frequency electromagnetic field exposure assessment. *Progress in Biophysics and Molecular Biology*. https://doi.org/10.1016/j.pbiomolbio.2012.10.002
19. Cronin, K., Ham, M. (2020) Open Source Capture and Analysis of 802.11 Management Frames. *Advances in Intelligent Systems and Computing*. https://doi.org/10.1007/978-3-030-43020-7_81
20. Yeo, J., Youssef, M., Agrawala, A. (2004) A framework for wireless LAN monitoring and its applications. *Proceedings of the 2004 ACM Workshop on Wireless Security, WiSe*. https://doi.org/10.1145/1023646.1023660
21. Petiz, I., Rocha, E., Salvador, P., Nogueira, A. (2013) Using multiscale traffic analysis to detect WPS attacks. *2013 IEEE International Conference on Communications Workshops, ICC 2013*. https://doi.org/10.1109/ICCW.2013.6649386
22. Agyemang, J.O., Kponyo, J.J., Klogo, G.S., Boateng, J.O. (2020) Lightweight rogue access point detection algorithm for WiFi-enabled Internet of Things(IoT) devices. *Internet of Things (Netherlands)*. https://doi.org/10.1016/j.iot.2020.100200
23. Tareef, Aya, Allawi, Yazan M., Alkasasbeh, Anas A., (...), Kang, Hunseok (2025) A machine learning approach for detecting WPA3 downgrade attacks in next-generation Wi-Fi systems. *PLoS ONE*. https://doi.org/10.1371/journal.pone.0331443
24. Chatzoglou, E., Kambourakis, G., Smiliotopoulos, C., Kolias, C. (2022) Best of Both Worlds: Detecting Application Layer Attacks through 802.11 and Non-802.11 Features. *Sensors*. https://doi.org/10.3390/s22155633
25. Agarwal, M. (2022) Detecting Flooding, Impersonation and Injection Attacks on AWID Dataset using ML based Methods. *Proceedings of 4th International Conference on Cybernetics, Cognition and Machine Learning Applications, ICCCMLA 2022*. https://doi.org/10.1109/ICCCMLA56841.2022.9989147
26. https://www.sciencedirect.com/science/article/pii/S1572819625001275
27. Sharma, A., Lashkari, A.H. (2025) A survey on encrypted network traffic: A comprehensive survey of identification/classification techniques, challenges, and future directions. *Computer Networks*. https://doi.org/10.1016/j.comnet.2024.110984
28. Alqithami, S., Stiawan, D., Budiarto, R. (2026) On-the-fly, memory-aware unsupervised learning for network anomaly detection: A systematic literature review. *e-Prime - Advances in Electrical Engineering, Electronics and Energy*. https://doi.org/10.1016/j.prime.2025.101146

29. Tüysüz, M.F., Uçan, M., Trestian, R. (2019) A real-time power monitoring and energy-efficient network/interface selection tool for android smartphones. *Journal of Network and Computer Applications*. https://doi.org/10.1016/j.jnca.2018.11.013

30. Rathebe, Phoka C., Kholopo, Mota (2026) Low-Cost Sensors in 5G RF-EMF Exposure Monitoring: Validity and Challenges. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s26020533

31. Rasool, M.B., Shah, U.M., Imran, M., (...), FREY, G. (2025) Invisible eyes: Real-time activity detection through encrypted Wi-Fi traffic without machine learning. *Internet of Things (The Netherlands)*. https://doi.org/10.1016/j.iot.2025.101602

32. Hashim, S.R., Abdulhamed, M.K., Abdalhameed, N.K. (2025) Detecting network activity using the wireshark utility. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0298413

33. Gohil, T., Kharvar, A., Mandalaywala, A. (2026) Performance Evaluation of Network Packet Analysis Tools using Analytical Techniques. *17th International Conference on Advances in Computing, Control, and Telecommunication Technologies, ACT 2026*. https://www.scopus.com/pages/publications/105047237606

34. Jivtesh, M.R., Gaushik, M.R., Adarsh, P., (...), Rao, N.S. (2022) A Comprehensive survey of WiFi Analyzer Tools. *2022 IEEE 3rd Global Conference for Advancement in Technology, GCAT 2022*. https://doi.org/10.1109/GCAT55367.2022.9972040

35. Nainar, N.K., Panda, A. (2022) Wireshark for network forensics: An essential guide for IT and cloud professionals. *Wireshark for Network Forensics: An Essential Guide for IT and Cloud Professionals*. https://doi.org/10.1007/978-1-4842-9001-9

36. Geiger, D.J., Scheets, G., Teague, K.A., Pitts, J. (2008) Multi-channel packet capture in 802.11b/g wireless networks. *Conference Record - Asilomar Conference on Signals, Systems and Computers*. https://doi.org/10.1109/ACSSC.2008.5074542

37. Claveirole, T., de Amorim, M. (2008) WiPal and WScout, two hands-on tools for wireless packet traces manipulation and visualization. *Proceedings of the Annual International Conference on Mobile Computing and Networking, MOBICOM*. https://doi.org/10.1145/1410077.1410101

38. Wu, S., Abed, S.H., Yang, Q., Wang, H. (2016) IEEE 802.11 traffic measurement and analysis. *International Conference on Mobile Multimedia Communications (MobiMedia)*. https://doi.org/10.4108/eai.18-6-2016.2264315

39. https://www.sciencedirect.com/science/article/pii/S1573772124000863

40. https://www.sciencedirect.com/science/article/pii/S1936645025002104

41. Choi, H., Gong, T., Kim, J., (...), Lee, S.-J. (2019) Use MU-MIMO at your own risk — Why we don't get Gb/s Wi-Fi. *Ad Hoc Networks*. https://doi.org/10.1016/j.adhoc.2018.08.019

42. Sathya, V., Zhang, L., Sahin, O., Yavuz, M. (2024) Enterprise Approach: Performance Analysis of Wi-Fi 6 and 5G Private LAN With Micro-Slicing Feature. *IEEE Access*. https://doi.org/10.1109/ACCESS.2024.3445295

43. Camacho, J., McDonald, C., Peterson, R., (...), Kotz, D. (2020) Longitudinal analysis of a campus Wi-Fi network. *Computer Networks*. https://doi.org/10.1016/j.comnet.2020.107103

44. Tickoo, O., Sikdar, B. (2002) Modeling and analysis of traffic characteristics in IEEE 802.11 MAC based networks. *Conference Record / IEEE Global Telecommunications Conference*. https://www.scopus.com/pages/publications/0036967221

45. de Poorter, E., Bouckaert, S., Moerman, I., Demeester, P. (2011) Non-intrusive aggregation in wireless sensor networks. *Ad Hoc Networks*. https://doi.org/10.1016/j.adhoc.2010.07.017

46. Li, Y., Huang, Y., Seneviratne, S., (...), Xu, R.Y.D. (2022) From traffic classes to content: A hierarchical approach for encrypted traffic classification. *Computer Networks*. https://doi.org/10.1016/j.comnet.2022.109017

47. Kuang, T., Williamson, C. (2004) Hierarchical analysis of RealMedia streaming traffic on an IEEE 802.11b wireless LAN. *Computer Communications*. https://doi.org/10.1016/j.comcom.2003.08.019

48. Romero-Hierro, P., Aguayo-Torres, M.C., Cárdenas Angelat, C., Baños-Polglase, J. (2016) Wi-Fi® channel load estimation based on control frames metrics. *IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, PIMRC*. https://doi.org/10.1109/PIMRC.2016.7794833

49. Raghuramu, A., Pathak, P.H., Zang, H., (...), Chuah, C.-N. (2016) Uncovering the footprints of malicious traffic in wireless/mobile networks. *Computer Communications*. https://doi.org/10.1016/j.comcom.2016.04.011

50. Stateczny, Andrzej, Gierlowski, Krzysztof, Hoeft, Michal (2022) Wireless Local Area Network Technologies as Communication Solutions for Unmanned Surface Vehicles. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s22020655

51. Ribeiro, Miguel, Nunes, Nuno, Nisi, Valentina, Schöning, Johannes (2020) Passive Wi-Fi monitoring in the wild: a long-term study across multiple location typologies. *Personal and Ubiquitous Computing*. https://doi.org/10.1007/s00779-020-01441-z