

MATERIAL SAFETY DATA SHEET

Product Name: MEK Solvent (Methyl Ethyl Ketone)

Chemical Name: Butan-2-one

CAS Number: 78-93-3

Trade Name: Industrial MEK Grade A

Section 2 - Hazard Identification

GHS Hazard Classification:

H225 - Highly flammable liquid and vapour

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

UN Hazard Class 3 - Flammable Liquids

Signal Word: DANGER

This material is flammable and toxic in high concentrations.

Section 9 - Physical and Chemical Properties

Flash Point: -9 deg C (closed cup, Pensky-Martens)

Boiling Point: 79.6 deg C

pH: Not applicable (non-aqueous solvent)

Density: 0.805 g/cm³ at 20 deg C

Vapour Pressure: 105 hPa at 20 deg C

Auto-ignition: 404 deg C