MOBSF

ANDROID STATIC ANALYSIS REPORT

Aptoide (9.22.5.3)

File Name:	app-netmirror-netmirrornew.apk
Package Name:	cm.aptoide.pt
Scan Date:	March 31, 2026, 8:59 a.m.
App Security Score:	52/100 (MEDIUM RISK)
Grade:	B
Trackers Detection:	6/432

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
4	26	2	4	2

FILE INFORMATION

File Name: app-netmirror-netmirrornew.apk
Size: 19.14MB
MD5: 2725e9ae81839a4ae69f8f362fc4d7e1
SHA1: 81833829fda154b743addf3572889d96f95fec22
SHA256: 188bbdb899be2da401ac0471ba4d10693612fa1067f2ea0987cc6e1afcfd4374

APP INFORMATION

App Name: Aptoide
Package Name: cm.aptoide.pt
Main Activity: cm.aptoide.pt.view.MainActivity
Target SDK: 32
Min SDK: 16
Max SDK:
Android Version Name: 9.22.5.3
Android Version Code: 12060

APP COMPONENTS

Activities: 11
Services: 19
Receivers: 19
Providers: 9
Exported Activities: 2
Exported Services: 2
Exported Receivers: 5
Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: ST=Portugal
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2009-09-22 14:53:51+00:00
Valid To: 2034-09-16 14:53:51+00:00
Issuer: ST=Portugal
Serial Number: 0x4ab8e4ff
Hash Algorithm: sha1
md5: 99bd1872bc56b4b2619e731ae9cbdc6f
sha1: d590a7d792fd0331542d99faf9997641790773a9
sha256: 73534d45c1345a4783c7eff2cf6038551ab5fdf09673f32c68c3b0864baa80e4
sha512: 8a5562a7825800df284d47dab79fcae1ccde0c3c46b1a181696809ed270576b92718130131ffef402f4d2822e235879de1e91224d91f0f4c0a0b58d2d2bc5b43
PublicKey Algorithm: rsa
Bit Size: 1024
Fingerprint: aae7fc687c60f98a8b14c3a3b9da6abc420f3a320de9309f960ce7b628a3063e
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.READ_SYNC_STATS	normal	read sync statistics	Allows an application to read the sync stats; e.g. the history of syncs that have occurred.
com.android.launcher.permission.INSTALL_SHORTCUT	unknown	Unknown permission	Unknown permission from android reference
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.INSTALL_PACKAGES	SignatureOrSystem	directly install applications	Allows an application to install new or updated Android packages. Malicious applications can use this to add new applications with arbitrarily powerful permissions.
android.permission.CHANGE_WIFI_MULTICAST_STATE	normal	allow Wi-Fi Multicast reception	Allows an application to receive packets not directly addressed to your device. This can be useful when discovering services offered nearby. It uses more power than the non-multicast mode.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.READ_SYNC_SETTINGS	normal	read sync settings	Allows an application to read the sync settings, such as whether sync is enabled for Contacts.
android.permission.WRITE_SYNC_SETTINGS	normal	write sync settings	Allows an application to modify the sync settings, such as whether sync is enabled for Contacts.
android.permission.AUTHENTICATE_ACCOUNTS	dangerous	act as an account authenticator	Allows an application to use the account authenticator capabilities of the Account Manager, including creating accounts as well as obtaining and setting their passwords.
android.permission.GET_ACCOUNTS	dangerous	list accounts	Allows access to the list of accounts in the Accounts Service.
android.permission.MANAGE_ACCOUNTS	dangerous	manage the accounts list	Allows an application to perform operations like adding and removing accounts and deleting their password.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.USE_CREDENTIALS	dangerous	use the authentication credentials of an account	Allows an application to request authentication tokens.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.QUERY_ALL_PACKAGES	normal	enables querying any normal app on the device.	Allows query of any normal app on the device, regardless of manifest declarations.
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.REQUEST_DELETE_PACKAGES	normal	enables an app to request package deletions.	Allows an application to request deleting packages.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check possible Build.SERIAL check network operator name check device ID check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes2.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
Build.HARDWARE check
Build.TAGS check
SIM operator check
network operator name check
possible VM check</td></tr>
<tr><td>Anti Debug Code</td><td>Debug.isDebuggerConnected() check</td></tr>
<tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr>
</table>
</td></tr>
<tr><td>classes3.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr>
</table>
</td></tr>
</table>

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.facebook.CustomTabActivity	Schemes: @string/fb_login_protocol_scheme://, fbconnect://, Hosts: cct.cm.aptoide.pt,
cm.aptoide.pt.DeepLinkIntentReceiver	Schemes: file://, http://, aptoide://, aptoiderepo://, aptoideinstall://, aptoideauth://, aptoidesearch://, aptoidefeature://, market://, https://, Hosts: *.aptoide.com, app.aptoide.com, Mime Types: application/vnd.cm.aptoide.pt, Paths: /appcoins, /app, Path Prefixes: /download, Path Patterns: /editorial/.*,

NETWORK SECURITY

HIGH: **0** | WARNING: **1** | INFO: **1** | SECURE: **0**

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	info	Base config is configured to trustbundled certs @raw/vanilla_cert.
2	*	warning	Base config is configured to trust system certificates.

CERTIFICATE ANALYSIS

HIGH: **1** | WARNING: **1** | INFO: **1**

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.
Certificate algorithm vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

MANIFEST ANALYSIS

HIGH: **1** | WARNING: **14** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 4.1-4.1.2, [minSdk=16]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.

NO	ISSUE	SEVERITY	DESCRIPTION
3	Launch Mode of activity (cm.aptoide.pt.view.MainActivity) is not standard.	warning	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
4	TaskAffinity is set for activity (cm.aptoide.pt.wallet.WalletInstallActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
5	Content Provider (cm.aptoide.pt.toolbox.ToolboxContentProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Activity (com.facebook.CustomTabActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	TaskAffinity is set for activity (cm.aptoide.pt.DeepLinkIntentReceiver)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.

NO	ISSUE	SEVERITY	DESCRIPTION
8	Activity (cm.aptoide.pt.DeepLinkIntentReceiver) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Broadcast Receiver (cm.aptoide.pt.install.InstalledBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Broadcast Receiver (cm.aptoide.pt.widget.SearchWidgetProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
12	Broadcast Receiver (com.google.android.gms.measurement.AppMeasurementInstallReferrerReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.INSTALL_PACKAGES [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
13	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
14	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
15	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
16	High Intent Priority (999) - {1} Hit(s) [android:priority]	warning	By setting an intent priority higher than another intent, the app effectively overrides other requests.

CODE ANALYSIS

HIGH: **1** | WARNING: **9** | INFO: **1** | SECURE: **3** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	cm/aptoide/pt/BuildConfig.java cm/aptoide/pt/DeepLinkIntentReceiver.java cm/aptoide/pt/account/AccountAnalytics.java cm/aptoide/pt/account/AndroidAccountManagerPersistence.java cm/aptoide/pt/account/view/LoginSignUpCredentialsFragment.java cm/aptoide/pt/app/view/MoreBundleFragment.java cm/aptoide/pt/bottomNavigation/BottomNavigationActivity.java cm/aptoide/pt/database/room/RoomNotification.java cm/aptoide/pt/database/room/RoomStore.java cm/aptoide/pt/dataprovider/WebService.java cm/aptoide/pt/dataprovider/model/v3/CheckUserCredentialsJson.java cm/aptoide/pt/home/HomeFragment.java cm/aptoide/pt/home/bundles/BundlesRepository.java cm/aptoide/pt/networking/Pnp1AuthorizationInterceptor.java cm/aptoide/pt/preferences/LocalPersistenceAdultContent.java cm/aptoide/pt/preferences/managed/ManagedKeys.java cm/aptoide/pt/promotions/ClaimPromotionDialogFragment.java cm/aptoide/pt/themes/ThemeManager.java cm/aptoide/pt/view/DeepLinkManager.java cm/aptoide/pt/view/app/ListStoreAppsFragment.java cm/aptoide/pt/view/fragment/GridRecyclerSwipeWithToolbarFragment.java cm/aptoide/pt/view/settings/SettingsFragment.java com/aptoide/aptoide_ab_testing/model/Distri

NO	ISSUE	SEVERITY	STANDARDS	FILES
				bution.java com/aptoide/aptoide_ab_testing/model/EvalContext.java
				com/aptoide/aptoide_ab_testing/model/Flag.java com/aptoide/aptoide_ab_testing/model/PostEvaluationResponseJson.java com/aptoide/aptoide_ab_testing/model/Variant.java com/bumptech/glide/load/engine/d.java com/bumptech/glide/load/engine/p.java com/bumptech/glide/load/engine/w.java com/bumptech/glide/load/h.java
				c/a/k/a/a.java c/a/o/g.java c/g/b/d.java c/g/b/k/f.java c/i/e/c.java c/i/e/e.java c/i/e/f.java c/i/e/g.java c/i/e/j.java c/i/e/k.java c/i/i/b.java c/k/a/c.java c/o/a/a.java c/p/a/b.java c/p/b/c.java c/q/a/a.java c/r/a.java c/r/b.java c/s/a/b.java c/u/a/c.java c/v/a/c.java c/w/a.java c/x/i0.java c/x/y.java c/y/a/a/i.java cm/aptoide/aptoideviews/common/StringUtilsKt.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				cm/aptoide/aptoideviews/downloadprogressview/DownloadProgressView$stateMachine$1.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	cm/aptoide/pt/AptoideFirebaseNotificationService.java cm/aptoide/pt/app/view/AppCoinsInfoFragment.java cm/aptoide/pt/crashreports/CrashReport.java cm/aptoide/pt/dataprovider/ws/v7/ListSearchAppsRequest.java cm/aptoide/pt/editorial/EditorialFragment.java cm/aptoide/pt/editorialList/EditorialListFragment.java cm/aptoide/pt/home/HomeFragment.java cm/aptoide/pt/install/installer/Root.java cm/aptoide/pt/install/remote/RemoteInstallationSenderManager.java cm/aptoide/pt/logger/Logger.java cm/aptoide/pt/networking/image/ImageLoader.java cm/aptoide/pt/notification/NotificationWorker.java cm/aptoide/pt/root/RootShell.java cm/aptoide/pt/root/containers/RootClass.java cm/aptoide/pt/toolbox/ToolboxContentProvider.java com/airbnb/epoxy/i.java com/airbnb/epoxy/p.java com/airbnb/lottie/LottieAnimationView.java com/airbnb/lottie/c.java com/airbnb/lottie/d.java com/airbnb/lottie/e.java com/airbnb/lottie/f.java com/airbnb/lottie/l.java com/airbnb/lottie/r/a.java com/airbnb/lottie/r/b.java com/airbnb/lottie/u/c.java com/airbnb/lottie/u/g.java com/airbnb/lottie/u/u.java com/aptoide/aptoide_ab_testing/model/EvalDebugLog.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/aptoide/aptoide_ab_testing/model/SegmentDebugLog.java com/bumptech/glide/c.java com/bumptech/glide/k/a.java com/bumptech/glide/l/d.java com/bumptech/glide/l/e.java com/bumptech/glide/load/engine/GlideException.java com/bumptech/glide/load/engine/a0/e.java com/bumptech/glide/load/engine/a0/i.java com/bumptech/glide/load/engine/b0/a.java com/bumptech/glide/load/engine/b0/b.java com/bumptech/glide/load/engine/h.java com/bumptech/glide/load/engine/i.java com/bumptech/glide/load/engine/k.java com/bumptech/glide/load/engine/y.java com/bumptech/glide/load/engine/z/j.java com/bumptech/glide/load/engine/z/k.java com/bumptech/glide/load/m/b.java com/bumptech/glide/load/m/j.java com/bumptech/glide/load/m/l.java com/bumptech/glide/load/m/o/c.java com/bumptech/glide/load/m/o/e.java com/bumptech/glide/load/n/c.java com/bumptech/glide/load/n/d.java com/bumptech/glide/load/n/f.java com/bumptech/glide/load/n/s.java com/bumptech/glide/load/n/t.java com/bumptech/glide/load/o/c/c.java com/bumptech/glide/load/o/c/j.java com/bumptech/glide/load/o/c/l.java com/bumptech/glide/load/o/c/m.java com/bumptech/glide/load/o/c/q.java com/bumptech/glide/load/o/c/w.java com/bumptech/glide/load/o/c/y.java com/bumptech/glide/load/o/g/a.java com/bumptech/glide/load/o/g/d.java com/bumptech/glide/load/o/g/j.java com/bumptech/glide/m/e.java com/bumptech/glide/m/f.java com/bumptech/glide/m/k.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/bumptech/glide/m/l.java com/bumptech/glide/m/n.java com/bumptech/glide/m/o.java com/bumptech/glide/n/d.java com/bumptech/glide/p/j.java com/bumptech/glide/p/l/j.java com/bumptech/glide/q/a.java com/bumptech/glide/r/l/a.java com/flurry/sdk/a.java e/b/a/a/a.java e/e/b/a/i/z/a.java e/e/b/c/a0/g.java e/e/b/c/m/h.java e/e/b/c/x/d.java e/e/b/c/y/b.java e/f/a/a/a.java io/rakam/api/h.java io/sentry/android/core/i0.java io/sentry/n5.java k/b/f/i.java rx/n/e/h.java rx/q/c.java
3	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	cm/aptoide/pt/ApplicationModule.java cm/aptoide/pt/abtesting/ABTestServiceProvider.java cm/aptoide/pt/dataprovider/WebService.java com/aptoide/aptoide_ab_testing/network/FlagrApiService.java com/aptoide/authentication/network/RemoteAuthenticationService.java com/flurry/sdk/l1.java
4	The file or SharedPreference is World Writable. Any App can write to the file	high	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	e/f/a/a/a.java
5	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	cm/aptoide/pt/preferences/PRNGFixes.java cm/aptoide/pt/utils/AptoideUtils.java io/sentry/util/u.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
6	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	cm/aptoide/pt/database/room/RoomInstalled.java cm/aptoide/pt/install/installer/DefaultInstaller.java cm/aptoide/pt/view/ActivityModule.java com/flurry/sdk/i4.java e/h/a/k0/f.java io/sentry/android/core/w0.java
7	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	c/u/a/g/a.java e/e/b/a/i/b0/j/r0.java e/e/b/a/i/b0/j/t0.java e/h/a/f0/d.java e/h/a/f0/e.java io/rakam/api/b.java
8	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	c/r/b.java cm/aptoide/pt/account/view/PhotoFileGenerator.java
9	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	cm/aptoide/pt/ads/AdsRepository.java cm/aptoide/pt/utils/AptoideUtils.java i/a/g/h.java i/a/g/l.java
10	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	cm/aptoide/pt/download/FileDownloadTask.java cm/aptoide/pt/utils/AptoideUtils.java e/h/a/k0/f.java
11	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	cm/aptoide/pt/BuildConfig.java cm/aptoide/pt/networking/UserAgentInterceptor.java i/a/g/l.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
12	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	io/sentry/android/core/internal/util/r.java
13	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	io/sentry/android/core/internal/util/r.java
14	This App uses SafetyNet API.	secure	OWASP MASVS: MSTG-RESILIENCE-7	cm/aptoide/pt/analytics/FirstLaunchAnalytics.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	armeabi-v7a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi-v7a/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	x86_64/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	x86_64/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	armeabi-v7a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	armeabi-v7a/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	x86/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	x86/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	x86_64/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	x86_64/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	cm/aptoide/pt/DeepLinkIntentReceiver.java cm/aptoide/pt/app/view/AppViewFragment.java cm/aptoide/pt/home/HomeFragment.java cm/aptoide/pt/install/view/remote/RemoteInstallDialog.java cm/aptoide/pt/link/CustomTabNativeReceiver.java cm/aptoide/pt/link/CustomTabsHelper.java cm/aptoide/pt/notification/ReadyToInstallNotificationManager.java cm/aptoide/pt/notification/SystemNotificationShower.java cm/aptoide/pt/promotions/ClaimPromotionsNavigator.java cm/aptoide/pt/util/ReferrerUtils.java cm/aptoide/pt/view/MainActivity.java cm/aptoide/pt/view/recycler/widget/GridDisplayWidget.java cm/aptoide/pt/widget/SearchWidgetProvider.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	c/r/a.java c/r/b.java c/u/a/g/b.java cm/aptoide/pt/ApplicationModule.java cm/aptoide/pt/account/view/ImageInfoProvider.java cm/aptoide/pt/database/room/RoomInstalled.java cm/aptoide/pt/file/CacheHelper.java cm/aptoide/pt/install/RootInstallerProvider.java cm/aptoide/pt/install/installer/DefaultInstaller.java cm/aptoide/pt/install/installer/RootInstaller.java cm/aptoide/pt/root/containers/RootClass.java cm/aptoide/pt/utils/MultiDexHelper.java com/airbnb/lottie/t/b.java com/airbnb/lottie/t/c.java com/fasterxml/jackson/databind/ser/std/FileSerializer.java com/flurry/sdk/b2.java com/flurry/sdk/m3.java com/flurry/sdk/n7.java com/flurry/sdk/v0.java com/flurry/sdk/z6.java e/h/a/d.java e/h/a/k0/f.java io/sentry/android/core/cache/b.java io/sentry/android/core/k0.java io/sentry/android/core/w0.java io/sentry/cache/o.java io/sentry/cache/p.java io/sentry/cache/q.java io/sentry/e1.java io/sentry/i1.java io/sentry/j3.java io/sentry/l3.java io/sentry/x4.java
00016	Get location info of the device and put it to JSON object	location collection	com/flurry/sdk/y5.java io/rakam/api/g.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	cm/aptoide/pt/link/CustomTabsHelper.java cm/aptoide/pt/util/ReferrerUtils.java cm/aptoide/pt/widget/SearchWidgetProvider.java
00013	Read file and put it into a stream	file	c/i/e/e.java c/i/e/k.java cm/aptoide/pt/packageinstaller/AppInstaller.java cm/aptoide/pt/preferences/PRNGFixes.java cm/aptoide/pt/root/execution/Shell.java cm/aptoide/pt/utils/AptoideUtils.java cm/aptoide/pt/utils/FileUtils.java com/airbnb/lottie/t/b.java com/airbnb/lottie/t/c.java com/bumptech/glide/k/a.java com/bumptech/glide/load/n/f.java com/fasterxml/jackson/core/JsonFactory.java com/flurry/sdk/b2.java com/flurry/sdk/c7.java com/flurry/sdk/g.java com/flurry/sdk/j2.java com/flurry/sdk/n3.java com/flurry/sdk/n7.java com/flurry/sdk/o7.java com/flurry/sdk/r0.java com/flurry/sdk/x6.java io/sentry/cache/o.java io/sentry/cache/p.java io/sentry/cache/q.java io/sentry/config/e.java io/sentry/i1.java io/sentry/j3.java io/sentry/l3.java io/sentry/util/l.java j/r.java

RULE ID	BEHAVIOUR	LABEL	FILES
00112	Get the date of the calendar event	collection calendar	cm/aptoide/pt/utils/AptoideUtils.java com/fasterxml/jackson/databind/ser/std/StdKeySerializers.java
00089	Connect to a URL and receive input stream from the server	command network	com/airbnb/lottie/t/c.java com/bumptech/glide/load/m/j.java com/flurry/sdk/k1.java e/h/a/e0/c.java io/sentry/transport/p.java
00030	Connect to the remote server through the given URL	network	com/airbnb/lottie/t/c.java com/bumptech/glide/load/m/j.java com/flurry/sdk/k1.java e/h/a/e0/c.java io/sentry/transport/p.java
00109	Connect to a URL and get the response code	network command	com/airbnb/lottie/t/c.java com/bumptech/glide/load/m/j.java com/flurry/sdk/k1.java e/h/a/e0/c.java io/sentry/transport/p.java
00012	Read data and put it into a buffer stream	file	io/sentry/cache/o.java io/sentry/cache/q.java io/sentry/config/e.java io/sentry/i1.java io/sentry/j3.java io/sentry/util/l.java
00009	Put data in cursor to JSON object	file	io/rakam/api/b.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	cm/aptoide/pt/app/view/AppViewFragment.java cm/aptoide/pt/home/HomeFragment.java cm/aptoide/pt/view/MainActivity.java cm/aptoide/pt/view/recycler/widget/GridDisplayWidget.java cm/aptoide/pt/widget/SearchWidgetProvider.java

RULE ID	BEHAVIOUR	LABEL	FILES
00091	Retrieve data from broadcast	collection	cm/aptoide/pt/AptoideFirebaseNotificationService.java cm/aptoide/pt/link/CustomTabsHelper.java cm/aptoide/pt/packageinstaller/InstallResultReceiver.java cm/aptoide/pt/view/MainActivity.java
00054	Install other APKs from file	reflection	cm/aptoide/pt/install/installer/DefaultInstaller.java
00023	Start another application from current application	reflection control	cm/aptoide/pt/utils/AptoideUtils.java
00035	Query the list of the installed packages	reflection	cm/aptoide/pt/utils/AptoideUtils.java
00078	Get the network operator name	collection telephony	cm/aptoide/pt/utils/AptoideUtils.java com/flurry/sdk/w.java io/rakam/api/d.java
00130	Get the current WIFI information	wifi collection	cm/aptoide/pt/install/remote/RemoteInstallationSenderManager.java
00096	Connect to a URL and set request method	command network	com/airbnb/lottie/t/c.java com/flurry/sdk/k1.java e/h/a/e0/c.java io/sentry/transport/p.java
00189	Get the content of a SMS message	sms	cm/aptoide/pt/account/view/ImageInfoProvider.java cm/aptoide/pt/account/view/UriToPathResolver.java
00188	Get the address of a SMS message	sms	cm/aptoide/pt/account/view/ImageInfoProvider.java cm/aptoide/pt/account/view/UriToPathResolver.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	cm/aptoide/pt/account/view/ImageInfoProvider.java
00191	Get messages in the SMS inbox	sms	cm/aptoide/pt/account/view/ImageInfoProvider.java

RULE ID	BEHAVIOUR	LABEL	FILES
00200	Query data from the contact list	collection contact	cm/aptoide/pt/account/view/ImageInfoProvider.java cm/aptoide/pt/account/view/UriToPathResolver.java
00201	Query data from the call log	collection calllog	cm/aptoide/pt/account/view/ImageInfoProvider.java cm/aptoide/pt/account/view/UriToPathResolver.java
00034	Query the current data network type	collection network	com/flurry/sdk/w.java
00137	Get last known location of the device	location collection	io/rakam/api/d.java
00115	Get last known location of the device	collection location	io/rakam/api/d.java
00132	Query The ISO country code	telephony collection	io/rakam/api/d.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	com/bumptech/glide/load/m/o/c.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/163274999232/namespaces/firebase:fetch?key=AIzaSyCc60S0ms7zR1xi4cp1JANTkBXF5NhcnTM. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	10/25	android.permission.WAKE_LOCK, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.ACCESS_WIFI_STATE, android.permission.GET_ACCOUNTS, android.permission.INTERNET, android.permission.READ_EXTERNAL_STORAGE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.CAMERA, android.permission.REQUEST_INSTALL_PACKAGES, android.permission.ACCESS_NETWORK_STATE
Other Common Permissions	6/44	com.android.launcher.permission.INSTALL_SHORTCUT, android.permission.AUTHENTICATE_ACCOUNTS, android.permission.FOREGROUND_SERVICE, com.google.android.c2dm.permission.RECEIVE, com.google.android.gms.permission.AD_ID, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION

DOMAIN	STATUS	GEOLOCATION
twitter.com	ok	**IP:** 162.159.140.229 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
diagnostics.rakam.io	ok	**IP:** 104.21.35.78 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ws75-cache.aptoide.com	ok	**IP:** 172.66.150.34 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ws75.aptoide.com	ok	**IP:** 37.48.77.180 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
aptoi.de	ok	**IP:** 52.23.47.7 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
impression.appsflyer.com	ok	**IP:** 18.66.41.126 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.slf4j.org	ok	**IP:** 159.100.250.151 **Country:** Switzerland **Region:** Vaud **City:** Lausanne **Latitude:** 46.515999 **Longitude:** 6.632820 **View:** Google Map
placeimg.com	ok	No Geolocation information available.
m.aptoide.com	ok	**IP:** 172.66.150.34 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
play.google.com	ok	**IP:** 142.250.207.206 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
api.aptoide.com	ok	**IP:** 104.20.24.150 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
cdn6.aptoide.com	ok	**IP:** 172.66.150.34 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
www.aptoide.com	ok	**IP:** 54.77.224.201 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
aptoide-mmp.aptoide.com	ok	**IP:** 172.66.150.34 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
data.flurry.com	ok	No Geolocation information available.
imgs.aptoide.com	ok	**IP:** 37.48.77.161 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
www.tiktok.com	ok	No Geolocation information available.
catappult.io	ok	**IP:** 52.211.87.69 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
sentry.aptoide.com	ok	**IP:** 37.48.77.181 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
pool.img.aptoide.com	ok	**IP:** 104.20.24.150 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
blog.aptoide.com	ok	**IP:** 37.48.77.161 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
ws75-primary.aptoide.com	ok	**IP:** 37.48.77.161 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
api.indicative.com	ok	**IP:** 34.98.104.50 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map
www.youtube.com	ok	**IP:** 142.251.42.238 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
webservices.aptoide.com	ok	**IP:** 37.48.77.165 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
github.com	ok	**IP:** 20.207.73.82 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.example.com	ok	**IP:** 104.18.27.120 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
facebook.com	ok	**IP:** 57.144.68.1 **Country:** United States of America **Region:** California **City:** Palo Alto **Latitude:** 37.441879 **Longitude:** -122.143021 **View:** Google Map
www.instagram.com	ok	**IP:** 57.144.42.34 **Country:** United States of America **Region:** California **City:** Palo Alto **Latitude:** 37.441879 **Longitude:** -122.143021 **View:** Google Map

EMAILS

EMAIL	FILE
filipo@emailo.como	com/aptoide/authentication/mock/MockAuthenticationService.java

EMAIL	FILE
support@aptoide.com	cm/aptoide/pt/AptoideApplication.java
4259b961735ba5eda557@sentry.aptoide	cm/aptoide/pt/BuildConfig.java
suport@aptoide.com aptoide@aptoide.com support@aptoide.com □□□suport@aptoide.com□□□□□□□	Android String Resource

TRACKERS

TRACKER	CATEGORIES	URL
Facebook Login	Identification	https://reports.exodus-privacy.eu.org/trackers/67
Flurry	Analytics, Advertisement	https://reports.exodus-privacy.eu.org/trackers/25
Google AdMob	Advertisement	https://reports.exodus-privacy.eu.org/trackers/312
Google CrashLytics	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/27
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49
Sentry	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/447

HARDCODED SECRETS

POSSIBLE SECRETS
"store_suggestion_provider_authority" : "cm.aptoide.pt.provider.StoreSearchSuggestionProvider"
"password" : "Salasana"
"store_username" : "Becenév"
"password" : "Пароль"
"store_username" : "Alcunha"
"password" : "□□"
"store_username" : "[redacted]"
"password" : "Hasło"
"store_username" : "Apelido"
"password" : "[redacted]"
"store_username" : "Никнейм"
"password" : "Palavra-passe"
"store_username" : "[redacted]"
"password" : "Jelszó"
"password" : "Wachtwoord"
"com.google.firebase.crashlytics.mapping_file_id" : "18651666d6e84952b2ae388bbb3f7e0e"

POSSIBLE SECRETS
"store_username" : "Псевдонім"
"nothing_inserted_user" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"password" : "گذرواژه"
"store_username" : "■■■■■"
"store_username" : "Weergavenaam"
"store_username" : "■■■■■"
"store_username" : "Прякор"
"store_username" : "Apodo"
"password" : "Парола"
"password" : "Contraseña"
"store_username" : "Pseudo"
"password" : "■■■■■■■■■■"
"store_username" : "□□□□□□"
"store_username" : "□□"
"store_username" : "Ψευδώνυμο"
"password" : "□□□□"

POSSIBLE SECRETS
"password" : "[redacted]"
"google_api_key" : "AIzaSyCc60S0ms7zR1xi4cp1JANTkBXF5NhcnTM"
"search_suggestion_provider_authority" : "cm.aptoide.pt.provider.SearchSuggestionProvider"
"store_username" : "Nadimak"
"store_username" : "Nickname"
"password" : "[redacted]"
"password" : "Şifre"
"password" : "□□"
"password" : "Passwort"
"password" : "[redacted]"
"store_username" : "[redacted]□[redacted]"
"password" : "Parolă"
"password" : "Lozinka"
"com_facebook_device_auth_instructions" : "□□facebook.com/device□□□□□□□□□□□□□"
"facebook_client_token" : "ab3495bb67f3e5f6db2b832e09705991"
"com_facebook_device_auth_instructions" : "facebook.com/device□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"

POSSIBLE SECRETS
"store_username" : "Nick"
"nothing_inserted_user" : "[redacted](□□□□□□□□□)[redacted]"
"nothing_inserted_user" : "□□□□□□□□□□□□□□□□□□□"
"store_username" : "Pseudonim"
"store_username" : "□□"
"password" : "Password"
"store_username" : "Nimimerkki"
"google_crash_reporting_api_key" : "AIzaSyCc60S0ms7zR1xi4cp1JANTkBXF5NhcnTM"
"password" : "□□□□□"
Bl3RSPeFXX48+A41tWFMGRj6+1eT4NHtkwATNUdtNkM=

POSSIBLE SECRETS
308205653082034ca00302010202044df76b53300d06092a864886f70d01010505003073310b3009060355040613027074311030 0e06035504081307556e6b6e6f776e310f300d060355040713064c6973626f6131153013060355040a130c4361697861204d6167696361311030 0e060355040b1307556e6b6e6f776e311830160603550403130f447561727465205369 6c7665697261302022230 0d06092a864886f70d01010105000382020f003082020a02820201026cfe7512fa0c40520971ee83e227208e072a1e1962a4fd0cd5c709e33dc45ce856e9ddc2b9a918394e96ec462d5fea2db81c443b9dbedd75a1031a1f1593b86eef83302f9ecdc0dfd227a3e11ccedb056e58c79b9177dbefba122a390dac88a90a317cb55a9171ab428b46c2e29b5d7fef2e823f5985b9c165a1edba7c82b4f8d5e3aa346996019cb8b7bcc768f5fdae15975add5e53c1fc022e4c99dababf3a80c5a09680ba4b8889cc4399940d92d11c289268d3f2671b98f871964f21c5870d9a1c72c8fbea65a637a06643f246e733fff37b7db4020fd2b6e7343fdbac2ddd20f8a48710d944d8f76432a3225f72c6a50c4e76247fb9256f294eeb9e24080ad28094fbfcfa6e4b5a85d652b1c5d967b39ee1272955a134a0ff1e89bb01f98d710204c72ca4c9dd44ecdd81358a8ef920fa371edd1bfc097c81678aa31b059b9218eba5c0ed2c209bd799a3ecab19e5e3b0e3d18029bf156b37e091969b4e5ae5024475b038b4d841e0e88580fd433154f606f1f7c14527f00509dd7448911e1ec44cb1e94f7dce59459e95438c4a245103d14fff047f97d14bf38f1802d84727b0f3aa98e02e8840892c629e303f76965e186de1d92263ec17e35aa224c33856d59095cf9195042ebfb5fd4703ef8add7ccf923640f266c22e432232f5c6b0873d99ebd509f9e66a77506eabef04ae1d9cf5edb40e13bc1cff39917da8b70203010001300d06092a864886f70d01010505000382020200069a29624d30983fdec4c4bf685f2f479214fda52e272a74ae8aee8bc7aae441ba79977cdd251cf5b21c56ee631dd1e17da28a2bd87d1190b4c1cc440140251e38af40aa694e6d3965c31b36ade9deccde0ca403639031f44f42e395b575a125cd210fd54e9ac760af1ed72c7b91f8f771074f6cafe0d28ab840510ee98a46eb84225be218ff6f90d036f47ec2e7dbfa067e9498cc633e5cab354ab86013b4d8047312643cdfbb6b3654dc26a87af0f4d83b2b0c6ad28d026483788daeda241c8e2631311e0e0d48c6f9284904cc4df114336c207e4c4f468f80f82f2d6917d8ec6b9e63fa2a0f126f668f8220667c92d26d55b5da7a4144b8693c0dec479a3c63b1d43eb96868eac1cb786e2f4b327bad553fc9ffe2dada3ab11bd6b1d7a623a92e821192b0dbcdabf0e4c361561bb5abb970d11e477050d56957fc8961106d2aaf1f209cbdde733a7a6e0577fd35d32f048e887b0e92c9415871e5b0d7458fe682256494b6c9443d04a076842d56374ee4c184a5c64a71c6818eafaa6dcbd66aae917907080d4895b7b0c941a4fae00be891666c0bdeb8b9331d0ff61d7ec2c26b80156aa64263e925dc9d84279bdb1e27e0403b57c14a1b2647a98c858ee20c92b967fb1eb963147fe390958e7c914fce69e1e2eb06139279b70a8eeabe99500ddf04223c3343e5c9b2722635856c65593aae9d2dbf3da704f79e8145f008e
9b8f518b086098de3d77736f9458a3d2f6f95a37
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650
tJgqVBYK8iACgXDpES6chgsdiLTk4pCmM15TE0z3kgM=
syWhPUhrPj9a+Sk0yzwWVrNh+MlfsynriPZ0XF+UPwU=
49f946663a8deb7054212b8adda248c6
c56fb7d591ba6704df047fd98f535372fea00211
8a3c4b262d721acd49a4bf97d5213199c86fa2b9

POSSIBLE SECRETS
Wd8xe/qfTwq3ylFNd3IpaqLHZbh2ZNCLluVzmeNkcpw=
686479766013060971498190079908139321726943530014330540939446345918554318339765539424505774633321719753296399637136332111386476861244038034037280889270700544 9
a4b7452e2ed8f5f191058ca7bbfd26b0d3214bfc
3ps9rI142V56fUZ22VD6Aav/U6wPd6aBlBvFChUyHGs=
Rd5vBa3cRt13XnZUPrTszYMRTqEgpzuKs4niQNpf2R+gTE/2OPB9o8u+o5NCRvjl
c103703e120ae8cc73c9248622f3cd1e
FfddiHmPb383DV6rreW8JKkRsedppg8iNKEfTaDysv4=
r05ido8PpVZ2h2V1HWb8y18UjWvZxnyZOvYK4Y06JVkYZsi7FS/S9aZJacgWNWb+
3pegtvj7nkb7e3rwh5b+3dnQATJj6aqtaosJ3DkOYPzNGN2w+CoarbJEsY1UQgeA
Y/1pb58VeX4F8K6fayOs4meS93jwIQ+AMpk0KVFaduEwXDgWis9Z812p7+pIfyJn
9bH7YEZYe5itvs31c1gcj+rhSSdPNkSIQfDNYXo9ahs=
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
kd3av/xIh4WVmhBCVqo9sHJVJ1Nfp9EEBESbqmCB4V8=
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
7VR2YqvFgyvOhGA7139KYJuSHHdzdCxudZ7JSzwex/E=

POSSIBLE SECRETS
2OUUc7NT0WkEjmK9+FJMealFwLTaZNBfYG9mkUVQmhidcpLE5upPJKg2uqM0WUBe
lQFXQNWHSdYD6r5tE84uy22hnfx5d1uQHcaULCOPbM14F5cpADjDJSLZMM39MwXu
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
j+Yj7UMoEzr9M6nnqL4N+TgP7ihZaPMbtnYW3NPxsNU=
919afcc635fd11ea817c025656b09b22
BYT/lgG9eBlnAgDZzPD0oHgzdaaxxy72moL0pisX7NM=
uhLcqjqmx4nAmM3qRNIgYeeALxilkZ+lc3aGgO+rkRY=
470fa2b4ae81cd56ecbcda9735803434cec591fa
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
7e316c0a1665c11b439c50fb81744638
df6b721c8b4d3b6eb44c861d4415007e5a35fc95
0000016742C00BDA259000000168CE0F13200000016588840DCE7118A0002FBF1C31C3275D78
uUwZgwDOxcBXrQcntwu+kYFpkiVkOaezL0WYEZ3anJc=
cc2751449a350f668590264ed76692694a80308a
B3EEABB8EE11C2BE770B684D95219ECB
pORZNbNq0Oj61ZjvW9kWzatiK7LMxOR6JjGIN24dRVcLieCRVYuov8581WrmSeOY

POSSIBLE SECRETS
SJ3SRTdt7T2FQX1UH4DWlnlLfmao1u+KeMI8XtxEgmSHdfgiJRyy0Txw8FmQ+pQw
3noVyuO3zFOuhvGfjg9nuflidaw0HmgQ5EVdw6MbLqs=
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66
b8af70fd9fdad33866f205f20eefc404
gjATLq4PR4tBy0NKJBUs0hq7sitSgRlGcsdxPuImAoM=
DRYWi0TWx0xeQUvY98UNqkz37+DffrKoPBm+2dnlFUG6mCEAnCrfVx/sGMEehzhv
e3NEybi6UG3v8IfP2IiRsp6KKM0H99WDhy4AYfUmNolCq+mgpr0V0zn7xdgcLXPM
051953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00
WPHSlfekhaYlGJ3yiaIbiBY4HTx7YM9tPghNjV2alPYI+KXTjj+VnW7A1O7Euzu8
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5
89014bfa01a24259b961735ba5eda557
tm6XtP5M5qvCs+TffoCZhF/AF3Fx7Ow8iqgApPbgXSw=
cAajgxHlj7GTSEIzlYIQxmEloOSoJq7VOaxWHfv72QM=
115792089210356248762697446949407573530086143415290314195533631308867097853951
mfDIsnw62VUq5CrwQygwwDHX4oFb9NZomMa1Qv0blGOGPAtzm7d2+whMgYfVEkXw
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643

POSSIBLE SECRETS
ace60f6352f6dd9289843b5b0b2ab3d4
pJdDeMB2kv4XBHX5K3sZ2yiaFa+GF7/AJrrVARYf41I=
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057151
JbQbUG5JMJUoI6brnx0x3vZF6jilxsapbXGVfjhN8Fg=
zu6uZ8u7nNJHsIXbotuBCEBd9hieUh9UBKC94dMPsF422AtJb3FisPSqZI3W+06A
SgMhksOnpMJMBH1JH74BErFMAiPE78L9kUpiye6ezUkIKoc+RVuDLvEf36QK5tpM
B9q/kZ3M4smaULlSVckwEJdUNHNhTESXBf44c8ZRnHeQQYAcBESnaqAhjIPahrI0
Tx+r89A46YvA23pzmXogrUOA3X/vGVWSwDDb1CKb3SB+k9Zvmo8EcgSe2zWDveRy
3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
KF7kIGwoAULxxzCbY3v7c6qTHz0AzEhtAn+fEEmtiVY=
RLH60+LqkTN+fFoMkyZr3rdaQt8CbwdFGeiAHk8G/Y1GpQIgUmMEvr7Qzmd4S0T8
1OoeMBy/0f4cuo3Q6fO79anCMG2ySlElR0298tBh7pCa++J4MQSzo8NUX4DLdHow

POSSIBLE SECRETS
308203643082024ca0030201020204503fc625300d06092a864886f70d01010505003073310b3009060355040613027074311030 0e06035504081307556e6b6e6f776e310f300d060355040713064c6973626f6e3115301306035504 0a130c4361697861204d6167696361311030 0e060355040b13074170746f696465311830160603550403130f447561727465205369 6c766569726130820122300d06092a864886f70d01010105000382010f003082010a0282010100a7032cb40819b62cd596bc1c121951724e9a7d6612222d63dab58a18970339f77911b8e2a0665aa15efb051d4dd710c99e1fcaea006a651b7c113a71649c315e27122b9e0a214a240f34559394cca116c609d5bbf670ed85c7b983f0026154278bffd2b53d8aea4735ed99c39ea45db004c16bee078bb0b40e38ae510cacd1955a4e3eb90347d344cdcce07bddb89d9cd2077558914179a8157a87eac86e1b1a07a3f697a5f3f6512e276741d76bcc0c4809117c279fbd55d8c2b3d70468fbe4869394d9f2740bcccdf727da10c06de5c6a0d2f893bce078e058604726d32ab17e3b113a3dcbe0c22f2532738cae8cc5fa98c6b8306680b07ef8f0fca5d5910b0203010001300d06092a864886f70d01010505000382010100361152e42ece11bfd72e5795c9e91079b39c5280e30e3394671ca108fd7de9c3cebef2fc2f5ba752664ba44fcddaf49e91a1d7683cafdc11275fa7c1487ae78a659a8dae5d696cd93de810c67f127568dfa60c1962ec5ad2a3ea0560f75ad4a2ea9d388d4497b561242f090de2d3347dd32494ba6305735fa21d82f037f4355583fdfb1f46a56c19526969ba5f7f556cca9b9069cd9a9e3cd566d2b8c33138609e8794fb0abb11d33ed2c507f7f7df9ce24b3b64713ccdf2450bb5ec4efedba541dce271c8b3759b340b0467c06624cd3881b769a1d4a1b1fc0bec97d6b8561b032089ab8ca108595759bbd9b95fd43a3d28f518fb9d193125c8fa9b224f831c
jtcoe3puh462k3igthcrkmi918i30edh47c1tksma0pe1uqmuhc2o7i3g7ansalg
d37fe27d97b8305241dccf817ceb2c1d
WoiWRyIOVNa9ihaBciRSC7XHjliYS9VwUGOIud4PB18=
2438bce1ddb7bd026d5ff89f598b3b5e5bb824b3
RDFKlEPOT0aQT6ARmaMKbVy+V0L7x+JIeY4JSh39pzY=
AIzaSyDRKQ9d6kfsoZT2lUnZcZnBYvH69HExNPE
SVqWumuteCQHvVIaALrOZXuzVVVeS7f4FGxxu6V+es4=
115792089210356248762697446949407573529996955224135760342422259061068512044369
3jRp5GOI+HfffIZaNgs5urp4INMy6m1jZanprlp8fEbfjaITI/GTtSmO29P018Ft
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b

POSSIBLE SECRETS
IIJxA/RzEPbEgRJQH0LQ8KVHKqG3NyhvdpUemJxyiMg=
305bdd41-271f-4618-a1ea-0793da9e04ef
UZJDjsNp1+4M5x9cbbdflB779y5YRBcV6Z6rBMLIrO4=
258EAFA5-E914-47DA-95CA-C5AB0DC85B11

SCAN LOGS

Timestamp	Event	Error
2026-03-31 08:59:33	Generating Hashes	OK
2026-03-31 08:59:33	Extracting APK	OK
2026-03-31 08:59:33	Unzipping	OK
2026-03-31 08:59:35	Parsing APK with androguard	OK
2026-03-31 08:59:41	Extracting APK features using aapt/aapt2	OK

2026-03-31 08:59:42	Getting Hardcoded Certificates/Keystores	OK
2026-03-31 08:59:51	Parsing AndroidManifest.xml	OK
2026-03-31 08:59:51	Extracting Manifest Data	OK
2026-03-31 08:59:51	Manifest Analysis Started	OK
2026-03-31 08:59:51	Reading Network Security config from network_security_config.xml	OK
2026-03-31 08:59:51	Parsing Network Security config	OK
2026-03-31 08:59:51	Performing Static Analysis on: Aptoide (cm.aptoide.pt)	OK
2026-03-31 08:59:52	Fetching Details from Play Store: cm.aptoide.pt	OK
2026-03-31 08:59:53	Checking for Malware Permissions	OK
2026-03-31 08:59:54	Fetching icon path	OK
2026-03-31 08:59:54	Library Binary Analysis Started	OK

2026-03-31 08:59:54	Analyzing lib/armeabi-v7a/libsentry.so	OK
2026-03-31 08:59:54	Analyzing lib/armeabi-v7a/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing lib/arm64-v8a/libsentry.so	OK
2026-03-31 08:59:54	Analyzing lib/arm64-v8a/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing lib/x86/libsentry.so	OK
2026-03-31 08:59:54	Analyzing lib/x86/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing lib/x86_64/libsentry.so	OK
2026-03-31 08:59:54	Analyzing lib/x86_64/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/armeabi-v7a/libsentry.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/armeabi-v7a/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/arm64-v8a/libsentry.so	OK

2026-03-31 08:59:54	Analyzing apktool_out/lib/arm64-v8a/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/x86/libsentry.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/x86/libsentry-android.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/x86_64/libsentry.so	OK
2026-03-31 08:59:54	Analyzing apktool_out/lib/x86_64/libsentry-android.so	OK
2026-03-31 08:59:54	Reading Code Signing Certificate	OK
2026-03-31 08:59:55	Running APKiD 3.0.0	OK
2026-03-31 09:00:03	Detecting Trackers	OK
2026-03-31 09:00:07	Decompiling APK to Java with JADX	OK
2026-03-31 09:01:06	Converting DEX to Smali	OK
2026-03-31 09:01:06	Code Analysis Started on - java_source	OK

2026-03-31 09:01:24	Android SBOM Analysis Completed	OK
2026-03-31 09:01:34	Android SAST Completed	OK
2026-03-31 09:01:34	Android API Analysis Started	OK
2026-03-31 09:01:41	Android API Analysis Completed	OK
2026-03-31 09:01:41	Android Permission Mapping Started	OK
2026-03-31 09:01:49	Android Permission Mapping Completed	OK
2026-03-31 09:01:50	Android Behaviour Analysis Started	OK
2026-03-31 09:02:00	Android Behaviour Analysis Completed	OK
2026-03-31 09:02:00	Extracting Emails and URLs from Source Code	OK
2026-03-31 09:02:13	Email and URL Extraction Completed	OK
2026-03-31 09:02:13	Extracting String data from APK	OK

2026-03-31 09:02:14	Extracting String data from SO	OK
2026-03-31 09:02:14	Extracting String data from Code	OK
2026-03-31 09:02:14	Extracting String values and entropies from Code	OK
2026-03-31 09:02:28	Performing Malware check on extracted domains	OK
2026-03-31 09:02:43	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.