

Enter password: *****
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 11
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;

Database
information_schema
mysql
nsnstudentdb
performance_schema
sakila
studentdb
sys
world

8 rows in set (0.00 sec)

mysql> create database studenttttdb
-> ;

Query OK, 1 row affected (0.01 sec)

mysql> use studenttttdb
Database changed

mysql> CREATE TABLE Department (
-> dept_id INT PRIMARY KEY,
-> dept_name VARCHAR(100)
->);

Query OK, 0 rows affected (0.05 sec)

mysql> desc department;

Field	Type	Null	Key	Default	Extra
dept_id	int	NO	PRI	NULL	
dept_name	varchar(100)	YES		NULL	

2 rows in set (0.00 sec)

mysql> CREATE TABLE Employee (
-> emp_id INT PRIMARY KEY,

```
mysql> CREATE TABLE Employee (
->     emp_id INT PRIMARY KEY,
->     emp_name VARCHAR(20),
->     dept_id INT,
->     FOREIGN KEY (dept_id) REFERENCES Department(dept_id)
-> );
```

Query OK, 0 rows affected (0.05 sec)

```
mysql> INSERT INTO Department (dept_id, dept_name) VALUES
-> (1, 'HR'),
-> (2, 'Engineering'),
-> (3, 'Marketing');
```

Query OK, 3 rows affected (0.01 sec)

Records: 3 Duplicates: 0 Warnings: 0

```
mysql> INSERT INTO Employee (emp_id, emp_name, dept_id) VALUES
-> (101, 'Alice', 1),
-> (102, 'Bob', 2),
-> (103, 'Charlie', 2);
```

Query OK, 3 rows affected (0.01 sec)

Records: 3 Duplicates: 0 Warnings: 0

```
mysql> desc department;
```

Field	Type	Null	Key	Default	Extra
dept_id	int	NO	PRI	NULL	
dept_name	varchar(100)	YES		NULL	

2 rows in set (0.00 sec)

```
mysql> CREATE TABLE Employee (
->     emp_id INT PRIMARY KEY,
->     emp_name VARCHAR(20),
->     dept_id INT,
->     FOREIGN KEY (dept_id) REFERENCES Department(dept_id)
-> );
```

ERROR 1050 (42S01): Table 'employee' already exists

```
mysql> select * from department;
```

dept_id	dept_name
1	HR
2	Engineering
3	Marketing

3 rows in set (0.00 sec)

```
mysql> select * from employee;
```

emp_id	emp_name	dept_id
101	Alice	1
102	Bob	2
103	Charlie	2

```
rows in set (0.00 sec)
```

```
mysql> insert into department value(4,'sale');
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from department;
```

dept_id	dept_name
1	HR
2	Engineering
3	Marketing
4	sale

```
rows in set (0.00 sec)
```

```
mysql> insert into employee value(104,'jaya',4);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from employee;
```

emp_id	emp_name	dept_id
101	Alice	1
102	Bob	2
103	Charlie	2
104	jaya	4

```
rows in set (0.00 sec)
```

```
mysql> CREATE TABLE student5
-> (
-> ID int NOT NULL,
-> NAME varchar(10) NOT NULL,
-> AGE int NOT NULL , CHECK (AGE >= 18)
-> );
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> insert into student5 values (1004,'ramesh',20);
Query OK, 1 row affected (0.03 sec)
```

```
mysql> insert into student5 values(1003,'prakash',35);
```