



SIMATS Online Programming Lab
C PROGRAMMING

KAVIYAASRI M
1923126148B

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q1 Operators and Expressions 1 mark

A macro #define A 10+5 is used in an expression A*2 without parentheses. What will be the output?
#define A 10+5
printf("%d", A*2);

A. 30

B. 25

C. 40

D. Error

Save Answer

Next →



SIMATS Online Programming Lab
C PROGRAMMING

KAVIYAASRI M
1923126148B

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q2 Operators and Expressions 1 mark

A macro #define X 10 is defined, and later a variable with the same name int X = 5; is declared. What will happen when printing X?
#define X 10
int X = 5;
printf("%d", X);

A. 10


B. 5

C. Error

D. Garbage

Save Answer

Next →



SIMATS Online Programming Lab
C PROGRAMMING

KAVIYAASRI M
1923126148B

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q3 Operators and Expressions 1 mark

A constant variable is declared as "const int x = 10" and then reassigned using "x = x + 5". What will be the result?
const int x = 10;
x = x + 5;

A. 15

B. 10

C. Error

D. Garbage

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q4 Operators and Expressions

1 mark

A student divides an integer (5) by a float (2) and prints the result using %f. What will be the output?

```
int a = 5;  
float b = 2;  
printf("%f", a/b);
```

A. 2.5

B. 2

C. 0.2

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q5 Operators and Expressions

1 mark

A float variable is initialized as float x = 5/2 and then printed using %f. What will be the output?

```
float x = 5/2;  
printf("%f", x);
```

A. 2.5

B. 2

C. 5

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q6 Operators and Expressions

1 mark

A character variable is assigned the value 100 and printed using %c. What will be displayed?

```
char c = 100;  
printf("%c", c);
```

A. 100

B. d

C. Error

D. Garbage

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q7 Operators and Expressions

1 mark

A macro, A, is defined and then undefined using #undef. What will happen when attempting to print A?

```
#define A 5
#undef A
printf("%d", A);
```

A. 5

C. Error

D. Garbage

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q8 Operators and Expressions

1 mark

A variable is declared but not initialized, and then printed. What will be the output?

```
int a;
printf("%d", a);
```

Output?

B. Error

C. Garbage Value

D. 1

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q9 Operators and Expressions

1 mark

A character, 'A', is stored in a variable, and 1 is added to it before printing the result as an integer. What will be the output?

```
char a = 'A';
int b = a + 1;
printf("%d", b);
```

A. 66

B. 65

C. A

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q10 Operators and Expressions

1 mark

A macro #define B 2+3 is used in the expression B + 4. What will be the output?

```
#define B 2+3  
printf("%d", B+4);
```

A. 9

B. 10

C. 11

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q11 Operators and Expressions

1 mark

A macro #define X 3+2 is used in the expression X*X without parentheses. What will be the output?

```
#define X 3+2  
printf("%d", X*X);
```

A. 25

B. 11

C. 19

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1
Operators and Expressions
1 mark
- Q2
Operators and Expressions
1 mark
- Q3
Operators and Expressions
1 mark
- Q4
Operators and Expressions
1 mark
- Q5
Operators and Expressions
1 mark
- Q6
Operators and Expressions
1 mark

Q12 Operators and Expressions

1 mark

An integer is divided by a float and printed using %f. What will be the output of 10/3?

```
int a = 10;  
float b = 3;  
printf("%f", a/b);
```

A. 3.333333

B. 3

C. 3.01

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q13 Operators and Expressions

1 mark

A character 'A' is printed using %d. What will be the output?

```
char ch = 'A';  
printf("%d", ch);
```

A. A

B. 65

C. Error

D. Garbage

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q14 Operators and Expressions

1 mark

A programmer wants to display the octal equivalent of a decimal number stored as 25 using printf. Which output will the program produce?

A. 31

B. 25

C. 32

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ

← Back

QUESTIONS

- Q1 Operators and Expressions
1 mark
- Q2 Operators and Expressions
1 mark
- Q3 Operators and Expressions
1 mark
- Q4 Operators and Expressions
1 mark
- Q5 Operators and Expressions
1 mark
- Q6 Operators and Expressions
1 mark

Q15 Operators and Expressions

1 mark

A developer prints an integer value 26 using the %x format specifier. Considering lowercase hexadecimal representation in C, what will be the output?

```
int n = 26;  
printf("%x", n);
```

A. 1A

B. 1a

C. 26

D. Error

Save Answer

Next →

CO1 - Assessment Tools - 1 MCQ
[← Back](#)
QUESTIONS
Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q16 Operators and Expressions

1 mark

Nerd initializes a variable using 017 and prints it using %d. Since the value is stored in a different number system, what will be the resulting output?

```
int n = 017;
printf("%d", n);
```

A. 17

B. 15

C. 16

D. Error

[Save Answer](#)
[Next →](#)
CO1 - Assessment Tools - 1 MCQ
[← Back](#)
QUESTIONS
Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q17 Operators and Expressions

1 mark

A variable is assigned a hexadecimal constant 0xA5 and printed using %d. After decimal conversion, what value will be displayed?

```
int n = 0xA5;
printf("%d", n);
```

A. 155

B. 165

C. 150

D. Error

[Save Answer](#)
[Next →](#)
CO1 - Assessment Tools - 1 MCQ
[← Back](#)
QUESTIONS
Q1
Operators and Expressions
1 mark

Q2
Operators and Expressions
1 mark

Q3
Operators and Expressions
1 mark

Q4
Operators and Expressions
1 mark

Q5
Operators and Expressions
1 mark

Q6
Operators and Expressions
1 mark

Q18 Operators and Expressions

1 mark

Geek uses 010 as the value of an integer and prints it using %x. After converting the value appropriately, what will be the final output?

```
int n = 010;
printf("%x", n);
```

A. 8

B. A

C. 10

D. Error

[Save Answer](#)
[Next →](#)

CO1 - Assessment Tools - 1 MCQ

[← Back](#)

QUESTIONS

Q1
Operators and Expressions
1 markQ2
Operators and Expressions
1 markQ3
Operators and Expressions
1 markQ4
Operators and Expressions
1 markQ5
Operators and Expressions
1 markQ6
Operators and Expressions
1 mark

Q19 Operators and Expressions

1 mark

A technician adds a hexadecimal value 0x10 and an octal value 010, then prints the result using %d. What will be the output?

```
printf("%d", 0x10 + 010);
```

A. 24

B. 18

C. 20

D. 16

[Save Answer](#)[Next →](#)

CO1 - Assessment Tools - 1 MCQ

[← Back](#)

QUESTIONS

Q1
Operators and Expressions
1 markQ2
Operators and Expressions
1 markQ3
Operators and Expressions
1 markQ4
Operators and Expressions
1 markQ5
Operators and Expressions
1 markQ6
Operators and Expressions
1 mark

Q20 Operators and Expressions

1 mark

A variable with value 20 is printed using both %o and %x format specifiers in the same statement. What will be the output?

```
int n = 20;  
printf("%o %x", n, n);
```

A. 24 14

B. 20 20

C. 24 20

D. Error

[Save Answer](#)