



ASKEVA API

Documentation



Overview,

The Send Message API enables sending template-based messages to recipients via Askeva's messaging platform. The API uses pre-approved templates with customizable parameters to ensure consistency and compliance. Messages can include dynamic text and interactive buttons, making it a flexible solution for businesses looking to streamline customer interactions

End point,

POST : <https://backend.askeva.io/v1/message/send-message?token>

Components :

POST Method : This API requires a POST request to send data.

Base URL : <https://backend.askeva.io/v1/message/send-message> is the primary API endpoint.

Query Parameter (token) : The API requires an authentication token passed as a query parameter (?token=) to validate and authorize the request.

Headers

Key	Value	Required	Description
Content- Type	Application/json	Yes	Defines the request format

Request Body Parameters

Parameter	Type	Description
to	String	Recipient's phone number with Country Code (e.g., 9198765XXXXX)
type	String	Type of message (Set as "template").
template	Object	Contains template details
template.name	String	Name of the pre defined template
template.language	Object	Specifies the language policy and code.
template.language.policy	String	Language selection policy (e.g., deterministic)

template.language.code	String	Language code (e.g., en for English).
template.components	Array	Contains dynamic template parameters
template.components[].type	String	Component type (e.g., header, "body" for dynamic variable).
template.components[].parameters	Array	Array of dynamic parameters.
template.components[].parameters[]. type	String	Type of parameter (e.g., text, image, video, document)
template.components[].parameters[]. text	String	Value of the dynamic variable (Only for body type)
template.components[].parameters[]. image.link	String	URL of the image (for image templates)
template.components[].parameters[]. video.link	String	URL of the video (for video templates).
template.components[].parameters[]. document.link	String	URL of the document (for document templates)
template.components[].parameters[]. document.filename	String	Name of the document file (for document templates)

1.Text Template Message

This API allows sending WhatsApp messages via AskEVA's messaging platform for a text template.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>"  
  }  
}
```

2. Text template table with Variables

This API allowssending WhatsApp messages via AskEVA's messaging platform for a text with variable template.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "body",  
        "parameters": [  

```

```
{  
  "type": "text",  
  "text": "<VARIABLE-1>"  
},  
{  
  "type": "text",  
  "text": "<VARIABLE-2>"  
}  
]  
}  
]  
}  
}
```

3. Image Template

This API allowssending WhatsApp messages via AskEVA's messaging platform for an Image template.

Request Body

Request Body:

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "header",  
        "parameters": [  
          {  
            "type": "image",  
            "image": {  
              "link": "<IMAGE-LINK>"  
            }  
          }  
        ]  
      }  
    ]  
  }  
}
```



```
    }  
  ]  
}  
}
```

4. Image with variable template

This API allows sending WhatsApp messages via AskEVA's messaging platform for a Image with variable template.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "text",  
        "text": "Hello, my name is AskEVA!"  
      },  
      {  
        "type": "image",  
        "image": {  
          "url": "https://askeva.com/logo.png"  
        }  
      }  
    ]  
  }  
}
```

```
{  
  "type": "header",  
  "parameters": [  
    {  
      "type": "image",  
      "image": {  
        "link": "<IMAGE-LINK>"  
      }  
    }  
  ]  
},  
  
{  
  "type": "body",  
  "parameters": [  
    {  
      "type": "text",  
      "text": "<VARIABLE-1>"  
    }  
  ],  
}
```

```
{  
  "type": "text",  
  "text": "<VARIABLE-2>"  
}  
]  
}  
]  
}  
}
```

5. Video Template

This API allows sending WhatsApp messages via AskEVA's messaging platform for a Image with variable template.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "media": {  
      "type": "image",  
      "url": "<IMAGE-URL>"  
    }  
  }  
}
```

```
"name": "<TEMPLATE-NAME>",  
"components": [  
  {  
    "type": "header",  
    "parameters": [  
      {  
        "type": "video",  
        "video": {  
          "link": "<VIDEO-LINK>"  
        }  
      }  
    ]  
  }  
]
```

6. Video with Variable Template

This API allowssending WhatsApp messages via AskEVA's messaging platform for a video with variable template.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "header",  
        "parameters": [  
          {  
            "type": "video",  
            "video": {  
              "link": "<VIDEO-LINK>"  
            }  
          }  
        ]  
      }  
    ]  
  }  
}
```

```
    }
  }
]
},

{
  "type": "body",
  "parameters": [
    {
      "type": "text",
      "text": "<VARIABLE-1>"
    }
  ]
}
]
```

7. Document Template

This API allowssending WhatsApp messages via AskEVA's messaging platform for a Document template.

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "header",  
        "parameters": [  
          {  
            "type": "document",  
            "document": {  
              "link": "<DOCUMENT-LINK>",  
              "filename": "<DOCUMENT-NAME>"  
            }  
          }  
        ]  
      }  
    ]  
  }  
}
```

```
        }
      }
    ]
  }
]
}
```

8. Document with Variable Template

This API allows sending WhatsApp messages via AskEVA's messaging platform for a Document with variable template.

Request Body

```
{
  "to": "<RECIPIENT-NUMBER>",
  "type": "template",
  "template": {
    "language": {
      "policy": "deterministic",
      "code": "en"
    }
  }
}
```



```
"name": "<TEMPLATE-NAME>",  
"components": [  
  {  
    "type": "header",  
    "parameters": [  
      {  
        "type": "document",  
        "document": {  
          "link": "<DOCUMENT-LINK>",  
          "filename": "<DOCUMENT-NAME>"  
        }  
      }  
    ]  
  },  
  {  
    "type": "body",  
    "parameters": [  

```

```
{  
  "type": "text",  
  "text": "<VARIABLE-1>"  
}  
]  
}  
]  
}  
}
```

Notes :

- Replace <YOUR_TOKEN> with your authentication token.
- Replace <RECIPIENT-NUMBER> with the target user's phone number.
- Replace <TEMPLATE-NAME> with the actual template name configured in the system.
- Replace <IMAGE-LINK> or <VIDEO-LINK> or <DOCUMENT-LINK> with a valid media URL.
- Replace <DOCUMENT-NAME> for sending a document with required dynamic name.

- <VARIABLE-1>, <VARIABLE-2>, etc., represent dynamic text values to be inserted into the template.
- Multiple variables can be included in the parameters array as needed.

9. Carousel Templates

This API allows sending WhatsApp messages via AskEVA's messaging platform for a carousel type template.

Request Parameters :

Parameter	Type	Description
to	String	Recipient's phone number with Country Code (e.g., +91 98765XXXXX).
type	String	Message type, always set to template.
template.name	String	The name of the pre defined template.
template.language.code	String	The language code for the template (e.g., en for English).
template.language.policy	String	Defines the selection policy for the language, typically deterministic.

<code>template.components</code>	Array	The message components, including carousels and optional variables.
<code>template.components[].type</code>	String	Defines the type of component (carousel, body, etc.).
<code>template.components[].cards[]</code>	Array	The carousel cards.
<code>template.components[].cards[] .card_index</code>	Integer	The index of the carousel card.
<code>template.components[].cards[] .components[]</code>	Array	The elements inside a card, such as images.
<code>template.components[].cards[] .components[].type</code>	String	Defines the type of element (header, body, etc.).
<code>template.components[].cards[] .components[].parameters[]</code>	Array	Parameters inside the component.
<code>template.components[].cards[] .components[].parameters[].type</code>	String	Defines the type of parameter (image, video, etc. "text" for dynamic variable in body type only)
Defines the type of parameter (image, video, etc. "text" for dynamic variable in body type only).	String	The URL of the image or video.
<code>template.components[].parameters[]</code>	Array	Used for text variables in the message body.

9.1. Carousel without variables

This API allows sending WhatsApp messages via AskEVA's messaging platform for a carousel template without variable.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "carousel",  
        "cards": [  
          {  
            "type": "image",  
            "image": {  
              "url": "<IMAGE-URL>"  
            },  
            "caption": {  
              "text": "<CAPTION-TEXT>"  
            },  
            "title": {  
              "text": "<TITLE-TEXT>"  
            },  
            "description": {  
              "text": "<DESCRIPTION-TEXT>"  
            },  
            "button": {  
              "text": "<BUTTON-TEXT>"  
            },  
            "url": {  
              "url": "<BUTTON-URL>"  
            }  
          }  
        ]  
      }  
    ]  
  }  
}
```

```
{
  "card_index": 0,
  "components": [
    {
      "type": "header",
      "parameters": [
        {
          "type": "image",
          "image": {
            "link": "<IMAGE-OR-VIDEO-LINK>"
          }
        }
      ]
    }
  ],
  {
    "card_index": 1,
    "components": [
```

```
{  
  "type": "header",  
  "parameters": [  
    {  
      "type": "image",  
      "image": {  
        "link": "<IMAGE-OR-VIDEO-LINK>"  
      }  
    }  
  ]  
}
```

9.2. Carousel with variables

This API allowssending WhatsApp messages via AskEVA's messaging platform for a carousel template with body variables.

Request Body

```
{  
  "to": "<RECIPIENT-NUMBER>",  
  "type": "template",  
  "template": {  
    "language": {  
      "policy": "deterministic",  
      "code": "en"  
    },  
    "name": "<TEMPLATE-NAME>",  
    "components": [  
      {  
        "type": "carousel",  
        "cards": [  
          {  
            "type": "image",  
            "image": {  
              "url": "<IMAGE-URL>"  
            },  
            "caption": {  
              "text": "<CAPTION-TEXT>"  
            },  
            "description": {  
              "text": "<DESCRIPTION-TEXT>"  
            },  
            "cta": {  
              "text": "<CTA-TEXT>"  
            },  
            "url": {  
              "url": "<CTA-URL>"  
            }  
          },  
          {  
            "type": "text",  
            "text": "<TEXT-CONTENT>"  
          },  
          {  
            "type": "button",  
            "text": "<BUTTON-TEXT>",  
            "url": {  
              "url": "<BUTTON-URL>"  
            }  
          }  
        ]  
      }  
    ]  
  }  
}
```



```
{
  "card_index": 0,
  "components": [
    {
      "type": "header",
      "parameters": [
        {
          "type": "image",
          "image": {
            "link": "<IMAGE-OR-VIDEO-LINK>"
          }
        }
      ]
    }
  ]
},
{
  "card_index": 1,
  "components": [
    {
      "type": "header",
      "parameters": [
```

```
{  
  "type": "image",  
  "image": {  
    "link": "<IMAGE-OR-VIDEO-LINK>"  
  }  
}  
]  
}  
]
```

```
{  
  "type": "body",  
  "parameters": [  
    {  
      "type": "text",  
      "text": "<VARIABLE-1>"
```

```

    }
  ]
}
]
}
}

```

Notes :

- Ensure the recipient's phone number is in the correct international format.
- The template name should match an existing approved template.
- Images and videos must be hosted on a public accessible URL.
- The carousel component allows multiple cards, each with different images or content.
- <VARIABLE-1>, <VARIABLE-2>, etc., represent dynamic text values to be inserted into the template.
- Multiple variables can be included in the parameters array as needed.

10. Authentication Template

This API allowssending WhatsApp messages via AskEVA's messaging platform for a authentication template

Request Parameters :

Parameter	Type	Description
to	String	Recipient's phone number with Country Code (e.g., 9198765XXXXX)
type	String	Message type (should be "template").
template.name	String	Name of the template to be used.
template.language.policy	String	Language policy (e.g., "deterministic").
template.language.code	String	Language code (e.g., "en" for English).
template.components	Array	List of components used in the template.
template.components[].type	String	Type of component (e.g., "body" or "button").
template.components[].parameters[].type	String	Parameter type (e.g., "text").

template.components[].parameters[].text	String	Dynamic text to be included in the template.
template.components[].sub_type	String	Subtype of the button (e.g., "url").
template.components[].index	String	Index of the button in the template.

Request Body

The request body should be in JSON format.

```
{
  "to": "<RECIPIENT_NUMBER>",
  "type": "template",
  "template": {
    "language": {
      "policy": "deterministic",
      "code": "en"
    },
    "name": "<TEMPLATE_NAME>",
    "components": [
```

```
{  
  "type": "body",  
  "parameters": [  
    {  
      "type": "text",  
      "text": "<OTP_CODE>"  
    },  
    {  
      "type": "button",  
      "sub_type": "url",  
      "index": "0",  
      "parameters": [  
        {  
          "type": "text",  
          "text": "<OTP_CODE>"  
        }  
      ]  
    }  
  ]  
}
```

Notes :

- Replace <RECIPIENT_NUMBER> with the recipient's phone number.
- Replace <TEMPLATE_NAME> with the actual name of the template configured in the system.
- Replace <OTP_CODE> with the actual OTP or dynamic text.
- The token parameter must be provided in the query string for authentication.

Success Response :

```
{  
  "messaging_product": "whatsapp",  
  "contacts": [  
    {  
      "input": "9190424XXXXX",  
      "wa_id": "9190424XXXXX"  
    }  
  ],  
}
```

```
"messages":[
{
  "id": "wamid.HBgMOTe5MDQyNDk4MDI1FQIAERgSNkZBQjgx
M0RDNDUxQjYzQjg0AA=="
}
]
}
```

Sample Error Responses :

1. Invalid recipient numbers

```
{
  "error": "Invalid request: Number must start with 2-3 digit country
code and contain no spaces"
}
```

2. Invalid template

```
{
  "error": "Template not found"
}
```


3. Invalid language code

```
{  
  "message": "(#132001) Template name does not exist in  
the translation",  
  "code": 132001,  
  "type": "OAuthException",  
  "error_data": {  
    "messaging_product": "whatsapp",  
    "details": "template name (test56465) does not exist in ta"  
  }  
}
```

4. Invalid media link

```
{  
  "message": "(#100) Paramtemplate['components'][0]['parameters']  
[0]['image']['link'] is not a valid  
URI.",  
  "code": 100,  
  "type": "OAuthException"  
}
```

```
{  
  "message": "(#100) Paramtemplate['components'][0]['parameters']  
  [0]['image']['link'] is not a valid  
  URI.",  
  "code": 100,  
  "type": "OAuthException"  
}
```

5. Parameters i.e., variable count doesn't match

```
{  
  "message": "(#132000) Number of parameters does not match  
  the expected number of params",  
  "code": 132000,  
  "type": "OAuthException",  
  "error_data": {  
    "messaging_product": "whatsapp",  
    "details": "body: number of localizable_params (1) does not match  
    the expected number of params (2)"  
  }  
}
```