

INTER PROCESS COMMUNICATION(IPC):

INPUT AND OUTPUT:

```
kaviya@localhost -- bash

2. IPC Using Shared Memory - receiver.c
[kaviya@localhost ~]$ cat receiver.c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>
#define SharedMemSize 50
void main()
{
    int shmid;
    key_t key;
    char *shared_memory;
    key = 5677;
    if ((shmid = shmget(key, SharedMemSize, 0666)) < 0) {
        perror("shmget");
        exit(1);
    }
    (file continues...)

3. Compile and Run Shared Memory Program
[kaviya@localhost ~]$ gcc sender.c -o sender
[kaviya@localhost ~]$ gcc receiver.c -o receiver
[kaviya@localhost ~]$ ./receiver
Message Received: Welcome to Shared Memory
[kaviya@localhost ~]$ ./sender
[kaviya@localhost ~]$
```

```
kaviya@localhost: ~/bash

1. IPC Using Shared Memory - sender.c
[kaviya@localhost ~]$ cat sender.c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#define SharedMemSize 50
void main()
{
    char c;
    int shmid;
    key_t key;
    char *shared_memory;
    key = 5677;
    if ((shmid = shmget(key, SharedMemSize, IPC_CREAT |
0666)) < 0) {
        perror("shmget");
        (file continues...)
    }
}
```