

15B17CI371 – Data Structures Lab  
ODD 2024  
Week 6-LAB A  
Practice Lab - STL

1.

```
#include<iostream>
#include<vector>
using namespace std;
int main()
{
    vector<int>v1;
    cout<<"Enter the no of elements "<<endl;
    int n,k;
    cin>>n;
    cout<<"Enter elements:"<<endl;
    for(int i=0;i<n;i++)
    {
        cin>>k;v1.push_back(k);
    }
    cout<<"Original Vector:"<<endl;
    for(int i=0;i<n;i++)
    {
        cout<<v1[i]<<" ";
    }
    sort(v1.begin(),v1.end());
    cout<<endl<<"Sorted Vector:"<<endl;
    for(int i=0;i<n;i++)
    {
        cout<<v1[i]<<" ";
    }
    return 0;
}
```

```
Enter the no of elements
4
Enter elements:
0 -7 5 4
Original Vector:
0 -7 5 4
Sorted Vector:
-7 0 4 5 %
```

2.

a)

```
#include <iostream>
#include<vector>
#include <algorithm>

using namespace std;
int main() {
    int n,value;
    n=4;
    int arr[4];
    cout<<"Enter 4 elements:"<<endl;
    for(int i=0;i<4;i++)
    {
        cin>>arr[i];
    }
    cout<<"Enter element to get its frequency\n";
    cin>>value;
    int count = std::count(begin(arr), end(arr), value);

    cout << "Frequency of " << value << " is: " << count << endl;

    return 0;
}
```

```
Enter 4 elements:
9 7 9 4
Enter element to get its frequency
9
Frequency of 9 is: 2
```

```
b)
#include <iostream>
#include<vector>
#include <algorithm>

using namespace std;
int main() {
    vector<int>v1;
    cout<<"Enter the no of elements "<<endl;
    int n,k,value;
    cin>>n;
    cout<<"Enter elements:"<<endl;
    for(int i=0;i<n;i++)
    {
        cin>>k;v1.push_back(k);
    }
    cout<<"Original Vector:"<<endl;
    for(int i=0;i<n;i++)
    {
        cout<<v1[i]<<" ";
    }
    cout<<"\nEnter element to erase:\n";
    cin>>value;
    vector<int>::iterator it=find(v1.begin(),v1.end(),value);
    v1.erase(it);

    cout<<"Updated Vector:"<<endl;
    for(int i=0;i<n-1;i++)
    {
        cout<<v1[i]<<" ";
    }
}
```

}

```
Enter the no of elements
4
Enter elements:
4 7 0 1
Original Vector:
4 7 0 1
Enter element to erase:
0
Updated Vector:
4 7 1 %
```

c)

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```


```
int main() {
    vector<int>vec;
    cout<<"Enter the no of elements "<<endl;
    int n,k,value;
    cin>>n;
    cout<<"Enter elements:"<<endl;
    for(int i=0;i<n;i++)
    {
        cin>>k;vec.push_back(k);
    }
    cout<<"Original Vector:"<<endl;
    for(int i=0;i<n;i++)
    {
        cout<<vec[i]<<" ";
    }
}
```

```

for (int i = 0; i < vec.size(); ++i) {
    for (int j = i + 1; j < vec.size(); ++j) {
        if (vec[i] == vec[j]) {
            for (int k = j; k < vec.size() - 1; ++k) {
                vec[k] = vec[k + 1];
            }
            vec.resize(vec.size() - 1);
            --j;
        }
    }
}

cout << "\nVector after removing duplicates: ";
for(int i=0;i<(vec.size());i++)
{
    cout<<vec[i]<<" ";
}
return 0;
}

```



```

Enter the no of elements
6
Enter elements:
4 1 4 1 7
7
Original Vector:
4 1 4 1 7 7
Vector after removing duplicates: 4 1 7

```

d)

```

#include <iostream>
using namespace std;

int main() {
    int n,value;
    n=7;
    int arr[7];
    cout<<"Enter 7 elements:"<<endl;


```

```

for(int i=0;i<7;i++)
{
    cin>>arr[i];
}
int*ptr =max_element(begin(arr),end(arr));
cout<<endl<<distance(begin(arr),ptr);

return 0;
}


```



```

Enter 7 elements:
0 1 2 3 4 5 6
6%

```



```

Enter 7 elements:
6 5 4 3 2 1 0
0%

```

3.

```

#include <iostream>
#include <list>
using namespace std;
int main() {
list<int> lst;
lst.push_back(7);
lst.push_back(3);
lst.push_back(2);
lst.push_back(4);
lst.push_back(4);
cout << "original List:\n";

```

```

for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
cout << "First element: " << lst.front() << endl;
cout << "Last element: " << lst.back() << endl;
lst.push_back(6);
cout << "After adding 6 at the end: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
lst.pop_front();
cout << "After removing the first element: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
list<int>::iterator it = lst.begin();
advance(it, 1);
lst.insert(it, 10);
cout << "After inserting 10 at the 2nd position: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
cout << "Size of the list: " << lst.size() << endl;
lst.remove(3);
cout << "After removing all elements equal to 3: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
lst.reverse();
cout << "After reversing the list: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
lst.unique();
cout << "After removing consecutive duplicates: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
list<int> lst2;
lst2.push_back(7);
lst2.push_back(8);
lst2.push_back(9);
cout << "List 2:\n";
for (list<int>::iterator it = lst2.begin(); it != lst2.end(); ++it) cout << *it << " ";
cout << endl;
lst.swap(lst2);
cout << "After swapping with another list: ";
for (list<int>::iterator it = lst.begin(); it != lst.end(); ++it) cout << *it << " ";
cout << endl;
return 0;
}

```

```

originsl List:
7 3 2 4 4
First element: 7
Last element: 4
After adding 6 at the end: 7 3 2 4 4 6
After removing the first element: 3 2 4 4 6
After inserting 10 at the 2nd position: 3 10 2 4 4 6
Size of the list: 6
After removing all elements equal to 3: 10 2 4 4 6
After reversing the list: 6 4 4 2 10
After removing consecutive duplicates: 6 4 2 10
List 2:
7 8 9
After swapping with another list: 7 8 9
kavyamalik@Kavyas-Air-2 sem3.c % 

```

4.

```

#include <iostream>
#include <map>

```

```

using namespace std;

```

```

int main() {
    map<char, int> myMap;

```

```

    // Take initial map size input

```

```

    int n;

```

```

    cout << "Enter the number of elements to insert initially: ";

```

```

    cin >> n;

```

```

    // Take initial elements input

```

```

    for (int i = 0; i < n; ++i) {

```

```

        char key;

```



```

    int value;
    cout << "Enter key and value (e.g., a 1): ";
    cin >> key >> value;
    myMap[key] = value;
}

// a. Find the number of elements in the map
cout << "Number of elements in the map: " << myMap.size() << endl;

// b. Add a new element to the map
char newKey;
int newValue;
cout << "Enter new key and value to add (e.g., d 4): ";
cin >> newKey >> newValue;
myMap[newKey] = newValue;

// c. Remove the key-value pair with a specific key
char keyToRemove;
cout << "Enter key to remove: ";
cin >> keyToRemove;
myMap.erase(keyToRemove);

// Print the map to verify changes
cout << "Map contents:\n ";
map<char, int>::iterator it = myMap.begin();

while (it != myMap.end()) {
    cout << "Key: " << it->first
        << ", Value: " << it->second << endl;
    ++it;
}
cout << endl;

return 0;
}

```

```
Enter the number of elements to insert initially: 3
Enter key and value (e.g., a 1): c
1
Enter key and value (e.g., a 1): a 2
Enter key and value (e.g., a 1): t 3
Number of elements in the map: 3
Enter new key and value to add (e.g., d 4): c
4
Enter key to remove: c
Map contents:
  Key: a, Value: 2
  Key: t, Value: 3
```