

# Rajalakshmi Engineering College

Name: KAVYA SRIRAM

Email: 241901045@rajalakshmi.edu.in

Roll no: 241901045

Phone: 8939657782

Branch: REC

Department: I CSE (CS) FA

Batch: 2028

Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_PAH\_Updated

Attempt : 1

Total Mark : 50

Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

Viha, a software developer, is working on a project to automate searching for a target value in a Binary Search Tree (BST). She needs to create a program that takes an integer target value as input and determines if that value is present in the BST or not.

Write a program to assist Viha.

#### ***Input Format***

The first line of input consists of integers separated by spaces, which represent the elements to be inserted into the BST. The input is terminated by entering -1.

The second line consists of an integer target, which represents the target value to be searched in the BST.

### **Output Format**

If the target value is found in the BST, print "[target] is found in the BST".

Else, print "[target] is not found in the BST"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5 3 7 1 4 6 8 -1

4

Output: 4 is found in the BST

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int value;  
    struct Node* left;  
    struct Node* right;  
} Node;
```

```
Node* createNode(int value) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->value = value;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
Node* insert(Node* root, int value) {  
    if (root == NULL) return createNode(value);  
    if (value < root->value)  
        root->left = insert(root->left, value);  
    else  
        root->right = insert(root->right, value);  
    return root;  
}
```

```

int search(Node* root, int target) {
    if (root == NULL) return 0;
    if (root->value == target) return 1;
    if (target < root->value)
        return search(root->left, target);
    else
        return search(root->right, target);
}

int main() {
    Node* root = NULL;
    int val;
    while (1) {
        scanf("%d", &val);
        if (val == -1) break;
        root = insert(root, val);
    }
    int target;
    scanf("%d", &target);
    if (search(root, target))
        printf("%d is found in the BST", target);
    else
        printf("%d is not found in the BST", target);
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Aishu is participating in a coding challenge where she needs to reconstruct a Binary Search Tree (BST) from given preorder traversal data and then print the in-order traversal of the reconstructed BST.

Since Aishu is just learning about tree data structures, she needs your help to write a program that does this efficiently.

### Input Format

The first line consists of an integer  $n$ , representing the number of nodes in the BST.

The second line of input contains n integers separated by spaces, which represent the preorder traversal of the BST.

### **Output Format**

The output displays n space-separated integers, representing the in-order traversal of the reconstructed BST.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 6

10 5 1 7 40 50

Output: 1 5 7 10 40 50

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <limits.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
} Node;
```

```
Node* createNode(int val) {  
    Node* node = (Node*)malloc(sizeof(Node));  
    node->data = val;  
    node->left = node->right = NULL;  
    return node;  
}
```

```
Node* buildBST(int preorder[], int* index, int min, int max, int n) {  
    if (*index >= n) return NULL;  
    int val = preorder[*index];  
    if (val < min || val > max) return NULL;
```

```
    Node* root = createNode(val);
```

```

        (*index)++;
        root->left = buildBST(preorder, index, min, val - 1, n);
        root->right = buildBST(preorder, index, val + 1, max, n);
        return root;
    }

    void inorder(Node* root) {
        if (root == NULL) return;
        inorder(root->left);
        printf("%d ", root->data);
        inorder(root->right);
    }

    int main() {
        int n;
        scanf("%d", &n);
        int preorder[15];
        for (int i = 0; i < n; i++) {
            scanf("%d", &preorder[i]);
        }
        int index = 0;
        Node* root = buildBST(preorder, &index, INT_MIN, INT_MAX, n);
        inorder(root);
        return 0;
    }

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Joseph, a computer science student, is interested in understanding binary search trees (BST) and their node arrangements. He wants to create a program to explore BSTs by inserting elements into a tree and displaying the nodes using post-order traversal of the tree.

Write a program to help Joseph implement the program.

#### **Input Format**

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

### ***Output Format***

The output prints N space-separated integer values after the post-order traversal.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 4

10 15 5 3

Output: 3 5 15 10

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
} Node;
```

```
Node* createNode(int val) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->data = val;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
Node* insert(Node* root, int val) {  
    if (root == NULL) return createNode(val);  
    if (val < root->data)  
        root->left = insert(root->left, val);  
    else  
        root->right = insert(root->right, val);  
    return root;
```

```
}
```

```
void postOrder(Node* root) {  
    if (root == NULL) return;  
    postOrder(root->left);  
    postOrder(root->right);  
    printf("%d ", root->data);  
}
```

```
int main() {  
    int n;  
    scanf("%d", &n);  
    int val;  
    Node* root = NULL;  
    for (int i = 0; i < n; i++) {  
        scanf("%d", &val);  
        root = insert(root, val);  
    }  
    postOrder(root);  
    return 0;  
}
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Arun is exploring operations on binary search trees (BST). He wants to write a program with an unsorted distinct integer array that represents the BST keys and construct a height-balanced BST from it.

After constructing, he wants to perform the following operations that can alter the structure of the tree and traverse them using a level-order traversal:

InsertionDeletion

Your task is to assist Arun in completing the program without any errors.

#### **Input Format**

The first line of input consists of an integer N, representing the number of initial

keys in the BST.

The second line consists of N space-separated integers, representing the initial keys.

The third line consists of an integer X, representing the new key to be inserted into the BST.

The fourth line consists of an integer Y, representing the key to be deleted from the BST.

### ***Output Format***

The first line of output prints "Initial BST: " followed by a space-separated list of keys in the initial BST after constructing it in level order traversal.

The second line prints "BST after inserting a new node X: " followed by a space-separated list of keys in the BST after inserting X n level order traversal.

The third line prints "BST after deleting node Y: " followed by a space-separated list of keys in the BST after deleting Y n level order traversal.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5  
25 14 56 28 12  
34  
12

Output: Initial BST: 25 14 56 12 28  
BST after inserting a new node 34: 25 14 56 12 28 34  
BST after deleting node 12: 25 14 56 28 34

### ***Answer***

```
#include <stdio.h>
#include <stdlib.h>
```

```
typedef struct Node {
    int val;
    struct Node *left, *right;
```



```
} Node;
```

```
Node* newNode(int val) {  
    Node* node = (Node*)malloc(sizeof(Node));  
    node->val = val;  
    node->left = node->right = NULL;  
    return node;  
}
```

```
Node* insert(Node* root, int val) {  
    if (!root) return newNode(val);  
    if (val < root->val) root->left = insert(root->left, val);  
    else root->right = insert(root->right, val);  
    return root;  
}
```

```
Node* minValueNode(Node* node) {  
    while (node && node->left) node = node->left;  
    return node;  
}
```

```
Node* deleteNode(Node* root, int val) {  
    if (!root) return NULL;  
    if (val < root->val) root->left = deleteNode(root->left, val);  
    else if (val > root->val) root->right = deleteNode(root->right, val);  
    else {  
        if (!root->left) {  
            Node* temp = root->right;  
            free(root);  
            return temp;  
        } else if (!root->right) {  
            Node* temp = root->left;  
            free(root);  
            return temp;  
        }  
        Node* temp = minValueNode(root->right);  
        root->val = temp->val;  
        root->right = deleteNode(root->right, temp->val);  
    }  
    return root;  
}
```

```

void levelOrder(Node* root) {
    if (!root) return;
    Node* queue[100];
    int front = 0, rear = 0;
    queue[rear++] = root;
    while (front < rear) {
        Node* curr = queue[front++];
        printf("%d ", curr->val);
        if (curr->left) queue[rear++] = curr->left;
        if (curr->right) queue[rear++] = curr->right;
    }
}

```

```

int main() {
    int n, x, y, arr[15];
    scanf("%d", &n);
    for (int i = 0; i < n; i++) scanf("%d", &arr[i]);
    scanf("%d %d", &x, &y);

```

```

    Node* root = NULL;
    for (int i = 0; i < n; i++) {
        root = insert(root, arr[i]);
    }

```

```

    printf("Initial BST: ");
    levelOrder(root);

```

```

    root = insert(root, x);
    printf("\nBST after inserting a new node %d: ", x);
    levelOrder(root);

```

```

    root = deleteNode(root, y);
    printf("\nBST after deleting node %d: ", y);
    levelOrder(root);

```

```

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Yogi is working on a program to manage a binary search tree (BST) containing integer values. He wants to implement a function that removes nodes from the tree that fall outside a specified range defined by a minimum and maximum value.

Help Yogi by writing a function that achieves this.

### ***Input Format***

The first line of input consists of an integer N, representing the number of elements to be inserted into the BST.

The second line consists of N space-separated integers, representing the elements to be inserted into the BST.

The third line consists of two space-separated integers min and max, representing the minimum value and the maximum value of the range.

### ***Output Format***

The output prints the remaining elements of the BST in an in-order traversal, after removing nodes that fall outside the specified range.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5  
10 5 15 20 12  
5 15  
Output: 5 10 12 15

### ***Answer***

```
#include <stdio.h>
#include <stdlib.h>
```

```
typedef struct Node {
    int val;
    struct Node *left, *right;
} Node;
```

```
Node* newNode(int v) {
    Node* n = (Node*)malloc(sizeof(Node));
    n->val = v;
    n->left = n->right = NULL;
    return n;
}
```

```
Node* insert(Node* root, int v) {
    if (root == NULL) return newNode(v);
    if (v < root->val) root->left = insert(root->left, v);
    else root->right = insert(root->right, v);
    return root;
}
```

```
Node* removeOutsideRange(Node* root, int min, int max) {
    if (root == NULL) return NULL;
    root->left = removeOutsideRange(root->left, min, max);
    root->right = removeOutsideRange(root->right, min, max);
    if (root->val < min) {
        Node* r = root->right;
        free(root);
        return r;
    }
    if (root->val > max) {
        Node* l = root->left;
        free(root);
        return l;
    }
    return root;
}
```

```
void inorder(Node* root) {
    if (root == NULL) return;
    inorder(root->left);
    printf("%d ", root->val);
    inorder(root->right);
}
```

```
int main() {
    int n, min, max;
    scanf("%d", &n);
```

```
int arr[20];
for (int i = 0; i < n; i++) scanf("%d", &arr[i]);
scanf("%d %d", &min, &max);

Node* root = NULL;
for (int i = 0; i < n; i++) root = insert(root, arr[i]);

root = removeOutsideRange(root, min, max);
inorder(root);
return 0;
}
```

**Status :** Correct

**Marks : 10/10**