Assignment-2

Name: Manasa.R

Regno: 20BCE1055

Campus: Chennai

Question:

In Wokwi, connect a push button and upload 0/1 to ibm cloud

Code:


```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#define LED 2
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
#define ORG "4xs7sh"//IBM ORGANITION ID
#define DEVICE_TYPE "wokwi"//Device type mentioned in ibm watson IOT Platform
#define DEVICE ID "A1"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678"
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
```

```
void setup()// configureing the ESP32
 Serial.begin(115200);
 pinMode(18, INPUT);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
void loop()// Recursive Function
 int buttonstatus = digitalRead(18);
 Serial.println(buttonstatus);
 PublishData(buttonstatus);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
      .....retrieving to
Cloud....*/
void PublishData(int p) {
 mqttconnect();//function call for connecting to ibm
    creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"Push Button Status\":";
 payload += p;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
   Serial.println("Publish ok");// if it sucessfully upload data on the cloud
then it will print publish ok in Serial monitor or else it will print publish
failed
 } else {
   Serial.println("Publish failed");
```

```
void mqttconnect() {
 if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
     initManagedDevice();
     Serial.println();
 }
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
 while (WiFi.status() != WL_CONNECTED) {
   delay(500);
    Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
 } else {
    Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {</pre>
   //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
```

```
}
Serial.println("data: "+ data3);
data3="";
}
```

Circuit:



Output:

```
Publish ok

1


Sending payload: {"Push Button Status":1}

Publish ok

0

Sending payload: {"Push Button Status":0}

Publish ok
```



Wokwi link:

https://wokwi.com/projects/366158491024057345