

Skill - Week6

Session 11:

1. To Store Commands, Maintain History Buffer, Handle Capacity Limits, Retrieve Entries, Display History, Validate Consistency.

```
#include <stdio.h>
#include <string.h>
#define MAX_HISTORY 5
#define MAX_COMMAND 100
char history[MAX_HISTORY][MAX_COMMAND];
int count = 0;
int next = 0;
/* Store a command */
void store_command(char *cmd) {
    strncpy(history[next], cmd, MAX_COMMAND - 1);
    history[next][MAX_COMMAND - 1] = '\0';
    next = (next + 1) % MAX_HISTORY;
    if (count < MAX_HISTORY)
        count++;
}
/* Retrieve a command */
void retrieve_command(int index) {
    if (index < 1 || index > count) {
        printf("Invalid history index\n");
        return;
    }
    int start = (next - count + MAX_HISTORY)
               % MAX_HISTORY;
    int position = (start + index - 1) % MAX_HISTORY;
    printf("Command %d: %s", index, history[position]);
}
/* Display history */
void display_history() {
    if (count == 0) {
        printf("History is empty\n");
        return;
    }
    int start = (next - count + MAX_HISTORY)
               % MAX_HISTORY;
    for (int i = 0; i < count; i++) {
        int position = (start + i) % MAX_HISTORY;
        printf("%d: %s", i + 1, history[position]);
    }
}
```

```
kavya_aluru@Pandu:~$ cd OS_Lab
kavya_aluru@Pandu:~/OS_Lab$ nano command_history.c
kavya_aluru@Pandu:~/OS_Lab$ gcc command_history.c -o command_history
kavya_aluru@Pandu:~/OS_Lab$ ./command_history

--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
Enter choice: 1
Enter command: ls
Command stored successfully

--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
Enter choice: 1
Enter command: pwd
Command stored successfully

--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
Enter choice: 3
1: ls
2: pwd

--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
```

```
--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
Enter choice: 2
Enter index: 2
Command 2: pwd

--- Command History ---
1. Store Command
2. Retrieve Entry
3. Display History
4. Validate Consistency
5. Exit
Enter choice: 5
kavya_aluru@Pandu:~/OS_Lab$ |
```

Report: The program stores commands in a fixed-size history buffer. A circular buffer handles capacity limits by overwriting the oldest entries. Users can retrieve specific commands, display the complete history, and validate the buffer's consistency.

2. To Create Pipeline Structures, Store Commands, Maintain Execution Order, Connect Processes, Validate Pipeline Layout, Test Configurations

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/wait.h>
#define MAX_COMMANDS 5
#define MAX_ARGS 10
#define MAX_LENGTH 100
typedef struct {
    char command[MAX_LENGTH];
} Command;
typedef struct {
    Command commands[MAX_COMMANDS];
    int count;
} Pipeline;
/* Initialize pipeline */
void init_pipeline(Pipeline *p) {
    p->count = 0;
}
/* Store command */
void store_command(Pipeline *p, char *cmd) {
    if (p->count >= MAX_COMMANDS) {
        printf("Error: Pipeline capacity exceeded\n");
        return;
    }
    strcpy(p->commands[p->count].command, cmd);
    p->count++;
    printf("Command stored successfully\n");
}
/* Display pipeline */
void display_pipeline(Pipeline *p) {
    printf("\nPipeline Layout:\n");
    for (int i = 0; i < p->count; i++) {
        printf("%d: %s\n", i + 1,
            p->commands[i].command);
    }
}
```

^G Help ^O Write Out ^E Where Is ^K Cut

```
kavya_aluru@Pandu:~/OS_Lab$ nano pipeline.c
kavya_aluru@Pandu:~/OS_Lab$ gcc pipeline.c -o pipeline
kavya_aluru@Pandu:~/OS_Lab$ ./pipeline
```

```
--- Pipeline Manager ---
```

1. Store Command
2. Display Pipeline
3. Validate Pipeline
4. Execute Pipeline
5. Exit

Enter choice: 1

Enter command: grep

Command stored successfully

```
--- Pipeline Manager ---
```

1. Store Command
2. Display Pipeline
3. Validate Pipeline
4. Execute Pipeline
5. Exit

Enter choice: 1

Enter command: ls

Command stored successfully

```
--- Pipeline Manager ---
```

1. Store Command
2. Display Pipeline
3. Validate Pipeline
4. Execute Pipeline
5. Exit

Enter choice: 2

Pipeline Layout:

1: grep

2: ls

```
--- Pipeline Manager ---
1. Store Command
2. Display Pipeline
3. Validate Pipeline
4. Execute Pipeline
5. Exit
Enter choice: 3
Pipeline layout is valid

--- Pipeline Manager ---
1. Store Command
2. Display Pipeline
3. Validate Pipeline
4. Execute Pipeline
5. Exit
Enter choice: 5
kavya_aluru@Pandu:~/OS_Lab$ ls | grep .c
builtin.c
command_history.c
export_env.c
fifo_client
fifo_client.c
fifo_client_auto
fifo_client_auto.c
fifo_server.c
fork_example.c
fork_example.c.save
pipeline.c
shell_dispatch
shell_dispatch.c
signal_handler.c
state_management.c
```

Report: The program creates a pipeline structure to store commands in order. It validates the number of commands and uses Linux system calls such as pipe(), fork(), dup2(), and waitpid() to connect processes and execute commands.

Session 12:

1. To Create Pipes, Redirect Streams, Execute Connected Commands, Close Descriptors, Synchronize Processes, Test Data Flow

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>
int main() {
    int fd[2];
    pid_t pid1, pid2;
    /* Create pipe */
    if (pipe(fd) == -1) {
        perror("pipe");
        exit(1);
    }
    printf("Pipe created successfully\n");
    /* First child process */
    pid1 = fork();
    if (pid1 == -1) {
        perror("fork");
        exit(1);
    }
    if (pid1 == 0) {
        /* Redirect stdout to pipe */
        dup2(fd[1], STDOUT_FILENO);
        /* Close unused descriptors */
        close(fd[0]);
        close(fd[1]);
        /* Execute first command */
        execlp("ls", "ls", NULL);
        perror("execlp");
        exit(1);
    }
    /* Second child process */
    pid2 = fork();
    if (pid2 == -1) {
        perror("fork");
        exit(1);
    }
}
```

```

kavya_aluru@Pandu:~/OS_Lab$ nano pipe_demo.c
kavya_aluru@Pandu:~/OS_Lab$ gcc pipe_demo.c -o pipe_demo
kavya_aluru@Pandu:~/OS_Lab$ ./pipe_demo
Pipe created successfully
24
Both processes completed
kavya_aluru@Pandu:~/OS_Lab$ ls | grep .c | wc -l
16
kavya_aluru@Pandu:~/OS_Lab$ ls | wc -l
24

```

Result: The pipe was created successfully. The output of ls was redirected to wc -l, and both child processes completed successfully. Data flow was verified using Linux pipeline commands.

2. To Support Multiple Pipes, Manage Descriptor Arrays, Launch Multiple Processes, Coordinate Execution, Cleanup Resources, Test Long Pipelines

```

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>
#define MAX_COMMANDS 5
int main() {
    /* Commands in execution order */
    char *commands[MAX_COMMANDS][4] = {
        {"ls", NULL, NULL, NULL},
        {"grep", ".c", NULL, NULL},
        {"wc", "-l", NULL, NULL}
    };
    int n = 3;
    /* Descriptor array */
    int pipes[MAX_COMMANDS - 1][2];
    pid_t pids[MAX_COMMANDS];
    /* Create multiple pipes */
    for (int i = 0; i < n - 1; i++) {
        if (pipe(pipes[i]) == -1) {
            perror("pipe");
            exit(1);
        }
        printf("Pipe %d created\n", i + 1);
    }
    /* Launch multiple processes */
    for (int i = 0; i < n; i++) {
        pids[i] = fork();
        if (pids[i] == -1) {
            perror("fork");
            exit(1);
        }
        if (pids[i] == 0) {
            /* Redirect input from previous pipe */
            if (i > 0) {
                dup2(pipes[i - 1][0], STDIN_FILENO);
            }
            /* Redirect output to next pipe */

```

```
kavya_aluru@Pandu:~/OS_Lab$ nano multi_pipe.c
kavya_aluru@Pandu:~/OS_Lab$ gcc multi_pipe.c -o multi_pipe
kavya_aluru@Pandu:~/OS_Lab$ ./multi_pipe
Pipe 1 created
Pipe 2 created
17

All processes completed
All pipe descriptors closed
```

```
kavya_aluru@Pandu:~/OS_Lab$ ls | grep .c | wc -l
18
kavya_aluru@Pandu:~/OS_Lab$ ls | grep .c | sort | wc -l
18
kavya_aluru@Pandu:~/OS_Lab$ ls | grep .c | sort | head -n 5 | wc -l
5
```

Report: The program supports multiple pipes by using a two-dimensional descriptor array. It launches one child process for each command, redirects input and output using `dup2()`, executes commands using `execvp()`, closes unused descriptors, and synchronizes all processes using `waitpid()`. Multiple pipeline configurations are tested to verify data flow and resource cleanup.