Feedback, Clarification & Messaging


Week 7 implementation review | existing endpoint repair, role-aware correspondence, responsive UI

249 FINAL CHECKS PASSED


0 FINAL FAILURES

6 LIVE READ-ONLY QUERIES
Employee / Owner / Admin

THE TRANSFORMATION



BEFORE / INACCESSIBLE REGISTER
Authentication-required state; messaging not accessible.



AFTER / THREE-PANEL MESSAGING
Policy context, conversations, owner routing and replies.

IMPLEMENTED WORKFLOW


Policy Assistant answer -> employee clarification -> owner assignment and in-app alert -> two-way replies -> resolve / close -> employee reopen; unassigned requests enter administrator triage.

SCOPE & EVIDENCE NOTE

OpenCode/Codex continued the existing implementation. Final automated workflows used isolated SQLite illustrative records; six actual Supabase list/notification queries were read-only. No live records, Auth users, RLS policies or database migrations were changed during this verification.


From clarification to resolution

Screenshots below are explicitly labelled LOCAL FIXTURE. They demonstrate behavior, not live Supabase writes.




01 / EMPLOYEE INBOX

My requests, status indicators and thread discovery.




02 / OWNER NOTIFICATION

Assignment arrives as an in-app alert.



03 / OWNER REPLY & RESOLUTION

Stored response and resolved-state controls.




04 / EMPLOYEE REOPEN


History retained; request returns to awaiting owner.

Access, adaptability & validation


Role-scoped oversight and a transparent account of verified versus pending production controls.



05 / ADMIN OVERSIGHT



06 / MOBILE 390 PX



07 / ACCESS DENIED

VERIFICATION MATRIX

Messaging workflow	73 / 73	Authorization & notifications	29 / 29	JWT verification	24 / 24
Pulse regression	97 / 97	Chrome / responsive	26 / 26		

ENCRYPTION & DEPLOYMENT

Verified: TLS 1.3 (AES-256-GCM) between application client and Supabase pooler. The observed pooler-to-Postgres backend reports no TLS; internal protection remains unverified. Production HTTPS, hostname checks, disk/backup encryption, production sign-in and direct-client RLS were not verified. Message content is not end-to-end encrypted.

DOCUMENTATION STATUS

Original Week 7 SQL migration / rollback and auth proposal remain unexecuted design artifacts, not proof of deployed RLS. Current messaging permissions were exercised via backend and isolated fixtures. Development/test scope: COMPLETE; production readiness: OUTSTANDING.

Evidence register & security boundaries

Diagnostic screenshot reproduced from read-only verification, paired with test methodology and release notes.



08 / ACTUAL TLS DIAGNOSTICS

WHAT WAS VERIFIED

- Scoped thread access; 401/403/404 enforcement; admin triage.
- Sender attribution, reassignment alerts and unread totals.
- Browser layout at 1440, 1280, 1024, 820 and 390 px.
- JWT invalid-signature, issuer, audience and expiry rejection.
- Read-only PostgreSQL queries for all three user roles.

KNOWN LIMITATIONS

- Fixtures are illustrative, not production account activity.
- No new writes or live migration/RLS tests were performed.
- Browser-to-server production TLS and internal DB transport are unverified.
- Policy creation/version authorization remains a separate gap.
- No E2E or field-level message encryption is claimed.

DELIVERY ASSESSMENT

Week 7 - Feedback & Messaging: functionally complete in development/test scope. The 249 passing automated checks and six read-only DB validations support the demonstrated features; they do not certify a production deployment or application-wide regulatory compliance.

Evidence basis: supplied Week 7 README, OpenAPI schema, verification logs, browser-results.json, read-only TLS diagnostics, proposed migration/rollback/verification documents, and the user-provided before/after and fixture screenshots.