

Machine-Level Programming II: Control

Kai Zhang
Fudan University
zhangk@fudan.edu.cn

Today

- **Control: Condition codes**
- Conditional branches
- Loops
- Switch Statements

Processor State (x86-64, Partial)

■ Information about currently executing program

- Temporary data (`%rax`, ...)
- Location of runtime stack (`%rsp`)
- Location of current code control point (`%rip`, ...)
- Status of recent tests (CF, ZF, SF, OF)

Current stack top

Registers

<code>%rax</code>	<code>%r8</code>
<code>%rbx</code>	<code>%r9</code>
<code>%rcx</code>	<code>%r10</code>
<code>%rdx</code>	<code>%r11</code>
<code>%rsi</code>	<code>%r12</code>
<code>%rdi</code>	<code>%r13</code>
<code>%rsp</code>	<code>%r14</code>
<code>%rbp</code>	<code>%r15</code>

`%rip`

Instruction pointer

CF

ZF

SF

OF

Condition codes

Condition Codes (Implicit Setting)

■ Single bit registers (P135)

- CF Carry Flag (for **unsigned**) SF Sign Flag (for **signed**)
- ZF Zero Flag OF Overflow Flag (for **signed**)

■ Implicitly set (as side effect) of arithmetic operations

Example: **addq Src,Dest** \leftrightarrow $t = a+b$

CF set if carry/borrow out from the most significant bit (unsigned overflow)

ZF set if $t == 0$

SF set if $t < 0$ (as signed, 最近的操作得到的结果为负数)

OF set if two's-complement (signed) overflow


$(a>0 \ \&\& \ b>0 \ \&\& \ t<0) \ || \ (a<0 \ \&\& \ b<0 \ \&\& \ t>=0)$

■ Not set by **leaq** instruction, since it is used to calculate address

ZF set when

00000000000...00000000000

SF set when




For [signed](#) arithmetic, this reports when result is a [negative](#) number

CF set when



For **unsigned** arithmetic, this reports **overflow**

OF set when



$$z = \sim y$$

($a > 0$ $\&\&$ $b > 0$ $\&\&$ $t < 0$) $\|$ ($a < 0$ $\&\&$ $b < 0$ $\&\&$ $t \geq 0$)

For **signed** arithmetic, this reports **overflow**

Condition Codes (Explicit Setting: Compare)

■ Explicit Setting by Compare Instruction

- **cmpq** Src2, Src1
 - **cmpq b, a** like computing **a-b** without setting destination
-
- **CF set** if carry/borrow out from most significant bit
(used for unsigned comparisons)
 - **ZF set** if **a == b**
 - **SF set** if **(a-b) < 0** (as signed)
 - **OF set** if two's-complement (signed) overflow
$$(a>0 \ \&\& \ b<0 \ \&\& \ (a-b)<0) \ \|\ (a<0 \ \&\& \ b>0 \ \&\& \ (a-b)>0)$$

Condition Codes (Explicit Setting: Test)

■ Explicit Setting by Test instruction

- `testq Src2, Src1`
 - `testq b, a` like computing `a&b` without setting destination
- Sets condition codes based on value of Src1 & Src2
- Useful to have one of the operands be a mask
- ZF set when `a&b == 0`
- SF set when `a&b < 0`

Very often:

`testq %rax,%rax`

Test if rax stores 0, positive or negative
`zf = 1; sf = 0; sf = 1`

Condition Codes (Explicit Reading: Set)

■ Explicit Reading by Set Instructions

- **setX** Dest: Set low-order byte of destination Dest to 0 or 1 based on combinations of condition codes
- Does not alter remaining 7 bytes of Dest

SetX	Condition	Description
sete	ZF	Equal / Zero
setne	~ZF	Not Equal / Not Zero
sets	SF	Negative
setns	~SF	Nonnegative
setg	~(SF^OF) & ~ZF	Greater (signed)
setge	~(SF^OF)	Greater or Equal (signed)
setl	SF^OF	Less (signed)
setle	(SF^OF) ZF	Less or Equal (signed)
seta	~CF & ~ZF	Above (unsigned)
setb	CF	Below (unsigned)

x86-64 Integer Registers

%rax	%al	%r8	%r8b
%rbx	%bl	%r9	%r9b
%rcx	%cl	%r10	%r10b
%rdx	%dl	%r11	%r11b
%rsi	%sil	%r12	%r12b
%rdi	%dil	%r13	%r13b
%rsp	%spl	%r14	%r14b
%rbp	%bpl	%r15	%r15b

- Can reference low-order byte

Explicit Reading Condition Codes (Cont.)

■ SetX Instructions:

- Set single byte based on combination of condition codes

■ One of addressable byte registers

- Does not alter remaining bytes
- Typically use `movzbl` to finish job (P123, 将零扩展的字节传送到双字)
 - 32-bit instructions also set upper 32 bits to 0

```
int gt (long x, long y)
{
    return x > y;
}
```


Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

```
cmpq %rsi, %rdi      # Compare x:y
setg %al               # Set when >
movzbl %al, %eax      # Zero rest of %rax
ret
```

Explicit Reading Condition Codes (Cont.)

Beware weirdness **movzbl** (and others)

movzbl %al, %eax



Zapped to all 0's

Use(s)

Argument x

Argument y

Return value

```
cmpq    %rsi, %rdi    # Compare x:y
setg    %al             # Set when >
movzbl %al, %eax      # Zero rest of %rax
ret
```

Exercise

cmpq b, a like computing $a - b$ w/o setting dest

- **CF set** if carry/borrow out from most significant bit (used for unsigned comparisons)
- **ZF set** if $a == b$
- **SF set** if $(a - b) < 0$ (as signed)
- **OF set** if two's-complement (signed) overflow

SetX	Condition	Description
sete	ZF	Equal / Zero
setne	$\sim ZF$	Not Equal / Not Zero
sets	SF	Negative
setns	$\sim SF$	Nonnegative
setg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (signed)
setge	$\sim (SF \wedge OF)$	Greater or Equal (signed)
setl	SF \wedge OF	Less (signed)
setle	$(SF \wedge OF) \mid ZF$	Less or Equal (signed)
seta	$\sim CF \& \sim ZF$	Above (unsigned)
setb	CF	Below (unsigned)

xorq	%rax, %rax
subq	\$1, %rax
cmpq	\$2, %rax
setl	%al
movzblq	%al, %eax

%rax	SF	CF	OF	ZF

Note: **setl** and **movzblq** do not modify condition codes

Quiz Time!

Exercise 3.13, 3.14

Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements

Jumping

■ jX Instructions

- Jump to different part of code depending on condition codes
- Implicit reading of condition codes

jX	Condition	Description
<code>jmp</code>	<code>1</code>	Unconditional
<code>je</code>	<code>ZF</code>	Equal / Zero
<code>jne</code>	<code>~ZF</code>	Not Equal / Not Zero
<code>js</code>	<code>SF</code>	Negative
<code>jns</code>	<code>~SF</code>	Nonnegative
<code>jg</code>	<code>~(SF^OF) & ~ZF</code>	Greater (signed)
<code>jge</code>	<code>~(SF^OF)</code>	Greater or Equal (signed)
<code>jl</code>	<code>SF^OF</code>	Less (signed)
<code>jle</code>	<code>(SF^OF) ZF</code>	Less or Equal (signed)
<code>ja</code>	<code>~CF & ~ZF</code>	Above (unsigned)
<code>jb</code>	<code>CF</code>	Below (unsigned)

Conditional Branch Example (Old Style)

■ Generation

```
shark> gcc -Og -S -fno-if-conversion control.c
```

Get to this shortly

```
long absdiff
(long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
absdiff:
    cmpq    %rsi, %rdi    # x:y
    jle     .L4
    movq    %rdi, %rax
    subq    %rsi, %rax
    ret
.L4:      # x <= y
    movq    %rsi, %rax
    subq    %rdi, %rax
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

Expressing with Goto Code

- C allows **goto** statement
- Jump to position designated by label

```
long absdiff
  (long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j
  (long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

General Conditional Expression Translation (Using Branches)

C Code

```
val = Test ? Then_Expr : Else_Expr;
```

```
val = x>y ? x-y : y-x;
```

Goto Version

```
if (!Test) goto Else;
val = Then_Expr;
goto Done;
Else:
    val = Else_Expr;
Done:
    . . .
```

- Create separate code regions for then & else expressions
- Execute appropriate one

Quiz Time!

Exercise 3.16

Using Conditional Moves

■ Conditional Move Instructions (P147)

- Instruction supports:
if (Test) Dest \leftarrow Src
- Supported in post-1995 x86 processors
- GCC tries to use them
 - But, only when known to be safe

■ Why?

- Branches are very disruptive to instruction flow through pipelines (P146)
- Conditional moves do not require control transfer

C Code

```
val = Test  
? Then_Expr  
: Else_Expr;
```

Goto Version

```
result = Then_Expr;  
eval = Else_Expr;  
nt = !Test;  
if (nt) result = eval;  
return result;
```

Conditional Move Example

```
long absdiff
    (long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

When is
this bad?

```
absdiff:
    movq    %rdi, %rax    # x
    subq    %rsi, %rax    # result = x-y
    movq    %rsi, %rdx
    subq    %rdi, %rdx    # eval = y-x
    cmpq    %rsi, %rdi    # x:y
    cmovle %rdx, %rax    # if <=, result = eval
    ret
```

Bad Cases for Conditional Move

Expensive Computations

```
val = Test(x) ? Hard1(x) : Hard2(x);
```

- Both values get computed
- Only makes sense when computations are very simple

Bad Performance

Risky Computations

```
val = p ? *p : 0;
```

- Both values get computed, what if p is NULL
- May have undesirable effects

Unsafe

Computations with side effects

```
val = x > 0 ? x*=7 : x+=3;
```

- Both values get computed
- Must be side-effect free

Illegal

Quiz Time!

Exercise 3.20, 3.21

Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements

“Do-While” Loop Example

C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

- Count number of 1's in argument x (“popcount”)
- Use conditional branch to either continue looping or to exit loop

“Do-While” Loop Compilation

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

```
        movl    $0, %eax      #   result = 0
.L2:                                # loop:
        movq    %rdi, %rdx
        andl    $1, %edx      #   t = x & 0x1
        addq    %rdx, %rax    #   result += t
        shrq    %rdi          #   x >>= 1
        jne     .L2          #   if(x) goto loop
        rep; ret
```

General “Do-While” Translation

C Code

```
do  
  Body  
  while (Test);
```

Goto Version

```
loop:  
  Body  
  if (Test)  
    goto loop
```

- **Body:** {
 Statement₁;
 Statement₂;
 ...
 Statement_n;
}

General “While” Translation #1

- “Jump-to-middle” translation
- Used with -Og

While version

```
while (Test)
    Body
```



Goto Version

```
goto test;
loop:
    Body
test:
    if (Test)
        goto loop;
done:
```

While Loop Example #1

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```

- Compare to do-while version of function
- Initial goto starts loop at test

Quiz Time!

Exercise 3.24

General “While” Translation #2

While version

```
while (Test)
  Body
```

- “Do-while” conversion
- Used with `-O1`

Do-While Version

```
if (!Test)
  goto done;
do
  Body
  while(Test);
done:
```

Goto Version

```
if (!Test)
  goto done;
loop:
  Body
  if (Test)
    goto loop;
done:
```

While Loop Example #2

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Do-While Version

```
long pcount_goto_dw
(unsigned long x) {
    long result = 0;
    if (!x) goto done;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
done:
    return result;
}
```

- Initial conditional **guards entrance to loop**
- Compare to do-while version of function

Quiz Time!

Exercise 3.25

“For” Loop Form

General Form

```
for (Init; Test; Update )  
    Body
```

```
#define WSIZE 8*sizeof(int)  
long pcount_for  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    for (i = 0; i < WSIZE; i++)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
    }  
    return result;  
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

“For” Loop → While Loop

For Version

```
for (Init; Test; Update)  
    Body
```



While Version

```
Init;  
  
while (Test) {  
    Body  
    Update;  
}
```

For-While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
long pcount_for_while  
    (unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    i = 0;  
    while (i < WSIZE)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
        i++;  
    }  
    return result;  
}
```

“For” Loop Do-While Conversion

C Code

Goto Version

```
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

```
long pcount_for_goto_dw
(unsigned long x) {
    size_t i;
    long result = 0;
    i = 0;
    if (! (i < WSIZE)) { Init
        goto done; ! Test
    }
    loop:
    {
        unsigned bit =
            (x >> i) & 0x1; Body
        result += bit;
    } Update
    if (i < WSIZE) { Test
        goto loop;
    }
    done:
    return result;
}
```

- Initial test can be optimized away

Quiz Time!

Exercise 3.29

Today

- Control: Condition codes
- Conditional branches
- Loops
- **Switch Statements**

```
long my_switch
  (long x, long y, long z)
{
    long w = 1;
    switch(x) {
        case 1:
            w = y*z;
            break;
        case 2:
            w = y/z;
            /* Fall Through */
        case 3:
            w += z;
            break;
        case 5:
        case 6:
            w -= z;
            break;
        default:
            w = 2;
    }
    return w;
}
```

Switch Statement Example

- Multiple case labels
 - Here: 5 & 6
- Fall through cases
 - Here: 2
- Missing cases
 - Here: 4

Jump Table Structure

Switch Form

```
switch(x) {  
    case val_0:  
        Block 0  
    case val_1:  
        Block 1  
        . . .  
    case val_n-1:  
        Block n-1  
}
```

Jump Table

jtab:



Jump Targets

Targ0:

Code Block
0

Targ1:

Code Block
1

Targ2:

Code Block
2

•
•
•

Targn-1:

Code Block
n-1

Translation (Extended C)

```
goto *JTab[x];
```

Switch Statement Example

```
long my_switch(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Setup

my_switch:

```
    movq    %rdx, %rcx
    cmpq    $6, %rdi    # x:6
    ja      .L8
    jmp    * .L4(,%rdi,8)
```

What range of values
takes default?

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Note that w not
initialized here

Switch Statement Example

```
long my_switch(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Setup

```
my_switch:
    movq    %rdx, %rcx
    cmpq    $6, %rdi    # x:6
    ja     .L8          # use default
    jmp    * .L4(,%rdi,8) # goto *Jtab[x]
```



Indirect
jump

Jump table

```
.section    .rodata
.align 8
.L4:
    .quad     .L8    # x = 0
    .quad     .L3    # x = 1
    .quad     .L5    # x = 2
    .quad     .L9    # x = 3
    .quad     .L8    # x = 4
    .quad     .L7    # x = 5
    .quad     .L7    # x = 6
```

Assembly Setup Explanation

■ Table Structure

- Each target requires 8 bytes
- Base address at `.L4`

■ Jumping

- **Direct:** `jmp .L8`
- Jump target is denoted by label `.L8`

- **Indirect:** `jmp * .L4(,%rdi,8)`
- Start of jump table: `.L4`
- Must scale by factor of 8 (addresses are 8 bytes)
- Fetch target from effective Address `.L4 + x*8`
 - Only for $0 \leq x \leq 6$

Jump table


```
.section .rodata
.align 8
.L4:
.quad .L8 # x = 0
.quad .L3 # x = 1
.quad .L5 # x = 2
.quad .L9 # x = 3
.quad .L8 # x = 4
.quad .L7 # x = 5
.quad .L7 # x = 6
```

Jump Table

Jump table

```
.section    .rodata
.align 8
.L4:
.quad      .L8    # x = 0
.quad      .L3    # x = 1
.quad      .L5    # x = 2
.quad      .L9    # x = 3
.quad      .L8    # x = 4
.quad      .L7    # x = 5
.quad      .L7    # x = 6
```

```
switch(x) {
    case 1:          // .L3
        w = y*z;
        break;
    case 2:          // .L5
        w = y/z;
        /* Fall Through */
    case 3:          // .L9
        w += z;
        break;
    case 5:
    case 6:          // .L7
        w -= z;
        break;
    default:         // .L8
        w = 2;
}
```



Code Blocks ($x == 1$)

```
switch(x) {  
    case 1:          // .L3  
        w = y*z;  
        break;  
    . . .  
}
```

```
.L3:  
    movq    %rsi, %rax  # y  
    imulq   %rdx, %rax  # y*z  
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Handling Fall-Through

```
long w = 1;  
. . .  
switch(x) {  
    . . .  
    case 2:  
        w = y/z;  
        /* Fall Through */  
    case 3:  
        w += z;  
        break;  
    . . .  
}
```

```
case 2:  
    w = y/z;  
    goto merge;
```

```
case 3:  
    w = 1;  
  
merge:  
    w += z;
```

Code Blocks ($x == 2$, $x == 3$)

```
long w = 1;  
.  
.  
switch(x) {  
.  
. . .  
case 2:  
    w = y/z;  
    /* Fall Through */  
case 3:  
    w += z;  
    break;  
.  
.  
}
```

```
.L5:                      # Case 2  
    movq    %rsi, %rax  
    cqto          # sign extend  
                  # rax to rdx:rax  
    idivq   %rcx      # y/z  
    jmp     .L6        # goto merge  
.L9:                      # Case 3  
    movl    $1, %eax    # w = 1  
.L6:  
    addq    %rcx, %rax # w += z  
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rcx	z
%rax	Return value

Code Blocks ($x == 5$, $x == 6$, default)

```
switch(x) {  
    . . .  
    case 5: // .L7  
    case 6: // .L7  
        w -= z;  
        break;  
    default: // .L8  
        w = 2;  
}
```

```
.L7:                      # Case 5,6  
    movl $1, %eax      # w = 1  
    subq %rdx, %rax   # w -= z  
    ret  
.L8:                      # Default:  
    movl $2, %eax      # 2  
    ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Quiz Time!

Exercise 3.30, 3.31

Summarizing

- C Control
 - if-then-else
 - do-while
 - while, for
 - switch
- Assembler Control
 - Conditional jump
 - Conditional move
 - Indirect jump (via jump tables)
 - Compiler generates code sequence to implement more complex control
- Standard Techniques
 - Loops converted to do-while or jump-to-middle form
 - Large switch statements use jump tables
 - Sparse switch statements may use decision trees (if-elseif-elseif-else)

Summary

■ Today

- Control: Condition codes
- Conditional branches & conditional moves
- Loops
- Switch statements

■ Next Time

- Stack
- Call / return
- Procedure call discipline

Finding Jump Table in Binary

```
00000000004005e0 <switch_eg>:  
4005e0: 48 89 d1          mov    %rdx,%rcx  
4005e3: 48 83 ff 06       cmp    $0x6,%rdi  
4005e7: 77 2b             ja     400614 <switch_eg+0x34>  
4005e9: ff 24 fd f0 07 40 00 jmpq   *0x4007f0(,%rdi,8)  
4005f0: 48 89 f0          mov    %rsi,%rax  
4005f3: 48 0f af c2       imul   %rdx,%rax  
4005f7: c3                retq  
4005f8: 48 89 f0          mov    %rsi,%rax  
4005fb: 48 99             cqto  
4005fd: 48 f7 f9          idiv   %rcx  
400600: eb 05             jmp    400607 <switch_eg+0x27>  
400602: b8 01 00 00 00     mov    $0x1,%eax  
400607: 48 01 c8          add    %rcx,%rax  
40060a: c3                retq  
40060b: b8 01 00 00 00     mov    $0x1,%eax  
400610: 48 29 d0          sub    %rdx,%rax  
400613: c3                retq  
400614: b8 02 00 00 00     mov    $0x2,%eax  
400619: c3                retq
```

Finding Jump Table in Binary (cont.)

```
00000000004005e0 <switch_eg>:  
.  
. . .  
4005e9: ff 24 fd f0 07 40 00 jmpq *0x4007f0(,%rdi,8)  
. . .
```

```
% gdb switch  
(gdb) x /8xg 0x4007f0  
0x4007f0: 0x0000000000400614 0x00000000004005f0  
0x400800: 0x00000000004005f8 0x0000000000400602  
0x400810: 0x0000000000400614 0x000000000040060b  
0x400820: 0x000000000040060b 0x2c646c25203d2078  
(gdb)
```

Finding Jump Table in Binary (cont.)

```
% gdb switch  
(gdb) x /8xg 0x4007f0  
0x4007f0: 0x00000000000400614  
0x400800: 0x000000000004005f8  
0x400810: 0x00000000000400614  
0x400820: 0x0000000000040060b  
0x400830: 0x000000000004005f0  
0x400840: 0x00000000000400602  
0x400850: 0x0000000000040060b  
0x400860: 0x2c646c25203d2078
```

```
...  
4005f0: 48 39 f0 mov %rsi,%rax  
4005f3: 48 0f af c2 imul %rdx,%rax  
4005f7: c3 retq  
4005f8: 48 39 f0 mov %rsi,%rax  
4005fb: 48 99 cqto  
4005fd: 48 f7 f9 idiv %rcx  
400600: eb 05 jmp 400607 <switch_eg+0x27>  
400602: b8 01 00 00 00 mov $0x1,%eax  
400607: 48 01 c8 add %rcx,%rax  
40060a: c3 retq  
40060b: b8 01 00 00 00 mov $0x1,%eax  
400610: 48 29 d0 sub %rdx,%rax  
400613: c3 retq  
400614: b8 02 00 00 00 mov $0x2,%eax  
400619: c3 retq
```