

Question 1 | Correct | Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int compare(const void *a, const void *b) {
5     return (*(int *)a - *(int *)b);
6 }
7
8 int main() {
9     int n;
10    scanf("%d", &n);
11
12    int a[n], b[n];
13
14    for (int i = 0; i < n; i++)
15        scanf("%d", &a[i]);
16
17    for (int i = 0; i < n; i++)
```

```

18     scanf("%d", &b[i]);
19
20     qsort(a, n, sizeof(int), compare);
21     qsort(b, n, sizeof(int), compare);
22
23     long long sum = 0;
24
25     for (int i = 0; i < n; i++)
26         sum += (long long)a[i] * b[n - 1 - i];
27
28     printf("%lld", sum);
29
30     return 0;
31 }

```

	Input	Expected	Got	
✓	3	28	28	✓
	1			
	2			
	3			
	4			
	5			
	6			