

Creating Lookup Table

Command to create the Lookup Table

- Create Hbase table with required column mapping in Hbase system by using below command.

sh createLookup.sh

```
#!/bin/bash
echo "create 'look_up_table', 'card_details', 'Member_details', 'Location',
'Rule_params'" | hbase shell -n
hive -f /home/hadoop/lookuptable.hql
```

- Command will create lookup table in Hbase and It will trigger hive hql file to create hive table which will point to Hbase table for data storage and processing.
- Now create **lookuptable.hql** file with look_up_table creation statement and hbase column mapping.

lookuptable.hql

```
CREATE EXTERNAL TABLE IF NOT EXISTS look_up_table (
  card_id STRING,
  card_purchase_dt STRING,
  transaction_dt STRING,
  member_id STRING,
  member_joining_dt STRING,
  country STRING,
  city STRING,
  UCL DOUBLE,
  postcode STRING,
  score INT
)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY ','
STORED BY "org.apache.hadoop.hive.hbase.HBaseStorageHandler"
WITH SERDEPROPERTIES ("hbase.columns.mapping" =
"card_details:card_purchase_dt,
card_details:transaction_dt,Member_details:member_id,
```

```
Member_details:member_joining_dt,
Location:country,Location:city,Rule_params:UCL,Rule_params:postcode,
Rule_params:score")
TBLPROPERTIES ("hbase.table.name" = "look_up_table");
```

Command to see the table created

- Hbase command:

```
list
scan "look_up_table"
```

- Hive Command:

```
show tables;
select count(*) from look_up_table;
```

Screenshot of the created table.

- Hbase table created successfully.

```
[hadoop@ip-172-31-5-175 ~]$ sudo hbase shell
HBase Shell
Use "help" to get list of supported commands.
Use "exit" to quit this interactive shell.
Version 1.4.13, rUnknown, Fri Apr 17 15:18:24 UTC 2020

hbase(main):001:0> list
TABLE
card_transactions
look_up_table
2 row(s) in 0.1680 seconds

=> ["card_transactions", "look_up_table"]
hbase(main):002:0> scan "look_up_table"
ROW                                COLUMN+CELL
0 row(s) in 0.0750 seconds

hbase(main):003:0> █
```

- Hive table is also created successfully.

```
ogging initialized using configuration in file:/etc/hive/conf.dist/hive-log4j2.properties Async: true
hive> show tables;
K
ard_transactions
ard_transactions_stg
ast_ten_transactions
ook_up_table
ime taken: 0.687 seconds, Fetched: 4 row(s)
hive> select count(*) from look_up_table;
K
ime taken: 1.853 seconds, Fetched: 1 row(s)
hive> █
```