Building Knowledge Graphs: From Sources to Verifiable Queries

Mick Cooney

9 November 2026

Table of Contents

1 Introduction **2**

2 Define the Boundary Before Building the Graph **3**
2.1 Source Roles and Competency Questions . . . 3
2.2 Completeness and Negative Answers . . . 4
2.3 Bounded Source Claim Construction . . . 6

3 Preserve Mentions, Entities, and Identifiers as Different Things **7**
3.1 Mentions and Entity References . . . 7
3.2 Stable, Namespaced Identifiers . . . 8

4 Model Qualified Claims and Source Assertions **9**
4.1 Qualified Assertions . . . 9
4.2 Temporal Scope . . . 10
4.3 Polarity and Conflicting Evidence . . . 10

5 Extract Conservatively and Resolve Identity with Abstention **11**
5.1 Candidate Extraction . . . 11
5.2 Identity Resolution . . . 11
5.3 Abstention and Review . . . 12

6 Provenance, Time, Contradiction, and Uncertainty **13**
6.1 Provenance Roles and Release History . . . 13
6.2 Valid Time and Observation Time . . . 14
6.3 Conflict and Authority . . . 14
6.4 Uncertainty and Path Interpretation . . . 15

7 Privacy and Proportionate Identity **15**

8 Construct and Query with Python and DuckDB **16**
8.1 From Fixture to Tables . . . 18
8.2 Direct and Two-Hop Questions . . . 20

8.3 Valid Time, Conflict and Evidence 21

9 Represent Claims in RDF and Property Graphs 23
9.1 RDF: Triples and Qualified Claims 23
9.2 SPARQL Evidence Queries 26
9.3 Validate Graph Structure with Shapes Constraint Language (SHACL) 27
9.4 Describe Production History with the PROV Ontology (PROV-O) . . 28
9.5 Property Graphs and Cypher 29
9.6 What Is Lost When a Graph Is Simplified? 31
9.7 Storage and Workload Determine the Boundary 33
9.8 A Bounded Future Neo4j Smoke Test 34

10 Analyse a Projection in R 35
10.1 Build the Positive Projection 37
10.2 Interpret Paths and Components 37

11 Validate, Evaluate, and Diagnose 38
11.1 Validation, Inference and Verification 38
11.2 Gold Sets and Useful Measures 40

12 Release, Update, and Govern 42
12.1 Diagnose and Apply a Release 43
12.2 Corrections, Retractions, and Dependencies 43
12.3 Responsibility, Access, and Boundaries 44

13 Further Reading 45

1 Introduction

A knowledge graph connects identified things and the relationships claimed between them. Its value is not that drawing an edge makes a statement true. Its value is that a reader can follow a chain from a question through explicit modelling decisions to the source records on which an answer depends. This primer develops that chain: from source material and uncertain names to qualified claims, evidence-backed queries, validation, and repeatable releases.

The reader is a software or data practitioner comfortable with tables, JSON, and basic Python or SQL. No prior graph-database or ontology experience is assumed. The main route follows Northbridge, a synthetic organisational-policy case, through the canonical Python and DuckDB construction pipeline. This is a construction guide, not a complete reference for database products, formal logic, or legal interpretation. Policy authority in the example is an explicit modelling assumption, not legal advice.

Follow the dependency from the questions and source boundary to mentions and identity, then to qualified claims, extraction, provenance, and privacy. These choices determine what the Python and DuckDB queries can return and when they must abstain. After those queries, continue at Analyse a Projection in R, then use validation and release governance to assess and maintain the result. The R projection is a separate analysis of selected relations, not an evidence-preserving replacement for the claims.

Represent Claims in RDF and Property Graphs is an optional representation and storage branch after the Python route. Read its RDF subsections for triples, SPARQL, SHACL, and PROV-O; read the property-graph subsection for the corresponding Cypher design; or consult the storage comparison and proposed Neo4j smoke test when choosing or testing a serving layer. These designs are illustrative and the Neo4j test is prospective. Start with the section introduction before either branch; resume the main route at Analyse a Projection in R.

The standards, DuckDB, Neo4j and repository-runtime claims are linked to primary sources. The source-to-claim example is deliberately bounded, and research and privacy claims are linked or flagged with their evidential limits. The graph-query, shape-validation and provenance snippets are illustrative and unexecuted.

2 Define the Boundary Before Building the Graph

A knowledge graph is an answer-producing model over a declared evidence set. Its boundary therefore includes more than the files that happened to be ingested. It includes the questions the model is intended to answer, the source classes it accepts, the period and population those sources cover, and the decisions it is authorised to make when records disagree. If any of these are implicit, users can mistake a bounded extract for a complete account.

2.1 Source Roles and Competency Questions

Northbridge makes the boundary concrete. The fixture contains an authorised policy register, a Northbridge directory, and Atlas meeting minutes. It represents two policy versions, two projects, Morgan Lee, and two distinct people named Alex Kim. For the teaching scenario, the register is treated as the designated source for recorded policy applicability and ownership; the directory

supports project affiliation; the minutes represent what a meeting record states. This is a modelling assumption, not a source-ranking rule implemented by the script. Those roles do not make the register universally authoritative about every question. The minutes are the primary evidence for the sentence recorded at the meeting, even where the register is preferred to answer which version the organisation recorded as applicable.

Competency questions turn that boundary into observable requirements. For example: which policy version did the register say applied to Atlas on 1 March 2024? What owner did the register give for that version? What did the 15 March minutes say, and did that statement agree with the register for the same date? Can the attendee called Alex Kim be tied to either directory person? Each question names a relation or answer, and should also settle relevant scope: source authority, temporal interpretation, required evidence, and what to do when evidence is insufficient. A question that asks "Who is responsible?" leaves open whether responsibility means policy ownership, project sponsorship, or meeting attendance.

Treat each question as a contract for a query and its result. A useful answer to the first Northbridge question includes the version, the date tested, the authority rule, and a source locator. An answer to the attendee question may be "the minutes name Alex Kim, but the fixture does not distinguish the two directory people." This is a successful outcome if the evidence does not support a unique link. A graph that always returns a person has encoded an assumption, not demonstrated better coverage.

2.2 Completeness and Negative Answers

The boundary also governs negative answers. The absence of a matching claim means only that no claim was found in this fixture after applying the query's filters. It does not establish that Northbridge has no other policies, that no other meeting discussed the rule, or that Atlas has no other affiliations. To interpret absence as a negative fact, the source set needs a completeness guarantee for a defined subject, predicate, period, and population. The small synthetic fixture offers no such guarantee. Its appropriate use is to demonstrate construction, conflict handling, and query behaviour on known records, not to estimate coverage of a real organisation.

This distinction prevents two common category errors. First, "the graph says"

should not conceal which source and selection rule produced the result. Second, a missing path is not evidence that a relationship does not exist. State the fixture boundary alongside conclusions, and return "not represented in the supplied sources" when that is all the query establishes.

The fixture is `primer_knowledge_graph/examples/fixture.json`. It is synthetic data, not a set of retained source documents. The table summarises its source records and selected assertions; the locators are the exact source-level labels in the JSON.

Source	Locator	Selected fixture content
Authorised policy register `s-register`	`R1:P1-P2`	`c1`: version 1 applies to Atlas from 1 January to 1 April 2024; `c2`: version 1 is owned by Morgan; `c6`: version 2 applies from 1 April.
Northbridge directory `s-directory`	`D1:A1`	`c3` and `c7`: Atlas and Orion belong to Northbridge. The shared source locator does not identify a separate Orion row.
Atlas meeting minutes `s-minutes`	`M1:paragraph-3`	From 15 March, `c4` asserts version 2 applies and `c5` denies that version 1 applies; `m-alex` is unresolved.

The fixture stores the two Alex entities but not their directory identifiers or the full register and minutes. The separate `examples/source_records.json` retains short synthetic excerpts and three directory rows for the executable construction slice. It records only version 1 ownership, not ownership of version 2. The start date on a meeting claim is an encoded valid-time interpretation, not a general rule that a publication date automatically fixes validity.


2.3 Bounded Source Claim Construction

The executable `examples/python/construction.py` reads the versioned synthetic excerpts in `examples/source_records.json`. Its three sentence patterns produce candidates with subject, predicate, object, source, dates, end kind and polarity, plus an evidence locator, character offsets, exact matched text and method `northbridge-patterns-v1`. Offsets are checked against the retained text. The following table follows the actual source sentences into candidates; the dates are calendar dates.

Retained text and locator	Candidate and interpretation	Ledger mapping
`R1:P1-P2`: "Travel Policy v1 applies to Atlas from 2024-01-01 until 2024-04-01."	Version 1 `applies_to` Atlas, positive; `bounded`, starting 1 January and ending exclusively on 1 April.	Constructed `c1`, with mention `m-policy-v1`.
`M1:paragraph-3`: "On 2024-03-15, version 2 applies to Atlas."	Version 2 `applies_to` Atlas, positive; `unknown` end, supported through 15 March.	Constructed `c4`, with `m-policy-v2-meeting`.
`M1:paragraph-3`: "On 2024-03-15, version 1 does not apply to Atlas."	Version 1 `applies_to` Atlas, negative; `unknown` end, supported through 15 March.	Constructed `c5`, with `m-policy-v1-meeting`.
`S1:1`: "Travel Policy v1 applies to Atlas from 2024-01-01 and continues until further notice."	A separate synthetic positive candidate with `unbounded` end because the source explicitly asserts continuation.	Used in a separate classifier test; not inserted as a ledger claim.

For the meeting sentences, the rule encodes the stated date as `valid_from` and `supported_through`; it does not infer continuation beyond that date. The method is deliberately restricted to these sentence forms and policy versions. Its selected claim IDs and mention IDs are assigned by a fixed source-and-subject mapping, rather than discovered by a general entity recogniser.

```
retained source + span
        | bounded rules: dates, negation, identifiers
```



The executable removes candidate evidence metadata before comparing every canonical field of constructed `c1`, `c4`, and `c5` with the fixture, then loads the fixture ledger. The evidence spans remain in the construction output, not in the DuckDB claims table. The other ledger claims are curated: `c2` records ownership, `c3` and `c7` project affiliation, and `c6` the register's version 2 applicability. They are not extracted by this slice, and their complete source passages are not retained. The constructed-versus-curated distinction describes how these example rows were supplied, not a judgement that either is independently verified. Full-document optical character recognition, open-domain language understanding, learned matching, and a general update engine remain outside this milestone.

3 Preserve Mentions, Entities, and Identifiers as Different Things

The boundary tells us which source occurrences matter; it does not tell us which occurrences refer to the same thing. Before converting those occurrences into claims, keep their source evidence separate from the identities the graph may assign.

3.1 Mentions and Entity References

A mention is an occurrence in a source; an entity is a thing the model refers to; an identifier names that entity within a defined namespace. A label is a human-readable description and need not be unique. These objects have different lifecycles and should not be collapsed into one row just because a simple graph drawing has one node per thing.

In the fixture, `m-alex` records "Alex Kim" in `s-minutes` with a null entity. Two distinct entities, `person:alex-kim-1` and `person:alex-kim-2`, share that label. Resolution decision `r2` records both candidates and abstains because the meeting gives no distinguishing identifier. The occurrence survives without inventing an identity or a third person.

The same separation applies to policy names. `policy:travel-v1` and `policy:travel-v2` are distinct version entities. The mentions `m-policy-v1`, `m-policy-v1-meeting`, `m-policy-v2-meeting`, and `m-policy-v2-register` are separate textual occurrences referring to those versions. A mention such as "version 2" is meaningful because its source context supplies a policy subject; outside that context the words alone may be ambiguous. Modelling the policy family as though it were identical to either version would blur the temporal question the fixture is designed to answer.

Each source has a logical locator: `R1:P1-P2`, `D1:A1`, or `M1:paragraph-3`. These identify synthetic source regions, not byte offsets or complete source documents; the construction input retains excerpts and checks character offsets within them; the register locator covers both rows rather than singling out one claim. A production evidence chain should point to a stable source version and a reproducible row key, page and paragraph, or character offsets against a content-addressed text extraction. Offsets without a reproducible text version are fragile; row numbers are fragile if rows can be sorted.

3.2 Stable, Namespaced Identifiers

Identifiers should be stable and namespaced. The fixture's IDs (`org:northbridge`, `project:atlas`, `policy:travel-v1`, and `person:morgan-lee`) are readable synthetic identifiers; the prefix suggests a kind but does not by itself guarantee global uniqueness or establish who issued it. Real source identifiers should retain their issuing authority, since `1234` in one system may identify something different from `1234` in another. A label change should not silently create a new entity, and a reused label should not silently merge two entities. If two records are linked, preserve the mapping and the basis for it so that a later correction can split the records without rewriting the source history.

The World Wide Web Consortium (W3C) RDF 1.1 Concepts recommendation makes a related distinction between Internationalised Resource Identifiers (IRIs), literals, and blank nodes: identifiers and values play different roles in a graph. Northbridge's JSON schema is not RDF, but the conceptual lesson applies across storage choices. A date such as `2024-03-15` is a value; `project:atlas` is a reference; "Atlas" is a label; and the occurrence `m-atlas` is evidence that a particular source used that label. Retaining these distinctions allows labels and interpretations to change without losing what the source

actually contained.

4 Model Qualified Claims and Source Assertions

A bare triple such as `policy:travel-v1 applies_to project:atlas` omits information needed to answer the Northbridge questions. The fixture's claim `c1` adds source `s-register`, mention `m-policy-v1`, the validity interval from 1 January to 1 April 2024, and positive polarity. These fields make the statement inspectable and temporally queryable. The corresponding positive relation in `relations` is only an analytical projection; it omits source, mention, interval, and polarity and must not become the evidence record used to explain an answer.

4.1 Qualified Assertions

The subject–predicate–object form remains useful for the core relation, but many claims are not adequately represented by an unqualified edge. A policy's applicability can be conditional on jurisdiction, staff class, or activity; ownership can have a role and appointment period; an employment relation can be asserted by one source and disputed by another. One representation is to make each qualified assertion a first-class record, as `claims` does, with references to its participants and evidence. Another is an n-ary relation node or a named graph with attached metadata. The design choice should preserve the fields needed by competency questions and validation. W3C's guidance on n-ary relations describes this general modelling problem; it does not prescribe one universal encoding.

Distinguish a proposition from an assertion of that proposition. In this primer, a claim is the qualified proposition under consideration; an assertion is a source or process presenting it. Claim `c4` says that `policy:travel-v2` applies to Atlas from 15 March according to the minutes. Claim `c6` says that the same version applies from 1 April according to the register. Claim `c5` records the minutes' negative assertion that version 1 applies on 15 March. Keeping source-specific assertions means the minutes and register remain separately queryable. It also avoids the misleading operation of overwriting one value with the other.

4.2 Temporal Scope

The temporal contract must distinguish three end kinds; nullness alone is not enough. A `bounded` claim has `valid_to > valid_from` and means the half-open interval `[valid_from, valid_to)`. An `unbounded` claim has no `valid_to` and explicitly says that the source asserts continuation; it remains revisable and is not a promise of eternal truth. An `unknown` claim has no `valid_to` but has a `supported_through` date: the source supports the inclusive period `[valid_from, supported_through]`, and applicability afterwards is indeterminate. `supported_through` is the last domain-valid date supported by the assertion, not its publication, ingestion, review, or transaction time. It must not be inferred from a single observation or from a source publication date.

Thus `c1` is bounded, covers 1 January through 31 March, and `c6` begins on 1 April. Existing claims with an unspecified end should be treated as `unknown` unless the source explicitly supplies continuation; do not silently promote them to `unbounded`. The fixture and runnable script require explicit `end_kind`, explicit nulls where applicable, and the corresponding `supported_through` rule. The predicate itself also needs a definition: `owned_by` means the register's recorded owner in this example, not necessarily the legal owner, budget holder, or operational decision-maker.

4.3 Polarity and Conflicting Evidence

Polarity is not the same as truth status. `c5` is a negative-polarity assertion from the minutes; its presence records that the minutes deny applicability of version 1 from 15 March. It does not erase positive `c1`, and the fact that `c1`'s validity interval ends on 1 April does not make `c5` true. The positive-claim `relations` projection intentionally excludes `c5`, so analyses over that projection cannot answer questions about the disagreement. Query design must choose whether it needs the positive topology, the full assertion ledger, or both. A projection is a derived view with documented loss, not a replacement for source-backed claims.

5 Extract Conservatively and Resolve Identity with Abstention

The claim model specifies what a usable record must retain. Construction must now decide whether a source supplies enough evidence to populate that record and link its participants; missing evidence can require abstention at either step.

5.1 Candidate Extraction

Extraction turns source material into candidate mentions and assertions. It is an interpretation step, even when a rule-based parser is used: sentence boundaries, negation scope, coreference, version references, and date expressions can all be misread. Preserve the input source and version, the extracted text or span, the proposed participants and predicate, and the extraction method. Separate this candidate record from a later accepted assertion so that changed rules can be compared against the same evidence.

The Northbridge examples expose why this matters. The register says version 1 applies to Atlas from 1 January until 1 April; the minutes, dated 15 March, say version 2 already applies and explicitly deny that version 1 applies. A system that extracts only affirmative noun–verb patterns may retain `c4` and lose `c5`. A system that treats the meeting date as the start date of the policy's validity may confuse when a statement was made with when the stated relationship holds. The fixture encodes the meeting assertions as valid from 15 March, but a richer representation would separately store the minutes' publication or event date and the time referred to by each statement. Extraction must retain enough context to assess those interpretations rather than hide them in a single edge.

5.2 Identity Resolution

Entity resolution is a separate decision: given a mention or source record and candidate entities, decide whether the evidence supports identity. Candidate generation and candidate matching have distinct failure modes. A blocking rule may fail to propose a true match; a matcher may incorrectly accept a proposed pair. Statistics Canada's study of blocking errors discusses why missed candidates need separate measurement from match decisions. Names, type compatibility, co-occurring identifiers, dates, and source-specific rules can help rank or reject candidates, but no string similarity threshold supplies evidence that is

absent from the source.

The executable identity walkthrough uses the separate retained excerpts and directory rows. The register says "Owner Morgan Lee has directory ID NB-104." Name matching proposes `person:morgan-lee`, whose directory row also has `NB-104`; `resolve` accepts that candidate. The fixture records the corresponding outcome as `r1` for `m-morgan`, although the identifier itself is outside the fixture. A separate test supplies `NB-999` for Morgan and gets a rejection for an incompatible identifier; that test is not an additional fixture decision.

The minutes say "Alex Kim attended." Name matching finds `person:alex-kim-1` (`NB-201`) and `person:alex-kim-2` (`NB-202`), but the sentence supplies neither identifier. The executable abstains with both candidates; curated decision `r2` likewise leaves `m-alex.entity` and its selected candidate null. These deliberately simple exact-match rules demonstrate acceptance, rejection and abstention on synthetic inputs; they do not measure identity-resolution accuracy or prove that an actual person attended.

The fixture records each decision ID, mention, candidate set, outcome, selected candidate where applicable, and reason. It contains one acceptance and one abstention, but no rejection. An operational decision record should also identify the method and version, review status and decision time. The Python validator checks the decision references and selected-candidate rules, and asserts the Alex abstention; it does not run a matcher or write the decisions into DuckDB.

5.3 Abstention and Review

Abstention is useful because the costs of errors are asymmetric. A missed link may leave a query incomplete; a false identity merge can attribute meeting attendance or policy ownership to the wrong person and contaminate every downstream path. Preserve uncertain candidate links outside the accepted graph, and make review possible. Pairwise decisions also need global consistency checks: accepting A–B and B–C does not prove A–C if the evidence is inconsistent or entities are not governed by a strict equivalence relation. Record enough provenance to reverse or revisit a merge.

Do not interpret a model's score as a probability of real-world truth unless it has been calibrated and evaluated for that task and population. Keep uncertainty tied to its source: ambiguous name, uncertain date, source reliabil-

ity, incomplete coverage, or extraction disagreement. Evaluation should report candidate-generation recall separately from accepted-match precision and review/abstention rates, using an explicitly described labelled sample. The synthetic fixture is a behavioural example; it cannot establish those rates for Northbridge or any wider population.

6 Provenance, Time, Contradiction, and Uncertainty

These concerns determine whether a graph answer can be traced, dated, compared with competing evidence, and qualified when the evidence is incomplete. Treat them as connected controls: provenance identifies the assertion, time limits its scope, conflict preserves disagreement, and uncertainty constrains the answer.

6.1 Provenance Roles and Release History

Provenance makes an answer auditable: which source version supported which assertion, what activity extracted or reviewed it, and which release and selection rule produced the answer. The W3C PROV Ontology (PROV-O) vocabulary models entities, activities, and agents and can inform an implementation. Even without adopting PROV-O, preserve stable source identifiers, version or digest, source and ingestion dates where known, reproducible locator, extraction or review method, and the responsible process or agent. A source publisher, the person quoted, and the extractor are different roles and should not be collapsed.

For the Northbridge register, one useful provenance chain is `s-register` as the source entity, an extraction activity that records the parser version and retained span, a review activity that accepts or changes the candidate claim, and a named process or agent responsible for that activity. A later release can then say that `c1` was derived from the register's `R1:P1-P2` span by one extraction run and included after one review rule, without implying that the extractor authored the policy. If the register is corrected, retain a new source version and connect the changed claim to the new activity; do not rewrite the old claim and lose the explanation of what an earlier release contained.

This distinction answers different audit questions. "Which document did the answer come from?" needs the source and locator. "How did this claim enter the graph?" needs the extraction or review activity and method version. "Who

may approve its publication?” needs an accountable agent and release record. A checksum proves which bytes were processed, but it does not prove that the source was authoritative or that the extraction rule interpreted it correctly.

6.2 Valid Time and Observation Time

Time commonly has at least two axes. Valid time describes when the asserted relationship holds in the domain; transaction or observation time describes when the system recorded that assertion. The fixture’s `valid_from` and `valid_to` encode valid time, while its `sources[].published` gives source publication dates. It has no ingestion timestamp or transaction history, so it cannot answer “what had the system recorded by 20 March?” without an external release record. A corrected register imported on 1 May should not rewrite the evidence available in an earlier release. Preserve both the old and new source versions and state whether a historical query asks what was known then or what current evidence says about then.

Consider `c1`, which is valid from 1 January until 1 April. A query asking whether version 1 applied on 31 March can use its valid interval; a query asking what the graph knew on 20 March also needs a release or ingestion timestamp showing that `c1` had already been admitted. A source published on 10 March might be observed by the system on 12 March, reviewed on 14 March, and published in graph release 3 on 16 March. Those dates answer different questions. If a corrected source arrives on 1 May, a current query about 31 March may use the correction, while a reconstruction of release 3 must use only the evidence admitted by that release.

When a schema stores only `valid_from` and `valid_to`, it can answer a domain-time question but cannot reconstruct the graph’s historical knowledge. That is not a reason to invent an observation date from the source publication date. Add the missing release history or state that the historical query is unsupported.

6.3 Conflict and Authority

For the date 15 March, the register’s `c1` covers Atlas under version 1; the minutes’ `c4` asserts version 2 and `c5` denies version 1 for the same project and date. Those are incompatible assertions under the fixture’s intended interpretation. `c6` begins version 2 on 1 April and is consistent with the end of `c1`; it is

not itself a contradiction. Before labelling two records contradictory, compare subject, predicate, object or competing value, temporal scope, jurisdiction, and relevant conditions. A conflict requires overlapping scope and mutually exclusive claims, not merely two different records.

Authority is purpose-specific. To answer “what did the register record?”, use the register. To answer “what did the minutes say?”, report the minutes. To answer “which version should a user treat as governing?”, the fixture alone cannot settle legal or operational force; its teaching rule can prefer the register only for the narrower question about recorded policy applicability. Keep the losing assertion visible and state the preference rule. Otherwise a source ranking can look like a truth mechanism and conceal a material disagreement.

6.4 Uncertainty and Path Interpretation

Uncertainty has multiple causes and should not be compressed into one confidence number. The Alex identity is underdetermined because the source lacks a distinguishing identifier. The applicability disagreement is not an extraction uncertainty in the fixture: two explicit, incompatible records are present. Source completeness is unknown because only three synthetic source records are included. An unknown end on `c2` means duration is supported only through its retained horizon; it is not an eternal interval. Each condition changes what a query can conclude and should be represented or reported separately.

Agreement between two assertions is not automatically independent corroboration. They may copy the same upstream register, share an author, or be generated from one database. Provenance can reveal common origin; counting edges cannot. Similarly, a path from a policy through a project to an organisation proves only that the selected projection contains those edges. It does not establish causality, authority, or completeness. Return evidence for each hop and keep interpretation distinct from topology.

7 Privacy and Proportionate Identity

Entity resolution can turn dispersed records into a more identifying profile than any single source. A name, project affiliation, and meeting attendance may be low-risk in isolation but sensitive when linked and made searchable. The Northbridge fixture is fictional, yet its two Alex Kim records demonstrate a practical

harm: an unsupported merge could attribute attendance to the wrong person. In a real system, that same error can affect access decisions, employment records, or investigations.

Collect and expose only the identifiers and attributes required by the competency questions. If a policy query needs the owner relation, it may not need personal contact details or a broad employee profile. Keep direct identifiers in a controlled mapping where possible, apply access controls to source text and derived claims, and record retention and deletion rules. A graph edge is still personal data when it identifies or can be linked to an individual; changing the storage format does not remove that responsibility. The appropriate legal basis, safeguards, and retention period depend on jurisdiction and purpose and require review against applicable law and organisational policy.

Privacy also affects provenance design. A public answer may need to show a source class, version, and redacted locator rather than expose an entire restricted document. The system should preserve enough controlled evidence for authorised audit while preventing broader access through graph traversal. Test both what an authorised reviewer can trace and what an ordinary query user can infer. Access restrictions and redaction must not silently erase the fact that evidence was withheld; report the limitation at a level that does not itself disclose protected information.

The practical design test is whether each identity link and exposed attribute is necessary for a stated question, supported by evidence, and available to the intended audience. For the ambiguous Northbridge attendee, abstaining protects both correctness and the people represented. It also leaves a clear route for adding a distinguishing identifier later, should an authorised source provide one.

8 Construct and Query with Python and DuckDB

The preceding decisions become observable when claims are built, checked, and queried. The executable route below retains source-specific records so that a date classification and an answer policy can be inspected separately: an applicable assertion is evidence for an answer, while a competing or temporally indeterminate assertion can prevent a definitive answer.

The canonical runnable example is `primer_knowledge_graph/examples/python/knowledge_graph`

its inputs are `primer_knowledge_graph/examples/source_records.json` and the canonical `primer_knowledge_graph/examples/fixture.json`. Both use synthetic records. The script applies the bounded construction slice, compares constructed claims with the ledger, validates references and intervals, writes claims and provenance to a file-backed DuckDB database, closes it, reopens it read-only, and runs bounded queries with assertions. It is not a general source extractor. Its manifest entry is `knowledge-graph-python` in `primer_knowledge_graph/examples/manifest.toml`. From the repository root, build the primer's runtime if necessary and run:

```
just build-python-duckdb-runtime
just examples knowledge_graph knowledge-graph-python
```

The runner provides a fresh temporary output directory, disables network access and discards the database afterwards. The script uses `EXAMPLE_OUT` when set and otherwise writes to its working directory. It creates tables with plain `CREATE TABLE`, so running it again against the same output database fails rather than silently replacing the previous build. Use a fresh directory for each standalone run. DuckDB documents file-backed and read-only connections; persistence here means the script can reopen and query its file, not that it publishes an enduring release.

The fixture contains eight entities, three source records, seven mentions and seven claim records. It also contains five `relations` for a separate analytical projection. The Python script validates entity references but does **not** create an entities or relations table. It writes only `claims`, `sources` and `mentions`. This is enough to demonstrate evidence-bearing joins, but an application needing entity labels, types, and database-enforced references must add those tables and load them. The R example independently hard-codes the same entity IDs and projection for analysis; the projection is not the canonical evidence store. The retained source records used by the construction slice are a separate synthetic input and include a deliberately refused date phrase.

The executable assertions also give a compact account of dated answers and evidence. The first four rows ask whether version 1 applies to Atlas across both register and minutes; the last two classify both edges of the register-backed version 1 → Atlas → Northbridge path. Locators are joined from the source table, and mention text is available for `c1` and `c5`.

Date and question	Evidence and temporal classification	Executable result
1 March 2024, applicability	c1 positive, applicable (R1:P1-P2); c5 outside (M1:paragraph-3).	supported
15 March 2024, applicability	c1 positive and c5 negative, both applicable, with their respective register and minutes locators.	abstain: conflicting evidence
16 March 2024, applicability	c1 applicable; c5 indeterminate beyond its support horizon.	abstain: indeterminate temporal scope
1 April 2024, applicability	c1 outside at its exclusive end; c5 indeterminate.	abstain: indeterminate temporal scope
1 January 2024, two-hop path	c1 applicable (R1:P1-P2); c3 applicable (D1:A1).	applicable
1 March 2024, two-hop path	c1 applicable; c3 indeterminate beyond 1 January.	indeterminate

These are fixture regression results under the executable's conservative answer policy, not a legal determination or evidence of production accuracy. The path status is a classification of both premises, not an inferred organisational claim.

8.1 From Fixture to Tables

In the target ledger, each JSON claim is a source-specific assertion with an ID, subject, predicate, object, source, optional mention, valid interval, temporal end kind, optional support horizon, and polarity. The field contract is: `bounded` requires `valid_to` and no `supported_through`; `unbounded` requires both to be null and explicit source wording of continuation; `unknown` requires a null `valid_to` and `supported_through >= valid_from`. Dates use calendar-date strings. The horizon is the last supported domain-valid date, inclusive; it is not publication or ingestion time. The checked-in fixture uses this contract. In either form, c1

says that `policy:travel-v1` applies to `project:atlas` from 1 January to 1 April 2024, according to `s-register`; `c5` records a negative assertion about the same subject, predicate and object from `s-minutes`, starting on 15 March. The two rows preserve disagreement. `c4` and `c6` both assert that version 2 applies to Atlas, but they have different sources and start dates. Neither should be collapsed into a single source-free edge if the question concerns evidence.

The executable's current data-definition language (DDL) is intentionally minimal; domain rules remain in the Python validator:

```
CREATE TABLE claims (id VARCHAR, subject VARCHAR, predicate VARCHAR,
    object VARCHAR, source VARCHAR, mention VARCHAR, valid_from DATE,
    valid_to DATE, end_kind VARCHAR, supported_through DATE,
    polarity BOOLEAN);
CREATE TABLE sources (id VARCHAR, title VARCHAR, published DATE, locator VARCHAR);
CREATE TABLE mentions (id VARCHAR, source VARCHAR, text VARCHAR, entity VARCHAR);
```

The executable loads both qualifier fields and validates the three combinations before insertion. A production-aligned schema would also make `end_kind` non-null, add keys and foreign keys, and enforce the cross-field combinations in the database as well as in application code.

Loading uses parameterised `executemany` calls, with columns selected in the same order as the DDL. The JSON dates are converted to DuckDB `DATE` values on insertion. Prepared values keep data separate from SQL syntax; they do not turn a dynamic table or column name into a safe identifier. See the DuckDB Python DB-API documentation for parameter binding. The executable validates before insertion, rather than relying on the DDL for uniqueness, required values or foreign keys.

The example's DDL does not enforce keys, required fields or foreign keys. The Python validator checks several of these before insertion, including that a claim's mention comes from its source and identifies a participant. A more defensive database schema could add primary and foreign keys, non-null fields and interval checks; cross-row conditions and domain rules would still need additional validation. Consult DuckDB constraints for the pinned version's behaviour.

The source table includes the fixture's logical locator, but the fixture has no source version, digest, ingestion time or complete source document. The separate construction input has a synthetic version and excerpts, which are not loaded into that table. A production system should add these and use assertion-to-evidence links where one assertion depends on several passages. Evidence

links can share a source and are not necessarily independent corroboration.

The distinction between a proposition and an assertion matters when several records say the same thing. This fixture uses `claims` as source-specific rows: the source and interval are part of each row. A larger model may instead give a canonical proposition its own ID and record each source assertion separately, including its extraction method and review state. Either design can work if it preserves which source made which assertion, under which scope, and does not mistake a merged proposition for a verified fact. The W3C PROV data model provides a general vocabulary for entities, activities and agents when interoperable provenance is needed; the fixture does not implement PROV.

8.2 Direct and Two-Hop Questions

A direct query returns all recorded assertions for a subject and predicate. In the executable, the parameters are `policy:travel-v1` and `applies_to`:

```
SELECT id, object, polarity
FROM claims
WHERE subject = ? AND predicate = ?
ORDER BY id;
```

The result is `c1, project:atlas, true` and `c5, project:atlas, false`. The query deliberately has no date or source filter. It establishes that the database contains two differently signed assertions; it does not decide which applies on a particular day. Filtering to positive rows first would hide the negative evidence. Filtering by `source = 's-register'` answers a different, explicitly source-scoped question, not an unrestricted question about all evidence.

A two-hop query follows a known relationship sequence. The executable joins the object of a positive `applies_to` claim to the subject of a positive `belongs_to` claim:

```
SELECT a.id, b.id, b.object
FROM claims a JOIN claims b ON a.object = b.subject
WHERE a.subject = ? AND a.predicate = ? AND b.predicate = ?
  AND a.polarity AND b.polarity
ORDER BY a.id, b.id;
```

With parameters `policy:travel-v1`, `applies_to` and `belongs_to`, the result is `(c1, c3, org:northbridge)`: the policy is linked through Atlas to Northbridge. Both claim IDs are returned, so the evidence for each step can be inspected. The join establishes a path under the query's conditions; it does not create a new assertion that the policy applies to the whole organisation. The executable's two-hop query has no time filter and therefore does not establish that

both links hold on any requested date. For a dated path, apply the same valid-time predicate to **each** row, and retain the individual intervals and sources. If several assertions support either step, the join can yield several paths; deciding whether to deduplicate answers is separate from retaining their evidence.

Bounded predicates and hop counts also constrain cost and interpretation. An unrestricted traversal may find a connection through irrelevant relationship types, combine incompatible dates, or return many paths created by duplicated evidence. State which predicate sequences answer the question and why their direction matters. A path through `owned_by` has a different meaning from one through `belongs_to`, even if both lead to a familiar name.

8.3 Valid Time, Conflict and Evidence

The target query policy classifies each matching assertion before aggregating an answer. A bounded end is exclusive; an explicit unbounded end remains applicable after its start; an unknown end is applicable only through its inclusive support horizon and is indeterminate afterwards. The classification is:

```
SELECT id, polarity, end_kind, supported_through,
  CASE
    WHEN CAST(? AS DATE) < valid_from THEN 'outside'
    WHEN end_kind = 'bounded' AND CAST(? AS DATE) < valid_to THEN 'applicable'
    WHEN end_kind = 'bounded' THEN 'outside'
    WHEN end_kind = 'unbounded' THEN 'applicable'
    WHEN end_kind = 'unknown'
      AND CAST(? AS DATE) <= supported_through THEN 'applicable'
    WHEN end_kind = 'unknown' THEN 'indeterminate'
    ELSE 'invalid'
  END AS temporal_status
FROM claims
WHERE subject = ? AND predicate = ? AND object = ?
ORDER BY id;
```

The source-specific answer policy is deliberately conservative: conflicting applicable polarities produce `abstain: conflicting evidence`; any indeterminate row produces `abstain: indeterminate temporal scope`; one applicable polarity produces `supported` or `refuted`; and no applicable or indeterminate evidence produces `abstain: no evidence`. This is a teaching policy, not the only valid aggregation rule. Do not turn an unknown negative into a definite refutation, or discard it to obtain a definite support. The executable applies this policy after retaining each row's temporal classification.

Under this contract, 31 December 2023 has no evidence; 15 March has applicable `c1` and `c5` and therefore a conflict; 16 March has applicable `c1` and inde-

terminate `c5`; and 1 April and 15 April have an outside `c1` and indeterminate `c5`. These are classifications relative to the selected evidence and policy, not claims that the world changed at an unobserved time. They do not establish when a reader could first have known each statement. For that, record when each assertion became available to the system, preserve its changes and filter both valid time and knowledge time. Publication date alone is not a substitute for ingestion or transaction history.

Here `refuted` means that the selected applicable rows contain negative evidence and no positive evidence under this policy. It is not a judgment that the negative source is authoritative or that every other relevant record has been found. No evidence is different from explicit negative evidence. Nor does a conflict force a particular authority decision: the policy does not rank the register above the minutes.

A provenance query makes that disagreement inspectable:

```
SELECT c.id, s.title, s.locator, m.text
FROM claims c
JOIN sources s ON c.source = s.id
LEFT JOIN mentions m ON c.mention = m.id
WHERE c.subject = ? AND c.predicate = ? AND c.object = ?
ORDER BY c.id;
```

The executable returns `c1` with `Authorised policy register`, `R1:P1-P2` and `Travel Policy v1`, and `c5` with `Atlas meeting minutes`, `M1:paragraph-3` and `version 1`. The left join matters because a claim such as `c7` has no mention. These source-level locators are logical labels, not the underlying documents or verified quotations. A real system needs source versions, reproducible locations, access conditions and retrieval context.

A dated query for version 2 illustrates a separate issue: `c4` is positive from 15 March and `c6` is positive from 1 April. The presence of two positive rows after 1 April does not prove independent corroboration or settle the register-versus-minutes interpretation. If an application adopts an authority hierarchy, make that policy a versioned input to answer generation, retain excluded evidence, and explain why it applies to this predicate, scope and date. A later correction must be able to change the answer without erasing the historical disagreement.

9 Represent Claims in RDF and Property Graphs

A representation is useful when it preserves the distinctions needed to answer a question, not merely when it draws a convincing network. Follow the Northbridge register's version 1 applicability statement through each representation: the policy version applies to Atlas from 1 January 2024 up to, but excluding, 1 April; the assertion comes from register `R1`, locator `R1:P1-P2`. The meeting minutes make a competing statement about version 2 on 15 March. A representation that retains only two policy-to-project arrows cannot reconstruct the dates, the source of either statement, or why the statements conflict. Nor should it turn the unresolved meeting mention of Alex Kim into an identified person.

This optional branch starts with the same evidence requirements as the DuckDB route and asks how another representation could preserve them. RDF readers can follow triples through querying, validation, and provenance; property-graph readers can proceed to Property Graphs and Cypher. The comparison and storage subsections apply to either choice, while the Neo4j smoke test is a prospective product-specific branch. Resume the main route at Analyse a Projection in R.

The examples in this section are illustrative designs inspired by the fixture. Their identifiers and vocabulary are local to the examples; they are not a claim that a particular RDF export, property-graph adapter, or Neo4j service has been implemented. In particular, distinguish a *claim*, which describes a qualified proposition, from an *assertion*, which records a source or process presenting that proposition. A source can support several claims, and several assertions can refer to the same claim while retaining separate locators and histories.

9.1 RDF: Triples and Qualified Claims

The Resource Description Framework (RDF) represents a graph as a set of triples: subject, predicate, and object. A triple says that the predicate relates the subject to the object. The subject is an IRI or blank node, the predicate an IRI, and the object an IRI, blank node, or literal. An IRI is an identifier in a global naming system; a literal is a value with a datatype or language tag. Blank nodes identify resources without providing a globally meaningful IRI. A graph is a *set*, so repeating the same triple does not record a second independent source. See RDF 1.1 Concepts for the abstract model.

For example, the Turtle statement `ex:atlas ex:belongsTo ex:northbridge .` is a readable serialisation of one triple. Prefix `ex:` abbreviates a namespace, rather than defining a separate kind of identifier. Turtle's punctuation lets multiple triples share a subject or predicate. Two serialisations with different ordering can describe the same RDF graph, and the spelling of a blank-node label in one file is not a stable identifier to use across releases. A persistent source locator or claim that must be cited across imports is therefore better given a governed IRI than identified by a local blank-node label.

A single direct triple such as `ex:travelV1 ex:appliesTo ex:atlas` does not contain the interval or source. Putting such a triple in a graph also asserts that relation in that graph; the existence of an assertion *about* the relation is a different modelling choice. For the conservative temporal contract, map `valid_from` and `valid_to` to `ex:validFrom` and optional `ex:validTo`; put exactly one `ex:endKind` on the claim using `ex:BoundedEnd`, `ex:UnboundedEnd`, or `ex:UnknownEnd`; put `ex:supportedThrough` on the source-specific assertion; and put required `ex:polarity` on the qualified claim. Use `xsd:dateTime` at midnight Coordinated Universal Time (UTC) for these domain dates so portable comparisons in the SPARQL Protocol and RDF Query Language (SPARQL) use one ordered datatype; this is an encoding convention, not invented time-of-day precision. Model the qualified proposition as its own resource instead:

```
@prefix ex:   <https://example.org/northbridge/> .
@prefix xsd:  <http://www.w3.org/2001/XMLSchema#> .
@prefix prov: <http://www.w3.org/ns/prov#> .

ex:claim-v1-atlas a ex:ApplicabilityClaim ;
    ex:policyVersion ex:travelV1 ;
    ex:project ex:atlas ;
    ex:validFrom "2024-01-01T00:00:00Z"^^xsd:dateTime ;
    ex:validTo "2024-04-01T00:00:00Z"^^xsd:dateTime ;
    ex:endKind ex:BoundedEnd ;
    ex:polarity true .

ex:assertion-r1-p1 a ex:Assertion, prov:Entity ;
    ex:asserts ex:claim-v1-atlas ;
    ex:sourceRecord ex:r1 ;
    ex:locator "R1:P1-P2" .

ex:claim-v1-atlas-minutes a ex:ApplicabilityClaim ;
    ex:policyVersion ex:travelV1 ;
    ex:project ex:atlas ;
    ex:validFrom "2024-03-15T00:00:00Z"^^xsd:dateTime ;
    ex:endKind ex:UnknownEnd ;
    ex:polarity false .

ex:assertion-minutes-p3 a ex:Assertion ;
    ex:asserts ex:claim-v1-atlas-minutes ;
```

```
    ex:sourceRecord ex:minutes ;
    ex:locator "M1:paragraph-3" ;
    ex:supportedThrough "2024-03-15T00:00:00Z"^^xsd:dateTime .
```

The local vocabulary specifies that `validTo` is exclusive; RDF does not infer that convention from its name. The code expresses a claim resource and an assertion resource; it deliberately does not add the unqualified direct `appliesTo` triple. The assertion's source, locator and support horizon make the example traceable at the fixture's source-level logical granularity. The unknown-ended minutes claim is not applicable after its horizon; it is indeterminate. A production record also needs the retained source version, a reproducible locator, and any extraction or review information required for an audit. Here `ex:r1` is an identifier for the register record, not the literal bytes of the source. These snippets are illustrative and unexecuted.

This is an n-ary relation: the application of a version to a project depends on more than the two endpoints. The claim resource makes the period and other conditions participants in one identified description. If a second source independently reports the *same* version, project, period and conditions, it can have a second assertion pointing to that claim. If it states a different interval or version, create a distinct claim. The W3C guidance on n-ary relations presents this family of patterns. Claim identity and deduplication remain application decisions; sharing an endpoint pair is not enough to establish that two claims are identical.

RDF datasets can organise a default graph and named graphs. A named graph can group an export or source-specific statements, but its name alone does not automatically say who asserted each statement, when it was obtained, or whether it is authoritative. Publish those semantics and provenance explicitly. Grouping by source may help access or retrieval, but one source can contain several locators and claims, and one assertion may rely on multiple source fragments. Named graphs do not remove the need to model that detail when a question requires it.

The examples use RDF 1.1 constructs for portability. Other statement-annotation facilities exist, but a deployment must specify the exact RDF version, syntax, semantics, and store support before depending on them. Even then, annotation syntax does not decide whether two observations are independent, which source takes precedence, or whether a date has been interpreted correctly.

9.2 SPARQL Evidence Queries

The SPARQL Protocol and RDF Query Language (SPARQL) matches graph patterns and returns bindings for variables. Each triple pattern below must match; the shared variables join the claim to its assertion and source. For the illustrative data above, this query retrieves the register claim applicable on 1 March, including its locator:

```
PREFIX ex:  <https://example.org/northbridge/>
PREFIX xsd: <http://www.w3.org/2001/XMLSchema#>

SELECT ?claim ?version ?assertion ?source ?locator ?start ?end
       ?kind ?polarity ?supportedThrough ?temporalStatus
WHERE {
  ?claim a ex:ApplicabilityClaim ;
         ex:policyVersion ?version ;
         ex:project ex:atlas ;
         ex:validFrom ?start .
  ?assertion ex:asserts ?claim ;
             ex:sourceRecord ?source ;
             ex:locator ?locator .
  ?claim ex:endKind ?kind ; ex:polarity ?polarity .
  OPTIONAL { ?claim ex:validTo ?end }
  OPTIONAL { ?assertion ex:supportedThrough ?supportedThrough }
  BIND ("2024-03-01T00:00:00Z"^^xsd:dateTime AS ?day)
  BIND (IF(?day < ?start, "outside",
       IF(?kind = ex:BoundedEnd,
          IF(BOUND(?end) && ?day < ?end, "applicable", "outside"),
       IF(?kind = ex:UnboundedEnd, "applicable",
       IF(?kind = ex:UnknownEnd && BOUND(?supportedThrough) &&
             ?day <= ?supportedThrough, "applicable",
       IF(?kind = ex:UnknownEnd, "indeterminate", "invalid")))))
       AS ?temporalStatus)
  FILTER (?source = ex:r1)
}
ORDER BY ?version ?assertion
```

The `BIND` classifies evidence rather than treating an unbound end as open. A query that returns only `?temporalStatus = "applicable"` is a deliberately narrower register-selection query; an answer-producing query must retain `indeterminate` rows for conservative aggregation. The source filter asks the narrower question of what the register records; removing it could expose both register and minutes claims, provided both have been loaded with comparable dates. To answer what the meeting said, select the minutes and their locator rather than changing the source record or deleting its competing assertion. The query is an illustrative, unexecuted SPARQL design; check syntax and store support before relying on it.

`OPTIONAL` preserves a solution when the optional pattern has no match, leaving its variable unbound. If multiple ends or multiple matching assertions are

present, the query can return multiple rows. That is useful evidence of multiplicity but can also duplicate apparent answers; impose appropriate constraints or aggregate deliberately, without suppressing distinct evidence. An omitted assertion fails the mandatory pattern and disappears from this particular result, so a separate validation or audit query is needed to find unsupported claims.

`FILTER NOT EXISTS` can ask whether a matching pattern is absent from the active dataset. It cannot prove that a source or relationship does not exist in the world. A query's dataset, default graph configuration, entailment settings, and access permissions all affect its results. State whether inferred triples are included and whether the selected release contains all relevant sources before treating absence as meaningful. SPARQL 1.1 defines graph patterns, optional matches, filters, datasets, and result forms; an implementation may add features whose behaviour should be documented separately.

9.3 Validate Graph Structure with Shapes Constraint Language (SHACL)

The Shapes Constraint Language (SHACL) expresses conditions over an RDF *data graph* in a separate *shapes graph*. A validator reports whether the chosen data conforms and identifies violations. For the local modelling rule that each applicability claim has one version, one project, and one start date, a compact shape is:

```
@prefix ex:  <https://example.org/northbridge/> .
@prefix sh:  <http://www.w3.org/ns/shacl#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .

ex:ApplicabilityShape a sh:NodeShape ;
    sh:targetClass ex:ApplicabilityClaim ;
    sh:property [ sh:path ex:policyVersion ;
                  sh:minCount 1 ; sh:maxCount 1 ; sh:nodeKind sh:IRI ] ;
    sh:property [ sh:path ex:project ;
                  sh:minCount 1 ; sh:maxCount 1 ; sh:nodeKind sh:IRI ] ;
    sh:property [ sh:path ex:validFrom ;
                  sh:minCount 1 ; sh:maxCount 1 ; sh:datatype xsd:dateTime ] ;
    sh:property [ sh:path ex:validTo ;
                  sh:maxCount 1 ; sh:datatype xsd:dateTime ] ;
    sh:property [ sh:path ex:endKind ;
            sh:minCount 1 ; sh:maxCount 1 ; sh:in ( ex:BoundedEnd ex:UnboundedEnd ex:UnknownEnd ) ] ;
    sh:property [ sh:path ex:polarity ;
                  sh:minCount 1 ; sh:maxCount 1 ; sh:datatype xsd:boolean ] ;
    sh:property [ sh:path [ sh:inversePath ex:asserts ] ;
                  sh:minCount 1 ; sh:class ex:Assertion ] .

ex:AssertionShape a sh:NodeShape ;
    sh:targetClass ex:Assertion ;
    sh:property [ sh:path ex:sourceRecord ; sh:minCount 1 ; sh:nodeKind sh:IRI ] ;
```

```
    sh:property [ sh:path ex:locator ; sh:minCount 1 ] ;
    sh:property [ sh:path ex:supportedThrough ;
                  sh:maxCount 1 ; sh:datatype xsd:dateTime ] .
```

The inverse path finds assertions pointing to the claim; the second shape checks the assertion's source, locator and optional support horizon. These are deliberately local requirements, not universal rules for all RDF claims. The shape also needs conditional constraints: `BoundedEnd` requires exactly one `validTo` and no `supportedThrough`; `UnboundedEnd` requires neither; and `UnknownEnd` requires no `validTo` and exactly one assertion horizon not before `validFrom`. Express those alternatives with `sh:xone`, or with a validation query joining each assertion to its claim. Check the end/start ordering and horizon/start ordering in that same validation layer. Targeting matters: if a malformed claim lacks the type that makes it a target, this shape alone may never inspect it. The data graph supplied to validation must also include the relevant assertions; validating an isolated claim graph could report missing evidence that exists elsewhere. This shape is illustrative and unexecuted.

Additional checks should test that an end follows the start under the chosen interval convention, source identifiers resolve to retained records, and claims expected to be exclusive do not overlap for the same scope. The last check depends on domain semantics and may require SPARQL-based constraints or a separate validation query. Shape conformance tells us only that selected conditions passed for the selected graph. A fabricated register row with a well-formed date can conform, and a correct but incomplete extraction can fail. Preserve the validation report and the shapes version with the release, and investigate failures rather than silently dropping records. See the SHACL Recommendation for targets, constraint components, and validation reports.

9.4 Describe Production History with the PROV Ontology (PROV-O)

Provenance records how a representation was produced and by whom. The PROV Ontology (PROV-O) describes entities, activities, and agents, with relations between them. In this model, a retained register version is a `prov:Entity`, extraction is a `prov:Activity`, and the software or responsible organisation may be a `prov:Agent`. The resulting assertion is another entity. A minimal extension to the earlier Turtle is:

```
ex:r1 a prov:Entity .
ex:extract-r1 a prov:Activity ;
```

```
    prov:used ex:r1 ;
    prov:wasAssociatedWith ex:extractor .
ex:extractor a prov:SoftwareAgent .
ex:assertion-r1-p1 prov:wasGeneratedBy ex:extract-r1 ;
    prov:wasDerivedFrom ex:r1 .
```

This describes a possible extraction history; the example does not pretend that the activity has actually run. In a real release, identify the source version, software and configuration, run or review time, and responsible agent where known. If a person reviewed a candidate later, represent the review as a separate activity with its own inputs and outputs. The register's publisher, the person whose statement appears in minutes, the extractor, and the reviewer may all be different agents with different roles. PROV-O's qualified relations can attach roles or additional detail when a simple association is insufficient.

Provenance does not supply the authority rule. `prov:wasDerivedFrom` does not mean the register is correct, and `prov:wasAssociatedWith` does not identify an agent as the author of the original policy. Any authority rule must be recorded separately and scoped to the relevant question; the executable uses abstention on conflicting evidence. Nor does extraction time replace valid time: an assertion generated on 20 March can describe applicability on 1 March. If a register correction is ingested later, keep the earlier source and release identifiable so that both a current answer and a historical answer can be reconstructed.

9.5 Property Graphs and Cypher

A property graph presents nodes connected by typed, directed relationships. Nodes may have labels and properties; relationships may also have properties. In Neo4j, a relationship has one type and a direction, and Cypher can match it in a directed or undirected pattern. Direction is part of the model even when a particular query ignores it. The Cypher manual describes matching patterns and the results produced by Neo4j.

An initial projection could represent the register claim as `(v1:PolicyVersion)-[:APPLIES_TO {validFrom: date('2024-01-01'), validTo: date('2024-04-01'), endKind: 'bounded', polarity: true}]->(atlas:Project)`. This keeps the claim qualifiers near the relationship. For an `unknown` end, retain `endKind: 'unknown'` and put `supportedThrough` on the source-specific assertion; for an `unbounded` end, retain `endKind: 'unbounded'` and no horizon. It can work for a view whose source and release are known and whose edge identity and evid-

ence are maintained. However, if each source has a separate edge, the graph must distinguish two sources making the same qualified claim from two different claims. If the relationship stores only one source field, multiple locators or extraction histories may be awkward to represent without duplication or loss. If another entity needs to refer to the assertion, a claim/assertion node design is often clearer.

For a closer match to the RDF example, use `(:ApplicabilityClaim)` nodes connected by `:POLICY_VERSION` and `:PROJECT`, with dates on the claim; `(:Assertion)-[:ASSERTS]->(:ApplicabilityClaim)` and `(:Assertion)-[:FROM_SOURCE]->(:Source)` preserve the separate assertion. The following illustrative query retrieves the same register-backed result. It assumes native date properties, a single source node with `id: 'R1'`, and a locator on each assertion:

```
MATCH (claim:ApplicabilityClaim)-[:POLICY_VERSION]->(version:PolicyVersion),
      (claim)-[:PROJECT]->(project:Project {id: 'atlas'}),
      (assertion:Assertion)-[:ASSERTS]->(claim),
      (assertion)-[:FROM_SOURCE]->(source:Source {id: 'R1'})
WITH claim, version, assertion, source, project, date('2024-03-01') AS day
WITH claim, version, assertion, source, project, day,
     CASE
       WHEN day < claim.validFrom THEN 'outside'
       WHEN claim.endKind = 'bounded' AND day < claim.validTo THEN 'applicable'
       WHEN claim.endKind = 'bounded' THEN 'outside'
       WHEN claim.endKind = 'unbounded' THEN 'applicable'
     WHEN claim.endKind = 'unknown' AND day <= assertion.supportedThrough THEN 'applicable'
       WHEN claim.endKind = 'unknown' THEN 'indeterminate'
       ELSE 'invalid'
     END AS temporalStatus
RETURN claim.id AS claimId, version.id AS versionId,
       assertion.id AS assertionId, source.id AS sourceId,
       assertion.locator AS locator, claim.validFrom AS start,
       claim.validTo AS end, claim.endKind AS endKind,
       assertion.supportedThrough AS supportedThrough,
       claim.polarity AS polarity, temporalStatus
ORDER BY versionId, assertionId
```

This query filters on the designated register and returns `indeterminate` rather than treating a missing end as forever. Missing properties evaluate as null in relevant Cypher expressions; absence must not be mapped to `unbounded`. To show disagreement, run a separate query for the minutes and return its claim, temporal status and locator alongside the register's. To answer a two-hop path question, classify both premises and return the claim and assertion identifiers for *each* hop; the endpoints alone are insufficient evidence. Parameterise application inputs rather than constructing query strings from user-provided values. This Cypher is illustrative and unexecuted.

Cypher and SPARQL are query languages for different graph representations; Neo4j is a particular graph database product implementing Cypher. A property graph is not inherently Neo4j, and RDF is not inherently a particular vendor's triple store. Product versions and implementations differ in syntax, constraints, transaction guarantees, import options, security, and query planning. Select a documented version for any reproducible example. Graph-shaped syntax makes traversals legible, but it does not guarantee that a query is fast or that a path is semantically meaningful.

9.6 What Is Lost When a Graph Is Simplified?

The following comparison assumes that the starting records contain the identified claims, assertions, and source information described above. It compares mappings, not the inherent expressive power of RDF, property graphs, or relational tables. Each richer representation can preserve the relevant information if the mapping is designed and tested to do so.

Mapping or projection	Retained	Lost or made ambiguous without extra fields
Qualified claim plus separate assertions	Version, project, interval, end kind, polarity, assertion IDs, source, locator and support horizon; disagreement can remain visible.	Nothing among these listed fields if all are mapped faithfully; extraction history, validity convention and release identity still need explicit representation.
One direct version-to-project edge with dates	Endpoints and stored interval, if the edge also carries end kind and polarity.	Source, locator, independent assertions, support horizon and indeterminate status unless separately attached; an unknown end may be mistaken for an unbounded one.

Mapping or projection	Retained	Lost or made ambiguous without extra fields
One unqualified version-to-project edge	Endpoints and relation type.	Interval, conditions, assertion identity, provenance, polarity, and whether the relation is merely reported or accepted.
Set of unique subject–predicate–object triples	Distinct triple values.	Repeated identical occurrences cannot encode the number or independence of sources; dates and evidence disappear unless modelled in additional triples.
Simple analytical graph collapsing edges by endpoints	Connectivity for the selected projection.	Parallel claims and their predicates, periods, polarity, sources, and sometimes direction, depending on the projection.
Name-only person node for the minutes' Alex	The surface name.	The difference between a mention and an identified person; merging with either directory person would invent an identity decision.

Loss is relative to the questions. A connectivity-only graph may be suitable for a labelled exploratory figure, provided the release states its selection rules and links back to the detailed records. It is unsuitable as the only evidence for who asserted a dated relationship. A round trip should compare stable identifiers, typed values, intervals, end kinds, support horizons, assertion multiplicity, source locators, polarity, unresolved mentions, and release information, not

merely node and edge counts. If a target cannot represent a field directly, retain a documented sidecar or declare the export lossy; never silently reconstruct an unknown end as unbounded or otherwise missing information as fact.

9.7 Storage and Workload Determine the Boundary

The comparison above identifies information a mapping must preserve; it does not choose an engine. That choice also depends on which questions must be served, how often data changes, and the cost of operating and checking the resulting system.

A graph model describes data and query meaning; a storage engine chooses physical structures to retrieve it. A table can store nodes and edges as rows with identifiers and use joins to follow paths. An RDF store may index permutations of subject, predicate, object and graph to find triples for different binding patterns. A property-graph engine may use indexes to find starting nodes and adjacency-oriented structures to expand relationships. These are common design approaches, not universal guarantees: engines vary, and a query planner may combine indexes, scans, joins, caching and traversal operators. Neo4j documents multiple store formats, so do not infer current physical layout or performance from a generic description of an older release.

Starting-point selectivity matters. Finding Atlas by a stable indexed ID and expanding a small, bounded neighbourhood is a different workload from scanning all claims for a date range or aggregating across every policy. A high-degree node can make even a short traversal expensive; an unbounded path can produce a very large number of possible paths or encounter cycles. A relational query can be efficient for repeated fixed-depth joins, and a graph database can also scan and aggregate. Measure actual plans, cardinalities, cache conditions, ingestion costs, and result size rather than assuming that one physical model wins every query.

DuckDB's role in the Northbridge construction route is to hold and query the tabular records produced by Python: it supports joins, filtering and aggregation, and its SQL also supports recursive common table expressions for iterative queries. It is not necessary to add a server merely because the data represents a graph. A separate RDF serving layer becomes attractive when shared RDF identifiers, a SPARQL interface, RDF interchange, or SHACL validation are central requirements. A property-graph service becomes worth testing when interact-

ive neighbourhood and path queries, graph-oriented application development, or a particular operational requirement justify it. Neo4j is one concrete choice within the latter category, not a synonym for a graph database.

Compare candidates using the *same* versioned data and questions. Include a register-scoped date query, a two-hop path returning evidence for every edge, a minutes disagreement query, and an unresolved-mention query. Add representative larger synthetic distributions only if they preserve useful properties such as degree skew and assertion multiplicity. Measure build and update time, storage, warm and cold query latency, throughput under expected concurrency, and the cost of exporting evidence. Fix hardware, versions, indexes, dataset, and result semantics; inspect plans and report failures as well as successful timings. A tiny Northbridge example tests correctness and integration, not production scalability. Include backup, access control, deployment, and skills in the decision, because a modest query-time improvement can be outweighed by the cost of maintaining another service.

9.8 A Bounded Future Neo4j Smoke Test

A later integration can test the mapping without making Neo4j a prerequisite for the canonical offline route. Use an isolated, single-node Neo4j Community container with an explicitly pinned image version or digest and a disposable database volume. Bind the service only as needed for the local test, use test-only credentials supplied through the test environment, and remove the test container and its disposable data after the run. Record the image, driver and Cypher versions and exact command in the repository's container workflow. This is a proposed test design, not an executed test or a production configuration.

Load the same frozen fixture through a documented mapping using stable application IDs for versions, projects, claims, assertions and sources. Preserve the original source locators, date values, polarity, and unresolved mentions; do not use internal database IDs as external identity. Create a uniqueness constraint on the selected stable IDs where supported by the pinned edition, and explicitly test required fields in the loader or validation query. A uniqueness constraint alone does not require every node to carry the property. Make loading idempotent under the chosen keys, and verify that a second load creates no extra nodes, relationships, or assertions. Consult the pinned version's constraint documentation for exact syntax and availability.

The smoke test has bounded acceptance cases:

1. Compare the loaded claim and assertion IDs, qualifiers, polarity, source IDs and locators with the frozen canonical export; fail on missing or extra records rather than merely comparing totals.
2. Query a dated applicability claim and a fixed two-hop path, returning the evidence for each hop. Compare ordered results with the canonical implementation under the *same* selection and conflict rules.
3. Return the minutes' competing assertion and its locator without deleting or silently resolving it; retain the fixture's unresolved Alex mention.
4. Reject or report an unknown endpoint, malformed interval, missing evidence, and duplicate stable ID. Test an end boundary on 1 April explicitly.
5. Apply a small, explicitly defined correction as a new source or assertion version, verify the changed current answer, and verify that the earlier release remains reconstructible. If release history is not yet implemented, mark this case blocked rather than claiming success.

Exercise only the fixed query patterns needed for these cases, using parameterised inputs and a timeout. Capture exit status and assertion failures, and clean up the test's own resources even on failure. This verifies mapping and basic operation on the fixture; it does not establish availability, security, disaster recovery, production throughput, or a performance advantage. Neither this design nor the illustrative Cypher above is evidence that Neo4j has been run.

10 Analyse a Projection in R

The companion `examples/r/knowledge_graph.R` hard-codes the fixture's eight entity identifiers and five positive-projection relations. It uses `igraph` to create a directed graph, and `tidygraph` to calculate node summaries. It does not read the JSON or query DuckDB, so changes to the fixture require the companion data to be kept in sync. This projection intentionally drops end kind, support horizon, polarity, provenance and claim identity; it is therefore undated and cannot implement the indeterminate answer policy. The igraph R documentation describes the graph operations.

Run the companion from the repository root with `just examples knowledge_graph knowledge-graph-r`. The command executes the pinned R runtime

and checks the path, component count, vertex count, and edge count. For an interactive exploration, open the script after the check and inspect the printed `node_summary`; the checked command is the reproducible baseline, while interactive filtering and plotting are exploratory operations.

The essential construction is short because the graph has already been reduced to an edge list, not because the modelling problem has disappeared. `vertices` preserves the two isolated Alex entities, and `relations` preserves edge types and unit weights for this particular structural analysis. `graph_from_data_frame()` joins those tables by the `name` column and creates a directed graph; it does not infer that two equal labels denote the same person.

R:

```
graph <- graph_from_data_frame(
  relations,
  directed = TRUE,
  vertices = entities |> rename(name = id)
)

path <- shortest_paths(
  graph,
  from = "policy:travel-v1",
  to = "org:northbridge",
  weights = E(graph)$weight,
  mode = "out",
  output = "vpath"
)$vpath[[1]]

weak_components <- components(graph, mode = "weak")
```

The companion converts the path vertices to labels and reports `Northbridge Travel Policy v1 -> Atlas -> Northbridge`, with unit cost 2. It reports three weak components: the main group and the two isolated Alex vertices. The `tidygraph` transformation then adds total degree and component membership to each node, which is useful for inspection but does not change the evidence represented by the graph.

This is a projection analysis, not a second claim store. The path is a sequence of edges in the selected positive topology; it does not establish that the policy was valid on the requested date, that the register outranks the minutes for every purpose, or that the path is causal. The example therefore demonstrates both the value of graph operations and the reason to return to the DuckDB claims and assertions when an answer needs dates, polarity, provenance, or source-specific evidence.

10.1 Build the Positive Projection

The edge list has one row per directed relation. Its five rows appear in the edge-list table; each has weight 1. The vertex table also supplies all eight identifiers, including the two Alex entities that have no edges. Passing that table to `graph_from_data_frame()` preserves those isolated vertices rather than constructing vertices solely from edge endpoints.

Source	Relation	Target
`policy:travel-v1`	`applies_to`	`project:atlas`
`policy:travel-v1`	`owned_by`	`person:morgan-lee`
`project:atlas`	`belongs_to`	`org:northbridge`
`policy:travel-v2`	`applies_to`	`project:atlas`
`project:orion`	`belongs_to`	`org:northbridge`

10.2 Interpret Paths and Components

Starting at `policy:travel-v1`, the outgoing `applies_to` edge reaches Atlas; its outgoing `belongs_to` edge reaches Northbridge. The two edge weights add to 2. The `owned_by` edge leads to Morgan Lee and does not continue to Northbridge in this projection. Reversing the question is different: `mode = "out"` cannot traverse these edges backwards. For weak components, however, ignore direction while grouping vertices connected by any sequence of edges. The first six entities form one component, and each isolated Alex entity forms a component of one, giving three in total. The node summary's total degree counts incident edges regardless of direction; it is a structural count, not a measure of a person's importance or the quality of the evidence.

The script asserts a directed shortest path from version 1 through Atlas to Northbridge, with total cost 2 under its unit weights. It also asserts three weakly connected components: the main connected group and the two isolated Alex entities. Weak connectivity ignores edge direction; the shortest path uses outgoing edges. Neither calculation establishes the authority, temporal validity or truth of the path. Weights here are assigned unit costs, not confidence scores.

The projection collapses the positive `c4` and `c6` assertions into one version-2 edge, discards `c5` and all dates, source IDs and locators, and retains `c1` even outside its validity interval. The R graph contains no claim IDs on edges, so a

path cannot itself trace each step back to its evidence; return to the claims table or build an evidence-preserving mapping. A dated or source-selected analysis requires a different, explicitly defined projection.

11 Validate, Evaluate, and Diagnose

This section separates three questions that are often conflated: whether the records satisfy declared constraints, whether rules derive a conclusion, and whether a source supports an assertion. It then turns those distinctions into evaluation cases and release decisions, so a passing database check cannot be mistaken for evidence that the graph is true or complete.

11.1 Validation, Inference and Verification

These operations answer different questions. **Validation** asks whether records satisfy declared constraints. The executable rejects duplicate IDs, unknown source and entity references, invalid date and end-kind combinations, invalid polarity or empty predicates, and a claim mention that fails the source-and-participant check. It also checks that the `relations` entries are unique, have positive weights and equal the set of positive claim triples. Its negative tests mutate copies of the fixture to exercise unknown entities, malformed temporal fields, a mismatched mention, a duplicate ID and a selected candidate on an abstention. The construction slice separately checks exact source spans, accepted/rejected/abstained identity decisions and a refused unsupported date phrase. Passing those checks says that these particular rules held for this input; it does not establish that the source text actually supports any claim.

The refusal and validation trace makes the boundary observable. The retained sentence at `S2:1`, “Travel Policy v1 applies to Atlas from sometime next spring.”, matches none of the supported date and sentence patterns. The executable returns no candidate for that record and a refusal with its source, method and reason `no supported date and sentence pattern`; it does not invent a date. For selected candidates, canonical comparison fails on a missing, duplicate or differing constructed claim. The ledger validator then checks its own structural rules, including the fixture’s references and temporal combinations; mutation tests confirm that specific invalid copies are rejected. This is a sequence of executable checks, not a human review of source truth. The refusal is separate

from the seven curated-and-constructed ledger rows.

The projection check compares positive triples, not dates, provenance, credibility or the numerical meaning of weights. As the R analysis illustrates, passing it does not make the projection a source-resolved, dated view.

The same distinction helps diagnose a failed answer. If the minutes' negative assertion `c5` is absent, inspect retrieval and extraction before changing the graph schema. If `c5` is present but the answer ignores it, inspect the evidence-selection or conflict policy. If the answer cites `c1` for a date after its bounded end, inspect temporal filtering. If Morgan is linked correctly but Alex is merged without an identifier, inspect identity resolution and its abstention rule. Each failure points to a different repair and should be recorded with the source span, intermediate claim or candidate decision, selected evidence, and policy version that produced the answer.

Inference derives a conclusion from premises under an explicit rule. For example, a system could define a rule that turns an `applies_to`/`belongs_to` path into a carefully named organisational association. The current Python example only returns the path; it does not implement that rule or materialise a new claim. Before adding it, specify its meaning, acceptable predicates, scope, source restrictions and temporal overlap. If two half-open input intervals overlap, the derived relationship can hold at most during their intersection; if they do not overlap, the path is not evidence of a simultaneous relationship. Record both premise IDs, the rule version and the derivation run, so a corrected premise or rule can invalidate the result. A derived association is not the same as an explicit statement in the register.

Verification checks whether an assertion is supported by the appropriate evidence and is adequate for the question. A reviewer could locate the retained register version, inspect its Atlas entry, confirm the version and interval, and record the review and its limitations. Checking that `c1.source` refers to `s-register` is validation; comparing `c1` with the actual register is verification. The synthetic excerpts permit comparison with the retained sample text, but neither they nor the fixture supply complete underlying documents or independent external evidence, so they cannot demonstrate that external verification step. It can demonstrate the structure of a review workflow and the need to abstain when the available evidence conflicts.

For RDF data, SHACL specifies validation of a data graph against shapes and produces a validation report. It does not make a conforming graph factually correct. Likewise, the DuckDB schema above and the Python checks are not a SHACL implementation. If a system validates inferred data, record whether validation ran on asserted data only or on an expanded graph, and keep the underlying asserted data distinguishable from derived results.

11.2 Gold Sets and Useful Measures

Build an evaluation set from questions and independently adjudicated evidence, not merely from rows copied from the graph being tested. A useful gold item contains the question, entity and predicate scope, requested valid date, source boundary, expected answer or abstention, supporting and opposing evidence identifiers, and an explanation of the adjudication. Record who reviewed it, the evidence version and the policy version. The fixture's date cases are useful regression examples, but their expected outputs were chosen from the same synthetic input and policy; passing them does not estimate accuracy on unfamiliar documents.

For the conservative target policy, a small regression table is:

Question for version 1 and Atlas	Expected selected evidence	Expected policy output
31 December 2023	none	`abstain: no evidence`
15 March 2024	`c1` positive, `c5` negative; both applicable	`abstain: conflicting evidence`
16 March 2024	`c1` applicable, `c5` indeterminate	`abstain: indeterminate temporal scope`
1 April 2024	`c1` outside, `c5` indeterminate	`abstain: indeterminate temporal scope`
15 April 2024	`c1` outside, `c5` indeterminate	`abstain: indeterminate temporal scope`

Add a boundary case for 1 April: `c1` is excluded at its bounded end, while the unknown-ended `c5` is indeterminate after its support horizon. A dated two-hop case should classify both edge intervals; an outside premise makes the path outside, while an indeterminate premise makes the path indeterminate. A proven-

ance case should check source, locator and mention, and that a missing mention such as `c7` does not eliminate the claim. The fixture records `m-alex` as unresolved and `r2` as abstaining between two candidates; the validator checks this representation, while the separate bounded resolver executes the synthetic identity cases described above.

Separate stages in the scorecard. For extraction, compare proposed source assertions with independently reviewed assertions and count correct, missing and spurious records. For entity resolution, evaluate links and non-links, especially same-name people and changing names. For retrieval, assess whether all required supporting and opposing passages were returned. For final answers, measure correctness with respect to the specified evidence and policy, as well as whether the cited evidence actually supports each answer. A correct label with an unrelated citation is an evidence failure. Report results by slice, including ambiguous identities, negative claims, conflicts and temporal boundaries; aggregate accuracy can conceal the cases that motivate a knowledge graph.

Precision is correct returned items divided by returned items; recall is correct returned items divided by all gold items that should have been returned. Define the matching unit before calculating either: a claim ID, a source-qualified assertion, a date-qualified answer or an evidence span can lead to different counts. A system can improve apparent precision by answering less often, so report answer coverage and the correctness of answered cases alongside the number and reasons for abstentions. If the denominator is zero, report the count and mark the ratio undefined rather than inventing a value. For a small gold set, publish counts rather than implying that a percentage gives a precise population estimate.

The following invented five-question evaluation makes those denominators concrete. The matching unit is one complete, date-qualified answer to a question; each answerable question has exactly one gold answer. An incorrect answer on an answerable question counts as both a returned false positive and a missed gold answer. `Abstain` is a system decision, not a returned answer. These labels and outcomes are hypothetical, not measurements of the fixture or the R script.

Question	Gold label	System outcome	Assessment
Q1	answer A	answer A	correct answer
Q2	answer B	answer B	correct answer

Question	Gold label	System outcome	Assessment
Q3	answer C	abstain	missed gold answer
Q4	abstain	answer D	unsupported answer
Q5	abstain	abstain	appropriate abstention

There are two correct answers among three returned answers, so answer precision is 2/3. Two of the three gold answers were returned correctly, so answer recall is 2/3. Answer coverage is 3/5 questions, and the abstention rate is 2/5; one of the two abstentions was appropriate under the gold policy. The Q4 answer raises coverage while lowering precision, whereas Q3 lowers coverage and recall. Reporting only precision would hide the missed answer and the difference between appropriate and unnecessary abstention. With five cases, these ratios explain a counting method; they do not support a population performance claim.

Construct a held-out set from source records or document families not used to tune extraction and matching rules. Splitting individual rows from the same document across development and test can leak the same wording, entities and corrections into both. Review difficult cases independently, resolve disagreements using written criteria, and retain unresolved or disputed labels rather than forcing a false consensus. Include negative examples and missing-evidence cases, but label absence as negative only when the gold-set scope justifies that conclusion. Re-run the same gold set after changing the schema, extraction pipeline, linking rules, answer policy or sources; investigate regressions before replacing expected answers.

12 Release, Update, and Govern

A release is a reproducible combination of input versions, transformations, schema and answer policy, not merely a database file. For the fixture, the inputs include `primer_knowledge_graph/examples/fixture.json`, `primer_knowledge_graph/examples/python/knowledge_graph.py`, the manifest and the primer-specific runtime definition. Record their revisions or digests, the runtime and dependency versions, validation results, evaluation results and the exact build command. The current example uses a fresh temporary DuckDB file and tests that it can be reopened; it does not itself create a release

manifest, preserve input snapshots or publish a database. Those are production extensions, not features to infer from the example.

12.1 Diagnose and Apply a Release

Use a failure to locate the stage that needs attention. A missing source passage may call for retrieval or source-coverage work; a retrieved passage with a missing claim points towards extraction; a correct claim attached to the wrong person points towards identity resolution. If the evidence is present but an answer ignores a conflicting assertion or an uncertain interval, inspect selection and answer policy before changing the extractor. Conversely, a valid-looking citation that does not support the answer is an evidence-linking failure even when the answer happens to match the gold label. Preserve the question, selected evidence, intermediate decisions and policy version so that these possibilities can be distinguished rather than treating every wrong answer as a graph-storage problem.

For an operational graph, ingest a new source version into a staging area; validate identifiers, references and intervals; compare the candidate with the previous release; run the evaluation set; and review material changes before publication. The diff should show added, changed and withdrawn assertions, affected entities and derived paths, changes in source coverage and the effect on representative questions. Build into a new versioned location rather than overwriting the only copy. Publish the version and its provenance together, and retain a tested route back to the prior release subject to retention and access rules. A reproducible build requires access to permitted input versions as well as code; a digest can identify missing material but cannot reconstruct it.

12.2 Corrections, Retractions, and Dependencies

A correction, an end of validity and a retraction are different events. Ending `c1` at 1 April describes the asserted policy interval; it does not say that the register was wrong when it made the assertion. A later correction might revise that interval and require a new source version. A retraction says that an assertion or source should no longer be relied upon under a stated policy. Preserve a record of the change, its effective and recorded times, reason, actor and replacement when applicable. Whether the old content itself can be retained depends on legal, privacy and retention obligations; a tombstone or restricted audit record

may be needed where the original must be removed. Do not silently delete an assertion and leave derived results or cached answers looking unchanged.

Trace dependencies from a changed assertion to derived claims, projections, indexes and published answers. On retraction, recompute or invalidate those dependants and reassess answers that relied on them. A derived result with two independent supporting paths may survive one withdrawn premise, but only if the remaining path still satisfies the rule and evidence policy. This dependency tracking is a proposed production feature; the Python fixture does not maintain it. For mutable sources, keep the old source version and locator where permitted so that a reviewer can explain what a previous release knew, even if the preferred answer has since changed.

12.3 Responsibility, Access, and Boundaries

Assign named responsibility for source admission, identity resolution, schema and predicate definitions, conflict policy, release approval and incident response. A data steward need not perform every task, but decisions require an accountable owner and a documented escalation route. Restrict access to sensitive sources and evidence spans, avoid publishing private attributes merely because they can be joined, and check whether downstream users can infer sensitive information from paths. Govern identifiers, corrections and deletion across replicas and caches, not only in the primary database. Review retention, permissions and intended use with the relevant owners before sharing a release.

Finally, communicate the graph's boundary with each release: which sources and dates it covers, which claims are asserted or derived, how conflicting evidence is presented, which validation and evaluation checks passed, and where a reader can report a suspected error. A reliable graph is one whose answers can be challenged and repaired; the presence of a graph database or a successful schema check is only one part of that process.

For this milestone, the omitted pieces are intentional: Neo4j execution remains a future pinned-container smoke test; the current Python example does not implement a full source extractor or update/retraction engine; the R companion remains a manually synchronised positive projection; and the synthetic fixture cannot support a research-grade coverage or accuracy study. No figures are required to make the model executable, so the accessible construction diagram and comparison tables carry that explanatory burden. These are scope disposi-

tions, not claims that the omitted capabilities are complete.

13 Further Reading

- RDF 1.1 Concepts and Abstract Syntax defines RDF graphs, triples, identifiers, literals, and the distinction between syntax and model.
- Defining N-ary Relations on the Semantic Web explains patterns for relations that need more than two participants or qualifiers.
- PROV-O provides vocabulary for describing provenance across entities, activities, and agents.
- SPARQL 1.1 Query Language and SHACL specify RDF graph querying and shape-based validation, respectively.
- Estimating the False Negatives Due to Blocking in Record Linkage examines candidate-selection error, a distinct source of identity-resolution failure.
- DuckDB documentation and the Neo4j Cypher manual provide implementation details that must be checked against the versions actually pinned for examples.