

Oh My Zsh: A Practical Guide to Your Shell

Mick Cooney — October 7, 2026

Table of Contents

Oh My Zsh: A Practical Guide to Your Shell	2
Introduction	2
What This Primer Covers	3
What This Primer Is Not	3
Assumed Background	3
Why ZSH Over Bash	3
Completion	4
Globbing	4
Parameter Expansion	4
History	5
Named Directories	5
How Oh My Zsh Works	6
The lib/ Layer	6
Enabling and Disabling Plugins	7
Choosing Plugins Without Bloating Startup	7
A .zshrc Structure That Scales	7
Plugins Worth Knowing Deeply	8
git	8
fzf	9
zsh-autosuggestions	9
zsh-syntax-highlighting	10
history	11
sudo	11
extract	11
colored-man-pages	12
command-not-found	12
timer	12
rsync	12
systemd	12
mise	13
gh	13
Commonly Worth Trying Next	13
Themes: What a Good Prompt Does	14
What Information Belongs in a Prompt	14

robbyrussell	15
agnoster	15
Powerlevel10k (p10k)	15
Quick Theme Comparison	16
Features Most OMZ Users Never Find	16
Custom Aliases and Functions in <code>custom/</code>	16
The <code>omz</code> Command	17
Smart Directory Navigation Without <code>cd</code>	17
<code>z</code> — Smarter Directory Jumping	17
ZSH Suffix Aliases	18
Global Aliases	18
ZSH Line Editor (ZLE) Widgets	18
Configuration Areas Worth Periodic Attention	19
High-Leverage Checks Most People Miss	20
Worked Example: Auditing a Real OMZ Setup	21
What This Setup Has	21
What’s Missing	21
Verify Existing Plugins Are Actually Used	22
Small Additions Worth Considering	22
Self-Audit Checklist	22
Troubleshooting Common Problems	23
Shell Startup Feels Slow	23
Prompt Changes Are Not Taking Effect	23
Completions Feel Broken or Inconsistent	24
A Plugin Causes Weird Behaviour	24
When OMZ Is Not Enough	24
Quick Reference: What to Do Next	25
Further Reading	25

Oh My Zsh: A Practical Guide to Your Shell

Mick Cooney — June 2026

Introduction

Most people who install Oh My Zsh do the same three things: change the theme, add the `git` plugin, and then forget about it for two years. The shell gets faster and prettier, but the actual productivity gain stays shallow. The plugin list grows by one every time someone on Reddit says “you need X,” but the full picture of what the framework can do — and what ZSH itself can do underneath it — never quite lands.

This primer tries to fix that. It starts with why ZSH is genuinely different from Bash (not

just cosmetically), explains how Oh My Zsh is actually structured, goes deep on the plugins and features that change how you work, and ends with a worked configuration audit you can reuse on your own setup.

What This Primer Covers

- What ZSH adds over Bash that actually matters in daily use
- How Oh My Zsh works under the hood — plugins, themes, the `custom/` directory
- The plugins worth knowing deeply, with real examples of what they do
- Themes: what a good prompt gives you and when to switch
- Advanced ZSH features that most OMZ users never touch
- A concrete worked audit and a checklist you can apply to your own shell

What This Primer Is Not

This is not a Bash-to-ZSH migration guide, and it does not cover every plugin in the OMZ repository. It also does not cover Prezto, Fish, or Nushell — all of which are worth knowing about, but that’s a different document. The focus is on getting maximum value out of Oh My Zsh specifically, for someone who already has it installed and wants to stop leaving capability on the table.

Assumed Background

You are comfortable in a terminal, have used Bash or ZSH before, and already have Oh My Zsh installed. You know what a `.zshrc` is. You don’t need to know anything about ZSH internals.

Before we dive in, a useful mental model: ZSH is Bash plus three meaningful upgrades. First, completion is context-aware rather than simple prefix matching. Second, globbing can filter by file metadata directly, so many `find | grep | awk` chains collapse into one expression. Third, the prompt and line editor are designed to be programmable interfaces, not fixed text. Oh My Zsh then adds a curated plugin/theme layer on top of those native capabilities.

Why ZSH Over Bash

It is worth spending a moment on why ZSH exists and what it actually adds, because understanding the foundation makes the Oh My Zsh layer easier to appreciate. ZSH is not Bash with a better theme engine. It has genuinely different capabilities.

Completion

ZSH's tab completion system — called `compsys` — is architecturally different from Bash's. In Bash, completion is mostly prefix matching: you type `git com` and it completes to `git commit`. In ZSH, completion is programmable and contextual. It knows what `git commit` accepts as flags. It knows that `-m` takes a string. It can complete hostnames from your SSH config, Docker container names, systemd unit names, `man` page sections, and hundreds of other context-specific things. Plugin authors write completion functions, and OMZ ships many of them.

You see this in practice every time you type `git <Tab>` and get a menu with descriptions, or type `docker run --<Tab>` and get the full flag list. Bash can approximate some of this with `bash-completion`, but ZSH's system is deeper and more consistent.

Globbering

ZSH's glob system is significantly more powerful than Bash's. This is not a feature most people discover organically, but once you know it, you reach for it constantly.

```
# Match all .log files recursively (** is a ZSH glob, not Bash)  
ls **/*.log
```

```
# Only files (not directories) modified in the last day  
ls *(m-1.)
```

```
# Only executable files  
ls *(x.)
```

```
# Files larger than 1MB  
ls *(Lm+1)
```

```
# Combine: executable files modified in the last week  
ls *(x.m-7)
```

The glob qualifiers (the characters inside (...)) filter on file metadata: type, modification time, size, permissions. This is the kind of thing you'd normally pipe through `find` with four flags; in ZSH it's a glob modifier.

Parameter Expansion

ZSH extends Bash's already capable parameter expansion with additional flags:

```
path="$HOME/projects/example-project/notes.md"
```

```
# Bash-compatible: get filename without path  
echo ${path##*/}           # notes.md
```

```
# ZSH-only: split on delimiter and get last element  
echo ${path:t}             # notes.md
```

```
# Strip extension
```

```

echo ${path:t:r}          # notes

# Directory part
echo ${path:h}            # your projects/example-project directory

# Uppercase
str="hello world"
echo ${(U)str}            # HELLO WORLD

# Split into array on /
parts=(${(s:/:)path})
echo $parts[1]            # home

```

The (U), (L), (s:delim:) and similar parameter flags are ZSH-specific. They're not a party trick; they eliminate a lot of `awk/sed` one-liners for string manipulation in scripts.

History

ZSH history is more configurable than Bash's. The key options that actually matter:

```

HISTSIZE=100000          # lines in memory
SAVEHIST=100000          # lines on disk
setopt HIST_IGNORE_DUPS  # don't record adjacent duplicates
setopt HIST_IGNORE_SPACE # don't record commands starting with space
setopt SHARE_HISTORY     # share history across sessions in real time
setopt EXTENDED_HISTORY  # record timestamp with each command

```

`SHARE_HISTORY` means that if you have three terminals open, history flows between them as each command finishes running — you don't have to close and reopen to pick up commands from another session. `HIST_IGNORE_SPACE` is the one you want for sensitive commands: prefix any command with a space and it doesn't go into history.

Worth knowing before you go copy these into your `.zshrc`: OMZ's `lib/history.zsh` already sets `HIST_IGNORE_SPACE`, `HIST_IGNORE_DUPS`, `SHARE_HISTORY`, and `EXTENDED_HISTORY` unconditionally, regardless of theme or plugins. The block above is shown for completeness — to make explicit what OMZ is doing for you — not because you need to add it yourself.

Named Directories

ZSH lets you name directories and use them like variables in paths:

```

hash -d work="$HOME/projects"
hash -d proj="$HOME/projects/example-project"

# Now you can use ~work and ~proj anywhere
cd ~proj
ls ~work/another-project

```

Put these in your `.zshrc` and they persist. It's the equivalent of shell aliases for paths, except they work in any context where a path is accepted.

How Oh My Zsh Works

Understanding the structure of OMZ makes it easier to know what to change and where. The repository lives at `~/.oh-my-zsh/` and has a clear layout:

```
~/.oh-my-zsh/  
lib/          # Core ZSH configuration loaded at startup  
plugins/      # Bundled plugins (git, docker, fzf, etc.)  
themes/       # Bundled themes  
custom/       # Your overrides: themes, plugins, functions  
  plugins/    # Third-party or custom plugins go here  
  themes/     # Custom themes go here  
  aliases.zsh # Put custom aliases here  
  functions.zsh # Put custom functions here (or any .zsh file)  
templates/    # Template for new .zshrc  
tools/        # Install/update scripts
```

When your shell starts, OMZ loads `oh-my-zsh.sh`, which: 1. Loads everything in `lib/` (history config, completion setup, key bindings, utility functions) 2. Sources each enabled plugin's `.plugin.zsh` file 3. Sources everything in `custom/` that ends in `.zsh` 4. Loads the theme

The `custom/` directory is where your personalizations live and where they survive OMZ updates. If you write a custom function and put it in `~/.oh-my-zsh/custom/myconfig.zsh`, it gets loaded automatically. If you put the same function in a bundled plugin file, the next `omz update` will overwrite it.

The theme loading last matters in practice: because it runs after `custom/`, a theme can clobber prompt-related settings you set in a custom file. If a customization to your prompt doesn't seem to be taking effect, check whether the theme is overwriting it on load.

The `lib/` Layer

Most users never look at `lib/`, but it does a lot. The files there configure:

- `completion.zsh` — sets up `compsys`, enables menu completion, configures case-insensitive matching
- `history.zsh` — the history options described earlier
- `key-bindings.zsh` — registers `Ctrl+R` for history search, `Ctrl+A/E` for line navigation, etc.
- `git.zsh` — the helper functions used by git-aware themes
- `functions.zsh` — utility functions used internally, like `omz_urlencode`

You rarely edit these directly, but knowing they exist explains why certain behaviors appear without you configuring them.

Enabling and Disabling Plugins

The `plugins` array in `.zshrc` is straightforward:

```
plugins=(
  git
  docker
  fzf
  zsh-autosuggestions
)
```

Each name must match either a directory in `~/.oh-my-zsh/plugins/` or `~/.oh-my-zsh/custom/plugins/`. OMZ looks in both places. Third-party plugins (like `zsh-autosuggestions`) are cloned into `custom/plugins/` and added to the list.

The startup cost of plugins is real. Each plugin sources a file. Most are small, but a plugin that initializes a large tool (like a package manager) adds perceptible latency. Keep only what you actually use.

Choosing Plugins Without Bloating Startup

The OMZ plugin list is large enough that it is easy to over-install and call it productivity. A practical selection framework:

1. Keep plugins that remove frequent friction from your real workflow (for example `git`, `fzf`, `sudo`, `extract`).
2. Keep plugins that provide completions or aliases for tools you use weekly (`gh`, `docker`, `systemd`, `mise`).
3. Remove plugins that only looked useful once but do not change your daily command lines.

As a baseline, most people land in the 10-15 plugin range. More can be fine, but measure rather than guess:

```
time zsh -i -c exit
```

Run this before and after plugin changes. If startup jumps meaningfully, the extra plugin had a real cost.

A `.zshrc` Structure That Scales

Many OMZ setups become hard to reason about because `.zshrc` turns into an unsorted script.

A predictable layout avoids that:

```
# 1) Environment and path basics
export EDITOR=vim
export PATH="$HOME/bin:$PATH"

# 2) Core OMZ settings
export ZSH="$HOME/.oh-my-zsh"
```

```

ZSH_THEME="robbyrussell"

# 3) Plugin list (must be set before sourcing OMZ)
plugins=(git fzf zsh-autosuggestions)

# 4) Load OMZ
source "$ZSH/oh-my-zsh.sh"

# 5) Local options and bindings
setopt AUTO_CD
setopt CORRECT

# 6) Project/personal customizations
# (aliases/functions in ~/.oh-my-zsh/custom/*.zsh)

```

Two ordering rules matter most in practice:

1. The `plugins=(...)` list must be defined before `source "$ZSH/oh-my-zsh.sh"`.
2. `zsh-syntax-highlighting` must be last in your `plugins` list.

If something “doesn’t load,” these two checks fix a surprising number of cases.

Plugins Worth Knowing Deeply

This is not a list of every plugin. It is a deep look at the ones that change how you work, with concrete examples of what they actually do.

git

The `git` plugin ships a very large alias set. Most people use `gst` (`git status`) and `gaa` (`git add --all`) and call it done. The more interesting ones:

```

# Commonly used
gst  # git status
ga   # git add
gaa  # git add --all
gcmgs # git commit -m
gp   # git push
gl   # git pull
gco   # git checkout
gcb   # git checkout -b
gd    # git diff
gds   # git diff --staged
glog  # git log --oneline --decorate --graph

# Less obvious but very useful
gpri  # git pull --rebase --autostash
gcf   # git config --list
gclean # git clean -id (interactive clean)
gwip  # commit a work-in-progress stash
gunwip # undo the last WIP stash commit

```

The `gwip` / `gunwip` pair is genuinely useful when you need to quickly switch branches mid-work without a full commit. `gwip` creates a temporary [WIP] commit; `gunwip` undoes it and restores the working state.

The plugin also provides `git_prompt_info()`, which most themes use to show the current branch and status in the prompt.

fzf

`fzf` is a fuzzy finder for the terminal. The OMZ plugin wires it into three key bindings:

```
Ctrl+R  - fuzzy search your command history
Ctrl+T  - fuzzy find a file in the current directory tree
Alt+C   - fuzzy cd into a subdirectory
```

Most people know `Ctrl+R` for history. The other two are underused. `Ctrl+T` is faster than typing a path when you remember the filename but not the full path. `Alt+C` is faster than `cd` with tab completion when you're navigating several levels deep.

`fzf` also integrates with commands directly:

```
# Preview files while browsing
fzf --preview 'cat {}'

# Select one of *your* processes, then send the normal TERM signal.
# Cancel or an empty selection does nothing. Review the command before running it.
selected_pid="$(
  ps -u "$USER" -o pid=,command= |
    fzf --prompt='process> ' |
    awk '{print $1}'
)"
[[ -n "$selected_pid" ]] && kill -- "$selected_pid"

# Open a selected local branch; canceling leaves the current branch unchanged.
selected_branch="$(git branch --format='%(%(refname:short))' | fzf --prompt='branch> ')"
[[ -n "$selected_branch" ]] && git switch -- "$selected_branch"

# Put a selected history entry on the command line for review; it does not run yet.
selected_command="$(history | fzf --prompt='history> ' | awk '{\$1=""; sub(/^ /, ""); print}')"
[[ -n "$selected_command" ]] && print -z -- "$selected_command"
```

The underlying tool accepts any input on stdin and returns the selected line on stdout, so it composes with everything. The OMZ plugin just provides the shell integration; learning `fzf`'s flags unlocks the full power. Treat a process picker as a destructive operation: inspect the selected command, start with the normal `TERM` signal, and reserve `kill -9` for a process that has not responded. Do not use `eval` to re-run fuzzy-selected history: loading the command with `print -z` gives you a final chance to inspect or edit it before pressing Enter.

zsh-autosuggestions

This plugin shows a greyed-out suggestion as you type, based on your history. The plugin's model splits into two groups of key bindings: widgets that accept the *whole* suggestion, and

widgets that accept it one word at a time.

```
# You type:
git commit

# It shows (in grey):
git commit -m "fix typo in README" ← suggestion from history

# Right arrow, End, and Ctrl+F all accept the whole suggestion
# Alt+F accepts one word at a time
```

By default, right arrow (`forward-char`), End (`end-of-line`), and Ctrl+F (also bound to `forward-char` in emacs mode) are all in `ZSH_AUTOSUGGEST_ACCEPT_WIDGETS` — that array controls which movement widgets, when invoked, accept the entire suggestion rather than just moving the cursor. There's no character-at-a-time acceptance by default; anything in that array takes the whole line.

Word-by-word acceptance is a separate array, `ZSH_AUTOSUGGEST_PARTIAL_ACCEPT_WIDGETS`, and it's driven by `forward-word` — Alt+F in emacs mode. There's no default Ctrl+Space binding for this.

If you want a custom key to accept a suggestion (whole or partial), you don't invent a new widget name — you bind an existing movement widget and add it to the relevant array. For example, to make Ctrl+Space accept one word at a time:

```
bindkey '^ ' forward-word
ZSH_AUTOSUGGEST_PARTIAL_ACCEPT_WIDGETS+=(forward-word)
```

One tuning option worth knowing: by default it only suggests from history. You can also enable completion-based suggestions:

```
ZSH_AUTOSUGGEST_STRATEGY=(history completion)
```

This means if history has no match, it falls back to ZSH completions.

zsh-syntax-highlighting

This plugin is not in the default OMZ bundle — it requires a separate install. It is, however, one of the highest-value things you can add. It highlights commands in real time as you type:

- Commands that exist: green
- Commands that don't exist: red
- Strings and quoted arguments: yellow

Options/flags and pipes/redirects/semicolons are recognized as distinct token types internally, but the default `main` highlighter styles leave them unstyled — no color unless you configure `ZSH_HIGHLIGHT_STYLES` yourself. If you want flags or separators to stand out visually, that's a `ZSH_HIGHLIGHT_STYLES` customization, not default behavior.

The value is catching typos before you press Enter. You type `pythno script.py` and the red highlight catches it immediately. You type `ls --recusrive` and it's red before you hit Enter. After using it for a week you will miss it in any shell that doesn't have it.

Install:

```
git clone https://github.com/zsh-users/zsh-syntax-highlighting.git \
  ${ZSH_CUSTOM:- ~/.oh-my-zsh/custom}/plugins/zsh-syntax-highlighting
```

Then add `zsh-syntax-highlighting` to your `plugins` array. It must be **last in the list** — this is important; the plugin works by modifying the line buffer, and it needs to run after everything else.

history

The `history` plugin provides convenient aliases:

```
h      # full history (with timestamps if HIST_STAMPS is set in .zshrc)
hs     # history | grep (case-sensitive)
hsi    # history | grep (case-insensitive)
# Find all git commands you've run
hs git

# Find recent docker run commands
hsi "docker run"
```

Simple but far faster than typing `history | grep` every time.

sudo

Press `Esc Esc` (two taps) to prepend `sudo` to the current command line or re-run the last command with `sudo`. No plugin is simpler or more immediately useful.

```
# You run:
apt install something-big
# Permission denied.

# Press Esc Esc
# Line becomes:
sudo apt install something-big
```

extract

The `extract` plugin provides a single command `x` (or `extract`) that works on any archive format:

```
x archive.tar.gz
x archive.zip
x archive.bz2
x archive.7z
x archive.tar.xz
x archive.rar
```

You never need to remember whether it's `tar -xzf` or `tar -xjf` or `unzip` or `7z x`. The plugin detects the format and uses the right tool. It works as long as the relevant tool is installed on the system.

colored-man-pages

Makes man pages render with color instead of monochrome. The improvement is significant for readability, especially for long man pages with lots of structure. No configuration needed; just include it in your plugins list.

command-not-found

When you type a command that doesn't exist, instead of a bare "command not found" error, the shell suggests the package you need to install:

```
$ tree
zsh: command not found: tree
```

Command 'tree' not found, but can be installed with:
sudo apt install tree

Requires command-not-found to be installed on the system (most Ubuntu/Debian systems have it). Saves a round-trip to the package manager search.

timer

Shows how long each command took, appended to the right side of your prompt after the command completes. Useful for scripts and builds where you want a rough sense of runtime without explicitly using `time`.

```
some-long-command [12s]
```

No configuration needed. If you find it noisy for short commands, set a minimum threshold:

```
TIMER_THRESHOLD=2 # only show if command took > 2 seconds
TIMER_FORMAT='%d seconds'
```

rsync

Provides aliases for common `rsync` patterns:

```
rsync-copy      # rsync --partial --progress -h --archive (archive, progress, human-readable)
rsync-move      # rsync --partial --progress -h --remove-source-files --recursive
rsync-update    # rsync --partial --progress -h --update --archive (skip files newer at destination)
rsync-synchronize # rsync --partial --progress -h --update --archive --delete (full sync)
```

The flags are ones you'd reach for often but never quite remember the exact combination of.

systemd

Provides short aliases for common `systemctl` operations. There's no `journalctl` coverage in this plugin — if you want short aliases for log commands, those are worth adding yourself.

```
sc-status      # sudo systemctl status
sc-start        # sudo systemctl start
sc-stop        # sudo systemctl stop
sc-restart     # sudo systemctl restart
sc-enable      # sudo systemctl enable
sc-enable-now  # sudo systemctl enable --now
```

```
sc-disable      # sudo systemctl disable
sc-disable-now  # sudo systemctl disable --now
sc-mask-now     # sudo systemctl mask --now
sc-list-units   # sudo systemctl list-units
```

The privileged aliases all embed `sudo` for you, so you don't type it separately. Every one of them also has a `scu-` twin that drops the `sudo` and adds `--user`, for managing your own user-level units instead of system-wide ones — `scu-status` is `systemctl --user status`, `scu-restart` is `systemctl --user restart`, and so on. If you run anything as a `systemd` user service, the `scu-` family is arguably more useful day to day than the system-wide aliases.

If you interact with `systemd` services regularly, these cut down the typing considerably.

mise

The `mise` plugin initializes `mise` (the polyglot version manager, formerly `rtx`) and enables its completions. It runs `mise activate zsh` during shell startup so that tool versions are correctly set in every shell session. Without this, you'd need to call `eval "$(mise activate zsh)"` manually in your `.zshrc`. That `eval` is appropriate only for initialization code emitted by a locally installed, trusted executable; never adapt the pattern to execute output fetched from the network.

gh

Completions for the GitHub CLI (`gh`). The plugin runs `gh completion --shell zsh` and caches the result, so you get tab-completion for `gh`'s commands and flags. It doesn't dynamically complete repository names or PR/issue numbers — that would need live API calls, which this plugin doesn't make. If you use `gh` frequently, the command/flag completion alone saves a lot of flag-hunting.

Commonly Worth Trying Next

These are common upgrades in mature setups. None are mandatory, but each can be high leverage in the right workflow.

1. vi-mode

- Gives Vim-style command-line editing in ZLE.
- Best if you already use Vim/Neovim motions.
- Skip if you strongly prefer emacs bindings.

2. direnv integration

- Auto-loads per-project environment via `.envrc`.
 - Excellent for project-specific `PATH`/env separation.
 - Requires the `direnv` binary and disciplined `.envrc` review.
3. **kubect1 and cloud CLI plugins (aws, gcloud, azure)**
- Useful completion and aliases when those CLIs are daily tools.
 - Not worth loading if you use them only occasionally.
4. **One version manager strategy (mise or asdf)**
- For polyglot stacks, one manager lowers cognitive overhead.
 - Avoid stacking multiple managers unless compatibility forces it.
5. **starship prompt (theme alternative)**
- Strong choice for cross-shell consistency with TOML config.
 - Worth trialing if you routinely jump between shells.

Themes: What a Good Prompt Does

The theme controls what your prompt looks like. Most people pick one that looks appealing and stop there. But a well-designed prompt is actually functional: it puts the right information in front of you at the right time.

What Information Belongs in a Prompt

A practical prompt should show:

1. **Current directory** — always. Abbreviated to the last 2-3 components if deep.
2. **Git state** — current branch, whether there are staged changes, unstaged changes, untracked files, and whether the branch is ahead/behind the remote.
3. **Last command exit code** — some indication of whether the last command succeeded or failed.
4. **Optionally:** active virtual environment, tool versions, execution time, `user@host` for remote sessions.

What a prompt should not do: show things that never change (always the same user on the same machine), show timestamps on every line (the `timer` plugin handles that better), or take noticeable time to render.

robbyrussell

The default theme. Clean, minimal:

```
→ example-project git:(main) ✕
```

Shows directory and git branch. The ✕ indicates there are uncommitted changes. It's good for its simplicity, but it doesn't show whether changes are staged vs unstaged, doesn't show remote divergence, and gives no indication of exit status.

agnoster

A powerline-style theme that uses special Unicode characters to create a segmented prompt: `you@hostname ~/projects/example-project main ✕`

(The segments have colored backgrounds in the actual terminal.) Shows user, host, path, git branch, and git state. More information than robbyrussell. Requires a Nerd Font or Powerline-patched font; without one, the segment characters render as boxes.

A common agnoster variant, `agnoster-timestamp-newline`, adds a timestamp and puts command input on its own line, which makes long paths more readable.

Powerlevel10k (p10k)

Powerlevel10k is a third-party theme, not bundled with OMZ. As of October 7, 2026, its [upstream README](#) explicitly warns of very limited support: no new features are planned, most bugs will remain unfixed, and help requests will be ignored. An existing setup can still work well, but do not assume that future compatibility problems will be fixed. For a new setup, compare its features with [Starship](#) and [Pure](#) before accepting that maintenance constraint.

What makes p10k different:

- **Configuration wizard** — runs `p10k configure` and walks you through every prompt option interactively, showing previews. You end up with a `.p10k.zsh` config that captures exactly what you chose.
- **Instant prompt** — p10k renders a partial prompt immediately, before the shell finishes loading. Shell startup feels instant even with slow plugins.
- **Async segments** — git status and other slow segments render asynchronously so they don't block input.
- **Transient prompt** — old prompts in the scroll buffer collapse to a minimal form, keeping the terminal cleaner.

For a full git-aware, multi-context prompt (git state, virtualenv, node version, exit status, command timing), p10k's instant prompt and configuration wizard remain useful features. Choose it if those features justify the limited support for your setup.

Install:

```
git clone --depth=1 https://github.com/romkatv/powerlevel10k.git \
  ${ZSH_CUSTOM:-$HOME/.oh-my-zsh/custom}/themes/powerlevel10k
```

Then set `ZSH_THEME="powerlevel10k/powerlevel10k"` and run `p10k configure`.

Quick Theme Comparison

If you are deciding between common options, this is the short version:

Theme	Strength	Tradeoff	Best For
robbyrussell	Minimal, no setup	Limited status detail	Simple prompt, low cognitive load
agnoster	Denser git/path signal	Needs patched font, can feel busy	Users who want always-visible context
powerlevel10k	Rich status, fast rendering, wizard	Very limited upstream support; extra config	Users who accept the maintenance constraint
pure	Clean async prompt	Less built-in segment breadth	People who want modern and minimal
starship	Cross-shell consistency	External binary and separate config	Mixed-shell workflows

Features Most OMZ Users Never Find

Custom Aliases and Functions in `custom/`

Any `.zsh` file in `~/.oh-my-zsh/custom/` is sourced automatically. This means you don't need to clutter `.zshrc` with personal aliases — put them in `~/.oh-my-zsh/custom/aliases.zsh` and they load automatically and survive OMZ updates:

```
# ~/.oh-my-zsh/custom/aliases.zsh
```

```
alias ll='ls -lAh --color=auto'
```

```
alias ports='ss -tlnp'
```

```
# This contacts a third party, which sees your public IP address and request metadata.
```

```
# Do not use it from a network where that disclosure is sensitive.
```

```
alias myip='curl --fail --silent --show-error https://api.ipify.org'
alias reload='source ~/.zshrc'
alias ...='cd ../../'
alias ....='cd ../../../'
```

Functions go in the same place or their own file:

```
# ~/.oh-my-zsh/custom/functions.zsh
```

```
# Create directory and cd into it
mcd() { mkdir -p "$1" && cd "$1" }
```

```
# Quick find by name
f() { find . -name "$1*" 2>/dev/null }
```

```
# Show the last N lines of a log file with color
lf() { tail -f "${1:-/var/log/syslog}" | grep --color=auto -E "ERROR|WARN|INFO|$" }
```

The omz Command

OMZ ships a management command that most users don't know exists:

```
omz update           # Update oh-my-zsh
omz plugin list      # List all available plugins
omz plugin enable git # Enable a plugin without hand-editing .zshrc
omz plugin disable git # Disable a plugin
omz theme list       # List available themes
omz theme use agnoster # Switch theme temporarily
omz changelog        # Show recent OMZ changes
```

The `plugin list` output is useful for discovery — there are plugins for tools you use that you may not know OMZ ships.

Smart Directory Navigation Without `cd`

ZSH can change directories without typing `cd`, if you enable it:

```
setopt AUTO_CD
```

With this set, typing a directory name alone (without `cd`) changes into it:

```
# Without AUTO_CD:
cd ~/projects/example-project
```

```
# With AUTO_CD:
~/projects/example-project
# or if it's in CDPATH:
example-project
```

Combine with `CDPATH` to jump to frequently used directories:

```
CDPATH=.:~/projects
```

With this set, typing `example-project` from anywhere searches `.`, `~`, and `~/projects` for that directory name and changes into it if found.

z — Smarter Directory Jumping

The `z` plugin (bundled with OMZ) tracks which directories you visit and lets you jump to them by partial name, ranked by how often and how recently you've been there:

```
# After you've visited ~/projects/example-project a few times:
z example      # cd's to ~/projects/example-project
z project      # same

# It picks the highest-ranked match for the pattern
z notes        # might jump to ~/projects/example-project/notes
```

The ranking function (“frecency”) is frequency $\times$ recency — directories you go to often and recently rank highest. For codebases you navigate daily, z eliminates most explicit cd commands.

zoxide is a faster modern alternative with the same concept. It integrates with OMZ via a plugin and can be configured to replace cd entirely. As with other shell initialization snippets, only eval output from a locally installed executable you trust:

```
# Install zoxide, then add to .zshrc:
eval "$(zoxide init zsh --cmd cd)"
# Now 'cd' uses zoxide's frecency ranking
```

ZSH Suffix Aliases

ZSH supports suffix aliases — aliases that apply to the file extension, so the shell knows what program to use to open a file type:

```
alias -s py=python3
alias -s md=glow      # terminal markdown renderer
alias -s pdf=evince
alias -s html=firefox
```

With these, typing script.py at the prompt opens it with python3, README.md opens with glow, and so on. You don’t need to prefix the program name.

Global Aliases

Regular aliases only work at the start of a command. Global aliases work anywhere in a command line:

```
alias -g G='| grep'
alias -g L='| less'
alias -g T='| tail -f'
alias -g NE='2>/dev/null'
alias -g NUL='>/dev/null 2>&1'
# With global aliases:
ps aux G python      # ps aux | grep python
cat big_log T        # cat big_log | tail -f
some-command NUL      # some-command >/dev/null 2>&1
```

This is a ZSH-specific feature with no Bash equivalent.

ZSH Line Editor (ZLE) Widgets

ZSH’s line editor is programmable. You can write functions and bind them to key sequences:

```

# Paste last argument of last command (already bound to Alt+. by default)
# But you can write custom widgets:

# Widget: prepend sudo to the current command
prepend-sudo() {
    BUFFER="sudo $BUFFER"
    CURSOR=$((CURSOR + 5))
}
zle -N prepend-sudo
bindkey '^[s' prepend-sudo # Alt+S

```

Realize halfway through typing a command that it needs root? `Alt+S` prepends `sudo` without you having to jump to the start of the line, type it, and jump back. `BUFFER` is the whole command line as a string, and `CURSOR` is the cursor's character offset into it — direct edits to both are the basic pattern for any custom ZLE widget.

Stock `zsh` (not something `OMZ` adds) already ships a related trick: `push-line` (bound to `Ctrl+Q` in emacs mode by default). If you're mid-command and realize you need to run something else first, `Ctrl+Q` parks your current input, you run what you need, and your original command comes back on the next prompt. One catch: if your terminal has flow control enabled (`stty ixon`, common on many default configs), `Ctrl+Q` is intercepted by the terminal driver as `XON` and never reaches `zsh` at all — the key will simply do nothing. If that's the case for you, either run `stty -ixon` or use the `Esc-q` alternative binding instead.

Configuration Areas Worth Periodic Attention

Beyond plugins and themes, these settings often determine whether a shell feels excellent or annoying:

1. History policy

- Validate `HISTSIZE`, `SAVEHIST`, and history sharing behavior against real usage.
- Keep `HIST_IGNORE_SPACE` active and use leading-space deliberately for sensitive commands.

2. Completion behaviour and cache health

- Slow completion is often stale cache or plugin overload.
- Revisit completion behaviour after major toolchain changes.

3. Editing mode and keymap consistency

- Pick `emacs` or `vi` intentionally and stay consistent.
- If using `vi` mode, make insert/normal status obvious in the prompt.

4. Prompt signal-to-noise

- Keep status fields that change decisions (git state, exit code, env) and remove decorative noise.
- Re-check latency whenever adding new prompt segments.

5. **PATH ordering and shim collisions**

- Ensure one intentional winner when multiple version managers provide the same binary.
- Remove duplicate PATH appends spread across shell files.

6. **Custom file hygiene**

- Keep aliases/functions/options organized in `custom/` files instead of growing one giant `.zshrc`.
- Periodically delete stale helpers you no longer use.

7. **Terminal/font compatibility**

- Nerd/Powerline prompts require compatible fonts.
- If symbols render as boxes, fix terminal/font config before debugging shell logic.

High-Leverage Checks Most People Miss

These are small checks that often catch real issues quickly:

1. **Custom guard files are loaded at all**

- If you keep policy helpers in standalone files (for example, host-execution guards), verify they are explicitly sourced.
- A correct file in the wrong location is still inactive.

2. **Duplicate settings agree across files**

- If key behaviour is configured in both plugins and aliases/functions (for example SSH key lifetime), align them.
- Inconsistent values create hard-to-explain behaviour after reloads.

3. **Generated completions are not rebuilt every shell start**

- Prefer one-time generation for tools like `just` unless you truly need dynamic regeneration.
- Rebuilding completion scripts on every startup adds avoidable latency and extra disk I/O.

4. **Theme and prompt ownership are not mixed accidentally**

- If you use an OMZ theme, avoid silently overriding `PROMPT` later unless intentional.

- Mixed ownership causes confusing prompt changes and harder troubleshooting.
-

Worked Example: Auditing a Real OMZ Setup

This is an audit of a representative real configuration. Read it as an example process you can replicate, not as a claim that every OMZ setup should look the same.

What This Setup Has

Active plugins in this example:

```
git ssh-agent colored-man-pages command-not-found extract history
docker timer sudo gh podman systemd chezmoi rsync fzf
mise zsh-autosuggestions zsh-clause-code-shell
```

This is a well-considered list. The `timer`, `sudo`, `extract`, `history`, and `colored-man-pages` plugins are all underrated workhorses that most setups skip. `fzf` and `zsh-autosuggestions` are two of the highest-value additions in most environments. The tool-specific plugins (`docker`, `podman`, `systemd`, `gh`, `chezmoi`, `rsync`, `mise`) are appropriate for this toolchain.

The history config is solid: 100k entries, persistent logging, session sharing. Most people have 1000 entries and then wonder why old commands disappear.

What's Missing

zsh-syntax-highlighting — highest-impact missing piece.

This is the gap with the most immediate impact. Every command is colour-coded as you type it: green means the command exists, red means it does not. You catch typos before Enter, see unclosed quotes quickly, and generally get a more readable command line. It is off by default because it is third-party, but it is near-standard in mature ZSH setups.

```
git clone https://github.com/zsh-users/zsh-syntax-highlighting.git \
  ~/.oh-my-zsh/custom/plugins/zsh-syntax-highlighting
```

Add `zsh-syntax-highlighting` to the plugins list, and put it **last**:

```
plugins=(
  ...your existing plugins...
  zsh-syntax-highlighting # must be last
)
```

z for directory jumping.

For any multi-repository workflow, this pays off quickly. The `z` plugin is bundled with OMZ, so just add it to the plugins list. After a few days of normal use, `z research` or `z building` gets you directly to the right directory from anywhere. No install needed:

```
plugins=(... z ...)
```

Consider the active theme choice.

This example has `agnoster-timestamp-newline` available but uses `robbyrussell`. That may be intentional, but it is worth re-evaluating periodically. A newline layout is easier to scan in deep paths, and `p10k` gives much richer git state visibility (staged, unstaged, untracked, ahead/behind) with a quick `p10k configure` run.

Verify Existing Plugins Are Actually Used

Before adding another plugin, exercise the high-value ones already installed in this setup:

- `fzf`: use `Ctrl+T` for file arguments and `Alt+C` for directory jumping, not only `Ctrl+R`.
- `sudo`: press `Esc Esc` after a failed command to put `sudo` in front of it.
- `extract`: use `x archive.tar.gz` instead of memorizing archive-specific flags.
- `history`: use `hs docker` instead of typing `history | grep docker`.

The earlier plugin sections explain these capabilities in detail; this audit is checking that they have become habits, not recommending more plugins.

Small Additions Worth Considering

A few things that are low-effort and pay off quickly:

In ~/.oh-my-zsh/custom/aliases.zsh

Directory navigation shortcuts

```
alias ..='cd ..'
alias ...='cd ../../'
alias ....='cd ../../..'
```

Quick list

```
alias ll='ls -lAh --color=auto'
```

Git shortcuts beyond what the git plugin provides

```
alias gst='git status'  # already from git plugin, but worth knowing
```

Show port usage

```
alias ports='ss -tlnp'
```

And a few ZSH options worth adding to your `.zshrc` if they're not there (note: `HIST_IGNORE_SPACE` and friends from the History section earlier are already set by OMZ's

`lib/history.zsh` — no need to add those yourself):

```
setopt AUTO_CD      # type a directory name to cd into it
setopt CORRECT      # suggest corrections for mistyped commands
```

Self-Audit Checklist

Use this checklist against your own shell every few months:

1. Does every enabled plugin remove regular friction, or is it leftover experimentation?

2. Is startup still fast (`time zsh -i -c exit`) after the latest plugin/theme additions?
3. Are high-impact basics present (`fzf`, `zsh-autosuggestions`, `zsh-syntax-highlighting`, `z`)?
4. Is your prompt giving useful state (branch, dirty state, exit code) without visual noise?
5. Are aliases/functions in `custom/` so updates do not overwrite your work?
6. Is `PATH` order intentional, with no duplicate manager shims?
7. Do key bindings match your editing mode (`emacs` or `vi`) without surprises?
8. Are all critical custom files actually sourced (not just present on disk)?
9. Do duplicated settings (like SSH key lifetimes) match across aliases, plugins, and helper scripts?
10. Are tool completions generated once instead of re-generated on every shell startup?

If two or more answers are “no,” you likely have a configuration debt cleanup worth doing.

Troubleshooting Common Problems

Shell Startup Feels Slow

Measure first:
`time zsh -i -c exit`

Then isolate cause by temporarily removing half the plugin list, re-measuring, and repeating (binary search). Typical culprits are plugin initializers that shell out to external tools at startup.

Prompt Changes Are Not Taking Effect

Check order:

1. Is `ZSH_THEME` set before sourcing OMZ?
2. Is another file in `custom/` modifying `PROMPT` after theme load?
3. If using `p10k`, is `~/.p10k.zsh` being sourced as expected?

Because theme loading happens late in OMZ startup, prompt variables changed earlier can be overwritten.

Completions Feel Broken or Inconsistent

Quick checks:

1. Confirm the relevant plugin is in `plugins=(...)`.
2. Start a clean shell and test again.
3. Update OMZ (`omz update`) in case a completion script is stale.

If completion for one command is still missing, inspect that plugin's `.plugin.zsh` file and verify the completion function is actually loaded.

A Plugin Causes Weird Behaviour

Run a temporary minimal profile:
`plugins=(git)`

If the issue disappears, re-add plugins in small groups until it returns. This is usually faster than reading every plugin source first.

When OMZ Is Not Enough

Oh My Zsh is the right choice for most people, but there are situations where it starts to show its age.

Startup speed. OMZ adds measurable startup latency, mostly from sourcing plugins and initializing completions. On modern hardware this is usually under 200ms, which is imperceptible. But if you're on a slow machine, opening many terminals, or doing a lot of `zsh -c` invocations in scripts, it accumulates. `zinit` and `zplug` are plugin managers that load plugins lazily or in parallel and can reduce startup time significantly. `sheldon` is another option with a simple TOML configuration.

Opinionated defaults. OMZ makes choices about completion settings, history handling, and key bindings that most people are fine with. If you find yourself fighting the defaults, vanilla ZSH with `zinit` and hand-picked plugins gives you more control.

Alternatives worth knowing. Prezto is OMZ's more modular cousin — faster startup, more configurable, smaller default footprint. Fish shell takes a different approach entirely: better out-of-the-box experience, but incompatible syntax with Bash/ZSH, which matters if you write a lot of scripts. Nushell is the most radical departure — structured data instead of text streams, genuinely different mental model, not a daily driver for most people yet.

For the typical developer workflow, OMZ with a curated plugin list and p10k as the theme is a well-tested configuration that will serve you well without requiring you to build from scratch.

Quick Reference: What to Do Next

In order of impact:

1. **Install `zsh-syntax-highlighting`** — see the install command in the plugin section above. Add it last in your plugins list.
 2. **Add `z`** to your plugins list (no install needed, it's bundled). Use it for a week.
 3. **Try `Ctrl+T` and `Alt+C`** with `fzf` — fuzzy file and directory completion. They're already wired up.
 4. **Internalize `Esc Esc`** (`sudo` plugin) and `x` (extract plugin) — you have both, just build the habit.
 5. **Consider `p10k`** if you want a richer prompt with git state detail.
 6. **Read `omz plugin list`** — there may be completions for tools you use daily that you didn't know OMZ ships.
-

Further Reading

- **OMZ repository** — `~/.oh-my-zsh/` itself: `plugins/<name>/<name>.plugin.zsh` files are the source of truth for what each plugin does and what commands/aliases it provides.
- **ZSH manual** — `man zsh` is the definitive reference. The sections on parameter expansion, globbing qualifiers, and ZLE are particularly worth having open.
- **Powerlevel10k** — read the support notice before installing; `p10k configure` documents the available prompt options interactively.
- **ZSH Users mailing list** / `r/zsh` — for real-world configuration questions; the OMZ wiki has gotten stale in places.