



≡ CLI > message

CLI

message

Single outbound command for sending messages and channel actions (Discord/Google Chat/Slack/Mattermost (plugin)/Telegram/WhatsApp/Signal/iMessage/MS Teams).

Usage

```
openclaw message <subcommand> [flags]
```



Channel selection:

`--channel` required if more than one channel is configured.

If exactly one channel is configured, it becomes the default.

Values:

`whatsapp|telegram|discord|googlechat|slack|mattermost|signal|imessage|msteams` (Mattermost requires plugin)

Target formats (`--target`):

WhatsApp: E.164 or group JID

Telegram: chat id or @username

Discord: `channel:<id>` or `user:<id>` (or `<@id>` mention; raw numeric ids are treated as channels)

Google Chat: `spaces/<spaceId>` or `users/<userId>`

Slack: `channel:<id>` or `user:<id>` (raw channel id is accepted)



Mattermost (plugin): `channel:<id>` , `user:<id>` , or `@username` (bare ids are treated as channels)

Signal: `+E.164` , `group:<id>` , `signal:+E.164` , `signal:group:<id>` , or
`username:<name>` / `u:<name>`

iMessage: `handle`, `chat_id:<id>` , `chat_guid:<guid>` , or `chat_identifier:<id>`

MS Teams: `conversation id (19:...@thread.tacv2)` or `conversation:<id>` or
`user:<aad-object-id>`

Name lookup:

For supported providers (Discord/Slack/etc), channel names like `Help` or `#help` are resolved via the directory cache.

On cache miss, OpenClaw will attempt a live directory lookup when the provider supports it.

Common flags

```
--channel <name>
--account <id>
--target <dest>  (target channel or user for send/poll/read/etc)
--targets <name> (repeat; broadcast only)
--json
--dry-run
--verbose
```

Actions

Core

send

Channels: `WhatsApp/Telegram/Discord/Google Chat/Slack/Mattermost (plugin)/Signal/iMessage/MS Teams`

Required: `--target` , plus `--message` or `--media`



Optional: `--media` , `--reply-to` , `--thread-id` , `--gif-playback`

Telegram only: `--buttons` (requires

`channels.telegram.capabilities.inlineButtons` to allow it)

Telegram only: `--thread-id` (forum topic id)

Slack only: `--thread-id` (thread timestamp; `--reply-to` uses the same field)

WhatsApp only: `--gif-playback`

poll

Channels: WhatsApp/Discord/MS Teams

Required: `--target` , `--poll-question` , `--poll-option` (repeat)

Optional: `--poll-multi`

Discord only: `--poll-duration-hours` , `--message`

react

Channels: Discord/Google Chat/Slack/Telegram/WhatsApp/Signal

Required: `--message-id` , `--target`

Optional: `--emoji` , `--remove` , `--participant` , `--from-me` , `--target-author` , `--target-author-uuid`

Note: `--remove` requires `--emoji` (omit `--emoji` to clear own reactions where supported; see `/tools/reactions`)

WhatsApp only: `--participant` , `--from-me`

Signal group reactions: `--target-author` or `--target-author-uuid` required

reactions

Channels: Discord/Google Chat/Slack

Required: `--message-id` , `--target`

Optional: `--limit`

read

Channels: Discord/Slack

Required: `--target`



Optional: `--limit` , `--before` , `--after`

Discord only: `--around`

`edit`

Channels: Discord/Slack

Required: `--message-id` , `--message` , `--target`

`delete`

Channels: Discord/Slack/Telegram

Required: `--message-id` , `--target`

`pin / unpin`

Channels: Discord/Slack

Required: `--message-id` , `--target`

`pins (list)`

Channels: Discord/Slack

Required: `--target`

`permissions`

Channels: Discord

Required: `--target`

`search`

Channels: Discord

Required: `--guild-id` , `--query`

Optional: `--channel-id` , `--channel-ids` (repeat), `--author-id` , `--author-ids` (repeat), `--limit`

Threads

`thread create`

Channels: Discord

Required: `--thread-name` , `--target` (channel id)

Optional: `--message-id` , `--auto-archive-min`



thread list

Channels: Discord

Required: `--guild-id`

Optional: `--channel-id` , `--include-archived` , `--before` , `--limit`

thread reply

Channels: Discord

Required: `--target` (thread id), `--message`

Optional: `--media` , `--reply-to`

Emojis

emoji list

Discord: `--guild-id`

Slack: no extra flags

emoji upload

Channels: Discord

Required: `--guild-id` , `--emoji-name` , `--media`

Optional: `--role-ids` (repeat)

Stickers

sticker send

Channels: Discord

Required: `--target` , `--sticker-id` (repeat)

Optional: `--message`

sticker upload

Channels: Discord

Required: `--guild-id` , `--sticker-name` , `--sticker-desc` , `--sticker-tags` , `--media`

Roles / Channels / Members / Voice



`role info` (Discord): `--guild-id`

`role add` / `role remove` (Discord): `--guild-id` , `--user-id` , `--role-id`

`channel info` (Discord): `--target`

`channel list` (Discord): `--guild-id`

`member info` (Discord/Slack): `--user-id` (+ `--guild-id` for Discord)

`voice status` (Discord): `--guild-id` , `--user-id`

Events

`event list` (Discord): `--guild-id`

`event create` (Discord): `--guild-id` , `--event-name` , `--start-time`

Optional: `--end-time` , `--desc` , `--channel-id` , `--location` , `--event-type`

Moderation (Discord)

`timeout` : `--guild-id` , `--user-id` (optional `--duration-min` or `--until` ; omit both to clear timeout)

`kick` : `--guild-id` , `--user-id` (+ `--reason`)

`ban` : `--guild-id` , `--user-id` (+ `--delete-days` , `--reason`)

`timeout` also supports `--reason`

Broadcast

`broadcast`

Channels: any configured channel; use `--channel all` to target all providers

Required: `--targets` (repeat)

Optional: `--message` , `--media` , `--dry-run`

Examples

Send a Discord reply:

```
openclaw message send --channel discord \  
  --target channel:123 --message "hi" --reply-to 456
```

Create a Discord poll:

```
openclaw message poll --channel discord \  
  --target channel:123 \  
  --poll-question "Snack?" \  
  --poll-option Pizza --poll-option Sushi \  
  --poll-multi --poll-duration-hours 48
```

Send a Teams proactive message:

```
openclaw message send --channel msteams \  
  --target conversation:19:abc@thread.tacv2 --message "hi"
```

Create a Teams poll:

```
openclaw message poll --channel msteams \  
  --target conversation:19:abc@thread.tacv2 \  
  --poll-question "Lunch?" \  
  --poll-option Pizza --poll-option Sushi
```

React in Slack:

```
openclaw message react --channel slack \  
  --target C123 --message-id 456 --emoji "👍"
```

React in a Signal group:



```
openclaw message react --channel signal \  
  --target signal:group:abc123 --message-id 1737630212345 \  
  --emoji "✅" --target-author-uuid 123e4567-e89b-12d3-a456-426614174000  
>
```



Send Telegram inline buttons:

```
openclaw message send --channel telegram --target @mychat --message  
  --buttons '[ [{"text":"Yes","callback_data":"cmd:yes"}], [{"text":"No","callb
```



< browser

agent >

Powered by [mintlify](https://mintlify.com)