

CS 577 - Approximation

Marc Renault

Department of Computer Sciences
University of Wisconsin – Madison

Spring 2023

TopHat Section 001 Join Code: 020205

TopHat Section 002 Join Code: 394523



WISCONSIN
UNIVERSITY OF WISCONSIN-MADISON

APPROXIMATION ALGORITHMS

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)
- Linear Programming Relaxations (and SDP)

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)
- Linear Programming Relaxations (and SDP)
- Primal-Dual (related to LPs)

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)
- Linear Programming Relaxations (and SDP)
- Primal-Dual (related to LPs)
- Local Search

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)
- Linear Programming Relaxations (and SDP)
- Primal-Dual (related to LPs)
- Local Search
- Metric Embeddings

APPROXIMATION ALGORITHMS

DEALING WITH HARD PROBLEMS

Efficient Approximation Algorithms

- Polynomial run-time
- Guaranteed (worst-case) performance.
- Bi-criteria Goal: Be as efficient as possible and as close to optimal as possible.

Some Common Techniques

- Heuristics (esp. Greedy ones)
- Linear Programming Relaxations (and SDP)
- Primal-Dual (related to LPs)
- Local Search
- Metric Embeddings
- Randomization

APPROXIMATION RATIO

Worst-Case Approximation Analysis

- Let $\text{ALG}(I)$ be the value of an algorithm ALG for an instance I of problem P .
- r -approximation ratio:

$$\forall I, \text{ALG}(I) \leq r \cdot \text{OPT}(I) + \eta$$

- η is some constant (not dependant on the input)

APPROXIMATION RATIO

Worst-Case Approximation Analysis

- Let $\text{ALG}(I)$ be the value of an algorithm ALG for an instance I of problem P .
- r -approximation ratio:

$$\forall I, \text{ALG}(I) \leq r \cdot \text{OPT}(I) + \eta$$

- η is some constant (not dependant on the input)
- $\eta = 0$ is a strict approximation ratio.
- $\eta > 0$ is a asymptotic approximation ratio.

APPROXIMATION RATIO

Worst-Case Approximation Analysis

- Let $\text{ALG}(I)$ be the value of an algorithm ALG for an instance I of problem P .
- r -approximation ratio:

$$\forall I, \text{ALG}(I) \leq r \cdot \text{OPT}(I) + \eta$$

- η is some constant (not dependant on the input)

Minimization vs Maximization

- Min: Approximation ratio ≥ 1 .
- Max: Approximation ratio ≤ 1 , or we use $c \geq 1$ where $1/c = r \leq 1$.

HEURISTICS

BIN PACKING PROBLEM

Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.


BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.


BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.


BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.

BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.

BIN PACKING PROBLEM




1

Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.


BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.

BIN PACKING PROBLEM



Definition

- Consists of:
 - an initial empty set of bins of capacity 1.
 - Finite request sequence: σ of length n .
- Each $r_i \in \sigma$ is an item with a size $s(r_i) \in (0, 1]$.
- Action: r_i must be packed in a bin without violating the capacity constraint.
- Goal: Minimize the number of bins used.

FIRST FIT HEURISTIC

First Fit (FF)

- A greedy heuristic
- Bins are opened (and ordered) sequentially.
- Heuristic: Place the next item in the open bin of lowest index in which it fits, opening a new bin if needed.

FIRST FIT HEURISTIC

First Fit (FF)

- A greedy heuristic
- Bins are opened (and ordered) sequentially.
- Heuristic: Place the next item in the open bin of lowest index in which it fits, opening a new bin if needed.

Tight Bounds

- Typically, approximation ratios are exact (no big-Oh).

FIRST FIT HEURISTIC

First Fit (FF)

- A greedy heuristic
- Bins are opened (and ordered) sequentially.
- Heuristic: Place the next item in the open bin of lowest index in which it fits, opening a new bin if needed.

Tight Bounds

- Typically, approximation ratios are exact (no big-Oh).
- For an algorithm with an approx ratio of $r \geq 1$:
 - r_ℓ is a *lower bound* if \exists an instance I where $\text{ALG}(I) \geq r_\ell \cdot \text{OPT}(I)$.
 - r_u is an *upper bound* if, \forall instances I , $\text{ALG}(I) \leq r_u \cdot \text{OPT}(I)$.

FIRST FIT HEURISTIC

First Fit (FF)

- A greedy heuristic
- Bins are opened (and ordered) sequentially.
- Heuristic: Place the next item in the open bin of lowest index in which it fits, opening a new bin if needed.

Tight Bounds

- Typically, approximation ratios are exact (no big-Oh).
- For an algorithm with an approx ratio of $r \geq 1$:
 - r_ℓ is a *lower bound* if \exists an instance I where $\text{ALG}(I) \geq r_\ell \cdot \text{OPT}(I)$.
 - r_u is an *upper bound* if, \forall instances I , $\text{ALG}(I) \leq r_u \cdot \text{OPT}(I)$.
- A tight bound is $r_\ell = r_u$.

FF LOWER BOUND

Theorem 1

FF has an approximation ratio $\geq 4/3$.

FF LOWER BOUND

Theorem 1

FF has an approximation ratio $\geq 4/3$.

Proof.

Consider a sequence of n items of size $\frac{1}{3} - 2\varepsilon$, followed by $2n$ items of size $\frac{1}{3} + \varepsilon$ (assume n divisible by 3):

FF LOWER BOUND

Theorem 1

FF has an approximation ratio $\geq 4/3$.

Proof.

Consider a sequence of n items of size $\frac{1}{3} - 2\varepsilon$, followed by $2n$ items of size $\frac{1}{3} + \varepsilon$ (assume n divisible by 3):

- FF packing: $\frac{n}{3}$ bins for the first n items, and n bins for the last $2n$ items. Overall $\frac{4}{3}n$ bins.

FF LOWER BOUND

Theorem 1

FF has an approximation ratio $\geq 4/3$.

Proof.

Consider a sequence of n items of size $\frac{1}{3} - 2\varepsilon$, followed by $2n$ items of size $\frac{1}{3} + \varepsilon$ (assume n divisible by 3):

- FF packing: $\frac{n}{3}$ bins for the first n items, and n bins for the last $2n$ items. Overall $\frac{4}{3}n$ bins.
- OPT packing: n bins each with 1 item of size $\frac{1}{3} - 2\varepsilon$, and 2 items of size $\frac{1}{3} + \varepsilon$.



FF UPPER BOUND

Observation 1

$\text{OPT} \geq N$, where N is the sum of the items.

FF UPPER BOUND

Observation 1

$OPT \geq N$, where N is the sum of the items.

Observation 2

In a packing S , if all bins are at least $0 < \alpha \leq 1$ full (except for possibly a constant number of bins), then the approximation ratio is α .

FF UPPER BOUND

Observation 1

$OPT \geq N$, where N is the sum of the items.

Observation 2

In a packing S , if all bins are at least $0 < \alpha \leq 1$ full (except for possibly a constant number of bins), then the approximation ratio is α .

Theorem 2

FF has an approximation ratio ≤ 2 .

FF UPPER BOUND

Observation 1

$\text{OPT} \geq N$, where N is the sum of the items.

Observation 2

In a packing S , if all bins are at least $0 < \alpha \leq 1$ full (except for possibly a constant number of bins), then the approximation ratio is α .

Theorem 2

FF has an approximation ratio ≤ 2 .

Proof.

All bins in FF are $\geq 1/2$ full (except possibly one bin). □

FF UPPER BOUND

Theorem 2

FF has an approximation ratio ≤ 2 .

Theorem 3

First fit decreasing (FFD) has an approximation ratio $\leq \frac{3}{2}$.

FF UPPER BOUND

Theorem 2

FF has an approximation ratio ≤ 2 .

Theorem 3

First fit decreasing (FFD) has an approximation ratio $\leq \frac{3}{2}$.

Proof.

- Let k be the number of bins in a FFD packing.
- Let b_i be the last bin with an item of size $> \frac{1}{3}$.

FF UPPER BOUND

Theorem 2

FF has an approximation ratio ≤ 2 .

Theorem 3

First fit decreasing (FFD) has an approximation ratio $\leq \frac{3}{2}$.

Proof.

- Let k be the number of bins in a FFD packing.
- Let b_i be the last bin with an item of size $> \frac{1}{3}$.
- If $i < k$, all bins are filled to at least $\frac{2}{3}$ (except possibly last bin).



FF UPPER BOUND

Theorem 2

FF has an approximation ratio ≤ 2 .

Theorem 3

First fit decreasing (FFD) has an approximation ratio $\leq \frac{3}{2}$.

Proof.

- Let k be the number of bins in a FFD packing.
- Let b_i be the last bin with an item of size $> \frac{1}{3}$.
- If $i < k$, all bins are filled to at least $\frac{2}{3}$ (except possibly last bin).
- If $i = k$, there are at least k items of size $> \frac{1}{3}$. Since these k items can fit at most 2 to a bin, $\text{OPT} \geq \frac{2}{3}k$.



FF UPPER BOUND

Theorem 2

FF has an approximation ratio ≤ 2 .

Theorem 3

First fit decreasing (FFD) has an approximation ratio $\leq \frac{3}{2}$.

Known Bounds

- FF has an approximation ratio of 1.7.
- FFD has an approximation ratio of $11/9$.

PTAS

ARBITRARILY GOOD APPROXIMATIONS

Polynomial Time Approximation Scheme (PTAS)

For some ε :

- An arbitrarily good approximation guarantee that is a function of ε .
- A run-time that is polynomial in the input for a fixed ε .

ARBITRARILY GOOD APPROXIMATIONS

Polynomial Time Approximation Scheme (PTAS)

For some ε :

- An arbitrarily good approximation guarantee that is a function of ε .
- A run-time that is polynomial in the input for a fixed ε .
- Run-time vs approximation ratio trade-off.

ARBITRARILY GOOD APPROXIMATIONS

Polynomial Time Approximation Scheme (PTAS)

For some ε :

- An arbitrarily good approximation guarantee that is a function of ε .
- A run-time that is polynomial in the input for a fixed ε .
- Run-time vs approximation ratio trade-off.

Inapproximability Results

- Not all problems admit a PTAS.

ARBITRARILY GOOD APPROXIMATIONS

Polynomial Time Approximation Scheme (PTAS)

For some ε :

- An arbitrarily good approximation guarantee that is a function of ε .
- A run-time that is polynomial in the input for a fixed ε .
- Run-time vs approximation ratio trade-off.

Inapproximability Results

- Not all problems admit a PTAS.
- Some problems have inapproximability results:
 - Unless $NP = P$, Vertex Cover cannot be approximated within a factor of 1.3606.

ARBITRARILY GOOD APPROXIMATIONS

Polynomial Time Approximation Scheme (PTAS)

For some ε :

- An arbitrarily good approximation guarantee that is a function of ε .
- A run-time that is polynomial in the input for a fixed ε .
- Run-time vs approximation ratio trade-off.

Inapproximability Results

- Not all problems admit a PTAS.
- Some problems have inapproximability results:
 - Unless $NP = P$, Vertex Cover cannot be approximated within a factor of 1.3606.
 - Unless $NP = P$, Bin Packing cannot be strictly approximated within a factor of $3/2$.

BIN PACKING BRUTE FORCE

Bin Types

- Let k be the number of different item sizes.

BIN PACKING BRUTE FORCE

Bin Types

- Let k be the number of different item sizes.
- Let ε be the smallest item size:
 - at most $M = \lfloor 1/\varepsilon \rfloor$ items in a bin.

BIN PACKING BRUTE FORCE

Bin Types

- Let k be the number of different item sizes.
- Let ε be the smallest item size:
 - at most $M = \lfloor 1/\varepsilon \rfloor$ items in a bin.
- $R = \binom{M}{k+1} = \binom{M+K}{M}$ bin types:
 - Choose M items to pack in a bin from $k + 1$ different items sizes (includes 0).

BIN PACKING BRUTE FORCE

Bin Types

- Let k be the number of different item sizes.
- Let ε be the smallest item size:
 - at most $M = \lfloor 1/\varepsilon \rfloor$ items in a bin.
- $R = \binom{M}{k+1} = \binom{M+K}{M}$ bin types:
 - Choose M items to pack in a bin from $k + 1$ different items sizes (includes 0).

Number of Packings

- At most n bins are need, and we have R types of bins, so there are:

$$P = \binom{n}{R+1} = \binom{n+R}{R}$$

feasible packings to check.

BIN PACKING BRUTE FORCE

Bin Types

- Let k be the number of different item sizes.
- Let ε be the smallest item size:
 - at most $M = \lfloor 1/\varepsilon \rfloor$ items in a bin.
- $R = \binom{M}{k+1} = \binom{M+K}{M}$ bin types:
 - Choose M items to pack in a bin from $k + 1$ different items sizes (includes 0).

Number of Packings

- At most n bins are need, and we have R types of bins, so there are:

$$P = \binom{n}{R+1} = \binom{n+R}{R} \leq (n+R)^R = O(n^R)$$

feasible packings to check.

BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $ALG_\varepsilon(I) \leq (1 + 2\varepsilon)OPT(I) + 1$ for all I .


BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $ALG_\varepsilon(I) \leq (1 + 2\varepsilon)OPT(I) + 1$ for all I .

Proof (PTAS).

- Split the items of size $\geq \varepsilon$ (denoted by L) into groups containing $\lfloor n\varepsilon^2 \rfloor$ items $\implies \lceil 1/\varepsilon^2 \rceil$ groups.
- Round items up to size of largest item:



BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $ALG_\varepsilon(I) \leq (1 + 2\varepsilon)OPT(I) + 1$ for all I .

Proof (PTAS).

- Split the items of size $\geq \varepsilon$ (denoted by L) into groups containing $\lfloor n\varepsilon^2 \rfloor$ items $\implies \lceil 1/\varepsilon^2 \rceil$ groups.
- Round items up to size of largest item.
- Pack rounded items: $O(n^{f(\frac{1}{\varepsilon})}) \implies O(n^{\frac{2}{\varepsilon^2}})$.

BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $ALG_\varepsilon(I) \leq (1 + 2\varepsilon)OPT(I) + 1$ for all I .

Proof (PTAS).

- Split the items of size $\geq \varepsilon$ (denoted by L) into groups containing $\lfloor n\varepsilon^2 \rfloor$ items $\implies \lceil 1/\varepsilon^2 \rceil$ groups.
- Round items up to size of largest item.
- Pack rounded items: $O(n^{f(\frac{1}{\varepsilon})}) \implies O(n^{\frac{2}{\varepsilon^2}})$.
- Pack items $< \varepsilon$ using FF.

BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $ALG_\varepsilon(I) \leq (1 + 2\varepsilon)OPT(I) + 1$ for all I .

Proof (PTAS).


- Approximation ratio:
 - $OPT(L) \geq \varepsilon|L| \geq n\varepsilon$.

BIN PACKING (ASYMPTOTIC) PTAS

Proof (PTAS).

- Approximation ratio:
 - if items $< \varepsilon$ fit in $\text{ALG}_\varepsilon(L)$ bins:

$$\text{ALG}_\varepsilon(I) = \text{ALG}_\varepsilon(L) \leq \text{ALG}_\varepsilon(L^{\text{DOWN}}) + n\varepsilon^2$$



- Let S'' be optimal packing of L^{DOWN} ($\text{ALG}_\varepsilon(L^{\text{DOWN}}) \leq \text{OPT}(L)$).
- We can pack σ using S'' :
 - (1) Group 1 items in bins by themselves ($\leq n\varepsilon^2$ bins at most).
 - (2) For $\lceil 1/\varepsilon^2 \rceil \geq i > 1$, pack the items of group i in the spots for the items of group $i - 1$ in S'' .

BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $\text{ALG}_\varepsilon(I) \leq (1 + 2\varepsilon)\text{OPT}(I) + 1$ for all I .

Proof (PTAS).

- Approximation ratio:
 - $\text{OPT}(L) \geq \varepsilon|L| \geq n\varepsilon$.
 - if items $< \varepsilon$ fit in $\text{ALG}_\varepsilon(L)$ bins:

$$\begin{aligned}\text{ALG}_\varepsilon(I) = \text{ALG}_\varepsilon(L) &\leq \text{ALG}_\varepsilon(L^{\text{DOWN}}) + n\varepsilon^2 \\ &\leq \text{OPT}(L) + \varepsilon\text{OPT}(L) \\ &= (1 + \varepsilon)\text{OPT}(L)\end{aligned}$$

BIN PACKING (ASYMPTOTIC) PTAS

Theorem 4

For any $\varepsilon > 0$, there is an ALG_ε that runs in $\text{poly}(n)$ time for which $\text{ALG}_\varepsilon(I) \leq (1 + 2\varepsilon)\text{OPT}(I) + 1$ for all I .

Proof (PTAS).


- Approximation ratio:
 - if items $< \varepsilon$ open new bins:
 - All bins (except possibly last one) are $(1 - \varepsilon)$ full:

$$\begin{aligned}\text{OPT}(I) &\geq (\text{ALG}_\varepsilon(I) - 1)(1 - \varepsilon) \\ \iff \text{ALG}_\varepsilon(I) &\leq (1 + 2\varepsilon)\text{OPT}(I) + 1\end{aligned}$$



LINEAR PROGRAMMING


LINEAR PROGRAMMING



Basic Linear Program

$$\begin{array}{ll}\min & 1.5x_1 + x_2 \\ \text{s.t.} & x_1 + 2x_2 \geq 6 \\ & 2x_1 + x_2 \geq 6 \\ & x_1 \geq 0, x_2 \geq 0\end{array}$$

LINEAR PROGRAMMING




Basic Linear Program

$$\begin{array}{ll}\min & 1.5x_1 + x_2 \\ \text{s.t.} & x_1 + 2x_2 \geq 6 \\ & 2x_1 + x_2 \geq 6 \\ & x_1 \geq 0, x_2 \geq 0\end{array}$$

TH1: What is the solution vector (x_1, x_2) ?

LINEAR PROGRAMMING



Basic Linear Program


$$\begin{aligned}
 \min \quad & 1.5x_1 + x_2 \\
 \text{s.t.} \quad & x_1 + 2x_2 \geq 6 \\
 & 2x_1 + x_2 \geq 6 \\
 & x_1 \geq 0, x_2 \geq 0
 \end{aligned}$$

General Linear Program

- Optimize a linear object function subject to linear constraints.

$$\begin{aligned}
 & \text{optimize}_x \quad c^T x \\
 & \text{subject to} \quad Ax \leq b \\
 & \quad \quad \quad x_j \geq 0 \quad \forall j
 \end{aligned}$$

LINEAR PROGRAMMING



Basic Linear Program

$$c^T = [1.5 \quad 1] \quad A = \begin{bmatrix} -1 & -2 \\ -2 & -1 \end{bmatrix}$$

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \quad b = \begin{bmatrix} -6 \\ -6 \end{bmatrix}$$

General Linear Program

- Optimize a linear object function subject to linear constraints.

$$\begin{array}{ll} \text{optimize}_x & c^T x \\ \text{subject to} & Ax \leq b \\ & x_j \geq 0 \quad \forall j \end{array}$$

LINEAR PROGRAMMING (LP)

Some Notes



- In 1947, Dantzig developed general linear programming.

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:
 - Interior Point Method (poly-time 1984 Karmarkar)

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:
 - Interior Point Method (poly-time 1984 Karmarkar)
 - Simplex (exp-time, usually poly-time 1947 Dantzig)

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:
 - Interior Point Method (poly-time 1984 Karmarkar)
 - Simplex (exp-time, usually poly-time 1947 Dantzig)
- BUT: Integer Linear Programming is NP-complete (one of Karp's 21 NP-complete problems)

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:
 - Interior Point Method (poly-time 1984 Karmarkar)
 - Simplex (exp-time, usually poly-time 1947 Dantzig)
- BUT: Integer Linear Programming is NP-complete (one of Karp's 21 NP-complete problems)
 - ILP requires all x to be integers.

LINEAR PROGRAMMING (LP)

Some Notes

- In 1947, Dantzig developed general linear programming.
- Khachiyan 1979: Ellipsoid Method, polynomial algorithm to solve LPs.
- In practice:
 - Interior Point Method (poly-time 1984 Karmarkar)
 - Simplex (exp-time, usually poly-time 1947 Dantzig)
- BUT: Integer Linear Programming is NP-complete (one of Karp's 21 NP-complete problems)
 - ILP requires all x to be integers.
 - Mixed ILP is also NP-complete.

VERTEX COVER

ILP

$$\begin{array}{ll}\min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in \{0, 1\} \quad \forall i \in V\end{array}$$

Weighted Vertex Cover

- A graph $G = (V, E)$.
- For each $v_i : w_i \geq 0$.
- Goal: Find the minimum weighted vertex cover.

VERTEX COVER

ILP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in \{0, 1\} \quad \forall i \in V \end{array}$$

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

Weighted Vertex Cover

- A graph $G = (V, E)$.
- For each $v_i : w_i \geq 0$.
- Goal: Find the minimum weighted vertex cover.

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - TH2: What is the minimum value for x_j if $(i, j) \in E$?

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll}\min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V\end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

Rounding Fractional Solution

Some methods:

- Fixed rounding rule
- Treat it as probability and do a probabilistic rounding.

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

Vertex Cover Rounding

- Round up to 1 if $x_i \geq 1/2$, else down to 0.

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll}\min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V\end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

Vertex Cover Rounding

- Round up to 1 if $x_i \geq 1/2$, else down to 0.
- Let S be the rounded solution, and S^* be the optimal ILP solution.

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll}\min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V\end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

Vertex Cover Rounding

- Round up to 1 if $x_i \geq 1/2$, else down to 0.
- Let S be the rounded solution, and S^* be the optimal ILP solution.
- S is a VC since, $\forall (i, j) \in E, x_i \text{ or } x_j > 1/2 \implies i \text{ or } j \in S$.

VERTEX COVER LP

Relaxed LP

$$\begin{array}{ll} \min_x & \sum_{i \in V} w_i x_i \\ \text{s.t.} & x_i + x_j \geq 1 \quad \forall (i, j) \in E \\ & x_i \in [0, 1] \quad \forall i \in V \end{array}$$

What does a solution mean?

- Say $x_i = 0.42$ in a solution to the LP:
 - $x_j \geq 0.58$ if $(i, j) \in E$
- It means we have 0.42 of i and ≥ 0.58 of j .

Vertex Cover Rounding

- Round up to 1 if $x_i \geq 1/2$, else down to 0.
- Let S be the rounded solution, and S^* be the optimal ILP solution.
- S is a VC since, $\forall (i, j) \in E, x_i \text{ or } x_j > 1/2 \implies i \text{ or } j \in S$.

$$w(S) = \sum_{i \in S} w_i \leq 2 \sum_{i \in S} w_i x_i \leq 2 \sum_i w_i x_i \leq 2w(S^*)$$

APPENDIX

REFERENCES

IMAGE SOURCES I



WISCONSIN
UNIVERSITY OF WISCONSIN-MADISON

<https://brand.wisc.edu/web/logos/>