

Task - 1

Implement the design of the **PlayerEarning** class so that the following output is produced:

Driver Code	Output
<pre># Write your code here print("*****") player1 = PlayerEarning('Buffon') player1.calculateTotal(250000) player1.printDetails() print("\n*****") player2 = PlayerEarning('Dybala') player2.calculateTotal(250000, 31) player2.printDetails() print("\n*****") player3 = PlayerEarning('Cuadrado') player3.calculateTotal(250000, 20) player3.printDetails()</pre>	<pre>***** Player Name: Buffon Player Season Earning without bonus: 250000 Bonus: 0 Player Season Earning After Bonus: 250000 ***** Player Name: Dybala Player Season Earning without bonus: 250000 Bonus: 22500 Player Season Earning After Bonus: 272500 ***** Player Name: Cuadrado Player Season Earning without bonus: 250000 Bonus: 12500 Player Season Earning After Bonus: 262500</pre>

Note: calculateTotal() method takes either 1 or 2 arguments. It takes earning without bonus as the first argument and number of goals as the second argument. Calculate the bonus only if the number of goals is given (see the hint). If the number of goals is not provided, the bonus is 0. Finally calculate the total after bonus.

Assume only these 2 ways you can call the calculateTotal() method.

Hint:

If Goal > 30, bonus = (5/100) * earning_without_bonus + 10000
else, bonus = (5/100) * earning_without_bonus

Task - 2

Design a **myList** class so that the following output is produced upon executing the following code:

Driver Code	Output
<pre>l1 = myList(2,3,4,5,6) #you might need a list inside your class to store the values l1.sum() l1.merge(4,5,9) l1.sum() l1.average() print("-----") l2 = myList() l2.average() l2.merge(1,2,4,8) l2.sum()</pre>	<pre>Sum: 20 Sum: 38 Average: 4.75 ----- Average: 0 Sum: 15</pre>

Task - 3

Implement the design of the **Bird** class so that the following output is produced:

Driver Code	Output
<pre>ostrich = Bird('Ostrich') duck = Bird("Duck", True) owl = Bird('Owl', True) print("#####") ostrich.fly() duck.fly() owl.fly() duck.setType('Water Birds') owl.setType('Birds of Prey') print("=====")</pre>	<pre>##### Ostrich can not fly Duck can fly Owl can fly ===== Name: Ostrich Type: Flightless Birds ===== Name: Duck Type: Water Birds</pre>

<pre>ostrich.printDetail() print("=====") duck.printDetail() print("=====") owl.printDetail()</pre>	<pre>===== Name: Owl Type: Birds of Prey</pre>
---	--

Task - 4

Implement the design of the **Account** class so that the following output is produced:

Driver Code	Output
<p># Write your code here</p> <pre>print('No of account holders:', Account.count) print("=====") p1 = Account("Abdul", 45, "Service Holder", 500000) p1.addMoney(300000) p1.printDetails() print("=====") p2 = Account("Rahim", 55, "Businessman", 700000) p2.withdrawMoney(700000) p2.printDetails() print("=====") p3 = Account("Ashraf", 62, "Govt. Officer", 200000) p3.withdrawMoney(250000) p3.printDetails() print("=====") print('No of account holders:', Account.count)</pre>	<pre>No of account holders: 0 ===== Name: Abdul Age: 45 Occupation: Service Holder Total Amount: 800000 ===== Name: Rahim Age: 55 Occupation: Businessman Total Amount: 0 ===== Name: Ashraf Age: 62 Occupation: Govt. Officer Total Amount: 200000 ===== No of account holders: 3</pre>

Task - 5

Write the **Smartphone** class with the required methods to give the following outputs as shown.

Write your codes here.

Do not change the following lines of code.

```
s1 = Smartphone()
print("=====")
s1.addFeature("Display", "6.1 inch")
print("=====")
s1.setName("Samsung Note 20")
s1.addFeature("Display", "6.1 inch")
s1.printDetail()
print("=====")
s2 = Smartphone("Iphone 12 Pro")
s2.addFeature("Display", "6.2 inch")
s2.addFeature("Ram", "6 GB")
print("=====")
s2.printDetail()
s2.addFeature("Display", "Amoled panel")
s2.addFeature("Ram", "DDR5")
print("=====")
s2.printDetail()
print("=====")
```

OUTPUT:

```
=====
Feature can not be added without phone name
=====
Phone Name: Samsung Note 20
Display: 6.1 inch
=====
=====
Phone Name: Iphone 12 Pro
Display: 6.2 inch
Ram: 6 GB
=====
Phone Name: Iphone 12 Pro
Display: 6.2 inch, Amoled panel
Ram: 6 GB, DDR5
=====
```

Task - 6

Design and implement the **Student** so that the following code gives the expected output
You are not allowed to change the given code.

Hint:

- You need to use class/static variables

Write Your Code Here

```
s1 = Student("Naruto", "CSE")
print('-----')
s1.individualInfo()
print('#####')
s1.totalInfo()
print('=====')

s2 = Student("Sakura", "BBA")
print('-----')
s2.individualInfo()
print('#####')
s2.totalInfo()
print('=====')

s3 = Student("Shikamaru", "CSE")
print('-----')
s3.individualInfo()
print('#####')
s3.totalInfo()
print('=====')

s4 = Student("Deidara", "BBA")
print('-----')
s4.individualInfo()
print('#####')
s4.totalInfo()
```

Output:

```
Creating Student Number: 1
-----
Naruto is from CSE department.
Serial of Naruto among all students' is: 1
Serial of Naruto in CSE department is: 1
#####
Total Number of Student: 1
Total Number of CSE Student: 1
Total Number of BBA Student: 0
=====
Creating Student Number: 2
-----
Sakura is from BBA department.
Serial of Sakura among all students' is: 2
Serial of Sakura in BBA department is: 1
#####
Total Number of Student: 2
Total Number of CSE Student: 1
Total Number of BBA Student: 1
=====
Creating Student Number: 3
-----
Shikamaru is from CSE department.
Serial of Shikamaru among all students' is: 3
Serial of Shikamaru in CSE department is: 2
#####
Total Number of Student: 3
Total Number of CSE Student: 2
Total Number of BBA Student: 1
=====
Creating Student Number: 4
-----
Deidara is from BBA department.
Serial of Deidara among all students' is: 4
Serial of Deidara in BBA department is: 2
#####
Total Number of Student: 4
Total Number of CSE Student: 2
Total Number of BBA Student: 2
```

Task - 7

Implement the design of the **fiction** and the **nonfiction** classes that inherit from **book** class so that the following code generates the output below:

Driver Code	Output
<pre>class book: def __init__(self, name): self.name = name self.genre='biography' def review(self): print('This book is just out of the world,mind-blowing!') # Write your code here b1 = fiction('The Shining','Psychological horror') b2 = nonfiction('A Beautiful Mind') b1.review() print('=====') b2.review() print('=====')</pre>	<pre>The Shining which is a Psychological horror is just out of the world, mind-blowing! ===== A Beautiful Mind which is a biography is just out of the world, mind-blowing! =====</pre>

Task - 8

Implement the **Intel** and the **AMD** class that inherit from **Processor** class so that the following code generates the output below:

Driver Code	Output
<pre>class Processor: def __init__(self, model, thread, core): self.model = model self.core = core self.thread = thread def getInfo(self): return "Model:" + self.model + "\nCores:" + str(self.core) + "\nThreads:" + str(self.thread) # Write your code here p1 = Intel("Intel i5 10th Gen",6,12,17000) p2 = AMD("Ryzen 5 3500X",6,6,13800) p3 = AMD("Ryzen 5 3600",6,12,16900) print('=====') p1.getInfo() print('=====') p2.getInfo() print('=====') p3.getInfo()</pre>	<pre>===== Model: Intel i5 10th Gen Cores: 6 Threads: 12 Price: 17000 taka ===== Model: Ryzen 5 3500X Cores: 6 Threads: 6 Price: 13800 taka ===== Model: Ryzen 5 3600 Cores: 6 Threads: 12 Price: 16900 taka</pre>

Task - 9

Write the **Mango** and **Jackfruit** class which are derived from the **fruit** class with the required methods to give the following outputs as shown.

[Hint: total price=weight * unit price]

Do not change the following lines of code.

Class Fruit:

Total_order=0

def __init__(self, Order_ID, weight):

self.Order_ID=Order_ID

self.weight=weight

Fruit.Total_order=Fruit.Total_order+1

def __str__(self):

return self.Order_ID+", Weight:

"+str(self.weight)

class Mango(Fruit):

#write your code here

class JackFruit(Fruit):

#write your code here

m1=Mango("Order Id 1", 5,"GopalVog",250)

print(m1)

m2=Mango("Order Id 2", 5,"HariVanga", 230)

print(m2)

j1=JackFruit("Order Id 3", 5,250)

print(j1)

j2=JackFruit("Order Id 4", 4,210)

print(j2)

print("Total number of Orders:

"+str(Fruit.Total_order))

print("=====")

print(m1+m2)

print("=====")

print(j1+j2)

OUTPUT:

Order Id 1, Weight: 5, Variety: GopalVog,
Total Price: 1250

Order Id 2, Weight: 5, Variety: HariVanga,
Total Price: 1150

Order Id 3, Weight: 5, Total Price: 1250

Order Id 4, Weight: 4, Total Price: 840

Total number of Orders: 4

=====

The total Price of the orders are: 2400

=====

The total Price of the orders are: 2090

Task - 10

Write the **CSEStudent** class with the required methods to give the following outputs as shown. **Hints:**

1. Each course has 3 credits.
2. $GPA = \frac{\sum(\text{per course grade} * \text{per course credit})}{\sum(\text{credit attended in that semester})}$
3. **Grading policy:** mark \geq 85: 4.0 ; 80 \leq mark \leq 84: 3.3;70 \leq mark \leq 79:3.0 ;65 \leq mark \leq 69: 2.3; 57 \leq mark \leq 64:2.0 ; 55 \leq mark \leq 56:1.3; 50 \leq mark \leq 54:1.0; >50:0.0

Driver Code	Output
<pre> class Student: def __init__(self,name,ID): self.name = name self.ID = ID def Details(self): return "Name: "+self.name+"\n"+"ID: "+self.ID+"\n" #Write your code here Bob = CSEStudent("Bob","20301018","Fall 2020") Carol = CSEStudent("Carol","16301814","Fall 2020") Anny = CSEStudent("Anny","18201234","Fall 2020") print("#####") print(Bob.Details()) print("#####") print(Carol.Details()) print("#####") print(Anny.Details()) print("#####") Bob.addCourseWithMarks("CSE111",83.5,"CSE230",73.0,"CSE260",92.5) Carol.addCourseWithMarks("CSE470",62.5,"CSE422",69.0,"CSE460",76.5,"CSE461",87.0) Anny.addCourseWithMarks("CSE340",45.5,"CSE321",95.0,"CSE370",91.0) print("-----") Bob.showGPA() print("-----") Carol.showGPA() print("-----") Anny.showGPA() </pre>	<pre> ##### Name: Bob ID: 20301018 Current semester: Fall 2020 ##### Name: Carol ID: 16301814 Current semester: Fall 2020 ##### Name: Anny ID: 18201234 Current semester: Fall 2020 ##### ----- Bob has taken 3 courses. CSE111: 3.3 CSE230: 3.0 CSE260: 4.0 GPA of Bob is: 3.43 ----- Carol has taken 4 courses. CSE470: 2.0 CSE422: 2.3 CSE460: 3.0 CSE461: 4.0 GPA of Carol is: 2.83 ----- Anny has taken 3 courses. CSE340: 0.0 CSE321: 4.0 CSE370: 4.0 GPA of Anny is: 2.67 </pre>

Task - 11

Design **Bus** class and **Train** class which inherit **Transport** class so that the following code provides the expected output.

Note: A passenger can carry upto 2 bags for free. 60 taka will be added if the number of bags is between 3 and 5. 105 taka will be added if the number of bags is greater than 5.

```
class Transport:
    total_traveller = 0

    def __init__(self, name, fare):
        self.name = name
        self.baseFare = fare

    def __str__(self):
        s = "Name: " + self.name + ", Base fare: " + str(self.baseFare)
        return s

# Write your codes here.
# Do not change the following lines of code.
t1 = Bus("Volvo", 950)
print("=====")
t1.addPassengerWithBags("David", 6, "Mike", 1, "Carol", 3)
print("=====")
print(t1)
print("=====")
t2 = Train("Silk City", 850)
print("=====")
t2.addPassengerWithBags("Bob", 2, "Simon", 4)
print("=====")
print(t2)
print("=====")
print("Total Passengers in Transport: ", Transport.total_traveller )
```

OUTPUT:

Base-fare of Volvo is 950 Taka

=====

Name: Volvo, Base fare: 950

Total Passenger(s): 3

Passenger details:

Name: David, Fare: 1055

Name: Mike, Fare: 950

Name: Carol, Fare: 1010

=====

Base-fare of Silk City is 850 Taka

=====

Name: Silk City, Base fare: 850

Total Passenger(s): 2

Passenger details:

Name: Bob, Fare: 850

Name: Simon, Fare: 910

=====

Total Passengers in Transport: 5

Task - 12

Write **MacBookPro2020** class and **iPhone12** class which inherit **AppleProduct** class so that the following code provides the expected output. You need to overwrite necessary methods along with operator overloading.

Hint:

- Base price for MacBookPro2020 is 1299
- Base price of iPhone12 is 799
- Total tax = (base price * rate of tax) / 100
- Total price = base price + total tax

```
class AppleProduct:
    def __init__(self, name, model,
base_price):
    self.name = name
    self.model = model
    self.base_price = base_price
    def companyInfo(self):
        st = ("Company Name: Apple\nFouder: Steve
Jobs, Steve Wozniak, Ronald Wayne\nCurrent
CEO: Tim Cook\nAddress: Apple Inc, 2511
Laguna Blvd, Elk Grove, CA 95758, United
States")
        return st
    def feature(self):
        st = (f"Name: {self.name}\nProduct Model:
{self.model}\nHardware Quality: Excellent
Hardwares\nGuarantee/ Warranty: Apple Care")
        return st
    def __str__(self):
        print('This is apple product.')
    def calculatePrice(self):
        print('Total Price:', self.base_price)

# Write your codes here.
# Do not change the following lines of code.

m1 = MacBookPro2020('MacBook',
'MacBookPro2020', 8, 'M1', 10)
print(m1)
print('=====')
```

OUTPUT:

Product Details:

Name: MacBook

Product Model: MacBookPro2020

Hardware Quality: Excellent Hardwares

Guarantee/ Warranty: Apple Care

RAM: 8GB

Chip: M1

Company Details:

Company Name: Apple

Fouder: Steve Jobs, Steve Wozniak, Ronald Wayne

Current CEO: Tim Cook

Address: Apple Inc, 2511 Laguna Blvd, Elk Grove, CA 95758, United States

=====

Calculating Total Price:

Base Price: 1299

Tax: 10%

Total Price: 1428.9

#####

Product Details:

Name: iPhone

Product Model: iPhone 12

Hardware Quality: Excellent Hardwares

Guarantee/ Warranty: Apple Care

RAM: 8GB

Chip: A14

Company Details:

Company Name: Apple

<pre> m1.calculatePrice() print('#####') iphone = iPhone12('iPhone', 'iPhone 12', 8, 'A14', 5) print(iphone) print('=====') iphone.calculatePrice() print('#####') print('Total Price of these two products: ',end='') print('%.2f Dollars'%(m1 + iphone)) </pre>	<p>Fouder: Steve Jobs, Steve Wozniak, Ronald Wayne</p> <p>Current CEO: Tim Cook</p> <p>Address: Apple Inc, 2511 Laguna Blvd, Elk Grove, CA 95758, United States</p> <p>=====</p> <p>Calculating Total Price:</p> <p>Base Price: 799</p> <p>Tax: 5%</p> <p>Total Price: 838.95</p> <p>#####</p> <p>Total Price of these two products: 2267.85 Dollars</p>
---	--

Task - 13

Write the CSE_dept and PHR_dept class with the required methods to give the following outputs as shown.

<pre> class University: name = "ABC University" numberOfStudents = 0 admissionFee = 28000 Library = 2000 def __init__(self, n,i): self.stName = n self.stId = i def payment(self): return self.admissionFee + self.Library def __str__(self): return "Student Name: {}, ID: {}\nFee: {}".format(self.stName, self.stId, self.payment()) # Write your codes here. # Do not change the following lines of code. c1 = CSE_dept("Mary","5678") print(c1) c1.payment_details() print("=====") </pre>	<p>OUTPUT:</p> <p>Student Name: Mary, ID: 5678</p> <p>Fee: 80050</p> <p>DETAILS:</p> <p>Admission Fee: 28000</p> <p>Library Fee: 2000</p> <p>Semester Fee: 7700</p> <p>Per Credit Fee: 6600</p> <p>Number of credits: 6</p> <p>Lab Fee: 2750</p> <p>=====</p> <p>Student Name: Simon, ID: 91011</p> <p>Fee: 100400</p> <p>DETAILS:</p> <p>Admission Fee: 28000</p> <p>Library Fee: 2000</p> <p>Semester Fee: 11000</p> <p>Per Credit Fee: 6600</p> <p>Number of credits: 9</p> <p>=====</p>
---	--

```

p1 = PHR_dept("Simon","91011")
print(p1)
p1.payment_details()
print("=====")
c2 = CSE_dept("Adam","1234", 12)
print(c2)
c2.payment_details()
print("=====")
p2 = PHR_dept("David","121314", 15)
print(p2)
p2.payment_details()
print("=====")
print("Total Number of Students:",
University.numberOfStudents)
print("Total University Revenue:", (c1 + c2) + (p1 + p2))
print("=====")
print("Due to the pandemic, admission and library fees
have been reduced for all departments. ")
University.admissionFee -= 1000
University.Library -= 100
print("The credit, semester and lab fees have been
reduced for the CSE department. ")
CSE_dept.PerCreditFee -= 100
CSE_dept.SemesterFee -= 100
CSE_dept.LabFee -=100
print("The credit and semester fees have been reduced
for the PHR department.\n ")
PHR_dept.PerCreditFee -= 100
PHR_dept.SemesterFee -= 1000
print(c1)
print(p1)
print(c2)
print(p2)
print("=====")
print("Total Number of Students:",
University.numberOfStudents)
print("Total University Revenue:", (c1 + c2) + (p1 + p2))

```

Student Name: Adam, ID: 1234
Fee: 119650

DETAILS:
Admission Fee: 28000
Library Fee: 2000
Semester Fee: 7700
Per Credit Fee: 6600
Number of credits: 12
Lab Fee: 2750
=====

Student Name: David, ID: 121314
Fee: 140000

DETAILS:
Admission Fee: 28000
Library Fee: 2000
Semester Fee: 11000
Per Credit Fee: 6600
Number of credits: 15
=====

Total Number of Students: 4
Total University Revenue: 440100
=====

Due to the pandemic, admission and library fees
have been reduced for all departments.
The credit, semester and lab fees have been
reduced for the CSE department.
The credit and semester fees have been reduced
for the PHR department.

Student Name: Mary, ID: 5678
Fee: 78150
Student Name: Simon, ID: 91011
Fee: 97400
Student Name: Adam, ID: 1234
Fee: 117150
Student Name: David, ID: 121314
Fee: 136400
=====

Total Number of Students: 4
Total University Revenue: 429100

Task - 14

Implement the “Student” class that is derived from the “Library” class.

```
class Library:
    Total_book = 1000
    borrow_data = {}

    def __init__(self,n,id):
        self.student_name = n
        self.student_id = id

    def borrowbook(self):
        print("A book is borrowed!")

    def __str__(self):
        return "Library: XYZ"
```

#Write your code here

```
s1 = Student("Alice",18101259)
s1.borrowbook("The Alchemist", "Hdw652")
print("=====")
print(s1)
print("=====")
print(Library.borrow_data)
print("=====")
s1.borrowbook("Wuthering Heights")
print("=====")
print(s1)
print("=====")
s2= Student("David",18141777)
s2.borrowbook("The Alchemist", "Hdw652")
print("=====")
s2.borrowbook("The Vampyre")
print("=====")
print(Library.borrow_data)
print("=====")
s1.returnAllBooks()
print("=====")
print(Library.borrow_data)
```

```
A book is borrowed!
'The Alchemist' book with the unique id Hdw652 is borrowed
by Alice(18101259)
Number of books available for borrowing = 999
=====
Library: XYZ
Student Name: Alice ID: 18101259
Books borrowed: The Alchemist
=====
{'The Alchemist': ['Alice']}
=====
A book is borrowed!
'Wuthering Heights' book is borrowed by Alice(18101259)
Number of books available for borrowing = 998
=====
Library: XYZ
Student Name: Alice ID: 18101259
Books borrowed: The Alchemist, Wuthering Heights
=====
Sorry David ! The Alchemist book is borrowed by Alice
=====
A book is borrowed!
'The Vampyre' book is borrowed by David(18141777)
Number of books available for borrowing = 997
=====
{ 'The Alchemist': ['Alice'], 'Wuthering Heights': ['Alice'], 'The
Vampyre': ['David']}
=====
All Books are returned by Alice.
=====
{'The Vampyre': ['David']}
```

Task - 15

Implement the “FootballPlayer” class that is derived from the “Player” class.
[Assume that every player name will consist of 2 words(First name, Last name).]

```
class Player:
    database={}
    playerNo = 0
    def __init__(self,name,team,jerseyNo):
        self.name = name
        self.team = team
        self.jerseyNo = jerseyNo
    def __str__(self):
        return "Name:{}\nTeam:{}\nJersey
No:{}".format(self.name,self.team,self.jerseyNo)
```

#Write your code here

```
print("Number of players:",Player.playerNo)
print("Player Database:",Player.database)
print("#####")
p1 = FootballPlayer("Lionel Messi","Barcelona",10,231)
print("-----Details of the player-----")
print(p1)
print("#####")
p2 = FootballPlayer("Cristiano Ronaldo","Juventus",7,215)
print("-----Details of the player-----")
print(p2)
print("#####")
p3 = FootballPlayer.createPlayer("Miroslav Klose","Lazio",11,
71,"11 Aug,2014")
print("-----Details of the player-----")
print(p3)
print("#####")
print("Number of players:",Player.playerNo)
print("Player Database:",Player.database)
```

Output

```
Number of players: 0
Player Database: {}
#####
-----Details of the player-----
Player ID:1LM10
Name:Lionel Messi
Team:Barcelona
Jersey No:10
Goals Scored:231
Retirement date:Not yet retired
#####
-----Details of the player-----
Player ID:2CR7
Name:Cristiano Ronaldo
Team:Juventus
Jersey No:7
Goals Scored:215
Retirement date:Not yet retired
#####
-----Details of the player-----
Player ID:3MK11
Name:Miroslav Klose
Team:Lazio
Jersey No:11
Goals Scored:71
Retirement date:11 Aug,2014
#####
Number of players: 3
Player Database: {'1LM10': ['Lionel Messi',
'Barcelona', 10, 231, 'Not yet retired'], '2CR7':
['Cristiano Ronaldo', 'Juventus', 7, 215, 'Not yet
retired'], '3MK11': ['Miroslav Klose', 'Lazio', 11,
71, '11 Aug,2014']}
```