

Formula field

SUBTITLE

Heading 1

Heading 2

Heading 3

Heading 4

Logical condition

Keyword	Syntax & Purpose	Example Use Case
IF	IF(logical_test, value_if_true, value_if_false)	IF(ISPICKVAL(StageName, 'Closed Won'), "Win!", "Active") (Determines a simple status label.)
AND	AND(logical1, logical2, ...)	AND(AnnualRevenue > 100000, NumberOfEmployees > 50) (Checks if <i>all</i> conditions are met.)
OR	OR(logical1, logical2, ...)	OR(ISPICKVAL(Priority, 'High'), CreatedDate = TODAY()) (Checks if <i>any</i> condition is met.)
NOT	NOT(logical_test)	NOT(ISBLANK(CloseDate)) (Checks if the field is NOT blank.)
CASE	CASE(expression, value1, result1, value2, result2, else_result)	CASE(BillingCountry, "USA", 0.10, "Canada", 0.15, 0.20) (Returns a specific tax rate based on country.)

2. Text/String Keywords (For Text Manipulation)

Keyword	Syntax & Purpose	Example Use Case
&	<code>text1 & text2</code> (Concatenation Operator)	FirstName & " " & LastName (Creates a full name.)
TEXT	<code>TEXT(value)</code> (Converts a number/date/picklist value into text.)	"The amount is: " & TEXT(Amount) (Used to mix numbers with text.)
VALUE	<code>VALUE(text)</code> (Converts a text string to a number.)	VALUE(External_ID_c) + 1 (Used if you need to perform math on a text field.)
MID	<code>MID(text, start_num, num_chars)</code> (Extracts a specific number of characters.)	MID(SerialNumber_c, 4, 3) (Pulls the 3-digit product code from a serial number.)
LEFT/RIGHT	<code>LEFT(text, num_chars) / RIGHT(text, num_chars)</code> (Extracts characters from the beginning or end.)	LEFT(AccountName, 1) (Pulls the first letter of the account name.)
BLANKVALUE	<code>BLANKVALUE(expression, substitute_expression)</code> (Returns a substitute if the expression is blank.)	BLANKVALUE(ShippingStreet, MailingStreet) (Uses Mailing Street if Shipping Street is empty.)

Function	What It Does	Example
CONCAT()	Joins multiple text values	CONCAT(FirstName, " ", LastName)
LEFT(text, num_chars)	Gets left part of a text	LEFT(Account.Name, 5)
RIGHT(text, num_chars)	Gets right part of text	RIGHT(Email, 3)
LEN(text)	Length of text	LEN(Phone)
LOWER(), UPPER()	Case conversion	UPPER(FirstName)
TRIM()	Removes spaces	TRIM(Name)
BEGINS(text, compare_text)	Returns TRUE if starts with...	BEGINS(Email, "sales@")
CONTAINS(text, compare_text)	Returns TRUE if contains...	CONTAINS(Email, ".org")
TEXT()	Converts number/date/picklist to text	TEXT(StageName)

3. Date & Time Keywords (For Time Calculations)

Keyword	Syntax & Purpose	Example Use Case
TODAY	TODAY() (Returns the current date only, with no time.)	TODAY() - CreatedDate (Calculates the number of days a record has been open.)
NOW	NOW() (Returns the current date and time.)	NOW() - LastModifiedDate (Calculates the time elapsed since the last update.)
DATE	DATE(year, month, day) (Returns a Date value from year, month, and day inputs.)	DATE(YEAR(TODAY()), MONTH(TODAY()), 1) (Calculates the first day of the current month.)
YEAR/MONTH/DAY	YEAR(date) / MONTH(date) / DAY(date) (Extracts the specific component from a Date field.)	MONTH(CloseDate) (Pulls the month number from the Close Date.)
ADDMONTHS	ADDMONTHS(date, num_months) (Adds/subtracts a number of months to a date.)	ADDMONTHS(Service_Start_Date__c, 12) (Calculates a one-year contract end date.)

Function	What It Does	Example
TODAY()	Current date	TODAY() - CreatedDate
NOW()	Current date & time	NOW() - LastModifiedDate
DATE(year, month, day)	Creates a date	DATE(2025, 12, 31)
YEAR(date), MONTH(date), DAY(date)	Extract parts	MONTH(CloseDate)
DATEVALUE(datetime)	Converts datetime → date	DATEVALUE(CreatedDate)
DATETIMEVALUE(text)	Converts text → datetime	DATETIMEVALUE("2025-01-01 00:00:00")
CASESAFEID(Id)	Converts 15-char ID → 18-char	CASESAFEID(Id)
ADDMONTHS(date, num)	Adds months	ADDMONTHS(TODAY(), 6)

4. Check/Validation Keywords (For Data Quality)

ISBLANK	ISBLANK(expression) (Checks if a field has no value. Works on text, number, and date fields.)	IF(ISBLANK(Next_Step__c), "Needs Follow-up", "On Track")
ISNULL	ISNULL(expression) (Similar to ISBLANK, but generally for numbers, dates, and currency.)	IF(ISNULL(Discount__c), 0, Discount__c) (Treats a null discount as 0.)
ISPICKVAL	ISPICKVAL(picklist_field, text_literal) (Checks the value of a non-multi-select picklist field.)	ISPICKVAL(StageName, 'New Lead') (Only works in validation rules and formula fields.)
ISCHANGED	ISCHANGED(field) (Checks if the value of a field has been changed by the user.)	ISCHANGED(OwnerId) (Mostly used in Validation Rules, Workflow Rules, and Process Builder/Flow.)

Function	What It Does	Example
IF(condition, true_value, false_value)	Conditional logic	IF(Amount > 10000, "High", "Low")
CASE(expression, when1, then1, when2, then2, else)	Multi-condition switch	CASE(StageName, "Prospecting", 10, "Closed Won", 100, 0)
BLANKVALUE(expr1, expr2)	If blank, use fallback	BLANKVALUE(Discount__c, 0)
ISBLANK(field)	Checks blank (Older, same as	ISBLANK(Phone)
ISNULL(field)	ISBLANK for non-text fields)	ISNULL(Email)
ISPICKVAL(field, text)	Checks picklist value	ISPICKVAL(StageName, "Closed Won")
TEXT(picklist)	Converts picklist to text	TEXT(StageName)

Operators:

Operator	Name	Purpose	Example
+ / - / * / /	Math Operators	Addition, Subtraction, Multiplication, Division.	(Amount * 0.10) / 1.15
= / !=	Equality	Equals to / Not equals to.	RecordType.Name != "Admin"
> / < / >= / <=	Comparison	Greater than, Less than, Greater than or equal to, Less than or equal to.	CloseDate < TODAY()
&	Text Concatenation	Joins two strings of text together.	"ID: " & Account_Number__c
()	Parentheses	Groups expressions to control the order of operations. Use heavily!	(Amount - Discount) * Tax

Function	What It Does	Example
Cross-object reference	Access parent object fields	Account . AnnualRevenue on Opportunity
\$User	Reference current user info	\$User . Department, \$User . Id
\$Profile	Current user's profile info	\$Profile . Name
\$Organization	Org-level info	\$Organization . Name
\$RecordType	Record type ID/name	\$RecordType . Name

Function	What It Does	Example
VLOOKUP()	Lookup a value from another object (special use)	VLOOKUP(\$ObjectType.Pricebook2.Fields.Name, Name, "Standard Price Book")
HYPERLINK(url, friendly_name)	Creates clickable link	HYPERLINK("/" & Id, Name)
IMAGE(url, alt_text, height, width)	Shows image	IMAGE("/img/samples/flag_green.gif", "Green", 15, 15)
PRIORVALUE(field)	Value before record update (for validation/workflow)	PRIORVALUE(StageName)

1.

salesforce

```
IF(
  AND(
    ISPICKVAL(StageName, "Closed Won"),
    Amount > 10000
  ),
  "🏆 Big Win – " & TEXT(Account.Name),
  "Regular Deal"
)
```

2.

Example 2: Opportunity Win Probability Category Formula: IF(Probability > 75, " Hot", IF(Probability > 40, " Warm", " Cold"))

Why it matters: Visually categorize sales opportunities using nested IFs.

Tip: Limit nesting; for complex logic, consider CASE() instead of deep IF chains.

3.

Example 5: Smart Lead Score Label Formula: CASE(TRUE, Score__c >= 90, " Elite", Score__c >= 70, " Promising", Score__c >= 40, " Nurture", " Cold")

Why it matters: Demonstrates advanced CASE logic with Boolean evaluation.

CASE(TRUE, ...) lets you write readable, scalable logic — cleaner than nested IFs!

Example 4: Subscription Renewal Reminder Formula:

```
IF( TODAY() > (Renewal_Date__c - 30), " Renew Soon", " Active" )
```

Why it matters: Flags records for attention before critical renewal dates.

Remember: Use `TODAY()` for date comparisons, not `NOW()`

