US 20220228708A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2022/0228708 A1**

Chao (43) **Pub. Date: Jul. 21, 2022**

(54) **MAGNETIC ATTACHMENT MULTI-CONFIGURATION GRIPPING CLIP FOR ELECTRONIC DEVICES**

(71) Applicant: **Vitec Imaging Solutions Spa**, Cassola (VI) (IT)

(72) Inventor: **Hen-Li Philip Chao**, Livingston, NJ (US)

(21) Appl. No.: **17/576,940**

(22) Filed: **Jan. 15, 2022**

Related U.S. Application Data

(60) Provisional application No. 63/138,399, filed on Jan. 16, 2021, provisional application No. 63/177,967, filed on Apr. 22, 2021.

Publication Classification

(51) **Int. Cl.**


F16M 13/02	(2006.01)
F16B 1/00	(2006.01)
H04M 1/04	(2006.01)

(52) **U.S. Cl.**

CPC ... ***F16M 13/022*** (2013.01); *F16B 2001/0035* (2013.01); ***H04M 1/04*** (2013.01); ***F16B 1/00*** (2013.01)

(57) **ABSTRACT**

A support for holding an electronic device, such as a cellular telephone, that attaches to the electronic device with a magnetic connector. The support may have support arms that can grip the electronic device. A magnetic mounting surface may include an annular magnet at its outer area, which is adapted to magnetically hold an electronic device such as a cellular telephone. The support arms may be able to move from a first position perpendicular to the magnetic mounting surface to a second positions parallel to the magnetic mounting surface. The support arms may be extendible from a central portion and this extension may be resisted by internal springs. A cellular telephone may be held within the extended arms to provide gripping support to the telephone. In the parallel configuration, the extendable arms may provide a further mounting surface for stability of the phone on its magnetic mounting surface.






FIGURE 1A




FIGURE 1B




FIGURE 1C




FIGURE 1D




FIGURE 1E




FIGURE 1F




FIGURE 2A




FIGURE 2B




FIGURE 3A




FIGURE 3B




FIGURE 3C




FIGURE 4A




FIGURE 4B




FIGURE 5A




FIGURE 5B




FIGURE 5C




FIGURE 6A




FIGURE 6B




FIGURE 7A




FIGURE 7B



FIGURE 7C




FIGURE 7D




FIGURE 7E




FIGURE 8A




FIGURE 8B




FIGURE 8C




FIGURE 9A




FIGURE 9B




FIGURE 10A




FIGURE 10B




FIGURE 11A




FIGURE 11B




FIGURE 11C




FIGURE 12A




FIGURE 12B




FIGURE 13A




FIGURE 13B




FIGURE 14




FIGURE 15A




FIGURE 15B




FIGURE 15C




FIGURE 16




FIGURE 17




FIGURE 18




FIGURE 19A




FIGURE 19B




FIGURE 19C




FIGURE 20




FIGURE 21A




FIGURE 21B




FIGURE 22A




FIGURE 22B




FIGURE 23




FIGURE 24A




FIGURE 24B




FIGURE 25




FIGURE 26A




FIGURE 26B




FIGURE 26C




FIGURE 26D




FIGURE 26E




FIGURE 26F




FIGURE 27A




FIGURE 27B




FIGURE 28A




FIGURE 28B




FIGURE 29A




FIGURE 29B




FIGURE 30A




FIGURE 30B




FIGURE 30C




FIGURE 30D




FIGURE 30E




FIGURE 30F




FIGURE 30G




FIGURE 30H




FIGURE 30I




FIGURE 30J




FIGURE 30K




FIGURE 30L




FIGURE 30M




FIGURE 30N




FIGURE 30O




FIGURE 30P




FIGURE 30Q




FIGURE 30R




FIGURE 30S




FIGURE 30T




FIGURE 30U




FIGURE 30V




FIGURE 30X




FIGURE 30Y




FIGURE 30Z




FIGURE 30AA




FIGURE 31A




FIGURE 31B




FIGURE 31C




FIGURE 32A




FIGURE 32B




FIGURE 33A




FIGURE 33B




FIGURE 33C




FIGURE 34A




FIGURE 34B




FIGURE 35A




FIGURE 35B




FIGURE 35C




FIGURE 36




FIGURE 37A




FIGURE 37B




FIG. 38A




FIG. 38B




FIG. 38C




FIG. 39A




FIG. 39B




FIG. 39C




FIG. 40




FIG. 41A




FIG. 41B




FIG. 41C




FIG. 41D




FIG. 41E




FIG. 42A




FIG. 42B




FIG. 43A




FIG. 43B




FIG. 43C




FIG. 44




FIG. 45A




FIG. 45B




FIG. 45C




FIG. 46A




FIG. 46B

MAGNETIC ATTACHMENT MULTI-CONFIGURATION GRIPPING CLIP FOR ELECTRONIC DEVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 63/138,399 to Chao, filed Jan. 16, 2021, which is hereby incorporated by reference in its entirety. This application claims the benefit of U.S. Provisional Application No. 63/177,967 to Chao, filed Apr. 22, 2021, which is hereby incorporated by reference in its entirety.

BACKGROUND

Field of the Invention

[0002] The present invention relates to accessories for an electronic device, and more particularly to a magnetic attachment for attaching and/or using the device.

Description of Related Art

[0003] Cellular telephones are increasingly used to support video conferencing and other video activities. Also, users may want to be able to support other accessory items, and may want to have them attached to the telephone, or to its case.

[0004] What is called for is a device which can provide a more secure way to hold the device, such as a cellular telephone, and which can support accessories.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIGS. **1**A-**1**F are views of a clip support with magnetic connector according to some embodiments of the present invention.

[0006] FIGS. **2**A-**2**B present views of a clip support with magnetic connector supporting a cellphone according to some embodiments of the present invention.

[0007] FIGS. **3**A-**3**C are views of a clip support with magnetic connector according to some embodiments of the present invention.

[0008] FIGS. **4**A-B present views of a clip support with magnetic connector supporting a cellphone according to some embodiments of the present invention.

[0009] FIGS. **5**A-**5**C are views of a microphone with magnetic connector according to some embodiments of the present invention.

[0010] FIGS. **6**A-**6**B are views of a microphone with magnetic connector on a cellphone according to some embodiments of the present invention.

[0011] FIGS. **7**A-**7**E are views of a flip up light with magnetic connector according to some embodiments of the present invention.

[0012] FIGS. **8**A-**8**C are views of a flip up light with magnetic connector in a flipped up configuration according to some embodiments of the present invention.

[0013] FIGS. **9**A-**9**B present views of a flip up light with magnetic connector on a cell phone according to some embodiments of the present invention.

[0014] FIGS. **10**A-**10**B present views of a flip up light with magnetic connector in a flipped up configuration on a cell phone according to some embodiments of the present invention.

[0015] FIGS. **11**A-**11**C present views of a support with magnetic connector according to some embodiments of the present invention.

[0016] FIGS. **12**A-**12**B present views of a support with magnetic connector on a cell phone according to some embodiments of the present invention.

[0017] FIGS. **13**A-**13**B present views of an adhesive support with magnetic connector according to some embodiments of the present invention.

[0018] FIG. **14** presents oblique views of an adhesive support with magnetic connector on a cell phone according to some embodiments of the present invention.

[0019] FIGS. **15**A-**15**C present views of a magnetic connector with cold shoe mount according to some embodiments of the present invention.

[0020] invention.

[0021] FIG. **16** presents oblique views of a magnetic connector with cold shoe mount on a cell phone according to some embodiments of the present invention.

[0022] FIG. **17** presents oblique views of a magnetic connector with a parallel plate mount according to some embodiments of the present invention.

[0023] FIG. **18** presents oblique views of a magnetic connector with a parallel plate mount on a cell phone according to some embodiments of the present invention.

[0024] FIG. **19**A-**19**C present views of a magnetic connector with legs according to some embodiments of the present invention.

[0025] FIG. **20** is an oblique view of a magnetic connector with legs in a stowed configuration on a cell phone according to some embodiments of the present invention.

[0026] FIGS. **21**A-**21**B are views of a magnetic connector with legs in a deployed configuration on a cell phone according to some embodiments of the present invention.

[0027] FIGS. **22**A-**22**B present views of a clip support with magnetic connector according to some embodiments of the present invention.

[0028] FIG. **23** is a view of a clip support with magnetic connector on a cell phone according to some embodiments of the present invention.

[0029] FIGS. **24**A-**24**B present views of a clip support with ring and magnetic connector according to some embodiments of the present invention.

[0030] FIG. **25** is a view of a clip support with ring and magnetic connector on a cell phone according to some embodiments of the present invention.

[0031] FIGS. **26**A-**26**F are views of a support with magnetic connector and arms in a flat configuration according to some embodiments of the present invention.

[0032] FIGS. **27**A-B are views of a support with magnetic connector and arms in a flat configuration with cell phone according to some embodiments of the present invention.

[0033] FIGS. **28**A-**28**B are views of a support with magnetic connector and arms in a gripping configuration according to some embodiments of the present invention.

[0034] FIGS. **29**A-**29**B are views of a support with magnetic connector and arms in a gripping configuration with a cell phone according to some embodiments of the present invention.

[0035] FIGS. **30**A-**30**AA are views of a second embodiment of a magnetic gripping clip according to some embodiments of the present invention.

[0036] FIGS. **31**A-**31**C are views of a support with magnetic connector and vent clip according to some embodiments of the present invention.

[0037] FIGS. **32**A-**32**B are views of a support with magnetic connector and vent clip and cell phone according to some embodiments of the present invention.

[0038] FIGS. **33**A-**33**C are views of an auxiliary battery with magnetic connector and vent clip according to some embodiments of the present invention.

[0039] FIGS. **34**A-**34**B are views of an auxiliary battery with magnetic connector and vent clip on a cell phone according to some embodiments of the present invention.

[0040] FIGS. **35**A-C are views of an auxiliary battery and battery holder with magnetic connector and vent clip according to some embodiments of the present invention.

[0041] FIG. **36** presents orthogonal views of a clip support with cold shoes and magnetic connector according to some embodiments of the present invention.

[0042] FIG. **37**A-**37**B are views of a clip support with a deployable cold shoe and magnetic connector according to some embodiments of the present invention.

[0043] FIG. **38**A-**38**C are views of a device support with magnetic connector according to some embodiments of the present invention.

[0044] FIG. **39**A is an oblique view of a device support with magnetic connector according to some embodiments of the present invention.

[0045] FIG. **39**B is an oblique view of a device support with magnetic connector according to some embodiments of the present invention.

[0046] FIG. **39**C is an oblique view of a device support with magnetic connector according to some embodiments of the present invention.

[0047] FIG. **40** is an oblique view of a device support with magnetic connector according to some embodiments of the present invention.

[0048] FIGS. **41**A-**41**E are views of a device support with magnetic connector according to some embodiments of the present invention.

[0049] FIGS. **42**A-**42**B are views of a device support with magnetic connector according to some embodiments of the present invention.

[0050] FIGS. **43**A-**43**C are views of a magnetic charger holder according to some embodiments of the present invention.

[0051] FIG. **44** presents views of a magnetic connector according to some embodiments of the present invention.

[0052] FIGS. **45**A-**45**C present views of a device support with magnetic connector according to some embodiments of the present invention.

[0053] FIGS. **46**A-**46**B illustrate views of a second embodiment of a magnetic gripping clip on a tripod according to some embodiments of the present invention.

SUMMARY OF THE INVENTION

[0054] A support for holding an electronic device, such as a cellular telephone, that attaches to the electronic device with a magnetic connector. The support may have support arms that can grip the electronic device. A magnetic mounting surface may include an annular magnet at its outer area, which is adapted to magnetically hold an electronic device such as a cellular telephone. The support arms may be able to move from a first position perpendicular to the magnetic mounting surface to a second positions parallel to the magnetic mounting surface. The support arms may be extendible from a central portion and this extension may be resisted by internal springs. A cellular telephone may be held within the extended arms to provide gripping support to the telephone. In the parallel configuration, the extendable arms may provide a further mounting surface for stability of the phone on its magnetic mounting surface.

DETAILED DESCRIPTION

[0055] In some embodiments of the present invention, as seen in FIGS. **1**A-**1**F, a clip support with magnetic connector **100** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the clip support **100** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **100** may have a circular, or substantially circular, connection body **101** coupled to a first bracket support **102**. The first bracket support **102** is coupled to a second bracket support **104**. The first bracket support **102** and the second bracket support **104** may be joined at a right angle. The bottom surface **108** of the second bracket support **104** may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **106**. The magnetic coupler **103** may present a flat surface **107** such that the surface **107** is adapted to couple to a magnetic coupling area of a cellular telephone. Side rails **105** on the second bracket support **104** allow for insertion and retention by a clip receiver, as may be seen on a tripod or other support structure.

[0056] FIG. **11**C illustrates a cross-section of a magnetic coupling body as seen in embodiments of the present invention. A front cover **245** provides the mating surface to the device, such as a cellular telephone. In some aspects, the front cover **245** may be of a frictional or resilient material to add to the security of the attachment. A circular magnet **243** resides within the coupling body **244**. In some aspects, the circular magnet **243** may have an exterior diameter of 54 mm and an interior diameter of 46 mm, and may be 2.25 mm thick. The circular magnet **243** allows for coupling of the cellular telephone to the clip support, or other accessory as described herein, to a mating magnetic, or magnetically susceptible, interface which also may circular in nature. The circular nature of the interface allows for held positional fit of the clip support to the cellular telephone, and may draw the clip support into this concentric fit if attached close to concentrically initially.

[0057] FIG. **2**A illustrates a cellular telephone **110** coupled to a clip support with magnetic connector **100** in a landscape configuration. The rear side **113** of the cellular telephone **110** may contain a circular magnetic interface feature. Camera lenses **111** may allow for imaging away from the rear side **113** of the cellular telephone **110**. The front side **112** of the cellular telephone **110** is away from the clip support **100**. FIG. **2**B illustrates a cellular telephone **110** coupled to a clip support with magnetic connector **100** in a portrait configuration.

[0058] In some embodiments of the present invention, as seen in FIGS. **3**A-**3**C, a clip support with magnetic connector **140** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the clip support **140** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **140** may have a circular, or

substantially circular, connection body **141** coupled to a first bracket support **142**. The first bracket support **142** is coupled to a second bracket support **144**. The first bracket support **142** and the second bracket support **104** may be joined at a right angle. The bottom surface **108** of the second bracket support **144** may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **146**. The magnetic coupler may present a flat surface **143** such that the surface **147** is adapted to couple to a magnetic coupling area of a cellular telephone. Side rails **15** on the second bracket support **14** allow for insertion and retention by an Arca-Swiss clip receiver, as may be seen on a tripod or other support structure.

[0059] FIG. **4**A illustrates a cellular telephone **110** coupled to a clip support with magnetic connector **140** in a landscape configuration. FIG. **4**B illustrates a cellular telephone **110** coupled to a clip support with magnetic connector **140** in a portrait configuration.

[0060] In some embodiments of the present invention, as seen in FIGS. **5**A-**5**C, a microphone with magnetic connector **180** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the microphone **180** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The microphone **180** may have a circular, or substantially circular, connection body **183**. The circular body may include battery and one or more microphones. An on-off switch may also be found on the exterior of the circular body. In some aspects, the microphone battery may be recharged using a charger with a cable such as a USB cable, and may have the appropriate port. In some aspects, the microphone battery may be charged without a cable, such as with a magsafe system. The microphone may be covered with an appropriate wind screening material **181**. The microphone **180** may be annular with a through hole **182**. FIGS. **6**A-**6**B illustrate the microphone with magnetic connector on a cellular telephone **110**.

[0061] In some embodiments of the present invention, as seen in FIGS. **7**A-**7**C, a deployable light with magnetic connector **220** is adapted to magnetically couple to an electronic device, such as a cellular telephone.

[0062] In some aspects, the deployable light **220** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The deployable light **220** may have a circular, or substantially circular, connection body **223**. The connection body may have a cover **235** which provides the mating surface to the device, such as a cellular telephone. In some aspects, the cover **235** may be of a frictional or resilient material to add to the security of the attachment. A magnet, which may be a circular magnet, resides within the coupling body connection. In some aspects, the circular, annular, magnet may have an exterior diameter of 54 mm and an interior diameter of 46 mm, and may be 2.25 mm thick. The circular magnet allows for coupling of the cellular telephone to the deployable light, to a mating magnetic, or magnetically susceptible, interface which also may circular in nature. The circular nature of the interface allows for held positional fit of the clip support to the cellular telephone, and may draw the clip support into this concentric fit if attached close to concentrically initially.

[0063] An extension portion **231** of the connection body **223** may culminate in a pivot **221** which is adapted to allow for the deployment of a lighting element **230**. In some aspects, the connection body **223** may include a battery electrically coupled to the lighting element **230**. In some aspects, the battery may reside within the annulus of the circular magnet. An on/off button and cord ports for charging may be found on the extension **222** or other suitable location.

[0064] In the stowed configuration of FIGS. **7**A-**7**C, the lighting element **230** is laid over the connection body. The lighting element **224** may be a circular, annular, lighting element with an inner surface **234**. The connection body **223** may have a raised external surface **235**. In some aspects, the inner surface **234** of the lighting element **224** may reside around external surface **235** of the connection body **223** in the stowed configuration. In some aspects, the lighting element **224** is comprised of a plurality of LEDs arranged in a circular pattern.

[0065] FIG. **7**D illustrates a variation of the lighting element further including a tab **239** which is an extension of the back surface **235** of the connection body **223***a*. The lighting element **224***a* of this variation may also have a recess **229** to allow room for the tab **239**. This tab **230** and recess **229** may allow a user to utilize the recess **229**, for example with a fingernail, to more easily move the lighting element from the stowed configuration to the deployed configuration. FIG. **7**E illustrates an exploded view of a connection body **223**, illustrating a battery **226** which may reside in a recess **227** within the annulus of the circular magnet. A top surface plate **225** of the connection body resides over the battery **226** and is the outside surface of this portion of the connection body.

[0066] FIGS. **8**A-**8**C illustrate the lighting element in a deployed configuration. In the deployed configuration the lighting element has been deployed 180 degrees from its position in the stowed configuration. The deployable light may have detents, or a mechanical stop, such that the lighting element is held in the deployed configuration with sufficient force that the lighting element will not pivot away from the deployed configuration in normal use, without further force purposefully applied by the user. A gap **238** between the raised external surface **235** of the connection body **223** and the raised area of the extension portion **231** allows the circular lighting element **224** to fit into the gap when the deployable light **220** is in the stowed configuration.

[0067] A charging port **236** is adapted to allow for the coupling of an external charging cord to the deployable light. In some aspects, the charging port may be compatible with a USB-C plug. One or more control buttons **237** allow the user to turn the lighting element of the deployable light on and off. In some aspects, the control buttons **237** may also allow the user to select various brightness levels for the light.

[0068] FIGS. **9**A and **9**B illustrate the deployable light **220** on a cellular telephone **110**, with the light in a stowed configuration. The magnet within the connection body **223** has magnetically coupled to the cellular telephone **110**. This stowed configuration allows for the light to shine in a direction to the rear of the cellular telephone. FIGS. **10**A and **10**B illustrate the deployable light **220** on a cellular telephone **110**, with the light in a deployed configuration. This deployed configuration allows for the light to shine in a direction to the front of the cellular telephone. In the deployed configuration, a user may use the cellular telephone for video recording or communication using the forward facing camera function of the cellular telephone,

which may allow the user to observe themself in real time during the video call, for example.

[0069] In some embodiments of the present invention, as seen in FIGS. **11**A-**11**C, a support with magnetic connector **240** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the support **240** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The support **240** may have a circular, or substantially circular, connection body **241** which presents a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. A threaded insert **242** allows for attachment of the support **240** to a support structure with a threaded post. FIGS. **12**A and **12**B illustrate the support **240** on a cellular telephone **110**.

[0070] In some embodiments of the present invention, as seen in FIGS. **13**A and **13**B a support with magnetic connector **260** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the support **260** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The support **260** may have a circular, or substantially circular, connection body **265** which presents a flat surface **261** such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. An adhesive surface **265** allows for attachment of the support **260** to a surface. FIG. **14** illustrates the support **260** on a cellular telephone **110**.

[0071] In some embodiments of the present invention, as seen in FIGS. **15**A-**15**C, a cold shoe clip with magnetic connector **280** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the cold shoe clip with magnetic connector **180** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The cold shoe clip with magnetic connector **180** may have a circular, or substantially circular, connection body **281**. The circular body may include an extension with a cold shoe clip **284**. The cold shoe clip may have a bottom mounting surface **285**. A tightening nut **283** is adapted to cinch down and tighten to hold the cold shoe clip to it mating interface. FIG. **16** illustrate the cold shoe clip with magnetic connector **280** on a cellular telephone **110**.

[0072] In some embodiments of the present invention, as seen in FIG. **17**, a support with magnetic connector **300** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the support **300** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The support **300** may have a circular, or substantially circular, connection body which presents a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. A multi-planar extension **301** allows for attachment of the support **300** to a support structure with a mating structure. FIG. **18** illustrates the support **300** on a cellular telephone **110**.

[0073] In some embodiments of the present invention, as seen in FIGS. **19**A-**19**C, a tripod with magnetic connector **320** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the tripod with magnetic connector **320** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The tripod with magnetic connector **320** may have a circular, or substantially circular, connection body which presents a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. A trio of legs **322**, **323**, **324** is adapted to stow in plane with each other and the connection body, and to pivot **325** to a deployed configuration. The legs may have plug extensions **327**.

[0074] FIG. **20** illustrates the tripod with magnetic connector **320** in a stowed configuration on a cellular telephone **110**. FIGS. **21**A and **21**B illustrate the tripod with magnetic connector **320** in a deployed position with the legs **322**, **323**, **324** extended in order to support a cellular telephone.

[0075] In some embodiments of the present invention, as seen in FIGS. **22**A and **22**B, a clip with magnetic connector **360** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the clip with magnetic connector **360** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip with magnetic connector **360** may have a circular, or substantially circular, connection body **361**. The circular body may include a recess **363** with a clip **362** within the recess, which may be adapted to clip into a clip receiver, such as may be seen on a tripod. FIG. **23** illustrate the clip with magnetic connector **360** on a cellular telephone **110**.

[0076] In some embodiments of the present invention, as seen in FIGS. **24**A and **24**B, a clip and ring with magnetic connector **380** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the clip and ring with magnetic connector **380** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip and ring with magnetic connector **380** may have a circular, or substantially circular, connection body. The circular body may include a recess **383** with a clip **382** within the recess, which may be adapted to clip into a clip receiver, such as may be seen on a tripod. A deployable ring **384** may also reside in the recess **383**. The ring **384** may stow into the recess, and the deploy to allow for the insertion of a finger, for example. FIG. **25** illustrates the clip and ring with magnetic connector **380** on a cellular telephone **110**.

[0077] In some embodiments of the present invention, as seen in FIGS. **26**A-**26**F, a first embodiment of a magnetic gripping clip for an electronic device **400** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the gripping clip with magnetic connector **400** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The gripping clip with magnetic connector **400** may have a circular, or substantially circular, magnetic connection body **401**. The circular magnetic connection body may be coupled to a clip body cross bracket **403** which may be rotatably coupled to the clip main post. The cross bracket may be centrally connected, at its center, to the main post **402**. The clip body cross bracket has a first gripping arm **404** and a second gripping arm **405**, which may be extendable relative to the clip body cross bracket **403**. A main post **402** has a first end and a second end. The first end of said main post is coupled to the clip body cross bracket **403**. A mount **408** is coupled to the main post. The mount **408** may have a threaded insert **409** such that the mount **408** may be coupled to threaded post, such as seen on a tripod.

[0078] FIGS. **26**C-**26**F illustrate the gripping arms **404**, **405** in a flat configuration. FIGS. **26**B and **28**A-B illustrate the gripping arms **404**, **405** in a gripping configuration. The

gripping arms **404**, **405** are adapted to rotate from a position in plane with the clip body **403** to a gripping position perpendicular to the clip body at a twist interface **406**, **407**. The twist interface may have detents such that the gripping arms can be set either in plane, or perpendicular, as shown comparatively in FIGS. **26**A and **26**B, for example. The gripping arms may be extendable outward, and resisted with springs within the clip body, allowing for gripping of devices of various dimension.

[0079] FIGS. **27**A and **27**B illustrate the gripping clip with magnetic connector **400** with a cellular telephone **110**. The flat configuration allows for the coupling of the cellular telephone when no extra forces are placed upon the cellular telephone, for example. FIGS. **29**A and **29**B illustrate the gripping clip with magnetic connector **400** with a cellular telephone **110** in a gripping configuration. The gripping configuration allows for the coupling of the cellular telephone when extra forces may be placed upon the cellular telephone, for example, and provides the security of the gripping arms to maintain telephone retention.

[0080] In some embodiments of the present invention, as seen in FIGS. **30**A-**30**AA, a second embodiment of a magnetic gripping clip for an electronic device **420** is adapted to magnetically couple to and support an electronic device, such as a cellular telephone. In some aspects, the magnetic gripping clip for an electronic device **420** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The magnetic gripping clip for an electronic device **420** may have a circular, or substantially circular, magnetic connection body **401**. The circular magnetic connection body may be coupled to a clip body cross bracket **403** which may be rotatably coupled to the clip main post. The cross bracket may be centrally connected, at its center, to the main post **440**. The clip body cross bracket has a first gripping arm **404** and a second gripping arm **405**, which may be extendable relative to the clip body cross bracket **403**. The gripping arms **404**, **405** are adapted to rotate from a position in plane with the clip body **403** to a gripping position perpendicular to the clip body at a twist interface **406**, **407**. The twist interface may have detents such that the gripping arms can be set either in plane, or perpendicular. The gripping arms may be extendable outward, and resisted with springs within the clip body, allowing for gripping of devices of various dimension. A main post **440** has a first end and a second end. The first end of the main post is coupled to the clip body cross bracket **403**. The second end the main post may have various threaded mounting inserts coupled to the main post. The mount **408** may have a threaded insert **428** on a bottom surface such that the mount **408** may be coupled to threaded post, such as seen on a tripod.

[0081] FIGS. **30**A-C illustrate the magnetic gripping clip **420** in a first configuration wherein the first gripping arm **404** and the second gripping arm **404** are positioned to be parallel to the mounting surface of the magnetic connection body **401**. The cross bracket **403** is perpendicular to the main post in this exemplary configuration. In such a configuration, a device such as a cellular telephone can magnetically couple to the magnet in the magnetic connection body. The extended gripping arms present a planar surface extension which may support the back surface of the cellular telephone. The planar surface extension reduces the torque which might be put onto the magnetic connection by limiting the amount of overhang of the telephone from the mounting surface. In contrast, FIGS. **30**D-G illustrate the magnetic gripping clip **420** wherein the first gripping arm **404** and the second gripping arm **404** are positioned to be parallel to the mounting surface of the magnetic connection body **401**. The first extension arm **424** and the first gripping arm **404** are seen extended from the cross bracket **403** on a first sliding section **425**, and the second extension arm **423** and the second gripping arm **405** are seen extended from the cross bracket **403** on a second sliding section **426**. In some aspects, the sliding sections **425**, **426** resist extension with the use of one or more springs configures to resist the extension of the extension arms. FIGS. **30**H-J further illustrate the magnetic gripping clip **420** which a cellular telephone mounted therein. In this exemplary configuration, the extension arms **423**, **424** have been somewhat extended, showing a portion of the sliders **425**, **426**. The cellular telephone **430** is magnetically held in place on the mounting connection body **401**, and then is further held by the gripping arms **404**, **405**, which are pulled in by the springs within the cross bracket **403**. The gripping arms **404**, **405** are adapted to rotate from a position in plane with the clip body **403** to a gripping position perpendicular to the clip body at a twist interface **406**, **407**. The twist interface may have detents such that the gripping arms can be set either in plane, or perpendicular, as shown comparatively in FIGS. **26**A and **26**B, for example. The gripping arms may be extendable outward, and resisted with springs within the clip body, allowing for gripping of devices of various dimension. The gripping arms **404**, **405** are in a configuration perpendicular to the mounting surface of the mounting connection body. Resilient pads **431**, **432** reset into the gripping arms **404**, **405** help hold the cellular telephone firmly.

[0082] FIGS. **30**K-M illustrate the magnetic gripping clip **420** in a configuration where the cross bracket **403** is perpendicular to the main post **440**, and the gripping arms **404**, **405** are configured to be parallel to the mounting surface of the mounting connection body. As can be seen, the extended surface provided by the gripping arms in this configuration enhances the stability of the mounting of the cellular telephone **430** to the magnetic gripping clip **440** despite not using the gripping aspect of the clip. The plane of the backside of the gripping arms is coplanar with the mounting surface of the mounting connection body.

[0083] FIGS. **30**N-**0** illustrate the magnetic gripping clip in an orientation wherein the cross bracket **403** is at an angle (45 degrees) to the main post **440** with the gripping arms in a configuration perpendicular to the magnetic mounting surface. A rotatable joint **434** between the cross bracket and the main post may be set with detents that allow for the cross bracket to be rotated when enough rotational force in applied, but then snaps into preset angular positions that then have sufficient detent for normal use.

[0084] FIGS. **30**P-Q illustrate the magnetic gripping clip in an orientation wherein the cross bracket **403** is at an angle (45 degrees) to the main post **440** with the gripping arms in a configuration parallel to the magnetic mounting surface. A rotatable joint **434** between the cross bracket and the main post may be set with detents that allow for the cross bracket to be rotated when enough rotational force in applied, but then snaps into preset angular positions that then have sufficient detent for normal use.

[0085] FIGS. **30**R-V illustrate the magnetic gripping clip in an orientation wherein the cross bracket **403** is parallel to the main post **440** with the gripping arms in various con-

figurations. A rotatable joint **434** between the cross bracket and the main post may be set with detents that allow for the cross bracket to be rotated when enough rotational force in applied, but then snaps into preset angular positions that then have sufficient detent for normal use.

[0086] FIGS. **30**X-Y illustrate the magnetic gripping clip **420** with a cellular telephone **430** mounted in a configuration wherein the cross bracket **403** is parallel to the main post **440** and the gripping arms are perpendicular to the magnetic mounting surface, and gripping the telephone. FIGS. **30**Z-AA illustrate the magnetic gripping clip **420** with a cellular telephone **430** mounted in a configuration wherein the cross bracket **403** is parallel to the main post **440** and the gripping arms are parallel to the magnetic mounting surface, and providing further mounting surface support for the telephone.

[0087] In some embodiments of the present invention, as seen in FIGS. **46**A-B, a magnetic gripping clip **420** supports a telephone **430**. The magnetic gripping clip is mounted onto a tripod **441**. In some aspects, the tripod **441** has a threaded post **442** which screws in the threaded mating insert on the bottom of the main post of the magnetic gripping clip **420**. Flexible extensions **443** are fastened to threaded mating inserts along the side of the main post of the magnetic gripping clip and allow for further mounting of accessories, such as lights and other devices.

[0088] In some embodiments of the present invention, as seen in FIGS. **30**A-**30**C, a platform vent clip with magnetic connector **460** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the platform vent clip with magnetic connector **460** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The platform vent clip with magnetic connector **460** may have a circular, or substantially circular, magnetic connector **461** with a platform **462**. The platform **462** may also have a magnetic key **463** for interfaces which include a keyed interface. The platform **462** may be coupled to a vent clip **464**. The vent clip may have an internal recess **406** with a compressible pad **406**. A tightening ring **467** may tighten the vent clip into place, and may be used in conjunction a ball joint. In an exemplary use, the platform vent clip with magnetic connector may be placed onto a fin of an auto vent, and a cellular telephone then placed upon the platform and magnetically coupled. FIGS. **31**A and **31**B illustrate a cellular telephone **110** on a vent clip with magnetic connector **460**.

[0089] In some embodiments of the present invention, as seen in FIGS. **32**A-**32**C, an auxiliary battery with magnetic connector **500** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the auxiliary battery with magnetic connector **500** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The auxiliary battery with magnetic connector **500** may have a circular, or substantially circular, connection body **501**. The circular body may contain a battery within it that is adapted to provide power to a mated device. A cord connector **503** and cable slot **504** may facilitate powered recharging of the auxiliary battery. FIGS. **33**A and **33**B illustrate the auxiliary battery with magnetic connector **500** coupled to a cellular telephone **110**.

[0090] In some embodiments of the present invention, as seen in FIGS. **34**A-**34**C, an auxiliary battery and receptacle **540** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the auxiliary battery and receptacle **540** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The circular body may contain a battery within it that is adapted to provide power to a mated device. A recess **543** is adapted to receive a puck type charger as may be used with a cellular telephone. The puck may reside within the recess against a surface **544** and may be contained with a slight interference fit. A cord connector **544** and cable slot **555** may facilitate powered recharging of the auxiliary battery. The charging puck may have its cable plugged into the cord connector **544** to allow the use of the charging puck to route the battery power from the auxiliary battery and receptacle **540**. The auxiliary battery and receptacle **540** with a charging puck in its recess may then be magnetically coupled to the cellular telephone.

[0091] In some embodiments of the present invention, as seen in FIGS. **36**A and **36**B, a clip support with magnetic connector is seen with a flip out cold shoe mount.

[0092] In embodiments of the present invention, device supports with a magnetic connector are adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The device support may have a circular, or substantially circular, connection body coupled to a bracket support, or the circular magnetic interface may be embedded within a surface of the device support. The magnetic coupler may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone.

[0093] FIG. **44** illustrates a cross-section of a magnetic coupling body as seen in embodiments of the present invention. A front cover **245** provides the mating surface to the device, such as a cellular telephone. A circular magnet **243** resides within the coupling body **244**. In some aspects, the circular magnet **243** may have an exterior diameter of 54 mm and an interior diameter of 46 mm, and may be 2.25 mm thick. The circular magnet **243** allows for coupling of the cellular telephone to the clip support, or other accessory as described herein, to a mating magnetic, or magnetically susceptible, interface which also may circular in nature. The circular nature of the interface allows for held positional fit of the clip support to the cellular telephone, and may draw the clip support into this concentric fit if attached close to concentrically initially.

[0094] In some embodiments of the present invention, as seen in FIGS. **38**A-**38**C, a device support with magnetic connector, folding stand, and rotating mount **600** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **600** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **600** may have a circular, or substantially circular, connection body **603** rotatably coupled to a first bracket support **602**. The first bracket support **602** is pivotally coupled to a second bracket support **601**. The first bracket support **602** and the second bracket support **601** may be joined at pivot adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The bottom surface of the second bracket support **601** may be a flat surface adapted to reside on a support, such as a tripod head, and may be

fastened to a threaded post of a tripod or other support using the threaded insert **607**. The magnetic coupler **603** may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. The pivoting of the rotatable connection body **603** allows the magnetic interface to face either direction. Side rails **604** on the second bracket support **601** may be extendable to act as an outrigger for enhanced stability.

[0095] In some embodiments of the present invention, as seen in FIG. **39**A, a device support with magnetic connector, folding stand, and rotating mount **620** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **620** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **620** may have a first bracket support **625** rotatably and pivotally coupled to a second bracket support **621**. The first bracket support **625** is rotatably coupled at a pivot joint to a second bracket support **621**. The first bracket support **625** and the second bracket support **621** may be joined at pivot adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The bottom surface of the second bracket support may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **622**. The magnetic coupler **626** may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. The second bracket support **621** may spread out at a sliding coupler **628** such that a first portion **621***a* and a second portion **621***b* configure for enhanced stability.

[0096] In some embodiments of the present invention, as seen in FIG. **39**B, a device support with magnetic connector, folding stand, and rotating mount **640** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **640** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **640** may have a first bracket support **645** spherically coupled to a second bracket support **641**. The first bracket support **645** and the second bracket support **641** may be adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The bottom surface of the second bracket support may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **642**. The magnetic coupler **646** may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. The second bracket support **641** may spread out at a sliding coupler such that a first portion **641***a* and a second portion **641***b* configure for enhanced stability. The second bracket support may have interfaces **647** adapted to fit into tripod mounting clips.

[0097] In some embodiments of the present invention, as seen in FIG. **39**C, a device support with magnetic connector and rotating mount **660** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **660** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The clip support **660** may have a first bracket support **665** spherically coupled to a second bracket support **661**. The first bracket support **665** and the second bracket support **661** may be adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The first bracket **665** may have a mirror **666** on a side opposite of the magnetic interface. The bottom surface of the second bracket support may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **662**. The magnetic coupler **646** may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. The second bracket support **661** may spread out at a sliding coupler such that a first portion **661***a* and a second portion **661***b* configure for enhanced stability. The second bracket support may have interfaces **667** adapted to fit into tripod mounting clips.

[0098] FIG. **40** illustrates another embodiment **680** of a device support with magnetic connector and rotating mount. The device support **680** represents another variation of a folding base with spreadable portions, wherein the upper bracket may both pivot and rotate relative to the lower bracket.

[0099] In some embodiments of the present invention, as seen in FIGS. **41**A-E, a device support with magnetic connector **700** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **700** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The circular magnetic interface may be embedded within a band **704**. The device support **700** may have a first bracket support **701** pivotally coupled to a second bracket support **702**. The first bracket support **701** and the second bracket support **702** may be adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The bottom surface of the second bracket support may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **705**. The magnetic coupler **704** may present a flat surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. FIGS. **4**D and **4**E illustrate a cellular telephone **710** coupled to the device support **700**.

[0100] In some embodiments of the present invention, as seen in FIGS. **42**A-B, a device support with magnetic connector and charger **740** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the device support **700** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface **751**. The circular magnetic interface may include a charging aspect adapted to charge a supported device, such as a cellular telephone. The device support **740** may have a first bracket support **741** pivotally coupled to a second bracket support **742** at a pivot **743**. The first bracket support **741** and the second bracket support **742** may be adapted to allow for placing into different angular configurations while having sufficient holding force to retain the position once placed. The bottom surface of the second bracket support may be a flat surface adapted to reside on a support, such as a tripod head, and may be fastened to a threaded post of a tripod or other support using the threaded insert **745**. The magnetic coupler **740** may present a flat

surface such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone.

[0101] In some embodiments of the present invention, as seen in FIGS. **43**A-C, a charger support **760** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the charger support **760** couples to a charging disc which contains a circular interface adapted to couple to a cellular telephone. In this way the charger support **760** may support the cellular telephone through the intermediate coupling of the charger support **760**. The device support **760** may have a first bracket support **760** with a recesses **764** within protruding bracket arms **763**. The first bracket support **760** is coupled to a second bracket support portion **762**. The second bracket support portion may act as a stand alone support or may be coupled to a tripod or other device. A magnetic coupling charging disc **765** may reside within the recesses **764**. The charging disc may include an external power cord **766** which may route through a slot **767** within the bracket.

[0102] In some embodiments of the present invention, as seen in FIGS. **45**A-C a support with magnetic connector **800** is adapted to magnetically couple to an electronic device, such as a cellular telephone. In some aspects, the support **800** couples to a cellular telephone with a magnetic or magnetically susceptible interface, which may be a circular interface. The support **800** may have a circular, or substantially circular, connection body which presents a flat surface **802** such that the surface is adapted to couple to a magnetic coupling area of a cellular telephone. An adhesive surface **803** allows for attachment of the support **260** to a surface. The adhesive mounting surface **803** may be parallel to the flat surface **802** for mounting to a cellular telephone. A plurality of slots **801** within the central portion **804** of the connection body are adapted to allow for routing, and fastening, of a power cord which may be coupled to the supported device. The power cord may be routed through a hollow central section which is accessed through the slots **801**. When the device is removed from the support, the cord may thusly remain with the support **800**. A front cover provides the mating surface to the device, such as a cellular telephone. In some aspects, the front cover may be of a frictional or resilient material to add to the security of the attachment. A circular magnet resides within the connection body. In some aspects, the circular magnet may have an exterior diameter of 54 mm and an interior diameter of 46 mm, and may be 2.25 mm thick. The circular magnet allows for coupling of the cellular telephone to the clip support, or other accessory as described herein, to a mating magnetic, or magnetically susceptible, interface which also may circular in nature. The circular nature of the interface allows for held positional fit of the clip support to the cellular telephone, and may draw the clip support into this concentric fit if attached close to concentrically initially.

[0103] As evident from the above description, a wide variety of embodiments may be configured from the description given herein and additional advantages and modifications will readily occur to those skilled in the art. The invention in its broader aspects is, therefore, not limited to the specific details and illustrative examples shown and described. Accordingly, departures from such details may be made without departing from the spirit or scope of the applicant's general invention.

1. A magnetic gripping clip for an electronic device, said magnetic gripping clip comprising:

a main post, said main post having a first end and a second end;

a cross bracket, said cross bracket centrally coupled along a back surface to said first end of said main post; and

a magnetic connection body, said magnetic connection body comprising:

a flat mounting surface on a first side; and

a magnet within said magnetic connection body under said flat mounting surface.

2. The magnetic gripping clip of claim **1** further comprising:

a first extension arm on a first side of said cross bracket; and

a second extension arm of a second side of said cross bracket.

3. The magnetic gripping clip of claim **2** further comprising:

a first gripping arm coupled to said first extension arm; and

a second gripping arm coupled to said second extension arm.

4. The magnetic gripping clip of claim **3** wherein said first extension arm is extendable from said cross bracket, and wherein said second extension arm is extendable from said cross bracket.

5. The magnetic gripping clip of claim **4** wherein the extension of said first extension arm from said cross bracket is resisted by a spring, and wherein the extension of said second extension arm from said cross bracket is resisted by a spring.

6. The magnetic gripping clip of claim **4** wherein said first gripping arm is rotatable from a first position parallel to said flat mounting surface to a second position perpendicular to said flat mounting surface, and wherein said second gripping arm is rotatable from a first position parallel to said flat mounting surface to a second position perpendicular to said flat mounting surface.

7. The magnetic gripping clip of claim **5** wherein said first gripping arm is rotatable from a first position parallel to said flat mounting surface to a second position perpendicular to said flat mounting surface, and wherein said second gripping arm is rotatable from a first position parallel to said flat mounting surface to a second position perpendicular to said flat mounting surface.

8. The magnetic gripping clip of claim **6** wherein said first gripping arm comprises a resilient portion along a device mounting surface of said first gripping clip, and wherein said second gripping arm comprises a resilient portion along a device mounting surface of said second gripping clip.

9. The magnetic gripping clip of claim **7** wherein said first gripping arm comprises a resilient portion along a device mounting surface of said first gripping clip, and wherein said second gripping arm comprises a resilient portion along a device mounting surface of said second gripping clip.

10. The magnetic gripping clip of claim **8** wherein said cross bracket is rotatably coupled to said main post.

11. The magnetic gripping clip of claim **9** wherein said cross bracket is rotatably coupled to said main post.

12. The magnetic gripping clip of claim **1** wherein said main post comprises a threaded mounting insert on a bottom surface of said main post.

13. The magnetic gripping clip of claim **8** wherein said main post comprises a threaded mounting insert on a bottom surface of said main post.

14. The magnetic gripping clip of claim **10** wherein said main post comprises a threaded mounting insert on a bottom surface of said main post.

15. The magnetic gripping clip of claim **11** wherein said main post comprises a threaded mounting insert on a bottom surface of said main post.

16. The magnetic gripping clip of claim **14** wherein said main post comprises one or more threaded mounting inserts along its side surface.

17. The magnetic gripping clip of claim **15** wherein said main post comprises one or more threaded mounting inserts along its side surface.

18. The magnetic gripping clip of claim **1** where said magnet is an annular magnet under an outer area of said flat mounting surface.

19. The magnetic gripping clip of claim **11** where said magnet is an annular magnet under an outer area of said flat mounting surface.

20. The magnetic gripping clip of claim **15** where said magnet is an annular magnet under an outer area of said flat mounting surface.

* * * * *