

App Integration Guide

For new app developers

Connect reports, tutorials, catalog and plans. Version 1.0.

1. Connect your app in 4 steps

Step 1 - Ask the Nexus admin for two things: (a) an API key (starts with kn_live_) and (b) your appId (Mongo ObjectId).

Step 2 - Send the key on every request in the x-api-key header.

Step 3 - Implement Reports (section 3) so users can send feedback.

Step 4 - Implement Help/Tutorial (section 4) using cached content.

Base URL is your Nexus domain, e.g. <https://kwl-nexus.onrender.com>

Keep the API key secret: ship it as a build secret, never in chat.

2. Authentication and limits

Header: x-api-key: kn_live_... (Authorization: Bearer also works)

Rate limit: 1000 requests per hour per key (shared by all installs).

401 = missing/invalid/revoked key. 429 = slow down and retry later.

404 on /apps/<id>/... usually means a wrong appId or unpublished app.

3. Reports API - POST /api/feedback

Send user reports (errors, suggestions, feature requests, ratings).

Required: appId, type, title (3-160 chars), description (5-5000).

type is one of: bug_report | suggestion | feature_request | rating

Optional: link (problem URL, max 2000), contactEmail, rating 1-5, screenshot (base64/text, max about 1.5MB).

Example: {"appId":"<ObjectId>","type":"bug_report",

```
"title":"Crash on export","description":"Steps: ...",  
"link":"https://...","contactEmail":"user@mail.com"}
```

201 returns { data: { id, status } }. Anything else: queue locally
and retry later - never lose a user report.

4. Tutorial API - GET /api/apps/<id>/tutorial

Public endpoint (no key needed). Powers the in-app Help view.

Response data: title, description, videoUrl/videoType (optional),
sections: [{ heading, bodyMarkdown }] (optional), appName, appSlug.

Cache the response on device and show the cached copy offline.
Refresh in background when online. 404 = no tutorial published yet.

5. Endpoint reference

GET /api/apps - List published apps.
GET /api/apps/[id] - Get one published app by id or slug.
GET /api/apps/[id]/plans - List active plans for an app.
GET /api/apps/popular - List most popular apps.
GET /api/apps/new-releases - List latest new releases.
GET /api/public/apps - Public app directory (no auth).
GET /api/apps/[id]/tutorial - Get tutorial for an app.
GET /api/payment/methods - List active payment methods (filtered HEALTHY).
POST /api/payment/request - Create a pending payment request.
GET /api/payment/status/[id] - Read the authenticated payment status.
GET /api/payment/history - List authenticated payment history.
GET /api/user/profile - Read the authenticated user profile.
GET /api/user/subscriptions - List the authenticated user's subscriptions.
POST /api/feedback - Submit a user report (bug/suggestion/feature/rating).
GET /api/feedback - List the authenticated user's feedback.
GET /api/system-config - Get public branding & system config.
GET /api/update-guidelines - Get latest update guidelines.
GET /api/health - Health check - keep-alive (no auth).
GET /api/ping - Ping - keep-alive alias (no auth).

6. Support

Lost key? The admin revokes it and generates a new one in seconds:

Admin panel > Settings > Project integrations > API keys.

Full interactive docs: <domain>/docs (admin) + test console.

Machine-readable spec: /api/docs/openapi and /api/docs/postman.