

App Integration Guide

For new app developers

Connect reports, tutorials, catalog and plans. Version 2.0.

1. Connect your app (admin + developer)

Step 1 - Admin imports the repo, picks a release, saves details, Publishes.

Note the app slug, e.g. kaziweblab-oss-kwl-video-downloader.

Step 2 - Admin creates an API key scoped to that app, copies it once, and delivers it over a secure channel only (never plain chat).

Step 3 - Developer configures baseUrl + apiKey + appId in the app.

Step 4 - App pings POST /api/apps/<id>/ping on startup and syncs.

2. Authentication, scope and limits

Header: x-api-key: kn_live_... (Authorization: Bearer also works)

One key = one app: scoped keys work only for their app (403 otherwise).

Rate limit: 1000 requests per hour per key (shared by all installs).

401 = missing/invalid/revoked key. 429 = slow down and retry later.

404 on /apps/<id>/... usually means a wrong appId or unpublished app.

3. Reports API - POST /api/feedback

Send user reports (errors, suggestions, feature requests, ratings).

Required: appId, type, title (3-160 chars), description (5-5000).

type is one of: bug_report | suggestion | feature_request | rating

Optional: link (problem URL, max 2000), contactEmail, rating 1-5, screenshot (base64/text, max about 1.5MB).

```
Example: {"appId":"<ObjectId>","type":"bug_report",  
"title":"Crash on export","description":"Steps: ...",  
"link":"https://...", "contactEmail":"user@mail.com"}
```

201 returns { data: { id, status } }. Anything else: queue locally and retry later - never lose a user report.

Replies: poll GET /api/feedback (on Help open) and render adminReply and status (pending / replied / resolved / ignored) to the user.

4. Features + tutorial sync

POST /api/apps/<id>/features with { features: [...] } (max 50).

Replace semantics: what the app sends becomes the master list.

PUT /api/admin/apps/<id>/tutorial with videoUrl/sections (same auth).

The tutorial video doubles as the storefront preview video.

Push on install/update; GET the current list first to compare.

Tutorial API - GET /api/apps/<id>/tutorial is public (no key).

Cache on device, show cached copy offline, refresh when online.

5. Endpoint reference

GET /api/apps - List published apps.

GET /api/apps/[id] - Get one published app by id or slug.

GET /api/apps/[id]/plans - List active plans for an app.

GET /api/apps/popular - List most popular apps.

GET /api/apps/new-releases - List latest new releases.

GET /api/public/apps - Public app directory (no auth).

GET /api/apps/[id]/tutorial - Get tutorial for an app.

GET /api/apps/[id]/features - Get the app master feature list.

POST /api/apps/[id]/features - Replace the app master feature list (desktop sync).

POST /api/apps/[id]/ping - Desktop heartbeat - marks the app API-connected.

GET /api/payment/methods - List active payment methods (filtered HEALTHY).

POST /api/payment/request - Create a pending payment request.

GET /api/payment/status/[id] - Read the authenticated payment status.

GET /api/payment/history - List authenticated payment history.

GET /api/user/profile - Read the authenticated user profile.

GET /api/user/subscriptions - List the authenticated user's subscriptions.
POST /api/feedback - Submit a user report (bug/suggestion/feature/rating).
GET /api/feedback - List the authenticated user's feedback.
GET /api/system-config - Get public branding & system config.
GET /api/update-guidelines - Get latest update guidelines.
GET /api/health - Health check - keep-alive (no auth).
GET /api/ping - Ping - keep-alive alias (no auth).
GET /api/v1/apps - V1 public catalog (published apps, paginated).
GET /api/v1/apps/[slug] - V1 public app metadata by slug.
GET /api/v1/apps/[slug]/latest - V1 update manifest (?platform=&arch=¤t=).
GET /api/v1/apps/[slug]/entitlement - V1 license check (session or scoped x-api-key).

6. Keys, leaks and support

Lost/leaked key? Admin revokes it and generates a new one in seconds:

Admin panel > Settings > Project integrations > API keys.

Full interactive docs: <domain>/docs (admin) + test console.

Machine-readable spec: /api/docs/openapi and /api/docs/postman.