



В СЦЕНАРІЇ від x-flight + Казуар Авіа ПРИСУТНІ обидва VOR/DME **SMF 116.6 MHz** і **SI 112.2 MHz**.



Вони встановлені в одному і тому ж місці, використовуйте будь-який з них.

Частоти ILS співпадають і в сценаріях і на чартах нижче.



Apt Elev
597'


Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'
This chart may only be used for
cross-checking of altitudes assigned
while under RADAR control.



FT/METER CONVERSION

QNH
10010' - 3050m
7060' - 2150m
6070' - 1850m
4430' - 1350m
2960' - 900m

ATIS
122.150 (Russian 127.2)
Apt Elev
597'
Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'



BURUD 1Y
DM 1Y
INBAK 1Y
RWY 01 RNAV ARRIVALS
RNAV (GNSS)
RNAV 1 (P-RNAV) APPROVAL REQUIRED
OTHERWISE ADVISE ATC
SPEED: MAX 250 KT
BELOW 10010'

SIMFEROPOL
116.6 SMF
N45 03.1 E033 58.8



1 Visual manoeuvring (CIRCLING) and visual approach
not authorized between SI R-102/R-137 and
D4.3 Arc SI/D9.7 Arc SI below 2960'.

HOLDINGS OVER


FF270
(Fly-over for holding only)



FFE01
(Fly-over for holding only)



STAR	ROUTING
BURUD 1Y	BURUD (FL140+) - FF275 (9030'+) - FF270 (9030'+) - FFS01 (6070'+) - FF260 (7060'+; 4930'+; K220-) - FF255 (6070'+; 4430'+) - FF250 (6070'+; 4430'+) - FF245 (6070'+; 4430'+) - FF215 (4930'+; 2960'+) - FF210 (2960'+).
DM 1Y	DM (8040'+) - FFE01 (6070'+) - FF265 (7060'+; 4930'+; K220-) - FF255 (6070'+; 4430'+) - FF250 (6070'+; 4430'+) - FF245 (6070'+; 4430'+) - FF215 (4930'+; 2960'+) - FF210 (2960'+).
INBAK 1Y	INBAK (10010'+) - FF275 (9030'+) - FF270 (9030'+) - FFS01 (6070'+) - FF260 (7060'+; 4930'+; K220-) - FF255 (6070'+; 4430'+) - FF250 (6070'+; 4430'+) - FF245 (6070'+; 4430'+) - FF215 (4930'+; 2960'+) - FF210 (2960'+).



BURUD

At or above
FL140





FT/METER CONVERSION	
QNH	
10010'	- 3050m
9030'	- 2750m
8040'	- 2450m
7060'	- 2150m
6070'	- 1850m
4930'	- 1500m
4430'	- 1350m
2960'	- 900m

SIMFEROPOL

RNAV STAR

JEPPESEN
24 AUG 18 10-2AUKFF
SIMFEROPOL

ATIS 122.150 (Russian 127.2)
Apt Elev 597'
Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'




BURUD 1Z
DM 1Z
INBAK 1Z
RWY 19 RNAV ARRIVALS
RNAV (GNSS)
RNAV 1 (P-RNAV) APPROVAL REQUIRED
OTHERWISE ADVISE ATC
SPEED: MAX 250 KT
BELOW 10010'

DMITROVKA
*690 DM
N45 28.7 E035 03.3
At or above
8040'

Visual manoeuvring (CIRCLING) and visual approach
not authorized between SI R-102/R-137 and
D4.3 Arc SI/D9.7 Arc SI below 2960'.

STAR	ROUTING
BURUD 1Z	BURUD (FL140+) - FF485 (10010'+) - FFE02 (6070'+) - FF475 (7060'-; 4930'+; K220-) - FF470 (6070'-; 3940'+) - FF465 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
DM 1Z	DM (8040'+) - FFE02 (6070'+) - FF475 (7060'-; 4930'+; K220-) - FF470 (6070'-; 3940'+) - FF465 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
INBAK 1Z	INBAK (10010'+) - FFS02 (9030'+) - FF480 (6070'+) - FF475 (7060'-; 4930'+; K220-) - FF470 (6070'-; 3940'+) - FF465 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').

HOLDING OVER
FF475
(Fly-over for holding only)




FT/METER CONVERSION	
QNH	
10010'	3050m
9030'	2750m
8040'	2450m
7060'	2150m
6070'	1850m
4930'	1500m
3940'	1200m
2960'	900m





CHANGES: SMF VOR DME revised SI VOR DME.

© JEPPESEN, 2014, 2018. ALL RIGHTS RESERVED.

ATIS 122.150 (Russian) 127.2	Apt Elev 597'	Alt Set: MM (hPa on request) Trans level: By ATC Trans alt: 10010'
---------------------------------	------------------	--



**HOLDING OVER
FF225**
(Fly-over for holding only)



NEROB 1Y
NOMPA 1Y
SOTAM 1Y
TINAL 1Y
TITAG 1Y
RWY 01 RNAV ARRIVALS
RNAV (GNSS)
RNAV 1 (P-RNAV) APPROVAL REQUIRED
OTHERWISE ADVISE ATC
SPEED: MAX 250 KT
BELOW 10010'

FT/METER CONVERSION	
QNH	
10010'	- 3050m
9030'	- 2750m
8040'	- 2450m
7060'	- 2150m
6070'	- 1850m
4930'	- 1500m
3940'	- 1200m
2960'	- 900m




STAR	ROUTING
NEROB 1Y	NEROB (10010'+) - FF235 (8040'+) - FFN01 (8040'+) - FF230 (6070'+) - FF225 (7060'+; 4930'+; K220-) - FF220 (6070'+; 3940'+) - FF215 (4930'-; 2960'+) - FF210 (2960').
NOMPA 1Y	NOMPA (9030'+) - FFN03 (8040'+) - FF230 (6070'+) - FF225 (7060'+; 4930'+; K220-) - FF220 (6070'+; 3940'+) - FF215 (4930'-; 2960'+) - FF210 (2960').
SOTAM 1Y	SOTAM (FL180+) - FF240 (6070'+) - FF225 (7060'-; 4930'+; K220-) - FF220 (6070'+; 3940'+) - FF215 (4930'-; 2960'+) - FF210 (2960').
TINAL 1Y	TINAL (FL150+) - FFW01 (8040'+) - FF240 (6070'+) - FF225 (7060'-; 4930'+; K220-) - FF220 (6070'+; 3940'+) - FF215 (4930'-; 2960'+) - FF210 (2960').
TITAG 1Y	TITAG (9030'+) - FF235 (8040'+) - FFN01 (8040'+) - FF230 (6070'+) - FF225 (7060'+; 4930'+; K220-) - FF220 (6070'+; 3940'+) - FF215 (4930'-; 2960'+) - FF210 (2960').

RNAV STAR

ATIS
122.150
Russian 127.2

Apt Elev
597'

Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'



TINAL

At or above
FL 150

FT/METER CONVERSION

QNH

10010'	-	3050m
9030'	-	2750m
8040'	-	2450m
7060'	-	2150m
6070'	-	1850m
4930'	-	1500m
3940'	-	1200m
2960'	-	900m

SOTAM

At or above
51.120

NOMPA

At or above

TITAG

At or above 9030'

NEROB

At or above 10010'

NEROB 17

NOMPA 17

SOTAM 1Z

TINAI 17

TITAG 17

RWY 19

RNAV ARRIVALS

RNAV (GNSS)

RNAV 1 (P-RNAV) APPROVAL REQUIRED

OTHERWISE ADVISE ATC

SPEED: MAX 250 KT


BELOW 10010'


Below 100%


STAR	ROUTING
NEROB 1Z	NEROB (10010'+) - FF460 (6070'+) - FF455 - FFW02 (6070'+) - FF435 (7060'-; 4930'+; K220-) - FF430 (6070'-; 3940'+) - FF425 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
NOMPA 1Z	NOMPA (9030'+) - FF450 (8040'+) - FFW02 (6070'+) - FF435 (7060'-; 4930'+; K220-) - FF430 (6070'-; 3940'+) - FF425 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
SOTAM 1Z	SOTAM (FL180'+) - FF445 - FFS04 (9030'+) - FF440 (6070'+) - FF435 (7060'-; 4930'+; K220-) - FF430 (6070'-; 3940'+) - FF425 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
TINAL 1Z	TINAL (FL150'+) - FF450 (8040'+) - FFW02 (6070'+) - FF435 (7060'-; 4930'+; K220-) - FF430 (6070'-; 3940'+) - FF425 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').
TITAG 1Z	TITAG (9030'+) - FF460 (6070'+) - FF455 - FFW02 (6070'+) - FF435 (7060'-; 4930'+; K220-) - FF430 (6070'-; 3940'+) - FF425 (6070'-; 3940'+) - FF420 (6070'-; 3940'+) - FF415 (4930'-; 2960'+) - FF410 (2960').

CHANGES: SMF VOR DME revised SI VOR DME.


© JEPPESEN, 2014, 2018. ALL RIGHTS RESERVED.







ATIS
122.150 (Russian 127.2)
 Apt Elev **597'**
 Alt Set: MM (hPa on request)
 Trans level: By ATC Trans alt: 10010'



NOMPA 1N
SOTAM 1N
RWY 19 ARRIVALS

By ATC

SPEED: MAX 250 KT
BELOW 10010'

NOMPAAt or above
9030'

HOLDING
OVER
SI



(IAF)

SIMFEROPOL
116.6 SMF

N45 03.1 E033 58.8

At or above
3940'MAX **220 KT****D18.9 SI**

At or above 6070'

SOTAMAt or above
FL180

FT/METER CONVERSION
QNH

10010' - 3050m
 9030' - 2750m
 6070' - 1850m
 3940' - 1200m
 2960' - 900m


STAR	ROUTING
NOMPA 1N	Intercept SI R-309 inbound to SI.
SOTAM 1N	On 050° track to D18.9 SI, turn RIGHT, intercept SI R-232 inbound to SI.

UKFF
SIMFEROPOL



JEPPESSEN
24 AUG 18 (10-2H)

SIMFEROPOL
STAR

ATIS
122.150 (Russian 127.2)
Apt Elev 597'
Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'



TINAL 1M
TITAG 1M
RWY 01 ARRIVALS
By ATC
SPEED: MAX 250 KT
BELOW 10010'



FT/METER CONVERSION QNH	
10010'	- 3050m
9030'	- 2750m
3940'	- 1200m
2960'	- 900m

STAR	ROUTING
TINAL 1M	Intercept SI R-283 inbound to SI.
TITAG 1M	Intercept SI R-328 inbound to SI.

CHANGES: SMF VOR DME revised SI VOR DME.


© JEPPESEN, 2014, 2018. ALL RIGHTS RESERVED.

UKFF
SIMFEROPOL

JEPPESSEN
24 AUG 18 10-2J

SIMFEROPOL
STAR

ATIS
122.150 (Russian 127.2)
Apt Elev 597'
Alt Set: MM (hPa on request)
Trans level: By ATC Trans alt: 10010'



TINAL IN
TITAG IN
RWY 19 ARRIVALS
By ATC
SPEED: MAX 250 KT
BELOW 10010'

TITAG

At or above
9030'

TINAL

At or above
FL150

HOLDING
OVER
SI



(IAF)

SIMFEROPOL
116.6 SMF

N45 03.1 E033 58.8

At or above
3940'

MAX 220 KT



NOT TO SCALE

FT/METER CONVERSION
QNH

10010' - 3050m
9030' - 2750m
3940' - 1200m
2960' - 900m


STAR	ROUTING
TINAL IN	Intercept SI R-283 inbound to SI.
TITAG IN	Intercept SI R-328 inbound to SI.

CHANGES: SMF VOR DME revised SI VOR DME.


© JEPPESEN, 2014, 2018. ALL RIGHTS RESERVED.

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'


**NOMPA 1X, SOTAM 1X
TINAL 1X, TITAG 1X
RWY 19 RNAV DEPARTURES**
RNAV (GNSS)

RNAV 1 (P-RNAV) APPROVAL REQUIRED, OTHERWISE ADVISE ATC




Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



**RENBA 1K
RENBA 1L
RWYS 01, 19 DEPARTURES**



FT/METER CONVERSION

QNH

2960'	-	900m
3940'	-	1200m
4430'	-	1350m
8040'	-	2450m
9030'	-	2750m
10010'	-	3050m



This SID requires a minimum climb gradient of
RENBA 1L: 7.5% up to 9030'.


Gnd speed-KT	75	100	150	200	250	300
7.5% V/V (fpm)	570	760	1139	1519	1899	2279

If unable to comply advise ATC.

SID	RWY	ROUTING
RENBA 1K	01	Climb on 007° track to D6.7 SI, turn RIGHT, 213° track to SI, turn LEFT, SI R-169 to RENBA.
RENBA 1L	19	Climb on 187° track to D6.7 SI, turn LEFT, 131° track, at SI R-172 turn RIGHT to RENBA.

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



SOGTA 1K
SOGTA 1L
SOGTA 2L
SOTAM 1K
SOTAM 1L
RWYS 01, 19 DEPARTURES


FT/METER CONVERSION

QNH

2960'	-	900m
4430'	-	1350m
6070'	-	1850m
8040'	-	2450m
10010'	-	3050m



NIKOLA
*326 NL
N44 58.0 E033 37.2



These SIDs require minimum climb gradients of

SOGTA 1L: 5.5% up to 8040'.
SOTAM 1L: 6.0% up to 6070'.


Gnd speed-KT	75	100	150	200	250	300
6.0% V/V (fpm)	456	608	911	1215	1519	1823
5.5% V/V (fpm)	418	557	835	1114	1392	1671

If unable to comply advise ATC.

SID	RWY	ROUTING
SOGTA 1K	01	Climb on 007° track to D6.7 SI, turn RIGHT, 063° track, at SI R-033 turn LEFT, intercept SI R-034 to SOGTA.
SOGTA 1L	19	Climb on 187° track to D6.7 SI, turn RIGHT, 049° track to SI, turn LEFT, SI R-034 to SOGTA.
SOGTA 2L		Climb on 187° track to D6.7 SI, turn LEFT, 131° track, at SI R-172, turn LEFT, 022° track to SOGTA.
SOTAM 1K By ATC	01	Climb on 007° track to D6.7 SI, turn RIGHT, 213° track to SI, turn RIGHT, SI R-232 to SOTAM.
SOTAM 1L By ATC	19	Climb on 187° track to D6.7 SI, turn RIGHT, intercept 280° bearing towards NL, at SI R-228 turn LEFT, intercept SI R-232 to SOTAM.

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



TINAL 1K
TINAL 1L
TITAG 1K
TITAG 1L
RWYS 01, 19 DEPARTURES
By ATC

TITAGAt or above
8040'

FT/METER CONVERSION

QNH

2960' - 900m

6070' - 1850m

8040' - 2450m

10010' - 3050m

TINALAt or above
FL140


NOT TO SCALE

This SID requires a minimum climb gradient
of

TITAG 1L: 5.5% up to 8040'.

Gnd speed-KT	75	100	150	200	250	300
5.5% V/V (fpm)	418	557	835	1114	1392	1671


If unable to comply advise ATC.



SID	RWY	ROUTING
TINAL 1K	01	Climb on 007° track to D6.7 SI, turn LEFT, 207° track, at SI R-299 turn RIGHT, intercept SI R-283 to TINAL.
TINAL 1L	19	Climb on 187° track to D6.7 SI, turn RIGHT, 007° track, at SI R-260 turn LEFT, intercept SI R-283 to TINAL.
TITAG 1K	01	Climb on 007° track to D6.7 SI, turn LEFT, 283° track, at SI R-331 turn RIGHT, intercept SI R-328 TITAG.
TITAG 1L	19	Climb on 187° track to D6.7 SI, turn RIGHT, 049° track to SI, turn LEFT, SI R-328 to TITAG.


Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



ETUNO 1W
INBAK 1W
SOGTA 1W
RWY 01 RNAV DEPARTURES
RNAV (GNSS)


RNAV 1 (P-RNAV) APPROVAL REQUIRED, OTHERWISE ADVISE ATC



SID	ROUTING
ETUNO 1W	FF110 (2960'+) - FF120 - FFE01 (4930'+) - FFS01 (10010'+) - FF125 - ETUNO (FL110+).
INBAK 1W	FF110 (2960'+) - FF120 - FFE01 (4930'+) - FFS01 (10010'+) - FF125 - INBAK (FL110+).
SOGTA 1W	FF110 (2960'+) - FF120 - SOGTA (FL110+).

Apt Elev
597'


Trans level: By ATC Trans alt: 10010'



ETUNO 1X
INBAK 1X
SOGTA 1X
RWY 19 RNAV DEPARTURES

RNAV (GNSS)


RNAV 1 (P-RNAV) APPROVAL REQUIRED, OTHERWISE ADVISE ATC



SID	ROUTING
ETUNO 1X	FF310 (2960'+) - FF325 (4430'+) - FF330 (9030'+) - ETUNO (FL110+).
INBAK 1X	FF310 (2960'+) - FF325 (4430'+) - FF330 (9030'+) - INBAK (FL110+).
SOGTA 1X	FF310 (2960'+) - FF325 (4430'+) - FFS02 (6070'+) - FFE02 (9030'+) - SOGTA (FL110+).


Apt Elev
597'

Trans level: By ATC Trans alt: 10010'



NOMPA 1W, SOTAM 1W
TINAL 1W, TITAG 1W
RWY 01 RNAV DEPARTURES
RNAV (GNSS)


RNAV 1 (P-RNAV) APPROVAL REQUIRED, OTHERWISE ADVISE ATC



SID	ROUTING
NOMPA 1W	FF110 (2960'+) - FFN01 (4930'+) - FF115 - NOMPA (10010'+).
SOTAM 1W	FF110 (2960'+) - FFN01 (4930'+) - FFN03 (7060'+) - FFW01 (9030'+) - SOTAM (FL170+).
TINAL 1W	FF110 (2960'+) - FFN01 (4930'+) - FFN03 (7060'+) - TINAL (FL140+).
TITAG 1W	FF110 (2960'+) - FFN01 (4930'+) - FF115 - TITAG (8040'+).

Apt Elev
597'

Trans level: By ATC Trans alt: 10010'

**NOMPA**At or above
10010'

NL 1K

NL 2L

NOMPA 1K

NOMPA 1L

RWYS 01, 19 DEPARTURES

NIKOLA
*326 NL
N44 58.0 E033 37.2At or above
9030'FT/METER CONVERSION
QNH

2960'	-	900m
8040'	-	2450m
9030'	-	2750m
10010'	-	3050m

These SIDs require minimum climb gradients
of

NL 2L: 7.0% up to 9030'.

NOMPA 1L: 5.5% up to 8040'.

Gnd speed-KT	75	100	150	200	250	300
7.0% V/V (fpm)	532	709	1063	1418	1772	2127
5.5% V/V (fpm)	418	557	835	1114	1392	1671

If unable to comply advise ATC.

SID	RWY	ROUTING
NL 1K	01	Climb on 007° track to D6.7 SI, turn RIGHT, 213° track to SI, turn RIGHT, SI R-245 to NL.
NL 2L	19	Climb on 187° track to D6.7 SI, turn RIGHT, intercept 280° bearing to NL.
NOMPA 1K By ATC	01	Climb on 007° track to D6.7 SI, turn LEFT, 249° track, at SI R-316 turn RIGHT, intercept SI R-309 to NOMPA.
NOMPA 1L By ATC	19	Climb on 187° track to D6.7 SI, turn RIGHT, 049° track to SI, turn LEFT, SI R-309 to NOMPA.

NOISE ABATEMENT

GENERAL

Noise abatement procedures during take-off and landing shall be carried out by crews of all aircraft, but not at the expense of flight safety.

DEPARTURES

NADP 1 and NADP 2 is applied for take-off and climbing procedures.

Restrictions



1. Take-off shall be carried out from RWY beginning.
2. Termination of noise abatement procedures shall not be carried out before 3.2NM from RWY THRs.

TRANS LEVEL: BY ATC
TRANS ALT: 10010'

SPECIAL ENGINE FAILURE PROCEDURE

"Advise ATC of Intentions"

RWY	PROCEDURE
19	At D7.0 SI RIGHT turn DCT to SI. HLDG: at SI, INB 007, LEFT turn (MHA 2150 ft).



CHANGES: Procedure.

© JEPPESEN, 2018. ALL RIGHTS RESERVED.

UKFF

Apt Elev **597'**
N45 03.1 E033 58.4

JEPPesen


23 FEB 18

10-9

Eff 1 Mar

SIMFEROPOL

SIMFEROPOL



CHANGES: Apron. Twys.

© JEPPESEN, 2000, 2018. ALL RIGHTS RESERVED.

UKFF


Apt Elev **597'**
N45 03.1 E033 58.4

JEPPESSEN

21 DEC 18 **10-9** Eff 3 Jan


SIMFEROPOL

SIMFEROPOL



CHANGES: Communications. Lights. Twy designator. Notes. Hot spots.

© JEPPESEN, 2000, 2018. ALL RIGHTS RESERVED.



INS COORDINATES

STAND No.	COORDINATES	STAND No.	COORDINATES
1	N45 02.0 E033 59.1	9 thru 11	N45 02.1 E033 58.8
1A	N45 02.1 E033 59.1	11A thru 13A	N45 02.1 E033 58.7
2	N45 02.0 E033 59.1	14 thru 16	N45 02.1 E033 58.6
3 thru 5	N45 02.1 E033 59.0		
5A thru 8	N45 02.1 E033 58.9		

ADDITIONAL RUNWAY INFORMATION

RWY		RVR	USABLE LENGTHS		TAKE-OFF	WIDTH
			Threshold	Landing Beyond		
01	HIRL (60m) CL (15m) HIALS PAPI-L (3.0°)	RVR		11,109' 3386m	1	197' 60m
19	HIRL (60m) CL (15m) HIALS TDZ PAPI-L (3.0°)	RVR		10,988' 3349m		

1 TAKE-OFF RUN AVAILABLE

RWY 01: From rwy head 12,142' (3701m)
twy A2 int 10,007' (3050m)
twy A3 int 8038' (2450m)

RWY 19: From rwy head 12,142' (3701m)
twy A9 int 11,417' (3480m)

LOW VISIBILITY PROCEDURE (LVP)

LVP shall be applied when RVR is 600m or less and/or ceiling is 60m or less.

Pilots will be informed by ATIS and ATC about beginning of LVP.

- After landing pilots should report about leaving RWY and location.
- Taxiing and parking is performed with follow-me car only.
- Only one acft allowed on the manoeuvring area at a time.

TAKE-OFF

AIR CARRIER (JAA)
All Rwys



LVP must be in force

	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL
A			
B	200m (150m)	250m	400m
C			
D	250m (200m)	300m	

RVR in parentheses if TDZ RVR is supplemented by Mid and/or Rollout RVR.

CHANGES: Hot spots. Usable lengths. Coord. Aprons C & T transferred to 10-9B.

© JEPPESEN, 2000, 2018. ALL RIGHTS RESERVED.



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		LANDING	BEYOND		
01	HIRL (60m) CL (15m) HIALS PAPI-L (3.0°) RVR	Threshold	Glide Slope		197'
19	HIRL (60m) CL (15m) HIALS TDZ PAPI-L (3.0°) RVR				60m

LOW VISIBILITY PROCEDURE (LVP)

LVP shall be applied when RVR is less than 600m.
Pilots will be informed by ATIS and ATC about beginning of LVP.


- After landing pilots should report about leaving RWY and location.
- Taxiing and parking is performed with follow-me car only.
- Only one acft allowed on the manoeuvring area at a time.

TAKE-OFF

AIR CARRIER (JAA)
All Rwys

LVP must be in force

	RL & CL	RCLM (DAY only) or RL	RCLM (DAY only) or RL
A			
B	200m	250m	400m
C			
D	250m	300m	



INS COORDINATES

STAND No.	COORDINATES	STAND No.	COORDINATES
G1, G2	N45 01.3 E033 59.8	24, 25	N45 01.2 E033 59.5
H1	N45 01.4 E033 59.8	26	N45 01.2 E033 59.7
H2	N45 01.3 E033 59.3	27, 28	N45 01.3 E033 59.7
H3	N45 01.2 E033 59.3	29 thru 34	N45 01.3 E033 59.6
H4, 1 thru 4	N45 01.2 E033 59.8	35 thru 37	N45 01.3 E033 59.5
5	N45 01.1 E033 59.8	38	N45 02.0 E033 59.2
6, 7	N45 01.1 E033 59.7	39 thru 41	N45 02.1 E033 59.2
8 thru 11	N45 01.0 E033 59.7		
12	N45 01.0 E033 59.6		
13, 14	N45 00.9 E033 59.6		
15, 16	N45 01.0 E033 59.8		
17	N45 01.0 E033 59.7		
18	N45 01.0 E033 59.5		
19, 20	N45 01.2 E033 59.7		
21 thru 23	N45 01.2 E033 59.6		

INS COORDINATES APRON C & T			
STAND No.	COORDINATES	STAND No.	COORDINATES
G1, G2	N45 01.3 E033 59.8	24, 25	N45 01.2 E033 59.5
H1	N45 01.4 E033 59.8	26	N45 01.2 E033 59.7
H2	N45 01.3 E033 59.3	27, 28	N45 01.3 E033 59.7
H3	N45 01.2 E033 59.3	29 thru 34	N45 01.3 E033 59.6
H4, 1 thru 4	N45 01.2 E033 59.8	35 thru 37	N45 01.3 E033 59.5
5	N45 01.1 E033 59.8	38	N45 02.0 E033 59.2
6, 7	N45 01.1 E033 59.7	39 thru 41	N45 02.1 E033 59.2
8 thru 11	N45 01.0 E033 59.7		
12	N45 01.0 E033 59.6		
13, 14	N45 00.9 E033 59.6		
15, 16	N45 01.0 E033 59.8		
17	N45 01.0 E033 59.7		
18	N45 01.0 E033 59.5		
19, 20	N45 01.2 E033 59.7		
21 thru 23	N45 01.2 E033 59.6		

STRAIGHT-IN RWY		A	B	C	D
01	ILS	797' (200')	797' (200')	797' (200')	797' (200')
	<i>FULL</i>	R550m	R550m	R550m	R550m
	<i>Limited</i>	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1200m	R1200m	R1200m	R1200m
	LOC ❶	910' (313')	910' (313')	910' (313')	910' (313')
	with D4.3	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1400m	R1400m	R1400m	R1400m
	LOC ❶	1100' (503')	1100' (503')	1100' (503')	1100' (503')
	w/o D4.3	R1500m	R1500m	R1600m	R1600m
	<i>ALS out</i>	R1500m	R1500m	C2400m	C2400m
	VOR ❶	1040' (443')	1040' (443')	1040' (443')	1040' (443')
		R1400m	R1400m	R1400m	R1400m
	<i>ALS out</i>	R1500m	R1500m	C2100m	C2100m
19	NDB ❶	970' (373')	970' (373')	970' (373')	970' (373')
	with LOM	R1000m	R1000m	R1000m	R1000m
	<i>ALS out</i>	R1500m	R1500m	R1700m	R1700m
	NDB ❶	1120' (523')	1120' (523')	1120' (523')	1120' (523')
	w/o LOM	R1500m	R1500m	R1700m	R1700m
	<i>ALS out</i>	R1500m	R1500m	C2400m	C2400m
	ILS	777' (200')	777' (200')	777' (200')	777' (200')
	<i>FULL</i>	R550m	R550m	R550m	R550m
	<i>Limited</i>	R750m	R750m	R750m	R750m
	<i>ALS out</i>	R1200m	R1200m	R1200m	R1200m
	LOC ❶	970' (393')	970' (393')	970' (393')	970' (393')
		R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m
	VOR ❶	970' (393')	970' (393')	1010' (433')	1020' (443')
		R1100m	R1100m	R1300m	R1400m
	<i>ALS out</i>	R1500m	R1500m	R2000m	C2100m
	NDB ❶	970' (393')	970' (393')	970' (393')	970' (393')
		R1100m	R1100m	R1100m	R1100m
	<i>ALS out</i>	R1500m	R1500m	R1800m	R1800m

❶ Continuous Descent Final Approach.


CIRCLE-TO-LAND	100 KT	135 KT	180 KT	205 KT
After ILS, LOC apch to rwy 01	1100' (503')	1100' (503')	1530' (933')	1530' (933')
After VOR apch to rwy 01	1070' (473')	1100' (503')	1530' (933')	1530' (933')
After NDB apch to rwy 01	1120' (523')	1120' (523')	1530' (933')	1530' (933')
After apch to rwy 19 ❷	1070' (493')	1100' (523')	1530' (953')	1530' (953')
	V1500m	V1600m	V2400m	V3600m

❷ Circling height based on rwy 19 thresh elev of 577'.

TAKE-OFF RWY 01, 19					
A B C D	Approved Operators	LVP must be in force			NIL (DAY only)
	HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL	
A	125m	150m	200m	250m	400m 500m
B					
C					
D	150m	200m	250m	300m	


CHANGES: Minimums.


© JEPPESSEN, 2010, 2014. ALL RIGHTS RESERVED.



CHANGES: Comm. VOR ident and frequency.

© JEPPESEN, 2000, 2018. ALL RIGHTS RESERVED.





SIMFEROPOL
NDB Rwy 01

STRAIGHT-IN LANDING RWY 01					CIRCLE-TO-LAND	
with LOM			w/o LOM			
MDA(H) 970' (373')			MDA(H) 1120' (523')			
		ALS out	ALS out		Max Kts	MDA(H)
A	1200m	RVR 1500m VIS 1600m	1200m	RVR 1500m VIS 1600m	100	1120' (523') 1600m
B					135	
C			RVR 1500m VIS 1600m	2400m	180	
D	RVR 1500m VIS 1600m	RVR 1800m VIS 2000m	2400m	2800m	205	1530' (933') 4800m

© JEPPESEN, 2000, 2018. ALL RIGHTS RESERVED.

