

Meetings

- **OpenAPI Version:** `3.1.1`
 - **API Version:** `2`

The Zoom Meeting APIs allow developers to interface with Zoom Meetings and Webinars programmatically.

Servers

- **URL:** `https://api.zoom.us/v2`

Operations

List archived files

- **Method:** `GET`
 - **Path:** `/archive\_files`
 - **Tags:** Archiving

Get an account's archived meeting or webinar files.

Zoom's [archiving solution](https://support.zoom.us/hc/en-us/articles/360050431572-Archiving-indicators) lets account administrators set up an automated mechanism to record, collect, and archive meeting data to a third-party platform of their choice to satisfy FINRA or other compliance requirements.

Prerequisites:

- The [**Meeting and Webinar Archiving** feature](https://support.zoom.us/hc/en-us/articles/4405656451213--Archiving-for-meetings-and-webinars) enabled for your account by [Zoom Support](https://support.zoom.us/hc/en-us/articles/201362003).

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **recording:read:admin`**

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **archiving:read:list_archived_files:admin`,`archiving:read:list_archived_files:master`**

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **MEDIUM`**

Responses

Status: 200 **HTTP Status Code:** `200` Archived files returned.

Content-Type: application/json

- **from**

string, format: **date-time** — The queried start date.

- **meetings**

array — Information about the meeting or webinar.

Items:

- **account_name** (required)

string — The user's account name.

- **archive_files** (required)

array — Information about the archive files.

Items:

- **download_url** (required)

string — The URL to download the the archive file. **OAuth apps** If a user has authorized and installed your OAuth app that contains recording scopes, use the user's **[OAuth access token]** (/docs/integrations/oauth/) to download the file. For example, **https://{{base-domain}}/rec/archive/download/xxx--header 'Authorization: Bearer {{OAuth-access-token}}'`** **Note:** This field does **not** return for **[Zoom on-premise accounts]** (https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment). Instead, this API will return the **file_path** field.

- **encryption_fingerprint** (required)

string — The archived file's encryption fingerprint, using the SHA256 hash algorithm.

- **file_extension** (required)

``string`` — The archived file's extension.

- **file_size** (required)**

``integer`` — The archived file's size, in bytes.

- **file_type** (required)**

``string``, possible values: ``"MP4"`, `"M4A"`, `"CHAT"`, `"CC"`, `"CHAT_MESSAGE"`, `"TRANSCRIPT"`, "SUB_GROUP_MEMBER_LOG"`, "AIC_CONVERSATION" — The archive file's type. `*` `MP4` - Video file. `*` `M4A` - Audio-only file. `*` `CHAT` - A TXT file containing in-meeting chat messages. `*` `CC` - A file containing the closed captions of the recording, in VTT file format. `*` `CHAT_MESSAGE` - A JSON file encoded in base64 format containing chat messages. The file also includes waiting room chats, deleted messages, meeting emojis and non-verbal feedback. `*` `TRANSCRIPT` - A JSON file include audio transcript wording. `*` `SUB_GROUP_MEMBER_LOG` - A json file containing records of members entering and leaving the subgroup. `*` `AIC_CONVERSATION` - A json file include internal user archive aic content.`

- **id** (required)**

``string`` — The archive file's unique ID.

- **individual** (required)**

``boolean`` — Whether the archive file is an individual recording file. ``*` `true`` - An individual recording file. ``*` `false`` - An entire meeting file.

- **participant_join_time** (required)**

``string``, format: ``date-time`` — The join time for the generated recording file. If this value is returned when the individual value is ``true``, it is the recording file's participant join time. When the individual value is ``false``, it returns the join time for the archiving gateway.

- **participant_leave_time** (required)**

``string``, format: ``date-time`` — The leave time for the generated recording file. If this value is returned when the individual value is ``true``, it is the recording file's participant leave time. When the individual value is ``false``, it returns the leave time for the archiving gateway.

- **recording_type** (required)**

``string``, possible values: ``"shared_screen_with_speaker_view"`, "audio_only"`, "chat_file"`, "closed_caption"`, "chat_message"`, "audio_transcript"`, "aic_conversation" — The archive file's recording type. `*` `shared_screen_with_speaker_view` `*` `audio_only` `*` `chat_file` `*` `closed_caption` `*` `chat_message` `*` `audio_transcript` `*` `aic_conversation` For more information, read our \[Managing and sharing cloud recordings\](https://support.zoom.us/hc/en-us/articles/205347605-Managing-and-sharing-cloud-recordings#h_9898497b-e736-4980-a749-d55608f10773) documentation.`

- **status** (required)**

``string``, possible values: ``"completed"`, "processing"`, "failed" — The archived file's processing status. `*` `completed` - The processing of the file is complete. `*` `processing` - The file is processing. `*` `failed` - The processing of the file failed.`

- **auto_delete****

``boolean`` — Whether to auto delete the archived file. ``*`*Prerequisites:*` Enable the "Tag Archiving Files for Deletion" feature in OP. Contact [\[Zoom Support\]](https://support.zoom.us/hc/en-us/articles/201362003)(<https://support.zoom.us/hc/en-us/articles/201362003>) to open.

- **file_path****

``string`` — The file path to the on-premise account archive file. ``*`*Note:*` The API only returns this field for [\[Zoom on-premise accounts\]](https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment)(<https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment>). It does ``*`*not*` return the ``download_url`` field.

- **number_of_messages****

``integer`` — The number of ``TXT`` or ``JSON`` file messages. This field returns only when the ``file_extension`` is ``JSON`` or ``TXT``.

- **participant_email****

``string``, format: ``email`` — The individual recording file's participant email address. This value is returned when the ``individual`` value is ``true``. If the participant is ``*`*not*` part of the host's account, this returns an empty string value, with some exceptions. See [\[Email address display rules\]](/docs/api/using-zoom-apis/#email-address-display-rules)(</docs/api/using-zoom-apis/#email-address-display-rules>) for details.

- **storage_location****

`string`, possible values: `"US", "AU", "BR", "CA", "EU", "IN", "JP", "SG", "CH"` — The region where the file is stored. This field returns only if the `Enable Distributed Compliance Archiving` feature is enabled.

- **complete_time** (required)

`string`, format: `date-time` — The meeting or webinar's archive completion time.

- **duration** (required)

`integer` — The meeting or webinar's scheduled duration.

- **duration_in_second** (required)

`integer` — The meeting or webinar's duration, in seconds.

- **host_id** (required)

`string` — The ID of the user set as the host of the archived meeting or webinar.

- **id** (required)

`integer`, format: `int64` — The meeting or webinar ID, either `meetingId` or `webinarId`.

- **is_breakout_room** (required)

`boolean` — Whether the room is a `[breakout room]` (<https://support.zoom.us/hc/en-us/articles/115005769646-Participating-in-breakout-rooms>).

- **meeting_type** (required)

`string`, possible values: `"internal", "external"` — Whether the meeting or webinar is internal or external. `internal` - An internal meeting or webinar. `external` - An external meeting or webinar. The `id`, `host_id`, and `topic` PII (Personal Identifiable Information) values in this response are removed when this value is `external`.

- **recording_count** (required)

`integer` — The number of archived files returned in the API call response.

- **start_time** (required)

`string`, format: `date-time` — The meeting or webinar's start time.

- **status** (required)

`string`, possible values: `"completed", "processing"` — The archive's processing status. `completed` - The archive's processing is complete. `processing` - The archive is processing.

- **timezone** (required)

`string` — The meeting or webinar's `[timezone]` ([/docs/api/references/abbreviations/#timezones](https://docs/api/references/abbreviations/#timezones)).

- **topic** (required)

`string` — The meeting or webinar topic.

- **total_size** (required)

`integer` — The total size of the archive file, in bytes.

- **type** (required)

`integer`, possible values: `1, 2, 3, 4, 5, 6, 7, 8, 9, 100` — The type of archived meeting or webinar. Meeting recordings use these archive types. `1` - Instant meeting. `2` - Scheduled meeting. `3` - A recurring meeting with no fixed time. `4` - A meeting created via PMI (Personal Meeting ID). `7` - A `[Personal Audio Conference]` (<https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference>) (PAC). `8` - Recurring meeting with a fixed time. Webinar recordings use these archive types. `5` - A webinar. `6` - A recurring webinar without a fixed time. `9` - A recurring webinar with a fixed time. If the recording is `not` from a meeting or webinar: `100` - A `[breakout room]` (<https://support.zoom.us/hc/en-us/articles/115005769646-Participating-in-breakout-rooms>).

- **uuid** (required)

`string` — The recorded meeting or webinar instance's universally unique identifier (UUID). Each meeting or webinar instance generates a UUID.

- **group_id**

``string`` — Primary group IDs of participants who belong to your account. Each group ID is separated by a comma.

- `**`parent_meeting_id`**`

``string`` — The parent meeting's universally unique ID (UUID). Each meeting or webinar instance generates a UUID. If the ``is_breakout_room`` value is ``true``, the API returns this value.

- `**`physical_files`**`

``array`` — Information about the physical files.

`**Items:**`

- `**`download_url`**`

``string`` — The URL to download the the archive file. ``*OAuth apps*`` If a user has authorized and installed your OAuth app that contains recording scopes, use the user's ``[OAuth access token]`` (`/docs/integrations/oauth/`) to download the file. Example: ``https://{base-domain}/rec/archive/attached/download/xxx--header 'Authorization: Bearer {[OAuth-access-token]}``

- `**`file_id`**`

``string`` — The physical file's unique ID.

- `**`file_name`**`

``string`` — The physical file's name.

- `**`file_size`**`

``integer`` — The physical file's size, in bytes.

- `**`next_page_token`**`

``string`` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes. ``*Note:*`` if you use ``next_page_token`` as a parameter, your other request parameters should be changeless to make sure that the large result set is what you want. For example, if your ``to`` parameter is for a future time, Zoom resets this value to the current time and returns this value in the response body, along with the ``next_page_token`` value. Use these same ``to`` and ``next_page_token`` values in requests for the remaining results set; otherwise you will get an invalid token error.

- `**`page_size`**`

``integer`` — The number of records returned within a single API call.

- `**`to`**`

``string``, format: ``date-time`` — The queried end date.

- `**`total_records`**`

``integer`` — The total number of returned meeting records.

`**Example:**`

```
``json
{
  "from": "2021-03-12T02:12:27Z",
  "meetings": [
    {
      "account_name": "account_01",
      "archive_files": [
        {
          "download_url": "https://example.com/recording/download/Qg75t7xZBtEbAkjdlgbfdngBBBB",
          "file_extension": "JSON",
          "file_path": "/9090876528/path01/demo.mp4",
          "file_size": 165743,
          "file_type": "CHAT",
          "id": "a2f19f96-9294-4f51-8134-6f0eea108eb2",
          "individual": true,
          "participant_email": "jchill@example.com",
          "participant_join_time": "2021-03-12T02:07:27Z",
          "participant_leave_time": "2021-03-12T02:12:27Z",
          "recording_type": "chat_message",
          "status": "completed",
          "encryption_fingerprint": "abf85f0fe6a4db3cdd8c37e505e1dd18a34d9696170a14b5bc6395677472cf43",
          "number_of_messages": 150,
          "storage_location": "US",

```

```

    "auto_delete": false
  }
],
"complete_time": "2021-03-12T02:57:27Z",
"duration": 1,
"duration_in_second": 1800,
"host_id": "Dhjdfgdkg8w",
"id": 553068284,
"is_breakout_room": false,
"meeting_type": "internal",
"parent_meeting_id": "atsXxhSEQWit9t+U02HXNQ==",
"recording_count": 2,
"start_time": "2021-04-26T05:23:18Z",
"timezone": "Asia/Shanghai",
"topic": "My Personal Meeting Room",
"total_size": 364463,
"type": 1,
"uuid": "y03dfhh3t467UkQ==",
"status": "completed",
"group_id": "pvFIYKSDTum9iCD00tQL4w,_FsQLyI0Rl06LVPeUVWi8g",
"physical_files": [
  {
    "file_id": "pvKocCqVSMYga0cKus5Afw",
    "file_name": "Screenshot 2025-02-12 at 10.42.27 AM.png",
    "file_size": 540680,
    "download_url":
"https://example.com/rec/archive/attached/download/HBAXbHc15BXbnq0JoDu6tc5MWlww9MAo9JJq2d14VAWkpcT5FEA.AK5ca
lud4EJB7bMq"
  }
]
}
],
"next_page_token": "At6eWnFZ1FB3arCXnRxqHLXKkbDW18yz2i2",
"page_size": 20,
"to": "2021-03-12T02:12:27Z",
"total_records": 20
}
},

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 2001` `Account does not exist: {accountId}`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).`

Get archived file statistics

```

- Method: GET
- Path: /archive_files/statistics
- Tags: Archiving

```

Get statistics about an account's archived meeting or webinar files.

Zoom's [archiving solution](https://support.zoom.us/hc/en-us/articles/360050431572-Archiving-indicators) lets account administrators set up an automated mechanism to record, collect, and archive meeting data to a third-party platform of their choice to satisfy FINRA and other compliance requirements.

Prerequisites:

- The **[Meeting and Webinar Archiving]** (https://support.zoom.us/hc/en-us/articles/4405656451213--Archiving-for-meetings-and-webinars) enabled for your account by [Zoom Support] (https://support.zoom.us/hc/en-us/articles/201362003).

[Scopes] (https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `recording:read:admin`

[Granular Scopes] (https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `archiving:read:archived_file_statistics:admin`

[Rate Limit Label] (https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`

Responses

Status: 200 `HTTP Status Code: 200` The statistics of Archived files returned.

Content-Type: application/json

```

- from

```

`string`, format: `date-time` — The queried start date.

```
- ``statistic_by_file_extension``

`object` — Statistics about archive files, by file extension.

- ``json_file_count``

`integer` — The number of json files.

- ``m4a_file_count``

`integer` — The number of m4a files.

- ``mp4_file_count``

`integer` — The number of mp4 files.

- ``txt_file_count``

`integer` — The number of txt files.

- ``vtt_file_count``

`integer` — The number of vtt files.

- ``statistic_by_file_status``

`object` — Statistics about archive files, by file status.

- ``completed_file_count``

`integer` — The number of completed files.

- ``failed_file_count``

`integer` — The number of failed files.

- ``processing_file_count``

`integer` — The number of processing files.

- ``to``

`string`, format: `date-time` — The queried end date.

- ``total_records``

`integer` — The total number of returned meeting records.
```

Example:

```
``json
{
  "from": "2021-03-18T05:41:36Z",
  "to": "2021-03-18T05:41:36Z",
  "total_records": 20,
  "statistic_by_file_extension": {
    "mp4_file_count": 1,
    "m4a_file_count": 1,
    "txt_file_count": 1,
    "json_file_count": 1,
    "vtt_file_count": 1
  },
  "statistic_by_file_status": {
    "processing_file_count": 1,
    "completed_file_count": 1,
    "failed_file_count": 1
  }
}
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 2001 **Account does not exist: {accountId}.**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Update an archived file's auto-delete status

```
- Method: PATCH
- Path: /archive_files/{fileId}
```

- **Tags:** Archiving

Update an archived file's auto-delete status.

Prerequisites:

- [Zoom Support](https://support.zoom.us/hc/en-us/articles/201362003) must enable the **Meeting and Webinar Archiving** feature](https://support.zoom.us/hc/en-us/articles/4405656451213--Archiving-for-meetings-and-webinars) for your account.

- Open the disabling auto-delete feature in OP. Contact [Zoom Support](https://support.zoom.us/hc/en-us/articles/201362003) to open.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:write`,`recording:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`archiving:update:archived\_file\_auto\_delete\_status`,`archiving:update:archived\_file\_auto\_delete\_status:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Request Body

Content-Type: application/json

- **auto_delete** (required)

`boolean` — Whether to auto-delete the archived file.

Example:

```
``json
{
  "auto_delete": true
}
```

Responses

Status: 204 **HTTP Status Code:** `204`
 auto-delete status updated

Status: 400 **HTTP Status Code:** `400`
 Bad Request

Status: 404 **HTTP Status Code:** `404`
 Not Found

Status: 429 **HTTP Status Code:** `429`
 Too Many Requests. For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get a meeting's archive token for local archiving

- **Method:** `GET`
- **Path:** `/meetings/{meetingId}/jointoken/local\_archiving`
- **Tags:** Archiving

Get a meeting's archive token to allow local archiving. The archive token allows a meeting SDK app or bot to get archive permission to access the meeting's raw audio and video media stream in real-time.

Prerequisites:

- A Pro or higher plan for the meeting host.
- The **Archive meetings and webinars** account setting enabled in the Zoom web portal.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting\_token:read:admin:local\_archiving`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:local\_archiving\_token:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 **HTTP Status Code:** `200`
 Meeting local archiving token returned.

Content-Type: application/json

- **expire_in**

`integer`, format: `int64`, possible values: `120` — The number of seconds the archive token is valid for before it expires. This value always returns `120`.

- **token**

string — The archive token.

Example:

```
```json
{
 "expire_in": 120,
 "token": "2njt50mj"
}
```

##### Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300 Invalid meeting ID. Cannot access webinar information. Error Code: 124 This API only supports OAuth2 authorization. Error Code: 300 Not allowed to start local archiving. To use this feature, enable the "Archive meetings and webinars" setting in the "Settings" page of the Zoom web portal. Error Code: 3161 Meeting hosting and scheduling capabilities are not allowed for your user account.

##### Status: 404 HTTP Status Code: 404 Not Found Error Code: 300 Meeting ID does not exist. Error Code: 3001 Meeting does not exist: {meetingId}

##### Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

## Get a meeting's archived files

- **Method:** GET  
- **Path:** /past\_meetings/{meetingUUID}/archive\_files  
- **Tags:** Archiving

Return a specific meeting instance's [archived files](https://support.zoom.us/hc/en-us/articles/360050431572-Archiving-indicators).

See [Archived JSON schemas](/docs/api/references/archived-json-schema/) for in-meeting chat message and subgroup archiving activity JSON schemas.

**Prerequisites:**

- The [Meeting and Webinar Archiving] feature(https://support.zoom.us/hc/en-us/articles/4405656451213--Archiving-for-meetings-and-webinars) enabled for your account by [Zoom Support](https://support.zoom.us/hc/en-us/articles/201362003).

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): recording:read

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): archiving:read:archived\_files:admin, archiving:read:archived\_files

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): LIGHT

#### Responses

##### Status: 200 HTTP Status Code: 200 Meeting archived files returned.

##### Content-Type: application/json

- **account\_name** (required)

string — The user's account name.

- **archive\_files** (required)

array — Information about the archive files.

**Items:**

- **download\_url** (required)

string — The URL to download the archive file. If a user has authorized and installed your OAuth app that contains recording scopes, use the user's [OAuth access token](/docs/integrations/oauth/) to download the file. For example: https://{base-domain}/rec/archive/download/xxx--header 'Authorization: Bearer {OAuth-access-token}' Note: This field does not return for [Zoom On-Premise accounts](https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment). Instead, this API will return the file\_path field.

- **encryption\_fingerprint** (required)



``string`` — The archived file's encryption fingerprint, using the SHA256 hash algorithm.

- **``file_extension`` (required)\*\***

``string`` — The archived file's extension.

- **``file_size`` (required)\*\***

``integer`` — The archived file's size, in bytes.

- **``file_type`` (required)\*\***

``string``, possible values: ``"MP4"`, "M4A"`, "CHAT"`, "CC"`, "CHAT_MESSAGE"`, "TRANSCRIPT"`, "SUB_GROUP_MEMBER_LOG"`, "AIC_CONVERSATION" — The archive file's type. `*``MP4` — Video file. `*``M4A` — Audio-only file. `*``CHAT` — A TXT file containing in-meeting chat messages. `*``CC` — A file containing the closed captions of the recording, in VTT file format. `*``CHAT_MESSAGE` — A JSON file encoded in base64 format containing chat messages. The file also includes waiting room chats, deleted messages, meeting emojis and non-verbal feedback. `*``TRANSCRIPT` — A JSON file include audio transcript wording. `*``SUB_GROUP_MEMBER_LOG` — A JSON file containing records of members entering and leaving the subgroup. `*``AIC_CONVERSATION` — A json file include internal user archive aic content.`

- **``id`` (required)\*\***

``string`` — The archive file's unique ID.

- **``individual`` (required)\*\***

``boolean`` — Whether the archive file is an individual recording file. ``*``true` — An individual recording file. `*``false` — An entire meeting file.`

- **``participant_join_time`` (required)\*\***

``string``, format: ``date-time`` — The join time for the generated recording file. If this value is returned when the individual value is true, then it is the recording file's participant join time. When the individual value is false, it returns the join time for the archiving gateway.

- **``participant_leave_time`` (required)\*\***

``string``, format: ``date-time`` — The leave time for the generated recording file. If this value is returned when the individual value is true, then it is the recording file's participant leave time. When the individual value is false, it returns the leave time for the archiving gateway.

- **``recording_type`` (required)\*\***

``string``, possible values: ``"shared_screen_with_speaker_view"`, "audio_only"`, "chat_file"`, "closed_caption"`, "chat_message"`, "audio_transcript"`, "aic_conversation" — The archive file's recording type. `*``shared_screen_with_speaker_view` `*``audio_only` `*``chat_file` `*``closed_caption` `*``chat_message` `*``audio_transcript` `*``aic_conversation` For more information, read our \[Managing and sharing cloud recordings\] (https://support.zoom.us/hc/en-us/articles/205347605-Managing-and-sharing-cloud-recordings#h\9898497b-e736-4980-a749-d55608f10773) documentation.`

- **``status`` (required)\*\***

``string``, possible values: ``"completed"`, "processing"`, "failed" — The archived file's processing status. `*``completed` — The processing of the file is complete. `*``processing` — The file is processing. `*``failed` — The processing of the file failed.`

- **``auto_delete``\*\***

``boolean`` — Whether to auto delete the archived file. ``*`*Prerequisites:*` ``*``The "Tag Archiving Files for Deletion" feature must be enabled in OP. Contact [Zoom Support] (https://support.zoom.us/hc/en-us/articles/201362003) to open.`

- **``file_path``\*\***

``string`` — The file path to the on-premise account archive file. ``*`*Note:*` ``*``The API only returns this field for [Zoom On-Premise accounts] (https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment). It does `*`*not* return the `download_url` field.`

- **``number_of_messages``\*\***

``integer`` — The number of ``TXT`` or ``JSON`` file messages. This field returns only when the ``file_extension`` is ``JSON`` or ``TXT``

- **``participant_email``\*\***

``string``, format: ``email`` — The individual recording file's participant email address. This value is returned when the ``individual`` value is ``true``. If the participant is ``*`*not*` part of the host's account, this returns an empty string value, with some exceptions. See [\[Email address display rules\]](#)

(/docs/api/using-zoom-apis/#email-address-display-rules) for details.

- **storage\_location**

`string`, possible values: `"US", "AU", "BR", "CA", "EU", "IN", "JP", "SG", "CH"` — The region where the file is stored. This field returns only `Enable Distributed Compliance Archiving` op feature is enabled.

- **complete\_time** (required)

`string`, format: `date-time` — The meeting or webinar's archive completion time.

- **duration** (required)

`integer` — The meeting or webinar's scheduled duration.

- **duration\_in\_second** (required)

`integer` — The meeting or webinar's duration, in seconds.

- **host\_id** (required)

`string` — The host's user ID for the archived meeting or webinar.

- **id** (required)

`integer`, format: `int64` — The meeting or webinar ID, either `meetingId` or `webinarId`.

- **is\_breakout\_room** (required)

`boolean` — Whether the room is a `breakout room` (<https://support.zoom.us/hc/en-us/articles/115005769646-Participating-in-breakout-rooms>).

- **meeting\_type** (required)

`string`, possible values: `"internal", "external"` — Whether the meeting or webinar is internal or external. `internal` - An internal meeting or webinar. `external` - An external meeting or webinar. The `id`, `host_id`, and `topic` PII (Personal Identifiable Information) values in this response are removed when this value is `external`.

- **recording\_count** (required)

`integer` — The number of archived files returned in the API call response.

- **start\_time** (required)

`string`, format: `date-time` — The meeting or webinar's start time.

- **status** (required)

`string`, possible values: `"completed", "processing"` — The archive's processing status. `completed` - The archive's processing is complete. `processing` - The archive is processing.

- **timezone** (required)

`string` — The meeting or webinar's `timezone` (</docs/api/references/abbreviations/#timezones>).

- **topic** (required)

`string` — The meeting or webinar topic.

- **total\_size** (required)

`integer` — The total size of the archive file, in bytes.

- **type** (required)

`integer`, possible values: `1, 2, 3, 4, 5, 6, 7, 8, 9, 100` — The type of archived meeting or webinar. If the recording is of a meeting: `1` - Instant meeting. `2` - Scheduled meeting. `3` - A recurring meeting with no fixed time. `4` - A meeting created via PMI (Personal Meeting ID). `7` - A `Personal Audio Conference` (<https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference>) (PAC). `8` - Recurring meeting with a fixed time. If the recording is of a webinar: `5` - A webinar. `6` - A recurring webinar without a fixed time. `9` - A recurring webinar with a fixed time. If the recording is `not` from a meeting or webinar: `100` - A `breakout room` (<https://support.zoom.us/hc/en-us/articles/115005769646-Participating-in-breakout-rooms>).

- **uuid** (required)

`string` — The universally unique identifier (UUID) of the recorded meeting or webinar instance. Each meeting or webinar instance generates a UUID.

- **group\_id**

**string** — Primary group IDs of participants who belong to your account. Each group ID is separated by a comma.

- **parent\_meeting\_id**

**string** — The parent meeting's universally unique ID (UUID). Each meeting or webinar instance generates a UUID. If the `is_breakout_room` value is `true`, the API returns this value.

- **physical\_files**

**array** — Information about the physical files.

**Items:**

- **download\_url**

**string** — The URL to download the the archive file. `{0}Auth apps{0}` If a user has authorized and installed your OAuth app that contains recording scopes, use the user's `{0}Auth access token{0}` (`/docs/integrations/oauth/`) to download the file. For example: `https://{base-domain}/rec/archive/attached/download/xxx--header 'Authorization: Bearer {0}Auth-access-token{0}'`

- **file\_id**

**string** — The physical file's unique ID.

- **file\_name**

**string** — The physical file's name.

- **file\_size**

**integer** — The physical file's size, in bytes.

**Example:**

`json`

```
{
 "account_name": "account_01",
 "archive_files": [
 {
 "download_url": "https://example.com/recording/download/Qg75t7xZBtEbAkjd1gbfdngBBBB",
 "file_extension": "JSON",
 "file_path": "/9090876528/path01/demo.mp4",
 "file_size": 165743,
 "file_type": "CHAT",
 "id": "a2f19f96-9294-4f51-8134-6f0eea108eb2",
 "individual": true,
 "participant_email": "jchill@example.com",
 "participant_join_time": "2021-03-12T02:07:27Z",
 "participant_leave_time": "2021-03-12T02:12:27Z",
 "recording_type": "chat_message",
 "status": "completed",
 "encryption_fingerprint": "abf85f0fe6a4db3cdd8c37e505e1dd18a34d9696170a14b5bc6395677472cf43",
 "number_of_messages": 150,
 "storage_location": "US",
 "auto_delete": false
 }
],
 "complete_time": "2021-03-12T02:57:27Z",
 "duration": 1,
 "duration_in_second": 1800,
 "host_id": "Dhjdfgdkg8w",
 "id": 553068284,
 "is_breakout_room": false,
 "meeting_type": "internal",
 "parent_meeting_id": "atsXxhSEQWit9t+U02HXNQ==",
 "recording_count": 2,
 "start_time": "2021-04-26T05:23:18Z",
 "timezone": "Asia/Shanghai",
 "topic": "My Personal Meeting Room",
 "total_size": 364463,
 "type": 1,
 "uuid": "y03dfhh3t467UkQ==",
 "status": "completed",
 "group_id": "pvFIYKSDTum9iCD00tQL4w,_FsQLyI0Rl06LVPeUVWi8g",
 "physical_files": [
 {
```

```

 "file_id": "pvKocCqVSMYga0cKus5Afw",
 "file_name": "Screenshot 2025-02-12 at 10.42.27 AM.png",
 "file_size": 540680,
 "download_url":
"https://local.zoom.us/rec/archive/attached/download/HBAXbHc15BXbnq0JoDu6tc5MWlww9MAo9JJq2d14VAWkpcT5FEA.AK5
calud4EJB7bMq"
 }
]
}
},

```

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001`  
Meeting {meetingUUID} does not exist.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits]` (`/docs/api/rate-limits/`).

### Delete a meeting's archived files

```

- **Method:** `DELETE`
- **Path:** `/past_meetings/{meetingUUID}/archive_files`
- **Tags:** Archiving

```

Delete all of a meeting's archived files.

**Prerequisites:**

- The `[Meeting and Webinar Archiving]` (`https://support.zoom.us/hc/en-us/articles/4405656451213--Archiving-for-meetings-and-webinars`) enabled for your account by `[Zoom Support]` (`https://support.zoom.us/hc/en-us/articles/201362003`).

**[Scopes]** (`https://developers.zoom.us/docs/integrations/oauth-scopes-overview/`): `recording:write:admin`

**[Granular Scopes]** (`https://developers.zoom.us/docs/integrations/oauth-scopes-overview/`): `archiving:delete:archived_files:admin`

**[Rate Limit Label]** (`https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits`): `LIGHT`

### Responses

##### Status: 204 `HTTP Status Code: 204` Meeting archived file deleted.

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 200` Only available for Paid account. `Error Code: 200` Not available for this account.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001`  
Meeting does not exist: {0}

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits]` (`https://developers.zoom.us/docs/api/rest/rate-limits/`).

### Get meeting recordings

```

- **Method:** `GET`
- **Path:** `/meetings/{meetingId}/recordings`
- **Tags:** Cloud Recording

```

Returns all of a meeting's `[recordings]` (`https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0062627#h_7420acb5-1897-4061-87b4-5b76e99c03b4`). Use the `download_url` property listed in the response to download the recording files. To access a password-protected cloud recording, send the `download_access_token` or the user's `[OAuth access token]` (`/docs/integrations/oauth/`) as a Bearer token in the Authorization header. For example:

```
`curl -H 'Authorization: Bearer <ACCESS_TOKEN>' https://{base-domain}/rec/archive/download/xyz`
```

Learn more about `[enabling cloud recordings]` (`https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923`) and `[managing cloud recording settings]` (`https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362`).

**[Scopes]** (`https://developers.zoom.us/docs/integrations/oauth-scopes-overview/`): `recording:read`, `phone_recording:read:admin`

**[Granular Scopes]** (`https://developers.zoom.us/docs/integrations/oauth-scopes-overview/`): `cloud_recording:read:list_recording_files:admin`, `cloud_recording:read:list_recording_files`, `cloud_recording:read:list_recording_files:master`

**[Rate Limit Label]** (`https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits`): `LIGHT`

### Responses

```
- **`recording files`**
```

``array`` — List of recording files.

**\*\*Items:\*\***

**\*\*All of:\*\***

- **\*\*`deleted\_time`\*\***

``string`` — The time when the recording was deleted. Returned in the response only for the trash query.
- **\*\*`download\_url`\*\***

``string`` — The URL to download the recording. If a user has authorized and installed your OAuth app that contains recording scopes, use the ``download_access_token`` or the user's ``[OAuth access token]`` (`/docs/integrations/oauth/`) to download the file. Set the ``access_token`` as a Bearer token in the Authorization header. For example: ``curl -H 'Authorization: Bearer <ACCESS_TOKEN>' https://{{base-domain}}/rec/archive/download/xyz`.` **\*\*Note:\*\*** This field does **\*\*not\*\*** return for Zoom on-premise accounts. Instead, this API returns the ``file_path`` field. The URL may be a redirect. In that case, use ``curl --location`` to follow redirects or use another tool, like Postman.
- **\*\*`file\_extension`\*\***

``string``, possible values: ``"MP4", "M4A", "TXT", "VTT", "CSV", "JSON", "JPG"`` — The file extension type of the recording file.
- **\*\*`file\_path`\*\***

``string`` — The file path to the on-premise account recording. **\*\*Note:\*\*** This API only returns this field for Zoom On-Premise accounts. It does **\*\*not\*\*** return the ``download_url`` field.
- **\*\*`file\_size`\*\***

``number`` — The recording file size.
- **\*\*`file\_type`\*\***

``string``, possible values: ``"MP4", "M4A", "CHAT", "TRANSCRIPT", "CSV", "TB", "CC", "CHAT_MESSAGE", "SUMMARY"`` — The recording file type. ``MP4`` - Video file of the recording. ``M4A`` - Audio-only file of the recording. ``TIMELINE`` - Timestamp file of the recording in JSON file format. To get a timeline file, the **\*\*Add a timestamp to the recording\*\*** setting must be enabled in the ``[recording settings]`` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0062627#h\\_3f14c3a4-d16b-4a3c-bbe5-ef7d2450048](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0062627#h_3f14c3a4-d16b-4a3c-bbe5-ef7d2450048)). The time will display in the host's timezone, set on their Zoom profile. ``TRANSCRIPT`` - Transcription file of the recording in VTT format. ``CHAT`` - A TXT file containing in-meeting chat messages that were sent during the meeting. ``CC`` - File containing closed captions of the recording in VTT file format. ``CSV`` - File containing polling data in csv format. A recording file object with file type of either ``CC`` or ``TIMELINE`` **\*\*does not have\*\*** these properties. ``id``, ``status``, ``file_size``, ``recording_type``, and ``play_url``. ``SUMMARY`` - Summary file of the recording in JSON file format.
- **\*\*`id`\*\***

``string`` — The recording file ID. It's included in the response of the general query.
- **\*\*`meeting\_id`\*\***

``string`` — The meeting ID.
- **\*\*`play\_url`\*\***

``string`` — The URL that can play a recording file.
- **\*\*`recording\_end`\*\***

``string`` — The recording end time. The response is in the general query.
- **\*\*`recording\_start`\*\***

``string`` — The recording start time.
- **\*\*`recording\_type`\*\***

``string``, possible values: ``"shared_screen_with_speaker_view(CC)", "shared_screen_with_speaker_view", "shared_screen_with_gallery_view", "active_speaker", "gallery_view", "shared_screen", "audio_only", "audio_transcript", "chat_file", "poll", "host_video", "closed_caption", "timeline", "thumbnail", "audio_interpretation", "summary", "summary_next_steps", "summary_smart_chapters", "sign_interpretation", "production_studio"`` — The recording type.
- **\*\*`status`\*\***

``string``, possible values: ``"completed"`` — The recording status.



```

- **`status`**

`string`, possible values: `"completed"` — The recording file's status.

Example:

``json
{
 "account_id": "Cx3wERazSgup7ZWRHQM8-w",
 "duration": 20,
 "host_id": "_0ctZtY0REqWalTmwvrdIw",
 "id": 6840331990,
 "recording_count": 22,
 "start_time": "2021-03-18T05:41:36Z",
 "topic": "My Personal Meeting",
 "total_size": 22,
 "type": "1",
 "uuid": "B0KXuumlTAGXuqwr3bLyuQ==",
 "recording_play_passcode": "yNYIS408EJygs7rE5vVsJwXIz4-VW7MH",
 "auto_delete": true,
 "auto_delete_date": "2028-07-12",
 "recording_files": [
 {
 "deleted_time": "2021-03-18T05:41:36Z",
 "download_url": "https://example.com/rec/download/Qg75t7xZBtEbAkjdlgbfdngBBBB",
 "file_path": "/9090876528/path01/demo.mp4",
 "file_size": 7220,
 "file_type": "MP4",
 "file_extension": "M4A",
 "id": "72576a1f-4e66-4a77-87c4-f13f9808bd76",
 "meeting_id": "L0AGOEPVR9m5WS00s/d+FQ==",
 "play_url": "https://example.com/rec/play/Qg75t7xZBtEbAkjdlgbfdngBBBB",
 "recording_end": "2021-03-18T05:41:36Z",
 "recording_start": "2021-03-18T05:41:36Z",
 "recording_type": "shared_screen_with_speaker_view",
 "status": "completed"
 }
],
 "download_access_token":
"abJhbGciOiJIUzUxMiJ9.eyJpc3MiOiJodHRwczovL2V2ZW50Ln timer 20udXMiLCJhY2NvdW50SWQiOiJNdDZzdjR1MFRBeVBrd2dzTDJseG
lBIiwiYXVkiOiJoiaHR0cHM6Ly9vYXV0aC56b29tLnVzIiwibWlkIjoieFp3SEc0c3BRU2VuekdZWG16dnpiUT09IiwiaXhwIjojNjI2MTM5NT
A3LCJ1c2VySWQiOiJEUWUhyZHBqclMzdWFPZjdkUGtrZzh3In0.a6KetiC6BlkDhf1dP4KBGUE1bb2brMeraoD45yhFx0eSSSTFdkHQnsKmlJ
Q-hdo9Zy-4vQw3r0xlyoHv583JyZ",
 "password": "981651",
 "participant_audio_files": [
 {
 "download_url": "https://example.com/rec/download/Qg75t7xZBtEbAkjdlgbfdngBBBB",
 "file_name": "test.json",
 "file_path": "/9090876528/path01/demo.mp4",
 "file_size": 65536,
 "file_type": "M4A",
 "id": "a2f19f96-9294-4f51-8134-6f0eea108eb2",
 "play_url": "https://example.com/rec/play/Qg75t7xZBtEbAkjdlgbfdngBBBB",
 "recording_end": "2021-06-30T22:14:57Z",
 "recording_start": "2021-06-30T22:14:57Z",
 "status": "completed"
 }
]
}
},
}

```

##### Status: 400 **\*\*HTTP Status Code:\*\*** 400 **\*\*Error Code:\*\*** 1010 **\*\*Bad Request** **\*\*Error Code:\*\*** 1010 **\*\*User not found on this account: {accountId}.**

##### Status: 404 **\*\*HTTP Status Code:\*\*** 404 **\*\*Error Code:\*\*** 1001 **\*\*Not Found** **\*\*Error Code:\*\*** 1001 **\*\*User "{userId}" does not exist or does not belong to this account.** **\*\*Error Code:\*\*** 3301 **\*\*There is no recording for this meeting.**

##### Status: 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Error Code:\*\*** 429 **\*\*Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).**

### Delete meeting or webinar recordings

```

- **Method:** DELETE
- **Path:** /meetings/{meetingId}/recordings
- **Tags:** Cloud Recording

```

Delete all of a meeting's or webinar's recording files.

**\*\*Prerequisites\*\***



- Enable Cloud Recording on the user's account. Learn more about [enabling cloud recordings](https://support.zoom.com/hc/en/article?id=zm\_kb&sysparm\_article=KB0063923) and [managing cloud recording settings](https://support.zoom.com/hc/en/article?id=zm\_kb&sysparm\_article=KB0065362).

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
 `recording:write:admin`, `recording:write`

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
 `cloud\_recording:delete:meeting\_recording`, `cloud\_recording:delete:meeting\_recording:admin`, `cloud\_recording:delete:meeting\_recording:master`

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

#### #### Responses

##### Status: 204 The recording was successfully deleted.

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 1010   
 User does not belong to this account: {accountId}.   
**Error Code:** 3310   
 This recording was selected for a simulative webinar. You cannot delete or trash it.

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 1001   
 User {userId} does not exist or does not belong to this account.   
**Error Code:** 3301   
 There is no recording for this meeting.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [Rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

#### ### Get a meeting or webinar recording's analytics details

- **Method:** GET  
 - **Path:** /meetings/{meetingId}/recordings/analytics\_details  
 - **Tags:** Cloud Recording

Retrieve a meeting or webinar recording's [analytics details](https://support.zoom.us/hc/en-us/articles/205347605-Managing-cloud-recordings#h\_0b665029-ce74-4849-9794-d1aa0320d163). **Maximum duration:** 1 month.

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
 `cloud\_recording:read:recording\_analytics\_details`, `cloud\_recording:read:recording\_analytics\_details:master`, `cloud\_recording:read:recording\_analytics\_details:admin`

#### #### Responses

##### Status: 200 **HTTP Status Code:** 200 **Analytics Detail listed successfully.**

##### Content-Type: application/json

- **analytics\_details**

array — Analytics Detail.

**Items:**

- **date\_time**

string, format: date-time — Explicit time to watch or download the recording.

- **duration**

integer — When the query type is by\_view, this field indicates the viewing time, unit: seconds

- **email**

string — The user's email who downloaded this Meeting Recording.

- **name**

string — The user's name who watched or downloaded.

- **from**

string, format: date — The queried start date

- **next\_page\_token**

string — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- **page\_size**  
 integer — The number of records returned within a single API call.

- **to**  
 string, format: date — The queried end date.

- **total\_records**  
 integer — The total number of all the records available across pages.

**Example:**

```
```json
{
  "from": "2020-07-30",
  "to": "2020-07-30",
  "next_page_token": "R4aF90j0fVM2hhezJTEmSKaBSkfesDwGy42",
  "page_size": 30,
  "total_records": 5,
  "analytics_details": [
    {
      "date_time": "2021-07-04T22:14:57Z",
      "name": "2",
      "email": "2",
      "duration": 60
    }
  ]
}
```

Status: 400 HTTP Status Code: 400 Bad Request Error Code: 1010
 User not found on this account: {accountId}.

Status: 404 HTTP Status Code: 404 Not Found Error Code: 1001
 "{userId}" does not exist or does not belong to this account. Error Code: 3301 There is no recording for this meeting.

Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get a meeting or webinar recording's analytics summary

- **Method:** GET
 - **Path:** /meetings/{meetingId}/recordings/analytics_summary
 - **Tags:** Cloud Recording

Retrieve meeting recording's [analytics summary](https://support.zoom.us/hc/en-us/articles/205347605-Managing-cloud-recordings#h_0b665029-ce74-4849-9794-d1aa0320d163). **Maximum duration:** 1 month.

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 cloud_recording:read:recording_analytics_summary, cloud_recording:read:recording_analytics_summary:master, cloud_recording:read:recording_analytics_summary:admin

Responses

Status: 200 HTTP Status Code: 200 Analytics Summary listed successfully.

Content-Type: application/json

- **analytics_summary**
 array — Analytics Summary.

Items:

- **date**
 string — Date of viewing or downloading the recording.

- **downloads_total_count**
 integer — The number of people who downloaded this Meeting Recording.

- **views_total_count**
 integer — The number of people who have watched this Meeting Recording.

- ****`from`****

``string``, format: ``date`` — The queried start date

- ****`to`****

``string``, format: ``date`` — The queried end date.

****Example:****

````json`

```
{
 "from": "2020-07-30",
 "to": "2020-07-30",
 "analytics_summary": [
 {
 "date": "2022-07-06",
 "views_total_count": 2,
 "downloads_total_count": 2
 }
]
}
```

##### Status: 400 ``HTTP Status Code`` ``400`` ``Bad Request`` ``Error Code`` ``1010`` ``User not found on this account: {accountId}``.

##### Status: 404 ``HTTP Status Code`` ``404`` ``Not Found`` ``Error Code`` ``1001`` ``User "{userId}" does not exist or does not belong to this account.`` ``Error Code`` ``3301`` ``There is no recording for this meeting.``

##### Status: 429 ``HTTP Status Code`` ``429`` ``Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)``.

**### List recording registrants**

- **\*\*Method:\*\*** ``GET``

- **\*\*Path:\*\*** ``/meetings/{meetingId}/recordings/registrants``

- **\*\*Tags:\*\*** Cloud Recording

Get a list of registrants of a past meeting's [on-demand cloud recordings](https://support.zoom.us/hc/en-us/articles/360000488283-On-demand-recordings). Users must [register](/api-reference/zoom-api/methods#operation/meetingRecordingRegistrantCreate) to view the recordings.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
``recording:read:admin``, ``recording:read``

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
``cloud_recording:read:list_recording_registrants``, ``cloud_recording:read:list_recording_registrants:admin``, ``cloud_recording:read:list_recording_registrants:master``

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** ``MEDIUM``

**#### Responses**

##### Status: 200 ``HTTP Status Code`` ``200`` ``Registrants returned.``

##### Content-Type: application/json

**\*\*All of:\*\***

**\*\*All of:\*\***

- **\*\*`next\_page\_token`\*\***

``string`` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **\*\*`page\_count`\*\***

``integer`` — The number of pages returned for the request made.

- **\*\*`page\_number`\*\***

``integer``, default: ``1`` — ``Deprecated`` We will no longer support this field in a future release. Instead, use the ``next_page_token`` for pagination.

- **\*\*`page\_size`\*\***

```

`integer`, default: `30` — The number of records returned with a single API call.

- **`total_records`**

 `integer` — The total number of all the records available across pages.

* **`registrants`**

 `array` — Information about the cloud recording registrants.

 Items:

 All of:

 - **`id`**

 `string` — The registrant's ID.

 All of:

 - **`email` (required)**

 `string`, format: `email` — The registrant's email address. See \[Email address display rules]\
 (https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value
 details.

 - **`first_name` (required)**

 `string` — The registrant's first name.

 - **`address`**

 `string` — The registrant's address.

 - **`city`**

 `string` — The registrant's city.

 - **`comments`**

 `string` — The registrant's questions and comments.

 - **`country`**

 `string` — The registrant's two-letter \[country code]\
 (https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

 - **`custom_questions`**

 `array` — Information about custom questions.

 Items:

 - **`title`**

 `string` — The custom question's title.

 - **`value`**

 `string` — The custom question's response value. This has a limit of 128 characters.

 - **`industry`**

 `string` — The registrant's industry.

 - **`job_title`**

 `string` — The registrant's job title.

 - **`last_name`**

 `string` — The registrant's last name.

 - **`no_of_employees`**

 `string`, possible values: `""`, "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-
 5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-
 50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ *
 \More than 10,000\

```

```

- **`org`**

`string` — The registrant's organization.

- **`phone`**

`string` — The registrant's phone number.

- **`purchasing_time_frame`**

`string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No
timeframe" — The registrant's purchasing time frame. * `Within a month` * `1-3 months` * `4-6
months` \* `More than 6 months` \* `No timeframe`

- **`role_in_purchase_process`**

`string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved"
— The registrant's role in the purchase process. * `Decision Maker` * `Evaluator/Recommender` *
`Influencer` * `Not involved`

- **`state`**

`string` — The registrant's state or province.

- **`status`**

`string`, possible values: `"approved", "denied", "pending"` — The registrant's status. * `approved`
- Registrant is approved. * `denied` - Registrant is denied. * `pending` - Registrant is waiting for
approval.

- **`zip`**

`string` — The registrant's ZIP or postal code.

```

**Example:**

```

```json
{
  "next_page_token": "w7587w4eiyfsudgf",
  "page_count": 1,
  "page_size": 30,
  "total_records": 20,
  "registrants": [
    {
      "id": "3Z7sEm0TQQieLav3c30D_g",
      "address": "1800 Amphibious Blvd.",
      "city": "Mountain View",
      "comments": "Looking forward to the discussion.",
      "country": "US",
      "custom_questions": [
        {
          "title": "What do you hope to learn from this?",
          "value": "Look forward to learning how you come up with new recipes and what other services you
offer."
        }
      ],
      "email": "jchill@example.com",
      "first_name": "Jill",
      "industry": "Food",
      "job_title": "Chef",
      "last_name": "Chill",
      "no_of_employees": "1-20",
      "org": "Cooking Org",
      "phone": "5550100",
      "purchasing_time_frame": "1-3 months",
      "role_in_purchase_process": "Influencer",
      "state": "CA",
      "status": "approved",
      "zip": "94045"
    }
  ]
}
```

```

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* `404` \<br> Not Found

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* `429` \<br> Too Many Requests. For more information, see \[rate limits]\(<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Create a recording registrant

```
- **Method:** `POST`
- **Path:** `/meetings/{meetingId}/recordings/registrants`
- **Tags:** Cloud Recording
```

Register a user to gain access to **On-demand cloud recordings** of a previous meeting.

Cloud recordings of past Zoom meetings can be made [on-demand](https://support.zoom.us/hc/en-us/articles/360000488283-On-demand-Recordings). Users should be [registered](/api-reference/zoom-api/methods#operation/meetingRecordingRegistrantCreate) to view these recordings.

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:write:admin`,`recording:write`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`cloud_recording:write:recording_registrant`,`cloud_recording:write:recording_registrant:master`,`cloud_recording:write:recording_registrant:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`
```

#### Request Body

##### Content-Type: application/json

**All of:**

- **`email` (required)**

`string`, format: `email` — The registrant's email address. See \[Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value details.

- **`first\_name` (required)**

`string` — The registrant's first name.

- **`address`**

`string` — The registrant's address.

- **`city`**

`string` — The registrant's city.

- **`comments`**

`string` — The registrant's questions and comments.

- **`country`**

`string` — The registrant's two-letter \[country code](https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

- **`custom\_questions`**

`array` — Information about custom questions.

**Items:**

- **`title`**

`string` — The title of the custom question.

- **`value`**

`string` — The custom question's response value. This has a limit of 128 characters.

- **`industry`**

`string` — The registrant's industry.

- **`job\_title`**

`string` — The registrant's job title.

- **`last\_name`**

`string` — The registrant's last name.

- **`no\_of\_employees`**

```

`string`, possible values: `""`, "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ * \More than 10,000\

- **`org`**

`string` — The registrant's organization.

- **`phone`**

`string` — The registrant's phone number.

- **`purchasing_time_frame`**

`string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No timeframe" — The registrant's purchasing time frame. * \Within a month\ * \1-3 months\ * \4-6 months\ * \More than 6 months\ * \No timeframe\

- **`role_in_purchase_process`**

`string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" — The registrant's role in the purchase process. * \Decision Maker\ * \Evaluator/Recommender\ * \Influencer\ * \Not involved\

- **`state`**

`string` — The registrant's state or province.

- **`status`**

`string`, possible values: "approved", "denied", "pending" — The registrant's status. * \approved\ - Registrant is approved. * \denied\ - Registrant is denied. * \pending\ - Registrant is waiting for approval.

- **`zip`**

`string` — The registrant's ZIP or postal code.

Example:

```json
{
  "address": "1800 Amphibious Blvd.",
  "city": "Mountain View",
  "comments": "Looking forward to the discussion.",
  "country": "US",
  "custom_questions": [
    {
      "title": "What do you hope to learn from this?",
      "value": "Look forward to learning how you come up with new recipes and what other services you offer."
    }
  ],
  "email": "jchill@example.com",
  "first_name": "Jill",
  "industry": "Food",
  "job_title": "Chef",
  "last_name": "Chill",
  "no_of_employees": "1-20",
  "org": "Cooking Org",
  "phone": "5550100",
  "purchasing_time_frame": "1-3 months",
  "role_in_purchase_process": "Influencer",
  "state": "CA",
  "status": "approved",
  "zip": "94045"
}
```

Responses

Status: 201 **HTTP Status Code:** \201\ Registration submitted.

Content-Type: application/json

- **`id`**

`integer`, format: `int64` — \[Meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-
```

a-Meeting-ID-): Unique identifier of the meeting in `"%s"` format (represented as int64 data type in JSON), also known as the meeting number.

- `**`registrant_id`**`

``string`` — Registrant ID

- `**`share_url`**`

``string`` — Share URL for the on-demand recording. This includes the `"token"` token for the registrant. This is similar to the token that Zoom returns in the URL response to join a registered meeting, for example: `"url?tk=xxxx"`. Except while the meeting registration token can be used to join the meeting, this token can only be used to watch the recording.

- `**`topic`**`

``string`` — Meeting Topic

**Example:**

```
```json
{
  "id": 6840331980,
  "registrant_id": "3Z7sEm0TQieLav3c30D_g",
  "share_url": "https://example.com/rec/share/Qg75t7xZBtEbAkjdLgbfdngBBBB",
  "topic": "My Personal Meeting Room"
},
```,
```

#### Status: 404 `"HTTP Status Code: 404"` Not Found

#### Status: 429 `"HTTP Status Code: 429"` Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/) (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Get registration questions

- **Method:** `GET`  
 - **Path:** `/meetings/{meetingId}/recordings/registrants/questions`  
 - **Tags:** Cloud Recording

Retrieve a list of questions that are displayed for users to complete when registering to view the recording of a specific meeting.

For [on-demand] (<https://support.zoom.us/hc/en-us/articles/360000488283-On-demand-Recordings>) meeting recordings, you can include fields with questions that will be shown to registrants when they register to view the recording.

Learn more about [enabling cloud recordings] ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0063923](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923)) and [managing cloud recording settings] ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0065362](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362)).

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `recording:read:admin`, `recording:read`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `cloud_recording:read:registration_questions`, `cloud_recording:read:registration_questions:master`, `cloud_recording:read:registration_questions:admin`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

#### Responses

#### Status: 200 `"HTTP Status Code: 200"` Recording registrant question object returned.

##### Content-Type: application/json

- `**`custom_questions`**`

``array`` — Array of registrant custom questions.

**Items:**

- `**`answers`**`

``array`` — Answer choices for the question. Cannot be used with short answer type.

**Items:**

``string``



```

- **`required`**

 `boolean` — Whether registrants are required to answer custom questions or not.

- **`title`**

 `string` — The question's title.

- **`type`**

 `string`, possible values: `"short", "single", "multiple"` — The type of registration question and answers.

- **`questions`**

 `array` — Array of registrant questions.

Items:

- **`field_name`**

 `string`, possible values: `"last_name", "address", "city", "country", "zip", "state", "phone", "industry", "org", "job_title", "purchasing_time_frame", "role_in_purchase_process", "no_of_employees", "comments"` — Field name.

- **`required`**

 `boolean` — Whether the field is required to be answered by the registrant or not.

```

**\*\*Example:\*\***

```

```json
{
  "custom_questions": [
    {
      "answers": [
        "true"
      ],
      "required": true,
      "title": "What's your name?",
      "type": "short"
    }
  ],
  "questions": [
    {
      "field_name": "last_name",
      "required": true
    }
  ]
}
```

```

##### Status: 404 `HTTP Status Code: 404` Not Found

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/) `(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### Update registration questions

```

- **Method:** `PATCH`
- **Path:** /meetings/{meetingId}/recordings/registrants/questions`
- **Tags:** Cloud Recording

```

Update registration questions for users to answer while registering to view a recording.

For [\[on-demand\]](https://support.zoom.us/hc/en-us/articles/360000488283-On-demand-Recordings) meeting recordings, you can include fields with questions that will be shown to registrants when they register to view the recording.

Learn more about [\[enabling cloud recordings\]](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923) and [\[managing cloud recording settings\]](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362).

**\*\*[Scopes]** `(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `recording:write:admin``, `recording:write``

**\*\*[Granular Scopes]** `(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `cloud_recording:update:registration_questions:admin``, `cloud_recording:update:registration_questions``, `cloud_recording:update:registration_questions:master``

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** **LIGHT**

#### Request Body

Content-Type: application/json

**All of:**

- **custom\_questions**

**array** — Array of registrant custom questions.

**Items:**

- **answers**

**array** — Answer choices for the question. Cannot be used with short answer type.

**Items:**

**string**

- **required**

**boolean** — Whether registrants are required to answer custom questions or not.

- **title**

**string** — The question's title.

- **type**

**string**, possible values: `"short", "single", "multiple"` — The type of registration question and answers.

- **questions**

**array** — Array of registrant questions.

**Items:**

- **field\_name**

**string**, possible values: `"last_name", "address", "city", "country", "zip", "state", "phone", "industry", "org", "job_title", "purchasing_time_frame", "role_in_purchase_process", "no_of_employees", "comments"` — Field name.

- **required**

**boolean** — Whether the field is required to be answered by the registrant or not.

**Example:**

```
```json
{
  "custom_questions": [
    {
      "answers": [
        "true"
      ],
      "required": true,
      "title": "What's your name?",
      "type": "short"
    }
  ],
  "questions": [
    {
      "field_name": "last_name",
      "required": true
    }
  ]
}
```
```

#### Responses

**Status: 204** **HTTP Status Code:** `200` Recording registrant questions updated

**Status: 404** **HTTP Status Code:** `404`   
 Not Found

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### ### Update a registrant's status

```
- **Method:** `PUT`
- **Path:** `/meetings/{meetingId}/recordings/registrants/status`
- **Tags:** Cloud Recording
```

Update a registrant's status. A registrant can either be approved or denied from viewing the `[on-demand]` (<https://support.zoom.us/hc/en-us/articles/360000488283-On-demand-Recordings>) recording.

Learn more about `[enabling cloud recordings]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0063923](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923)) and `[managing cloud recording settings]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0065362](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362)).

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `**`recording:write:admin`,`recording:write``

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `**`cloud_recording:update:registrant_status`,`cloud_recording:update:registrant_status:master`,`cloud_recording:update:registrant_status:admin``

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `**`MEDIUM``

### #### Request Body

##### Content-Type: application/json

```
- **`action` (required)**
 `string`, possible values: `"approve", "deny"`

- **`registrants`**
 `array` — List of registrants.

 Items:
 - **`id`**
 `string`
```

**Example:**

```
```json
{
  "action": "approve",
  "registrants": [
    {
      "id": "3Z7sEm0TQieLav3c30D_g"
    }
  ]
}
```

Responses

Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` Registrant status updated.

Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br>` Not Found

Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

Get meeting recording settings

```
- **Method:** `GET`
- **Path:** `/meetings/{meetingId}/recordings/settings`
- **Tags:** Cloud Recording
```

Retrieve settings applied to a meeting's `[cloud recording]` (<https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording>).

Response includes recording content access information, which requires the current user to have the ``View the recording content`` permission to access it.

Learn more about `[enabling cloud recordings]` (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923) and `[managing cloud recording settings]` (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362).

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `recording:read:admin`,`recording:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `cloud\_recording:read:recording\_settings`,`cloud\_recording:read:recording\_settings:admin`,`cloud\_recording:read:recording\_settings:master`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `HTTP Status Code:200` Meeting recording settings returned.

Content-Type: application/json

- **`approval\_type`**

`integer`, possible values: `0, 1, 2` — The registration approval type. `0` - Automatically approve the registration when a user registers. `1` - Manually approve or deny the registration of a user. `2` - No registration required to view the recording.

- **`authentication\_domains`**

`string` — The domains for authentication.

- **`authentication\_name`**

`string` — The name for authentication.

- **`authentication\_option`**

`string` — The options for authentication.

- **`auto\_delete`**

`boolean` — Auto-delete status of a meeting's `[cloud recording](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording)`. Prerequisite: To get the auto-delete status, the host of the recording must have the recording setting "Delete cloud recordings after a specified number of days" enabled.

- **`auto\_delete\_date`**

`string` — The date when the recording will be auto-deleted when `auto_delete` is `true`. Otherwise, no date is returned.

- **`on\_demand`**

`boolean` — This field determines whether registration is required to view the recording.

- **`password`**

`string` — This field enables passcode protection for the recording by setting a passcode. The passcode must have a minimum of `eight` characters with a mix of numbers, letters and special characters. **Note:** If the account owner or the admin has set minimum passcode strength requirements for recordings through Account Settings, the passcode value provided here must meet those requirements. If the requirements are enabled, you can view those requirements by calling either the `[Get user settings](/api-reference/zoom-api/methods#operation/userSettings)` API or the `[Get account settings](/api-reference/zoom-api/ma#operation/accountSettings)` API.

- **`recording\_authentication`**

`boolean` — Only allow authenticated users to view.

- **`send\_email\_to\_host`**

`boolean` — Enable sending an email to the host when someone registers to view the recording. This applies for On-demand recordings only.

- **`share\_recording`**

`string`, possible values: `"publicly"`, `"internally"`, `"none"` — Determine how the meeting recording is shared.

- **`show\_social\_share\_buttons`**

`boolean` — Show social share buttons on the registration page. This applies for On-demand recordings only.

- **`topic`**

```

`string` — The recording's name.

- **`viewer_download`**

`boolean` — Determine whether a viewer can download the recording file or not.

**Example:**

```json
{
 "approval_type": 0,
 "authentication_domains": "example.com",
 "authentication_option": "auth_option",
 "authentication_name": "auth display name",
 "on_demand": false,
 "password": "975238724",
 "recording_authentication": true,
 "send_email_to_host": false,
 "share_recording": "publicly",
 "show_social_share_buttons": true,
 "topic": "My Personal Meeting Room",
 "viewer_download": true,
 "auto_delete": true,
 "auto_delete_date": "2028-07-12"
}
```

##### Status: 404 \*\*HTTP Status Code:\*\* \`404\` \<br> Not Found

##### Status: 429 \*\*HTTP Status Code:\*\* \`429\` \<br> Too Many Requests. For more information, see \
[rate limits](/docs/api/rate-limits/).

### Update meeting recording settings

- **Method:** `PATCH`
- **Path:** `/meetings/{meetingId}/recordings/settings`
- **Tags:** Cloud Recording

Update settings applied to a meeting's [cloud recording](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording). The request contains the recording content access information, which requires the current user to have the `view recording content` and `recording editing` permissions to access.

Learn more about [enabling cloud recordings](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923) and [managing cloud recording settings](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362).

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`recording:write:admin`, `recording:write`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`cloud_recording:update:recording_settings`, `cloud_recording:update:recording_settings:master`, `cloud_recording:update:recording_settings:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

#### Request Body

##### Content-Type: application/json

- **`approval_type`**

`integer`, possible values: `0, 1, 2` — The approval type for the registration. \0\` - Automatically approve the registration when a user registers. \1\` - Manually approve or deny the registration of a user. \2\` - No registration required to view the recording.

- **`authentication_domains`**

`string` — The authentication domains.

- **`authentication_option`**

`string` — The authentication options.

- **`auto_delete`**

`boolean` — Update the auto-delete status of a meeting's \[cloud recording](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording). Prerequisite: To update the auto-delete status, the host of the recording must have the recording setting "Delete cloud recordings after a

```

specified number of days" enabled.

- **on_demand**

boolean — Determine whether the registration is required to view the recording.

- **password**

string — Enable passcode protection for the recording by setting a passcode. The passcode must have a minimum of 8 characters with a mix of numbers, letters and special characters. **Note:** If the account owner or the admin has set minimum passcode strength requirements for recordings through Account Settings, the passcode value provided here must meet those requirements. If the requirements are enabled, you can view those requirements by calling either the `GET /api-reference/zoom-api/methods#operation/userSettings` API or the `GET /api-reference/zoom-api/methods#operation/accountSettings` API.

- **recording_authentication**

boolean — Indicate that only authenticated users can view.

- **send_email_to_host**

boolean — Send an email to host when someone registers to view the recording. This setting applies for On-demand recordings only.

- **share_recording**

string, possible values: "publicly", "internally", "none" — Determine how the meeting recording is shared.

- **show_social_share_buttons**

boolean — Show social share buttons on registration page. This setting applies for On-demand recordings only.

- **topic**

string — The name of the recording.

- **viewer_download**

boolean — Determine whether a viewer can download the recording file or not.

Example:

```
```json
{
 "approval_type": 0,
 "authentication_domains": "test.com",
 "authentication_option": "auth_option",
 "on_demand": false,
 "password": "975238724",
 "recording_authentication": true,
 "send_email_to_host": false,
 "share_recording": "publicly",
 "show_social_share_buttons": true,
 "topic": "My Personal Meeting Room",
 "viewer_download": true,
 "auto_delete": false
}
```

#### #### Responses

##### Status: 204 **HTTP Status Code:** 204 Meeting recording setting's updated.

##### Status: 404 **HTTP Status Code:** 404   
 Not Found

##### Status: 429 **HTTP Status Code:** 429   
 Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Delete a recording file for a meeting or webinar

- **Method:** DELETE  
 - **Path:** /meetings/{meetingId}/recordings/{recordingId}  
 - **Tags:** Cloud Recording

Delete a specific recording file from a meeting or webinar. Note: To use this API, you must enable the **The host can delete cloud recordings** setting. Find this setting in the **Recording** tab of the **Settings** interface in the [Zoom web portal](https://zoom.us/)(https://zoom.us/).

```

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:write:admin`,`recording:write`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`cloud_recording:delete:recording_file`,`cloud_recording:delete:recording_file:admin`,`cloud_recording:delete:recording_file:master`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

```

#### #### Responses

##### Status: 204 The recording file was successfully deleted.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 1010` `User does not belong to this account: {accountId}`. `You can not delete an uncompleted meeting`. `This recording was selected for a simulative webinar. You cannot delete or trash it`. `Unable to delete this file because this recording is being used for Zoom IQ for Sales`.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `User {userId} does not exist or does not belong to this account`. `There is no recording for this meeting`.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests`. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

#### ### Recover a single recording

```

- **Method:** `PUT`
- **Path:** `/meetings/{meetingId}/recordings/{recordingId}/status`
- **Tags:** Cloud Recording

```

Recover a single recording file from the meeting.

Zoom lets users recover recordings from trash for up to 30 days from the deletion date.

```

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:write:admin`,`recording:write`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`cloud_recording:update:recover_single_recording`,`cloud_recording:update:recover_single_recording:master`,`cloud_recording:update:recover_single_recording:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

```

#### #### Request Body

##### Content-Type: application/json

```

- **`action`**

 `string`, possible values: `recover`

```

**Example:**

```

```json
{
  "action": "recover"
}
```

```

#### #### Responses

##### Status: 204 `HTTP Status Code: 204` Meeting recording recovered.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 1010` `User does not belong to this account: {accountId}`. `Not enough cloud storage available. Either purchase additional storage or delete cloud recordings to free up storage`.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `User {userId} does not exist or does not belong to this account`. `There is no recording for this meeting`.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests`. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

#### ### Get a meeting transcript

```

- **Method:** `GET`

```

```
- **Path:** `/meetings/{meetingId}/transcript`
- **Tags:** Cloud Recording
```

Return a meeting's [transcript](https://support.zoom.com/hc/en/article?id=zm\_kb&sysparm\_article=KB0076632) information. Use the `download\_url` property listed in the response to download the transcript content.

To download the transcript, send the user's [OAuth access token](/docs/integrations/oauth/) as a Bearer token in the Authorization header.

```
`curl -H 'Authorization: Bearer <ACCESS_TOKEN>' https://{base-domain}/rec/meeting/transcript/download/xyz`
```

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:read`,`recording:write`,`recording:read:admin`,`recording:write:admin`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`cloud_recording:read:meeting_transcript`,`cloud_recording:read:meeting_transcript:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`
```

#### #### Responses

##### Status: 200 HTTP Status Code: 200 Transcript object returned.

##### Content-Type: application/json

```
- **`account_id`**
```

`string` — The user account's unique identifier.

```
- **`auto_delete`**
```

`boolean` — Auto-delete status of a meeting's transcript Prerequisite: To get the auto-delete status, the host of the recording must have the recording setting `Delete cloud recordings after a specified number of days` enabled.

```
- **`auto_delete_date`**
```

`string` — The date when the recording will be auto-deleted when `auto\_delete` is true. Otherwise, no date will be returned.

```
- **`can_download`**
```

`boolean` — Whether the meeting transcript is available for download. `true`: The transcript is ready and `download\_url` will be returned. `false`: The transcript cannot be downloaded. and the `download\_restriction\_reason` field will be returned instead with the explanation. Only when `can\_download` is `true`, the transcript file can be accessed.

```
- **`download_restriction_reason`**
```

`string | null`, possible values: `DELETED\_OR\_TRASHED`, `UNSUPPORTED`, `NO\_TRANSCRIPT\_DATA`, `NOT\_READY` — If `can\_download` is false, this field provides the reason why the transcript cannot be downloaded. This field is only present when `can\_download` is `false`. If present, `download\_url` will not be included.

| Value              | Description                                                                   |
|--------------------|-------------------------------------------------------------------------------|
| DELETED_OR_TRASHED | The transcript has been deleted or moved to trash and is no longer available. |
| UNSUPPORTED        | The transcript format is not supported for download.                          |
| NO_TRANSCRIPT_DATA | No transcript data exists for the meeting.                                    |
| NOT_READY          | The transcript is still being processed and not yet ready for download.       |

```
- **`download_url`**
```

`string | null` — The URL to download the transcript. This field is only present when `can\_download` is `true`. If present, `download\_restriction\_reason` will not be included. If a user has authorized and installed your OAuth app that contains recording scopes, use the user's [OAuth access token](https://developers.zoom.us/docs/integrations/oauth/) to download the file. Set the `access\_token` as a Bearer token in the Authorization header. For example: `curl -H 'Authorization: Bearer <ACCESS\_TOKEN>' https://{base-domain}/rec/archive/download/xyz`.

```
- **`host_id`**
```

`string` — ID of the user set as the host of the meeting.

```
- **`meeting_id`**
```

`string` — The meeting ID

```
- **`meeting_topic`**
```

`string` — The meeting topic.



- **transcript\_created\_time**

**string** — The date and time that the meeting's transcript was created.

**Example:**

**json**

```
{
 "meeting_id": "uaFkQyFCSwya8iNYtkAw3A==",
 "account_id": "Cx3wERazSgup7ZWRHQM8-w",
 "meeting_topic": "My Personal Meeting",
 "host_id": "_0ctZtY0REqWalTmwvrdIw",
 "transcript_created_time": "2025-06-27T13:48:24Z",
 "can_download": true,
 "auto_delete": true,
 "auto_delete_date": "2052-11-07",
 "download_url":
"https://example.com/rec/meeting/transcript/download/YDztop0PYLrAQat616a1q1H86RM4jf1Bf3p42a4Ap1jV3bWAJAE.jji
xtQU52SEwrsuJ",
 "download_restriction_reason": "NOT_READY"
}
```

**Status: 403** HTTP Status Code: 403 Forbidden No permission

**Status: 404** HTTP Status Code: 404 Not Found Error Code: 3322 This meeting transcript does not exist.

**Status: 429** HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).

**Delete a meeting or webinar transcript**

**Method:** DELETE  
**Path:** /meetings/{meetingId}/transcript  
**Tags:** Cloud Recording

Delete a transcript for a meeting or webinar.

**Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): recording:write, recording:write:admin

**Granular Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): cloud\_recording:delete:meeting\_transcript, cloud\_recording:delete:meeting\_transcript:admin

**Rate Limit Label**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): MEDIUM

**Responses**

**Status: 204** HTTP Status Code: 204 Meeting transcript has been deleted.

**Status: 400** HTTP Status Code: 400 Bad Request

**Status: 403** HTTP Status Code: 403 Forbidden No permission

**Status: 404** HTTP Status Code: 404 Not Found Error Code: 3322 This meeting transcript does not exist.

**Status: 429** HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).

**Recover meeting recordings**

**Method:** PUT  
**Path:** /meetings/{meetingUUID}/recordings/status  
**Tags:** Cloud Recording

Recover all deleted [cloud recordings](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording) of a specific meeting.  
Zoom lets users recover recordings from trash for up to 30 days from the deletion date.

**Prerequisites:**

- A Pro user with Cloud Recording enabled.

**Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): recording:write:admin, recording:write

**Granular Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): cloud\_recording:update:recover\_meeting\_recordings, cloud\_recording:update:recover\_meeting\_recordings:maste

```
r`, `cloud_recording:update:recover_meeting_recordings:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`
```

```
Request Body
```

```
Content-Type: application/json
```

```
- **`action`**
```

```
 `string`, possible values: `"recover"`
```

```
Example:
```

```
```json
{
  "action": "recover"
}
```
```

```
Responses
```

```
Status: 200 `HTTP Status Code: 200` Recordings recovered. `Error Code: 200` You do not have the right permissions.
```

```
Status: 400 `HTTP Status Code: 400`
 Bad Request `Error Code: 1010`
 User does not belong to this account: {accountId}.
 `Error Code: 3309`
 Not enough cloud storage available. Either purchase additional storage or delete cloud recordings to free up storage.

```

```
Status: 404 `HTTP Status Code: 404`
 Not Found `Error Code: 1001`
 User does not exist: {userId}.

 `Error Code: 3301`
 There is no recording for this meeting.

```

```
Status: 429 `HTTP Status Code: 429`
 Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).
```

```
List all recordings
```

```
- **Method:** `GET`
- **Path:** `/users/{userId}/recordings`
- **Tags:** Cloud Recording
```

Lists all [cloud recordings](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-Recording) for a user.

For user-level apps, pass the [me` value](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter. To access a user's passcode protected cloud recording, send the user's [OAuth access token](https://developers.zoom.us/docs/integrations/oauth/) as a bearer token in the authorization header.

```
Example: `curl -H "Authorization: Bearer <ACCESS_TOKEN>" https://{base-domain}/rec/archive/download/xyz`
```

```
Prerequisites:
```

```
- Must have a Pro or a higher plan.
- Must enable Cloud Recording on the user's account. Learn more about [enabling cloud recordings](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063923) and [managing cloud recording settings](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065362).
```

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`recording:read:admin`, `recording:read`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`cloud_recording:read:list_user_recordings`, `cloud_recording:read:list_user_recordings:master`, `cloud_recording:read:list_user_recordings:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`
```

```
Responses
```

```
Status: 200 `HTTP Status Code: 200` List of recording objects returned.
```

```
Content-Type: application/json
```

```
All of:
```

```
- **`from`**
```

```
 `string`, format: `date` — The start date.
```

```
- **`topic`**
```

```

`string` — Meeting topic.

- **`total_size`**

`integer`, format: `int64` — The total file size of the recording. This includes the
`recording_files` and `participant_audio_files` files.

- **`type`**

`string`, possible values: `1`, `2`, `3`, `4`, `5`, `6`, `7`, `8`, `9`, `99` — The recording's
associated type of meeting or webinar: If the recording is of a meeting: `1` - Instant meeting. `2` - Scheduled meeting. `3` - A recurring meeting with no fixed time. `4` - A meeting created
via Personal Meeting ID (PMI). `7` - A [Personal Audio Conference](https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference) (PAC). `8` - Recurring meeting
with a fixed time. If the recording is of a webinar: `5` - A webinar. `6` - A recurring webinar
without a fixed time. `9` - A recurring webinar with a fixed time. If the recording is `not` from
a meeting or webinar: `99` - A recording uploaded via the [Recordings](https://zoom.us/recording) interface on the Zoom Web Portal.

- **`uuid`**

`string` — Unique Meeting Identifier. Each instance of the meeting will have its own UUID.

All of:

- **`recording_files`**

`array` — List of recording file.

Items:

All of:

- **`deleted_time`**

`string` — The time when recording was deleted. Returned in the response only for trash query.

- **`download_url`**

`string` — The URL to download the recording. If a user has authorized and installed your OAuth app
that contains recording scopes, use the `download_access_token` or the user's [OAuth access token](https://developers.zoom.us/docs/integrations/oauth/) to download the file. Set the token as a Bearer token
in the Authorization header. `curl -H 'Authorization: Bearer <ACCESS_TOKEN>' https://{base-domain}/rec/archive/download/xyz`. Note: This field does not return for [Zoom On-Premise
accounts](https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment). Instead,
this API will return the `file_path` field. The URL may be a redirect. In that case, use `curl --location` to follow redirects or use another tool, like Postman.

- **`file_extension`**

`string`, possible values: `MP4`, `M4A`, `TXT`, `VTT`, `CSV`, `JSON`, `JPG` — The file extension
type of the recording file.

- **`file_path`**

`string` — The file path to the On-Premise account recording. Note: This API only returns
this field for [Zoom On-Premise accounts](https://support.zoom.us/hc/en-us/articles/360034064852-Zoom-On-Premise-Deployment). It does not return the `download_url` field.

- **`file_size`**

`number` — The recording file size.

- **`file_type`**

`string`, possible values: `MP4`, `M4A`, `CHAT`, `TRANSCRIPT`, `CSV`, `TB`, `CC`, `CHAT_MESSAGE`,
`SUMMARY` — The recording file type. `MP4` - Video file of the recording. `M4A` - Audio-only file of the
recording. `TIMELINE` - Timestamp file of the recording in JSON file format. To get a timeline file, the
`Add a timestamp to the recording` setting must be enabled in the [recording settings](https://support.zoom.us/hc/en-us/articles/203741855-Cloud-recording#h_3f14c3a4-d16b-4a3c-bbe5-ef7d24500048). The time will display in the host's timezone, set on their Zoom profile. `TRANSCRIPT` -
Transcription file of the recording in VTT format. `CHAT` - A TXT file containing in-meeting chat messages
that were sent during the meeting. `CC` - File containing closed captions of the recording in VTT file
format. `CSV` - File containing polling data in CSV format. A recording file object with file type of
either `CC` or `TIMELINE` does not have the following properties: `id`, `status`,
`file_size`, `recording_type`, and `play_url`. `SUMMARY` - Summary file of the recording in JSON
file format.

- **`id`**

```

`string` — The recording file ID. Included in the response of general query.

- **meeting\_id**

`string` — The meeting ID.

- **play\_url**

`string` — The URL to play a recording file.

- **recording\_end**

`string` — The recording end time. Response in general query.

- **recording\_start**

`string` — The recording start time.

- **recording\_type**

`string`, possible values: `"shared_screen_with_speaker_view(CC)", "shared_screen_with_speaker_view", "shared_screen_with_gallery_view", "active_speaker", "gallery_view", "shared_screen", "audio_only", "audio_transcript", "chat_file", "poll", "host_video", "closed_caption", "timeline", "thumbnail", "audio_interpretation", "summary", "summary_next_steps", "summary_smart_chapters", "sign_interpretation", "production_studio"` — The recording type. `"shared\_screen\_with\_speaker\_view(CC)"`, `"shared\_screen\_with\_speaker\_view"`, `"shared\_screen\_with\_gallery\_view"`, `"active\_speaker"`, `"gallery\_view"`, `"shared\_screen"`, `"audio\_only"`, `"audio\_transcript"`, `"chat\_file"`, `"poll"`, `"host\_video"`, `"closed\_caption"`, `"timeline"`, `"thumbnail"`, `"audio\_interpretation"`, `"summary"`, `"summary\_next\_steps"`, `"summary\_smart\_chapters"`, `"sign\_interpretation"`, `"production\_studio"`

- **status**

`string`, possible values: `"completed"` — The recording status.

**Example:**

```
```json
{
  "from": "2022-01-01",
  "to": "2022-04-01",
  "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
  "page_count": 1,
  "page_size": 30,
  "total_records": 1,
  "meetings": [
    {
      "account_id": "Cx3wERazSgup7ZWRHQM8-w",
      "duration": 20,
      "host_id": "_0ctZtY0REqWalTmwvrdIw",
      "id": 6840331990,
      "recording_count": 22,
      "start_time": "2021-03-18T05:41:36Z",
      "topic": "My Personal Meeting",
      "total_size": 22,
      "type": "1",
      "uuid": "BOKXuumlTAGXuqwr3bLyuQ==",
      "recording_play_passcode": "yNYIS408EJygs7rE5vVsJwXIz4-VW7MH",
      "auto_delete": true,
      "auto_delete_date": "2028-07-12",
      "recording_files": [
        {
          "deleted_time": "2021-03-18T05:41:36Z",
          "download_url": "https://example.com/rec/download/Qg75t7xZBtEbAkjdlgbfdngBBBB",
          "file_path": "/9090876528/path01/demo.mp4",
          "file_size": 7220,
          "file_type": "MP4",
          "file_extension": "M4A",
          "id": "72576a1f-4e66-4a77-87c4-f13f9808bd76",
          "meeting_id": "L0AG0EPVR9m5WS00s/d+FQ==",
          "play_url": "https://example.com/rec/play/Qg75t7xZBtEbAkjdlgbfdngBBBB",
          "recording_end": "2021-03-18T05:41:36Z",
          "recording_start": "2021-03-18T05:41:36Z",
          "recording_type": "shared_screen_with_speaker_view",
          "status": "completed"
        }
      ]
    }
  ]
}
```

```
##### Status: 401 \*\*HTTP Status Code:\*\* \`401\` \<br> Unauthorized \*\*Error Code:\*\* \`124\` \<br> Requires an access token. \<br>
```

```
##### Status: 404 \*\*HTTP Status Code:\*\* \`404\` \<br> Not Found \*\*Error Code:\*\* \`1001\` \<br> User {userId} does not exist, or does not belong to this account. \<br> \*\*Error Code:\*\* \`3301\` \<br> There is no recording for this session. \<br>
```

```
##### Status: 429 \*\*HTTP Status Code:\*\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).
```

List devices

```
- **Method:** \`GET\`
- **Path:** \`/devices\`
- **Tags:** Devices
```

This API lets you list devices.

```
**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
\`device:read:admin\`,\`device:write:admin\`
```

```
**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** \`HEAVY\`
```

Responses

```
##### Status: 200 \*\*HTTP Status Code:\*\* \`200\` \*\*OK\*\* Device detail returned successfully.
```

```
##### Content-Type: application/json
```

```
- **\`devices\`**
```

```
\`array\`
```

```
**Items:**
```

```
- **\`app_version\`**
```

```
\`string\` — App version of Zoom Rooms.
```

```
- **\`connected_to_zdm\`**
```

```
\`boolean\` — Whether the device connected to ZDM (Zoom Device Management).
```

```
- **\`device_id\`**
```

```
\`string\` — Unique identifier of the device.
```

```
- **\`device_name\`**
```

```
\`string\` — The name of the device.
```

```
- **\`device_status\`**
```

```
\`integer\`, possible values: \`-1, 0, 1\` — Filter devices by status. Device Status: \`0\` - offline. \`1\` - online. \`-1\` - unlink
```

```
- **\`device_type\`**
```

```
\`integer\`, possible values: \`0, 1, 2, 3, 4, 5, 6\` — Filter devices by device type. Device Type: \`-1\` - All Zoom Room device(0,1,2,3,4,6). \`0\` - Zoom Rooms Computer. \`1\` - Zoom Rooms Controller. \`2\` - Zoom Rooms Scheduling Display. \`3\` - Zoom Rooms Control System. \`4\` - Zoom Rooms Whiteboard. \`5\` - Zoom Phone Appliance. \`6\` - Zoom Rooms Computer (with Controller).
```

```
- **\`enrolled_in_zdm\`**
```

```
\`boolean\` — Whether the device enrolled in ZDM (Zoom Device Management).
```

```
- **\`last_online\`**
```

```
\`string\` — The time when device was online last time.
```

```
- **\`mac_address\`**
```

```
\`string\` — The mac address of the device.
```

```
- **\`model\`**
```

```
\`string\` — The device's model.
```

- **platform_os**
`string` — The device's platform.
- **room_id**
`string` — id of the Zoom Room.
- **room_name**
`string` — Name of the Zoom Room.
- **serial_number**
`string` — The device's serial number.
- **skd_version**
`string` — The version of the SDK.
- **tag**
`string` — The name of the tag.
- **user_email**
`string` — The owner of the phone device
- **vendor**
`string` — The device's manufacturer.
- **next_page_token**
`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.
- **page_size**
`integer` — The number of records returned within a single API call.

Example:

```
```json
{
 "next_page_token": "At6eWnFZ1FB3arCXnRxqHLXKhbDW18yz2i2",
 "page_size": 20,
 "devices": [
 {
 "device_id": "F1C6E9DF-429E-4FA1-85DA-AC95464F3D18",
 "device_name": "My device",
 "mac_address": "01-23-45-67-89-AB",
 "serial_number": "6NRN2A0",
 "vendor": "Poly",
 "model": "StudioX30",
 "platform_os": "Epos expandvision5 1.2.22315.04",
 "app_version": "5.13.0.5762",
 "tag": "personal rooms",
 "enrolled_in_zdm": true,
 "connected_to_zdm": true,
 "room_id": "72afdc13-a289-40c3-b358-50c8b8de",
 "room_name": "My Personal Meeting Room",
 "device_type": 0,
 "skd_version": "2.0.11",
 "device_status": 0,
 "last_online": "2022-10-27T10:23:15Z",
 "user_email": "test-user@ya.us"
 }
]
}
```

#### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 30055008` `no permission.`

#### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### Add a new device

```
- **Method:** `POST`
- **Path:** `/devices`
- **Tags:** Devices
```

Add a new device to Zoom account.

```
Scope: `device:write:admin`
```

```
[Rate Limit Label](https://developers.zoom.us/docs/api/rest/rate-limits/): `Medium`
```

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `device:write:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`
```

#### Request Body

```
Content-Type: application/json
```

```
- **`device_name` (required)**
```

```
 `string` — The device's name.
```

```
- **`device_type` (required)**
```

```
 `integer`, possible values: `0, 1, 5` — Device type. `0` - Zoom Rooms computer. `1` - Zoom Rooms controller. `5` - Zoom Phone appliance.
```

```
- **`mac_address` (required)**
```

```
 `string` — The device's mac address.
```

```
- **`model` (required)**
```

```
 `string` — The device's model.
```

```
- **`serial_number` (required)**
```

```
 `string` — The device's serial number.
```

```
- **`vendor` (required)**
```

```
 `string` — The device's manufacturer.
```

```
- **`extension_number`**
```

```
 `string` — The extension number.
```

```
- **`room_id`**
```

```
 `string` — The Zoom Room's ID. Only for Zoom Room devices.
```

```
- **`tag`**
```

```
 `string` — The name of the tag.
```

```
- **`user_email`**
```

```
 `string` — User email for assigning the Zoom Phone device. Only for Zoom Phone devices.
```

```
- **`zdm_group_id`**
```

```
 `string` — The ZDM group ID.
```

```
Example:
```

```
```json
{
  "device_name": "My device",
  "mac_address": "01-23-45-67-89-AB",
  "serial_number": "6NRN2A0",
  "vendor": "Poly",
  "model": "StudioX30",
  "room_id": "72afdc13-a289-40c3-b358-50c8b8de",
  "user_email": "test-user@ya.us",
  "device_type": 0,
  "tag": "personal rooms",
  "zdm_group_id": "ff49588c-92c4-4406-99e6-1942d8a61a7b",
  "extension_number": "802"
}
```


Responses

Status: 202 `HTTP Status: 202` Accepted Request processed successfully.

Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 30055001` zoom room does not exist.
`Error Code: 30055002` required param can not be empty or null.
`Error Code: 30055003` device type does not support.
`Error Code: 30055004` model or vendor not exist.
`Error Code: 30055005` tag length can not be more than 64.
`Error Code: 30055006` device has already exist.
`Error Code: 30055007` invalid mac address.
`Error Code: 30055008` no permission.
`Error Code: 30055009` email does not have plan.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get ZDM group info

- `Method:` GET
 - `Path:` /devices/groups
 - `Tags:` Devices

Get Zoom Device Manager (ZDM) group information for an account.

`[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):` device:read:admin

`[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):` device:read:list_groups:admin, device:read:list_groups:master

`[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):` MEDIUM

Responses

Status: 200 `HTTP Status Code: 200` OK Version detail returned successfully.

Content-Type: application/json

- `groups`

array — All ZDM group information under current account.

`Items:`

- `description`
- string — The ZDM group's describe.
- `name`
- string — The ZDM group's name.
- `zdm_group_id`
- string — The ZDM group's unique ID.
- `next_page_token`
- string — Use the next page token to paginate through a large set of results. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.
- `page_size`
- integer — The total number of records returned from a single API call.

`Example:`

```
```json
{
 "groups": [
 {
 "zdm_group_id": "ff49588c-92c4-4406-99e6-1942d8a61a7b",
 "name": "HeFei-group",
 "description": "Group in Hefei region"
 }
],
 "next_page_token": "Ra087FrnwXvFQta5aV8sU5C3c908s9Nraq2",
 "page_size": 30
}
```

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br> Bad Request \*\*Error Code:\*\* \`30051037\`` `\<br> Invalid parameters. \<br>`

##### Status: 403 `\*\*HTTP Status Code:\*\* \`403\`` `\<br> Forbidden \*\*Error Code:\*\* \`30055008\`` `\<br> No permission. \<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).`

### Assign a device to a user or commonarea

- `**Method:** \`POST\``  
 - `**Path:** \`/devices/zpa/assignment\``  
 - `**Tags:** Devices`

Assign a device to a user or common area, or move a device to another user or common area, or remove a device.

`**Prerequisites:**`

- Device must be enrolled in Zoom Device Management (ZDM).

`**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** \`device:write:admin\``

`**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** \`device:write:zpa_device:admin\`, \`device:write:zpa_device:master\``

`**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** \`MEDIUM\``

#### Request Body

##### Content-Type: application/json

- `**\`mac_address\` (required)**`  
`\`string\`` — The device's mac address.  
 - `**\`vendor\` (required)**`  
`\`string\`` — The device's manufacturer.  
 - `**\`extension_number\`**`  
`\`string\`` — The extension number.

`**Example:**`

```
``json
{
 "extension_number": "802",
 "mac_address": "64167ffc0ed7",
 "vendor": "poly"
}
```

#### Responses

##### Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` `\*\*No Content\*\*` Request processed successfully.

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br> Bad Request \*\*Error Code:\*\* \`30055003\`` `\<br> Device vendor does not support. \<br> \*\*Error Code:\*\* \`30055007\`` `\<br> Mac address is wrong. \<br> \*\*Error Code:\*\* \`30051039\`` `\<br> Device not exists. \<br> \*\*Error Code:\*\* \`30055002\`` `\<br> AUTO RECEPTIONIST user can not assign to device. \<br> \*\*Error Code:\*\* \`30055009\`` `\<br> User not have phone plan. \<br> \*\*Error Code:\*\* \`30052024\`` `\<br> Extension number not exists. \<br> \*\*Error Code:\*\* \`30055002\`` `\<br> Missing required input. \<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).`

### Get Zoom Phone Appliance settings by user ID

- `**Method:** \`GET\``  
 - `**Path:** \`/devices/zpa/settings\``  
 - `**Tags:** Devices`

Get a user's Zoom Phone Appliance (ZPA) device profile settings. For user-level apps, pass the `\`me\`` value instead of the `\`userId\`` parameter.

```

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `device:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`device:read:user_setting:admin`, `device:read:user_setting:master`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`

```

#### #### Responses

##### Status: 200 `HTTP Status Code: 200 OK` Version detail returned successfully.

##### Content-Type: application/json

- **device\_infos**

array — The ZPA information.

**Items:**

- **device\_id**

string — The device ID.

- **device\_type**

string — The device type.

- **model**

string — The device's model name.

- **policy**

object — The device policy.

- **call\_control**

object

- **status**

string, possible values: "unsupported", "on", "off" — This field lets the call control feature to the current device. Configure the desk phone devices to enable call control, which lets users perform desk phone's call control actions from the Zoom desktop client, including making and accepting calls. `unsupported on off`

- **hot\_desking**

object

- **status**

string, possible values: "online", "offline" — The device's status, either `online` or `offline`.

- **status**

string, possible values: "online", "offline" — The device's status, either `online` or `offline`.

- **vendor**

string — The device's manufacturer.

- **language**

string — The user's language.

- **timezone**

string — The user's timezone.

**Example:**

```

{
 "language": "English",
 "timezone": "(GMT+6:00) Astana, Dhaka",
 "device_infos": [
 {

```



##### Status: 202 The upgrade request has been accepted and is currently being processed.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 30052029` `Missing required input: firmware_versions.` `Error Code: 30055020` `Upgrade type dose not exist.` `Error Code: 30055018` `Zdm group id dose not exist.` `Error Code: 30052030` `Missing required input: app_version.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Delete ZPA device by vendor and mac address

```
- **Method:** `DELETE`
- **Path:** `/devices/zpa/vendors/{vendor}/mac_addresses/{macAddress}`
- **Tags:** Devices
```

Remove a ZPA device from the device manager, by vendor and mac address.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:write:admin`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:delete:zpa_device:admin`, `device:delete:zpa_device:master`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

#### Responses

##### Status: 204 `HTTP Status Code: 204` `No Content` Device deleted successfully.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 30052026` `Device is not ZPA.` `Error Code: 30055003` `Device vendor does not support.` `Error Code: 30055007` `Mac address is wrong.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 30051039` `Zdm device not found.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Get ZPA version info

```
- **Method:** `GET`
- **Path:** `/devices/zpa/zdm_groups/{zdmGroupId}/versions`
- **Tags:** Devices
```

Get ZPA firmware and app version information that can be upgraded for devices.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:read:admin`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:read:list_zpa_versions:admin`, `device:read:list_zpa_versions:master`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

#### Responses

##### Status: 200 `HTTP Status Code: 200` `OK` Version detail returned successfully.

##### Content-Type: application/json

```
- **`app_versions`**

`array` — List of app versions that can be upgraded.

Items:

`string` — The app version.

- **`firmware_versions`**

`array` — List of firmware that can be upgraded.

Items:

- **`model`**

`string` — The device's model name.

- **`vendor`**
```

```

 `string` — The device's manufacturer.
- **`version`**
 `string` — The package version.
- **`warn_info`**
 `string` — The prompt information for this version.
Example:
```json
{
  "firmware_versions": [
    {
      "vendor": "AudioCodes",
      "model": "C470HD",
      "version": "1.19.552",
      "warn_info": "You are about to perform an Android operating system upgrade. The change is permanent
and cannot be reversed."
    }
  ],
  "app_versions": [
    "5.16.5.3920"
  ]
}
```

Status: 400 `HTTP Status Code: 400`
 Bad Request `Error Code: 30051037`

`AccountId is empty.`

Status: 404 `HTTP Status Code: 404`
 Not Found `Error Code: 30052027`

`ZdmGroup not found.`

Status: 429 `HTTP Status Code: 429`
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get device detail

- **Method:** `GET`
- **Path:** `/devices/{deviceId}`
- **Tags:** Devices

Retrieve a device's details.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`device:read:admin`, `device:write:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `HEAVY`

Responses

Status: 200 `HTTP Status Code: 200` `OK` Device detail returned successfully.

Content-Type: application/json

- **`app_version`**
 `string` — App version of Zoom Rooms.
- **`connected_to_zdm`**
 `boolean` — Whether the device is connected to ZDM (Zoom Device Management).
- **`device_id`**
 `string` — The device's unique identifier.
- **`device_name`**
 `string` — The name of the device.
- **`device_status`**
 `integer`, possible values: -1, 0, 1 — Filter devices by status. Device Status: `0` - offline. `1` -
 online. `-1` - unlink
- **`device_type`**

```

`integer`, possible values: `0, 1, 2, 3, 4, 5, 6` — Filter devices by device type. Device Type: \-1\ - All Zoom Room device(0,1,2,3,4,6). \0\ - Zoom Rooms Computer. \1\ - Zoom Rooms Controller. \2\ - Zoom Rooms Scheduling Display. \3\ - Zoom Rooms Control System. \4\ - Zoom Rooms Whiteboard. \5\ - Zoom Phone Appliance. \6\ - Zoom Rooms Computer (with Controller).

- **`enrolled\_in\_zdm`**

`boolean` — Whether the device is enrolled in ZDM (Zoom Device Management).

- **`last\_online`**

`string` — The time when the device was last online.

- **`mac\_address`**

`string` — The device's MAC address.

- **`model`**

`string` — The device's model.

- **`platform\_os`**

`string` — The device's platform.

- **`room\_id`**

`string` — The Zoom Room's ID.

- **`room\_name`**

`string` — The Zoom Room's name.

- **`sdk\_version`**

`string` — The SDK version.

- **`serial\_number`**

`string` — The device's serial number.

- **`tag`**

`string` — The tag's name.

- **`user\_email`**

`string` — The phone device's owner.

- **`vendor`**

`string` — The device's manufacturer.

**\*\*Example:\*\***

```
```json
{
  "device_id": "F1C6E9DF-429E-4FA1-85DA-AC95464F3D18",
  "device_name": "My device",
  "mac_address": "01-23-45-67-89-AB",
  "serial_number": "6NRN2A0",
  "vendor": "Poly",
  "model": "StudioX30",
  "platform_os": "Epos expandvision5 1.2.22315.04",
  "app_version": "5.13.0.5762",
  "tag": "personal rooms",
  "enrolled_in_zdm": true,
  "connected_to_zdm": true,
  "room_id": "72afdc13-a289-40c3-b358-50c8b8de",
  "room_name": "My Personal Meeting Room",
  "device_type": 0,
  "sdk_version": "2.0.11",
  "device_status": 0,
  "last_online": "2022-10-27T10:23:15Z",
  "user_email": "test-user@ya.us"
},
```,
```

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \400\ \<br> Bad Request \\*\\*Error Code:\\*\\* \30055008\ \<br>

No permission. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`30055012\` \<br> No found unified deviceId. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Delete device

```
- **Method:** `DELETE`
- **Path:** `/devices/{deviceId}`
- **Tags:** Devices
```

Delete a device from a Zoom account.

**Prerequisites:**

- Device must be enrolled in ZMD (Zoom Device Management)

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **device:write:admin**

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **HEAVY**

### #### Responses

##### Status: 204 \\*\\*HTTP Status Code:\\*\\* \`204\` \\*\\*No Content\\*\\* Device deleted successfully.

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`30055008\` \<br> no permission. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`30055012\` \<br> no found unified deviceId. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Change device

```
- **Method:** `PATCH`
- **Path:** `/devices/{deviceId}`
- **Tags:** Devices
```

Change device name.

**Prerequisites:**

- Device must be enrolled in ZMD (Zoom Device Management)

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **device:write:admin**

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **MEDIUM**

### #### Request Body

##### Content-Type: application/json

```
- **`device_name` (required)**
```

  `string` — The name of the device.

```
- **`device_type`**
```

  `integer`, possible values: `0, 1, 3` — Device Type: `0` - Zoom Rooms Computer. `1` - Zoom Rooms Controller. `2` - Zoom Rooms Scheduling Display.

```
- **`room_id`**
```

  `string` — id of the Zoom Room.

```
- **`tag`**
```

  `string` — The name of the tag.

**Example:**

```
```json
{
  "device_name": "My device",
  "tag": "personal rooms",

```



```
"room_id": "72afdc13-a289-40c3-b358-50c8b8de",
"device_type": 1
},
}
```

Responses

Status: 204 `HTTP Status Code: 204` `No Content` Request processed successfully.

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 30055001` `zoom room does not exist.` `Error Code: 30055002` `required param can not be empty or null.` `Error Code: 30055003` `device type does not support.` `Error Code: 30055011` `device is not enrolled.` `Error Code: 30055013` `device not support this app.` `Error Code: 30055014` `room not support this app.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 30055012` `Device does not exist: {deviceId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Assign a device to a group

```
- **Method:** `PATCH`
- **Path:** `/devices/{deviceId}/assign_group`
- **Tags:** Devices
```

Assign a device to a new group.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:write:admin`

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:write:group:admin`, `device:write:group:master`

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

Responses

Status: 204 Request processed successfully.

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 30052010` `Group does not exist.`

Status: 401 `HTTP Status Code: 401` `Unauthorized` No permission.

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 30055012` `Device does not exist.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Change device association

```
- **Method:** `PATCH`
- **Path:** `/devices/{deviceId}/assignment`
- **Tags:** Devices
```

Change a device's association from one Zoom Room to another. **Prerequisites** Device must be enrolled in ZDM (Zoom Device Management). **Note** Currently, only Poly TC10's may make Zoom Room assignments.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:write:admin`

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `device:update:zdm_device_assignment:admin`

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

Request Body

Content-Type: application/json

```
- **`app_type`**
```

`string`, possible values: `"ZR"`, `"ZRC"`, `"ZRP"`, `"ZRW"`, default: `"ZR"` — Specify one of these values for this field. `ZR` - Zoom Room computer. `ZRC` - Zoom Room controller. `ZRP` - Scheduling display. `ZRW` - Companion whiteboard.

```
- **`room_id`**
```

`string` — The Zoom Room ID of the device being associated to. The `room_id` is required. It can be \

\` or the specific room ID. If it is \`, it means release from the room. If the room ID is a specific value, assign that room to the device .

****Example:****

```
``json
{
  "room_id": "qMOLddnySIGGVycz8aX_JQ",
  "app_type": "ZR"
}
```

Responses

Status: 204 \`\`\`HTTP Status Code:\`\`\` 204\`\`\` No Content\`\`\` Request processed successfully.

Status: 400 \`\`\`HTTP Status Code:\`\`\` 400\`\`\` <br> Bad Request \`\`\`Error Code:\`\`\` 8500\`\`\`
 Device not enrolled in Zoom Device Management.
 \`\`\`Error Code:\`\`\` 8501\`\`\` <br> Device does not support this app. <br> \`\`\`Error Code:\`\`\` 8502\`\`\`
 Room does not support this app.

Status: 404 \`\`\`HTTP Status Code:\`\`\` 404\`\`\` <br> Not Found \`\`\`Error Code:\`\`\` 1012\`\`\`
 Room does not exist: {roomId}.
 \`\`\`Error Code:\`\`\` 8503\`\`\`
 Device does not exist: {deviceId}.

Status: 429 \`\`\`HTTP Status Code:\`\`\` 429\`\`\`
 Too Many Requests. For more information, see \[rate limits]\(<https://developers.zoom.us/docs/api/rest/rate-limits/>).

List H.323/SIP devices

- ****Method:**** `GET`
- ****Path:**** `/h323/devices`
- ****Tags:**** H323 Devices

A H.323 or SIP device can make a video call to a [Room Connector](<https://support.zoom.us/hc/en-us/articles/201363273-Getting-Started-With-H-323-SIP-Room-Connector>) to join a Zoom cloud meeting. A Room Connector can also call out to a H.323 or SIP device to join a Zoom cloud meeting. Use this API to list all H.323/SIP Devices on a Zoom account.

****[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):**** `h323:read:admin`

****[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):**** `h323\_device:read:list\_devices:admin`

****[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>):**** `MEDIUM`

Responses

Status: 200 \`\`\`HTTP Status Code:\`\`\` 200\`\`\` List of H.323/SIP devices returned. \`\`\`Error Code:\`\`\` 200\`\`\` No permission.

Content-Type: application/json

****All of:****

- ****`next\_page\_token`****

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- ****`page\_count`****

`integer` — The number of pages returned for the request made.

- ****`page\_number`****

`integer`, default: `1` — \`\`\`Deprecated.\`\`\` We will no longer support this field in a future release. Instead, use the `next\_page\_token` for pagination.

- ****`page\_size`****

`integer`, default: `30` — The number of records returned with a single API call.

- ****`total\_records`****

`integer` — The total number of all the records available across pages.

- ****`devices`****

`array` — List of H.323/SIP Device objects.

```

**Items:**

**All of:**

- **`id`**

  `string` — Device ID.

* **`encryption` (required)**

  `string`, possible values: `"auto", "yes", "no"` — Device encryption: `auto` - auto. `yes` - yes.
  `no` - no.

* **`ip` (required)**

  `string` — Device IP.

* **`name` (required)**

  `string` — Device name.

* **`protocol` (required)**

  `string`, possible values: `"H.323", "SIP"` — Device protocol: `H.323` - H.323. `SIP` - SIP.

**Example:**

```json
{
 "next_page_token": "w7587w4eiyfsudgf",
 "page_count": 1,
 "page_size": 30,
 "total_records": 20,
 "devices": [
 {
 "id": "abceHewahkrehwik",
 "encryption": "auto",
 "ip": "127.0.0.1",
 "name": "api_test_20190508",
 "protocol": "H.323"
 }
]
}
```

##### Status: 400 **HTTP Status Code:** 400 <br> Bad Request

##### Status: 401 **HTTP Status Code:** 401 <br> Unauthorized

##### Status: 403 **HTTP Status Code:** 403 <br> Forbidden

##### Status: 429 **HTTP Status Code:** 429 <br> Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Create a H.323/SIP device

- **Method:** `POST`
- **Path:** `/h323/devices`
- **Tags:** H323 Devices

A H.323 or SIP device can make a video call to a [Room Connector](https://support.zoom.us/hc/en-us/articles/201363273-Getting-Started-With-H-323-SIP-Room-Connector) to join a Zoom cloud meeting. A Room Connector can also call out to a H.323 or SIP device to join a Zoom cloud meeting. Use this API to add a H.323/SIP device to your Zoom account

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `h323:write:admin`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `h323_device:write:device:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

### Request Body

##### Content-Type: application/json

- **`encryption` (required)**

  `string`, possible values: `"auto", "yes", "no"` — Device encryption: `auto` - auto. `yes` - yes.
  `no` - no.

```

```

- **`ip` (required)**
  `string` — Device IP.
- **`name` (required)**
  `string` — Device name.
- **`protocol` (required)**
  `string`, possible values: `H.323`, `SIP` — Device protocol: `H.323` - H.323. `SIP` - SIP.
**Example:**
```json
{
 "encryption": "auto",
 "ip": "127.0.0.1",
 "name": "api_test_20190508",
 "protocol": "H.323"
}
```

#### Responses

##### Status: 201 **HTTP Status Code:** 201 **H.323/SIP device created.

##### Content-Type: application/json

**All of:**
- **`id`**
  `string` — Device ID.
- **`encryption` (required)**
  `string`, possible values: `auto`, `yes`, `no` — Device encryption: `auto` - auto. `yes` - yes.
  `no` - no.
- **`ip` (required)**
  `string` — Device IP.
- **`name` (required)**
  `string` — Device name.
- **`protocol` (required)**
  `string`, possible values: `H.323`, `SIP` — Device protocol: `H.323` - H.323. `SIP` - SIP.
**Example:**
```json
{
 "id": "abceHewahkrehwiK",
 "encryption": "auto",
 "ip": "127.0.0.1",
 "name": "api_test_20190508",
 "protocol": "H.323"
}
```

##### Status: 400 **HTTP Status Code:** 400 **Bad Request **Error Code:** 200 **No permission.

##### Status: 401 **HTTP Status Code:** 401 **Unauthorized

##### Status: 403 **HTTP Status Code:** 403 **Forbidden

##### Status: 404 **HTTP Status Code:** 404 **Not Found **Error Code:** 2020 **H.323 device's display name {displayName} is already in use.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Delete a H.323/SIP device

```

```
- **Method:** `DELETE`
- **Path:** `/h323/devices/{deviceId}`
- **Tags:** H323 Devices
```

A H.323 or SIP device can make a video call to a [Room Connector](https://support.zoom.us/hc/en-us/articles/201363273-Getting-Started-With-H-323-SIP-Room-Connector) to join a Zoom cloud meeting. A Room Connector can also call out to a H.323 or SIP device to join a Zoom cloud meeting. Use this API to delete a H.323/SIP device from your Zoom account.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `h323:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`h323\_device:delete:device:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

Responses

Status: 200 You do not have the permission to delete this device.

Status: 400 `HTTP Status Code: 400`
 Bad Request

Status: 401 `HTTP Status Code: 401`
 Unauthorized

Status: 403 `HTTP Status Code: 403`
 Forbidden

Status: 404 `HTTP Status Code: 404`
 Not Found

Status: 429 `HTTP Status Code: 429`
 Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

Update a H.323/SIP device

```
- **Method:** `PATCH`
- **Path:** `/h323/devices/{deviceId}`
- **Tags:** H323 Devices
```

Edit information for a H.323/SIP device from your Zoom account.

A H.323 or SIP device can make a video call to a [Room Connector](https://support.zoom.us/hc/en-us/articles/201363273-Getting-Started-With-H-323-SIP-Room-Connector) to join a Zoom cloud meeting. A Room Connector can also call out to a H.323 or SIP device to join a Zoom cloud meeting.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `h323:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`h323\_device:update:device:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

Request Body

Content-Type: application/json

- **`encryption` (required)**

 `string`, possible values: `"auto", "yes", "no"` — Device encryption: `auto` - auto. `yes` - yes. `no` - no.

- **`ip` (required)**

 `string` — Device IP.

- **`name` (required)**

 `string` — Device name.

- **`protocol` (required)**

 `string`, possible values: `"H.323", "SIP"` — Device protocol. `H.323` - H.323. `SIP` - SIP.

Example:

```
```json
{
 "encryption": "auto",
 "ip": "127.0.0.1",
 "name": "api_test_20190508",
 "protocol": "H.323"
}
```

### #### Responses

##### Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` H.323/SIP device updated.

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br>` Bad Request

##### Status: 401 `\*\*HTTP Status Code:\*\* \`401\`` `\<br>` Unauthorized

##### Status: 403 `\*\*HTTP Status Code:\*\* \`403\`` `\<br>` Forbidden

##### Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br>` Not Found `\*\*Error Code:\*\* \`2020\`` `\<br>` H.323 device's display name {displayName} is already in use. `\<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### ### Add a meeting app

```
- **Method:** `POST`
- **Path:** `/meetings/{meetingId}/open_apps`
- **Tags:** In-Meeting Apps
```

Add an auto-open app in a meeting. This endpoint lets a developer auto-open an app in a specific meeting. This is only for configuring an app to automatically open before a given session. This can't open the app while a meeting or webinar is in session.

#### **\*\*Prerequisites\*\*:**

- The meeting must not be a live meeting.
- The **\*\*Zoom Apps Quick Launch Button\*\*** setting enabled in the Zoom web portal.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`meeting:write`, `meeting:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`meeting:write:open\_app`, `meeting:write:open\_app:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

### #### Responses

##### Status: 201 `\*\*HTTP Status Code:\*\* \`201\`` App added.

##### Content-Type: application/json

```
- **`app_id`**
```

    `string` — The app's ID.

```
- **`id`**
```

    `integer`, format: `int64` — The `\[meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-)`: Unique identifier of the meeting in `\*\*long\*\*` format (represented as int64 data type in JSON), also known as the meeting number.

```
- **`start_time`**
```

    `string`, format: `date-time` — For scheduled meetings only. Meeting start date-time in UTC/GMT, such as `\`2020-03-31T12:02:00Z\``.

#### **\*\*Example:\*\***

```
``json
{
 "id": 92674392836,
 "start_time": "2022-03-25T07:29:29Z",
 "app_id": "fdgsfh2ey82fuh"
}
```

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br>` Bad Request `\*\*Error Code:\*\* \`300\`` `\<br>` Invalid meeting ID. `\<br>` `\*\*Error Code:\*\* \`3000\`` `\<br>` You can only add up to 3 apps. `\<br>` `\*\*Error Code:\*\* \`3000\`` `\<br>` Meeting {meetingId} has started. `\<br>` `\*\*Error Code:\*\* \`3000\`` `\<br>` Zoom Apps disabled. To use this feature, enable the 'Zoom Apps Quick Launch Button' setting in the 'Settings' page of the Zoom web portal. `\<br>`

##### Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br>` Not Found `\*\*Error Code:\*\* \`3001\`` `\<br>` Meeting does not exist: {meetingId} `\<br>`

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](/docs/api/rest/rate-limits/).

### ### Delete a meeting app

- **Method:** `DELETE`  
 - **Path:** `/meetings/{meetingId}/open_apps`  
 - **Tags:** In-Meeting Apps

Delete a meeting auto-open app.

#### \*\*Prerequisites:\*\*

- The meeting must not be a live meeting.
- The **Zoom Apps Quick Launch Button** setting enabled in the Zoom web portal.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write`, `meeting:write:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:delete:open_app`, `meeting:delete:open_app:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **LIGHT**

### #### Responses

##### Status: 204 `HTTP Status Code: 201` App deleted.

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 300` Invalid meeting ID. `Error Code: 3000` Meeting {meetingId} has started. `Error Code: 3000` Zoom Apps disabled. To use this feature, enable the **Zoom Apps Quick Launch Button** setting in the **Settings** page of the Zoom web portal.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001` Meeting does not exist: {meetingId}

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](/docs/api/rest/rate-limits/).

### ### Delete a live meeting message

- **Method:** `DELETE`  
 - **Path:** `/live_meetings/{meetingId}/chat/messages/{messageId}`  
 - **Tags:** In-Meeting Features

Delete a message in a live meeting, based on ID.

#### \*\*Prerequisites:\*\*

- Have Zoom enable the DLP for the in-meeting chat feature to use this API.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write`, `meeting:write:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:delete:live_meeting_chat_message`, `meeting:delete:live_meeting_chat_message:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **MEDIUM**

### #### Responses

##### Status: 204 `HTTP Status Code: 204` Meeting chat message deleted.

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 300` DLP is not enabled on this account.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001` Meeting does not exist: {meetingId}.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Update a live meeting message

- **Method:** `PATCH`  
 - **Path:** `/live_meetings/{meetingId}/chat/messages/{messageId}`  
 - **Tags:** In-Meeting Features

Update a message in a live meeting, based on ID. **Prerequisites:** Have Zoom enable the DLP for the in-

meeting chat feature to use this API.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:write`, `meeting:write:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:update:live\_meeting\_chat\_message`, `meeting:update:live\_meeting\_chat\_message:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **MEDIUM**

#### Request Body

Content-Type: application/json

- **message\_content** (required)

string — The content of the chat message.

**Example:**

```
``json
{
 "message_content": "This is a test message"
},
``
```

#### Responses

**Status: 204** HTTP Status Code: 204 Meeting chat message updated.

**Status: 400** HTTP Status Code: 400 Bad Request Error Code: 300 DLP is not enabled on this account.

**Status: 404** HTTP Status Code: 404 Not Found Error Code: 3001 Meeting does not exist: {meetingId}.

**Status: 429** HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](<https://developers.zoom.us/docs/api-rest/rate-limits/>).

#### In-meeting controls

- **Method:** PATCH  
- **Path:** /live\_meetings/{meetingId}/events  
- **Tags:** In-Meeting Features

[In-meeting](<https://support.zoom.us/hc/en-us/articles/360021921032-In-Meeting-Controls>) controls include starting, stopping, pausing, and resuming a recording; inviting participants; updating the waiting room with a custom message; and starting, stopping, or disabling the AI Companion.

**Note:** This API's recording control only works for cloud recordings, **not** for local recordings.

**Prerequisites:**

- The user calling this API must be the host or an alternative meeting host.
- The meeting must be a live meeting, except when inviting participants to the meeting through [call out (phone)]([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0062038](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0062038))/[call out (room system)]([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0065721](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065721)).
- The [Cloud recording](<https://support.zoom.us/hc/en-us/articles/360060231472-Enabling-cloud-recording>) control must be enabled.
- The [AI Companion]([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0057623](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057623)) control must be enabled.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:write`, `meeting:write:admin`, `meeting:master`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:update:in\_meeting\_controls`, `meeting:update:in\_meeting\_controls:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **MEDIUM**

#### Request Body

Content-Type: application/json

- **method**

string, possible values: "recording.start", "recording.stop", "recording.pause", "recording.resume", "participant.invite", "participant.invite.callout", "participant.invite.room\_system\_callout", "waiting\_room.update", "ai\_companion.start", "ai\_companion.stop", "ai\_companion.disable" — The method that you would like to control. `recording.start` - Start the recording. `recording.stop` - Stop the



recording. \\* \`recording.pause\` - Pause the recording. \\* \`recording.resume\` - Resume a paused recording. \\* \`participant.invite\` - Invite a participant to the meeting. \\* \`participant.invite.callout\` - Invite a participant to the meeting through \[call out (phone)]\ ([https://support.zoom.com/hc/en/article?id=zm\kb&sysparm\\_article=KB0062038](https://support.zoom.com/hc/en/article?id=zm\kb&sysparm_article=KB0062038)). \\* \`participant.invite.room\\_system\\_callout\` - Invite a participant to the meeting through \[call out (room system)]\ ([https://support.zoom.com/hc/en/article?id=zm\kb&sysparm\\_article=KB0065721](https://support.zoom.com/hc/en/article?id=zm\kb&sysparm_article=KB0065721)). \\* \`waiting\\_room.update\` - Update the waiting room with a custom message. \\* \`ai\\_companion.start\` - Start the AI Companion. \\* \`ai\\_companion.stop\` - Stop the AI Companion. \\* \`ai\\_companion.disable\` - Disable the AI Companion.

- **\`params\`**

\`object\` — The in-meeting parameters.

- **\`ai\\_companion\\_mode\`**

\`string\`, possible values: \`"questions", "summary", "all"\`, default: \`"all"\` — Which AI Companion mode to start or stop. Use this field if you pass the \`ai\\_companion.start\` or \`ai\\_companion.stop\` value for the \`method\` field. \\* \`questions\` — The AI Companion for answering questions. \\* \`summary\` — The AI Companion for generating meeting summaries. \\* \`all\` — Both modes. If this field is not provided, \`all\` is used by default.

- **\`call\\_type\`**

\`string\` — The type of call out. Use a value of \`h323\` or \`sip\`. Use this field if you pass the \`participant.invite.room\\_system\\_callout\` value for the \`method\` field.

- **\`contacts\`**

\`array\` — The user's email address or the user ID, up to a maximum of 10 contacts. The account must be a part of the meeting host's account.

**\`Items\`**

- **\`email\`**

\`string\` — The user's email address. Use this value if you do not have the user's ID. If you pass the \`id\` value, the API ignores this query parameter.

- **\`id\`**

\`string\` — The user's ID.

- **\`delete\\_meeting\\_assets\`**

\`boolean\`, default: \`false\` — Whether to delete all meeting assets - such as transcripts and summaries - when stopping the AI Companion. Use this field only if you pass the \`ai\\_companion.stop\` value for the \`method\` field \\*\`and\\*\` the \`ai\\_companion\\_mode\` field is set to \`all\`.

- **\`device\\_ip\`**

\`string\` — The user's device IP address or URI. Use this field if you pass the \`participant.invite.room\\_system\\_callout\` value for the \`method\` field.

- **\`h323\\_headers\`**

\`object\` — Enable customers to leverage services that require customization of the FROM header to identify the caller. Use this field if you pass the \`participant.invite.room\\_system\\_callout\` value for the \`method\` field and the \`h323\` value for the \`call\\_type\` field.

- **\`from\\_display\\_name\`**

\`string\` — Custom name that will be used within the h323 Header.

- **\`to\\_display\\_name\`**

\`string\` — Custom remote name that will be used within the meeting.

- **\`invite\\_options\`**

\`object\` — Information about the \`participant.invite.callout\` settings.

- **\`require\\_greeting\`**

\`boolean\`, default: \`true\` — Whether to require a greeting before being connected. Use this field if you pass the \`participant.invite.callout\` value for the \`method\` field.

- **\`require\\_pressing\\_one\`**

\`boolean\`, default: \`true\` — Whether to require pressing 1 before being connected. Use this field if

you pass the `\`participant.invite.callout\`` value for the `\`method\`` field.

- **`\`invitee_name\``**

`\`string\`` — The user's name to display in the meeting. Use this field if you pass the `\`participant.invite.callout\`` value for the `\`method\`` field.

- **`\`phone_number\``**

`\`string\`` — The user's phone number. Use this field if you pass the `\`participant.invite.callout\`` value for the `\`method\`` field. As a best practice, ensure this includes a country code and area code. If you are dialing a phone number that includes an extension, type a hyphen '-' after the phone number and enter the extension. For example, 6032331333-156 dials the extension 156.

- **`\`retain_meeting_transcript\``**

`\`boolean\`` — Whether to retain the meeting transcript when starting or stopping the AI Companion meeting summary. This field applies only when both of these conditions are met: `\`*\` The \`method\` is \`ai_companion.start\` or \`ai_companion.stop\`. \`*\` The \`ai_companion_mode\` is \`summary\` or \`all\`. \`*\`Note:\`*\` This field only takes effect when the account-level setting \`*\`Allow users to retain transcripts generated by meeting summary for use by other AI Companion services\`*\` is enabled. If this account-level setting is disabled, this field has no effect. If this field is not provided, the behavior follows the user-level setting \`*\`Start meeting transcript\`*\`.`

- **`\`sip_headers\``**

`\`object\`` — Enable customers to leverage services that require customization of the FROM header to identify the caller. Use this field if you pass the `\`participant.invite.room_system_callout\`` value for the `\`method\`` field and the `\`sip\`` value for the `\`call_type\`` field.

- **`\`additional_headers\``**

`\`array\`` — Ability to add 1 to 10 custom headers, each of which has a maximum length of 256 bytes to comply with SIP standards. Custom headers would leverage header names starting with 'X-' per SIP guidelines.

**`\`Items:\``**

- **`\`key\``**

`\`string\`` — Additional custom SIP header's key.

- **`\`value\``**

`\`string\`` — Additional custom SIP header's value.

- **`\`from_display_name\``**

`\`string\`` — Custom name that will be used within the SIP Header.

- **`\`from_uri\``**

`\`string\`` — Custom URI that will be used within the SIP Header. The URI must start with 'sip:' or 'sips:' as a valid URI based on parameters defined by the platform.

- **`\`to_display_name\``**

`\`string\`` — Custom remote name that will be used within the meeting.

- **`\`waiting_room_description\``**

`\`string\`` — The description shown in the waiting room. Use this field if you pass the `\`waiting_room.update\`` value for the `\`method\`` field.

- **`\`waiting_room_title\``**

`\`string\`` — The title displayed in the waiting room. Use this field if you pass the `\`waiting_room.update\`` value for the `\`method\`` field.

**`\`Example:\``**

```
``json
{
 "method": "recording.start",
 "params": {
 "contacts": [
 {
 "email": "jchill@example.com",
 "id": "30R7kT7bTIKSNUFEuH_Qlg"
 }
]
 },
}
```

```

 "invitee_name": "Jill Chill",
 "phone_number": "5550100",
 "invite_options": {
 "require_greeting": true,
 "require_pressing_one": true
 },
 "call_type": "h323",
 "device_ip": "10.100.111.237",
 "h323_headers": {
 "from_display_name": "display name",
 "to_display_name": "display name"
 },
 "sip_headers": {
 "from_display_name": "display name",
 "to_display_name": "display name",
 "from_uri": "sip:username@domain.company.org",
 "additional_headers": [
 {
 "key": "X-Header1",
 "value": "X-body1"
 }
]
 },
 "waiting_room_title": "waiting room title",
 "waiting_room_description": "waiting room description",
 "ai_companion_mode": "questions",
 "retain_meeting_transcript": true,
 "delete_meeting_assets": false
 }
}

```

#### #### Responses

##### Status: 202 `HTTP Status: 202` Request processed successfully.

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 300` Meeting ID does not exist. `Error Code: 301` Invalid meeting ID. `Error Code: 302` Meeting does not exist. `Error Code: 303` No permission. `Error Code: 304` This API is not available for this account. Please contact Zoom support. `Error Code: 305` Not enough cloud storage available. Either purchase additional storage or delete cloud recordings to free up storage.

##### Status: 403 `HTTP Status Code: 403` Forbidden `Error Code: 2314` Not allowed to manage the AI Companion. To use this feature, enable either the `Allow users to ask AI Companion questions about the meeting` setting or the `Meeting summary with AI Companion` setting in the `Settings` page of the Zoom web portal. `Error Code: 2314` Not allowed to manage the AI Companion summary. To use this feature, enable the `Meeting summary with AI Companion` setting in the `Settings` page of the Zoom web portal. `Error Code: 2314` Not allowed to manage the AI Companion questions. To use this feature, enable the `Allow users to ask AI Companion questions about the meeting` setting in the `Settings` page of the Zoom web portal. `Error Code: 2314` Not allowed to manage the AI Companion. To use this feature, enable either the `Allow users to ask AI Companion questions about the webinar` setting or the `Webinar summary with AI Companion` setting in the `Settings` page of the Zoom web portal. `Error Code: 2314` Not allowed to manage the AI Companion summary. To use this feature, enable the `Webinar summary with AI Companion` setting in the `Settings` page of the Zoom web portal. `Error Code: 2314` Not allowed to manage the AI Companion questions. To use this feature, enable the `Allow users to ask AI Companion questions about the webinar` setting in the `Settings` page of the Zoom web portal.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001` Meeting {meetingId} is not found or has expired.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(<https://developers.zoom.us/docs/api/rest/rate-limits/>).

#### ### Get a meeting's join token for local recording

```

- **Method:** GET
- **Path:** /meetings/{meetingId}/jointoken/local_recording
- **Tags:** In-Meeting Features

```

Get a meeting's join token to allow for local recording. The join token lets a recording bot implemented using Zoom Meeting SDK to connect to a Zoom meeting. The recording bot can then automatically start locally recording. This supports both regular and raw local recording types.

#### \*\*Prerequisites:\*\*

- The **Local recording** user setting enabled in the Zoom web portal.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):

```
`meeting_token:read:admin:local_recording`,`meeting_token:read:local_recording`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:local_recording_token`,`meeting:read:local_recording_token:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `HTTP Status Code:` `200` Meeting local recording token returned.

Content-Type: application/json

- **`expire_in`**

 `integer`, format: `int64`, possible values: `120` — The number of seconds the join token is valid for before it expires. This value always returns `120`.

- **`token`**

 `string` — The join token.

Example:

```json
{
  "expire_in": 120,
  "token": "2njt50mj"
}
```

Status: 400 `HTTP Status Code:` `400`
 Bad Request `Error Code:` `300`
 Invalid meeting ID.
 `Error Code:` `3000`
 Cannot access webinar information.
 `Error Code:` `124`
 This API only supports OAuth2 authorization.
 `Error Code:` `3000`
 Not allowed to start local recording. To use this feature, enable the `Local Recording` setting in the `Settings` page of the Zoom web portal.
 `Error Code:` `3161`
 Meeting hosting and scheduling capabilities are not allowed for your user account.

Status: 404 `HTTP Status Code:` `404`
 Not Found `Error Code:` `300`
 Meeting ID does not exist.
 `Error Code:` `3001`
 Meeting does not exist: {meetingId}.

Status: 429 `HTTP Status Code:` `429`
 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

Get meeting's token

- **Method:** `GET`
- **Path:** `/meetings/{meetingId}/token`
- **Tags:** In-Meeting Features

Get a meeting's [closed caption token (caption URL)](https://support.zoom.us/hc/en-us/articles/115002212983-Using-a-third-party-closed-captioning-service). This token lets you use a third-party service to stream text to their closed captioning software to the Zoom meeting.

Prerequisites:

- The **Closed captioning** setting enabled in the Zoom web portal.
- The **Allow use of caption API Token to integrate with third-party closed captioning services** setting enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read`,`meeting:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:token`,`meeting:read:token:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `HTTP Status Code:` `200` Meeting token returned.

Content-Type: application/json

- **`token`**

 `string` — The generated meeting token.

Example:
```

```
```json
{
  "token": "https://example.com/closedcaption?
id=200610693&ns=GZHkEA==&expire=86400&sparams=id%2Cns%2Cexpire&signature=nYtXJqRKCW"
}
```
```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid meeting ID.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.` `Error Code: 3000` `Cannot access webinar information.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 300` `Meeting ID does not exist.` `Error Code: 3001` `Meeting does not exist: {meetingId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](/docs/api/rest/rate-limits/)`.

### ### Perform batch registration

- **Method:** `POST`
- **Path:** `/meetings/{meetingId}/batch_registrants`
- **Tags:** `Invitation & Registration`

Register up to 30 registrants at once for a meeting that requires `[registration]` (<https://support.zoom.us/hc/en-us/articles/211579443-Registration-for-Meetings>).

#### **Prerequisites:**

- The meeting host must be a Licensed user.
- The meeting must require registration and should be of type `2`, i.e., they should be scheduled meetings. Instant meetings and Recurring meetings are not supported by this API.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write`, `meeting:write:admin`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write:batch_registrants`, `meeting:write:batch_registrants:admin`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `HEAVY`

### #### Request Body

##### Content-Type: `application/json`

- **`auto_approve`**

`boolean` — If a meeting was scheduled with approval `_type 1` (manual approval), but you would like to automatically approve the registrants that are added via this API, you can set the value of this field to `true`. You `cannot` use this field to change approval setting for a meeting that was originally scheduled with approval `_type 0` (automatic approval).

- **`registrants`**

`array`

**Items:**

- **`email` (required)**

`string`, format: `email` — Email address of the registrant.

- **`first_name` (required)**

`string` — First name of the registrant.

- **`last_name`**

`string` — Last name of the registrant.

- **`registrants_confirmation_email`**

`boolean` — Send confirmation Email to Registrants

**Example:**

```
```json
{
```

```

    "auto_approve": true,
    "registrants_confirmation_email": true,
    "registrants": [
      {
        "email": "jchill@example.com",
        "first_name": "Jill",
        "last_name": "Chill"
      }
    ]
  }
}

```

Responses

Status: 201 `HTTP Status Code: 200 OK` Registrants added.

Content-Type: application/json

- `registrants`

`array`

`Items:`

- `email`

`string` — Email address of the registrant.

- `join_url`

`string` — Unique URL using which registrant can join the meeting.

- `participant_pin_code`

`integer`, format: `int64` — The participant PIN code is used to authenticate audio participants before they join the meeting.

- `registrant_id`

`string` — Unique identifier of the registrant.

`Example:`

```

{
  "registrants": [
    {
      "email": "jchill@example.com",
      "join_url": "https://example.com/j/11111",
      "registrant_id": "9tboDiHUQAe0nbmudzWa5g",
      "participant_pin_code": 380303
    }
  ]
}

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3038` `Meeting is over, you can not register now. If you have any questions, please contact the Meeting host.` `Error Code: 303` `This API can only be used for scheduled meeting(meeting type: 2). Batch registration is not supported for other meeting types.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.` `Error Code: 3043` `Meeting has reached maximum attendee capacity.` `Error Code: 404` `Registration has not been enabled for this meeting: {meetingId}.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Meeting does not exist: {meetingId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

Get meeting invitation

- `Method:` `GET`

- `Path:` `/meetings/{meetingId}/invitation`

- `Tags:` Invitation & Registration

Retrieve the meeting invitation note for a specific meeting.

`Prerequisites:`

- Host user must have a Zoom Meetings Basic license or higher.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):
`meeting:read`, `meeting:read:admin`

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):
`meeting:read:invitation`, `meeting:read:invitation:admin`

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>):
`LIGHT`

Responses

Status: 200 **HTTP Status Code:** `200` Meeting invitation returned.

Content-Type: application/json

- **invitation**

string — Meeting invitation.

- **sip_links**

array — A list of SIP phone addresses.

Items:

string

Example:

```
```json
{
 "invitation": "Jill Chill is inviting you to a scheduled Zoom meeting.\n\nTopic: My Meeting\nTime: Mar 25, 2022 03:32 PM America, Los Angeles\n\nJoin Zoom Meeting\nhttps://zoom.us/j/55544443210?pwd=8pEkRweVXPV30b2KJYgFTRlDtl1gSn.1\n\nMeeting ID: 555 4444 3210\nPasscode: 123456\n\nOne tap mobile\n+5678901234,,55544443210#,,,,*123456# US (gg)\n\nDial by your location\n+1 15550100 US (gg)\n\nMeeting ID: 555 4444 3210\nPasscode: 123456\n\nFind your local number:\nhttps://zoom.us/u/ab12cdef34jh\n\nJoin by SIP\n5550100@zoomcrc.com\n\nJoin by H.323\n192.0.2.1 (US West)\n\nMeeting ID: 555 4444 3210\nPasscode: 123456\n\n",
 "sip_links": [
 "5550100@zoomcrc.com"
]
}
```

##### Status: 400 **HTTP Status Code:** `400`   
Bad Request **Error Code:** `3161`   
Meeting hosting and scheduling capabilities are not allowed for your user account.

##### Status: 404 **HTTP Status Code:** `404`   
Not Found **Error Code:** `3001`   
Meeting does not exist: {meetingId}.

##### Status: 429 **HTTP Status Code:** `429`   
Too Many Requests. For more information, see [\[rate limits\]](#)(/docs/api/rest/rate-limits/).

#### ### Create a meeting's invite links

- **Method:** `POST`  
- **Path:** `/meetings/{meetingId}/invite\_links`  
- **Tags:** Invitation & Registration

Create a batch of invitation links for a meeting.

**Prerequisites:**

- The `ttl` value, in seconds, defines the invite link's expiration time. It must be between `0` or no expiration and `7776000` or 90 days, and has a default value of `7200` or 2 hours.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:write:admin`, `meeting:write`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`meeting:write:invite\_links`, `meeting:write:invite\_links:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>):  
`LIGHT`

#### #### Request Body

##### Content-Type: application/json

- **attendees**

```

`array` — The attendees list.

Items:

- **`name` (required)**

 `string` — User display name.

- **`disable_audio`**

 `boolean`, default: `false` — Whether to disable participant audio when joining the meeting. If not provided or set to `false`, the participant audio will follow the meeting's default settings.

- **`disable_video`**

 `boolean`, default: `false` — Whether to disable participant video when joining the meeting. If not provided or set to `false`, the participant video will follow the meeting's default settings.

- **`ttl`**

 `integer`, format: `int64`, default: `7200` — The invite link's expiration time, in seconds. This value defaults to `7200`.

```

**Example:**

```

```json
{
  "attendees": [
    {
      "name": "Jill Chill",
      "disable_video": false,
      "disable_audio": false
    }
  ],
  "ttl": 1000
}
```

```

#### #### Responses

##### Status: 201 `HTTP Status Code: 201` Meeting invitation links created.

##### Content-Type: application/json

```

- **`attendees`**

 `array` — The attendee list.

 Items:

 - **`join_url`**

 `string` — The URL to join the meeting.

 - **`name`**

 `string` — The user's display name.

```

**Example:**

```

```json
{
  "attendees": [
    {
      "join_url": "https://example.com/j/11111",
      "name": "Jill Chill"
    }
  ]
}
```

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid meeting ID.` `Error Code: 3000` `Cannot access webinar information.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Meeting does not exist: {meetingId}`



##### Status: 429 `\**HTTP Status Code:\**`429`` Too Many Requests. For more information, see `\[rate limits]\(/docs/api/rest/rate-limits/)`.

### ### List meeting registrants

- **Method:** `GET``  
 - **Path:** `/meetings/{meetingId}/registrants``  
 - **Tags:** Invitation & Registration

List users that have registered for a meeting. A host or a user with admin permission can require `\[registration for a Zoom meeting](https://support.zoom.us/hc/en-us/articles/211579443-Registration-for-Meetings)`.

#### **Prerequisites:**

- Host user type must be **Pro** or higher plan.
- Registration must be enabled for the meeting.

**[Scopes]**`(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `meeting:read:admin`,`meeting:read``

**[Granular Scopes]**`(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `meeting:read:list_registrants`,`meeting:read:list_registrants:admin``

**[Rate Limit Label]**`(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits)`: **MEDIUM**

### ### Responses

##### Status: 200 `\**HTTP Status Code:\**`200`` Successfully listed meeting registrants.

##### Content-Type: application/json

**All of:**

**All of:**

- **next\_page\_token**

`string`` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **page\_count**

`integer`` — The number of pages returned for the request made.

- **page\_number**

`integer``, default: `1`` — `\**Deprecated.\**` We will no longer support this field in a future release. Instead, use the `next_page_token`` for pagination.

- **page\_size**

`integer``, default: `30`` — The number of records returned with a single API call.

- **total\_records**

`integer`` — The total number of all the records available across pages.

\* **registrants**

`array`` — List of registrant objects.

**Items:**

**All of:**

- **id**

`string`` — Registrant ID.

**All of:**

- **email** (required)

`string``, format: `email`` — The registrant's email address. See `\[Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules)` for return value details.

- **first\_name** (required)

```

 `string` — The registrant's first name.
- **`address`**
 `string` — The registrant's address.
- **`city`**
 `string` — The registrant's city.
- **`comments`**
 `string` — The registrant's questions and comments.
- **`country`**
 `string` — The registrant's two-letter \[country code]\(\/docs/api/rest/other-references/abbreviation-
lists/#countries).
- **`custom_questions`**
 `array` — Information about custom questions.
 Items:
- **`title`**
 `string` — The title of the custom question.
- **`value`**
 `string` — The custom question's response value. This has a limit of 128 characters.
- **`industry`**
 `string` — The registrant's industry.
- **`job_title`**
 `string` — The registrant's job title.
- **`last_name`**
 `string` — The registrant's last name.
- **`no_of_employees`**
 `string`, possible values: `""`, "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-
5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-
50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ *
\More than 10,000\
- **`org`**
 `string` — The registrant's organization.
- **`phone`**
 `string` — The registrant's phone number.
- **`purchasing_time_frame`**
 `string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No
timeframe" — The registrant's purchasing time frame. * \Within a month\ * \1-3 months\ * \4-6
months\ * \More than 6 months\ * \No timeframe\
- **`role_in_purchase_process`**
 `string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" —
The registrant's role in the purchase process. * \Decision Maker\ * \Evaluator/Recommender\ *
\Influencer\ * \Not involved\
- **`state`**
 `string` — The registrant's state or province.
- **`status`**
 `string`, possible values: `"approved", "denied", "pending"` — The registrant's status. * \approved\

```

- Registrant is approved. \\* \`denied\` - Registrant is denied. \\* \`pending\` - Registrant is waiting for approval.

- \\*\`zip\`\\*

\`string\` — The registrant's ZIP or postal code.

\\*\`create\_time\`\\*

\`string\`, format: \`date-time\` — The time when the registrant registered.

\\*\`join\_url\`\\*

\`string\`, format: \`string\` — The URL that an approved registrant can use to join the meeting or webinar.

\\*\`participant\_pin\_code\`\\*

\`integer\`, format: \`int64\` — The participant PIN code is used to authenticate audio participants before they join the meeting.

\\*\`status\`\\*

\`string\` — The status of the registrant's registration. \`approved\` - User has been successfully approved for the webinar. \`pending\` - The registration is still pending. \`denied\` - User has been denied from joining the webinar.

**Example:**

```json

```
{
  "next_page_token": "w7587w4eiyfsudgf",
  "page_count": 1,
  "page_size": 30,
  "total_records": 20,
  "registrants": [
    {
      "id": "9tboDiHUQAeOnbmudzWa5g",
      "address": "1800 Amphibious Blvd.",
      "city": "Mountain View",
      "comments": "Looking forward to the discussion.",
      "country": "US",
      "custom_questions": [
        {
          "title": "What do you hope to learn from this?",
          "value": "Look forward to learning how you come up with new recipes and what other services you offer."
        }
      ],
      "email": "jchill@example.com",
      "first_name": "Jill",
      "industry": "Food",
      "job_title": "Chef",
      "last_name": "Chill",
      "no_of_employees": "1-20",
      "org": "Cooking Org",
      "phone": "5550100",
      "purchasing_time_frame": "1-3 months",
      "role_in_purchase_process": "Influencer",
      "state": "CA",
      "status": "approved",
      "zip": "94045",
      "create_time": "2022-03-22T05:59:09Z",
      "join_url": "https://example.com/j/11111",
      "participant_pin_code": 380303
    }
  ]
}
```

Status: 400 *\`HTTP Status Code:\\*\` \`400\` \
 Bad Request *\`Error Code:\\*\` \`300\` \
 Cannot access webinar info. \
 *\`Error Code:\\*\` \`3161\` \
 Meeting hosting and scheduling capabilities are not allowed for your user account. \

Status: 404 *\`HTTP Status Code:\\*\` \`404\` \
 Not Found *\`Error Code:\\*\` \`3001\` \
 Meeting does not exist: {meetingId}. \

Status: 429 *\`HTTP Status Code:\\*\` \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(</docs/api/rest/rate-limits/>).

Add a meeting registrant

```
- **Method:** `POST`
- **Path:** `/meetings/{meetingId}/registrants`
- **Tags:** Invitation & Registration
```

Create and submit a user's registration to a meeting. See [Customizing webinar registration](https://support.zoom.us/hc/en-us/articles/202835649-Customizing-webinar-registration) for details on how to set the requirements for these fields. Note that there is a maximum limit of 4,999 registrants per meeting and users will see an error if the meeting's capacity is reached.

Prerequisites:

- The host must be a **Licensed** user type.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
 `meeting:write:admin`, `meeting:write`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
 `meeting:write:registrant`, `meeting:write:registrant:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

Request Body

Content-Type: application/json

All of:

- **`email` (required)****
 `string`, format: `email` — The registrant's email address.
- **`first\_name` (required)****
 `string` — The registrant's first name.
- **`address`****
 `string` — The registrant's address.
- **`city`****
 `string` — The registrant's city.
- **`comments`****
 `string` — The registrant's questions and comments.
- **`country`****
 `string` — The registrant's two-letter [country code](https://marketplace.zoom.us/docs/api-reference/other-references/abbreviation-lists#countries).
- **`custom\_questions`****
 `array` — Information about custom questions.
****Items:****
 - **`title`****
 `string` — The title of the custom question.
 - **`value`****
 `string` — The custom question's response value. This has a limit of 128 characters.
- **`industry`****
 `string` — The registrant's industry.
- **`job\_title`****
 `string` — The registrant's job title.
- **`last\_name`****
 `string` — The registrant's last name.

- **no_of_employees**

`string`, possible values: `""`, "1-20", "21-50", "51-100", "101-500", "500-1,000", "1,001-5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees: * *1-20* * *21-50* * *51-100* * *101-500* * *500-1,000* * *1,001-5,000* * *5,001-10,000* * *More than 10,000*

- **org**

`string` — The registrant's organization.

- **phone**

`string` — The registrant's phone number.

- **purchasing_time_frame**

`string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No timeframe" — The registrant's purchasing time frame: * *Within a month* * *1-3 months* * *4-6 months* * *More than 6 months* * *No timeframe*

- **role_in_purchase_process**

`string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" — The registrant's role in the purchase process: * *Decision Maker* * *Evaluator/Recommender* * *Influencer* * *Not involved*

- **state**

`string` — The registrant's state or province.

- **zip**

`string` — The registrant's ZIP or postal code.

* **language**

`string`, possible values: "en-US", "de-DE", "es-ES", "fr-FR", "jp-JP", "pt-PT", "ru-RU", "zh-CN", "zh-TW", "ko-KO", "it-IT", "vi-VN", "pl-PL", "Tr-TR" — The registrant's language preference for confirmation emails: * *en-US* \— English (US) * *de-DE* \— German (Germany) * *es-ES* \— Spanish (Spain) * *fr-FR* \— French (France) * *jp-JP* \— Japanese * *pt-PT* \— Portuguese (Portugal) * *ru-RU* \— Russian * *zh-CN* \— Chinese (PRC) * *zh-TW* \— Chinese (Taiwan) * *ko-KO* \— Korean * *it-IT* \— Italian (Italy) * *vi-VN* \— Vietnamese * *pl-PL* \— Polish * *Tr-TR* \— Turkish

- **auto_approve**

`boolean` — If a meeting was scheduled with the `approval\_type` field value of `1` (manual approval) but you want to automatically approve meeting registrants, set the value of this field to `true`. **Note:** You cannot use this field to change approval setting for a meeting originally scheduled with the `approval\_type` field value of `0` (automatic approval).

Example:

``json

```
{
  "first_name": "Jill",
  "last_name": "Chill",
  "email": "jchill@example.com",
  "address": "1800 Amphibious Blvd.",
  "city": "Mountain View",
  "state": "CA",
  "zip": "94045",
  "country": "US",
  "phone": "5550100",
  "comments": "Looking forward to the discussion.",
  "custom_questions": [
    {
      "title": "What do you hope to learn from this?",
      "value": "Look forward to learning how you come up with new recipes and what other services you offer."
    }
  ],
  "industry": "Food",
  "job_title": "Chef",
  "no_of_employees": "1-20",
  "org": "Cooking Org",
  "purchasing_time_frame": "1-3 months",
  "role_in_purchase_process": "Influencer",
  "language": "en-US",
  "auto_approve": true
}
```

```
}
\,\,
```

Responses

Status: 201 **HTTP Status Code:** \`201\` Meeting registration created.

Content-Type: application/json

- ****id****

\`integer\`, format: \`int64\` — The meeting ID.

- ****join_url****

\`string\` — The URL the registrant can use to join the meeting. The API will not return this field if the meeting was \[created\](/docs/api-reference/zoom-api/methods#operation/meetingCreate) with the \`approval\\_type\` field value of \`1\` (manual approval).

- ****occurrences****

\`array\` — Array of occurrence objects.

****Items:****

- ****duration****

\`integer\` — Duration.

- ****occurrence_id****

\`string\` — Occurrence ID: Unique Identifier that identifies an occurrence of a recurring webinar. \[Recurring webinars\](https://support.zoom.us/hc/en-us/articles/216354763-How-to-Schedule-A-Recurring-Webinar) can have a maximum of 50 occurrences.

- ****start_time****

\`string\`, format: \`date-time\` — Start time.

- ****status****

\`string\` — Occurrence status.

- ****participant_pin_code****

\`integer\`, format: \`int64\` — The participant PIN code is used to authenticate audio participants before they join the meeting.

- ****registrant_id****

\`string\` — The registrant's ID.

- ****start_time****

\`string\`, format: \`date-time\` — The meeting's start time.

- ****topic****

\`string\` — The meeting's topic.

****Example:****

```
```json
{
 "id": 85746065,
 "join_url": "https://example.com/j/11111",
 "registrant_id": "fdgsfh2ey82fuh",
 "start_time": "2021-07-13T21:44:51Z",
 "topic": "My Meeting",
 "occurrences": [
 {
 "duration": 60,
 "occurrence_id": "1648194360000",
 "start_time": "2022-03-25T07:46:00Z",
 "status": "available"
 }
],
 "participant_pin_code": 380303
}
\,\,
```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3043` `Meeting has reached maximum attendee capacity.` `Error Code: 3000` `Cannot access meeting info.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `Meeting does not exist: {meetingId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### ### List registration questions

- `Method: GET`
- `Path: /meetings/{meetingId}/registrants/questions`
- `Tags: Invitation & Registration`

List registration questions that will be displayed to users while `[registering for a meeting]` (<https://support.zoom.us/hc/en-us/articles/211579443-Registration-for-Meetings>).

#### `**Prerequisites**`:

- Host user type must be `**Pro**` or higher plan.
- Registration must be enabled for the meeting.

`**[Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:read`, `meeting:read:admin`

`**[Granular Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:read:list_registration_questions`, `meeting:read:list_registration_questions:admin`

`**[Rate Limit Label]` (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `** LIGHT`

### #### Responses

##### Status: 200 `HTTP Status Code: 200` Meeting Registrant Question object returned

##### Content-Type: `application/json`

#### `**All of:**`

- `custom_questions`

`array` — Array of custom questions for registrants.

`**Items:**`

- `answers`

`array` — Answer choices for the question. Can not be used for `short` question type as this type of question requires registrants to type out the answer.

`**Items:**`

`string`

- `required`

`boolean` — Whether or not the custom question is required to be answered by participants or not.

- `title`

`string` — Title of the custom question.

- `type`

`string`, possible values: `"short"`, `"single"` — Type of the question being asked.

- `questions`

`array` — Array of registrant questions.

`**Items:**`

- `field_name`

`string`, possible values: `"last_name"`, `"address"`, `"city"`, `"country"`, `"zip"`, `"state"`, `"phone"`, `"industry"`, `"org"`, `"job_title"`, `"purchasing_time_frame"`, `"role_in_purchase_process"`, `"no_of_employees"`, `"comments"` — Field name of the question.

- **required**

**boolean** — Whether or not the displayed fields are required to be filled out by registrants.

**Example:**

json

```
{
 "custom_questions": [
 {
 "answers": [
 "Good"
],
 "required": true,
 "title": "How are you?",
 "type": "short"
 }
],
 "questions": [
 {
 "field_name": "last_name",
 "required": true
 }
]
}
```

##### Status: 400 HTTP Status Code: 400 Bad Request Error Code: 3161  
Meeting hosting and scheduling capabilities are not allowed for your user account.

##### Status: 404 HTTP Status Code: 404 Not Found Error Code: 3001  
Meeting does not exist: {meetingId}.

##### Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

### Update registration questions

- **Method:** PATCH  
- **Path:** /meetings/{meetingId}/registrants/questions  
- **Tags:** Invitation & Registration

Update registration questions that will be displayed to users while [registering for a meeting](https://support.zoom.us/hc/en-us/articles/211579443-Registration-for-Meetings).

**Prerequisites:**

- Host user type must be **Pro** or higher plan.  
- Registration must be enabled for the meeting.

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
meeting:write, meeting:write:admin

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
meeting:update:registration\_question, meeting:update:registration\_question:admin

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

#### Request Body

##### Content-Type: application/json

**All of:**

- **custom\_questions**

**array** — Array of Registrant Custom Questions

**Items:**

- **answers**

**array** — Answer choices for the question. Can not be used for **short** question type as this type of question requires registrants to type out the answer.

**Items:**

**string**



```

- **`required`**

 `boolean` — Indicates whether or not the custom question is required to be answered by participants or not.

- **`title`**

 `string` — Title of the custom question.

- **`type`**

 `string`, possible values: `"short", "single"` — The type of question being asked.

- **`questions`**

 `array` — Array of registrant questions.

Items:

- **`field_name`**

 `string`, possible values: `"last_name", "address", "city", "country", "zip", "state", "phone", "industry", "org", "job_title", "purchasing_time_frame", "role_in_purchase_process", "no_of_employees", "comments"` — The question's field name.

- **`required`**

 `boolean` — Indicates whether or not the displayed fields are required to be filled out by registrants.

```

**\*\*Example:\*\***

```

```json
{
  "custom_questions": [
    {
      "answers": [
        "Good"
      ],
      "required": true,
      "title": "How are you?",
      "type": "short"
    }
  ],
  "questions": [
    {
      "field_name": "last_name",
      "required": true
    }
  ]
}
```

```

**#### Responses**

**##### Status: 204** `HTTP Status Code: 204` Meeting Registrant Questions Updated

**##### Status: 400** `HTTP Status Code: 400` `<br>` Bad Request `HTTP Error Code: 3161` `<br>` Meeting hosting and scheduling capabilities are not allowed for your user account. `<br>`

**##### Status: 404** `HTTP Status Code: 404` `<br>` Not Found `HTTP Error Code: 3001` `<br>` Meeting does not exist: {meetingId}. `<br>`

**##### Status: 429** `HTTP Status Code: 429` `<br>` Too Many Requests. For more information, see `[rate limits](/docs/api/rest/rate-limits/)`.

**### Update registrant's status**

```

- **Method:** `PUT`
- **Path:** /meetings/{meetingId}/registrants/status
- **Tags:** Invitation & Registration

```

Update a meeting registrant's status by either approving, cancelling or denying a registrant from joining the meeting.

**\*\*Prerequisites:\*\***

- Host user type must be **\*\*Pro\*\*** or higher plan.
- Registration must be enabled for the meeting.

This API has an additional rate limit of requests per registrant, per 24-hour period. [See the Rate Limits

page](/docs/api/rate-limits/) for more information.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `meeting:write:admin`, `meeting:write`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `meeting:update:registrant\_status`, `meeting:update:registrant\_status:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `MEDIUM`

#### #### Request Body

##### Content-Type: application/json

- **action** (required)

string, possible values: "approve", "cancel", "deny" — Registrant status. `approve` - Approve registrant. `cancel` - Cancel previously approved registrant's registration. `deny` - Deny registrant.

- **registrants**

array — List of registrants.

**Items:**

- **email**

string

- **id**

string

**Example:**

```
```json
{
  "action": "approve",
  "registrants": [
    {
      "email": "jchill@example.com",
      "id": "9tboDiHUQAe0nbmudzWa5g"
    }
  ]
}
```

Responses

Status: 204 **HTTP Status Code:** 204 Registrant status updated.

Status: 400 **HTTP Status Code:** 400
 Bad Request **Error Code:** 3000
 Cannot access webinar information.
 Error Code: 3161
 Meeting hosting and scheduling capabilities are not allowed for your user account.

Status: 404 **HTTP Status Code:** 404
 Not Found **Error Code:** 3001
 Meeting does not exist: {meetingId}.

Status: 429 **HTTP Status Code:** 429
 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

Get a meeting registrant

- **Method:** GET

- **Path:** /meetings/{meetingId}/registrants/{registrantId}

- **Tags:** Invitation & Registration

Retrieve details on a specific user who has registered for the meeting. A host or a user with administrative permissions can require [registration for Zoom meetings](https://support.zoom.us/hc/en-us/articles/211579443-Registration-for-Meetings).

Prerequisites:

- The account must have a Meeting plan

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `meeting:read:admin`, `meeting:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `meeting:read:registrant`, `meeting:read:registrant:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

Responses

Status: 200 Success.

Content-Type: application/json

All of:

- **id**

string

All of:

- **email** (required)

string, format: email — The registrant's email address. See [Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value details.

- **first_name** (required)

string — The registrant's first name.

- **address**

string — The registrant's address.

- **city**

string — The registrant's city.

- **comments**

string — The registrant's questions and comments.

- **country**

string — The registrant's two-letter [country code](https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

- **custom_questions**

array — Information about custom questions.

Items:

- **title**

string — The title of the custom question.

- **value**

string — The custom question's response value. This has a limit of 128 characters.

- **industry**

string — The registrant's industry.

- **job_title**

string — The registrant's job title.

- **last_name**

string — The registrant's last name.

- **no_of_employees**

string, possible values: "", "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ * \More than 10,000\

- **org**

string — The registrant's organization.

- **phone**

string — The registrant's phone number.

- **purchasing_time_frame**

string, possible values: "", "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No timeframe" — The registrant's purchasing time frame. * Within a month * 1-3 months * 4-6 months * More than 6 months * No timeframe

- **role_in_purchase_process**

string, possible values: "", "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" — The registrant's role in the purchase process. * Decision Maker * Evaluator/Recommender * Influencer * Not involved

- **state**

string — The registrant's state or province.

- **status**

string, possible values: "approved", "denied", "pending" — The registrant's status. * approved - Registrant is approved. * denied - Registrant is denied. * pending - Registrant is waiting for approval.

- **zip**

string — The registrant's ZIP or postal code.

* **create_time**

string, format: date-time — The registrant's registration date and time.

* **join_url**

string, format: url — The URL with which the approved registrant can join the meeting.

* **participant_pin_code**

integer, format: int64 — The participant PIN code is used to authenticate audio participants before they join the meeting.

* **status**

string, possible values: "approved", "pending", "denied" — The registrant's registration status. * approved - The registrant is approved to join the meeting. * pending - The registrant's registration is pending. * denied - The registrant was declined to join the meeting.

Example:

```
```json
```

```
{
 "id": "9tboDiHUQAeOnbmudzWa5g",
 "address": "1800 Amphibious Blvd.",
 "city": "Mountain View",
 "comments": "Looking forward to the discussion.",
 "country": "US",
 "custom_questions": [
 {
 "title": "What do you hope to learn from this?",
 "value": "Look forward to learning how you come up with new recipes and what other services you offer."
 }
],
 "email": "jchill@example.com",
 "first_name": "Jill",
 "industry": "Food",
 "job_title": "Chef",
 "last_name": "Chill",
 "no_of_employees": "1-20",
 "org": "Cooking Org",
 "phone": "5550100",
 "purchasing_time_frame": "1-3 months",
 "role_in_purchase_process": "Influencer",
 "state": "CA",
 "status": "approved",
 "zip": "94045",
 "create_time": "2022-03-22T05:58:44Z",
}
```

```
"join_url": "https://example.com/j/11111",
"participant_pin_code": 380303
},
```

```
Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`3000\` \

Cannot access webinar info. \
 Error Code: \`3161\` \
 Meeting hosting and scheduling
capabilities are not allowed for your user account. \

```

```
Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \

Meeting does not exist: {meetingId}. \

```

```
Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).
```

### ### Delete a meeting registrant

```
- **Method:** `DELETE`
- **Path:** `/meetings/{meetingId}/registrants/{registrantId}`
- **Tags:** Invitation & Registration
```

Delete a meeting registrant.

#### \*\*Prerequisites\*\*:

- Host user type must be Pro or higher plan.
- Registration must be enabled for the meeting.
- For recurring meetings:
  - The `registration\_type` must be 2 or 3 to require the `occurrence\_id` field.
  - If the `registration\_type` is 1, the `occurrence\_id` is not needed, as registrants can attend any occurrence.

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:write:admin`,`meeting:write`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:delete:registrant`,`meeting:delete:registrant:admin`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`
```

### #### Responses

```
Status: 204 **HTTP status code:** \`204\` OK
```

```
Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`200\` \
 Only
available for paid users: {userId}. \
 Error Code: \`300\` \
 The value that you entered for
the Registrant ID field is invalid. Enter a valid value and try again. \
 Error Code: \`300\` \

 Registration has not been enabled for this meeting: {meetingId}. \
 Error Code: \`3000\` \

 Cannot access webinar info. \
 Error Code: \`3161\` \
 Meeting hosting and scheduling
capabilities are not allowed for your user account. \

```

```
Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \

Meeting does not exist: {meetingId}. \

```

```
Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \
[rate limits](/docs/api/rest/rate-limits/).
```

### ### Get a meeting's join token for live streaming

```
- **Method:** `GET`
- **Path:** `/meetings/{meetingId}/jointoken/live_streaming`
- **Tags:** Live streaming
```

Get a meeting's join token to allow live streaming. The join token allows a recording bot implemented using Zoom meeting SDK to connect to a Zoom meeting "hosted by the issuer of the token", and can call the streaming method automatically. It supports both regular live streaming, and raw streaming.

#### \*\*Prerequisites\*\*:

- A Pro or higher plan for the meeting host.
- The **Allow livestreaming of meetings** user setting enabled in the Zoom web portal.

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting_token:read:admin:live_streaming`,`meeting_token:read:live_streaming`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:live_streaming_token`,`meeting:read:live_streaming_token:admin`
```

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** **Light**

#### Responses

**Status:** 200 **HTTP Status Code:** 200 Meeting live streaming token returned.

**Content-Type:** application/json

**expire\_in**

integer, format: int64, possible values: 120 — The number of seconds the join token is valid for before it expires. This value always returns 120.

**token**

string — The join token.

**Example:**

```
```json
{
  "expire_in": 120,
  "token": "2njt50mj"
}
```

Status: 400 **HTTP Status Code:** 400 **Error Code:** 300 Bad Request **Error Code:** 300 Invalid meeting ID. **Error Code:** 300 Cannot access webinar information. **Error Code:** 124 This API only supports OAuth2 authorization. **Error Code:** 300 Not allowed to start live streaming. To use this feature, enable the "Allow livestreaming of meetings" setting in the "Settings" page of the Zoom web portal. **Error Code:** 3161 Meeting hosting and scheduling capabilities are not allowed for your user account.

Status: 404 **HTTP Status Code:** 404 **Error Code:** 300 Not Found **Error Code:** 3001 Meeting ID does not exist: {meetingId}

Status: 429 **HTTP Status Code:** 429 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

Get livestream details

Method: GET
Path: /meetings/{meetingId}/livestream
Tags: Live streaming

Zoom allows users to [livestream a meeting](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service) to a custom platform. Get a meeting's livestream configuration details such as Stream URL, Stream Key and Page URL.

Prerequisites:

- Meeting host must be a licensed user with a Pro or higher plan.
- Live streaming details must have been [configured](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h_01589a6f-a40a-4e18-a448-cb746e52ebc5) for the meeting.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): meeting:read:admin, meeting:read

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): meeting:read:livestream, meeting:read:livestream:admin

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **Light**

Responses

Status: 200 **HTTP Status Code:** 200 **OK** Live Stream details returned.

Content-Type: application/json

page_url

string — Live streaming page URL. This is the URL using which anyone can view the livestream of the meeting.

resolution

```

`string` — The number of pixels in each dimension that the video camera can display.

- stream_key

  `string` — Stream Key.

- stream_url

  `string` — Stream URL.

Example:

```json
{
 "page_url": "https://example.com/livestream/123",
 "stream_key": "contact-ic@example.com",
 "stream_url": "https://example.com/livestream",
 "resolution": "720p"
}
```

##### Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300 Invalid meeting id. Error Code: 3161 Meeting hosting and scheduling capabilities are not allowed for your user account.

##### Status: 404 HTTP Status Code: 404 Not Found Error Code: 3001 Meeting does not exist: {meetingId}.

##### Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see \[rate limits\]\(/docs/api/rest/rate-limits/\).

### Update a livestream

- Method: PATCH
- Path: /meetings/{meetingId}/livestream
- Tags: Live streaming

Update a meeting's livestream information. Zoom allows users to \[livestream a meeting\]\(https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service\) to a custom platform.

Prerequisites:

- Meeting host must have a Pro license.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
meeting:write:admin, meeting:write

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
meeting:update:livestream, meeting:update:livestream:admin

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): LIGHT

#### Request Body

##### Content-Type: application/json

- page_url (required)

  `string`, format: uri — The live stream page URL.

- stream_key (required)

  `string` — Stream name and key.

- stream_url (required)

  `string` — Streaming URL.

- resolution

  `string` — The number of pixels in each dimension that the video camera can display, required when a user enables 1080p. Use a value of 720p or 1080p

```

Example:

```

```json
{
 "page_url": "https://example.com/livestream/123",
 "stream_key": "contact-it@example.com",

```

```
"stream_url": "https://example.com/livestream",
"resolution": "720p"
}
,
```

#### #### Responses

```
Status: 204 **HTTP Status Code:** \`204\` Meeting livestream updated.
```

```
Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`3000\` \

Cannot access webinar info. \
 Error Code: \`3161\` \
 Meeting hosting and scheduling
capabilities are not allowed for your user account. \

```

```
Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \

Meeting does not exist: {meetingId}. \

```

```
Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).
```

#### ### Update livestream status

```
- **Method:** \`PATCH\`
- **Path:** \`/meetings/{meetingId}/livestream/status\`
- **Tags:** Live streaming
```

Zoom allows users to [livestream a meeting](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service) to a custom platform. Update the status of a meeting's livestream.

#### \*\*Prerequisites:\*\*

- Meeting host must have a Pro license.

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
\`meeting:write:admin\`, \`meeting:write\`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
\`meeting:update:livestream_status\`, \`meeting:update:livestream_status:admin\`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): \`LIGHT\`
```

#### #### Request Body

```
Content-Type: application/json
```

```
- **\`action\`**
```

\`string\`, possible values: \`"start", "stop", "mode"\` — The meeting's livestream status. \\*\`start\` - Start a livestream. \\*\`stop\` - Stop an ongoing livestream. \\*\`mode\` - Control a livestream view at runtime.

```
- **\`settings\`**
```

\`object\` — The meeting's livestreaming settings.

```
- **\`active_speaker_name\`**
```

\`boolean\` — Whether to display the name of the active speaker during a meeting's livestream. Use this field if you pass the \`start\` value for the \`action\` field.

```
- **\`close_caption\`**
```

\`string\`, possible values: \`"burnt-in", "embedded", "off"\`, default: \`"burnt-in"\` — The livestream's closed caption type for this session. Use this field if you pass the \`start\` or \`mode\` value for the \`action\` field. \\*\`burnt-in\` - Burnt in captions. \\*\`embedded\` - Embedded captions. \\*\`off\` - Turn off captions.

```
- **\`display_name\`**
```

\`string\` — The display name of the meeting's livestream. Use this field if you pass the \`start\` value for the \`action\` field.

```
- **\`layout\`**
```

\`string\`, possible values: \`"follow\_host", "gallery\_view", "speaker\_view"\`, default: \`"follow\_host"\` — The layout of the meeting's livestream. Use this field if you pass the \`start\` or \`mode\` value for the \`action\` field. \\*\`follow\_host\` - Follow host view. \\*\`gallery\_view\` - Gallery view. \\*\`speaker\_view\` - Speaker view.

#### \*\*Example:\*\*



```
``json
{
 "action": "start",
 "settings": {
 "active_speaker_name": true,
 "display_name": "Jill Chill",
 "layout": "follow_host",
 "close_caption": "burnt-in"
 }
}
},

```

#### #### Responses

##### Status: 204 `HTTP Status Code: 204` Meeting livestream updated.

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 3000` Cannot access webinar info. `Error Code: 3161` Your user account is not allowed meeting hosting and scheduling capabilities. `Error Code: 4400` End-to-end encrypted meetings currently do not support the livestreaming feature. `Error Code: 300` Invalid meeting ID. `Error Code: 4927` Meeting {meetingId} has not started.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001` Meeting does not exist: {meetingId}.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

#### ### Update participant Real-Time Media Streams (RTMS) app status

```
- **Method:** PATCH
- **Path:** /live_meetings/{meetingId}/rtms_app/status
- **Tags:** Meetings
```

Update the Real-Time Media Streams (RTMS) status for a specific participant in an ongoing meeting. Zoom lets individuals control their own RTMS during a meeting.

##### \*\*Prerequisites:\*\*

- The meeting must be in progress.
- Contact [Developer Support](https://developers.zoom.us/support/) to enable RTMS features.
- The `Allow apps to access meeting content` setting enabled in the Zoom web portal.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `meeting:write:admin`, `meeting:write`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `meeting:update:participant_rtms_app_status`, `meeting:update:participant_rtms_app_status:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `MEDIUM`

#### #### Request Body

##### Content-Type: application/json

```
- **`action`**
```

`string`, possible values: `"start"`, `"stop"`, `"pause"`, `"resume"` — The participant's RTMS app status. `"start"` - Start an RTMS app. `"stop"` - Stop an ongoing RTMS app. `"pause"` - Pause an ongoing RTMS app. `"resume"` - Resume a paused RTMS app.

```
- **`settings`**
```

`object` — The participant's RTMS app settings.

```
- **`client_id` (required)**
```

`string` — The unique identifier of the authorized app, configured in the Account Settings under `Allow apps to access meeting content`. This app must have host approval to access in-meeting content. Use this field if you pass the `"start"`, `"stop"`, `"pause"` or `"resume"` value for the `"action"` field.

```
- **`participant_user_id`**
```

`string` — The participant's user ID. This field is optional. If not provided, the user ID will be automatically obtained from the authentication token. This value matches the `"id"` field in the `GET /api/users/{tag}/users/{userId}` API response. Use this field if you pass the `"start"`, `"stop"`, `"pause"` or `"resume"` value for the `"action"` field.

**\*\*Example:\*\***

```

```json
{
  "action": "start",
  "settings": {
    "participant_user_id": "30R7kT7bTIKSNUFEuH_Qlg",
    "client_id": "a-Zu0X_FVBjUycmEi9ms5hg"
  }
}
```

```

#### #### Responses

##### Status: 204 `HTTP Status Code: 204` Participant's RTMS app status updated.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid meeting ID.` `Error Code: 3000` `Meeting {meetingId} has not started.` `Error Code: 2310` `Failed to perform RTMS app operation.` `Error Code: 13277` `Unable to '{action}' the RTMS app for user '{participant_user_id}' because it has not been started.` `Error Code: 2312` `User does not exist: {participant_user_id}.`

##### Status: 403 `HTTP Status Code: 403` `Forbidden` `Error Code: 2308` `User '{participant_user_id}' is not allowed to start the RTMS app. Only the meeting host or an alternative host can perform this action.` `Error Code: 2309` `User '{participant_user_id}' is not allowed to start the RTMS app. Only the webinar host, alternative host, or panelist can perform this action.` `Error Code: 13273` `The current meeting does not support the RTMS app feature.` `Error Code: 13267` `RTMS app disabled. To use this feature, enable the 'Share realtime meeting content with apps' setting in the 'Settings' page of the Zoom web portal.` `Error Code: 13262` `The app '{client_id}' is not authorized to access meeting content. Please add it in the 'Allow apps to access meeting content' setting in the 'Settings' page of the Zoom web portal.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Meeting does not exist: {meetingId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see [\[rate limits\]\(/docs/api/rate-limits/\)](#).

#### ### Get a meeting

```

- Method: GET
- Path: /meetings/{meetingId}
- Tags: Meetings

```

Retrieve the given meeting's details.

#### **Prerequisites**

- Host user must have a Zoom Meetings Basic license or higher.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:read`, `meeting:read:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:read:meeting`, `meeting:read:meeting:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

#### #### Responses

##### Status: 200 `HTTP Status Code: 200` Meeting object returned.

##### Content-Type: application/json

```

- agenda
 `string` — The meeting description.
- assistant_id
 `string` — The ID of the user who scheduled this meeting on behalf of the host.
- chat_join_url
 `string` — The URL to join the chat.
- created_at
 `string`, format: `date-time` — The creation time.

```

- **creation\_source**

`string`, possible values: `"other"`, `"open_api"`, `"web_portal"` — The platform used when creating the meeting. `"other"` - Created through another platform. `"open_api"` - Created through Open API. `"web_portal"` - Created through the web portal.

- **duration**

`integer` — The meeting duration.

- **dynamic\_host\_key**

`string` — The meeting dynamic host key.

- **encrypted\_password**

`string` — Encrypted passcode for third party endpoints (H323/SIP).

- **h323\_password**

`string` — H.323/SIP room system passcode.

- **host\_email**

`string`, format: `email` — The meeting host's email address.

- **host\_id**

`string` — The ID of the user who is set as the meeting host.

- **id**

`integer`, format: `int64` — `[Meeting ID]`(<https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID->): Unique identifier of the meeting in `"long"` format, represented as `int64` data type in JSON, also known as the meeting number.

- **join\_url**

`string` — The URL for participants to join the meeting. This URL should only be shared with users invited to the meeting.

- **occurrences**

`array` — Array of occurrence objects.

**Items:**

- **duration**

`integer` — Duration.

- **occurrence\_id**

`string` — Occurrence ID. The unique identifier for an occurrence of a recurring meeting. `[Recurring meetings]`(<https://support.zoom.us/hc/en-us/articles/214973206-Scheduling-Recurring-Meetings>) can have a maximum of 50 occurrences.

- **start\_time**

`string`, format: `date-time` — Start time.

- **status**

`string`, possible values: `"available"`, `"deleted"` — Occurrence status. `"available"` - Available occurrence. `"deleted"` - Deleted occurrence.

- **password**

`string` — Meeting passcode.

- **pmi**

`string` — `[Personal meeting ID (PMI)]`([/docs/api/rest/using-zoom-apis/#understanding-personal-meeting-id-pmi](https://support.zoom.us/hc/en-us/articles/360020187492-Zoom-for-GSuite-add-on)). Only used for scheduled meetings and recurring meetings with no fixed time.

- **pre\_schedule**

`boolean`, default: `false` — Whether the prescheduled meeting was created via the `[GSuite app]`(<https://support.zoom.us/hc/en-us/articles/360020187492-Zoom-for-GSuite-add-on>). This `"only"` supports the meeting `type` value of `2` (scheduled meetings) and `3` (recurring meetings with no fixed time).

\\* \true\ - A GSuite prescheduled meeting. \\* \false\ - A regular meeting.

- \*\*\pstn\_password\\*\*

\string\ — Password for participants to join the meeting via \[PSTN]\(https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference).

- \*\*\recurrence\\*\*

\object\ — Recurrence object. Use this object only for a meeting with type \8\, a recurring meeting with a fixed time.

- \*\*\type\ (required)\*\*

\integer\, possible values: \1, 2, 3\ — Recurring meeting types. \1\ - Daily. \2\ - Weekly. \3\ - Monthly.

- \*\*\end\_date\_time\\*\*

\string\, format: \date-time\ — Select the final date when the meeting will recur before it is canceled. Should be in UTC time, such as 2017-11-25T12:00:00Z. (Cannot be used with \end\_times\.)

- \*\*\end\_times\\*\*

\integer\, default: \1\ — Select how many times the meeting should recur before it is canceled. If \end\_times\ is set to 0, it means there is no end time. The maximum number of recurrences is 60. Cannot be used with \end\_date\_time\.

- \*\*\monthly\_day\\*\*

\integer\, default: \1\ — Use this field only if you're scheduling a recurring meeting of type \3\ to state the day in a month when the meeting should recur. The value range is from 1 to 31. For example, for a meeting to recur on 23rd of each month, provide \23\ as this field's value and \1\ as the \repeat\_interval\ field's value. Instead, to have the meeting to recur every three months on 23rd of the month, change the \repeat\_interval\ field's value to \3\.

- \*\*\monthly\_week\\*\*

\integer\, possible values: \-1, 1, 2, 3, 4\ — Use this field only if you're scheduling a recurring meeting of type \3\ to state the week of the month when the meeting should recur. If you use this field, \\*you must also use the \monthly\_week\_day\ field to state the day of the week when the meeting should recur.\\*\ \-1\ - Last week of the month. \1\ - First week of the month. \2\ - Second week of the month. \3\ - Third week of the month. \4\ - Fourth week of the month.

- \*\*\monthly\_week\_day\\*\*

\integer\, possible values: \1, 2, 3, 4, 5, 6, 7\ — Use this field \\*only if you're scheduling a recurring meeting of type \\* \3\ to state a specific day in a week when the monthly meeting should recur. To use this field, you must also use the \monthly\_week\ field. \1\ - Sunday. \2\ - Monday. \3\ - Tuesday. \4\ - Wednesday. \5\ - Thursday. \6\ - Friday. \7\ - Saturday.

- \*\*\repeat\_interval\\*\*

\integer\ — Define the interval when the meeting should recur. For instance, to schedule a meeting that recurs every two months, you must set this field's value as \2\ and the \type\ parameter's value as \3\. For a daily meeting, the maximum interval you can set is \99\ days. For a weekly meeting the maximum interval that you can set is of \50\ weeks. For a monthly meeting, there is a maximum of \10\ months.

- \*\*\weekly\_days\\*\*

\string\, possible values: \1, 2, 3, 4, 5, 6, 7\, default: \1\ — This field is required if you're scheduling a recurring meeting of type \2\ to state which days of the week the meeting should repeat. The value for this field could be a number between \1\ to \7\ in string format. For instance, if the meeting should recur on Sunday, provide \1\ as this field's value. \\*\Note\\* To have the meeting occur on multiple days of a week, provide comma separated values for this field. For instance, if the meeting should recur on Sundays and Tuesdays provide \1,3\ as this field's value. \1\ - Sunday. \2\ - Monday. \3\ - Tuesday. \4\ - Wednesday. \5\ - Thursday. \6\ - Friday. \7\ - Saturday.

- \*\*\registration\_url\\*\*

\string\ — The URL that registrants can use to register for a meeting. This field is only returned for meetings that have enabled registration.

- \*\*\settings\\*\*

\object\ — Meeting settings.

- \*\*\additional\_data\_center\_regions\\*\*

``array`` — Add additional meeting `\[data center regions]\(https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars)`. Provide this value as an array of `\[country codes]\(/docs/api/references/abbreviations/#countries)` for the countries available as data center regions in the `\[Account Profile\*\*]\(https://zoom.us/account/setting)` interface but have been opted out of in the `\[user settings]\(https://zoom.us/profile)`. For example, the data center regions selected in your `\[Account Profile\*\*]\(https://zoom.us/account)` are `\`Europe\``, `\`Hong Kong SAR\``, `\`Australia\``, `\`India\``, `\`Japan\``, `\`China\``, `\`United States\``, and `\`Canada\``. However, in the `\[My Profile\*\*]\(https://zoom.us/profile)` settings, you did `\*\*not\*\*` select `\`India\`` and `\`Japan\`` for meeting and webinar traffic routing. To include `\`India\`` and `\`Japan\`` as additional data centers, use the `\[IN, TY]\`` value for this field.

`**Items:**`

``string``

- `**`allow_host_control_participant_mute_state`**`

``boolean`` — Whether to allow the host and co-hosts to fully control the mute state of participants. This option cannot be used together with `\`request_permission_to_unmute_participants\``, only one of the two can be enabled at a time.

- `**`allow_multiple_devices`**`

``boolean`` — Allow attendees to join the meeting from multiple devices. This setting only works for meetings that require `\[registration]\(https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-registration-for-a-meeting)`.

- `**`alternative_host_manage_cloud_recording`**`

``boolean`` — Whether to allow an alternative host to manage meeting cloud recordings.

- `**`alternative_host_manage_meeting_summary`**`

``boolean`` — Whether to allow an alternative host to manage meeting summaries.

- `**`alternative_host_update_polls`**`

``boolean`` — Whether the `\*\*Allow alternative hosts to add or edit polls\*\*` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `**`alternative_hosts`**`

``string`` — A semicolon-separated list of the meeting's alternative hosts' email addresses or IDs.

- `**`alternative_hosts_email_notification`**`

``boolean``, default: ``true`` — Flag to determine whether to send email notifications to alternative hosts, default value is true.

- `**`approval_type`**`

``integer``, possible values: ``0``, ``1``, ``2``, default: ``2`` — Enable registration and set approval for the registration. Note that this feature requires the host to be of `\*\*Licensed\*\*` user type. `\*\*Registration` cannot be enabled for a basic user. `\*\`0\`` - Automatically approve. `\`1\`` - Manually approve. `\`2\`` - No registration required.

- `**`approved_or_denied_countries_or_regions`**`

``object`` — Approve or block users from specific regions/countries from joining this meeting.

- `**`approved_list`**`

``array`` — List of countries/regions from where participants can join this meeting.

`**Items:**`

``string``

- `**`denied_list`**`

``array`` — List of countries or regions from where participants can not join this meeting.

`**Items:**`

``string``

- `**`enable`**`

``boolean`` — `\`true\`` - Setting enabled to either allow users or block users from specific regions to join your meetings. `\`false\`` - Setting disabled.

### - **method**

`string`, possible values: `"approve"`, `"deny"` — Specify whether to allow users from specific regions to join this meeting; or block users from specific regions from joining this meeting. `"approve"`: Allow users from specific regions/countries to join this meeting. If this setting is selected, the approved regions/countries must be included in the `approved_list`. `"deny"`: Block users from specific regions/countries from joining this meeting. If this setting is selected, the approved regions/countries must be included in the `denied_list`.

### - **audio**

`string`, possible values: `"both"`, `"telephony"`, `"voip"`, `"thirdParty"`, default: `"both"` — Determine how participants can join the audio portion of the meeting. `"both"` - Both Telephony and VoIP. `"telephony"` - Telephony only. `"voip"` - VoIP only. `"thirdParty"` - Third party audio conference.

### - **audio\_conference\_info**

`string` — Third party audio conference information.

### - **authentication\_domains**

`string` — If user has configured `[Sign Into Zoom with Specified Domains]` ([https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f)) option, this will list the domains that are authenticated.

### - **authentication\_exception**

`array` — The participants added here will receive unique meeting invite links and bypass authentication.

#### **Items:**

### - **email**

`string`, format: `email` — The participant's email address.

### - **join\_url**

`string` — URL for participants to join the meeting

### - **name**

`string` — The participant's name.

### - **authentication\_name**

`string` — Authentication name set in the `[authentication profile]` ([https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f)).

### - **authentication\_option**

`string` — Meeting authentication option ID.

### - **auto\_add\_recording\_to\_video\_management**

`object` — Automatically add meeting recordings to a video channel in video management. To enable this feature for your account, please `[contact Zoom Support]` (<https://support.zoom.us/hc/en-us>).

### - **enable` (required)**

`boolean`, default: `false` — Whether to automatically add the meeting recording to video management.

### - **channels**

`array` — List of video management channels where the meeting recording will be added.

#### **Items:**

### - **channel\_id` (required)**

`string` — The unique ID of a video management channel.

### - **name**

`string` — The name of the video management channel.

### - **auto\_recording**

`string`, possible values: `"local", "cloud", "none"`, default: `"none"` — Automatic recording.  
 `local` - Record on local. `cloud` - Record on cloud. `none` - Disabled.

- **auto\_start\_ai\_companion\_questions**

`boolean`, default: `false` — Whether to automatically start AI Companion questions.

- **auto\_start\_meeting\_summary**

`boolean`, default: `false` — Whether to automatically start a meeting summary.

- **breakout\_room**

`object` — Setting to `[pre-assign breakout rooms]` ([https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h\\_36f71353-4190-48a2-b999-ca129861c1f4](https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4)).

- **enable**

`boolean` — Set this field's value to `true` if you would like to enable the `[breakout room pre-assign]` ([https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h\\_36f71353-4190-48a2-b999-ca129861c1f4](https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4)) option.

- **rooms**

`array` — Create room or rooms.

**Items:**

- **name**

`string` — The breakout room's name.

- **participants**

`array` — Email addresses of the participants who are to be assigned to the breakout room.

**Items:**

`string`

- **calendar\_type**

`integer`, possible values: `1, 2` — Indicates the type of calendar integration used to schedule the meeting. `1` - `[Zoom Outlook add-in]` (<https://support.zoom.us/hc/en-us/articles/360031592971-Getting-started-with-Outlook-plugin-and-add-in>) `2` - `[Zoom for Google Workspace add-on]` (<https://support.zoom.us/hc/en-us/articles/360020187492-Using-the-Zoom-for-Google-Workspace-add-on>) Works with the `private_meeting` field to determine whether to share details of meetings or not.

- **close\_registration**

`boolean`, default: `false` — Close registration after event date.

- **cn\_meeting**

`boolean`, default: `false` — Host meeting in China.

- **contact\_email**

`string` — Contact email for registration.

- **contact\_name**

`string` — Contact name for registration.

- **continuous\_meeting\_chat**

`object` — Information about the `Enable continuous meeting chat` feature. This setting only applies to scheduled and recurring meetings, types `2`, `3`, or `8`. It is `not supported` for type `1` instant meetings or type `10` screen share only meetings.

- **auto\_add\_invited\_external\_users**

`boolean` — Whether to enable the `Automatically add invited external users` setting.

- **auto\_add\_meeting\_participants**

`boolean` — Whether to enable the `Automatically add meeting participants` setting.

- **channel\_id**

```

 `string` — The channel's ID.
- **`enable`**

 `boolean` — Whether to enable the `Enable continuous meeting chat` setting.
- **`custom_keys`**

 `array` — Custom keys and values assigned to the meeting.
 Items:
 - **`key`**

 `string` — Custom key associated with the user.
 - **`value`**

 `string` — Value of the custom key associated with the user.
- **`device_testing`**

 `boolean`, default: `false` — Enable the device testing.
- **`disable_participant_video`**

 `boolean`, default: `false` — Whether to disable the participant video during meeting. To enable this feature for your account, please [contact Zoom Support](https://support.zoom.us/hc/en-us).
- **`email_in_attendee_report`**

 `boolean` — Whether to include authenticated guest's email addresses in meetings' attendee reports.
- **`email_notification`**

 `boolean`, default: `true` — Whether to send email notifications to [alternative hosts](https://support.zoom.us/hc/en-us/articles/208220166) and [users with scheduling privileges](https://support.zoom.us/hc/en-us/articles/201362803-Scheduling-privilege). This value defaults to `true`.
- **`encryption_type`**

 `string`, possible values: `enhanced_encryption`, `e2ee` — Choose between enhanced encryption and [end-to-end encryption](https://support.zoom.us/hc/en-us/articles/360048660871) when starting or a meeting. When using end-to-end encryption, several features (e.g. cloud recording, phone/SIP/H.323 dial-in) will be `automatically disabled`. `enhanced_encryption` - Enhanced encryption. Encryption is stored in the cloud if you enable this option. `e2ee` - [End-to-end encryption](https://support.zoom.us/hc/en-us/articles/360048660871). The encryption key is stored in your local device and can not be obtained by anyone else. Enabling this setting also `disables` the join before host, cloud recording, streaming, live transcription, breakout rooms, polling, 1:1 private chat, and meeting reactions features.
- **`enforce_login`**

 `boolean` — Only signed in users can join this meeting. `This field is deprecated and will not be supported in the future.` As an alternative, use the `meeting_authentication`, `authentication_option`, and `authentication_domains` fields to understand the [authentication configurations](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the meeting.
- **`enforce_login_domains`**

 `string` — Only signed in users with specified domains can join meetings. `This field is deprecated and will not be supported in the future.` As an alternative, use the `meeting_authentication`, `authentication_option`, and `authentication_domains` fields to understand the [authentication configurations](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the meeting.
- **`focus_mode`**

 `boolean` — Whether the [Focus Mode] feature](https://support.zoom.us/hc/en-us/articles/360061113751-Using-focus-mode) is enabled when the meeting starts.
- **`global_dial_in_countries`**

 `array` — List of global dial-in countries.
 Items:
 `string`

```



```

- **`global_dial_in_numbers`**

 `array` — Global Dial-in Countries and Regions

 Items:

- **`city`**

 `string` — City of the number, if any. For example, Chicago.

- **`country`**

 `string` — Country code, such as BR.

- **`country_name`**

 `string` — Full name of country, such as Brazil.

- **`number`**

 `string` — Phone number, such as +1 2332357613.

- **`type`**

 `string`, possible values: `toll`, `tollfree` — Type of number.

- **`host_save_video_order`**

 `boolean` — Whether the `Allow host to save video order` feature is enabled.

- **`host_video`**

 `boolean` — Start video when the host joins the meeting.

- **`in_meeting`**

 `boolean`, default: `false` — Host meeting in India.

- **`internal_meeting`**

 `boolean`, default: `false` — Whether to set the meeting as an internal meeting.

- **`jbh_time`**

 `integer`, possible values: `0, 5, 10, 15` — If the value of `join_before_host` field is set to true, this field can be used to indicate time limits when a participant may join a meeting before a host.
 `0` - Allow participant to join anytime. `5` - Allow participant to join 5 minutes before meeting start time.
 `10` - Allow participant to join 10 minutes before meeting start time. `15` - Allow participant to join 15 minutes before meeting start time.

- **`join_before_host`**

 `boolean`, default: `false` — Allow participants to join the meeting before the host starts the meeting. Only used for scheduled or recurring meetings.

- **`language_interpretation`**

 `object` — The meeting's [language interpretation settings](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details.
 Note: This feature is only available for certain Meeting add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will not be applied to the meeting.

- **`enable`**

 `boolean` — Whether to enable [language interpretation](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768) for the meeting.

- **`interpreters`**

 `array` — Information about the meeting's language interpreters.

 Items:

- **`email`**

 `string`, format: `email` — The interpreter's email address.

- **`interpreter_languages`**

```

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the ``language_interpretation`` object's ``languages`` and ``custom_languages`` values in the ``[*]*Get user settings[*]*`` (`/docs/api/users/#tag/users/GET/users/{userId}/settings`) API response. ``[*]*languages[*]*``: System-supported languages include ``English``, ``Chinese``, ``Japanese``, ``German``, ``French``, ``Russian``, ``Portuguese``, ``Spanish``, and ``Korean``. ``[*]*custom_languages[*]*``: User-defined languages added by the user. For example, an interpreter translating between English and French should use ``English,French``.

- ``[*]*languages[*]*``

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: ``US`` (English), ``CN`` (Chinese), ``JP`` (Japanese), ``DE`` (German), ``FR`` (French), ``RU`` (Russian), ``PT`` (Portuguese), ``ES`` (Spanish), and ``KR`` (Korean). For example, to set an interpreter translating from English to Chinese, use ``US,CN``.

- ``[*]*meeting_authentication[*]*``

``boolean`` — ``true`` - Only authenticated users can join meetings.

- ``[*]*meeting_invitees[*]*``

``array`` — A list of the meeting's invitees.

``Items``:

- ``[*]*email[*]*``

``string``, format: ``email`` — The invitee's email address.

- ``[*]*internal_user[*]*``

``boolean``, default: ``false`` — Whether the meeting invitee is an internal user.

- ``[*]*mute_upon_entry[*]*``

``boolean``, default: ``false`` — Mute participants upon entry.

- ``[*]*participant_focused_meeting[*]*``

``boolean``, default: ``false`` — Whether to set the meeting as a participant focused meeting.

- ``[*]*participant_video[*]*``

``boolean`` — Start video when participants join the meeting.

- ``[*]*private_meeting[*]*``

``boolean`` — Whether the meeting is set as private.

- ``[*]*push_change_to_calendar[*]*``

``boolean``, default: ``false`` — Whether to push meeting changes to the calendar. To enable this feature, configure the ``[*]*Configure Calendar and Contacts Service[*]*`` in the user's profile page of the Zoom web portal and enable the ``[*]*Automatically sync Zoom calendar events information bi-directionally between Zoom and integrated calendars[*]*`` setting in the ``[*]*Settings[*]*`` page of the Zoom web portal. ``true`` - Push meeting changes to the calendar. ``false`` - Do not push meeting changes to the calendar.

- ``[*]*question_and_answer[*]*``

``object`` — ``Q&A`` (`https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065237`) for meeting.

- ``[*]*allow_anonymous_questions[*]*``

``boolean`` — ``true`` - Allow participants to send questions without providing their name to the host, co-host, and panelists. ``false`` - Don't allow anonymous questions. Not supported for simulative meetings.

- ``[*]*allow_submit_questions[*]*``

``boolean`` — ``true`` - Allow participants to submit questions. ``false`` - Don't allow participants to submit questions.

- ``[*]*attendees_can_comment[*]*``

``boolean`` — ``true`` - Attendees can answer questions or leave a comment in the question thread. ``false`` - Attendees can't answer questions or leave a comment in the question thread.

- ``[*]*attendees_can_upvote[*]*``

``boolean`` — `\* \true\`` - Attendees can select the thumbs up button to bring popular questions to the top of the Q&A window. `\* \false\`` - Attendees can't select the thumbs up button on questions.

- `**`enable`**`

``boolean`` — `\* \true\`` - Enable `\[Q&A](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065237)` for the meeting. `\* \false\`` - Disable Q&A for the meeting.

- `**`question_visibility`**`

``string``, possible values: `"answered"`, `"all"` — Indicate whether you want attendees to be able to view only answered questions, or view all questions. `\* \answered\`` - Attendees can only view answered questions. `\* \all\`` - Attendees can view all questions submitted in the Q&A.

- `**`registrants_confirmation_email`**`

``boolean`` — Whether to send registrants an email confirmation. `\* \true\`` - Send a confirmation email. `\* \false\`` - Do not send a confirmation email.

- `**`registrants_email_notification`**`

``boolean`` — Whether to send registrants email notifications about their registration approval, cancellation, or rejection. `\* \true\`` - Send an email notification. `\* \false\`` - Do not send an email notification. Set this value to `\true\`` to also use the `\registrants\_confirmation\_email\`` parameter.

- `**`registration_type`**`

``integer``, possible values: `1`, `2`, `3`, default: `1` — Registration type. Used for recurring meeting with fixed time only. `\1\`` Attendees register once and can attend any of the occurrences. `\2\`` Attendees need to register for each occurrence to attend. `\3\`` Attendees register once and can choose one or more occurrences to attend.

- `**`request_permission_to_unmute_participants`**`

``boolean`` — Whether to enable the `\[*\*Request permission to unmute participants\*\*](https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting)` setting. This option cannot be used together with `\allow\_host\_control\_participant\_mute\_state\``, only one of the two can be enabled at a time.

- `**`resources`**`

``array`` — The meeting's resources.

`**Items:**`

- `**`permission_level`**`

``string``, possible values: `"editor"`, `"commenter"`, `"viewer"`, default: `"editor"` — The permission levels for users to access the whiteboard. `\* \editor\`` - Users with link access can edit the board. `\* \commenter\`` - Users with link access can comment on the board. `\* \viewer\`` - Users with link access can view the board.

- `**`resource_id`**`

``string`` — The resource ID.

- `**`resource_type`**`

``string``, possible values: `"whiteboard"` — The resource type.

- `**`show_join_info`**`

``boolean`` — Whether to show the meeting's join information on the registration confirmation page. This setting is only applied to meetings with registration enabled.

- `**`show_share_button`**`

``boolean`` — Show social share buttons on the meeting registration page. This setting only works for meetings that require `\[registration](https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-registration-for-a-meeting)`.

- `**`sign_language_interpretation`**`

``object`` — The meeting's `\[sign language interpretation settings](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)`. Make sure to add the language in the web portal in order to use it in the API. See link for details. `\*\*Note:\*\*` If this feature is not enabled on the host's account, this setting will `\*\*not\*\*` be applied to the meeting.

- `**`enable`**`

``boolean`` — Whether to enable `\[sign language interpretation]\`(<https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar>) for the meeting.

- `**`interpreters`**`

``array`` — Information about the meeting's sign language interpreters.

`**Items:**`

- `**`email`**`

``string``, format: ``email`` — The interpreter's email address.

- `**`sign_language`**`

``string`` — The interpreter's sign language. To get this value, use the `\sign\_language\_interpretation\` object's `\languages\` and `\custom\_languages\` values in the `\[*\*Get user settings\*\*]\`([/docs/api/rest/reference/zoom-api/methods#operation/userSettings](https://developers.zoom.us/docs/api/rest/reference/zoom-api/methods#operation/userSettings)) API response.

- `**`summary_template_id`**`

``string`` — The summary template ID used to generate a meeting summary based on a predefined template. To get available summary templates, use the `\[*\*Get user summary templates\*\*]` API. To enable this feature for your account, please [contact Zoom Support](https://support.zoom.com/hc/en)(<https://support.zoom.com/hc/en>).

- `**`use_pmi`**`

``boolean`` — Whether to use a `\[Personal Meeting ID (PMI)]\`([/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi](https://developers.zoom.us/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi)) for the meeting. This field is only used for scheduled meetings(`\2\`) and recurring meetings with no fixed time(`\3\`).

- `**`waiting_room`**`

``boolean``, default: ``false`` — Enable waiting room

- `**`waiting_room_options`**`

``object`` — Configuration settings for the meeting's waiting room.

- `**`mode` (required)**`

``string``, possible values: ``follow_setting``, ``custom`` — This field specifies the waiting room behavior for this meeting. `\* \follow\_setting\` - Use the Zoom web portal setting. `\* \custom\` - Specify which participants should go into the waiting room.

- `**`who_goes_to_waiting_room`**`

``string``, possible values: ``everyone``, ``users_not_in_account``, ``users_not_in_account_or_whitelisted_domains``, ``users_not_on_invite``, ``users_not_in_org`` — Which participants should be placed into the waiting room. Required if `\mode\` is set to `\custom\`. `\* \everyone\` - Everyone. `\* \users\_not\_in\_account\` - Users not in your account. `\* \users\_not\_in\_account\_or\_whitelisted\_domains\` - Users who are not in your account and not part of your whitelisted domains. `\* \users\_not\_on\_invite\` - Users not on the meeting invite. `\* \users\_not\_in\_org\` - Users not in your organization.

- `**`watermark`**`

``boolean``, default: ``false`` — Add a watermark when viewing a shared screen.

- `**`who_can_ask_questions`**`

``integer``, possible values: ``1``, ``2``, ``3``, ``4``, ``5`` — Defines who can ask questions about this meeting's transcript. This field is applicable only when `\auto\_start\_ai\_companion\_questions\` is set to `\true\`. `\* \1\` - All participants and invitees. `\* \2\` - All participants only from when they join. `\* \3\` - Only meeting host. `\* \4\` - Participants and invitees in our organization. `\* \5\` - Participants in our organization only from when they join.

- `**`who_will_receive_summary`**`

``integer``, possible values: ``1``, ``2``, ``3``, ``4`` — Defines who will receive a summary after this meeting. This field is applicable only when `\auto\_start\_meeting\_summary\` is set to `\true\`. `\* \1\` - Only meeting host. `\* \2\` - Only meeting host, co-hosts, and alternative hosts. `\* \3\` - Only meeting host and meeting invitees in our organization. `\* \4\` - All meeting invitees including those outside of our organization.

- `**`start_time`**`

``string``, format: ``date-time`` — Meeting start time in GMT or UTC. Start time will not be returned if the meeting is an `\[*\*instant\*\*]` meeting.

### - **start\_url**

**string** — The `start_url` of a meeting is a URL that a host or an alternative host can start the meeting. The expiration time for the `start_url` field listed in the response of the `POST /docs/api/rest/reference/zoom-api/methods#operation/meetingCreate` API is two hours for all regular users. For users created using the `POST /docs/api/rest/reference/zoom-api/methods#operation/userCreate` API, the expiration time of the `start_url` field is 90 days. For security reasons, to retrieve the updated value for the `start_url` field programmatically after the expiry time, you must call the `GET /docs/api/rest/reference/zoom-api/methods#operation/meeting` API and refer to the value of the `start_url` field in the response. This URL should only be used by the host of the meeting and **should not be shared with anyone other than the host** of the meeting as anyone with this URL will be able to login to the Zoom Client as the host of the meeting.

### - **status**

**string**, possible values: `"waiting"`, `"started"` — The meeting status. `"waiting"` - The meeting has not started. `"started"` - The meeting is currently in progress.

### - **template\_id**

**string** — The account admin meeting template ID used to schedule a meeting using a `meeting template` (<https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates>). For a list of account admin-provided meeting templates, use the `GET /docs/api-reference/zoom-api/methods#operation/listMeetingTemplates` API. **At this time, this field only accepts account admin meeting template IDs.** To enable the account admin meeting templates feature, [contact Zoom support](https://support.zoom.us/hc/en-us) (<https://support.zoom.us/hc/en-us>).

### - **timezone**

**string** — The timezone to format the meeting start time.

### - **topic**

**string** — Meeting topic.

### - **tracking\_fields**

**array** — Tracking fields.

**Items:**

#### - **field**

**string** — The tracking field's label.

#### - **value**

**string** — The tracking field's value.

#### - **visible**

**boolean** — Indicates whether the `tracking field` (<https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields>) is visible in the meeting scheduling options in the Zoom Web Portal or not. `true`: Tracking field is visible. `false`: Tracking field is not visible to the users when they look at the meeting details in the Zoom Web Portal but the field was used while scheduling this meeting via API. An invisible tracking field can be used by users while scheduling meetings via API only.

### - **type**

**integer**, possible values: `1`, `2`, `3`, `4`, `8`, `10`, default: `2` — The type of meeting. `1` - An instant meeting. `2` - A scheduled meeting. `3` - A recurring meeting with no fixed time. `4` - A PMI Meeting. `8` - A recurring meeting with fixed time. `10` - A screen share only meeting.

### - **uuid**

**string** — Unique meeting ID. Each meeting instance generates its own meeting UUID - after a meeting ends, a new UUID is generated for the next instance of the meeting. Retrieve a list of UUIDs from past meeting instances using the `GET /docs/api/rest/reference/zoom-api/methods#operation/pastMeetings` API. **[Double encode]** `/docs/api/rest/using-zoom-apis/#meeting-id-and-uuid` your UUID when using it for API calls if the UUID begins with a `/` or contains `/` in it.

### **Example:**

**json**

```
{
 "assistant_id": "kFFvsJc-Q10SxaJQLvaa_A",
 "host_email": "jchill@example.com",
```

```

"host_id": "30R7kT7bTIKSNUFEuH_Qlg",
"id": 97763643886,
"uuid": "aDYl0hsHRtCd4ii1uC2+hA==",
"registration_url": "https://example.com/meeting/register/7ksAkRCoEpt1Jm0wa-E6lICLur9e7Lde5oW6",
"agenda": "My Meeting",
"created_at": "2022-03-25T07:29:29Z",
"duration": 60,
"encrypted_password": "8pEkRweVXPV30b2KJYgFTRlDt1lgSn.1",
"pstn_password": "123456",
"h323_password": "123456",
"join_url": "https://example.com/j/11111",
"chat_join_url": "https://example.com/launch/jc/11111",
"occurrences": [
 {
 "duration": 60,
 "occurrence_id": "1648194360000",
 "start_time": "2022-03-25T07:46:00Z",
 "status": "available"
 }
],
"password": "123456",
"pmi": "97891943927",
"pre_schedule": false,
"recurrence": {
 "end_date_time": "2022-04-02T15:59:00Z",
 "end_times": 7,
 "monthly_day": 1,
 "monthly_week": 1,
 "monthly_week_day": 1,
 "repeat_interval": 1,
 "type": 1,
 "weekly_days": "1"
},
"settings": {
 "additional_data_center_regions": [
 "TY"
],
 "allow_multiple_devices": true,
 "alternative_hosts": "jchill@example.com;thill@example.com",
 "alternative_hosts_email_notification": true,
 "alternative_host_update_polls": true,
 "alternative_host_manage_meeting_summary": true,
 "alternative_host_manage_cloud_recording": false,
 "approval_type": 0,
 "approved_or_denied_countries_or_regions": {
 "approved_list": [
 "CX"
],
 "denied_list": [
 "CA"
],
 "enable": true,
 "method": "approve"
 },
 "audio": "telephony",
 "audio_conference_info": "test",
 "authentication_domains": "example.com",
 "authentication_exception": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "join_url": "https://example.com/s/11111"
 }
],
 "authentication_name": "Sign in to Zoom",
 "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
 "auto_recording": "cloud",
 "auto_add_recording_to_video_management": {
 "enable": true,
 "channels": [
 {
 "channel_id": "Uyh5qeykTDiA66YQEYmFPg",
 "name": "Team Weekly Meetings"
 }
]
 },
 "breakout_room": {
 "enable": true,
 "rooms": [
 {

```

```

 "name": "room1",
 "participants": [
 "jchill@example.com"
]
 }
],
"calendar_type": 1,
"close_registration": false,
"contact_email": "jchill@example.com",
"contact_name": "Jill Chill",
"custom_keys": [
 {
 "key": "key1",
 "value": "value1"
 }
],
"email_notification": true,
"encryption_type": "enhanced_encryption",
"focus_mode": true,
"global_dial_in_countries": [
 "US"
],
"global_dial_in_numbers": [
 {
 "city": "New York",
 "country": "US",
 "country_name": "US",
 "number": "+1 1000200200",
 "type": "toll"
 }
],
"host_video": true,
"jbh_time": 0,
"join_before_host": true,
"question_and_answer": {
 "enable": true,
 "allow_submit_questions": true,
 "allow_anonymous_questions": true,
 "question_visibility": "all",
 "attendees_can_comment": true,
 "attendees_can_upvote": true
},
"language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "interpreter_languages": "English,French"
 }
]
},
"sign_language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "sign_language": "American"
 }
]
},
"meeting_authentication": true,
"mute_upon_entry": false,
"participant_video": false,
"private_meeting": false,
"registrants_confirmation_email": true,
"registrants_email_notification": true,
"registration_type": 1,
"show_share_button": true,
"show_join_info": true,
"use_pmi": false,
"waiting_room": false,
"waiting_room_options": {
 "mode": "follow_setting",
 "who_goes_to_waiting_room": "everyone"
},
"watermark": false,
"host_save_video_order": true,
"internal_meeting": false,
"meeting_invitees": [

```

```

 {
 "email": "jchill@example.com",
 "internal_user": false
 }
],
 "continuous_meeting_chat": {
 "enable": true,
 "channel_id": "cabcd1234567defghijkl01234"
 },
 "participant_focused_meeting": false,
 "push_change_to_calendar": false,
 "resources": [
 {
 "resource_type": "whiteboard",
 "resource_id": "X4Hy02w3QU0dskKofgb9Jg",
 "permission_level": "editor"
 }
],
 "auto_start_meeting_summary": false,
 "who_will_receive_summary": 1,
 "auto_start_ai_companion_questions": false,
 "who_can_ask_questions": 1,
 "summary_template_id": "1e1356ad",
 "device_testing": false,
 "request_permission_to_unmute_participants": true,
 "allow_host_control_participant_mute_state": false,
 "disable_participant_video": false,
 "email_in_attendee_report": true
},
"start_time": "2022-03-25T07:29:29Z",
"start_url": "https://example.com/s/11111",
"status": "waiting",
"template_id": "Dv4YdINdTk+Z5RToadh5ug==",
"timezone": "America/Los_Angeles",
"topic": "My Meeting",
"tracking_fields": [
 {
 "field": "field1",
 "value": "value1",
 "visible": true
 }
],
"type": 2,
"dynamic_host_key": "123456",
"creation_source": "open_api"
}

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3000` `Cannot access webinar info.` `Error Code: 3161` `Your user account is not allowed meeting hosting and scheduling capabilities.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Meeting does not exist: {meetingId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](/docs/api/rate-limits/)`.

### ### Delete a meeting

```

- Method: DELETE
- Path: /meetings/{meetingId}
- Tags: Meetings

```

Delete a meeting.

#### **Prerequisites:**

- For recurring meetings, the `occurrence_id` is required to delete a specific occurrence. If not provided, the entire recurring series will be deleted.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write:admin`, `meeting:write`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:delete:meeting`, `meeting:delete:meeting:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

### #### Responses



#### Status: 204 `HTTP Status Code`: `204` Meeting deleted.

#### Status: 400 `HTTP Status Code`: `400` `Bad Request` `Error Code`: `300` `Invalid parameter: occurrence_id`. `3000` `Cannot access webinar information`. `3018` `Not allowed to delete PMI`. `3037` `Not allowed to delete PAC`. `3161` `Meeting hosting and scheduling capabilities are not allowed for your user account`.

#### Status: 404 `HTTP Status Code`: `404` `Not Found` `Error Code`: `3001` Meeting does not exist: {meetingId}.

#### Status: 429 `HTTP Status Code`: `429` `Too Many Requests`. For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

### ## Update a meeting

- **Method**: `PATCH`  
 - **Path**: `/meetings/{meetingId}`  
 - **Tags**: `Meetings`

Updates meeting details.

#### **Prerequisites**

- The `start_time` value must be a future date. If the value is omitted or a date is in the past, the API ignores this value and does not update any recurring meetings.
- The `recurrence` object is required only when updating the entire series of a recurring meeting with `type=8`.
- This API has a rate limit of **100 requests per day**. You can update a meeting for a maximum of 100 times within a 24-hour period.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write`, `meeting:write:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:update:meeting:admin`, `meeting:update:meeting`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

### #### Request Body

##### Content-Type: `application/json`

- **agenda**

`string` — Meeting description.

- **duration**

`integer` — The meeting's scheduled duration, in minutes. This field is used for type `2` scheduled meetings and type `8` recurring meetings with a fixed time. The value must be between 1 and 1440 minutes, which equates to 24 hours.

- **password**

`string` — The passcode required to join the meeting. By default, a passcode can **only** have a maximum length of 10 characters and only contain alphanumeric characters and the `@`, `-`, `_`, and `\` characters. **Note** If the account owner or administrator has configured `[minimum passcode requirement settings]`([https://support.zoom.us/hc/en-us/articles/360033559832-Meeting-and-webinar-passwords#h\\_a427384b-e383-4f80-864d-794bf0a37604](https://support.zoom.us/hc/en-us/articles/360033559832-Meeting-and-webinar-passwords#h_a427384b-e383-4f80-864d-794bf0a37604)), the passcode **must** meet those requirements. If passcode requirements are enabled, use the `[Get user settings]`([/docs/api/users/#tag/users/GET/users/{userId}/settings](#)) API or the `[Get account settings]`([/docs/api/accounts/#tag/accounts/GET/accounts/{accountId}/settings](#)) API to get the requirements. If the **Require a passcode when scheduling new meetings** account setting is enabled and locked, a passcode will be automatically generated if one is not provided.

- **pre\_schedule**

`boolean`, default: `false` — Whether to create a prescheduled meeting through the `[GSuite app]`(<https://support.zoom.us/hc/en-us/articles/360020187492-Zoom-for-GSuite-add-on>). This **only** supports the meeting `type` value of `2` - scheduled meetings- and `3` - recurring meetings with no fixed time. `true` - Create a prescheduled meeting. `false` - Create a regular meeting.

- **recurrence**

`object` — Recurrence object. Use this object only for a meeting with type `8`, a recurring meeting with fixed time.

- **type** (required)

``integer``, possible values: ``1, 2, 3`` — Recurrence meeting types. ``1`` - Daily. ``2`` - Weekly. ``3`` - Monthly.

- `**`end_date_time`**`

``string``, format: ``date-time`` — Select the final date when the meeting recurs before it is canceled. Should be in UTC time, such as 2017-11-25T12:00:00Z. Cannot be used with ``end_times``.

- `**`end_times`**`

``integer``, default: ``1`` — Select how many times the meeting should recur before it is canceled. If ``end_times`` is set to 0, it means there is no end time. The maximum number of recurrences is 60. Cannot be used with ``end_date_time``.

- `**`monthly_day`**`

``integer``, default: ``1`` — Use this field ``*``only if you're scheduling a recurring meeting of type ``3`` to state the day in a month when the meeting should recur. The value range is from 1 to 31. For instance, if the meeting should recur on 23rd of each month, provide ``23`` as this field's value and ``1`` as the ``repeat_interval`` field's value. If the meeting should recur every three months on 23rd of the month, change the ``repeat_interval`` field's value to ``3``.

- `**`monthly_week`**`

``integer``, possible values: ``-1, 1, 2, 3, 4`` — Use this field ``*``only if you're scheduling a recurring meeting of type ``3`` to state the week of the month when the meeting should recur. If you use this field, you must also use the ``monthly_week_day`` field to state the day of the week when the meeting should recur. ``-1`` - Last week of the month. ``1`` - First week of the month. ``2`` - Second week of the month. ``3`` - Third week of the month. ``4`` - Fourth week of the month.

- `**`monthly_week_day`**`

``integer``, possible values: ``1, 2, 3, 4, 5, 6, 7`` — Use this field only if you're scheduling a recurring meeting of type ``3`` to state a specific day in a week when a monthly meeting should recur. To use this field, you must also use the ``monthly_week`` field. ``1`` - Sunday. ``2`` - Monday. ``3`` - Tuesday. ``4`` - Wednesday. ``5`` - Thursday. ``6`` - Friday. ``7`` - Saturday.

- `**`repeat_interval`**`

``integer`` — Define the interval when the meeting should recur. For instance, to schedule a meeting that recurs every two months, set this field's value as ``2`` and the ``type`` parameter's value to ``3``. For a daily meeting, the maximum interval is ``99`` days. For a weekly meeting, the maximum interval is ``50`` weeks. For a monthly meeting, the maximum value is ``10`` months.

- `**`weekly_days`**`

``string``, possible values: ``"1", "2", "3", "4", "5", "6", "7"``, default: ``"1"`` — This field is required if you're scheduling a recurring meeting of type ``2``, to state which days of the week the meeting should repeat. This field's value could be a number between ``1`` to ``7`` in string format. For instance, if the meeting should recur on Sunday, provide ``1`` as this field's value. ``*`Note`*`` If you would like the meeting to occur on multiple days of a week, you should provide comma separated values for this field. For instance, if the meeting should recur on Sundays and Tuesdays provide ``1,3`` as this field's value. ``1`` - Sunday. ``2`` - Monday. ``3`` - Tuesday. ``4`` - Wednesday. ``5`` - Thursday. ``6`` - Friday. ``7`` - Saturday.

- `**`schedule_for`**`

``string`` — The email address or ``userId`` of the user to schedule a meeting for.

- `**`settings`**`

``object`` — Meeting settings.

- `**`allow_host_control_participant_mute_state`**`

``boolean`` — Whether to allow the host and co-hosts to fully control the mute state of participants. This option cannot be used together with ``request_permission_to_unmute_participants``, only one of the two can be enabled at a time.

- `**`allow_multiple_devices`**`

``boolean`` — Allow attendees to join the meeting from multiple devices. This setting only works for meetings that require ``[registration]`` (<https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-registration-for-a-meeting>).

- `**`alternative_host_manage_cloud_recording`**`

``boolean`` — Whether to allow an alternative host to manage meeting cloud recordings.

```

- alternative_host_manage_meeting_summary

 boolean — Whether to allow an alternative host to manage meeting summaries.

- alternative_host_update_polls

 boolean — Whether the Allow alternative hosts to add or edit polls feature is enabled. This requires Zoom version 5.8.0 or higher.

- alternative_hosts

 string — A semicolon-separated list of the meeting's alternative hosts' email addresses or IDs.

- alternative_hosts_email_notification

 boolean, default: true — Flag to determine whether to send email notifications to alternative hosts, default value is true.

- approval_type

 integer, possible values: 0, 1, 2, default: 2 — Enable registration and set approval for the registration. Note that this feature requires the host to be of Licensed user type. Registration cannot be enabled for a basic user. 0 - Automatically approve. 1 - Manually approve. 2 - No registration required.

- approved_or_denied_countries_or_regions

 object — Approve or block users from specific regions or countries from joining this meeting.

- approved_list

 array — List of countries or regions from where participants can join this meeting.

 Items:

 string

- denied_list

 array — List of countries or regions from where participants can not join this meeting.

 Items:

 string

- enable

 boolean — true - Setting enabled to either allow users or block users from specific regions to join your meetings. false - Setting disabled.

- method

 string, possible values: "approve", "deny" — Specify whether to allow users from specific regions to join this meeting, or block users from specific regions from joining this meeting. approve - Allow users from specific regions or countries to join this meeting. If this setting is selected, include the approved regions or countries in the approved_list. deny - Block users from specific regions or countries from joining this meeting. If this setting is selected, include the approved regions or countries in the denied_list.

- audio

 string, possible values: "both", "telephony", "voip", "thirdParty", default: "both" — Determine how participants can join the audio portion of the meeting. both - Both Telephony and VoIP. telephony - Telephony only. voip - VoIP only. thirdParty - Third party audio conference.

- audio_conference_info

 string — Third party audio conference info.

- authentication_domains

 string — If user has configured [Sign Into Zoom with Specified Domains] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f) option, this will list the domains that are authenticated.

- authentication_exception

 array — The participants added here will receive unique meeting invite links and bypass authentication.

```

```

Items:

- **`email`**

 `string`, format: `email` — The participant's email address.

- **`join_url`**

 `string` — URL for participants to join the meeting

- **`name`**

 `string` — The participant's name.

- **`authentication_name`**

 `string` — Authentication name set in the \[authentication profile]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f).

- **`authentication_option`**

 `string` — Meeting authentication option ID.

- **`auto_add_recording_to_video_management`**

 `object` — Automatically add meeting recordings to a video channel in video management. To enable this feature for your account, please \[contact Zoom Support]\(https://support.zoom.us/hc/en-us).

 - **`enable` (required)**

 `boolean`, default: `false` — Whether to automatically add the meeting recording to video management.

- **`channels`**

 `array` — List of video management channels where the meeting recording will be added.

Items:

- **`channel_id` (required)**

 `string` — The unique ID of a video management channel.

- **`name`**

 `string` — The video management channel's name.

- **`auto_recording`**

 `string`, possible values: `"local", "cloud", "none"`, default: `"none"` — Automatic recording.
 \`local\` - Record on local. \`cloud\` - Record on cloud. \`none\` - Disabled.

- **`auto_start_ai_companion_questions`**

 `boolean`, default: `false` — Whether to automatically start AI Companion questions.

- **`auto_start_meeting_summary`**

 `boolean`, default: `false` — Whether to automatically start meeting summary.

- **`breakout_room`**

 `object` — Setting to \[pre-assign breakout rooms]\(https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4).

 - **`enable`**

 `boolean` — Set this field's value to `true` to enable the \[breakout room pre-assign]\(https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4) option.

 - **`rooms`**

 `array` — Create room(s).

Items:

 - **`name`**

```

```

 `string` — The breakout room's name.

- **`participants`**

 `array` — Email addresses of the participants who are to be assigned to the breakout room.

 Items:

 `string`

- **`calendar_type`**

 `integer`, possible values: `1, 2` — The type of calendar integration used to schedule the meeting. \
 \1\ - \[Zoom Outlook add-in](https://support.zoom.us/hc/en-us/articles/360031592971-Getting-started-with-Outlook-plugin-and-add-in) \
 \2\ - \[Zoom for Google Workspace add-on](https://support.zoom.us/hc/en-us/articles/360020187492-Using-the-Zoom-for-Google-Workspace-add-on) Works with the \private\meeting\ field to determine whether to share details of meetings.

- **`close_registration`**

 `boolean`, default: `false` — Close registration after the event date.

- **`cn_meeting`**

 `boolean`, default: `false` — Host the meeting in China.

- **`contact_email`**

 `string` — Contact email for registration.

- **`contact_name`**

 `string` — Contact name for registration.

- **`continuous_meeting_chat`**

 `object` — Information about the **Enable continuous meeting chat** feature. This setting only applies to scheduled and recurring meetings, type \2\, \3\, and \8\. It is **not supported** for type \1\ instant meetings or type \10\ screen share only meetings.

- **`auto_add_invited_external_users`**

 `boolean` — Whether to enable the **Automatically add invited external users** setting.

- **`auto_add_meeting_participants`**

 `boolean` — Whether to enable the **Automatically add meeting participants** setting.

- **`enable`**

 `boolean` — Whether to enable the **Enable continuous meeting chat** setting.

- **`custom_keys`**

 `array` — Custom keys and values assigned to the meeting.

 Items:

 - **`key`**

 `string` — Custom key associated with the user.

 - **`value`**

 `string` — Value of the custom key associated with the user.

- **`device_testing`**

 `boolean`, default: `false` — Enable the device testing.

- **`disable_participant_video`**

 `boolean`, default: `false` — Whether to disable the participant video during a meeting. To enable this feature for your account, \[contact Zoom Support](https://support.zoom.us/hc/en-us).

- **`email_in_attendee_report`**

 `boolean` — Whether to include authenticated guest's email addresses in meetings' attendee reports.

- **`email_notification`**

```

``boolean``, default: ``true`` — Whether to send email notifications to `\[alternative hosts]\` (<https://support.zoom.us/hc/en-us/articles/208220166>) and `\[users with scheduling privileges]\` (<https://support.zoom.us/hc/en-us/articles/201362803-Scheduling-privilege>). This value defaults to ``true``.

- `**`encryption_type`**`

``string``, possible values: ``"enhanced_encryption", "e2ee"`` — Choose between enhanced encryption and `\[end-to-end encryption]\` (<https://support.zoom.us/hc/en-us/articles/360048660871>) when starting or a meeting. When using end-to-end encryption, several features such cloud recording and phone/SIP/H.323 dial-in, will be `\[*]automatically disabled[*]`. ``enhanced_encryption`` - Enhanced encryption. Encryption is stored in the cloud if you enable this option. ``e2ee`` - `\[End-to-end encryption]\` (<https://support.zoom.us/hc/en-us/articles/360048660871>). The encryption key is stored in your local device and can not be obtained by anyone else. Enabling this setting also `\[*]disables[*]` the features join before host, cloud recording, streaming, live transcription, breakout rooms, polling, 1:1 private chat, and meeting reactions.

- `**`enforce_login`**`

``boolean`` — Only signed in users can join this meeting. `\[*]This field is deprecated and will not be supported in the future.[*]` As an alternative, use the ``meeting_authentication``, ``authentication_option``, and ``authentication_domains`` fields to understand the `\[authentication configurations]\` (<https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars>) set for the meeting.

- `**`enforce_login_domains`**`

``string`` — Only signed in users with specified domains can join meetings. `\[*]This field is deprecated and will not be supported in the future.[*]` As an alternative, use the ``meeting_authentication``, ``authentication_option``, and ``authentication_domains`` fields to understand the `\[authentication configurations]\` (<https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars>) set for the meeting.

- `**`focus_mode`**`

``boolean`` — Whether the `\[*]Focus Mode[*]` feature (<https://support.zoom.us/hc/en-us/articles/360061113751-Using-focus-mode>) is enabled when the meeting starts.

- `**`global_dial_in_countries`**`

``array`` — List of global dial-in countries

`**Items:**`

``string``

- `**`global_dial_in_numbers`**`

``array`` — Global dial-in countries or regions

`**Items:**`

- `**`city`**`

``string`` — City of the number, if any, such as Chicago.

- `**`country`**`

``string`` — Country code, such as BR.

- `**`country_name`**`

``string`` — Full name of country, such as Brazil.

- `**`number`**`

``string`` — Phone number, such as +1 2332357613.

- `**`type`**`

``string``, possible values: ``"toll", "tollfree"`` — Type of number.

- `**`host_save_video_order`**`

``boolean`` — Whether the `\[*]Allow host to save video order[*]` feature is enabled.

- `**`host_video`**`

``boolean`` — Start video when the host joins the meeting.

```

- in_meeting

 `boolean`, default: `false` — Host meeting in India.

- internal_meeting

 `boolean`, default: `false` — Whether to set the meeting as an internal meeting.

- jbh_time

 `integer`, possible values: `0, 5, 10, 15` — If the value of `join_before_host` field is set to true, use this field to indicate time limits for a participant to join a meeting before a host. `0` - Allow participant to join anytime. `5` - Allow participant to join 5 minutes before meeting start time. `10` - Allow participant to join 10 minutes before meeting start time. `15` - Allow participant to join 15 minutes before meeting start time.

- join_before_host

 `boolean`, default: `false` — Allow participants to join the meeting before the host starts the meeting. Only used for scheduled or recurring meetings.

- language_interpretation

 `object` — The meeting's [language interpretation settings](https://support.zoom.com/hc/en/article?id=zm\kb\&sysparm_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details. Note: This feature is only available for certain Meeting add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will not be applied to the meeting.

 - enable

 `boolean` — Whether to enable [language interpretation](https://support.zoom.com/hc/en/article?id=zm\kb\&sysparm_article=KB0064768) for the meeting.

 - interpreters

 `array` — Information about the meeting's language interpreters.

 Items:

 - email

 `string`, format: `email` — The interpreter's email address.

 - interpreter_languages

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the `language_interpretation` object's `languages` and `custom_languages` values in the [Get user settings](/docs/api/users/#tag/users/GET/users/{userId}/settings) API response. languages: System-supported languages include `English`, `Chinese`, `Japanese`, `German`, `French`, `Russian`, `Portuguese`, `Spanish`, and `Korean`. custom_languages: User-defined languages added by the user. For example, an interpreter translating between English and French should use `English,French`.

 - languages

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: `US` (English), `CN` (Chinese), `JP` (Japanese), `DE` (German), `FR` (French), `RU` (Russian), `PT` (Portuguese), `ES` (Spanish), and `KR` (Korean). For example, to set an interpreter translating from English to Chinese, use `US,CN`.

 - meeting_authentication

 `boolean` — `true` - Only authenticated users can join meetings.

 - meeting_invitees

 `array` — A list of the meeting's invitees.

 Items:

 - email

 `string`, format: `email` — The invitee's email address.

 - mute_upon_entry

 `boolean`, default: `false` — Mute participants upon entry.

```

```

- **`participant_focused_meeting`**

 `boolean`, default: `false` — Whether to set the meeting as a participant focused meeting.

- **`participant_video`**

 `boolean` — Start video when participants join the meeting.

- **`private_meeting`**

 `boolean` — Whether the meeting is set as private.

- **`push_change_to_calendar`**

 `boolean` — Whether to push meeting changes to the calendar. To enable this feature, configure the
 Configure Calendar and Contacts Service in the user's profile page of the Zoom web portal and enable
 the **Automatically sync Zoom calendar events information bi-directionally between Zoom and integrated
 calendars.** setting in the **Settings** page of the Zoom web portal. * `true` - Push meeting
 changes to the calendar. * `false` - Do not push meeting changes to the calendar.

- **`question_and_answer`**

 `object` — \[Q\&A\](https://support.zoom.com/hc/en/article?id=zm_kb\&sysparm_article=KB0065237)
 for meeting.

- **`allow_anonymous_questions`**

 `boolean` — * `true` - Allow participants to send questions without providing their name to the
 host, co-host, and panelists.. * `false` - Do not allow anonymous questions.(Not supported for simulative
 meeting.)

- **`allow_submit_questions`**

 `boolean` — * `true`: Allow participants to submit questions. * `false`: Do not allow submit
 questions.

- **`attendees_can_comment`**

 `boolean` — * `true` - Attendees can answer questions or leave a comment in the question thread.
 * `false` - Attendees can not answer questions or leave a comment in the question thread

- **`attendees_can_upvote`**

 `boolean` — * `true` - Attendees can click the thumbs up button to bring popular questions to the
 top of the Q\&A window. * `false` - Attendees can not click the thumbs up button on questions.

- **`enable`**

 `boolean` — * `true` - Enable \[Q\&A\](https://support.zoom.com/hc/en/article?
 id=zm_kb\&sysparm_article=KB0065237) for meeting. * `false` - Disable Q\&A for meeting.

- **`question_visibility`**

 `string`, possible values: `answered`, `all` — Indicate whether you want attendees to be able to
 view answered questions only or view all questions. * `answered` - Attendees are able to view answered
 questions only. * `all` - Attendees are able to view all questions submitted in the Q\&A.

- **`registrants_confirmation_email`**

 `boolean` — Whether to send registrants an email confirmation. * `true` - Send a confirmation email.
 * `false` - Do not send a confirmation email.

- **`registrants_email_notification`**

 `boolean` — Whether to send registrants email notifications about their registration approval,
 cancellation, or rejection. * `true` - Send an email notification. * `false` - Do not send an email
 notification. Set this value to `true` to also use the `registrants\_confirmation\_email` parameter.

- **`registration_type`**

 `integer`, possible values: `1, 2, 3`, default: `1` — Registration type. Used for recurring meeting
 with fixed time only. `1` - Attendees register once and can attend any of the occurrences. `2` -
 Attendees need to register for each occurrence to attend. `3` - Attendees register once and can choose one
 or more occurrences to attend.

- **`request_permission_to_unmute_participants`**

 `boolean` — Whether to enable the \[**Request permission to unmute participants**\](
 https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting)
 setting. This option cannot be used together with `allow\_host\_control\_participant\_mute\_state`, only

```



one of the two can be enabled at a time.

- **resources**
  - `array` — The meeting's resources.
  - Items**
- **permission\_level**
  - `string`, possible values: `"editor"`, `"commenter"`, `"viewer"`, default: `"editor"` — The permission levels for users to access the whiteboard. `"editor"` - Users with link access can edit the board. `"commenter"` - Users with link access can comment on the board. `"viewer"` - Users with link access can view the board.
- **resource\_id**
  - `string` — The resource ID.
- **resource\_type**
  - `string`, possible values: `"whiteboard"` — The resource type.
- **show\_share\_button**
  - `boolean` — Show social share buttons on the meeting registration page. This setting only works for meetings that require `[registration]` (<https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-registration-for-a-meeting>).
- **sign\_language\_interpretation**
  - `object` — The meeting's `[sign language interpretation settings]` (<https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar>). Make sure to add the language in the web portal in order to use it in the API. See link for details. **Note:** If this feature is not enabled on the host's account, this setting will **not** be applied to the meeting.
  - **enable**
    - `boolean` — Whether to enable `[sign language interpretation]` (<https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar>) for the meeting.
  - **interpreters**
    - `array` — Information about the meeting's sign language interpreters.
    - Items**
    - **email**
      - `string`, format: `email` — The interpreter's email address.
    - **sign\_language**
      - `string` — The interpreter's sign language. To get this value, use the `[sign_language_interpretation]` object's `languages` and `custom_languages` values in the `[Get user settings]` (</api-reference/zoom-api/methods#operation/userSettings>) API response.
  - **summary\_template\_id**
    - `string` — The summary template ID used to generate a meeting summary based on a predefined template. To get available summary templates, use the `[Get user summary templates]` API. To enable this feature for your account, please `[contact Zoom Support]` (<https://support.zoom.com/hc/en>).
  - **use\_pmi**
    - `boolean` — Whether to use a `[Personal Meeting ID (PMI)]` (</docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi>) for the meeting. This field is only used for scheduled meetings (`2`) and recurring meetings with no fixed time (`3`).
  - **waiting\_room**
    - `boolean`, default: `false` — Enable waiting room.
  - **waiting\_room\_options**
    - `object` — Configuration settings for the meeting's waiting room.
    - **mode (required)**
      - `string`, possible values: `"follow_setting"`, `"custom"` — The waiting room behavior for this meeting.

\\* \`follow\\_setting\` - Use the Zoom web portal setting. \\* \`custom\` - Specify which participants should go into the waiting room.

- **\`who\_goes\_to\_waiting\_room\`**

\`string\`, possible values: "everyone", "users\_not\_in\_account", "users\_not\_in\_account\_or\_whitelisted\_domains", "users\_not\_on\_invite", "users\_not\_in\_org" — Which participants should be placed into the waiting room. Required if \`mode\` is set to \`custom\`. \\* \`everyone\` - Everyone. \\* \`users\\_not\\_in\\_account\` - Users not in your account. \\* \`users\\_not\\_in\\_account\\_or\\_whitelisted\\_domains\` - Users who are not in your account and not part of your whitelisted domains. \\* \`users\\_not\\_on\\_invite\` - Users not on the meeting invite. \\* \`users\\_not\\_in\\_org\` - Users not in your organization.

- **\`watermark\`**

\`boolean\`, default: false — Add a watermark when viewing a shared screen.

- **\`who\_can\_ask\_questions\`**

\`integer\`, possible values: 1, 2, 3, 4, 5 — Defines who can ask questions about this meeting's transcript. This field is applicable only when \`auto\\_start\\_ai\\_companion\\_questions\` is set to true. \\* 1 — All participants and invitees. \\* 2 — All participants only from when they join. \\* 3 — Only meeting host. \\* 4 — Participants and invitees in our organization. \\* 5 — Participants in our organization only from when they join.

- **\`who\_will\_receive\_summary\`**

\`integer\`, possible values: 1, 2, 3, 4 — Defines who will receive a summary after this meeting. This field is applicable only when \`auto\\_start\\_meeting\\_summary\` is set to true. \\* 1 — Only meeting host. \\* 2 — Only meeting host, co-hosts, and alternative hosts. \\* 3 — Only meeting host and meeting invitees in our organization. \\* 4 — All meeting invitees including those outside of our organization.

- **\`start\_time\`**

\`string\`, format: date-time — Meeting start time. When using a format like yyyy-MM-dd'T'HH:mm:ss'Z', always use GMT time. When using a format like yyyy-MM-dd'T'HH:mm:ss', use local time and specify the time zone. Only used for scheduled meetings and recurring meetings with a fixed time.

- **\`template\_id\`**

\`string\` — Unique identifier of the meeting template. [Schedule the meeting from a meeting template] (https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates#h\_86f06c9f-0852-4998-81c5-c83663c176fb). Retrieve this field's value by calling the [List meeting templates] (/docs/api/meetings/#tag/templates/get/users/{userId}/meeting\_templates) API.

- **\`timezone\`**

\`string\` — The timezone to assign to the \`start\\_time\` value. Only use this field for scheduled or recurring meetings with a fixed time. For a list of supported timezones and their formats, see our [timezone list] (/docs/api/references/abbreviations/#timezones).

- **\`topic\`**

\`string\` — Meeting topic.

- **\`tracking\_fields\`**

\`array\` — Tracking fields.

**Items:**

- **\`field\`**

\`string\` — Tracking fields type.

- **\`value\`**

\`string\` — Tracking fields value.

- **\`type\`**

\`integer\`, possible values: 1, 2, 3, 8, 10, default: 2 — The type of meeting. \\* 1 — An instant meeting. \\* 2 — A scheduled meeting. \\* 3 — A recurring meeting with no fixed time. \\* 8 — A recurring meeting with fixed time. \\* 10 — A screen share only meeting.

**Example:**

```
```json
{
```

```

"agenda": "My Meeting",
"duration": 60,
"password": "123456",
"pre_schedule": false,
"schedule_for": "jchill@example.com",
"recurrence": {
  "end_date_time": "2022-04-02T15:59:00Z",
  "end_times": 7,
  "monthly_day": 1,
  "monthly_week": 1,
  "monthly_week_day": 1,
  "repeat_interval": 1,
  "type": 1,
  "weekly_days": "1"
},
"settings": {
  "allow_multiple_devices": true,
  "alternative_hosts": "jchill@example.com;thill@example.com",
  "alternative_hosts_email_notification": true,
  "alternative_host_update_polls": true,
  "alternative_host_manage_meeting_summary": true,
  "alternative_host_manage_cloud_recording": false,
  "approval_type": 0,
  "approved_or_denied_countries_or_regions": {
    "approved_list": [
      "CX"
    ],
    "denied_list": [
      "CA"
    ],
    "enable": true,
    "method": "approve"
  },
  "audio": "telephony",
  "audio_conference_info": "test",
  "authentication_domains": "example.com",
  "authentication_exception": [
    {
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "join_url": "https://example.com/s/11111"
    }
  ],
  "authentication_name": "Sign in to Zoom",
  "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
  "auto_recording": "cloud",
  "auto_add_recording_to_video_management": {
    "enable": true,
    "channels": [
      {
        "channel_id": "Uyh5qeykTDiA66YQEYmFPg",
        "name": "Team Weekly Meetings"
      }
    ]
  },
  "breakout_room": {
    "enable": true,
    "rooms": [
      {
        "name": "room1",
        "participants": [
          "jchill@example.com"
        ]
      }
    ]
  },
  "calendar_type": 1,
  "close_registration": false,
  "contact_email": "jchill@example.com",
  "contact_name": "Jill Chill",
  "custom_keys": [
    {
      "key": "key1",
      "value": "value1"
    }
  ],
  "email_notification": true,
  "encryption_type": "enhanced_encryption",
  "focus_mode": true,
  "global_dial_in_countries": [

```

```

    "US"
  ],
  "global_dial_in_numbers": [
    {
      "city": "New York",
      "country": "US",
      "country_name": "US",
      "number": "+1 1000200200",
      "type": "toll"
    }
  ],
  "host_video": true,
  "jbh_time": 0,
  "join_before_host": true,
  "question_and_answer": {
    "enable": true,
    "allow_submit_questions": true,
    "allow_anonymous_questions": true,
    "question_visibility": "all",
    "attendees_can_comment": true,
    "attendees_can_upvote": true
  },
  "language_interpretation": {
    "enable": true,
    "interpreters": [
      {
        "email": "interpreter@example.com",
        "interpreter_languages": "English,French"
      }
    ]
  },
  "sign_language_interpretation": {
    "enable": true,
    "interpreters": [
      {
        "email": "interpreter@example.com",
        "sign_language": "American"
      }
    ]
  },
  "meeting_authentication": true,
  "meeting_invitees": [
    {
      "email": "jchil@example.com"
    }
  ],
  "mute_upon_entry": false,
  "participant_video": false,
  "private_meeting": false,
  "registrants_confirmation_email": true,
  "registrants_email_notification": true,
  "registration_type": 1,
  "show_share_button": true,
  "use_pmi": false,
  "waiting_room": false,
  "waiting_room_options": {
    "mode": "follow_setting",
    "who_goes_to_waiting_room": "everyone"
  },
  "watermark": false,
  "host_save_video_order": true,
  "internal_meeting": false,
  "continuous_meeting_chat": {
    "enable": true
  },
  "participant_focused_meeting": false,
  "push_change_to_calendar": false,
  "resources": [
    {
      "resource_type": "whiteboard",
      "resource_id": "X4Hy02w3QU0dskKofgb9Jg",
      "permission_level": "editor"
    }
  ],
  "auto_start_meeting_summary": false,
  "who_will_receive_summary": 1,
  "auto_start_ai_companion_questions": false,
  "who_can_ask_questions": 1,
  "summary_template_id": "1e1356ad",
  "device_testing": false,

```

```

    "request_permission_to_unmute_participants": true,
    "allow_host_control_participant_mute_state": false,
    "disable_participant_video": false,
    "email_in_attendee_report": true
  },
  "start_time": "2022-03-25T07:29:29Z",
  "template_id": "5Cj3ceXoSt06TGOVvIOVPA==",
  "timezone": "America/Los_Angeles",
  "topic": "My Meeting",
  "tracking_fields": [
    {
      "field": "field1",
      "value": "value1"
    }
  ],
  "type": 2
}

```

Responses

Status: 204 `HTTP Status Code: 204` Meeting updated.

Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 3161` Your user account is not allowed meeting hosting and scheduling capabilities. `Error Code: 300` The value that you entered in the `schedule_for` field is invalid. Enter a valid value and try again. `Error Code: 300` Invalid `enforce_login_domains`. Separate multiple domains with semicolons. `Error Code: 3000` Cannot access webinar information. `Error Code: 3000` Instant meetings do not support the `schedule_for` parameter, and you can't schedule an instant meeting for another user. `Error Code: 3000` Users in `{userId}` have been blocked from joining meetings and webinars. To unblock them, go to the `Settings` page in the Zoom web portal and update `Block users in specific domains from joining meetings and webinars`. `Error Code: 3000` You cannot schedule a meeting for `{userId}`. `Error Code: 3000` Prescheduling is only available for scheduled meetings (type 2) and recurring meetings with no fixed time (type 3). `Error Code: 3000` Unable to schedule for a user outside of your account for a meeting with continuous chat.

Status: 401 `HTTP Status Code: 401` Unauthorized `Error Code: 124` Invalid access token. `Error Code: 124` Access token has expired.

Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001` Meeting does not exist: `{meetingId}`.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rate-limits/>). `Error Code: 4001` You have reached the maximum per-second rate limit for this API. Try again later.

Get a meeting SIP URI with passcode

```

- Method: POST
- Path: /meetings/{meetingId}/sip_dialing
- Tags: Meetings

```

Get a meeting's SIP URI. The URI consists of the meeting ID, and may include the user-supplied passcode and participant identifier code. The API return data also includes additional fields to indicate whether the API caller has a valid Cloud Room Connector subscription, the participant identifier code from the URI, and the SIP URI validity period in seconds.

Prerequisites:

- The SIP URI is valid for 2 hours, or 7200 seconds, by default. After this period, the URI will expire and the API must be called again to retrieve a new one.

[Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write:sip_dialing`, `meeting:write:admin:sip_dialing`

[Granular Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write:sip_dialing`, `meeting:write:sip_dialing:admin`

[Rate Limit Label] (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

Request Body

Content-Type: application/json

```

- passcode

```

`string` — If customers desire that a passcode be embedded in the SIP URI dial string, they must supply the passcode. Zoom will not validate the passcode.

****Example:****

```
```json
{
 "passcode": "xxxx"
},
```,
```

Responses

Status: 200 `\*\*HTTP Status Code:\*\* \200\` Meeting's encoded SIP URI returned.

Content-Type: application/json

- ****`expire\_in`****

``integer``, format: ``int64`` — The number of seconds the encoded SIP URI is valid before it expires.

- ****`paid\_crc\_plan\_participant`****

``boolean`` — Whether the API caller has a CRC (Conference Room Connector) plan.

- ****`participant\_identifier\_code`****

``string`` — This value identifies the meeting participant. It is automatically embedded in the SIP URI if the API caller has a CRC (Conference Room Connector) plan.

- ****`sip\_dialing`****

``string`` — The meeting's encoded SIP URI.

****Example:****

```
```json
{
 "sip_dialing": "9678722567.xxxx...30qonrvgy@zoomcrc.com",
 "paid_crc_plan_participant": true,
 "participant_identifier_code": "30qonrvgy",
 "expire_in": 7200
},
```,
```

Status: 400 `\*\*HTTP Status Code:\*\* \400\` `\<br> Bad Request \*\*Error Code:\*\* \300\` `\<br> Invalid meeting ID. \<br> \*\*Error Code:\*\* \3000\` `\<br> The meeting's SIP URI does not exist: {meetingId}. \<br>`

Status: 404 `\*\*HTTP Status Code:\*\* \404\` `\<br> Not Found \*\*Error Code:\*\* \300\` `\<br> Meeting ID does not exist. \<br> \*\*Error Code:\*\* \3001\` `\<br> Meeting does not exist: {meetingId} \<br>`

Status: 429 `\*\*HTTP Status Code:\*\* \429\` `\<br> Too Many Requests. For more information, see \[rate limits]\(/docs/api/rest/rate-limits/).`

Update meeting status

- ****Method:**** ``PUT``

- ****Path:**** ``/meetings/{meetingId}/status``

- ****Tags:**** Meetings

Update the status of a meeting.

****Prerequisites:****

- Host user must have a Zoom Meetings Basic license or higher.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
``meeting:write:admin`,`meeting:write``

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
``meeting:update:status`,`meeting:update:status:admin``

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** ``LIGHT``

Request Body

Content-Type: application/json

- ****`action`****

``string``, possible values: ``"end", "recover"`` — ``\end\`` - End a meeting. ``\recover\`` - ``\[Recover]\``

(<https://support.zoom.us/hc/en-us/articles/360038297111-Recover-a-deleted-meeting>) a deleted meeting.

Example:

```
```json
{
 "action": "recover"
}
```
```

Responses

Status: 204 **HTTP Status Code:** 204 Meeting updated.

Status: 400 **HTTP Status Code:** 400 **Error Code:** 3000 **Message:** Bad Request Cannot access webinar info. **Error Code:** 3063 **Message:** Can not end on-premise user's meeting: {meetingId}. **Error Code:** 3161 **Message:** Meeting hosting and scheduling capabilities are not allowed for your user account.

Status: 404 **HTTP Status Code:** 404 **Error Code:** 3001 **Message:** Not Found Meeting does not exist: {meetingId}.

Status: 429 **HTTP Status Code:** 429 **Message:** Too Many Requests. For more information, see [\[rate limits\]](#) (</docs/api/rest/rate-limits/>).

Get past meeting details

```
- Method: GET
- Path: /past_meetings/{meetingId}
- Tags: Meetings
```

Get information about a past meeting.

Prerequisites

- The meeting must have ended before you can retrieve the data.
- You cannot access a meeting that occurred more than one year ago.

Scopes: (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): meeting:read:admin, meeting:read

Granular Scopes: (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): meeting:read:past_meeting, meeting:read:past_meeting:admin

Rate Limit Label: (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): LIGHT

Responses

Status: 200 **HTTP Status Code:** 200 Meeting information returned.

Content-Type: application/json

- ```
- dept
 string — The meeting host's department.
- duration
 integer — The meeting's duration, in minutes.
- end_time
 string, format: date-time — The meeting's end date and time.
- has_meeting_summary
 boolean — Whether the summary feature was used in the meeting.
- host_id
 string — The host's ID.
- id
 integer, format: int64 — The [meeting ID] (https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID).
- participants_count
 integer — The number of meeting participants.
```

- **source**

**string** — Whether the meeting was created directly through Zoom or via an API request: **\*** If the meeting was created via an OAuth app, this field returns the OAuth app's name. **\*** If the meeting was created via JWT or the Zoom Web Portal, this returns the **Zoom** value.

- **start\_time**

**string**, format: **date-time** — The meeting's start date and time.

- **topic**

**string** — The meeting's topic.

- **total\_minutes**

**integer** — The total number of minutes attended by the meeting's host and participants.

- **type**

**integer**, possible values: **0, 1, 2, 3, 4, 7, 8** — The meeting type. **0** - A prescheduled meeting. **1** - An instant meeting. **2** - A scheduled meeting. **3** - A recurring meeting with no fixed time. **4** - A **[personal meeting room]** (<https://support.zoom.us/hc/en-us/articles/201362843>). **7** - A **[PAC (personal audio conference)]** (<https://support.zoom.us/hc/en-us/articles/205172455-Hosting-a-Personal-Audio-Conference-PAC-meeting>) meeting. **8** - A recurring meeting with a fixed time.

- **user\_email**

**string**, format: **email** — The user's email address.

- **user\_name**

**string** — The user's display name.

- **uuid**

**string** — The meeting's UUID. You must **[double encode]** (<https://marketplace.zoom.us/docs/api-reference/using-zoom-apis/#meeting-id-and-uuid>) this value if the meeting UUID begins with a **/** character or contains the **/** character.

**Example:**

**json**

```
{
 "id": 5638296721,
 "uuid": "4444AAAiAAAAAiAiAiAi==",
 "duration": 60,
 "start_time": "2021-07-13T21:44:51Z",
 "end_time": "2021-07-13T23:00:51Z",
 "host_id": "x1yCzABCDEFg23HiJKl4mN",
 "dept": "Developers",
 "participants_count": 2,
 "source": "Zoom",
 "topic": "My Meeting",
 "total_minutes": 55,
 "type": 1,
 "user_email": "jchill@example.com",
 "user_name": "Jill Chill",
 "has_meeting_summary": false
}
```

**#### Status: 400** **HTTP Status Code:** **400** **Bad Request** **Error Code:** **300** **Cannot access meeting information.** **Error Code:** **200** **Only available for paid account:** {accountId}. **Error Code:** **12702** **Cannot access a meeting a year ago.**

**#### Status: 404** **HTTP Status Code:** **404** **Not Found** **Error Code:** **3001** **Meeting does not exist:** {meetingId}.

**#### Status: 429** **HTTP Status Code:** **429** **Too Many Requests.** For more information, see **[rate limits]** (</docs/api/rate-limits/>).

**## List past meeting instances**

- **Method:** **GET**

- **Path:** **/past\_meetings/{meetingId}/instances**

- **Tags:** **Meetings**

Return a list of past meeting instances.



**\*\*Prerequisites\*\***

- The meeting must have already occurred at least once. This endpoint only returns instances of meetings that have ended.
- You cannot retrieve instances for meetings that occurred more than 15 months ago.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `meeting:read:admin`, `meeting:read`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `meeting:read:list\_past\_instances`, `meeting:read:list\_past\_instances:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

**#### Responses**

**##### Status:** 200 **HTTP Status Code:** 200 **List of ended meeting instances returned.**

**##### Content-Type:** application/json

**\*\*All of:\*\***

- **\*\*`meetings`\*\***

`array` — List of ended meeting instances.

**\*\*Items:\*\***

**\*\*All of:\*\***

- **\*\*`start\_time`\*\***

`string`, format: `date-time` — Start time

- **\*\*`uuid`\*\***

`string` — Meeting UUID. Unique meeting ID. Each meeting instance will generate its own Meeting UUID (i.e., after a meeting ends, a new UUID will be generated for the next instance of the meeting). [\\[Double encode\]\(https://marketplace.zoom.us/docs/api-reference/using-zoom-apis/#meeting-id-and-uuid\)](https://marketplace.zoom.us/docs/api-reference/using-zoom-apis/#meeting-id-and-uuid) your UUID when using it for API calls if the UUID begins with a '/' or contains '/' in it.

**\*\*Example:\*\***

```
``json
{
 "meetings": [
 {
 "start_time": "2022-03-26T05:37:59Z",
 "uuid": "Vg8IdgluR5WDeWIkpJlElQ=="
 }
]
}
```

**##### Status:** 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Meeting does not exist: {meetingId}.**

**##### Status:** 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](https://marketplace.zoom.us/docs/api-reference/rate-limits/).

**### Get past meeting participants**

- **\*\*Method:\*\*** `GET`  
 - **\*\*Path:\*\*** `/past\_meetings/{meetingId}/participants`  
 - **\*\*Tags:\*\*** Meetings

Retrieve information on participants from a past meeting. Note the API doesn't return results if there's only one participant in a meeting.

**\*\*Prerequisites:\*\***

- Paid account on a Pro or higher plan.

**\*\*Note:\*\*** Please double encode your UUID when using this API if the UUID begins with a '/' or contains '/' in it.

**\*\*NOTE:\*\*** After meetings with hundreds of participants, the attendance data takes some time to be generated. If you receive a duration of 0 for users' time in the meeting, you may have called the endpoint before the data is fully processed. Implement a short delay or retry logic before fetching participant data.

```

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:admin`,`meeting:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`meeting:read:list_past_participants`,`meeting:read:list_past_participants:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`

```

#### #### Responses

##### Status: 200 `\*\*HTTP Status Code:\*\*` `200` Meeting participants' report returned.

##### Content-Type: application/json

**All of:**

- **`next_page_token`**

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- **`page_count`**

`integer` — The number of pages returned for the request made.

- **`page_size`**

`integer`, default: `30` — The number of records returned within a single API call.

- **`total_records`**

`integer` — The number of all records available across pages.

\* **`participants`**

`array` — Array of meeting participant objects.

**Items:**

- **`duration`**

`integer` — Participant duration, in seconds, calculated by subtracting the `leave_time` from the `join_time` for the `user_id`. If the participant leaves and rejoins the same meeting, they will be assigned a different `user_id` and Zoom displays their new duration in a separate object. Note that because of this, the duration may not reflect the total time the user was in the meeting.

- **`failover`**

`boolean` — Indicates if failover happened during the meeting.

- **`id`**

`string` — Universally unique identifier of the Participant. It is the same as the User ID of the participant if the participant joins the meeting by logging into Zoom. If the participant joins the meeting without logging in, the value of this field will be blank.

- **`internal_user`**

`boolean`, default: `false` — Whether the meeting participant is an internal user.

- **`join_time`**

`string`, format: `date-time` — Participant join time.

- **`leave_time`**

`string`, format: `date-time` — Participant leave time.

- **`name`**

`string` — Participant display name.

- **`registrant_id`**

`string` — The participant's unique registrant ID. This field only returns if you pass the `registrant_id` value for the `include_fields` query parameter. This field does not return if the `type` query parameter is the `live` value.

- **status**

string, possible values: "in\_meeting", "in\_waiting\_room" — The participant's status. \\* \in\\_meeting\\* - In a meeting. \\* \in\\_waiting\\_room\\* - In a waiting room.

- **user\_email**

string — Email address of the user. If the participant is \\*not\\* part of the host's account, this returns an empty string value, with some exceptions. See [Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

- **user\_id**

string — Participant ID. This is a unique ID assigned to the participant joining a meeting and is valid for that meeting only.

**Example:**

```
``json
{
 "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
 "page_count": 1,
 "page_size": 30,
 "total_records": 1,
 "participants": [
 {
 "id": "30R7kT7bTIKSNUFEuH_Qlg",
 "name": "Jill Chill",
 "user_id": "27423744",
 "registrant_id": "_f08HhPJS82MIVLuuFaJPg",
 "user_email": "jchill@example.com",
 "join_time": "2022-03-23T06:58:09Z",
 "leave_time": "2022-03-23T07:02:28Z",
 "duration": 259,
 "failover": false,
 "status": "in_meeting",
 "internal_user": false
 }
]
}
```

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`200\` \<br> Only available for paid account: {accountId} \<br> \\*\\*Error Code:\\*\\* \`12702\` \<br> Can not access a meeting a year ago. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Meeting does not exist: {meetingId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

**List past meetings' Q&A**

- **Method:** GET

- **Path:** /past\_meetings/{meetingId}/qa

- **Tags:** Meetings

List Q&A of a specific meeting.

The question & answer (Q&A) feature for Zoom Meetings lets attendees ask questions during a meeting and lets the other attendees answer those questions.

**Prerequisites:**

- Q&A must be enabled for the meeting.
- The meeting must have ended before you can retrieve the data.
- You cannot retrieve Q&A data for meetings that occurred more than 15 months ago.

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): \\*meeting:read:admin\\*, \\*meeting:read\\*

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): \\*meeting:read:past\_qa\\*, \\*meeting:read:past\_qa:admin\\*

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): MEDIUM

**Responses**

##### Status: 200 \\*\\*HTTP Status Code:\\*\\* \`200\` \\*\\*OK\\*\\* Q&A returned successfully.

##### Content-Type: application/json

- **id**

**integer**, format: **int64** — \[Meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-): Unique identifier of the meeting in **long** format, represented as int64 data type in JSON, also known as the meeting number.

- **questions**

**array**

**Items:**

- **email**

**string** — The user's email address. If the user is **not** part of the host's account, this returns an empty string value, with some exceptions. See \[Email address display rules]\(https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

- **name**

**string** — The user's name. If **anonymous** option is enabled for the Q&A, the participant's information is kept anonymous and the value of **name** field is **Anonymous Attendee**.

- **question\_details**

**array**

**Items:**

- **answer**

**string** — An answer submitted for the question. The value is 'live answered' if this is a live answer.

- **question**

**string** — A question asked during the Q&A.

- **start\_time**

**string**, format: **date-time** — The meeting's start time.

- **uuid**

**string** — Meeting UUID.

**Example:**

```
```json
{
  "id": 95204914252,
  "questions": [
    {
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "question_details": [
        {
          "answer": "Good",
          "question": "How are you?"
        }
      ]
    }
  ],
  "start_time": "2022-03-26T06:44:14Z",
  "uuid": "Bznyg8KZTdCVbQxvS/oZ7w=="
}
```
```

##### Status: 401 **HTTP Status Code:** 401 **Unauthorized** **Error Code:** 1010   
 User does not belong to this account:{accountId}.

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001   
 Meeting ID is invalid or not end.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests**. For more information, see \[rate limits]\(docs/api/rest/rate-limits/).

### ### List meetings

```
- **Method:** `GET`
- **Path:** `/users/{userId}/meetings`
- **Tags:** Meetings
```

List a meeting host user's scheduled meetings. For user-level apps, pass [the `me` value] (/docs/api/rest/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter.

#### \*\*Prerequisites:\*\*

- This API **only** supports scheduled meetings. This API does not return information about instant meetings.
- This API only returns a user's [unexpired meetings](https://support.zoom.us/hc/en-us/articles/201362373-Meeting-ID#h\_c73f9b08-c1c0-4a1a-b538-e01ebb98e844).
- When `type` is set to `upcoming`, `upcoming\_meetings`, or `previous\_meetings`, only a maximum of 6 months of meeting data will be returned.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`meeting:read:admin`, `meeting:read`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`meeting:read:list\_meetings`, `meeting:read:list\_meetings:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

### #### Responses

##### Status: 200 \\*\*HTTP Status Code:\*\*\`200\` List of meeting objects returned.

##### Content-Type: application/json

#### \*\*All of:\*\*

- **next\_page\_token**

`string` — Use the next page token to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **page\_count**

`integer` — The number of pages returned for the request made.

- **page\_number**

`integer`, default: `1` — The page number of the current results.

- **page\_size**

`integer`, default: `30` — The number of records returned with a single API call.

- **total\_records**

`integer` — The total number of all the records available across pages.

**meetings**

`array` — List of meeting objects.

**Items:**

**All of:**

- **agenda**

`string` — Meeting description. The length of agenda gets truncated to 250 characters when you list all of a user's meetings. To view a meeting's complete agenda, or to retrieve details for a single meeting, use the \[\*Get a meeting\*\](/docs/api-reference/zoom-api/methods#operation/meeting) API.

- **created\_at**

`string`, format: `date-time` — Time of creation.

- **duration**

`integer` — Meeting duration.

- **host\_id**

``string`` — ID of the user who is set as the meeting's host.

- `**`id`**`

``integer``, format: ``int64`` — Meeting ID - also known as the meeting number in long (int64) format.

- `**`join_url`**`

``string`` — URL using which participants can join a meeting.

- `**`pmi`**`

``string`` — `\[Personal meeting ID]\(\/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi)`. This field is only returned if PMI was used to schedule the meeting.

- `**`start_time`**`

``string``, format: ``date-time`` — Meeting start time.

- `**`timezone`**`

``string`` — Timezone to format the meeting start time.

- `**`topic`**`

``string`` — Meeting topic.

- `**`type`**`

``integer``, possible values: ``1, 2, 3, 8`` — Meeting types. ``1`` - Instant meeting. ``2`` - Scheduled meeting. ``3`` - Recurring meeting with no fixed time. ``8`` - Recurring meeting with fixed time.

- `**`uuid`**`

``string`` — Unique Meeting ID. Each meeting instance will generate its own Meeting UUID.

**Example:**

```
```json
{
  "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
  "page_count": 1,
  "page_number": 1,
  "page_size": 30,
  "total_records": 1,
  "meetings": [
    {
      "agenda": "My Meeting",
      "created_at": "2022-03-23T05:31:16Z",
      "duration": 60,
      "host_id": "30R7kT7bTIKSNUFEuH_Qlg",
      "id": 97763643886,
      "join_url": "https://example.com/j/11111",
      "pmi": "97891943927",
      "start_time": "2022-03-23T06:00:00Z",
      "timezone": "America/Los_Angeles",
      "topic": "My Meeting",
      "type": 2,
      "uuid": "aDYlohsHRtCd4i1uC2+hA=="
    }
  ]
}
```

Status: 400 `\*\*HTTP Status Code:\*\* `400`` `\<br>` Bad Request `\*\*Error Code:\*\* `3161`` `\<br>` Meeting hosting and scheduling capabilities are not allowed for your user account. `\<br>`

Status: 403 `\*\*HTTP Status Code:\*\* `403`` `\<br>` Forbidden `\*\*Error Code:\*\* `2306`` `\<br>` Not allowed to view meetings scheduled for others. To use this feature, enable the `\*\*Display meetings scheduled for others\*` setting in the `\*\*Account Settings\*` page of the Zoom web portal. `\<br>`

Status: 404 `\*\*HTTP Status Code:\*\* `404`` `\<br>` Not Found `\*\*Error Code:\*\* `1001`` `\<br>` User does not exist: {userId}. `\<br>`

Status: 429 `\*\*HTTP Status Code:\*\* `429`` `\<br>` Too Many Requests. For more information, see `\[rate limits](https://developers.zoom.us/docs/api/rate-limits/)`.

Create a meeting

- `**Method:**` ``POST``

```
- **Path:** `/users/{userId}/meetings`
- **Tags:** Meetings
```

[Creates a meeting](https://support.zoom.us/hc/en-us/articles/201362413-Scheduling-meetings) for a user. For user-level apps, pass [the `me` value](/docs/api/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter.

****Prerequisites:****

- A meeting's `start\_url` value is the URL a host or an alternative host can use to start a meeting. The `start\_url` value's expiration time is **two hours** for all regular users.
- For `custCreate` meeting hosts - users created with the `custCreate` parameter via the **[Create users](/docs/api/users/#tag/users/POST/users)** API - the expiration time of the `start\_url` parameter is **90 days** from the generation of the `start\_url`.
- For security reasons, the recommended way to programmatically get the updated `start\_url` value after expiry is to call the **[Get a meeting](/docs/api/meetings/#tag/meetings/GET/meetings/{meetingId})** API. Refer to the `start\_url` value in the response.
- **100 requests per day**. The rate limit is applied against the `userId` of the **meeting host** used to make the request.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`meeting:write:admin`, `meeting:write`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`meeting:write:meeting`, `meeting:write:meeting:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

Request Body

Content-Type: application/json

- **`agenda`**

`string` — The meeting's agenda. This value has a maximum length of 2,000 characters.

- **`default\_password`**

`boolean`, default: `true` — Whether to automatically generate a passcode for the meeting when no passcode is provided and the user's **[Require a passcode when scheduling new meetings](https://support.zoom.us/hc/en-us/articles/115005269866-Using-Tiered-Settings#locked)** setting is enabled. Defaults to `true`. When set to `false`, meetings will only have a passcode if one is explicitly provided.

- **`duration`**

`integer`, default: `60` — The meeting's scheduled duration, in minutes. This field is used for **[2] scheduled meetings and [8] recurring meetings with a fixed time**. The value must be between 1 and 1440 minutes, which is equivalent to 24 hours.

- **`password`**

`string` — The meeting passcode. By default, it can be up to 10 characters in length and may contain alphanumeric characters as well as special characters such as !, @, #, etc. **[Note]:** - If the account owner or administrator has configured **[Passcode Requirement](https://support.zoom.us/hc/en-us/articles/201362413-Scheduling-meetings)**, the passcode **must** meet those requirements. You can retrieve the requirements using the **[Get user settings](/docs/api/users/#tag/users/GET/users/{userId}/settings)** API or the **[Get account settings](/docs/api/accounts/#tag/accounts/GET/accounts/{accountId}/settings)** API. - If the **[Require a passcode when scheduling new meetings]** user setting is enabled and **[default_password]** is not explicitly set to `false`, a passcode will be automatically generated when one is not provided. - If the **[Require a passcode when scheduling new meetings]** setting is enabled and **[locked](https://support.zoom.us/hc/en-us/articles/115005269866-Using-Tiered-Settings#locked)** for the user, a passcode will be automatically generated when one is not provided.

- **`pre\_schedule`**

`boolean`, default: `false` — Whether to create a prescheduled meeting via the **[GSuite app](https://support.zoom.us/hc/en-us/articles/360020187492-Zoom-for-GSuite-add-on)**. This **only** supports the meeting **type** value of **[2] scheduled meetings and [3] recurring meetings with no fixed time**. **[true]** - Create a prescheduled meeting. **[false]** - Create a regular meeting.

- **`recurrence`**

`object` — The recurrence object. Use this object only for a meeting with type **[8]**, a recurring meeting with a fixed time.

- **`type` (required)**

`integer`, possible values: `1, 2, 3` — The recurrence meeting types. **[1]** - Daily. **[2]** - Weekly. **[3]** - Monthly.

```

- **`end_date_time`**

  `string`, format: `date-time` — This field selects the final date when the meeting will recur before it is canceled. Should be in UTC time, such as 2017-11-25T12:00:00Z. Cannot be used with `end_times`.

- **`end_times`**

  `integer`, default: `1` — This field selects how many times the meeting should recur before it is canceled. If `end_times` is set to 0, it means there is no end time. The maximum number of recurring is 60. Cannot be used with `end_date_time`.

- **`monthly_day`**

  `integer`, default: `1` — This field is only for scheduling a recurring meeting of type 3. It states the day in a month when the meeting should recur. The value range is from `1` to `31`. For the meeting to recur on 23rd of each month, provide `23` as this field's value and `1` as the repeat_interval field's value. To have the meeting recur every three months on 23rd of the month, change the repeat_interval field value to `3`.

- **`monthly_week`**

  `integer`, possible values: `-1, 1, 2, 3, 4` — This field is only if only for scheduling a recurring meeting of type 3. It states the week of the month when the meeting should recur. If you use this field, you must also use the monthly_week_day field to state the day of the week when the meeting should recur. -1 - Last week of the month. 1 - First week of the month. 2 - Second week of the month. 3 - Third week of the month. 4 - Fourth week of the month.

- **`monthly_week_day`**

  `integer`, possible values: `1, 2, 3, 4, 5, 6, 7` — This field is only if only for scheduling a recurring meeting of type 3. It states a specific day in a week when the monthly meeting should recur. To use this field, you must also use the monthly_week field. 1 - Sunday. 2 - Monday. 3 - Tuesday. 4 - Wednesday. 5 - Thursday. 6 - Friday. 7 - Saturday.

- **`repeat_interval`**

  `integer` — This field defines the interval when the meeting should recur. For instance, to schedule a meeting that recurs every two months, set this field's value as `2` and the value of the type parameter as `3`. For a daily meeting, the maximum number of recurrences is `99` days. For a weekly meeting, the maximum is `50` weeks. For a monthly meeting, the maximum is `10` months.

- **`weekly_days`**

  `string`, possible values: `"1", "2", "3", "4", "5", "6", "7"`, default: `"1"` — This field is required if you're scheduling a recurring meeting of type `2`. It states the days of the week when the meeting should repeat. This field's value could be a number between `1` to `7` in string format. For instance, if the meeting should recur on Sunday, provide `1` as this field's value. Note: To set the meeting to occur on multiple days of a week, provide comma separated values for this field. For instance, if the meeting should recur on Sundays and Tuesdays, provide `1,3` as this field's value. 1 - Sunday. 2 - Monday. 3 - Tuesday. 4 - Wednesday. 5 - Thursday. 6 - Friday. 7 - Saturday.

- **`schedule_for`**

  `string` — The email address or user ID of the user to schedule a meeting for.

- **`settings`**

  `object` — Information about the meeting's settings.

- **`additional_data_center_regions`**

  `array` — This field adds additional meeting [data center regions] (https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars). Provide this value as an array of [country codes] (/docs/api/references/abbreviations/#countries) for the countries available as data center regions in the [Account Profile] (https://zoom.us/account/setting) interface but have been opted out of in the [user settings] (https://zoom.us/profile). For example, the data center regions selected in your [Account Profile] (https://zoom.us/account) are Europe, Hong Kong SAR, Australia, India, Japan, China, United States, and Canada. However, in the [My Profile] (https://zoom.us/profile) settings, you did not select India and Japan for meeting and webinar traffic routing. To include India and Japan as additional data centers, use the [IN, TY] value for this field.

  Items:

  `string`

- **`allow_host_control_participant_mute_state`**

```


``boolean`` — Whether to allow the host and co-hosts to fully control the mute state of participants. If not provided, the default value will be based on the user's setting. This option cannot be used together with ``request\_permission\_to\_unmute\_participants``, only one of the two can be enabled at a time.

- `**`allow_multiple_devices`**`

``boolean`` — Whether to allow attendees to join a meeting from multiple devices. This setting is only applied to meetings with registration enabled.

- `**`alternative_host_manage_cloud_recording`**`

``boolean`` — Whether to allow an alternative host to manage meeting cloud recordings.

- `**`alternative_host_manage_meeting_summary`**`

``boolean`` — Whether to allow an alternative host to manage meeting summaries.

- `**`alternative_host_update_polls`**`

``boolean`` — Whether the ``Allow alternative hosts to add or edit polls`` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `**`alternative_hosts`**`

``string`` — A semicolon-separated list of the meeting's alternative hosts' email addresses or IDs.

- `**`alternative_hosts_email_notification`**`

``boolean``, default: ``true`` — Whether to send email notifications to alternative hosts. This value defaults to ``true``.

- `**`approval_type`**`

``integer``, possible values: ``0``, ``1``, ``2``, default: ``2`` — Enable meeting registration approval. ``0`` — Automatically approve registration. ``1`` — Manually approve registration. ``2`` — No registration required. This value defaults to ``2``.

- `**`approved_or_denied_countries_or_regions`**`

``object`` — The list of approved or blocked users from specific countries or regions who can join the meeting.

- `**`approved_list`**`

``array`` — The list of approved countries or regions.

`**Items:**`

``string``

- `**`denied_list`**`

``array`` — The list of blocked countries or regions.

`**Items:**`

``string``

- `**`enable`**`

``boolean`` — Whether to enable the ``Approve or block entry for users from specific countries/regions`` (<https://support.zoom.us/hc/en-us/articles/360060086231-Approve-or-block-entry-for-users-from-specific-countries-regions>) setting.

- `**`method`**`

``string``, possible values: ``approve``, ``deny`` — Whether to allow or block users from specific countries or regions. ``approve`` — Allow users from specific countries or regions to join the meeting. If you select this setting, include the approved countries or regions in the ``approved\_list`` field. ``deny`` — Block users from specific countries or regions from joining the meeting. If you select this setting, include the blocked countries or regions in the ``denied\_list`` field.

- `**`audio`**`

``string``, possible values: ``both``, ``telephony``, ``voip``, ``thirdParty``, default: ``both`` — How participants join the audio portion of the meeting. ``both`` — Both telephony and VoIP. ``telephony`` — Telephony only. ``voip`` — VoIP only. ``thirdParty`` — Third party audio conference.

- `**`audio_conference_info`**`

`string` — Third party audio conference information.

- **`authentication\_domains`**

`string` — The meeting's authenticated domains. Only Zoom users whose email address contains an authenticated domain can join the meeting. Comma-separate multiple domains or use a wildcard for listing domains.

- **`authentication\_exception`**

`array` — A list of participants who can bypass meeting authentication. These participants will receive a unique meeting invite.

Items:

- **`email`**

`string`, format: `email` — The participant's email address.

- **`name`**

`string` — The participant's name.

- **`authentication\_option`**

`string` — If the `\meeting\authentication\` value is `\true\`, the type of authentication required for users to join a meeting. To get this value, use the `\authentication\options\` array's `\id\` value in the `\[*\*Get user settings\*\]` ([/docs/api-reference/zoom-api/methods#operation/userSettings](https://developers.zoom.us/docs/api-reference/zoom-api/methods#operation/userSettings)) API response.

- **`auto\_add\_recording\_to\_video\_management`**

`object` — Automatically add meeting recordings to a video channel in video management. To enable this feature for your account, please [contact Zoom Support](https://support.zoom.us/hc/en-us) (<https://support.zoom.us/hc/en-us>).

- **`enable` (required)**

`boolean`, default: `false` — Whether to automatically add the meeting recording to video management.

- **`channels`**

`array` — List of video management channels where the meeting recording will be added.

Items:

- **`channel\_id` (required)**

`string` — The unique ID of a video management channel.

- **`name`**

`string` — The name of the video management channel.

- **`auto\_recording`**

`string`, possible values: `"local"`, `"cloud"`, `"none"`, default: `"none"` — The automatic recording settings. `\*\local\` - Record the meeting locally. `\*\cloud\` - Record the meeting to the cloud. `\*\none\` - Auto-recording disabled. This value defaults to `"none"`.

- **`auto\_start\_ai\_companion\_questions`**

`boolean` — Whether to automatically start AI Companion questions. If not provided, the default value will be based on the user's setting.

- **`auto\_start\_meeting\_summary`**

`boolean` — Whether to automatically start a meeting summary. If not provided, the default value will be based on the user's setting.

- **`breakout\_room`**

`object` — The `\[pre-assigned breakout rooms\]` (<https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms>) settings.

- **`enable`**

`boolean` — Whether to enable the `\[*\*Breakout Room pre-assign\*\]` (<https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms>) option.

- **`rooms`**

```

`array` — Information about the breakout rooms.

**Items:**

- **`name`**

  `string` — The breakout room's name.

- **`participants`**

  `array` — The email addresses of the participants to assign to the breakout room.

  **Items:**

  `string`

- **`calendar_type`**

  `integer`, possible values: `1, 2` — The type of calendar integration used to schedule the meeting. \*
  \1\ - \[Zoom Outlook add-in]\(https://support.zoom.us/hc/en-us/articles/360031592971-Getting-started-
  with-Outlook-plugin-and-add-in) \* \2\ - \[Zoom for Google Workspace add-on]\
  (https://support.zoom.us/hc/en-us/articles/360020187492-Using-the-Zoom-for-Google-Workspace-add-on) Works
  with the \private_meeting\ field to determine whether to share details of meetings or not.

- **`close_registration`**

  `boolean`, default: `false` — Whether to close registration after the event date. This value defaults
  to `false`.

- **`cn_meeting`**

  `boolean`, default: `false` — Whether to host the meeting in China (CN). This value defaults to
  `false`.

- **`contact_email`**

  `string` — The contact email address for meeting registration.

- **`contact_name`**

  `string` — The contact name for meeting registration.

- **`continuous_meeting_chat`**

  `object` — Information about the \*\*Enable continuous meeting chat\*\* feature. This setting only
  applies to scheduled and recurring meetings, types \2\, \3\, and \8\. It is \*\*not supported\*\* for
  type \1\ instant meetings or type \10\ screen share only meetings.

  - **`auto_add_invited_external_users`**

    `boolean` — Whether to enable the \*\*Automatically add invited external users\*\* setting.

  - **`auto_add_meeting_participants`**

    `boolean` — Whether to enable the \*\*Automatically add meeting participants\*\* setting.

  - **`enable`**

    `boolean` — Whether to enable the \*\*Enable continuous meeting chat\*\* setting. The default value
    is based on user settings. When the \*\*Enable continuous meeting chat\*\* setting is enabled, the default
    value is true. When the setting is disabled, the default value is false.

  - **`device_testing`**

    `boolean`, default: `false` — Enable the device testing.

  - **`disable_participant_video`**

    `boolean`, default: `false` — Whether to disable the participant video during meeting. To enable this
    feature for your account, please \[contact Zoom Support]\(https://support.zoom.us/hc/en-us).

  - **`email_in_attendee_report`**

    `boolean` — Whether to include authenticated guest's email addresses in meetings' attendee reports.

  - **`email_notification`**

    `boolean`, default: `true` — Whether to send email notifications to \[alternative hosts]\
    (https://support.zoom.us/hc/en-us/articles/208220166) and \[users with scheduling privileges]\

```

(<https://support.zoom.us/hc/en-us/articles/201362803-Scheduling-privilege>). This value defaults to `\`true\``.

- `**`encryption_type`**`

``string``, possible values: ``"enhanced_encryption", "e2ee"`` — The type of `\[end-to-end (E2EE) encryption]`(<https://support.zoom.us/hc/en-us/articles/360048660871>) to use for the meeting. `\[*`enhanced_encryption` - Enhanced encryption. Encryption is stored in the cloud when you enable this option. \[*`e2ee` - End-to-end encryption. The encryption key is stored on your local device and \[*cannot\[* be obtained by anyone else. When you use E2EE encryption, \[certain features]`(<https://support.zoom.us/hc/en-us/articles/360048660871>), such as cloud recording or phone and SIP/H.323 dial-in, are `\[*disabled\[*`.

- `**`focus_mode`**`

``boolean`` — Whether to enable the `\[*Focus Mode\[* feature]`(<https://support.zoom.us/hc/en-us/articles/360061113751-Using-focus-mode>) when the meeting starts.

- `**`global_dial_in_countries`**`

``array`` — A list of available global dial-in countries.

`**Items:**`

``string``

- `**`host_save_video_order`**`

``boolean`` — Whether the `\[*Allow host to save video order\[* feature` is enabled.

- `**`host_video`**`

``boolean`` — Whether to start meetings with the host video on.

- `**`in_meeting`**`

``boolean``, default: ``false`` — Whether to host the meeting in India (IN). This value defaults to `\`false\``.

- `**`internal_meeting`**`

``boolean``, default: ``false`` — Whether to set the meeting as an internal meeting.

- `**`jbh_time`**`

``integer``, possible values: ``0, 5, 10, 15`` — If the value of the `\`join_before_host\`` field is `\`true\``, this field indicates the time limits when a participant can join a meeting before the meeting's host. `\[*`0` - Allow the participant to join the meeting at anytime. \[*`5` - Allow the participant to join 5 minutes before the meeting's start time. \[*`10` - Allow the participant to join 10 minutes before the meeting's start time. \[*`15` - Allow the participant to join 15 minutes before the meeting's start time.`

- `**`join_before_host`**`

``boolean``, default: ``false`` — Whether participants can join the meeting before its host. This field is only used for scheduled meetings (`\`2\``) or recurring meetings (`\`3\`` and `\`8\``). This value defaults to `\`false\``. If the `\[*Waiting Room\[* feature]`(<https://support.zoom.us/hc/en-us/articles/115000332726-Waiting-Room>) is enabled, this setting is `\[*disabled\[*`.

- `**`language_interpretation`**`

``object`` — The meeting's `\[language interpretation settings]`(https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details. `\[*Note\[* This feature is only available for certain Meeting add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will \[*not\[* be applied to the meeting.`

- `**`enable`**`

``boolean`` — Whether to enable `\[language interpretation]`(https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768) for the meeting. If not provided, the default value will be based on the user's setting.

- `**`interpreters`**`

``array`` — Information about the meeting's language interpreters.

`**Items:**`

- `**`email`**`

``string``, format: ``email`` — The interpreter's email address.

- `**`interpreter_languages`**`

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the `\\language_interpretation\\`` object's `\\languages\\`` and `\\custom_languages\\`` values in the `\\[*\\`Get user settings\\`*\\`]` (`/docs/api/users/#tag/users/GET/users/{userId}/settings`) API response. `\\[*\\_languages\\`*\\`]`: System-supported languages include `\\English\\``, `\\Chinese\\``, `\\Japanese\\``, `\\German\\``, `\\French\\``, `\\Russian\\``, `\\Portuguese\\``, `\\Spanish\\``, and `\\Korean\\``. `\\[*\\_custom\\_languages\\`*\\`]`: User-defined languages added by the user. For example, an interpreter translating between English and French should use `\\English,French\\``.

- `**`languages`**`

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: `\\US\\`` (English), `\\CN\\`` (Chinese), `\\JP\\`` (Japanese), `\\DE\\`` (German), `\\FR\\`` (French), `\\RU\\`` (Russian), `\\PT\\`` (Portuguese), `\\ES\\`` (Spanish), and `\\KR\\`` (Korean). For example, to set an interpreter translating from English to Chinese, use `\\US,CN\\``.

- `**`meeting_authentication`**`

``boolean`` — If true, only `\\[authenticated]\\``(`https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars`) users can join the meeting.

- `**`meeting_invitees`**`

``array`` — A list of the meeting's invitees.

`**Items:**`

- `**`email`**`

``string``, format: ``email`` — The invitee's email address.

- `**`mute_upon_entry`**`

``boolean``, default: ``false`` — Whether to mute participants upon entry.

- `**`participant_focused_meeting`**`

``boolean``, default: ``false`` — Whether to set the meeting as a participant focused meeting.

- `**`participant_video`**`

``boolean`` — Whether to start meetings with the participant video on.

- `**`private_meeting`**`

``boolean`` — Whether to set the meeting as private.

- `**`push_change_to_calendar`**`

``boolean``, default: ``false`` — Whether to push meeting changes to the calendar. To enable this feature, configure the `\\[*\\_Configure Calendar and Contacts Service\\`*\\`]` in the user's profile page of the Zoom web portal and enable the `\\[*\\_Automatically sync Zoom calendar events information bi-directionally between Zoom and integrated calendars\\`*\\`]` setting in the `\\[*\\_Settings\\`*\\`]` page of the Zoom web portal. `\\[*_true\\`` - Push meeting changes to the calendar. `\\[*\\_false\\`` - Do not push meeting changes to the calendar.

- `**`question_and_answer`**`

``object`` — `\\[Q&A]\\``(`https://support.zoom.com/hc/en/article?id=zm\\_kb\\&sysparm\\_article=KB0065237`) for meeting.

- `**`allow_anonymous_questions`**`

``boolean`` — `\\[*_true\\`` - Allow participants to send questions without providing their name to the host, co-host, and panelists. `\\[*\\_false\\`` - Do not allow anonymous questions. Not supported for simulative meeting.

- `**`allow_submit_questions`**`

``boolean`` — `\\[*_true\\`` - Allow participants to submit questions. `\\[*\\_false\\`` - Don't allow participants to submit questions.

- `**`attendees_can_comment`**`

``boolean`` — `\\[*_true\\`` - Attendees can answer questions or leave a comment in the question thread. `\\[*\\_false\\`` - Attendees can not answer questions or leave a comment in the question thread

```

- **`attendees_can_upvote`**

  `boolean` — \* \true\ - Attendees can select the thumbs up button to bring popular questions to the top of the Q&A window. \* \false\ - Attendees can't select the thumbs up button on questions.

- **`enable`**

  `boolean` — \* \true\ - Enable \[Q&A](https://support.zoom.com/hc/en/article?id=zm\kb\&sysparm\article=KB0065237) for meeting. \* \false\ - Disable Q&A for meeting. If not provided, the default value will be based on the user's setting.

- **`question_visibility`**

  `string`, possible values: "answered", "all" — Indicate whether you want to allow attendees to be able to view only answered questions or all questions. \* \answered\ - Attendees are able to view answered questions only. \* \all\ - Attendees are able to view all questions submitted in the Q&A.

- **`registrants_confirmation_email`**

  `boolean` — Whether to send registrants an email confirmation. \* \true\ - Send a confirmation email. \* \false\ - Do not send a confirmation email.

- **`registrants_email_notification`**

  `boolean` — Whether to send registrants email notifications about their registration approval, cancellation, or rejection. \* \true\ - Send an email notification. \* \false\ - Do not send an email notification. Set this value to \true\ to also use the \registrants\confirmation\email\ parameter.

- **`registration_type`**

  `integer`, possible values: 1, 2, 3, default: 1 — The meeting's registration type. \* \1\ - Attendees register once and can attend any meeting occurrence. \* \2\ - Attendees must register for each meeting occurrence. \* \3\ - Attendees register once and can select one or more meeting occurrences to attend. This field is only for recurring meetings with fixed times (\8\). This value defaults to \1\.
```

```

- **`request_permission_to_unmute_participants`**

  `boolean`, default: false — Whether to enable the \[*Request permission to unmute participants\*](https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting) setting. This option cannot be used together with \allow\host\control\participant\mute\state\, only one of the two can be enabled at a time.

- **`resources`**

  `array` — The meeting's resources.

  **Items:**

- **`permission_level`**

  `string`, possible values: "editor", "commenter", "viewer", default: "editor" — The permission levels for users to access the whiteboard. \* \editor\ - Users with link access can edit the board. \* \commenter\ - Users with link access can comment on the board. \* \viewer\ - Users with link access can view the board.

- **`resource_id`**

  `string` — The resource ID.

- **`resource_type`**

  `string`, possible values: "whiteboard" — The resource type.

- **`show_join_info`**

  `boolean` — Whether to show the meeting's join information on the registration confirmation page. This setting is only applied to meetings with registration enabled.

- **`show_share_button`**

  `boolean` — Whether to include social media sharing buttons on the meeting's registration page. This setting is only applied to meetings with registration enabled.

- **`sign_language_interpretation`**

  `object` — The meeting's \[sign language interpretation settings](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar). Make sure to add the language in the web portal in order to use it in the API. See link for details. \*Note:\* If this feature is not enabled on the host's account, this setting will \*not\* be applied to the meeting.

```

- **enable**

boolean — Whether to enable `\[sign language interpretation]\(https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)` for the meeting. If not provided, the default value will be based on the user's setting.

- **interpreters**

array — Information about the meeting's sign language interpreters.

Items:

- **email**

string, format: **email** — The interpreter's email address.

- **sign_language**

string — The interpreter's sign language. To get this value, use the `\[sign_language_interpretation]` object's `\[languages]` and `\[custom_languages]` values in the `\[*]*Get user settings\[*]*](/api-reference/zoom-api/methods#operation/userSettings)` API response.

- **summary_template_id**

string — The summary template ID used to generate a meeting summary based on a predefined template. To get available summary templates, use the `\[*]*Get user summary templates\[*]*` API. If not provided, the default value will be based on the user's setting. To enable this feature for your account, please `\[contact Zoom Support]\(https://support.zoom.com/hc/en)`.

- **use_pmi**

boolean — Whether to use a `\[Personal Meeting ID (PMI)](/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi)` for the meeting. This field is only used for scheduled meetings(`\2\`) and recurring meetings with no fixed time(`\3\`). If not provided, the default value will be based on the user's setting.

- **waiting_room**

boolean — Whether to enable the `\[*]*Waiting Room\[*]*` feature](https://support.zoom.us/hc/en-us/articles/115000332726-Waiting-Room). If this value is `\true\`, this `\[*]*disables\[*]*` the `\join_before_host\` setting.

- **waiting_room_options**

object — Configuration settings for the meeting's waiting room.

- **mode** (required)

string, possible values: `"follow_setting"`, `"custom"` — The waiting room behavior for this meeting. `\[*]*follow_setting\` - Use the Zoom web portal setting. `\[*]*custom\` - Specify which participants should go into the waiting room.

- **who_goes_to_waiting_room**

string, possible values: `"everyone"`, `"users_not_in_account"`, `"users_not_in_account_or_whitelisted_domains"`, `"users_not_on_invite"`, `"users_not_in_org"` — Which participants should be placed into the waiting room. Required if `\mode\` is set to `\custom\`. `\[*]*everyone\` - Everyone. `\[*]*users_not_in_account\` - Users not in your account. `\[*]*users_not_in_account_or_whitelisted_domains\` - Users who are not in your account and not part of your whitelisted domains. `\[*]*users_not_on_invite\` - Users not on the meeting invite. `\[*]*users_not_in_org\` - Users not in your organization.

- **watermark**

boolean — Whether to add a watermark when viewing a shared screen. If not provided, the default value will be based on the user's setting.

- **who_can_ask_questions**

integer, possible values: `1`, `2`, `3`, `4`, `5` — Defines who can ask questions about this meeting's transcript. This field is applicable only when `\auto_start_ai_companion_questions\` is set to `\true\`. `\[*]*1\` - All participants and invitees. `\[*]*2\` - All participants only from when they join. `\[*]*3\` - Only meeting host. `\[*]*4\` - Participants and invitees in our organization. `\[*]*5\` - Participants in our organization only from when they join. If not provided, the default value will be based on the user's setting.

- **who_will_receive_summary**

integer, possible values: `1`, `2`, `3`, `4` — Defines who will receive a summary after this meeting. This field is applicable only when `\auto_start_meeting_summary\` is set to `\true\`. `\[*]*1\` - Only meeting

host. * \2\ - Only meeting host, co-hosts, and alternative hosts. * \3\ - Only meeting host and meeting invitees in our organization. * \4\ - All meeting invitees including those outside of our organization. If not provided, the default value will be based on the user's setting.

- **start_time**

string, format: **date-time** — The meeting's start time. This field is only used for scheduled or recurring meetings with a fixed time. This supports local time and GMT formats. * To set a meeting's start time in GMT, use the **yyyy-MM-ddTHH:mm:ssZ** date-time format, such as **2020-03-31T12:02:00Z**. * To set a meeting's start time using a specific timezone, use the **yyyy-MM-ddTHH:mm:ss** date-time format and specify the **[timezone ID]** (</docs/api/references/abbreviations/#timezones>) in the **timezone** field. If you do not specify a timezone, the **timezone** value defaults to your Zoom account's timezone. You can also use **UTC** for the **timezone** value. **Note:** If **start_time** is not specified or is set to a past value, it defaults to the current time.

- **template_id**

string — The account admin meeting template ID used to schedule a meeting using a **[meeting template]** (<https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates>). For a list of account admin-provided meeting templates, use the **[*List meeting templates*]** (</docs/api-reference/zoom-api/methods#operation/listMeetingTemplates>) API. * At this time, this field **only** accepts account admin meeting template IDs. * To enable the account admin meeting templates feature, [contact Zoom support](#) (<https://support.zoom.us/hc/en-us>).

- **timezone**

string — The timezone to assign to the **start_time** value. This field is only used for scheduled or recurring meetings with a fixed time. For a list of supported timezones and their formats, see our **[timezone list]** (</docs/api/references/abbreviations/#timezones>).

- **topic**

string — The meeting's topic.

- **tracking_fields**

array — Information about the meeting's tracking fields.

Items:

- **field** (required)

string — The tracking field's label.

- **value**

string — The tracking field's value.

- **type**

integer, possible values: **1, 2, 3, 8, 10**, default: **2** — The type of meeting. * **1** - An instant meeting. * **2** - A scheduled meeting. * **3** - A recurring meeting with no fixed time. * **8** - A recurring meeting with fixed time. * **10** - A screen share only meeting.

Example:

```
``json
{
  "agenda": "My Meeting",
  "default_password": true,
  "duration": 60,
  "password": "123456",
  "pre_schedule": false,
  "recurrence": {
    "end_date_time": "2022-04-02T15:59:00Z",
    "end_times": 7,
    "monthly_day": 1,
    "monthly_week": 1,
    "monthly_week_day": 1,
    "repeat_interval": 1,
    "type": 1,
    "weekly_days": "1"
  },
  "schedule_for": "jchill@example.com",
  "settings": {
    "additional_data_center_regions": [
      "TY"
    ],
    "allow_multiple_devices": true,
    "alternative_hosts": "jchill@example.com;thill@example.com",

```



```

"alternative_hosts_email_notification": true,
"approval_type": 2,
"approved_or_denied_countries_or_regions": {
  "approved_list": [
    "CX"
  ],
  "denied_list": [
    "CA"
  ],
  "enable": true,
  "method": "approve"
},
"audio": "telephony",
"audio_conference_info": "test",
"authentication_domains": "example.com",
"authentication_exception": [
  {
    "email": "jchill@example.com",
    "name": "Jill Chill"
  }
],
"authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
"auto_recording": "cloud",
"auto_add_recording_to_video_management": {
  "enable": true,
  "channels": [
    {
      "channel_id": "Uyh5qeykTDiA66YQEYmFPg",
      "name": "Team Weekly Meetings"
    }
  ]
},
"breakout_room": {
  "enable": true,
  "rooms": [
    {
      "name": "room1",
      "participants": [
        "jchill@example.com"
      ]
    }
  ]
},
"calendar_type": 1,
"close_registration": false,
"contact_email": "jchill@example.com",
"contact_name": "Jill Chill",
"email_notification": true,
"encryption_type": "enhanced_encryption",
"focus_mode": true,
"global_dial_in_countries": [
  "US"
],
"host_video": true,
"jbh_time": 0,
"join_before_host": false,
"question_and_answer": {
  "enable": true,
  "allow_submit_questions": true,
  "allow_anonymous_questions": true,
  "question_visibility": "all",
  "attendees_can_comment": true,
  "attendees_can_upvote": true
},
"language_interpretation": {
  "enable": true,
  "interpreters": [
    {
      "email": "interpreter@example.com",
      "interpreter_languages": "English,French"
    }
  ]
},
"sign_language_interpretation": {
  "enable": true,
  "interpreters": [
    {
      "email": "interpreter@example.com",
      "sign_language": "American"
    }
  ]
}

```

```

    ],
    "meeting_authentication": true,
    "meeting_invitees": [
      {
        "email": "jchill@example.com"
      }
    ],
    "mute_upon_entry": false,
    "participant_video": false,
    "private_meeting": false,
    "registrants_confirmation_email": true,
    "registrants_email_notification": true,
    "registration_type": 1,
    "show_share_button": true,
    "show_join_info": true,
    "use_pmi": false,
    "waiting_room": false,
    "waiting_room_options": {
      "mode": "follow_setting",
      "who_goes_to_waiting_room": "everyone"
    },
    "watermark": false,
    "host_save_video_order": true,
    "alternative_host_update_polls": true,
    "alternative_host_manage_meeting_summary": true,
    "alternative_host_manage_cloud_recording": false,
    "internal_meeting": false,
    "continuous_meeting_chat": {
      "enable": true
    },
    "participant_focused_meeting": false,
    "push_change_to_calendar": false,
    "resources": [
      {
        "resource_type": "whiteboard",
        "resource_id": "X4Hy02w3QU0dskKofgb9Jg",
        "permission_level": "editor"
      }
    ],
    "auto_start_meeting_summary": false,
    "who_will_receive_summary": 1,
    "auto_start_ai_companion_questions": false,
    "who_can_ask_questions": 1,
    "summary_template_id": "1e1356ad",
    "device_testing": false,
    "request_permission_to_unmute_participants": true,
    "allow_host_control_participant_mute_state": false,
    "disable_participant_video": false,
    "email_in_attendee_report": true
  },
  "start_time": "2022-03-25T07:32:55Z",
  "template_id": "Dv4YdINdTk+Z5RToadh5ug==",
  "timezone": "America/Los_Angeles",
  "topic": "My Meeting",
  "tracking_fields": [
    {
      "field": "field1",
      "value": "value1"
    }
  ],
  "type": 2
}

```

Responses

Status: 201 **HTTP Status Code:** \`201\` Meeting created.

Content-Type: application/json

- **`agenda`**

 `string` — Agenda

- **`assistant\_id`**

 `string` — The ID of the user who scheduled this meeting on behalf of the host.

- **`chat\_join\_url`**

```

`string` — The URL to join the chat.

- **`created_at`**

  `string`, format: `date-time` — The date and time when this meeting was created.

- **`creation_source`**

  `string`, possible values: `"other", "open_api", "web_portal"` — The platform through which the meeting
  was created. \* `other` - Created through another platform. \* `open_api` - Created through Open API.
  \* `web_portal` - Created through the web portal.

- **`duration`**

  `integer` — The meeting duration.

- **`dynamic_host_key`**

  `string` — The meeting dynamic host key.

- **`encrypted_password`**

  `string` — Encrypted passcode for third party endpoints (H323/SIP).

- **`h323_password`**

  `string` — H.323/SIP room system passcode

- **`host_email`**

  `string`, format: `email` — The meeting host's email address.

- **`host_id`**

  `string` — The ID of the user who is set as the meeting host.

- **`id`**

  `integer`, format: `int64` — The \[meeting ID\](https://support.zoom.us/hc/en-us/articles/201362373-
  What-is-a-Meeting-ID): Unique identifier of the meeting in \*`long`*\* format(represented as int64 data
  type in JSON), also known as the meeting number.

- **`join_url`**

  `string` — URL for participants to join the meeting. This URL should only be shared with users that you
  would like to invite for the meeting.

- **`occurrences`**

  `array` — Array of occurrence objects.

  **Items:**

  - **`duration`**

    `integer` — Duration.

  - **`occurrence_id`**

    `string` — Occurrence ID. The unique identifier for an occurrence of a recurring webinar. \[Recurring
    webinars\](https://support.zoom.us/hc/en-us/articles/216354763-How-to-Schedule-A-Recurring-Webinar) can
    have a maximum of 50 occurrences.

  - **`start_time`**

    `string`, format: `date-time` — Start time.

  - **`status`**

    `string`, possible values: `"available", "deleted"` — Occurrence status. `available` - Available
    occurrence. `deleted` - Deleted occurrence.

- **`password`**

  `string` — The meeting passcode. By default, it can be up to 10 characters in length and may contain
  alphanumeric characters as well as special characters such as !, @, #, etc.

- **`pmi`**

```

``string`` — \[Personal meeting ID (PMI)]\(/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi). Only used for scheduled meetings and recurring meetings with no fixed time.

- `**`pre_schedule`**`

``boolean``, default: ``false`` — Whether the prescheduled meeting was created via the \[GSuite app]\ (https://support.zoom.us/hc/en-us/articles/360020187492-Zoom-for-GSuite-add-on). This only supports the meeting ``type`` value of ``2`` (scheduled meetings) and ``3`` (recurring meetings with no fixed time). ``true`` - A GSuite prescheduled meeting. ``false`` - A regular meeting.

- `**`pstn_password`**`

``string`` — Passcode for participants to join the meeting via \[PSTN]\(https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference).

- `**`recurrence`**`

``object`` — Recurrence object. Use this object only for a meeting with type ``8``, a recurring meeting with fixed time.

- `**`type` (required)**`

``integer``, possible values: ``1``, ``2``, ``3`` — Recurrence meeting types. ``1`` - Daily. ``2`` - Weekly. ``3`` - Monthly.

- `**`end_date_time`**`

``string``, format: ``date-time`` — Select the final date when the meeting will recur before it is canceled. Should be in UTC time, such as 2017-11-25T12:00:00Z. Cannot be used with ``end_times``.

- `**`end_times`**`

``integer``, default: ``1`` — Select how many times the meeting should recur before it is canceled. If ``end_times`` is set to 0, it means there is no end time. The maximum number of recurring is 60. Cannot be used with ``end_date_time``.

- `**`monthly_day`**`

``integer``, default: ``1`` — Use this field only if you're scheduling a recurring meeting of type ``3`` to state the day in a month when the meeting should recur. The value range is from 1 to 31. For instance, if you would like the meeting to recur on 23rd of each month, provide ``23`` as this field's value and ``1`` as the ``repeat_interval`` field's value. Instead, to have the meeting recur every three months on 23rd of the month, change the value of the ``repeat_interval`` field to ``3``.

- `**`monthly_week`**`

``integer``, possible values: ``-1``, ``1``, ``2``, ``3``, ``4`` — Use this field ``*``only if you're scheduling a recurring meeting of type ``*`` ``3`` to state the week of the month when the meeting should recur. If you use this field, you must also use the ``monthly_week_day`` field to state the day of the week when the meeting should recur. ``-1`` - Last week of the month. ``1`` - First week of the month. ``2`` - Second week of the month. ``3`` - Third week of the month. ``4`` - Fourth week of the month.

- `**`monthly_week_day`**`

``integer``, possible values: ``1``, ``2``, ``3``, ``4``, ``5``, ``6``, ``7`` — Use this field ``*``only if you're scheduling a recurring meeting of type ``*`` ``3`` to state a specific day in a week when the monthly meeting should recur. To use this field, you must also use the ``monthly_week`` field. ``1`` - Sunday. ``2`` - Monday. ``3`` - Tuesday. ``4`` - Wednesday. ``5`` - Thursday. ``6`` - Friday. ``7`` - Saturday.

- `**`repeat_interval`**`

``integer`` — Define the interval for the meeting to recur. For instance, to schedule a meeting that recurs every two months, set this field's value to ``2`` and the value of the ``type`` parameter as ``3``. For a daily meeting, the maximum interval you can set is ``99`` days. For a weekly meeting the maximum interval that you can set is ``50`` weeks. For a monthly meeting, there is a maximum of ``10`` months.

- `**`weekly_days`**`

``string``, possible values: ``"1"`, `"2"`, `"3"`, `"4"`, `"5"`, `"6"`, `"7"`, default: `"1"` — This field is required `*`if you're scheduling a recurring meeting of type `*` `2` to state the days of the week when the meeting should repeat. This field's value could be a number between `1` to `7` in string format. For instance, if the meeting should recur on Sunday, provide `1` as this field's value. `*`Note:`*` If you would like the meeting to occur on multiple days of a week, provide comma separated values for this field. For instance, if the meeting should recur on Sundays and Tuesdays, provide `1,3` as this field's value. `1` - Sunday. `2` - Monday. `3` - Tuesday. `4` - Wednesday. `5` - Thursday. `6` - Friday. `7` - Saturday.`

- `**`registration_url`**`

``string`` — The URL that registrants can use to register for a meeting. This field is only returned for

meetings that have enabled registration.

- **settings**

object — Meeting settings.

- **additional_data_center_regions**

array — Add additional meeting `[data center regions]` (<https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars>). Provide this value as an array of `[country codes]` ([/docs/api/references/abbreviations/#countries](https://developers.zoom.us/docs/api/references/abbreviations/#countries)) for the countries available as data center regions in the `[Account Profile]` (<https://zoom.us/account/setting>) interface but have been opted out of in the `[user settings]` (<https://zoom.us/profile>). For example, the data center regions selected in your `[Account Profile]` (<https://zoom.us/account>) are `Europe`, `Hong Kong SAR`, `Australia`, `India`, `Japan`, `China`, `United States`, and `Canada`. However, in the `[My Profile]` (<https://zoom.us/profile>) settings, you did `not` select `India` and `Japan` for meeting and webinar traffic routing. To include `India` and `Japan` as additional data centers, use the `[IN, TY]` value for this field.

Items:

string

- **allow_host_control_participant_mute_state**

boolean — Whether to allow the host and co-hosts to fully control the mute state of participants. If not provided, the default value will be based on the user's setting. This option cannot be used together with `request_permission_to_unmute_participants`, only one of the two can be enabled at a time.

- **allow_multiple_devices**

boolean — Allow attendees to join the meeting from multiple devices. This setting only works for meetings that require `[registration]` (<https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-registration-for-a-meeting>).

- **alternative_host_manage_cloud_recording**

boolean — Whether to allow an alternative host to manage meeting cloud recordings.

- **alternative_host_manage_meeting_summary**

boolean — Whether to allow an alternative host to manage meeting summaries.

- **alternative_host_update_polls**

boolean — Whether the `Allow alternative hosts to add or edit polls` feature is enabled. This requires Zoom version 5.8.0 or higher.

- **alternative_hosts**

string — A semicolon-separated list of the meeting's alternative hosts' email addresses or IDs.

- **alternative_hosts_email_notification**

boolean, default: `true` — Flag to determine whether to send email notifications to alternative hosts, default value is true.

- **approval_type**

integer, possible values: `0`, `1`, `2`, default: `2` — Enable registration and set approval for the registration. Note that this feature requires the host to be of `Licensed` user type. `Registration` cannot be enabled for a basic user. `0` - Automatically approve. `1` - Manually approve. `2` - No registration required.

- **approved_or_denied_countries_or_regions**

object — Approve or block users from specific regions or countries from joining this meeting.

- **approved_list**

array — List of countries or regions from where participants can join this meeting.

Items:

string

- **denied_list**

array — List of countries or regions from where participants can not join this meeting.

```

**Items:**

  `string`

  - **`enable`**

    `boolean` — `true` - Setting enabled to either allow users or block users from specific regions to join your meetings. `false` - Setting disabled.

  - **`method`**

    `string`, possible values: `approve`, `deny` — Specify whether to allow users from specific regions to join this meeting; or block users from specific regions from joining this meeting. `approve`: Allow users from specific regions/countries to join this meeting. If this setting is selected, the approved regions/countries must be included in the `approved_list`. `deny`: Block users from specific regions/countries from joining this meeting. If this setting is selected, the approved regions/countries must be included in the `denied_list`

  - **`audio`**

    `string`, possible values: `both`, `telephony`, `voip`, `thirdParty`, default: `both` — Determine how participants can join the audio portion of the meeting. `both` - Both Telephony and VoIP. `telephony` - Telephony only. `voip` - VoIP only. `thirdParty` - Third party audio conference.

  - **`audio_conference_info`**

    `string` — Third party audio conference info.

  - **`authentication_domains`**

    `string` — If user has configured `[Sign Into Zoom with Specified Domains]` (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f) option, this will list the domains that are authenticated.

  - **`authentication_exception`**

    `array` — The participants added here will receive unique meeting invite links and bypass authentication.

**Items:**

  - **`email`**

    `string`, format: `email` — The participant's email address.

  - **`join_url`**

    `string` — URL for participants to join the meeting.

  - **`name`**

    `string` — The participant's name.

  - **`authentication_name`**

    `string` — Authentication name set in the `[authentication profile]` (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f).

  - **`authentication_option`**

    `string` — Meeting authentication option ID.

  - **`auto_add_recording_to_video_management`**

    `object` — Automatically add meeting recordings to a video channel in Video Management. To enable this feature for your account, please `[contact Zoom Support]` (https://support.zoom.us/hc/en-us).

    - **`enable` (required)**

      `boolean`, default: `false` — Whether to automatically add the meeting recording to video management.

    - **`channels`**

      `array` — List of video management channels where the meeting recording will be added.

**Items:**

  - **`channel_id` (required)**

```

``string`` — The unique ID of a video management channel.

- `**`name`**`

``string`` — The name of the video management channel.

- `**`auto_recording`**`

``string``, possible values: ``"local", "cloud", "none"``, default: ``"none"`` — Automatic recording.
``"local"`` - Record on local. ``"cloud"`` - Record on cloud. ``"none"`` - Disabled.

- `**`auto_start_ai_companion_questions`**`

``boolean`` — Whether to automatically start AI Companion questions. If not provided, the default value will be based on the user's setting.

- `**`auto_start_meeting_summary`**`

``boolean`` — Whether to automatically start a meeting summary. If not provided, the default value will be based on the user's setting.

- `**`breakout_room`**`

``object`` — Setting to ``[pre-assign breakout rooms]``(https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4).

- `**`enable`**`

``boolean`` — Set this field's value to ``true`` to enable the ``[breakout room pre-assign]``(https://support.zoom.us/hc/en-us/articles/360032752671-Pre-assigning-participants-to-breakout-rooms#h_36f71353-4190-48a2-b999-ca129861c1f4) option.

- `**`rooms`**`

``array`` — Create a room or rooms.

`**Items:**`

- `**`name`**`

``string`` — The breakout room's name.

- `**`participants`**`

``array`` — Email addresses of the participants who are to be assigned to the breakout room.

`**Items:**`

``string``

- `**`calendar_type`**`

``integer``, possible values: ``1, 2`` — The type of calendar integration used to schedule the meeting. ``1`` - ``[Zoom Outlook add-in]``(<https://support.zoom.us/hc/en-us/articles/360031592971-Getting-started-with-Outlook-plugin-and-add-in>) ``2`` - ``[Zoom for Google Workspace add-on]``(<https://support.zoom.us/hc/en-us/articles/360020187492-Using-the-Zoom-for-Google-Workspace-add-on>) Works with the ``private_meeting`` field to determine whether to share details of meetings or not.

- `**`close_registration`**`

``boolean``, default: ``false`` — Close registration after event date.

- `**`cn_meeting`**`

``boolean``, default: ``false`` — Host meeting in China.

- `**`contact_email`**`

``string`` — Contact email for registration

- `**`contact_name`**`

``string`` — Contact name for registration

- `**`continuous_meeting_chat`**`

``object`` — Information about the ``Enable continuous meeting chat`` feature. This setting only applies to scheduled and recurring meetings (type ``2``, ``3``, and ``8``). It is ``not supported`` for type ``1`` instant meetings or type ``10`` screen share only meetings.

```

- auto_add_invited_external_users

  `boolean` — Whether to enable the Automatically add invited external users setting.

- auto_add_meeting_participants

  `boolean` — Whether to enable the Automatically add meeting participants setting.

- channel_id

  `string` — The channel's ID.

- enable

  `boolean` — Whether to enable the Enable continuous meeting chat setting. The default value is based on user settings. When the Enable continuous meeting chat setting is enabled, the default value is true. When the setting is disabled, the default value is false.

- custom_keys

  `array` — Custom keys and values assigned to the meeting.

  Items:

  - key

    `string` — Custom key associated with the user.

  - value

    `string` — Value of the custom key associated with the user.

- device_testing

  `boolean`, default: false — Enable the device testing.

- disable_participant_video

  `boolean`, default: false — Whether to disable the participant video during meeting. To enable this feature for your account, please contact Zoom Support (https://support.zoom.us/hc/en-us).

- email_in_attendee_report

  `boolean` — Whether to include authenticated guest's email addresses in meetings' attendee reports.

- email_notification

  `boolean`, default: true — Whether to send email notifications to [alternative hosts] (https://support.zoom.us/hc/en-us/articles/208220166) and [users with scheduling privileges] (https://support.zoom.us/hc/en-us/articles/201362803-Scheduling-privilege). This value defaults to true.

- encryption_type

  `string`, possible values: "enhanced_encryption", "e2ee" — Choose between enhanced encryption and [end-to-end encryption] (https://support.zoom.us/hc/en-us/articles/360048660871) when starting or a meeting. When using end-to-end encryption, several features (e.g. cloud recording, phone/SIP/H.323 dial-in) will be automatically disabled. enhanced_encryption - Enhanced encryption. Encryption is stored in the cloud if you enable this option. e2ee - [End-to-end encryption] (https://support.zoom.us/hc/en-us/articles/360048660871). The encryption key is stored in your local device and can not be obtained by anyone else. Enabling this setting also disables the join before host, cloud recording, streaming, live transcription, breakout rooms, polling, 1:1 private chat, and meeting reactions features.

- enforce_login

  `boolean` — Only signed in users can join this meeting. This field is deprecated and will not be supported in the future. As an alternative, use the meeting_authentication, authentication_option, and authentication_domains fields to understand the [authentication configurations] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the meeting.

- enforce_login_domains

  `string` — Only signed in users with specified domains can join meetings. This field is deprecated and will not be supported in the future. As an alternative, use the meeting_authentication, authentication_option, and authentication_domains fields to understand the [authentication configurations] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the meeting.

```



```

- focus_mode

`boolean` — Whether the \[*\*Focus Mode\*\* feature](https://support.zoom.us/hc/en-us/articles/360061113751-Using-focus-mode) is enabled when the meeting starts.

- global_dial_in_countries

`array` — List of global dial-in countries.

Items:

`string`

- global_dial_in_numbers

`array` — Global dial-in countries or regions.

Items:

- city

`string` — City of the number, such as Chicago.

- country

`string` — The country code, such as BR.

- country_name

`string` — Full name of country, such as Brazil.

- number

`string` — A phone number, such as +1 2332357613.

- type

`string`, possible values: "toll", "tollfree" — Type of number.

- host_save_video_order

`boolean` — Whether the \[*\*Allow host to save video order\*\* feature is enabled.

- host_video

`boolean` — Start video when the host joins the meeting.

- in_meeting

`boolean`, default: false — Host meeting in India.

- internal_meeting

`boolean`, default: false — Whether to set the meeting as an internal meeting.

- jbh_time

`integer`, possible values: 0, 5, 10, 15 — If the value of \join\_before\_host\` field is set to true\`, use this field to indicate time limits when a participant may join a meeting before a host. \* \0\` - Allow participant to join anytime. \* \5\` - Allow participant to join 5 minutes before meeting start time. \* \10\` - Allow participant to join 10 minutes before meeting start time. \* \15\` - Allow the participant to join 15 minutes before the meeting's start time.

- join_before_host

`boolean`, default: false — Allow participants to join the meeting before the host starts the meeting. Only used for scheduled or recurring meetings.

- language_interpretation

`object` — The meeting's \[language interpretation settings](https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details. \[*\*Note\*\* This feature is only available for certain Meeting add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will \[*\*not\*\* be applied to the meeting.

- enable

`boolean` — Whether to enable \[language interpretation](https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0064768) for the meeting. If not provided, the default value will be based on

```

the user's setting.

- **``interpreters``**

``array`` — Information about the meeting's language interpreters.

``Items``

- **``email``**

``string``, format: ``email`` — The interpreter's email address.

- **``interpreter\_languages``**

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the `language_interpretation`` object's `languages`` and `custom_languages`` values in the `[/api/users/{userId}/settings]` API response. `languages``: System-supported languages include `English``, `Chinese``, `Japanese``, `German``, `French``, `Russian``, `Portuguese``, `Spanish``, and `Korean``. `custom_languages``: User-defined languages added by the user. For example, an interpreter translating between English and French should use `English,French``.

- **``languages``**

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: `US`` (English), `CN`` (Chinese), `JP`` (Japanese), `DE`` (German), `FR`` (French), `RU`` (Russian), `PT`` (Portuguese), `ES`` (Spanish), and `KR`` (Korean). For example, to set an interpreter translating from English to Chinese, use `US,CN``.

- **``meeting\_authentication``**

``boolean`` — `true`` - Only authenticated users can join meetings.

- **``meeting\_invitees``**

``array`` — A list of the meeting's invitees.

``Items``

- **``email``**

``string``, format: ``email`` — The invitee's email address.

- **``mute\_upon\_entry``**

``boolean``, default: `false`` — Mute participants upon entry.

- **``participant\_focused\_meeting``**

``boolean``, default: `false`` — Whether to set the meeting as a participant focused meeting.

- **``participant\_video``**

``boolean`` — Start video when participants join the meeting.

- **``private\_meeting``**

``boolean`` — Whether the meeting is set as private.

- **``push\_change\_to\_calendar``**

``boolean``, default: `false`` — Whether to push meeting changes to the calendar. To enable this feature, configure the `Configure Calendar and Contacts Service`` in the user's profile page of the Zoom web portal and enable the `Automatically sync Zoom calendar events information bi-directionally between Zoom and integrated calendars`` setting in the `Settings`` page of the Zoom web portal. `true`` - Push meeting changes to the calendar. `false`` - Do not push meeting changes to the calendar.

- **``question\_and\_answer``**

``object`` — `[Q&A](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065237)` for meeting.

- **``allow\_anonymous\_questions``**

``boolean`` — `true`` - Allow participants to send questions without providing their name to the host, co-host, and panelists.. `false`` - Do not allow anonymous questions.(Not supported for simulative meeting.)

- **``allow\_submit\_questions``**

``boolean`` — `\* `true``: Allow participants to submit questions. `\* `false``: Do not allow submit questions.

- `**`attendees_can_comment`**`

``boolean`` — `\* `true`` - Attendees can answer questions or leave a comment in the question thread. `\* `false`` - Attendees can not answer questions or leave a comment in the question thread

- `**`attendees_can_upvote`**`

``boolean`` — `\* `true`` - Attendees can click the thumbs up button to bring popular questions to the top of the Q&A window. `\* `false`` - Attendees can not click the thumbs up button on questions.

- `**`enable`**`

``boolean`` — `\* `true`` - Enable `\[Q&A](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0065237)` for meeting. `\* `false`` - Disable Q&A for meeting. If not provided, the default value will be based on the user's setting.

- `**`question_visibility`**`

``string``, possible values: ``"answered"`, `"all"`` — Indicate whether you want attendees to be able to view answered questions only or view all questions. `\* `answered`` - Attendees are able to view answered questions only. `\* `all`` - Attendees are able to view all questions submitted in the Q&A.

- `**`registrants_confirmation_email`**`

``boolean`` — Whether to send registrants an email confirmation. `\* `true`` - Send a confirmation email. `\* `false`` - Do not send a confirmation email.

- `**`registrants_email_notification`**`

``boolean`` — Whether to send registrants email notifications about their registration approval, cancellation, or rejection. `\* `true`` - Send an email notification. `\* `false`` - Do not send an email notification. Set this value to ``true`` to also use the ``registrants_confirmation_email`` parameter.

- `**`registration_type`**`

``integer``, possible values: ``1, 2, 3``, default: ``1`` — Registration type. Used for recurring meeting with fixed time only. ``1`` - Attendees register once and can attend any of the occurrences. ``2`` - Attendees need to register for each occurrence to attend. ``3`` - Attendees register once and can choose one or more occurrences to attend.

- `**`request_permission_to_unmute_participants`**`

``boolean``, default: ``false`` — Whether to enable the `\[*]Request permission to unmute participants\[*](https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting)` setting. This option cannot be used together with ``allow_host_control_participant_mute_state``, only one of the two can be enabled at a time.

- `**`resources`**`

``array`` — The meeting's resources.

`**Items:**`

- `**`permission_level`**`

``string``, possible values: ``"editor"`, `"commenter"`, `"viewer"``, default: ``"editor"`` — The permission levels for users to access the whiteboard. `\* `editor`` - Users with link access can edit the board. `\* `commenter`` - Users with link access can comment on the board. `\* `viewer`` - Users with link access can view the board.

- `**`resource_id`**`

``string`` — The resource ID.

- `**`resource_type`**`

``string``, possible values: ``"whiteboard"`` — The resource type.

- `**`show_join_info`**`

``boolean`` — Whether to show the meeting's join information on the registration confirmation page. This setting is only applied to meetings with registration enabled.

- `**`show_share_button`**`

``boolean`` — Show social share buttons on the meeting registration page. This setting only works for meetings that require `\[registration](https://support.zoom.us/hc/en-us/articles/211579443-Setting-up-`

registration-for-a-meeting).

- **sign_language_interpretation**

object — The meeting's [sign language interpretation settings](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar). Make sure to add the language in the web portal in order to use it in the API. See link for details. **Note:** If this feature is not enabled on the host's account, this setting will **not** be applied to the meeting.

- **enable**

boolean — Whether to enable [sign language interpretation](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar) for the meeting. If not provided, the default value will be based on the user's setting.

- **interpreters**

array — Information about the meeting's sign language interpreters.

Items:

- **email**

string, format: **email** — The interpreter's email address.

- **sign_language**

string — The interpreter's sign language. To get this value, use the **sign_language_interpretation** object's **languages** and **custom_languages** values in the **Get user settings** [API reference/zoom-api/methods#operation/userSettings] API response.

- **summary_template_id**

string — The summary template ID used to generate a meeting summary based on a predefined template. To get available summary templates, use the **Get user summary templates** API. If not provided, the default value will be based on the user's setting. To enable this feature for your account, please [contact Zoom Support](https://support.zoom.com/hc/en).

- **use_pmi**

boolean — Whether to use a [Personal Meeting ID (PMI)](/docs/api/using-zoom-apis/#understanding-personal-meeting-id-pmi) for the meeting. This field is only used for scheduled meetings (2) and recurring meetings with no fixed time (3). If not provided, the default value will be based on the user's setting.

- **waiting_room**

boolean, default: **false** — Enable the waiting room.

- **waiting_room_options**

object — Configuration settings for the meeting's waiting room.

- **mode** (required)

string, possible values: **follow_setting**, **custom** — The waiting room behavior for this meeting. **follow_setting** - Use the Zoom web portal setting. **custom** - Specify which participants should go into the waiting room.

- **who_goes_to_waiting_room**

string, possible values: **everyone**, **users_not_in_account**, **users_not_in_account_or_whitelisted_domains**, **users_not_on_invite**, **users_not_in_org** — Which participants should be placed into the waiting room. Required if **mode** is set to **custom**. **everyone** - Everyone. **users_not_in_account** - Users not in your account. **users_not_in_account_or_whitelisted_domains** - Users who are not in your account and not part of your whitelisted domains. **users_not_on_invite** - Users not on the meeting invite. **users_not_in_org** - Users not in your organization.

- **watermark**

boolean — Whether to add a watermark when viewing a shared screen. If not provided, the default value will be based on the user's setting.

- **who_can_ask_questions**

integer, possible values: **1**, **2**, **3**, **4**, **5** — Defines who can ask questions about this meeting's transcript. This field is applicable only when **auto_start_ai_companion_questions** is set to **true**. **1** - All participants and invitees. **2** - All participants only from when they join. **3** - Only meeting host. **4** - Participants and invitees in our organization. **5** - Participants in our

organization only from when they join. If not provided, the default value will be based on the user's setting.

- **who_will_receive_summary**

`integer`, possible values: `1, 2, 3, 4` — Defines who will receive a summary after this meeting. This field is applicable only when `auto_start_meeting_summary` is set to `true`. `1` - Only meeting host. `2` - Only meeting host, co-hosts, and alternative hosts. `3` - Only meeting host and meeting invitees in our organization. `4` - All meeting invitees including those outside of our organization. If not provided, the default value will be based on the user's setting.

- **start_time**

`string`, format: `date-time` — Meeting start date-time in UTC/GMT, such as `2020-03-31T12:02:00Z`.

- **start_url**

`string` — URL to start the meeting. This URL should only be used by the host of the meeting and `should not be shared with anyone other than the host` of the meeting, since anyone with this URL will be able to log in to the Zoom Client as the host of the meeting.

- **status**

`string`, possible values: `"waiting", "started"` — The meeting status. `waiting` - The meeting has not started. `started` - The meeting is currently in progress.

- **template_id**

`string` — The account admin meeting template ID used to schedule a meeting using a `[meeting template]` (<https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates>). For a list of account admin-provided meeting templates, use the `[*]List meeting templates[*]` ([/docs/api-reference/zoom-api/methods#operation/listMeetingTemplates](https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates)) API. `At this time, this field only accepts account admin meeting template IDs.` `To enable the account admin meeting templates feature, [contact Zoom support](https://support.zoom.us/hc/en-us).`

- **timezone**

`string` — Timezone to format `start_time`.

- **topic**

`string` — Meeting topic.

- **tracking_fields**

`array` — Tracking fields.

Items:

- **field**

`string` — The tracking field's label.

- **value**

`string` — The tracking field's value.

- **visible**

`boolean` — Indicates whether the `[tracking field]` (<https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields>) is visible in the meeting scheduling options in the Zoom Web Portal or not. `true`: Tracking field is visible. `false`: Tracking field is not visible to the users in the meeting options in the Zoom Web Portal but the field was used while scheduling this meeting via API. An invisible tracking field can be used by users while scheduling meetings via API only.

- **type**

`integer`, possible values: `1, 2, 3, 8, 10`, default: `2` — The meeting type. `1` - An instant meeting. `2` - A scheduled meeting. `3` - A recurring meeting with no fixed time. `8` - A recurring meeting with fixed time. `10` - A screen share only meeting.

- **uuid**

`string` — Unique meeting ID. Each meeting instance generates its own meeting UUID - after a meeting ends, a new UUID is generated for the next instance of the meeting. Retrieve a list of UUIDs from past meeting instances using the `[*]List past meeting instances[*]` ([/docs/api/rest/reference/zoom-api/methods#operation/pastMeetings](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields)) API. `[Double encode]` ([/docs/api/rest/using-zoom-apis/#meeting-id-and-uuid](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields)) your UUID when using it for API calls if the UUID begins with a `/` or contains `/` in it.

Example:

```

```json
{
 "assistant_id": "kFFvsJc-Q10SxaJQLvaa_A",
 "host_email": "jchill@example.com",
 "host_id": "30R7kT7bTIKSNUFEuH_Qlg",
 "id": 92674392836,
 "uuid": "aDYlohsHRtCd4iiluC2+hA==",
 "registration_url": "https://example.com/meeting/register/7ksAkRCoEpt1Jm0wa-E6lICLur9e7Lde5oW6",
 "agenda": "My Meeting",
 "created_at": "2022-03-25T07:29:29Z",
 "duration": 60,
 "encrypted_password": "8pEkRweVXPV30b2KJYgFTRlDt1lgSn.1",
 "pstn_password": "123456",
 "h323_password": "123456",
 "join_url": "https://example.com/j/11111",
 "chat_join_url": "https://example.com/launch/jc/11111",
 "occurrences": [
 {
 "duration": 60,
 "occurrence_id": "1648194360000",
 "start_time": "2022-03-25T07:46:00Z",
 "status": "available"
 }
],
 "password": "123456",
 "pmi": "97891943927",
 "pre_schedule": false,
 "recurrence": {
 "end_date_time": "2022-04-02T15:59:00Z",
 "end_times": 7,
 "monthly_day": 1,
 "monthly_week": 1,
 "monthly_week_day": 1,
 "repeat_interval": 1,
 "type": 1,
 "weekly_days": "1"
 },
 "settings": {
 "additional_data_center_regions": [
 "TY"
],
 "allow_multiple_devices": true,
 "alternative_hosts": "jchill@example.com;thill@example.com",
 "alternative_hosts_email_notification": true,
 "alternative_host_update_polls": true,
 "alternative_host_manage_meeting_summary": true,
 "alternative_host_manage_cloud_recording": false,
 "approval_type": 0,
 "approved_or_denied_countries_or_regions": {
 "approved_list": [
 "CX"
],
 "denied_list": [
 "CA"
],
 "enable": true,
 "method": "approve"
 },
 "audio": "telephony",
 "audio_conference_info": "test",
 "authentication_domains": "example.com",
 "authentication_exception": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "join_url": "https://example.com/s/11111"
 }
],
 "authentication_name": "Sign in to Zoom",
 "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
 "auto_recording": "cloud",
 "auto_add_recording_to_video_management": {
 "enable": true,
 "channels": [
 {
 "channel_id": "Uyh5qeykTDiA66YQEYmFPg",
 "name": "Team Weekly Meetings"
 }
]
 }
 }
}

```

```

 },
 "breakout_room": {
 "enable": true,
 "rooms": [
 {
 "name": "room1",
 "participants": [
 "jchill@example.com"
]
 }
]
 },
 "calendar_type": 1,
 "close_registration": false,
 "contact_email": "jchill@example.com",
 "contact_name": "Jill Chill",
 "custom_keys": [
 {
 "key": "key1",
 "value": "value1"
 }
],
 "email_notification": true,
 "encryption_type": "enhanced_encryption",
 "focus_mode": true,
 "global_dial_in_countries": [
 "US"
],
 "global_dial_in_numbers": [
 {
 "city": "New York",
 "country": "US",
 "country_name": "US",
 "number": "+1 1000200200",
 "type": "toll"
 }
],
 "host_video": true,
 "jbh_time": 0,
 "join_before_host": true,
 "question_and_answer": {
 "enable": true,
 "allow_submit_questions": true,
 "allow_anonymous_questions": true,
 "question_visibility": "all",
 "attendees_can_comment": true,
 "attendees_can_upvote": true
 },
 "language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "interpreter_languages": "English,French"
 }
]
 },
 "sign_language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "sign_language": "American"
 }
]
 },
 "meeting_authentication": true,
 "mute_upon_entry": false,
 "participant_video": false,
 "private_meeting": false,
 "registrants_confirmation_email": true,
 "registrants_email_notification": true,
 "registration_type": 1,
 "show_share_button": true,
 "show_join_info": true,
 "use_pmi": false,
 "waiting_room": false,
 "waiting_room_options": {
 "mode": "follow_setting",
 "who_goes_to_waiting_room": "everyone"
 }
 }
}

```

```

 },
 "watermark": false,
 "host_save_video_order": true,
 "internal_meeting": false,
 "meeting_invitees": [
 {
 "email": "jchill@example.com"
 }
],
 "continuous_meeting_chat": {
 "enable": true,
 "channel_id": "cabcd1234567defghijkl01234"
 },
 "participant_focused_meeting": false,
 "push_change_to_calendar": false,
 "resources": [
 {
 "resource_type": "whiteboard",
 "resource_id": "X4Hy02w3QU0dskKofgb9Jg",
 "permission_level": "editor"
 }
],
 "auto_start_meeting_summary": false,
 "who_will_receive_summary": 1,
 "auto_start_ai_companion_questions": false,
 "who_can_ask_questions": 1,
 "summary_template_id": "1e1356ad",
 "device_testing": false,
 "request_permission_to_unmute_participants": true,
 "allow_host_control_participant_mute_state": false,
 "disable_participant_video": false,
 "email_in_attendee_report": true
 },
 "start_time": "2022-03-25T07:29:29Z",
 "start_url": "https://example.com/s/11111",
 "status": "waiting",
 "template_id": "Dv4YdINdTk+Z5RToadh5ug==",
 "timezone": "America/Los_Angeles",
 "topic": "My Meeting",
 "tracking_fields": [
 {
 "field": "field1",
 "value": "value1",
 "visible": true
 }
],
 "type": 2,
 "dynamic_host_key": "123456",
 "creation_source": "open_api"
},
},

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3161` `Your user account is not allowed meeting hosting and scheduling capabilities.` `Error Code: 3000` `Instant meetings do not support the schedule_for parameter, and you can't schedule an instant meeting for another user.` `Error Code: 3000` `Users in '{userId}' have been blocked from joining meetings and webinars. To unblock them, go to the Settings page in the Zoom web portal and update Block users in specific domains from joining meetings and webinars.` `Error Code: 3000` `You cannot schedule a meeting for {userId}` `Error Code: 300` `The value that you entered in the schedule_for field is invalid. Enter a valid value and try again.` `Error Code: 300` `Invalid enforce_login_domains. Separate multiple domains with semicolons.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `User does not exist: {userId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see \[rate limits\]`.

### ### List upcoming meetings

```

- **Method:** `GET`
- **Path:** `/users/{userId}/upcoming_meetings`
- **Tags:** Meetings

```

List a Zoom user's upcoming meetings. For user-level apps, pass [the `me` value](/docs/api/rest/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter.

**\*\*Notes\*\*:**



- This API includes the meetings that Zoom users schedule and the meetings they are invited to join.
- This API only includes upcoming meetings within the next 24 hours.

#### **\*\*Prerequisites\*\*:**

- To retrieve data for Zoom meetings that the user has been invited to from a third-party calendar (Google, Exchange, Office 365, Apple iCloud), the **[\*\*Calendar and Contacts Integration\*\*]** ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0069503](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0069503)) must be enabled in the Zoom Web Portal.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `meeting:read`, `meeting:read:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `meeting:read:list\_upcoming\_meetings`, `meeting:read:list\_upcoming\_meetings:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

#### #### Responses

##### Status: 200 `HTTP Status Code:` `200` List of upcoming meeting objects returned.

##### Content-Type: application/json

- **\*\*`meetings`\*\***

`array` — List of upcoming meeting objects.

**\*\*Items:\*\***

- **\*\*`created\_at`\*\***

`string`, format: `date-time` — The meeting creation time.

- **\*\*`duration`\*\***

`integer` — Meeting duration.

- **\*\*`id`\*\***

`integer`, format: `int64` — The `[meeting ID]` (<https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID->) - a unique identifier of the meeting in `long` format, represented as int64 data type in JSON. Also known as the meeting number.

- **\*\*`is\_all\_day`\*\***

`boolean` — Whether the meeting is scheduled as an all-day event.

- **\*\*`is\_host`\*\***

`boolean` — Whether the current user is the host of the meeting.

- **\*\*`join\_url`\*\***

`string` — The URL that participants can use to join a meeting.

- **\*\*`passcode`\*\***

`string` — The meeting passcode. This passcode may only contain characters `[a-z A-Z 0-9 @ - _ \* !]`.`

- **\*\*`start\_time`\*\***

`string`, format: `date-time` — The meeting's start time.

- **\*\*`timezone`\*\***

`string` — The timezone to format the meeting start time.

- **\*\*`topic`\*\***

`string` — The meeting topic.

- **\*\*`type`\*\***

`integer`, possible values: `1, 2, 3, 8` — Meeting types. `1` - Instant meeting. `2` - Scheduled meeting. `3` - Recurring meeting with no fixed time. `8` - Recurring meeting with a fixed time.

- **\*\*`use\_pmi`\*\***

``boolean`` — Use a `\[personal meeting ID (PMI)]\(/docs/api/rest/using-zoom-apis/#understanding-personal-meeting-id-pmi)`. Only used for scheduled meetings and recurring meetings with no fixed time.

- `**`total_records`**`

``integer`` — The total number of all records available across all pages.

**Example:**

```
```json
{
  "total_records": 1,
  "meetings": [
    {
      "id": 97763643886,
      "topic": "My Meeting",
      "type": 2,
      "start_time": "2022-03-23T06:00:00Z",
      "duration": 60,
      "timezone": "America/Los_Angeles",
      "created_at": "2022-03-23T05:31:16Z",
      "join_url": "https://example.com/j/11111",
      "passcode": "123456",
      "use_pmi": false,
      "is_host": true,
      "is_all_day": false
    }
  ]
}
```

Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br>` Not Found `\*\*Error Code:\*\* \`3001\`` `\<br>` User does not exist: {userId}. `\<br>`

Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(/docs/api/rest/rate-limits/)`.

List a user's PAC accounts

- **Method:** ``GET``
 - **Path:** ``/users/{userId}/pac``
 - **Tags:** PAC

Retrieve a list of a user's [personal audio conference (PAC)](<https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference>) accounts. For user-level apps, pass [the ``me`` value](<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#the-me-keyword>) instead of the ``userId`` parameter.

PAC allows Pro or higher account holders to host meetings through PSTN (phone dial-in) only.

Prerequisites

- A Pro or higher plan with an [Audio Conferencing](<https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference>) subscription.
 - The **[Personal Audio Conference]**(https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference#h_01F5BPM447M6QDJXX50RSFXKJ3) setting enabled in the user's profile.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `**`pac:read:admin`,`pac:read``

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `**`pac:read:list_pac_accounts`,`pac:read:list_pac_accounts:admin``

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `**`LIGHT``

Responses

Status: 200 `\*\*HTTP Status Code:\*\* \`200\`` PAC account list returned.

Content-Type: application/json

- `**`pac_accounts`**`

``array`` — Information about the PAC accounts.

Items:

- `**`conference_id`**`

``integer``, format: ``int64`` — The conference ID.

```

- **`dedicated_dial_in_number`**

  `array` — Information about the account's dedicated dial-in numbers.

**Items:**

- **`country`**

  `string` — The dial-in country code.

- **`number`**

  `string` — The dial-in number.

- **`global_dial_in_numbers`**

  `array` — Information about the account's global dial-in numbers.

**Items:**

- **`country`**

  `string` — The global dial-in country code.

- **`number`**

  `string` — The global dial-in number.

- **`listen_only_password`**

  `string` — The listen-only password, up to six characters in length.

- **`participant_password`**

  `string` — The participant password, up to six characters in length.

**Example:**

```json
{
 "pac_accounts": [
 {
 "conference_id": 111111,
 "dedicated_dial_in_number": [
 {
 "country": "USA",
 "number": "5550110"
 }
],
 "global_dial_in_numbers": [
 {
 "country": "USA",
 "number": "5550100"
 }
],
 "listen_only_password": "3c2b1a",
 "participant_password": "a1b2c3"
 }
]
}
```

##### Status: 400 **HTTP Status Code:** 400 **Error Code:** 2024 **User does not have PAC enabled.

##### Status: 404 **HTTP Status Code:** 404 **Error Code:** 1001 **User does not exist: $userId

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Perform batch poll creation

- **Method:** POST
- **Path:** /meetings/{meetingId}/batch_polls
- **Tags:** Polls

```

Polls allow the meeting host to survey attendees. Create batch [polls](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings) for a meeting.

****Prerequisites**:**

- Host user type must be ****Pro**** or higher plan.
- Polling feature must be enabled in the host's account.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
 `meeting:write:admin`, `meeting:write`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
 `meeting:write:batch\_polls`, `meeting:write:batch\_polls:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits)**** `LIGHT`

Request Body

Content-Type: application/json

- ****`polls`****

`array` — The information about the meeting's polls.

****Items:****- ****`anonymous`****

`boolean`, default: `false` — Whether to allow meeting participants to answer poll questions anonymously: `true` — Anonymous polls enabled. `false` — Participants cannot answer poll questions anonymously. This value defaults to `false`.

- ****`poll\_type`****

`integer`, possible values: `1, 2, 3`, default: `1` — The type of poll: `1` — Poll. `2` — Advanced Poll. This feature must be enabled in your Zoom account. `3` — Quiz. This feature must be enabled in your Zoom account. This value defaults to `1`.

- ****`questions`****

`array` — The information about the poll's questions.

****Items:****- ****`answer\_max\_character`****

`integer` — The allowed maximum number of characters. This field only applies to `short\_answer` and `long\_answer` polls: For `short\_answer` polls, a maximum of 500 characters. For `long\_answer` polls, a maximum of 2,000 characters.

- ****`answer\_min\_character`****

`integer` — The allowed minimum number of characters. This field only applies to `short\_answer` and `long\_answer` polls. You must provide at least a `one` character minimum value.

- ****`answer\_required`****

`boolean`, default: `false` — Whether participants must answer the question: `true` — The participant must answer the question. `false` — The participant does not need to answer the question. **Note:** When the poll's `type` value is `1` (Poll), this value defaults to `true`. When the poll's `type` value is the `2` (Advanced Poll) or `3` (Quiz) values, this value defaults to `false`.

- ****`answers`****

`array` — The poll question's available answers. This field requires a **minimum** of two answers. For `single` and `multiple` polls, you can only provide a maximum of 10 answers. For `matching` polls, you can only provide a maximum of 16 answers. For `rank\_order` polls, you can only provide a maximum of seven answers.

****Items:****

`string`

- ****`case\_sensitive`****

`boolean`, default: `false` — Whether the correct answer is case sensitive. This field only applies to `fill\_in\_the\_blank` polls: `true` — The answer is case-sensitive. `false` — The answer is not case-sensitive. This value defaults to `false`.

- ****`name`****

``string`` — The poll question's title, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You ``**must`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``*`` For ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``*`` For ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating_min_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``*required`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box: ``true`` — Show as a drop-down box. ``false`` — Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``single``, ``multiple``, ``matching``, ``rank_order``, ``short_answer``, ``long_answer``, ``fill_in_the_blank``, ``rating_scale`` — The poll's question and answer type: ``single`` — Single choice. ``multiple`` — Multiple choice. ``matching`` — Matching. ``rank_order`` — Rank order. ``short_answer`` — Short answer. ``long_answer`` — Long answer. ``fill_in_the_blank`` — Fill in the blank. ``rating_scale`` — Rating scale.

- `**`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

```
``json
{
  "polls": [
    {
```

```

    "anonymous": false,
    "poll_type": 2,
    "questions": [
      {
        "answer_max_character": 200,
        "answer_min_character": 1,
        "answer_required": false,
        "answers": [
          "Extremely useful"
        ],
        "case_sensitive": false,
        "name": "How useful was this meeting?",
        "prompts": [
          {
            "prompt_question": "How are you?",
            "prompt_right_answers": [
              "Good"
            ]
          }
        ],
        "rating_max_label": "Extremely Likely",
        "rating_max_value": 4,
        "rating_min_label": "Not likely",
        "rating_min_value": 1,
        "right_answers": [
          "Good"
        ],
        "show_as_dropdown": false,
        "type": "single"
      }
    ],
    "title": "Learn something new"
  }
]
}
}

```

Responses

Status: 201 **HTTP Status Code:** \`201\` Meeting Poll Created

Content-Type: application/json

- ****polls****

\`array\`

****Items:****

- ****anonymous****

\`boolean\` — Whether to allow meeting participants to answer poll questions anonymously: *\`true\` \— Anonymous polls enabled. *\`false\` \— Participants cannot answer poll questions anonymously.

- ****id****

\`string\` — Meeting Poll ID

- ****poll_type****

\`integer\`, possible values: \`1, 2, 3\` — The type of poll: *\`1\` \— Poll. *\`2\` \— Advanced Poll. This feature must be enabled in your Zoom account. *\`3\` \— Quiz. This feature must be enabled in your Zoom account.

- ****questions****

\`array\` — The information about the poll's questions.

****Items:****

- ****answer_max_character****

\`integer\` — The allowed maximum number of characters. This field only returns for \`\`short_answer\` and \`\`long\\_answer\` polls.

- ****answer_min_character****

\`integer\` — The allowed minimum number of characters. This field only returns for \`\`short_answer\` and \`\`long\\_answer\` polls.

```

- answer_required

  boolean — Whether participants must answer the question: true — The participant must answer the question. false — The participant does not need to answer the question.

- answers

  array — The poll question's available answers.

  Items:

  string

- case_sensitive

  boolean, default: false — Whether the correct answer is case sensitive. This field only returns for fill_in_the_blank polls: true — The answer is case-sensitive. false — The answer is not case-sensitive.

- name

  string — The poll question's title. For fill_in_the_blank polls, this field is the poll's question.

- prompts

  array — The information about the prompt questions. This object only returns for matching and rank_order polls.

  Items:

  - prompt_question

    string — The question prompt's title.

  - prompt_right_answers

    array — The question prompt's correct answers.

    Items:

    string

- rating_max_label

  string — The high score label for the rating_max_value field. This field only returns for rating_scale polls.

- rating_max_value

  integer — The rating scale's maximum value. This field only returns for rating_scale polls.

- rating_min_label

  string — The low score label for the rating_min_value field. This field only returns for rating_scale polls.

- rating_min_value

  integer — The rating scale's minimum value. This field only returns for rating_scale polls.

- right_answers

  array — The poll question's correct answer(s).

  Items:

  string

- show_as_dropdown

  boolean — Whether to display the radio selection as a drop-down box: true — Show as a drop-down box. false — Do not show as a drop-down box.

- type

  string, possible values: "single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale" — The poll's question and answer type: single — Single choice. multiple — Multiple choice. matching — Matching. *

```

\`rank\`_order\` — Rank order. \\* \`short\`\_answer\` — Short answer. * \`long\`_answer\`
 \` — Long answer. \\* \`fill\`\_in\`_the\`\_blank\` — Fill in the blank. * \`rating\`_scale\` —
 Rating scale.

- *\`status\`*

\`string\`, possible values: \`"notstart", "started", "ended", "sharing"\` — The status of the meeting
 poll: \`"notstart"\` - Poll not started \`"started"\` - Poll started \`"ended"\` - Poll ended \`"sharing"\` -
 Sharing poll results

- *\`title\`*

\`string\` — The title for the poll.

\`Example:\`

```
```json
{
 "polls": [
 {
 "anonymous": true,
 "id": "QalIoKWLtJehBJ8e1xRrbQ",
 "poll_type": 2,
 "questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
 }
],
 "status": "notstart",
 "title": "Learn something new"
}
```
```

Status: 400 *\`HTTP Status Code:\\*\` \`400\` \
 Bad Request *\`Error Code:\\*\` \`300\` \

 Invalid Meeting ID. \
 *\`Error Code:\\*\` \`3000\` \
 Cannot access meeting information. \

 *\`Error Code:\\*\` \`4400\` \
 You can only add a maximum of 50 polls. \
 *\`Error Code:\\*\`
 \`3161\` \
 Meeting hosting and scheduling capabilities are not allowed for your user account. \

 *\`Error Code:\\*\` \`4400\` \
 Meeting polls disabled. To enable this feature, enable the "Meeting
 Polls/Quizzes" setting in the Zoom web portal's "Settings" interface. \
 *\`Error Code:\\*\` \`4400\` \

 Advanced meeting polls disabled. To enable this feature, enable the "Allow host to create advanced
 polls and quizzes" setting in the Zoom web portal's "Settings" interface. \

Status: 404 *\`HTTP Status Code:\\*\` \`404\` \
 Not Found *\`Error Code:\\*\` \`3001\` \

 Meeting does not exist: {meetingId}. \

Status: 429 *\`HTTP Status Code:\\*\` \`429\` \
 Too Many Requests. For more information, see \

 [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

List meeting polls

- *\`Method:\\*\` \`GET\`
 - *\`Path:\\*\` \`/meetings/{meetingId}/polls\`
 - *\`Tags:\\*\` Polls

Polls allow the meeting host to survey attendees. List all [polls](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings) of a meeting.

****Prerequisites**:**

- Host user type must be ****Pro**** or higher plan.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
 `meeting:read:admin`, `meeting:read`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
 `meeting:read:list\_polls`, `meeting:read:list\_polls:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** `LIGHT`

Responses

Status: 200 `HTTP Status Code:` List polls of a Meeting returned

Content-Type: application/json

****All of:****

- ****`polls`****

`array` — An array of polls.

****Items:****

****All of:****

- ****`id`****

`string` — The poll ID.

- ****`status`****

`string`, possible values: `notstart`, `started`, `ended`, `sharing`, `deactivated` — The meeting poll's status. `notstart` - Poll not started `started` - Poll started `ended` - Poll ended `sharing` - Sharing poll results `deactivated` - Poll deactivated

* ****`anonymous`****

`boolean`, default: `false` — Whether meeting participants can answer poll questions anonymously. This value defaults to `false`.

* ****`poll\_type`****

`integer`, possible values: `1`, `2`, `3` — The type of poll. `1` - Poll. `2` - Advanced Poll. This feature must be enabled in your Zoom account. `3` - Quiz. This feature must be enabled in your Zoom account. This value defaults to `1`.

* ****`questions`****

`array` — Information about the poll's questions.

****Items:****

- ****`answer\_max\_character`****

`integer` — The allowed maximum number of characters. This field only applies to `short\_answer` and `long\_answer` polls: `1` For `short\_answer` polls, a maximum of 500 characters. `2` For `long\_answer` polls, a maximum of 2,000 characters.

- ****`answer\_min\_character`****

`integer` — The allowed minimum number of characters. This field only applies to `short\_answer` and `long\_answer` polls. You must provide at least a `1` character minimum value.

- ****`answer\_required`****

`boolean`, default: `false` — Whether participants must answer the question: `true` — The participant must answer the question. `false` — The participant does not need to answer the question. ****Note:**** When the poll's `type` value is `1` (Poll), this value defaults to `true`. When the poll's `type` value is the `2` (Advanced Poll) or `3` (Quiz) values, this value defaults to `false`.

- ****`answers`****

``array`` — The poll question's available answers. This field requires a ``minimum`` of two answers. ``single`` and ``multiple`` polls, you can only provide a maximum of 10 answers. ``matching`` polls, you can only provide a maximum of 16 answers. ``rank_order`` polls, you can only provide a maximum of seven answers.

`**Items:**`

``string``

- `**`case_sensitive`**`

``boolean``, default: ``false`` — Whether the correct answer is case sensitive. This field only applies to ``fill_in_the_blank`` polls: ``true`` — The answer is case-sensitive. ``false`` — The answer is not case-sensitive. This value defaults to ``false``.

- `**`name`**`

``string`` — The poll question, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- `**`prompts`**`

``array`` — Information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You ``must`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating_min_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``required`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box: ``true`` — Show as a drop-down box. ``false`` — Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``single``, ``multiple``, ``matching``, ``rank_order``, ``short_answer``,

"long_answer", "fill_in_the_blank", "rating_scale" — The poll's question and answer type: * \single\ \‐ Single choice. * \multiple\ \‐ Multiple choice. * \matching\ \‐ Matching. * \rank_order\ \‐ Rank order. * \short_answer\ \‐ Short answer. * \long_answer\ \‐ Long answer. * \fill_in_the_blank\ \‐ Fill in the blank. * \rating_scale\ \‐ Rating scale.

* **`title`**

`string` — The poll's title, up to 64 characters.

- **`total\_records`**

`integer` — The number of all records available across pages

****Example:****

```
``json
{
  "polls": [
    {
      "id": "QalIoKwLTJehBJ8e1xRrbQ",
      "status": "notstart",
      "anonymous": true,
      "poll_type": 2,
      "questions": [
        {
          "answer_max_character": 200,
          "answer_min_character": 1,
          "answer_required": false,
          "answers": [
            "Extremely useful"
          ],
          "case_sensitive": false,
          "name": "How useful was this meeting?",
          "prompts": [
            {
              "prompt_question": "How are you?",
              "prompt_right_answers": [
                "Good"
              ]
            }
          ],
          "rating_max_label": "Extremely Likely",
          "rating_max_value": 4,
          "rating_min_label": "Not likely",
          "rating_min_value": 0,
          "right_answers": [
            "Good"
          ],
          "show_as_dropdown": false,
          "type": "single"
        }
      ],
      "title": "Learn something new"
    }
  ],
  "total_records": 1
}
```

Status: 400 **HTTP Status Code:** \400\ \
 Bad Request **Error Code:** \4400\ \
 Meeting polls disabled. To enable this feature, enable the "Meeting Polls/Quizzes" setting in the Zoom web portal's "Settings" interface. \
 Error Code: \3161\ \
 Meeting hosting and scheduling capabilities are not allowed for your user account. \

Status: 404 **HTTP Status Code:** \404\ \
 Not Found **Error Code:** \404\ \
 Meeting Poll not found \

Status: 429 **HTTP Status Code:** \429\ \
 Too Many Requests. For more information, see \[rate limits]\(\/docs\/api\/rest\/rate-limits\/).

Create a meeting poll

- ****Method:**** `POST`
 - ****Path:**** \meetings\/{meetingId}\/polls`
 - ****Tags:**** Polls

Polls allow the meeting host to survey attendees. Create a [poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings) for a meeting.

****Prerequisites**:**

- Host user type must be ****Pro**** or higher plan.
- Polling feature must be enabled in the host's account.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
``meeting:write:admin`,`meeting:write``

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
``meeting:write:poll`,`meeting:write:poll:admin``

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits)**** ``LIGHT``

Request Body

Content-Type: application/json

****All of:****

- ****`anonymous`****

``boolean``, default: ``false`` — Whether meeting participants answer poll questions anonymously. This value defaults to ``false``.

- ****`poll\_type`****

``integer``, possible values: ``1, 2, 3`` — The type of poll: ``1`` — Poll. ``2`` — Advanced Poll. This feature must be enabled in your Zoom account. ``3`` — Quiz. This feature must be enabled in your Zoom account. This value defaults to ``1``.

- ****`questions`****

``array`` — The information about the poll's questions.

****Items:****

- ****`answer\_max\_character`****

``integer`` — The allowed maximum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls: ``1`` For ``short_answer`` polls, a maximum of 500 characters. ``2`` For ``long_answer`` polls, a maximum of 2,000 characters.

- ****`answer\_min\_character`****

``integer`` — The allowed minimum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls. You must provide at least a ``one`` character minimum value.

- ****`answer\_required`****

``boolean``, default: ``false`` — Whether participants must answer the question: ``true`` — The participant must answer the question. ``false`` — The participant does not need to answer the question. ****Note:**** When the poll's ``type`` value is ``1`` (Poll), this value defaults to ``true``. When the poll's ``type`` value is the ``2`` (Advanced Poll) or ``3`` (Quiz) values, this value defaults to ``false``.

- ****`answers`****

``array`` — The poll question's available answers. This field requires a ``minimum`` of two answers. ``1`` For ``single`` and ``multiple`` polls, you can only provide a maximum of 10 answers. ``2`` For ``matching`` polls, you can only provide a maximum of 16 answers. ``3`` For ``rank_order`` polls, you can only provide a maximum of seven answers.

****Items:****

``string``

- ****`case\_sensitive`****

``boolean``, default: ``false`` — Whether the correct answer is case sensitive. This field only applies to ``fill_in_the_blank`` polls: ``true`` — The answer is case-sensitive. ``false`` — The answer is not case-sensitive. This value defaults to ``false``.

- ****`name`****

``string`` — The poll question, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- ****`prompts`****

``array`` — The information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You ``*`must`*`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``*`` For ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``*`` For ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating_min_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``*`required`*`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box: ``*`true`` — Show as a drop-down box. ``*`false`` — Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``"single"`, "multiple"`, "matching"`, "rank_order"`, "short_answer"`, "long_answer"`, "fill_in_the_blank"`, "rating_scale" — The poll's question and answer type: `*`single` — Single choice. `*`multiple` — Multiple choice. `*`matching` — Matching. `*`rank_order` — Rank order. `*`short_answer` — Short answer. `*`long_answer` — Long answer. `*`fill_in_the_blank` — Fill in the blank. `*`rating_scale` — Rating scale.`

- `**`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

````json`

```
{
 "anonymous": true,
 "poll_type": 2,
 "questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
```

```

 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
}
],
"title": "Learn something new"
}
},
}

```

#### #### Responses

##### Status: 201 `\**HTTP Status Code:\** \`201\`` Meeting Poll Created

##### Content-Type: application/json

**\*\*All of:\*\***

- **\*\*`id`\*\***

``string`` — The meeting poll ID

- **\*\*`status`\*\***

``string``, possible values: ``"notstart", "started", "ended", "sharing"`` — The status of the meeting poll:  
`\`notstart\`` - Poll not started `\`started\`` - Poll started `\`ended\`` - Poll ended `\`sharing\`` - Sharing poll results

**\* **\*\*`anonymous`\*\*****

``boolean``, default: ``false`` — Whether meeting participants answer poll questions anonymously. This value defaults to `\`false\``.

**\* **\*\*`poll\_type`\*\*****

``integer``, possible values: ``1, 2, 3`` — The type of poll: `\* \`1\` \&mdash; Poll. \* \`2\` \&mdash; Advanced Poll. This feature must be enabled in your Zoom account. \* \`3\` \&mdash; Quiz. This feature must be enabled in your Zoom account. This value defaults to \`1\`.`

**\* **\*\*`questions`\*\*****

``array`` — The information about the poll's questions.

**\*\*Items:\*\***

- **\*\*`answer\_max\_character`\*\***

``integer`` — The allowed maximum number of characters. This field only applies to `\`short\_answer\`` and `\`long\_answer\`` polls: `\* For \`short\_answer\` polls, a maximum of 500 characters. \* For \`long\_answer\` polls, a maximum of 2,000 characters.`

- **\*\*`answer\_min\_character`\*\***

``integer`` — The allowed minimum number of characters. This field only applies to `\`short\_answer\`` and `\`long\_answer\`` polls. You must provide at least a `\**one\**` character minimum value.

- **\*\*`answer\_required`\*\***

``boolean``, default: ``false`` — Whether participants must answer the question: `\* \`true\` \&mdash; The participant must answer the question. \* \`false\` \&mdash; The participant does not need to answer the question. \**Note:\** \* When the poll's \`type\` value is \`1\` (Poll), this value defaults to \`true\`. \* When the poll's \`type\` value is the \`2\` (Advanced Poll) or \`3\` (Quiz) values, this value defaults to \`false\`.`

```

- answers

 array — The poll question's available answers. This field requires a minimum of two answers.
 For single and multiple polls, you can only provide a maximum of 10 answers. For matching
 polls, you can only provide a maximum of 16 answers. For rank_order polls, you can only provide a
 maximum of seven answers.

 Items:

 string

- case_sensitive

 boolean, default: false — Whether the correct answer is case sensitive. This field only applies to
 fill_in_the_blank polls: true — The answer is case-sensitive. false — The
 answer is not case-sensitive. This value defaults to false.

- name

 string — The poll question, up to 1024 characters. For fill_in_the_blank polls, this field is
 the poll's question. For each value that the user must fill in, ensure that there are the same number of
 right_answers values.

- prompts

 array — The information about the prompt questions. This field only applies to matching and
 rank_order polls. You must provide a minimum of two prompts, up to a maximum of 10 prompts.

 Items:

 - prompt_question

 string — The question prompt's title.

 - prompt_right_answers

 array — The question prompt's correct answers: For matching polls, you must provide a
 minimum of two correct answers, up to a maximum of 10 correct answers. For rank_order polls, you can
 only provide one correct answer.

 Items:

 string

- rating_max_label

 string — The high score label for the rating_max_value field. This field only applies to the
 rating_scale poll.

- rating_max_value

 integer — The rating scale's maximum value, up to a maximum value of 10. This field only applies to
 the rating_scale poll.

- rating_min_label

 string — The low score label for the rating_min_value field. This field only applies to the
 rating_scale poll.

- rating_min_value

 integer — The rating scale's minimum value. This value cannot be less than zero. This field only
 applies to the rating_scale poll.

- right_answers

 array — The poll question's correct answer(s). This field is required if the poll's type
 value is 3 (Quiz). For single and matching polls, this field only accepts one answer.

 Items:

 string

- show_as_dropdown

 boolean, default: false — Whether to display the radio selection as a drop-down box: true
 — Show as a drop-down box. false — Do not show as a drop-down box. This value defaults
 to false.

```

- **type** — The poll's question and answer type: `single`, `multiple`, `matching`, `rank_order`, `short_answer`, `long_answer`, `fill_in_the_blank`, `rating_scale` — The poll's question and answer type: `single` — Single choice. `multiple` — Multiple choice. `matching` — Matching. `rank_order` — Rank order. `short_answer` — Short answer. `long_answer` — Long answer. `fill_in_the_blank` — Fill in the blank. `rating_scale` — Rating scale.

**title** — The poll's title, up to 64 characters.

**Example:**

```
```json
{
  "id": "QaIioKwLTJehBJ8e1xRrbQ",
  "status": "notstart",
  "anonymous": true,
  "poll_type": 2,
  "questions": [
    {
      "answer_max_character": 200,
      "answer_min_character": 1,
      "answer_required": false,
      "answers": [
        "Extremely useful"
      ],
      "case_sensitive": false,
      "name": "How useful was this meeting?",
      "prompts": [
        {
          "prompt_question": "How are you?",
          "prompt_right_answers": [
            "Good"
          ]
        }
      ],
      "rating_max_label": "Extremely Likely",
      "rating_max_value": 4,
      "rating_min_label": "Not likely",
      "rating_min_value": 0,
      "right_answers": [
        "Good"
      ],
      "show_as_dropdown": false,
      "type": "single"
    }
  ],
  "title": "Learn something new"
}
```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 4400` `Meeting polls disabled. To enable this feature, enable the "Meeting Polls/Quizzes" setting in the Zoom web portal's "Settings" interface. Advanced meeting polls disabled. To enable this feature, enable the "Allow host to create advanced polls and quizzes" setting in the Zoom web portal's "Settings" interface.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 404` `Meeting not found`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

Get a meeting poll

- **Method:** `GET`
 - **Path:** `/meetings/{meetingId}/polls/{pollId}`
 - **Tags:** Polls

Retrieves information about a specific meeting [poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings).

Prerequisites:

- Host must have Pro or higher plan.
- Enable the **Meeting Polls/Quizzes** setting in the Zoom web portal.


```

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`meeting:read:admin`,`meeting:read`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`meeting:read:poll`,`meeting:read:poll:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

#### Responses

##### Status: 200 \*\*HTTP Status Code:\*\* `200` Meeting Poll object returned

##### Content-Type: application/json

**All of:**

- `id`

  `string` — The meeting poll ID.

- `status`

  `string`, possible values: `"notstart", "started", "ended", "sharing", "deactivated"` — The meeting poll's status.
  `notstart` - Poll not started
  `started` - Poll started
  `ended` - Poll ended
  `sharing` - Sharing poll results
  `deactivated` - Poll deactivated

* `anonymous`

  `boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value defaults to `false`.

* `poll_type`

  `integer`, possible values: `1, 2, 3` — The poll's type.
  `1` - Poll.
  `2` - Advanced poll. This feature must be enabled in your Zoom account.
  `3` - Quiz. This feature must be enabled in your Zoom account. This value defaults to `1`.

* `questions`

  `array` — Information about the poll's questions.

  **Items:**

  - `answer_max_character`

    `integer` — The allowed maximum number of characters. This field only applies to `short_answer` and `long_answer` polls.
    For `short_answer` polls, a maximum of 500 characters.
    For `long_answer` polls, a maximum of 2,000 characters.

  - `answer_min_character`

    `integer` — The allowed minimum number of characters. This field only applies to `short_answer` and `long_answer` polls.
    You must provide at least a one-character minimum value.

  - `answer_required`

    `boolean`, default: `false` — Whether participants must answer the question.
    `true` - The participant must answer the question.
    `false` - The participant does not need to answer the question.

    **Note:** When the poll's `type` value is `1` (Poll), this value defaults to `true`.
    When the poll's `type` value is the `2` (Advanced Poll) or `3` (Quiz) values, this value defaults to `false`.

  - `answers`

    `array` — The poll question's available answers. This field requires a minimum of two answers.
    For `single` and `multiple` polls, you can only provide a maximum of 10 answers.
    For `matching` polls, you can only provide a maximum of 16 answers.
    For `rank_order` polls, you can only provide a maximum of seven answers.

    **Items:**

    `string`

  - `case_sensitive`

    `boolean`, default: `false` — Whether the correct answer is case sensitive. This field only applies to `fill_in_the_blank` polls.
    `true` — The answer is case-sensitive.
    `false` — The answer is not case-sensitive. This value defaults to `false`.

```

```

- **`name`**

`string` — The poll question, up to 1024 characters. For `fill_in_the_blank` polls, this field is
the poll's question. For each value that the user must fill in, ensure that there are the same number of
`right_answers` values.

- **`prompts`**

`array` — The information about the prompt questions. This field only applies to `matching` and
`rank_order` polls. You must provide a minimum of two prompts, up to a maximum of 10 prompts.

Items:

- **`prompt_question`**

`string` — The question prompt's title.

- **`prompt_right_answers`**

`array` — The question prompt's correct answers: For `matching` polls, you must provide a
minimum of two correct answers, up to a maximum of 10 correct answers. For `rank_order` polls, you can
only provide one correct answer.

Items:

`string`

- **`rating_max_label`**

`string` — The high score label for the `rating_max_value` field. This field only applies to the
`rating_scale` poll.

- **`rating_max_value`**

`integer` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to
the `rating_scale` poll.

- **`rating_min_label`**

`string` — The low score label for the `rating_min_value` field. This field only applies to the
`rating_scale` poll.

- **`rating_min_value`**

`integer` — The rating scale's minimum value. This value cannot be less than zero. This field only
applies to the `rating_scale` poll.

- **`right_answers`**

`array` — The poll question's correct answer(s). This field is required if the poll's `type` value is
`3` (Quiz). For `single` and `matching` polls, this field only accepts one answer.

Items:

`string`

- **`show_as_dropdown`**

`boolean`, default: `false` — Whether to display the radio selection as a drop-down box. True -
Show as a drop-down box. False - Do not show as a drop-down box. This value defaults to `false`.

- **`type`**

`string`, possible values: `single`, `multiple`, `matching`, `rank_order`, `short_answer`,
`long_answer`, `fill_in_the_blank`, `rating_scale` — The poll's question and answer type. single -
Single choice. multiple - Multiple choice. matching - Matching. rank_order - Rank
order. short_answer - Short answer. long_answer - Long answer. fill_in_the_blank -
Fill in the blank. rating_scale - Rating scale.

* title

`string` — The poll's title, up to 64 characters.

Example:

``json
{
  "id": "QaIioKwLTJehBJ8e1xRrbQ",
  "status": "notstart",
  "anonymous": true,

```

```

"poll_type": 2,
"questions": [
  {
    "answer_max_character": 200,
    "answer_min_character": 1,
    "answer_required": false,
    "answers": [
      "Extremely useful"
    ],
    "case_sensitive": false,
    "name": "How useful was this meeting?",
    "prompts": [
      {
        "prompt_question": "How are you?",
        "prompt_right_answers": [
          "Good"
        ]
      }
    ]
  },
  {
    "rating_max_label": "Extremely Likely",
    "rating_max_value": 4,
    "rating_min_label": "Not likely",
    "rating_min_value": 0,
    "right_answers": [
      "Good"
    ],
    "show_as_dropdown": false,
    "type": "single"
  }
],
"title": "Learn something new"
}

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 4400` `Meeting polls disabled. To enable this feature, enable the "Meeting Polls/Quizzes" setting in the Zoom web portal's "Settings" interface.` `Error Code: 3161` `Meeting hosting and scheduling capabilities are not allowed for your user account.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 404` `Meeting Poll not found.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).`

Update a meeting poll

```

- Method: PUT
- Path: /meetings/{meetingId}/polls/{pollId}
- Tags: Polls

```

Polls allow the meeting host to survey attendees. Update information of a specific meeting [poll] (<https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings>).

Prerequisites:

- Host user type must be **Pro** or higher plan.
- The **Meeting Polls/Quizzes** setting enabled in the Zoom web portal.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

Scopes(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:write:admin`, `meeting:write`

Granular Scopes(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `meeting:update:poll`, `meeting:update:poll:admin`

Rate Limit Label(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **LIGHT**

Request Body

Content-Type: application/json

All of:

- **anonymous**

`boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value defaults to `false`.

- **poll_type**

``integer``, possible values: ``1, 2, 3`` — The type of poll. ``1`` - Poll. ``2`` - Advanced Poll. This feature must be enabled in your Zoom account. ``3`` - Quiz. This feature must be enabled in your Zoom account. This value defaults to ``1``.

- `**`questions`**`

``array`` — The information about the poll's questions.

`**Items:**`

- `**`answer_max_character`**`

``integer`` — The allowed maximum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls. ``1`` For ``short_answer`` polls, a maximum of 500 characters. ``2`` For ``long_answer`` polls, a maximum of 2,000 characters.

- `**`answer_min_character`**`

``integer`` — The allowed minimum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls. You must provide at least a one character minimum value.

- `**`answer_required`**`

``boolean``, default: ``false`` — Whether participants must answer the question. ``true`` - The participant must answer the question. ``false`` - The participant does not need to answer the question. `**Note:**` When the poll's ``type`` value is ``1`` (Poll), this value defaults to ``true``. When the poll's ``type`` value is the ``2`` (Advanced Poll) or ``3`` (Quiz) values, this value defaults to ``false``.

- `**`answers`**`

``array`` — The poll question's available answers. This field requires a ``minimum`` of two answers. ``1`` For ``single`` and ``multiple`` polls, you can only provide a maximum of 10 answers. ``2`` For ``matching`` polls, you can only provide a maximum of 16 answers. ``3`` For ``rank_order`` polls, you can only provide a maximum of seven answers.

`**Items:**`

``string``

- `**`case_sensitive`**`

``boolean``, default: ``false`` — Whether the correct answer is case sensitive. This field only applies to ``fill_in_the_blank`` polls: ``true`` - The answer is case-sensitive. ``false`` - The answer is not case-sensitive. This value defaults to ``false``.

- `**`name`**`

``string`` — The poll question, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You must provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``1`` For ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``2`` For ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating\_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating\_min\_value`` field. This field only applies to the ``rating\_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating\_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``**required`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box. ``true`` - Show as a drop-down box. ``false`` - Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``"single"`, "multiple"`, "matching"`, "rank_order"`, "short_answer"`, "long_answer"`, "fill_in_the_blank"`, "rating_scale` — The poll's question and answer type. `single` - Single choice. `multiple` - Multiple choice. `matching` - Matching. `rank_order` - Rank order. `short_answer` - Short answer. `long_answer` - Long answer. `fill_in_the_blank` - Fill in the blank. `rating_scale` - Rating scale.`

- `**`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

```
```json
{
 "anonymous": true,
 "poll_type": 2,
 "questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
 }
],
 "title": "Learn something new"
},
{
 "type": "single"
}
],
"title": "Learn something new"
}
```
```

Responses

Status: 204 **HTTP Status Code:** \`204\` Meeting Poll Updated

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`4400\` \
 Meeting polls disabled. To enable this feature, enable the "Meeting Polls/Quizzes" setting in the Zoom web portal's "Settings" interface. \
 Error Code: \`3161\` \
 Meeting hosting and scheduling capabilities are not allowed for your user account. \
 Error Code: \`4400\` \
 Advanced meeting polls disabled. To enable this feature, enable the **Allow host to create advanced polls and quizzes** setting in the Zoom web portal's **Settings** interface. \

Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`404\` \
 Meeting Poll not found \
 Error Code: \`3001\` \
 Meeting does not exist: {meetingId}. \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(</docs/api/rest/rate-limits/>).

Delete a meeting poll

- **Method:** \`DELETE\`
- **Path:** \`/meetings/{meetingId}/polls/{pollId}\`
- **Tags:** Polls

Polls allow the meeting host to survey attendees. Delete a meeting [poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings).

Prerequisites:

- Host user type must be **Pro**.
- Polling feature should be enabled in the host's account.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 \`meeting:write:admin\`, \`meeting:write\`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 \`meeting:delete:poll\`, \`meeting:delete:poll:admin\`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

Responses

Status: 204 **HTTP Status Code:** \`204\` Meeting Poll deleted

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`4400\` \
 Meeting polls disabled. To enable this feature, enable the **Meeting Polls/Quizzes** setting in the Zoom web portal's **Settings** interface. \
 Error Code: \`3161\` \
 Meeting hosting and scheduling capabilities are not allowed for your user account. \

Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`404\` \
 Meeting poll not found. \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(</docs/api/rest/rate-limits/>).

List past meeting's poll results

- **Method:** \`GET\`
- **Path:** \`/past\_meetings/{meetingId}/polls\`
- **Tags:** Polls

[Polls](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings) allow the meeting host to survey attendees. List poll results of a meeting.

Prerequisites:

- Host user type must be **Pro**.
- Meeting must be a scheduled meeting. Instant meetings do not have polling features enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 \`meeting:read:admin\`, \`meeting:read\`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 \`meeting:read:list\_poll\_results\`, \`meeting:read:list\_poll\_results:admin\`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **MEDIUM**

Responses

Status: 200 **HTTP Status Code:** \`200\` **OK** Polls returned successfully.

Content-Type: application/json

- **id**

`integer`, format: `int64` — `[Meeting ID]`(<https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID->): Unique identifier of the meeting in `long` format (represented as `int64` data type in JSON), also known as the meeting number.

- **questions**

`array`

Items:

- **email**

`string` — Email address of the user who submitted answers to the poll. If the user is `not` part of the host's account, this returns an empty string value, with some exceptions. See `[Email address display rules]`(<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules>) for details.

- **name**

`string` — Name of the user who submitted answers to the poll. If `anonymous` option is enabled for a poll, the participant's polling information will be kept anonymous and the value of `name` field will be `Anonymous Attendee`.

- **question_details**

`array`

Items:

- **answer**

`string` — Answer submitted by the user.

- **date_time**

`string`, format: `date-time` — Date and time at which the answer to the poll was submitted.

- **polling_id**

`string` — Unique identifier of the poll.

- **question**

`string` — Question asked during the poll.

- **start_time**

`string`, format: `date-time` — The start time of the meeting.

- **uuid**

`string` — Meeting UUID.

Example:

```
```json
{
 "id": 93398114182,
 "questions": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "question_details": [
 {
 "answer": "Good",
 "date_time": "2022-03-26T05:37:59Z",
 "polling_id": "QalIoKWLtJehBJ8e1xRrbQ",
 "question": "How are you?"
 }
]
 }
],
 "start_time": "2022-03-26T05:37:59Z",
 "uuid": "Vg8IdgluR5WDeWIkPj1ElQ=="
},
```,
```

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`12702\` \
 Can not access a meeting a year ago. \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(\/docs\/api\/rest\/rate-limits\/).

Get sign In / sign out activity report

- **Method:** `GET`
- **Path:** `/report/activities`
- **Tags:** Reports

Retrieve a list of sign in / sign out activity logs [report](https://support.zoom.us/hc/en-us/articles/201363213-Getting-Started-with-Reports) of users under a Zoom account.

Prerequisites

- Pro or higher plan.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:user_activities:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `Heavy`

Responses

Status: 200 **HTTP Status Code:** \`200\` Success

Content-Type: application/json

- **activity_logs**

`array` — Array of activity logs.

Items:

- **client_type**

`string` — The client interface type using which the activity was performed.

- **email**

`string`, format: `email` — Email address of the user used for the activity.

- **ip_address**

`string` — The IP address of the user's device.

- **time**

`string`, format: `date-time` — Time during which the activity occurred.

- **type**

`string`, possible values: `"Sign in", "Sign out"` — The type of activity. `"Sign in"` — Sign in activity by user. `"Sign out"` — Sign out activity by user.

- **version**

`string` — Zoom client version of the user.

- **from**

`string` — Start date from which you want the activity logs report to be generated.

- **next_page_token**

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- **page_size**

`integer` — The number of records returned with a single API call.

- **to**

`string` — End date until which you want the activity logs report to be generated

****Example:****

```

```json
{
 "activity_logs": [
 {
 "client_type": "Browser",
 "email": "jchill@example.com",
 "ip_address": "192.0.2.1",
 "time": "2019-09-15T19:13:41Z",
 "type": "Sign out",
 "version": "5.9.1.2581"
 }
],
 "from": "2019-09-01T00:00:00Z",
 "next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
 "page_size": 30,
 "to": "2019-09-20T00:00:00Z"
}
```

```

Status: 400 ****HTTP Status Code:**** 400 ****Error Code:**** 200 ****Message:**** Bad Request No permission.

Status: 429 ****HTTP Status Code:**** 429 ****Message:**** Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get billing reports

```

- **Method:** GET
- **Path:** /report/billing
- **Tags:** Reports

```

Get department billing reports of a Zoom account.

****Prerequisites:****

- Pro or a higher account with Department Billing option enabled. Contact Zoom Support team for details.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** report:read:admin

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** report:read:billing:admin

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** Heavy

Responses

Status: 200 ****HTTP Status Code:**** 200 ****Message:**** Billing report returned.

Content-Type: application/json

```

- **`billing_reports`**

```

```

  `array`

```

```

  **Items:**

```

```

  - **`end_date`**

```

```

    `string`, format: `date` — End date of the billing period.

```

```

  - **`id`**

```

`string` — Unique Identifier of the report. Use this ID to retrieve billing invoice via the `Get Billing Invoices API`. You can also use this ID to export a CSV file of the billing report from this URL: `https://zoom.us/account/report/billing/export?id={id}`.

```

  - **`start_date`**

```

```

    `string`, format: `date` — Start date of the billing period.

```

```

  - **`tax_amount`**

```

```

    `string` — Total tax amount for this billing period.

```

```

  - **`total_amount`**

```

```

    `string` — Total billing amount for this billing period.

```

- **type**

`integer`, possible values: `0`, `1` — Type of the billing report. The value should be either of the following: `0` - Detailed Billing Reports `1` - Custom Billing Reports

- **currency**

`string` — Currency of the billed amount.

Example:

`json`

```
{
  "billing_reports": [
    {
      "end_date": "2022-03-25",
      "id": "indfhgfhfho",
      "start_date": "2022-03-25",
      "tax_amount": "456",
      "total_amount": "456",
      "type": 1
    }
  ],
  "currency": "USD"
}
```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

Get billing invoice reports

- **Method:** `GET`
 - **Path:** `/report/billing/invoices`
 - **Tags:** Reports

Get department billing invoices reports for a specific billing period. Provide the `billing_id` of the billing period for which you would like to retrieve the invoices. Retrieve this ID from the **Get Billing Reports** API.

Prerequisites:

- Pro or a higher account with Department Billing option enabled. Contact the Zoom Support team to enable this feature.

[Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:admin`

[Granular Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:billing_invoice:admin`

[Rate Limit Label] (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `HEAVY`

Responses

Status: 200 `HTTP Status Code: 200` `OK` Billing Invoice reports returned.

Content-Type: `application/json`

- **currency**

`string` — Currency of the billed amount in the invoice.

- **invoices**

`array`

Items:

- **end_date**

`string`, format: `date` — End date of the invoice period.

- **invoice_charge_name**

`string` — Name of the invoice.

- **invoice_number**
`string` — Invoice number
- **quantity**
`integer` — Number of licenses bought.
- **start_date**
`string`, format: `date` — Start date of the invoice period.
- **tax_amount**
`string` — Tax amount in the invoice.
- **total_amount**
`string` — Total billed amount in the invoice.

Example:

```
```json
{
 "currency": "USD",
 "invoices": [
 {
 "end_date": "2022-03-25",
 "invoice_charge_name": "Audio Conferencing Options",
 "invoice_number": "3",
 "quantity": 45,
 "start_date": "2022-03-25",
 "tax_amount": "34",
 "total_amount": "45"
 }
]
}
```

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **Invalid parameter "billing\_id"**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 5010 **Report does not exist.**

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]](/docs/api/rest/rate-limits/).

### Get cloud recording usage report

- **Method:** GET
- **Path:** /report/cloud\_recording
- **Tags:** Reports

Retrieve cloud recording usage report for a specified period. You can only get cloud recording reports that is one day earlier than the current date and for the most recent period of 6 months. The date gap between from and to dates should be smaller or equal to 30 days.

**Prerequisites**

- Pro or higher plan.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): report:read:admin

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): Heavy

#### Responses

##### Status: 200 **HTTP Status Code:** 200 **Cloud Recording Report Returned**

##### Content-Type: application/json

**All of:**

- **from**  
`string`, format: `date` — Start date for this report
- **to**

```

`string`, format: `date` — End date for this report

* **`cloud_recording_storage`**

`array` — Array of cloud usage objects

Items:

- **`date`**

 `string`, format: `date` — Date of the usage

- **`free_usage`**

 `string` — Free storage

- **`plan_usage`**

 `string` — Paid storage

- **`usage`**

 `string` — Storage used on the date

Example:

```json
{
  "from": "2021-12-01",
  "to": "2021-12-30",
  "cloud_recording_storage": [
    {
      "date": "2021-12-05",
      "free_usage": "Unlimited",
      "plan_usage": "3 TB",
      "usage": "3 MB"
    }
  ]
}
```

Status: 400, `HTTP Status Code: 400` \
 Bad Request `Error Code: 200` \
 No permission.\

Status: 429 `HTTP Status Code: 429` \
 Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

Get daily usage report

- **Method:** `GET`
- **Path:** `/report/daily`
- **Tags:** Reports

Retrieve daily report to access the account-wide usage of Zoom services for each day in a given month. It lists the number of new users, meetings, participants, and meeting minutes.

Prerequisites

- Pro or higher plan.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `HEAVY`

Responses

Status: 200 `HTTP Status Code: 200` Daily report retrieved. This is only available for paid accounts: {accountId}.

Content-Type: application/json

- **`dates`**

 `array` — Array of date objects.

 Items:

 - **`date`**

 `string`, format: `date` — Date for this object.

```

- **meeting\_minutes**  
 integer — Number of meeting minutes on this date.
- **meetings**  
 integer — Number of meetings on this date.
- **new\_users**  
 integer — Number of new users on this date.
- **participants**  
 integer — Number of participants on this date.
- **month**  
 integer — Month for this report.
- **year**  
 integer — Year for this report.

**Example:**

```
```json
{
  "dates": [
    {
      "date": "2022-03-01",
      "meeting_minutes": 34,
      "meetings": 2,
      "new_users": 3,
      "participants": 4
    }
  ],
  "month": 3,
  "year": 2022
}
```

Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300
 Daily report can only be provided for a month that falls within the recent 6 months. Error Code: 200 No permission.

Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rate-limits/).

Get disclaimer report

- **Method:** GET
- **Path:** /report/disclaimer
- **Tags:** Reports

Retrieve a list of disclaimer records.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:admin

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:disclaimer:admin

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): HEAVY

Responses

Status: 200 Disclaimer records list.

Content-Type: application/json

- **disclaimer_records**
 array — Array of disclaimer records.
- Items:**
- **client_type**
 string — User login client types. When the user is a guest, the client type is empty.

```

- **`disclaimer_status`**

  `string`, possible values: `"Agree", "Cancel", "Passive Agree", "Decline Attend"` — The disclaimer status.

- **`disclaimer_type`**

  `string` — The disclaimer type.

- **`display_name`**

  `string` — The disclaimer's user name.

- **`group_ids`**

  `array` — The user's group IDs.

  **Items:**

  `string` — The group ID.

- **`is_guest`**

  `boolean` — Whether the user is a guest.

- **`is_zoom_event`**

  `boolean` — Whether the meeting is a Zoom Event.

- **`meeting_id`**

  `string` — The disclaimer's meeting ID.

- **`meeting_number`**

  `integer`, format: `int64` — The disclaimer's meeting number.

- **`time`**

  `string` — The disclaimer's generated time.

- **`user_email`**

  `string` — The disclaimer's user email. There are several special cases where user email display will be handled specially. - The client type is `*gw*.pstn*`. The user email will be empty. - The user is guest. That is the `is_guest` is `*true*`. The user email will be empty. - The meeting is Zoom Event. That is the `is_zoom_event` is `*true*`. The user email will be masked.

- **`next_page_token`**

  `string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **`page_size`**

  `integer` — The number of records returned in a single API call.

```

Example:

```

```json
{
 "disclaimer_records": [
 {
 "disclaimer_status": "Agree",
 "time": "2026-01-15T10:17:35Z",
 "disclaimer_type": "AI Companion",
 "user_email": "jchill@example.com",
 "meeting_number": 93201235621,
 "meeting_id": "gm8s9L+PTEC+FG3sFbd1Cw==",
 "client_type": "iphone",
 "is_zoom_event": false,
 "is_guest": true,
 "group_ids": [
 "TaVA8QKik_1233"
],
 "display_name": "Jill Chill"
 }
],
}
```

```

```
"next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
"page_size": 30
},

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `The next page token is invalid or expired.` `Error Code: 300` `Invalid parameter: {0}.`

Status: 401 `HTTP Status Code: 401` `Unauthorized`

Status: 403 `HTTP Status Code: 403` `Forbidden` `Error Code: 12703` `No permission for the group: {0}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](https://developers.zoom.us/docs/api/rate-limits/)`.

Get history meeting and webinar list

```
- **Method:** `GET`
- **Path:** `/report/history_meetings`
- **Tags:** Reports
```

Retrieve a list of history meetings and webinars.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:admin`

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:list_history_meetings:admin`

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `HEAVY`

Responses

Status: 200 HTTP Status Code: 200 Success.

Content-Type: application/json

```
- **`history_meetings`**

`array` — Array of history meetings.

**Items:**

- **`create_time`**

  `string` — The meeting's create date and time.

- **`custom_fields`**

  `array` — The custom attributes that the host is assigned

  **Items:**

  - **`key`**

    `string` — The custom attribute's name.

  - **`value`**

    `string` — The custom attribute's value.

- **`department`**

  `string` — The host's department.

- **`duration`**

  `integer` — The meeting's duration, in minutes.

- **`end_time`**

  `string` — The meeting's end date and time.

- **`feature_used`**

  `object` — Features used in the meeting.

- **`annotation`**

  `boolean` — Whether annotation was used in the meeting.
```

- **avatar**
`boolean` — Whether anyone used an avatar in the meeting.
- **breakout_room**
`boolean` — Whether breakout room was enabled in the meeting.
- **closed_caption**
`boolean` — Whether closed caption was enabled in the meeting.
- **color_themes**
`boolean` — Whether anyone used color themes in the meeting.
- **document_collaboration**
`boolean` — Whether anyone shared the document in the meeting.
- **file_sharing**
`boolean` — Whether anyone sent files in the meeting chat.
- **gen_ai_virtual_background**
`boolean` — Whether anyone used the GenAI virtual background in the meeting.
- **immersive_scene**
`boolean` — Whether immersive scene was enabled in then meeting.
- **in_meeting_chat**
`boolean` — Whether anyone in the meeting has sent a message in the meeting chat.
- **join_by_room**
`boolean` — Whether anyone has joined the meeting by Zoom Room.
- **language_interpretation**
`boolean` — Whether language translation was used in the meeting.
- **live_transcription**
`boolean` — Whether live transcription was turned on.
- **live_translation**
`boolean` — Whether live translation was used in the meeting.
- **meeting_questions**
`boolean` — Whether the meeting questions was enabled.
- **meeting_summary**
`boolean` — Whether the meeting summary was enabled.
- **meeting_wallpaper**
`boolean` — Whether host set wallpaper in the meeting.
- **multi_share**
`boolean` — Whether multi-share was used in the meeting
- **multi_speaker**
`boolean` — Whether anyone used the multi-speaker view in the meeting.
- **personalized_audio_isolation**
`boolean` — Whether anyone used personalized audio isolation in the meeting.
- **poll**
`boolean` — Whether the meeting has poll data.

- **`portrait_lighting`**
`boolean` — Whether anyone used portrait lighting in the meeting.
- **`raise_hand`**
`boolean` — Whether anyone has raised hand in the meeting.
- **`reaction`**
`boolean` — Whether anyone sent an emoticon.
- **`record_to_cloud`**
`boolean` — Whether to record the meeting to the cloud.
- **`record_to_computer`**
`boolean` — Whether to record the meeting to the local computer.
- **`registration`**
`boolean` — Whether registration was enabled for the meeting.
- **`remote_control`**
`boolean` — Whether to use remote control in the meeting.
- **`screen_sharing`**
`boolean` — Whether the screen was shared in the meeting.
- **`smart_recording`**
`boolean` — Whether smart recording was enabled for the meeting.
- **`switch_to_mobile`**
`boolean` — Whether anyone switched the meeting to their mobile phone.
- **`telephone_usage`**
`boolean` — Whether anyone has joined the meeting by telephone.
- **`video_on`**
`boolean` — Whether the video was on in the meeting.
- **`virtual_background`**
`boolean` — Whether anyone used a virtual background in the meeting.
- **`waiting_room`**
`boolean` — Whether to open the waiting room for the meeting.
- **`whiteboard`**
`boolean` — Whether a whiteboard was used in the meeting.
- **`zoom_apps`**
`boolean` — Whether the Zoom app was used in the meeting.
- **`group`**
`array` — The host's groups
`Items:`
`string` — The host's group name
- **`host_display_name`**
`string` — The host's display name.
- **`host_email`**
`string` — The host's email address.

```

- max_concurrent_views

`integer` — The maximum number of online viewers at the same time during the webinar, excluding panelists.

- meeting_id

`integer`, format: `int64` — The [meeting ID](https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-): Unique identifier of the meeting in "long" format (represented as int64 data type in JSON), also known as the meeting number.

- meeting_uuid

`string` — The meeting unique universal identifier (UUID). Double encode your UUID when using it for API calls if the UUID begins with a '/' or contains '/' in it.

- participants

`integer` — The number of meeting participants.

- source

`string` — Whether the meeting was created directly through Zoom or via an API request:
  * If the meeting was created via an OAuth app, this field returns the OAuth app's name.
  * If the meeting was created via JWT or the Zoom Web Portal, this returns the `Zoom` value.

- start_time

`string` — The meeting's start date and time.

- topic

`string` — The meeting's topic.

- total_participant_minutes

`integer` — The total duration of all participants, in minutes.

- tracking_fields

`array` — The tracking fields and values assigned to the meeting.

Items:

- field

`string` — The label of the tracking field.

- value

`string` — The value of the tracking field.

- type

`string`, possible values: `Meeting`, `Webinar` — The meeting type, either Meeting or Webinar.

- unique_viewers

`integer` — This value shows how many people viewed the webinar on their computer. It does not include panelists or attendees who only listened by phone. Viewers who joined the meeting multiple times or from multiple devices are counted only once.

- next_page_token

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- page_size

`integer` — The number of records returned with a single API call.

```

Example:

```

```json
{
 "next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
 "page_size": 30,
 "history_meetings": [

```

```

{
 "meeting_uuid": "gm8s9L+PTEC+FG3sFbd1Cw==",
 "meeting_id": 93201235621,
 "type": "Meeting",
 "host_display_name": "Jill Chill",
 "host_email": "jchill@example.com",
 "start_time": "2024-12-23T07:09:03Z",
 "end_time": "2024-12-23T08:09:03Z",
 "topic": "My Meeting",
 "participants": 5,
 "duration": 60,
 "total_participant_minutes": 83,
 "department": "Developers",
 "group": "group_01",
 "source": "Zoom",
 "unique_viewers": 4,
 "max_concurrent_views": 3,
 "create_time": "2024-12-23T06:09:03Z",
 "custom_fields": [
 {
 "key": "attribute 1",
 "value": "test"
 }
],
 "tracking_fields": [
 {
 "field": "Meeting purpose.",
 "value": "Support"
 }
],
 "feature_used": {
 "screen_sharing": true,
 "video_on": true,
 "remote_control": true,
 "closed_caption": false,
 "breakout_room": false,
 "language_interpretation": false,
 "telephone_usage": true,
 "in_meeting_chat": false,
 "poll": true,
 "join_by_room": false,
 "waiting_room": false,
 "live_transcription": false,
 "reaction": true,
 "zoom_apps": false,
 "annotation": false,
 "raise_hand": true,
 "virtual_background": true,
 "whiteboard": true,
 "immersive_scene": false,
 "avatar": true,
 "switch_to_mobile": false,
 "file_sharing": true,
 "meeting_summary": false,
 "meeting_questions": false,
 "record_to_computer": true,
 "record_to_cloud": true,
 "live_translation": false,
 "registration": false,
 "smart_recording": true,
 "multi_speaker": false,
 "meeting_wallpaper": true,
 "gen_ai_virtual_background": true,
 "multi_share": true,
 "document_collaboration": false,
 "portrait_lighting": false,
 "personalized_audio_isolation": true,
 "color_themes": false
 }
}
]
}
}

```

##### Status: 400 \\\*\\\*HTTP Status Code:\\\*\\\* \\`400\\` \\<br> Bad Request \\\*\\\*Error Code:\\\*\\\* \\`300\\` \\<br> The next page token is invalid or expired. \\<br> \\\*\\\*Error Code:\\\*\\\* \\`300\\` \\<br> Invalid parameter: {0}. \\<br>

##### Status: 401 \\\*\\\*HTTP Status Code:\\\*\\\* \\`401\\` \\<br> Unauthorized

##### Status: 403 \\\*\\\*HTTP Status Code:\\\*\\\* \\`403\\` \\<br> Forbidden \\\*\\\*Error Code:\\\*\\\* \\`12703\\` \\<br> No

permission for the group: {0}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(\/docs\/api\/rest\/rate-limits\/).

### Get a meeting activities report

- **\*\*Method:\*\*** `GET`  
 - **\*\*Path:\*\*** `/report/meeting\_activities`  
 - **\*\*Tags:\*\*** Reports

Retrieve a list of a meeting activity logs. Contact Zoom Support to enable the meeting audit trail log feature on your account.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*** `report:read:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `report:read:meeting\_activity\_log:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `HEAVY`

#### Responses

##### Status: 200 \\*\\*HTTP Status Code:\\*\\* \`200\` Success. Only available for Paid or ZMP account {accountId}.

##### Content-Type: application/json

- **\*\*`meeting\_activity\_logs`\*\***

`array` — Array of meeting activity logs.

**\*\*Items:\*\***

- **\*\*`activity\_category` (required)\*\***

`string` — The operator's activity category. -1 - All Activities. 0 - Meeting created. 1 - Meeting started. 2 - User joined. 3 - User left. 4 - Remote control. 5 - In-meeting chat. 9 - Meeting ended.

- **\*\*`activity\_detail` (required)\*\***

`string` — The operator's activity detail.

- **\*\*`activity\_time` (required)\*\***

`string` — The operator's activity time.

- **\*\*`meeting\_number` (required)\*\***

`string` — The meeting number.

- **\*\*`operator` (required)\*\***

`string` — The operator's display name.

- **\*\*`operator\_email` (required)\*\***

`string` — The operator's email.

- **\*\*`next\_page\_token`\*\***

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **\*\*`page\_size`\*\***

`number`, default: `30` — The number of records returned with a single API call.

**\*\*Example:\*\***

```
```json
{
  "meeting_activity_logs": [
    {
      "meeting_number": "982 610 0285",
      "activity_time": "2024-03-21 07:09:03:216",
      "operator": "Jill Chill",
      "operator_email": "jillchill@example.com",
      "activity_category": "Meeting Started",

```

```

    "activity_detail": "Meeting Started"
  }
],
"next_page_token": "z5qFlq5cvH7C46k7PT7BQmpnW6izo0UWWt3",
"page_size": 30
}

```

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request

Status: 403 **HTTP Status Code:** \`403\` \
 Forbidden No permission.

Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`1010\` \
 User does not belong to this account {accountId}.\
 \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

Get meeting detail reports

```

- **Method:** `GET`
- **Path:** `/report/meetings/{meetingId}`
- **Tags:** Reports

```

Get a detailed report for a past meeting.

****Prerequisites****

- Pro or a higher plan.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** `report:read:admin`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** `report:read:meeting:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** `HEAVY`

Responses

Status: 200 **HTTP Status Code:** \`200\` Meeting details returned. This is only available for paid account.

Content-Type: application/json

```

- **`custom_keys`**

```

`array` — Custom keys and values assigned to the meeting.

****Items:****

```

- **`key`**

```

`string` — Custom key associated with the user.

```

- **`value`**

```

`string` — Value of the custom key associated with the user.

```

- **`dept`**

```

`string` — Department of the host.

```

- **`duration`**

```

`integer` — Meeting duration.

```

- **`end_time`**

```

`string`, format: `date-time` — Meeting end time.

```

- **`id`**

```

`integer`, format: `int64` — \[Meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-): Unique identifier of the meeting in \"**long**"; format(represented as int64 data type in JSON), also known as the meeting number.

```

- **`participants_count`**

```

`integer` — Number of meeting participants.

```
- **`start_time`**
```

```
`string`, format: `date-time` — Meeting start time.
```

```
- **`topic`**
```

```
`string` — Meeting topic.
```

```
- **`total_minutes`**
```

``integer`` — Number of meeting minutes. This represents the total amount of meeting minutes attended by each participant including the host, for meetings hosted by the user. For instance if there were one host(named A) and one participant(named B) in a meeting, the value of `total\_minutes` would be calculated as below: `\*\`total_minutes\`\* = Total Meeting Attendance Minutes of A + Total Meeting Attendance Minutes of B`

```
- **`tracking_fields`**
```

``array`` — Tracking fields.

```

**Items:**

```

- **field**

``string`` — Tracking fields type.

```
- **`value`**
```

``string`` — Tracking fields value.

```
- **`type`**
```

``integer`` — Meeting type.

```
- **`user_email`**
```

``string`` — User email.

```
- **`user name`**
```

``string`` — User display name.

```
- **`uuid`**
```

``string`` — Meeting UUID. Each meeting instance will generate its own UUID(i.e., after a meeting ends, a new UUID will be generated for the next instance of the meeting). `\[Double encode]\`
(<https://marketplace.zoom.us/docs/api-reference/using-zoom-apis/#meeting-id-and-uuid>) your UUID when using it for API calls if the UUID begins with a '/' or contains '/' in it.

****Example:****

```

{
  "custom_keys": [
    {
      "key": "Host Nation",
      "value": "US"
    }
  ],
  "dept": "HR",
  "duration": 2,
  "end_time": "2022-03-15T07:42:22Z",
  "id": 3927350525,
  "participants_count": 2,
  "start_time": "2022-03-15T07:40:46Z",
  "topic": "My Meeting",
  "total_minutes": 3,
  "tracking_fields": [
    {
      "field": "Host Nation",
      "value": "US"
    }
  ],
  "type": 2,
  "user_email": "jchill@example.com",
  "user_name": "Jill Chill",
  "uuid": "i0TQZPmhTUq5a232ETb9eg=="
}

```

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`12702\` \
 Can not access meeting a year ago.\
 \
 Error Code: \`200\` \
 No permission.\
 \

Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \
 Meeting {meetingId} not found or has expired.\
 \
 Error Code: \`1001\` \
 User does not exist. \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

Get meeting participant reports

- **Method:** `GET`
 - **Path:** `/report/meetings/{meetingId}/participants`
 - **Tags:** Reports

Return a report of a past meeting with two or more participants, including the host. To return a report for past meeting with only **one** participant, use the **List meeting participants** `/docs/api/accounts/#tag/dashboards/GET/metrics/meetings/%7BmeetingId%7D/participants` API.

Note:

This API may return empty values for participants' `user_name`, `ip_address`, `location`, and `email` responses when the account calling this API:

- Is a **legacy** HIPAA BAA account `/docs/api/references/legacy-business-associate-agreements/`.

Prerequisites:

- A Pro or a higher plan.

[Scopes] `(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `report:read:admin`

[Granular Scopes] `(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)`: `report:read:list_meeting_participants:admin`

[Rate Limit Label] `(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits)`: `HEAVY`

Responses

Status: 200 **HTTP Status Code:** \`200\` Meeting participants report returned. Only available for Paid or ZMP account: {accountId}.

Content-Type: application/json

All of:

- `next_page_token`

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- `page_count`

`integer` — The number of pages returned for the request made.

- `page_size`

`integer`, default: `30` — The number of records returned within a single API call.

- `total_records`

`integer` — The number of all records available across pages.

participants

`array` — Array of meeting participant objects.

Items:

- `bo_mtg_id`

`string` — The `[breakout room]` `(https://support.zoom.us/hc/en-us/articles/206476313-Managing-breakout-rooms)` ID. Each breakout room is assigned a unique ID.

- `customer_key`

`string` — The participant's SDK identifier. This value can be alphanumeric, up to a maximum length of 35 characters.

- **duration**

`integer` — Participant duration, in seconds, calculated by subtracting the `leave_time` from the `join_time` for the `user_id`. If the participant leaves and rejoins the same meeting, they are assigned a different `user_id` and Zoom displays their new duration in a separate object. Because of this, the duration may not reflect the total time the user was in the meeting.

- **failover**

`boolean` — Indicates if failover happened during the meeting.

- **id**

`string` — The participant's universally unique ID (UUID). `*` If the participant joins the meeting by logging into Zoom, this value is the `id` value in the `[\/*Get a user*\*](/docs/api-reference/zoom-api/methods#operation/user)` API response. `*` If the participant joins the meeting `*\*without*\*` logging into Zoom, this returns an empty string value. `*\*Note:*\*` Use the `participant_user_id` value instead of this value. We will remove this response in a future release.

- **join_time**

`string`, format: `date-time` — Participant join time.

- **leave_time**

`string`, format: `date-time` — Participant leave time.

- **name**

`string` — Participant display name. This returns an empty string value if the account calling the API is a BAA account.

- **participant_user_id**

`string` — The participant's universally unique ID (UUID). `*` If the participant joins the meeting by logging into Zoom, this value is the `id` value in the `[\/*Get a user*\*](/docs/api-reference/zoom-api/methods#operation/user)` API response. `*` If the participant joins the meeting `*\*without*\*` logging into Zoom, this returns an empty string value.

- **registrant_id**

`string` — Unique identifier of the registrant. This field is only returned if you entered `"registrant_id"` as the value of `include_fields` query parameter.

- **status**

`string`, possible values: `"in_meeting"`, `"in_waiting_room"` — The participant's status. `*\*in_meeting\*` - In a meeting. `*\*in_waiting_room\*` - In a waiting room.

- **user_email**

`string` — Participant email. If the participant is `*\*not*\*` part of the host's account, this returns an empty string value, with some exceptions. See `[Email address display rules](/docs/api-reference/using-zoom-apis#email-address)` for details. This returns an empty string value if the account calling the API is a BAA account.

- **user_id**

`string` — Participant ID. This is a unique ID assigned to the participant joining a meeting and is valid for that meeting only.

Example:

```
```json
{
 "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
 "page_count": 1,
 "page_size": 30,
 "total_records": 1,
 "participants": [
 {
 "customer_key": "349589LkJyeW",
 "duration": 259,
 "failover": false,
 "id": "30R7kT7bTIKSNUFEuH_Q1g",
 "join_time": "2022-03-23T06:58:09Z",
 "leave_time": "2022-03-23T07:02:28Z",
 "name": "example",
 "registrant_id": "abcdefghijklmnopq23456",

```



```

 "status": "in_meeting",
 "user_email": "jchill@example.com",
 "user_id": "27423744",
 "bo_mtg_id": "27423744",
 "participant_user_id": "DYHrdpjrS3uaOf7dPkkg8w"
 }
]
}

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 1010` `User does not belong to this account:{accountId}`.  
`Error Code: 12702` `Can not access meeting a year ago`.  
`Error Code: 200` `No permission`.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Meeting {MeetingId} not found or has expired`.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests`. For more information, see `[rate limits](/docs/api/rate-limits/)`.

### Get meeting poll reports

```

- Method: GET
- Path: /report/meetings/{meetingId}/polls
- Tags: Reports

```

Use this API to get a report of `[poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meetings)` results for a past meeting.

#### Prerequisites:

- A Pro or a higher plan.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `report:read:admin`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `report:read:list_meeting_polls:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `Heavy`

### Responses

##### Status: 200 `HTTP Status Code: 200` `Meeting polls report returned`. `This is only available for paid account: {accountId}`

##### Content-Type: `application/json`

```

- id

```

`integer`, format: `int64` — The `[meeting ID](https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID)`.

```

- questions

```

`array` — Information about the meeting questions.

**Items:**

```

- email

```

`string`, format: `email` — The participant's email address.

```

- first_name

```

`string` — The participant's first name. If the `Allow participants to answer questions anonymously` setting is enabled for a `[poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meet)`, the participant's polling information is kept anonymous and the `first_name` field will return the `"Anonymous Attendee"` value.

```

- last_name

```

`string` — The participant's last name. If the `Allow participants to answer questions anonymously` setting is enabled for a `[poll](https://support.zoom.us/hc/en-us/articles/213756303-Polling-for-Meet)`, the participant's polling information is kept anonymous and the `last_name` field will return the `"Anonymous Attendee"` value.

```

- name

```

`string` — The participant's display name. If the `Allow participants to answer questions anonymously` setting is enabled for a `[poll](https://support.zoom.us/hc/en-us/articles/213756303-`

Polling-for-Meet), the participant's polling information is kept anonymous and the `\`name\`` field will return the `\`Anonymous Attendee\`` value.

- **`\`question_details\``**
  - `\`array\`` — Information about the user's questions and answers.
- `**Items:**`**
- **`\`answer\``**
  - `\`string\`` — The user's given answer.
- **`\`date_time\``**
  - `\`string\`` — The date and time at which the user answered the poll question.
- **`\`polling_id\``**
  - `\`string\`` — The poll's ID.
- **`\`question\``**
  - `\`string\`` — The poll question.
- **`\`start_time\``**
  - `\`string\``, format: `\`date-time\`` — The meeting's start time.
- **`\`uuid\``**
  - `\`string\`` — The meeting's universally unique identifier (UUID). Each meeting instance generates a meeting UUID.

**`**Example:**`**

```
```json
{
  "id": 123456,
  "uuid": "4444AAAIAAAAAiAiAiAi==",
  "start_time": "2022-02-01T12:34:12.66Z",
  "questions": [
    {
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "first_name": "Jill",
      "last_name": "Chill",
      "question_details": [
        {
          "answer": "I am wonderful.",
          "date_time": "2022-02-01T12:37:12.660Z",
          "polling_id": "798fGJEWRA",
          "question": "How are you?"
        }
      ]
    }
  ]
}
```

Status: 400 `\`*\`HTTP Status Code:\`*\` \`400\`` `\`<br> Bad Request \`*\`Error Code:\`*\` \`12702\`` `\`
 Can not access meeting a year ago. \`*\`Error Code:\`*\` \`200\`` `\`
 No permission.\`<br>`

Status: 404 `\`*\`HTTP Status Code:\`*\` \`404\`` `\`<br> Not Found \`*\`Error Code:\`*\` \`3001\`` `\`
 Meeting "{meetingId}" not found or has expired.`

Status: 429 `\`*\`HTTP Status Code:\`*\` \`429\`` `\`
 Too Many Requests. For more information, see \`[rate limits]\`(https://developers.zoom.us/docs/api/rest/rate-limits/).`

`### Get meeting Q&A report`

- **`**Method:**`** `\`GET\``
- **`**Path:**`** `\`/report/meetings/{meetingId}/qa\``
- **`**Tags:**`** Reports

Retrieve a report on questions asked and answered by participants from past meetings.

`**Prerequisites:**`

- Pro plan or higher.

```

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `report:read:admin`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**
`report:read:meeting_qna:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `HEAVY`

#### Responses

##### Status: 200 \*\*HTTP Status Code:\*\* `200` Meeting Q&A report returned. Only available for
Paid or ZMP account: {accountId}.

##### Content-Type: application/json

- **`id`**

  `integer`, format: `int64` — The meeting ID in `long` format, represented as int64 data type in JSON.
  Also known as the meeting number.

- **`questions`**

  `array` — Array of meeting question objects.

  **Items:**

  - **`email`**

    `string` — Participant's email. If the participant is \*\*not\*\* part of the host's account, this
    returns an empty string value, with some exceptions. See [Email address display rules](
    https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

  - **`name`**

    `string` — Participant's display name. If the anonymous [Q&A](https://support.zoom.us/hc/en-
    us/articles/203686015-Getting-Started-with-Question-Answer) option is enabled and if a participant submits
    the Q&A without providing their name, the value of the `name` field is "Anonymous
    Attendee".

  - **`question_details`**

    `array` — Array of questions from user.

    **Items:**

    - **`answer`**

      `string` — The given answer. If this is a live answer, the value is 'live answered'. \*\*Note:\*\*
      All answers will be returned together and separated by semicolons. For more detailed answer information,
      please see the "answer_details" field.

    - **`answer_details`**

      `array` — Array of answers from the user.

      **Items:**

      - **`content`**

        `string` — The answer from host or the comment from participant.

      - **`create_time`**

        `string` — Content submit time.

      - **`email`**

        `string` — Participant's email. If the participant is \*\*not\*\* part of the host's account, this
        returns an empty string value, with some exceptions. See [Email address display rules](
        https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

      - **`name`**

        `string` — User display name, including the host or participant.

      - **`type`**

        `string`, possible values: `default`, `host_answered_publicly`, `host_answered_privately`,
        `participant_commented`, `host_answered`, default: `default` — Type of answer.

```

```

- **`user_id`**

  `string` — The user ID of the user who answered the question. This value returns blank for external users.

- **`create_time`**

  `string` — Question create time.

- **`question`**

  `string` — Asked question.

- **`question_id`**

  `string` — Question UUID.

- **`question_status`**

  `string`, possible values: `"default", "open", "dismissed", "answered", "deleted"` — Question status.
  If not supported, the value will be `default`.

- **`user_id`**

  `string` — The user ID of the user who asked the question. This value returns blank for external users.

- **`start_time`**

  `string`, format: `date-time` — Meeting start time.

- **`uuid`**

  `string` — The meeting UUID. Each meeting instance will generate its own UUID - for example, after a
  meeting ends, a new UUID will be generated for the next instance of the meeting. Double-encode your UUID
  when using it for API calls if the UUID begins with a '/' or contains '//'.

```

****Example:****

```

```json
{
 "id": 245603123123,
 "questions": [
 {
 "user_id": "hyR0rs0TRCSvwmadI7L13w",
 "email": "jchilll@example.com",
 "name": "Jill Chill",
 "question_details": [
 {
 "question": "how are you",
 "question_id": "zxU4wOwnlxs",
 "create_time": "2022-03-15T07:48:00Z",
 "question_status": "open",
 "answer_details": [
 {
 "user_id": "Cn_5wJ9mRNGyY0mpjVufBQ",
 "name": "Paul",
 "email": "paul@example.com",
 "content": "fine",
 "create_time": "2022-03-15T07:50:00Z",
 "type": "default"
 }
]
 }
]
 }
]
},
{
 "start_time": "2022-03-15T07:40:46Z",
 "uuid": "4444AAAiAAAAAiAiAiAi=="
}
]
```

```

Status: 400 ****HTTP Status Code:**** 400 ****Error Code:**** 200 ****Message:**** Bad Request No permission.

Status: 404 ****HTTP Status Code:**** 404 ****Error Code:**** 1001 ****Message:**** Not Found User does not exist: {userId}. ****Error Code:**** 3001 ****Message:**** Meeting {meetingId} not found or has expired.

Status: 429 ****HTTP Status Code:**** 429 ****Message:**** Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get meeting survey report

- **Method:** `GET`
 - **Path:** `/report/meetings/{meetingId}/survey`
 - **Tags:** Reports

Retrieve a report on past [meeting survey](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559).

Prerequisites:

- Pro or a higher plan.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:meeting_survey:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `HEAVY`

Responses

Status: 200 `\**HTTP Status Code:\** \200\` Meeting survey report returned. Only available for Paid or ZMP account: {accountId}.

Content-Type: application/json

- **meeting_id**
`integer`, format: `int64` — The meeting ID.

- **meeting_uuid**
`string` — The meeting's universally unique identifier (UUID). Each meeting instance generates a meeting UUID.

- **start_time**
`string`, format: `date-time` — The meeting's start time.

- **survey_answers**
`array` — Information about the survey questions and answers.

Items:

- **answer_details**
`array` — Information about the user's questions and answers.

Items:

- **answer**
`string` — The user's given answer.

- **date_time**
`string` — The date and time at which the user answered the survey question.

- **question**
`string` — The survey question.

- **question_id**
`string` — The question's ID

- **email**
`string`, format: `email` — The participant's email address.

- **first_name**
`string` — The participant's first name. If the `\**Allow participants to answer questions anonymously\**` setting is enabled for a [survey](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the `\first_name\` field will return the `"Anonymous Attendee"` value.

- **last_name**

string — The participant's last name. If the **Allow participants to answer questions anonymously** setting is enabled for a **[survey]**(https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the **last_name** field will return the **"Anonymous Attendee"** value.

- **name**

string — The participant's display name. **Allow participants to answer questions anonymously** setting is enabled for a **[survey]**(https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the **name** field will return the **"Anonymous Attendee"** value.

- **survey_id**

string — The survey's ID

- **survey_name**

string — The name of survey

Example:

```
```json
{
 "meeting_id": 123456,
 "meeting_uuid": "4444AAAiAAAAAiAiAiAi==",
 "start_time": "2022-02-01T12:34:12.66Z",
 "survey_id": "8SFHRTGHAAAiAAAAAiAiAiAi==",
 "survey_name": "Survey of this meeting",
 "survey_answers": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "first_name": "Jill",
 "last_name": "Chill",
 "answer_details": [
 {
 "question": "How are you?",
 "question_id": "798fGJEWRA",
 "answer": "I am wonderful.",
 "date_time": "2022-02-01T12:37:12.660Z"
 }
]
 }
]
}
```
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 1010 **User does not belong to this account:**{accountId}. **Error Code:** 12702 **Can not access a webinar a year ago.** **Error Code:** 200 **No permission.**

Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Webinar {webinarId} not found or has expired.**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see **[rate limits]**(<https://developers.zoom.us/docs/api/rest/rate-limits/>).

Get operation logs report

- **Method:** GET
- **Path:** /report/operationlogs
- **Tags:** Reports

The **[Operations Logs]**(<https://support.zoom.us/hc/en-us/articles/360032748331-Operation-Logs>) report allows you to audit admin and user activity, such as adding a new user, changing account settings, and deleting recordings.

Use this API to retrieve operation logs report for a specified period of time.

Prerequisites:

- Pro or higher plan.

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): **report:read:admin**

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): **report:read:operation_logs:admin**

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **HEAVY**

Responses

Status: 200 **HTTP Status Code:** **200** **Operation Logs Report Returned**

Content-Type: application/json

All of:

- **next_page_token**

string — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of the available result list exceeds the page size. The expiration period is 15 minutes.

- **page_size**

integer, default: **30** — The amount of records returns within a single API call.

operation_logs

array — Array of operation log objects

Items:

- **action**

string — Action

- **category_type**

string — Category type

- **operation_detail**

string — Operation detail

- **operator**

string — The user who performed the operation.

- **time**

string, format: **date-time** — The time at which the operation was performed.

Example:

```
``json
{
  "next_page_token": "uBTK3NzNksdkuCUAQaFVFd86ky0r59zg4U2",
  "page_size": 30,
  "operation_logs": [
    {
      "action": "delete",
      "category_type": "user",
      "operation_detail": "delete user - user2@example.com",
      "operator": "admin@example.com",
      "time": "2022-01-25T17:52:16Z"
    }
  ]
}
```

Status: 400 **HTTP Status Code:** **400** **Bad Request** **Error Code:** **200** **No permission.**

Status: 429 **HTTP Status Code:** **429** **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

Get remote support report

- **Method:** **GET**

- **Path:** **/report/remote_support**

- **Tags:** **Reports**

Retrieve a list of remote support records.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **report:read:admin**

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:remote_support:admin``

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `HEAVY``

Responses

Status: 200 Remote support records list.

Content-Type: application/json

- `next_page_token``

`string`` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- `page_size``

`integer`` — The number of records returned with a single API call.

- `remote_support_logs``

`array`` — Array of remote support logs.

Items:

- `duration``

`string`` — The duration of remote support, formatted in `hh:mm:ss``.

- `end_time``

`string`` — Remote support end time

- `meeting_host_id``

`string`` — The meeting's host id.

- `meeting_number``

`integer`` — The meeting number.

- `meeting_start_time``

`string`` — The meeting's start time.

- `meeting_uuid``

`string`` — The meeting's unique universal identifier (UUID). Double encode your UUID when using it for API calls if the UUID begins with a `/` or contains `//` in it.

- `request_time``

`string`` — The time to request remote support.

- `start_time``

`string`` — Remote support start time.

- `supportee_email``

`string`` — The supportee's user email.

- `supportee_name``

`string`` — The supportee's user name.

- `supporter_email``

`string`` — The supporter's user email.

- `supporter_name``

`string`` — The supporter's user name.

- `topic``

`string`` — The meeting's topic.

- ****`wait\_time`****

`string` — The waiting time for remote support from request to start, formatted in **`hh:mm:ss`**.

****Example:****

```
```json
{
 "remote_support_logs": [
 {
 "meeting_start_time": "2025-09-15T13:20:12Z",
 "meeting_uuid": "gm8s9L+PTEC+FG3sFbd1Cw==",
 "meeting_number": 93201235621,
 "topic": "My Meeting",
 "meeting_host_id": "FyOCGDLEShWSihPcupWHtA",
 "supporter_name": "Jill Chill",
 "supporter_email": "jchill@example.com",
 "supportee_name": "Tom",
 "supportee_email": "tom@example.com",
 "request_time": "2025-09-15T13:21:29Z",
 "wait_time": "01:28",
 "start_time": "2025-09-15T13:22:57Z",
 "end_time": "2025-09-15T13:42:34Z",
 "duration": "19:37"
 }
],
 "next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
 "page_size": 30
},
```
```

Status: 400 **`HTTP Status Code`**: **`400`** **`<br> Bad Request`** **`Error Code`**: **`300`** **`<br> The next page token is invalid or expired.`**

Status: 401 **`HTTP Status Code`**: **`401`** **`<br> Unauthorized`**

Status: 429 **`HTTP Status Code`**: **`429`** **`<br> Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rate-limits/).`**

Get telephone reports

- ****Method:**** **`GET`**
 - ****Path:**** **`/report/telephone`**
 - ****Tags:**** Reports

The [telephone report](https://support.zoom.us/hc/en-us/articles/206514816-Telephone-reports) allows you to view who dialed into meetings via phone (Audio Conferencing or SIP Connected Audio) and which number they dialed into and other details. Use this API to get telephone report for a specified period of time.

****Prerequisites:****

- Pro or higher plan.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** **`report:read:admin`**

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** **`report:read:telephone:admin`**

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** **`HEAVY`**

Responses

Status: 200 **`HTTP Status Code`**: **`200`** Telephone report returned. This is only available for paid account: {accountId}. The requested report cannot be generated for this account because this account has not subscribed to toll-free audio conference plan. Enable the **`Toll Report`** feature to perform this action. Contact the Zoom Support team for help.

Content-Type: application/json

****All of:****

- ****`from`****

`string`, format: **`date`** — Start date for this report.

- ****`next\_page\_token`****

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this

token is 15 minutes.

- **page_count**

`integer` — The number of pages returned for the request made. This field does `not` return if the `query_date_type` parameter is the `meeting_start_time` or `meeting_end_time` value.

- **page_size**

`integer` — The number of records returned with a single API call.

- **to**

`string`, format: `date` — End date for this report.

- **total_records**

`integer` — The total number of all the records available across pages. This field does `not` return if the `query_date_type` parameter is the `meeting_start_time` or `meeting_end_time` value.

* **telephony_usage**

`array` — Array of telephony objects.

Items:

- **call_in_number**

`string` — Caller's call-in number.

- **country_name**

`string` — Country name.

- **dept**

`string` — User department.

- **duration**

`integer` — Call leg duration

- **end_time**

`string`, format: `date-time` — Call leg end time

- **host_email**

`string` — User email.

- **host_id**

`string` — The user ID of the meeting host.

- **host_name**

`string` — User display name.

- **meeting_id**

`integer`, format: `int64` — `[Meeting ID]`(<https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID->): Unique identifier of the meeting in `"*long*"` format (represented as `int64` data type in JSON), also known as the meeting number.

- **meeting_type**

`string` — Meeting type.

- **phone_number**

`string` — Toll-free telephone number.

- **rate**

`number` — Calling rate for the telephone call.

- **signaled_number**

`string` — The number that is signaled to Zoom.

- **start_time**
`string`, format: `date-time` — Call leg start time
- **total**
`number` — Total cost (USD) for Call Out. Calculated as plan rate by duration.
- **type**
`string`, possible values: `toll-free`, `call-out`, `call-in`, `US toll-number`, `global toll-number`, `premium`, `premium call-in`, `Toll` — Call type.
- **uuid**
`string` — Meeting UUID.

Example:

```

{
  "from": "2019-06-20",
  "next_page_token": "w7587w4eiyfsudgk",
  "page_count": 1,
  "page_size": 30,
  "to": "2019-07-20",
  "total_records": 1,
  "telephony_usage": [
    {
      "call_in_number": "ZoomGW",
      "country_name": "US",
      "dept": "HR",
      "duration": 2,
      "end_time": "2022-03-15T07:42:22Z",
      "host_email": "jchill@example.com",
      "host_id": "Rn_hal7ToG5p0AWwIIsjQ",
      "host_name": "Jill Chill",
      "meeting_id": 94908911701,
      "meeting_type": "Meeting",
      "phone_number": "+1 8243",
      "rate": 0.03,
      "signaled_number": "+1 8243",
      "start_time": "2022-03-15T07:40:46Z",
      "total": 0.03,
      "type": "call-out",
      "uuid": "4444AAAiAAAAAiAiAiAi=="
    }
  ]
}

```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **The next page token is invalid or expired.**

Status: 401 **HTTP Status Code:** 401 **Unauthorized**

Status: 403 **HTTP Status Code:** 403 **Forbidden**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

Get upcoming events report

- **Method:** GET
- **Path:** /report/upcoming_events
- **Tags:** Reports

Use this API to list upcoming meeting and/or webinar events within a specified period of time. The report's time range is limited to one month.

Prerequisites:

- A Pro or higher plan

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): **report:read:admin**

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): **report:read:upcoming_meetings_webinars:admin**

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **Heavy**

Responses

Status: 200 **HTTP Status Code:** 200 Upcoming events report returned.

Content-Type: application/json

All of:

- **from**

string, format: **date** — The report's start date. This value must be within the past six months.

- **next_page_token**

string — The next page token is used to paginate through large result sets. A next page token returns when the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- **page_size**

integer, default: 30 — The number of records returned in a single API call.

- **to**

string, format: **date** — The report's end date. This value must be within the past six months and cannot exceed a month from the **from** value.

- **upcoming_events**

array — Information about the upcoming event.

Items:

- **dept**

string — The event host's department.

- **host_id**

string — The event host's ID.

- **host_name**

string — The event host's name.

- **id**

string — The event's unique ID.

- **start_time**

string — The event's start time.

- **topic**

string — The event's topic.

Example:

```
``json
{
  "from": "2022-03-01",
  "next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
  "page_size": 30,
  "to": "2022-03-25",
  "upcoming_events": [
    {
      "dept": "HR",
      "host_id": "0r4-ZeV_SHC0fWRC7101Fg",
      "host_name": "chi chi",
      "id": "vawMH9zAQLyTjCnQiQXSUG==",
      "start_time": "2022-03-15T07:40:46Z",
      "topic": "My Meeting"
    }
  ]
}
```

Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 200` This is only available for the paid account: {accountId} `Error Code: 300` The next page token is invalid or expired. `Error Code: 200` No permission.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get active or inactive host reports

- `Method: GET`
- `Path: /report/users`
- `Tags: Reports`

Retrieve a host report for a specified period of time within the last six months. The report time range is limited to a month.

You can specify the type of report and date range using the query parameters.

- The `Active Hosts` report displays a list of meetings, participants, and meeting minutes. An `active host` is defined as any user who has hosted at least one meeting during the month specified in the `from` and `to` range.
- The `Inactive Hosts` report pulls a list of users who were not active during a specific period of time. An `inactive host` is defined as any user who has not hosted any meetings during the specified period of time for the report. to be inactive.

`Prerequisites:`

- Pro or higher plan.

`[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:admin`

`[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:list_users:admin`

`[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): HEAVY`

Responses

Status: 200 `HTTP Status Code: 200` Active or inactive hosts report returned. Only available for Paid or ZMP account: {accountId}.

Content-Type: application/json

`All of:`

- `from`

`string`, format: `date` — Start date for this report.

- `next_page_token`

`string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

- `page_count`

`integer` — The number of pages returned for the request made.

- `page_number`

`integer`, default: `1` — The page number of the current results.

- `page_size`

`integer`, default: `30` — The number of records returned with a single API call.

- `to`

`string`, format: `date` — End date for this report.

- `total_records`

`integer` — The total number of all the records available across pages.

- `total_meeting_minutes`

`integer` — Number of meeting minutes for this range.

```

* **`total_meetings`**

`integer` — Number of meetings for this range.

* **`total_participants`**

`integer` — Number of participants for this range.

* **`users`**

`array` — Array of user objects.

**Items:**

- **`custom_attributes`**

  `array` — Custom attributes that have been assigned to the user.

  **Items:**

  - **`key`**

    `string` — Identifier for the custom attribute.

  - **`name`**

    `string` — Name of the custom attribute.

  - **`value`**

    `string` — Value of the custom attribute.

- **`dept`**

  `string` — User department.

- **`email`**

  `string` — User email.

- **`id`**

  `string` — User ID.

- **`meeting_minutes`**

  `integer` — Number of meeting minutes for user.

- **`meetings`**

  `integer` — Number of meetings for user.

- **`participants`**

  `integer` — Number of participants in meetings for user.

- **`type`**

  `integer` — User type.

- **`user_name`**

  `string` — User display name.

```

Example:

```

```json
{
 "from": "2022-03-01",
 "next_page_token": "b43YBRLJFg3V4vsSpxvGdKIGtNbxn9h9If2",
 "page_count": 30,
 "page_number": 1,
 "page_size": 30,
 "to": "2022-03-25",
 "total_records": 850,
 "total_meeting_minutes": 345,
 "total_meetings": 34,
 "total_participants": 56,
 "users": [
 {

```

``integer`` — The total number of all the records available across pages.

\* \*\*`from`\*\*

`string`, format: `date` — The report's start date.

\* \*\*`meetings`\*\*

`array` — Information about the meeting.

\*\*Items:\*\*

- \*\*`custom\_keys`\*\*

`array` — Information about the meeting's assigned custom keys and values. This returns a maximum of 10 items.

\*\*Items:\*\*

- \*\*`key`\*\*

`string` — The custom key name.

- \*\*`value`\*\*

`string` — The custom key's value.

- \*\*`duration`\*\*

`integer` — The meeting's duration.

- \*\*`end\_time`\*\*

`string`, format: `date-time` — The meeting's end date and time.

- \*\*`has\_chat`\*\*

`boolean` — Whether or not the chat feature was used by this user in the meeting. This is meeting feature for attendee level.

- \*\*`has\_recording`\*\*

`boolean` — Whether or not the recording feature was enabled by this user in the meeting. This is meeting feature for attendee level.

- \*\*`has\_screen\_share`\*\*

`boolean` — Whether or not the screenshare feature was used by this user in the meeting. This is meeting feature for attendee level.

- \*\*`host\_name`\*\*

`string` — Host's name.

- \*\*`host\_organization`\*\*

`string` — Host Account Name of Hosting Organization.

- \*\*`id`\*\*

`integer` — The \[meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID).

- \*\*`join\_time`\*\*

`string` — The date and time at which the attendee joined the meeting.

- \*\*`join\_waiting\_room\_time`\*\*

`string` — The date and time at which the attendee joined the waiting room.

- \*\*`leave\_time`\*\*

`string` — The date and time at which the attendee left the meeting.

- \*\*`meeting\_encryption\_status`\*\*

`integer`, possible values: `1, 2` — The meeting's encryption status. \\* `1` - E2E encryption. \\* `2` - Enhanced encryption.

- \*\*`participants\_count`\*\*



```

`integer` — The number of meeting participants.

- **`participants_count_my_account`**

 `integer` — The number of meeting participants from my account.

- **`schedule_time`**

 `string` — The meeting's scheduled date and time.

- **`session_key`**

 `string` — The Video SDK custom session ID.

- **`source`**

 `string` — Whether the meeting was created directly through Zoom or via an API request: * If the meeting was created via an OAuth app, this field returns the OAuth app's name. * If the meeting was created via JWT or the Zoom Web Portal, this returns the `Zoom` value.

- **`start_time`**

 `string`, format: `date-time` — The meeting's start date and time.

- **`topic`**

 `string` — The meeting's topic.

- **`total_minutes`**

 `integer` — The sum of meeting minutes from all meeting participants in the meeting.

- **`type`**

 `integer`, possible values: `1, 2, 3, 4, 5, 6, 7, 8, 9` — The type of meeting or webinar. meeting: * \1\ - Instant meeting. * \2\ - Scheduled meeting. * \3\ - A recurring meeting with no fixed time. * \4\ - A meeting created via PMI (Personal Meeting ID). * \7\ - A \[Personal Audio Conference\] \(\https://support.zoom.us/hc/en-us/articles/204517069-Getting-Started-with-Personal-Audio-Conference\) (PAC). * \8\ - Recurring meeting with a fixed time. webinar: * \5\ - A webinar. * \6\ - A recurring webinar without a fixed time * \9\ - A recurring webinar with a fixed time.

- **`user_email`**

 `string`, format: `email` — The user's email address.

- **`user_name`**

 `string` — The user's display name.

- **`uuid`**

 `string` — The meeting's universally unique identifier (UUID). Each meeting instance generates a meeting UUID.

* **`next_page_token`**

 `string` — The next page token is used to paginate through large result sets. A next page token will be returned whenever the set of available results exceeds the current page size. The expiration period for this token is 15 minutes.

* **`to`**

 `string`, format: `date` — The report's end date.

```

**Example:**

```

```json
{
  "next_page_token": "w7587w4eiyfsudgk",
  "page_count": 1,
  "page_size": 30,
  "total_records": 20,
  "from": "2020-07-14",
  "meetings": [
    {
      "custom_keys": [
        {
          "key": "Host Nation",
          "value": "US"
        }
      ]
    }
  ]
}
```

```

```

],
 "duration": 6,
 "end_time": "2020-07-15T23:30:19Z",
 "id": 12345,
 "participants_count": 2,
 "session_key": "ABC36ja8I145",
 "source": "Zoom",
 "start_time": "2019-07-15T23:24:52Z",
 "topic": "My Meeting",
 "total_minutes": 11,
 "type": 2,
 "user_email": "jchill@example.com",
 "user_name": "Jill Chill",
 "uuid": "4444AAAIAAAAAiAiAiAi==",
 "schedule_time": "12/22/2021 16:20",
 "join_waiting_room_time": "02/11/2022 16:15",
 "join_time": "12/22/2021 16:20",
 "leave_time": "12/22/2021 17:13",
 "host_organization": "org",
 "host_name": "Jill",
 "has_screen_share": false,
 "has_recording": false,
 "has_chat": false,
 "meeting_encryption_status": 1,
 "participants_count_my_account": 2
 }
],
"to": "2020-08-14"
}

```

##### Status: 400 \\\*\\\*HTTP Status Code:\\\*\\\* \\`400\\` \\<br> Bad Request \\\*\\\*Error Code:\\\*\\\* \\`200\\` \\<br> This is only available for paid account: {accountId}.\\<br> \\<br> \\\*\\\*Error Code:\\\*\\\* \\`300\\` \\<br> The next page token is invalid or expired. \\<br> \\\*\\\*Error Code:\\\*\\\* \\`200\\` \\<br> No permission. \\<br>

##### Status: 404 \\\*\\\*HTTP Status Code:\\\*\\\* \\`404\\` \\<br> Not Found \\\*\\\*Error Code:\\\*\\\* \\`1001\\` \\<br> User {userId} not exist or not belong to this account. \\<br>

##### Status: 429 \\\*\\\*HTTP Status Code:\\\*\\\* \\`429\\` \\<br> Too Many Requests For more information, see \\[rate limits]\\(\\/docs\\/api\\/rate-limits\\/).

### ### Get webinar detail reports

```

- **Method:** `GET`
- **Path:** `\\/report\\/webinars\\/\\{webinarId}\\`
- **Tags:** Reports

```

Retrieve a [report](https://support.zoom.us/hc/en-us/articles/201393719-Webinar-Reporting) containing past webinar details.

#### \*\*Prerequisites:\*\*

- Pro or higher plan with Webinar add-on.

\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\* `report:read:admin`

\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\* `report:read:webinar:admin`

\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* `Heavy`

### #### Responses

##### Status: 200 \\\*\\\*HTTP Status Code:\\\*\\\* \\`200\\` Webinar details returned. This is only available for paid account:{accountId}.

##### Content-Type: application/json

```

- **`custom_keys`**

```

`array` — Custom keys and values assigned to the meeting.

```

Items:

```

```

- **`key`**

```

`string` — Custom key associated with the user.

```

- **`value`**

```

```

`string` — Value of the custom key associated with the user.

- **`dept`**

 `string` — Department of the host.

- **`duration`**

 `integer` — Meeting duration.

- **`end_time`**

 `string`, format: `date-time` — Meeting end time.

- **`id`**

 `integer`, format: `int64` — \[Meeting ID](https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-): Unique identifier of the meeting in \"**long**" format (represented as int64 data type in JSON), also known as the meeting number.

- **`participants_count`**

 `integer` — Number of meeting participants.

- **`start_time`**

 `string`, format: `date-time` — Meeting start time.

- **`topic`**

 `string` — Meeting topic.

- **`total_minutes`**

 `integer` — Number of Webinar minutes. This represents the total amount of Webinar minutes attended by each participant including the host, for a Webinar hosted by the user. For instance if there were one host (named A) and one participant (named B) in a Webinar, the value of total_minutes would be calculated as below: **total_minutes** = Total Webinar Attendance Minutes of A + Total Webinar Attendance Minutes of B

- **`tracking_fields`**

 `array` — Tracking fields.

 Items:

 - **`field`**

 `string` — Tracking fields type.

 - **`value`**

 `string` — Tracking fields value.

- **`type`**

 `integer` — Meeting type.

- **`user_email`**

 `string` — User email.

- **`user_name`**

 `string` — User display name.

- **`uuid`**

 `string` — Webinar UUID. Each webinar instance will generate its own UUID (i.e., after a meeting ends, a new UUID will be generated when the next instance of the webinar starts). \[double encode] \[https://marketplace.zoom.us/docs/api-reference/using-zoom-apis/#meeting-id-and-uuid) the UUID when using it for API calls if the UUID begins with a '/' or contains '/' in it.

```

**Example:**

```

```json
{
  "custom_keys": [
    {
      "key": "Host Nation",

```

```

    "value": "US"
  }
],
"dept": "HR",
"duration": 2,
"end_time": "2022-03-15T07:42:22Z",
"id": 345678902224,
"participants_count": 4,
"start_time": "2022-03-15T07:40:46Z",
"topic": "My Meeting",
"total_minutes": 3,
"tracking_fields": [
  {
    "field": "Host Nation",
    "value": "US"
  }
],
"type": 4,
"user_email": "jchill@example.com",
"user_name": "Jill Chill",
"uuid": "4444AAAIAAAAAiAiAiAi=="
}

```

Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 1010`
 User does not belong to this account: {accountId}. `Error Code: 12702` Can not access a
 webinar a year ago. `Error Code: 200` No permission.

Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 3001`
 Meeting {meetingId} not found or has expired.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Get webinar participant reports

```

- **Method:** `GET`
- **Path:** `/report/webinars/{webinarId}/participants`
- **Tags:** Reports

```

Get a detailed report on each webinar attendee. You can get webinar participant reports for the last 6 months.

Prerequisites:

- A Pro or a higher plan with Webinar add-on enabled.

[Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:admin`

[Granular Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:list_webinar_participants:admin`

[Rate Limit Label] (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `HEAVY`

Responses

Status: 200 `HTTP Status Code: 200` Meeting participants report returned. Only available for Paid or ZMP account: {accountId}.

Content-Type: application/json

All of:

- `next_page_token`

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- `page_count`

`integer` — The number of pages returned for the request made.

- `page_size`

`integer`, default: `30` — The number of records returned within a single API call.

- `total_records`

`integer` — The number of all records available across pages.

*** **`participants`****

`array` — Information about the webinar participant.

****Items:****

- ****`bo\_mtg\_id`****

`string` — The `\[breakout room]\(https://support.zoom.us/hc/en-us/articles/206476313-Managing-breakout-rooms)` ID. Each breakout room is assigned a unique ID.

- ****`customer\_key`****

`string` — The participant's SDK identifier. This value can be alphanumeric, up to a maximum length of 35 characters.

- ****`duration`****

`integer` — Participant duration, in seconds, calculated by subtracting the `\`leave_time\`` from the `\`join\_time\`` for the `\`user_id\``. If the participant leaves and rejoins the same meeting, they will be assigned a different `\`user\_id\`` and Zoom displays their new duration in a separate object. Note that because of this, the duration may not reflect the total time the user was in the meeting.

- ****`failover`****

`boolean` — Whether failover occurred during the webinar.

- ****`id`****

`string` — The participant's universally unique ID (UUID). `\*` If the participant joins the meeting by logging into Zoom, this value is the `\`id\`` value in the `\[*\`Get a user\`*\](/docs/api-reference/zoom-api/methods#operation/user)` API response. `\*` If the participant joins the meeting `\*\`without\`*` logging into Zoom, this returns an empty string value. `\*\`Note:\`*` Use the `\`participant\_user\_id\`` value instead of this value. We will remove this response in a future release.

- ****`join\_time`****

`string`, format: ``date-time`` — The participant's join time.

- ****`leave\_time`****

`string`, format: ``date-time`` — The participant's leave time.

- ****`name`****

`string` — The participant's display name. This returns an empty string value if the account calling the API is a BAA account.

- ****`participant\_user\_id`****

`string` — The participant's universally unique ID (UUID). `\*` If the participant joins the meeting by logging into Zoom, this value is the `\`id\`` value in the `\[*\`Get a user\`*\](/docs/api-reference/zoom-api/methods#operation/user)` API response. `\*` If the participant joins the meeting `\*\`without\`*` logging into Zoom, this returns an empty string value.

- ****`registrant\_id`****

`string` — The registrant's ID. This field only returns if you provide the `\`registrant_id\`` value for the `\`include\_fields\`` query parameter.

- ****`status`****

`string`, possible values: ``"in_meeting", "in_waiting_room"`` — The participant's status. `\*\`in_meeting\`*` - In a meeting. `\*\`in_waiting_room\`*` - In a waiting room.

- ****`user\_email`****

`string` — The participant's email address. If the participant is `\*\`not\`*` part of the host's account, this returns an empty string value, with some exceptions. See `\[Email address display rules]\(/docs/api-reference/using-zoom-apis#email-address)` for details. This returns an empty string value if the account calling the API is a BAA account.

- ****`user\_id`****

`string` — The participant's ID. This ID is assigned to the participant upon joining the webinar and is only valid for that webinar.

****Example:****

```

```json
{
 "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
 "page_count": 1,
 "page_size": 30,
 "total_records": 1,
 "participants": [
 {
 "customer_key": "349589LkJyeW",
 "duration": 20,
 "failover": false,
 "id": "ABCDEF123456",
 "join_time": "2019-02-01T12:34:12.66Z",
 "leave_time": "2019-02-01T12:54:12.66Z",
 "name": "jchill",
 "registrant_id": "123456FEDCBA",
 "status": "in_meeting",
 "user_email": "jchill@example.com",
 "user_id": "ABCDEF123456",
 "participant_user_id": "DYHrdpjrS3uaOf7dPkkg8w",
 "bo_mtg_id": "Dkgwu8nm/ExG1vM+GhLRhA=="
 }
]
}
```

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 1010` `User does not belong to this account: {accountId}` `Error Code: 12702` `Can not access a webinar a year ago.` `Error Code: 200` `No permission.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar "{webinarId}" not found or has expired`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

Get webinar poll reports

```

- Method: GET
- Path: /report/webinars/{webinarId}/polls
- Tags: Reports

```

Retrieve a report on past [webinar polls](https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars).

Prerequisites:

- Pro or a higher plan with Webinar add-on enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:admin

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): report:read:list_webinar_polls:admin

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): Heavy

Responses

Status: 200 `HTTP Status Code: 200` Webinar polls report returned. Missing webinar subscription plan. Only available for Paid or ZMP account: {accountId}.

Content-Type: application/json

```

- id

```

integer, format: int64 — The webinar ID.

```

- questions

```

array — Information about the webinar questions.

Items:

```

- email

```

string, format: email — The participant's email address.

```

- first_name

```

string — The participant's first name. If the `Allow participants to answer questions`

```
- **`last_name`**
```

```
-  **`name`**
```

```
- **`question_details`**
```

```
**Items:**
```

```
- **`answer`**
```

```
- **`date_time`**
```

```
- **`polling_id`**
```

```
- **`question`**
```

```
- **`start_time`**
```

```
- **`uuid`**
```

****Example:****

```
##### Status: 404 \*\*HTTP Status Code:\*\* \`404\` \<br> Not Found \*\*Error Code:\*\* \`3001\` \<br>
```

Webinar {webinarId} not found or has expired.\

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

Get webinar Q&A report

- **Method:** `GET`
 - **Path:** `/report/webinars/{webinarId}/qa`
 - **Tags:** Reports

Retrieve a report on questions asked by participants and answered by panelists, co-hosts and hosts from past webinars.

Prerequisites:

- Pro or a higher plan with the Webinar add-on enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `report:read:webinar_qna:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `HEAVY`

Responses

Status: 200 **HTTP Status Code:** \`200\` Webinar Q&A report returned. Only available for Paid or ZMP account: {accountId}. A report can't be generated for this account because this account is not subscribed to a webinar plan.

Content-Type: application/json

- **id**

`integer`, format: `int64` — Webinar ID in `long` format, represented as int64 data type in JSON. Also known as the webinar number.

- **questions**

`array` — Array of webinar question objects.

Items:

- **email**

`string` — Participant's email. If the participant is `not` part of the host's account, this returns an empty string value, with some exceptions. See `[Email address display rules]` (https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

- **name**

`string` — Participant's display name. If anonymous `[Q&A]` (https://support.zoom.us/hc/en-us/articles/203686015-Getting-Started-with-Question-Answer) option is enabled and if a participant submits the Q&A without providing their name, the value of the `name` field will be `"Anonymous Attendee"`.

- **question_details**

`array` — Array of questions from the user.

Items:

- **answer**

`string` — The given answer. If this is a live answer, the value is `'live answered'`. `Note:` All answers will be returned together and separated by semicolons. For more detailed answer information, please see the `answer_details` field.

- **answer_details**

`array` — Array of answers from user.

Items:

- **content**

`string` — The answer from the host or the comment from a participant.

- **create_time**

``string`` — Content submission time.

- `**`email`**`

``string`` — Participant's email. If the participant is ``*\*not\*`` part of the host's account, this returns an empty string value, with some exceptions. See ``[Email address display rules]`` (<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules>) for details.

- `**`name`**`

``string`` — User display name, including the host or participant.

- `**`type`**`

``string``, possible values: ``"default", "host_answered_publicly", "host_answered_privately", "participant_commented", "host_answered"``, default: ``"default"`` — Type of answer.

- `**`user_id`**`

``string`` — The user ID of the user who answered the question. This value returns blank for external users.

- `**`create_time`**`

``string`` — Question creation time.

- `**`question`**`

``string`` — Asked question.

- `**`question_id`**`

``string`` — Question UUID.

- `**`question_status`**`

``string``, possible values: ``"default", "open", "dismissed", "answered", "deleted"`` — Question status. If not supported, the value will be ``default``.

- `**`user_id`**`

``string`` — The user ID of the user who asked the question. This value returns blank for external users.

- `**`start_time`**`

``string``, format: ``date-time`` — Webinar start time.

- `**`uuid`**`

``string`` — Webinar UUID. Each webinar instance will generate its own UUID - after a webinar ends, a new UUID will be generated for the next instance of the webinar. Double-encode your UUID when using it for API calls if the UUID begins with a ``/`` or contains ``//`` in it.

Example:

```
```json
{
 "id": 245603123123,
 "questions": [
 {
 "user_id": "hyR0rs0TRCSvwmadI7L13w",
 "email": "jchilll@example.com",
 "name": "Jill Chill",
 "question_details": [
 {
 "question": "how are you",
 "question_id": "zxU4w0wnlxs",
 "create_time": "2022-03-15T07:48:00Z",
 "question_status": "open",
 "answer_details": [
 {
 "user_id": "Cn_5wJ9mRNGyY0mpjVuFBQ",
 "name": "Paul",
 "email": "paul@example.com",
 "content": "fine",
 "create_time": "2022-03-15T07:50:00Z",
 "type": "default"
 }
]
 }
]
 }
]
}
```

```

 }
]
},
"start_time": "2022-03-15T07:40:46Z",
"uuid": "4444AAAIAAAAAiAiAiAi=="
}

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `User does not exist: {userId}.` `Error Code: 3001` `Webinar {webinarId} not found or has expired.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### ### Get webinar survey report

```

- Method: GET
- Path: /report/webinars/{webinarId}/survey
- Tags: Reports

```

Retrieve a report on past `[webinar survey]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0057559](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559)).

#### \*\*Prerequisites:\*\*

- Pro or a higher plan with Webinar add-on enabled.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:admin`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `report:read:webinar_survey:admin`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `HEAVY`

### #### Responses

##### Status: 200 `HTTP Status Code: 200` `Webinar survey report returned.` Missing webinar subscription plan. Only available for Paid or ZMP account: `{accountId}`.

##### Content-Type: `application/json`

```

- start_time
 string, format: date-time — The webinar's start time.
- survey_answers
 array — Information about the survey questions and answers.
 Items:
 - answer_details
 array — Information about the user's questions and answers.
 Items:
 - answer
 string — The user's given answer.
 - date_time
 string — The date and time at which the user answered the survey question.
 - question
 string — The survey question.
 - question_id
 string — The question's ID
 - email

```

```

`string`, format: `email` — The participant's email address.

- **`first_name`**

`string` — The participant's first name. If the Allow participants to answer questions anonymously setting is enabled for a [survey] (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the first_name field will return the "Anonymous Attendee" value.

- **`last_name`**

`string` — The participant's last name. If the Allow participants to answer questions anonymously setting is enabled for a [survey] (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the last_name field will return the "Anonymous Attendee" value.

- **`name`**

`string` — The participant's display name. Allow participants to answer questions anonymously setting is enabled for a [survey] (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0057559), the participant's survey information is kept anonymous and the name field will return the "Anonymous Attendee" value.

- **`survey_id`**

`string` — The survey's ID

- **`survey_name`**

`string` — The name of survey

- **`webinar_id`**

`integer`, format: `int64` — The webinar ID.

- **`webinar_uuid`**

`string` — The webinar's universally unique identifier (UUID). Each webinar instance generates a webinar UUID.

```

**Example:**

```

```json
{
  "webinar_id": 123456,
  "webinar_uuid": "4444AAAiAAAAAiAiAiAi==",
  "start_time": "2022-02-01T12:34:12.66Z",
  "survey_id": "8SFHRTGHAAAiAAAAAiAiAiAi==",
  "survey_name": "Survey of this meeting",
  "survey_answers": [
    {
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "first_name": "Jill",
      "last_name": "Chill",
      "answer_details": [
        {
          "question": "How are you?",
          "question_id": "798fGJEWrA",
          "answer": "I am wonderful.",
          "date_time": "2022-02-01T12:37:12.660Z"
        }
      ]
    }
  ]
}
```

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 1010` `User does not belong to this account:{accountId}`.  
 ##### Status: 403 `HTTP Status Code: 403` `Forbidden` `Error Code: 12702` `Can not access a webinar a year ago`.  
 ##### Status: 403 `HTTP Status Code: 403` `Forbidden` `Error Code: 200` `No permission`.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar {webinarId} not found or has expired`.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests`. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### List SIP phones

```
- **Method:** `GET`
- **Path:** `/sip_phones/phones`
- **Tags:** SIP Phone
```

List SIP phones on an account.

Zoom's Phone System Integration (PSI), also referred as SIP phones, enables an organization to leverage the Zoom client to complete a Softphone registration to supported premise based PBX system. End users will have the ability to have Softphone functionality within a single client while maintaining a comparable interface to Zoom Phone.

**\*\*Prerequisites\*\*:**

- Currently only supported on Cisco and Avaya PBX systems.
- User must enable SIP Phone Integration by contacting the [Sales](https://zoom.us/contactsales) team.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*** `sip\_phone:read:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`sip\_phone:read:list\_sip\_phones:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

#### Responses

##### Status: 200 **HTTP Status Code:** `200` SIP phones listed successfully. **Error Code:**   
`200` Permission missing. Enable SIP phone integration by contacting a Zoom admin first.

##### Content-Type: application/json

- **next\_page\_token**

string

- **page\_size**

integer, default: `30` — The number of records returned within a single API call.

- **phones**

array — SIP phones object.

**Items:**

- **authorization\_name**

string — The authorization name of the user that is registered for SIP phone.

- **display\_number**

string — The displayed phone number associated with the user can be either in extension format or E.164 format. You can specify the displayed number when the dialable number differs from the SIP username.

- **domain**

string — The name or IP address of your provider's SIP domain.

- **password**

string — The password generated for the user in the SIP account.

- **phone\_id**

string — The SIP phone ID.

- **registration\_expire\_time**

integer — The number of minutes after which the SIP registration of the Zoom client user will expire, and the client will auto register to the SIP server.

- **server**

object — Defined a set of basic components of SIP network architecture, including proxy\_server, register\_server and transport\_protocol.

- **proxy\_server**

string — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same

as the Register Server.

- **register\_server**

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- **transport\_protocol**

`string`, possible values: `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"` — Protocols supported by the SIP provider. The value must be either `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"`.

- **server\_2**

`object` — Defined a set of basic components of SIP network architecture, including `proxy_server`, `register_server` and `transport_protocol`.

- **proxy\_server**

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- **register\_server**

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- **transport\_protocol**

`string`, possible values: `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"` — Protocols supported by the SIP provider. The value must be either `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"`.

- **server\_3**

`object` — Defined a set of basic components of SIP network architecture, including `proxy_server`, `register_server` and `transport_protocol`.

- **proxy\_server**

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- **register\_server**

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- **transport\_protocol**

`string`, possible values: `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"` — Protocols supported by the SIP provider. The value must be either `"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"`.

- **user\_email**

`string`, format: `email` — The email address of the user to associate with the SIP Phone. Can add `.pc`, `.mobile`, `.pad` at the end of the email (for example, `user@example.com.pc`) to add accounts for different platforms for the same user.

- **user\_name**

`string` — The phone number associated with the user in the SIP account.

- **voice\_mail**

`string` — The number to dial for checking voicemail.

**Example:**

```
```json
{
  "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
  "page_size": 30,
  "phones": [
```

```
{
  "authorization_name": "testname",
  "domain": "example.com",
  "phone_id": "123456",
  "password": "apassword1",
  "registration_expire_time": 60,
  "user_email": "jchill@example.com",
  "user_name": "Jill Chill",
  "voice_mail": "4000",
  "display_number": "5551110105",
  "server": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  },
  "server_2": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  },
  "server_3": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  }
}
]
}
},
}
```

Status: 400 `HTTP Status Code: 400` `<br>` Bad Request

Status: 401 `HTTP Status Code: 401` `<br>` Unauthorized `Error Code: 124` `<br>` Invalid access token. `<br>`

Status: 403 `HTTP Status Code: 403` `<br>` Forbidden `Error Code: 3306` `<br>` No permission. `<br>`

Status: 429 `HTTP Status Code: 429` `<br>` Too Many Requests. For more information, see `[rate limits](/docs/api/rate-limits/)`.

Enable SIP phone

```
- **Method:** `POST`
- **Path:** `/sip_phones/phones`
- **Tags:** SIP Phone
```

Enable a user to use a SIP phone.

Zoom's Phone System Integration (PSI), also referred as SIP phones, enables an organization to leverage the Zoom client to complete a softphone registration to supported premise based PBX system. End users will have the ability to have softphone functionality within a single client while maintaining a comparable interface to Zoom Phone.

Prerequisites:

- Currently only supported on Cisco and Avaya PBX systems.
- The account owner or account admin must first enable SIP Phone Integration by contacting the [Sales](https://zoom.us/contactsales) team.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `sip_phone:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `sip_phone:write:sip_phone:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Request Body

Content-Type: application/json

- **`authorization_name`** (required)

`string` — The authorization name of the user that is registered for SIP phone.

- **`domain`** (required)

`string` — The name or IP address of your provider's SIP domain, such as example.com.

- **`password`** (required)

`string` — The password generated for the user in the SIP account.

- ****`server` (required)****

`object` — Defined a set of basic components of SIP network architecture, including proxy_server, register_server and transport_protocol.

- ****`proxy\_server`****

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- ****`register\_server`****

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- ****`transport\_protocol`****

`string`, possible values: `"UDP", "TCP", "TLS", "AUTO"` — Protocols supported by the SIP provider. The value must be either `\"UDP\", \"TCP\", \"TLS\", \"AUTO\"`.

- ****`user\_email` (required)****

`string`, format: `email` — The email address of the user to associate with the SIP Phone. Can add `\".pc\", \".mobile\", \".pad\"` at the end of the email, such as `\"user@example.com.pc\",` to add accounts for different platforms for the same user.

- ****`user\_name` (required)****

`string` — The phone number associated with the user in the SIP account.

- ****`display\_number`****

`string` — The displayed phone number associated with the user can be either in extension format or E.164 format. You can specify the displayed number when the dialable number differs from the SIP username.

- ****`registration\_expire\_time`****

`integer`, default: `60` — The number of minutes after which the SIP registration of the Zoom client user expires, and the client will auto register to the SIP server.

- ****`server\_2`****

`object` — Defined a set of basic components of SIP network architecture, including proxy_server, register_server and transport_protocol.

- ****`proxy\_server`****

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- ****`register\_server`****

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- ****`transport\_protocol`****

`string`, possible values: `"UDP", "TCP", "TLS", "AUTO"` — Protocols supported by the SIP provider. The value must be either `\"UDP\", \"TCP\", \"TLS\", \"AUTO\"`.

- ****`server\_3`****

`object` — Defined a set of basic components of SIP network architecture, including proxy_server, register_server and transport_protocol.

- ****`proxy\_server`****

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- ****`register\_server`****

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- ****`transport\_protocol`****

``string``, possible values: ``"UDP"`, "TCP", "TLS", "AUTO"` — Protocols supported by the SIP provider. The value must be either ``"UDP"`, "TCP"`, "TLS"`, "AUTO"`.`

- ****`voice\_mail`****

``string`` — The number to dial for checking voicemail.

****Example:****

```
```json
{
 "authorization_name": "testname",
 "domain": "example.com",
 "password": "123456",
 "registration_expire_time": 60,
 "user_email": "jchill@example.com",
 "user_name": "Jill Chill",
 "voice_mail": "4000",
 "display_number": "5551110105",
 "server": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 },
 "server_2": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 },
 "server_3": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 }
}
```

### **#### Responses**

**#####** Status: 201 ``*`HTTP Status Code: `*` `201` SIP phone created.`

**#####** Content-Type: application/json

### - **\*\*`authorization\_name`\*\***

``string`` — The authorization name of the user that is registered for SIP phone.

### - **\*\*`display\_number`\*\***

``string`` — The displayed phone number associated with the user can be either in extension format or E.164 format. You can specify the displayed number when the dialable number differs from the SIP username.

### - **\*\*`domain`\*\***

``string`` — The name or IP address of your provider's SIP domain (example: CDC.WEB).

### - **\*\*`password`\*\***

``string`` — The password generated for the user in the SIP account.

### - **\*\*`phone\_id`\*\***

``string`` — The SIP phone ID.

### - **\*\*`registration\_expire\_time`\*\***

``integer``, default: ``60`` — The number of minutes after which the SIP registration of the Zoom client user will expire, and the client will auto register to the SIP server.

### - **\*\*`server`\*\***



``object`` — Defined a set of basic components of SIP network architecture, including `proxy\_server`, `register\_server` and `transport\_protocol`.

- `**`proxy_server`**`

``string`` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- `**`register_server`**`

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- `**`transport_protocol`**`

``string``, possible values: ``"UDP", "TCP", "TLS", "AUTO"`` — Protocols supported by the SIP provider. The value must be either ``UDP\`, `TCP\`, `TLS\`, `AUTO\``.

- `**`server_2`**`

``object`` — Defined a set of basic components of SIP network architecture, including `proxy\_server`, `register\_server` and `transport\_protocol`.

- `**`proxy_server`**`

``string`` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- `**`register_server`**`

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- `**`transport_protocol`**`

``string``, possible values: ``"UDP", "TCP", "TLS", "AUTO"`` — Protocols supported by the SIP provider. The value must be either ``UDP\`, `TCP\`, `TLS\`, `AUTO\``.

- `**`server_3`**`

``object`` — Defined a set of basic components of SIP network architecture, including `proxy\_server`, `register\_server` and `transport\_protocol`.

- `**`proxy_server`**`

``string`` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- `**`register_server`**`

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- `**`transport_protocol`**`

``string``, possible values: ``"UDP", "TCP", "TLS", "AUTO"`` — Protocols supported by the SIP provider. The value must be either ``UDP\`, `TCP\`, `TLS\`, `AUTO\``.

- `**`user_email`**`

``string``, format: ``email`` — The email address of the user to associate with the SIP Phone. Can add ``pc\`, `mobile\`, `pad\`` at the end of the email (for example, ``user@example.com.mac\``) to add accounts for different platforms for the same user.

- `**`user_name`**`

``string`` — The phone number associated with the user in the SIP account.

- `**`voice_mail`**`

``string`` — The number to dial for checking voicemail.

**\*\*Example:\*\***

```json

```
{
  "phone_id": "123456",
  "authorization_name": "testname",
  "domain": "example.com",
  "password": "123456",
  "registration_expire_time": 60,
  "user_email": "jchill@example.com",
  "user_name": "Jill Chill",
  "voice_mail": "4000",
  "display_number": "5551110105",
  "server": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  },
  "server_2": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  },
  "server_3": {
    "proxy_server": "192.0.2.2",
    "register_server": "192.0.2.2",
    "transport_protocol": "UDP"
  }
}
```

Status: 400 ****HTTP Status Code:**** 400 ****Error Code:**** 200 ****Error Code:**** 300
Bad Request ****Error Code:**** 200
Permission missing. Enable SIP phone integration by contacting a Zoom admin first.
SIP phone with the same email already exists.

Status: 401 ****HTTP Status Code:**** 401 ****Error Code:**** 124
Unauthorized ****Error Code:**** 124
Invalid access token.

Status: 403 ****HTTP Status Code:**** 403 ****Error Code:**** 3306
Forbidden ****Error Code:**** 3306
No permission.

Status: 404 ****HTTP Status Code:**** 404 ****Error Code:**** 1001
Not Found ****Error Code:**** 1001
User {email} not exist or not belong to this account.

Status: 429 ****HTTP Status Code:**** 429
Too Many Requests. For more information, see [\[rate limits\]\(/docs/api/rate-limits/\)](#).

Delete SIP phone

```
- **Method:** DELETE
- **Path:** /sip_phones/phones/{phoneId}
- **Tags:** SIP Phone
```

Delete a Zoom account's SIP phone.

****Prerequisites:****

- Currently only supported on Cisco and Avaya PBX systems.
- The user must enable ****SIP Phone Integration**** by contacting the [\[Zoom Sales\]](https://zoom.us/contactsales) (<https://zoom.us/contactsales>) team.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** sip_phone:write:admin

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
sip_phone:delete:sip_phone:admin

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** LIGHT

Responses

Status: 204 ****HTTP Status Code:**** 204 SIP phone deleted.

Status: 401 ****HTTP Status Code:**** 401 ****Error Code:**** 124
Unauthorized ****Error Code:**** 124
Invalid access token.

Status: 403 ****HTTP Status Code:**** 403 ****Error Code:**** 3336
Forbidden ****Error Code:**** 3336
No permission.

Status: 404 ****HTTP Status Code:**** 404 ****Error Code:**** 2305
Not Found ****Error Code:**** 2305
SIP

phone does not exist: {phone_id}. \

Status: 429 *HTTP Status Code:*\`429\` \
 Too Many Requests. For more information, see \[rate limits]\(\/docs\/api\/rest\/rate-limits\/).

Update SIP phone

```
- **Method:** `PATCH`
- **Path:** `/sip_phones/phones/{phoneId}`
- **Tags:** SIP Phone
```

Update the information of a specific SIP phone on a Zoom account.

Zoom's Phone System Integration (PSI), also referred as SIP phones, lets an organization leverage the Zoom client to complete a softphone registration to supported premise based PBX system. End users can have softphone functionality within a single client while maintaining a comparable interface to a Zoom Phone.

****Prerequisites**:**

- Currently only supported on Cisco and Avaya PBX systems.
- The account owner or account admin must first enable SIP Phone Integration by contacting the [Sales](https://zoom.us/contactsales) team.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** `sip\_phone:write:admin`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**** `sip\_phone:update:sip\_phone:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** `LIGHT`

Request Body

Content-Type: application/json

- ****`authorization\_name`****

`string` — The authorization name of the user that is registered for SIP phone.

- ****`display\_number`****

`string` — The displayed phone number associated with the user can be either in extension format or E.164 format. You can specify the displayed number when the dialable number differs from the SIP username.

- ****`domain`****

`string` — The name or IP address of your provider's SIP domain, such as example.com.

- ****`password`****

`string` — The password generated for the user in the SIP account.

- ****`registration\_expire\_time`****

`integer`, default: `60` — The number of minutes after which the SIP registration of the Zoom client user will expire, and the client will auto register to the SIP server.

- ****`server`****

`object` — Defined a set of basic components of SIP network architecture, including proxy_server, register_server and transport_protocol.

- ****`proxy\_server`****

`string` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- ****`register\_server`****

`string` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- ****`transport\_protocol`****

`string`, possible values: `UDP`, `TCP`, `TLS`, `AUTO` — Protocols supported by the SIP provider. The value must be either `UDP`, `TCP`, `TLS`, `AUTO`.

- ****`server\_2`****

``object`` — Defined a set of basic components of SIP network architecture, including `proxy\_server`, `register\_server` and `transport\_protocol`.

- `**`proxy_server`**`

``string`` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- `**`register_server`**`

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- `**`transport_protocol`**`

``string``, possible values: ``"UDP", "TCP", "TLS", "AUTO"`` — Protocols supported by the SIP provider. The value must be either ``"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"`.`

- `**`server_3`**`

``object`` — Defined a set of basic components of SIP network architecture, including `proxy\_server`, `register\_server` and `transport\_protocol`.

- `**`proxy_server`**`

``string`` — The IP address of the proxy server for SIP requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address. If you are not using a proxy server, this value can be the same as the Register Server.

- `**`register_server`**`

``string`` — The IP address of the server that accepts REGISTER requests. Note that if you are using the UDP transport protocol, the default port is 5060. If you are using UDP with a different port number, that port number must be included with the IP address.

- `**`transport_protocol`**`

``string``, possible values: ``"UDP", "TCP", "TLS", "AUTO"`` — Protocols supported by the SIP provider. The value must be either ``"UDP"`, `"TCP"`, `"TLS"`, `"AUTO"`.`

- `**`user_name`**`

``string`` — The phone number associated with the user in the SIP account.

- `**`voice_mail`**`

``string`` — The number to dial for checking voicemail.

Example:

```
```json
{
 "authorization_name": "testname",
 "domain": "example.com",
 "password": "123456",
 "registration_expire_time": 60,
 "user_name": "Jill Chill",
 "voice_mail": "4000",
 "display_number": "5551110105",
 "server": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 },
 "server_2": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 },
 "server_3": {
 "proxy_server": "192.0.2.2",
 "register_server": "192.0.2.2",
 "transport_protocol": "UDP"
 }
}
```

### #### Responses

##### Status: 204 `\*\*Status Code:\*\* \`204\`` SIP phone updated.

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br>` Bad Request

##### Status: 401 `\*\*HTTP Status Code:\*\* \`401\`` `\<br>` Unauthorized `\*\*Error Code:\*\* \`124\`` `\<br>` Invalid access token. `\<br>`

##### Status: 403 `\*\*HTTP Status Code:\*\* \`403\`` `\<br>` Forbidden `\*\*Error Code:\*\* \`3336\`` `\<br>` No permission. `\<br>`

##### Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br>` Not Found `\*\*Error Code:\*\* \`2305\`` `\<br>` SIP phone does not exist: {phone\_id}. `\<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(\/docs/api/rate-limits\/)`.

### ### List an account's meeting or webinar summaries

- `\*\*Method:\*\*` `\`GET\``  
 - `\*\*Path:\*\*` `\`\/meetings/meeting_summaries\``  
 - `\*\*Tags:\*\*` Summaries

Retrieve a list of all meeting or webinar summaries available for an account.

#### **`\*\*Prerequisites\*\*`**

- The host must have a Pro, Business, or higher subscription plan.
- For meetings - the host's **`\*\*Meeting Summary with AI Companion\*\*`** user setting must be enabled.
- For webinars - the host's **`\*\*Webinar Summary with AI Companion\*\*`** user setting must be enabled.
- End-to-End Encrypted (E2EE) meetings do not support summaries.

Learn more about [enabling or disabling AI Companion meeting summaries]  
 ([https://support.zoom.com/hc/en/article?id=zm\\_kb\&sysparm\\_article=KB0057960](https://support.zoom.com/hc/en/article?id=zm_kb\&sysparm_article=KB0057960)).

**`\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`**  
`\`meeting_summary:read:admin\``

**`\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`**  
`\`meeting:read:list_summaries:admin\``

**`\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*`** `\`MEDIUM\``

### #### Responses

##### Status: 200 `\*\*HTTP Status Code:\*\* \`200\`` Successfully listed meeting summaries of an account.

##### Content-Type: application/json

- `\*\*\`from\`\*\*`

`\`string\``, format: `\`date-time\`` — The start date, in `\`yyyy-MM-dd'T'HH:mm:ss'Z'\`` UTC format, used to retrieve the meeting summaries' creation date range.

- `\*\*\`next_page_token\`\*\*`

`\`string\`` — Use the next page token to paginate through a large set of results. The next page token returns whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- `\*\*\`page_size\`\*\*`

`\`integer\``, default: `\`30\`` — The number of records returned with a single API call.

- `\*\*\`summaries\`\*\*`

`\`array\`` — List of meeting summary objects.

**`\*\*Items:\*\*`**

- `\*\*\`meeting_end_time\`\*\*`

`\`string\``, format: `\`date-time\`` — The meeting's end date and time.

- `\*\*\`meeting_host_email\`\*\*`

`\`string\``, format: `\`email\`` — The meeting host's email address.

```

- **`meeting_host_id`**

`string` — The ID of the user who is set as the meeting host.

- **`meeting_id`**

`integer`, format: `int64` — \[Meeting ID]\(https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-) - the meeting's unique identifier in `*\`long\`*` format, represented as int64 data type in JSON, also known as the meeting number.

- **`meeting_start_time`**

`string`, format: `date-time` — The meeting's start date and time.

- **`meeting_topic`**

`string` — Meeting topic.

- **`meeting_uuid`**

`string` — Unique meeting ID. Each meeting instance generates its own meeting UUID. After a meeting ends, a new UUID is generated for the next instance of the meeting. Retrieve a list of UUIDs from past meeting instances using the \[*\`List past meeting instances\`*\]\(/docs/api-reference/zoom-api/methods#operation/pastMeetings) API. \[Double encode]\(/docs/api/using-zoom-apis/#meeting-id-and-uuid) your UUID when using it for API calls if the UUID begins with a `\/` or contains `\/` in it.

- **`summary_created_time`**

`string`, format: `date-time` — The date and time when the meeting summary was created.

- **`summary_end_time`**

`string`, format: `date-time` — The summary's end date and time.

- **`summary_last_modified_time`**

`string`, format: `date-time` — The date and time when the meeting summary was last modified.

- **`summary_start_time`**

`string`, format: `date-time` — The summary's start date and time.

- **`to`**

`string`, format: `date-time` — The end date, in `\\yyyy-MM-dd'T'HH:mm:ss'Z'\` UTC format, used to retrieve the meeting summaries' creation date range.

```

**Example:**

```

```json
{
  "page_size": 30,
  "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
  "from": "2023-10-19T07:00:00Z",
  "to": "2023-10-20T07:00:00Z",
  "summaries": [
    {
      "meeting_host_id": "30R7kT7bTIKSNUFEuH_Qlg",
      "meeting_host_email": "jchill@example.com",
      "meeting_uuid": "aDYlohsHRtCd4i1uC2+hA==",
      "meeting_id": 97763643886,
      "meeting_topic": "My Meeting",
      "meeting_start_time": "2019-07-15T23:24:52Z",
      "meeting_end_time": "2020-07-15T23:30:19Z",
      "summary_start_time": "2019-07-15T23:24:52Z",
      "summary_end_time": "2020-07-15T23:30:19Z",
      "summary_created_time": "2019-07-15T23:24:52Z",
      "summary_last_modified_time": "2020-07-15T23:30:19Z"
    }
  ]
}
```

```

#### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 3161 **Meeting hosting and scheduling capabilities are not allowed for your user account.** **Error Code:** 3000 **Meeting summary disabled. To enable this feature, enable the Meeting Summary with AI Companion setting in the Zoom web portal's Settings interface.** **Error Code:** 200 **Only available for Paid account.**

##### Status: 403 `\*\*HTTP Status Code:\*\* `403`` `\<br> Forbidden \*\*Error Code:\*\* `2305`` `\<br>` Access to meeting summaries is restricted by account settings. To use this feature, disable the `\*\*Only share meeting summaries by email\*\*` setting in the `\*\*Account Settings\*\*` page of the Zoom web portal. `\<br>` `\*\*Error Code:\*\* `2305`` `\<br>` Access to meeting summaries is restricted to specific IP address ranges. To allow access, go to the `\*\*Settings\*\*` page in the Zoom web portal and update the `\*\*IP address access control\*\*` setting. `\<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* `429`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(\/docs/api/rest/rate-limits\/)`.

### ### Get a meeting or webinar summary

- `\*\*Method:\*\* `GET``  
 - `\*\*Path:\*\* `\/meetings/{meetingId}/meeting_summary``  
 - `\*\*Tags:\*\* Summaries`

Retrieve the summary of a meeting or webinar.

#### `\*\*Prerequisites\*\*`

- The host must have a Pro, Business, or higher subscription plan.
- For meetings - the host's `\*\*Meeting Summary with AI Companion\*\*` user setting must be enabled.
- For webinars - the host's `\*\*Webinar Summary with AI Companion\*\*` user setting must be enabled.
- End-to-End Encrypted (E2EE) meetings do not support summaries.

Learn more about `\[enabling or disabling AI Companion meeting summaries]`  
`(https://support.zoom.com/hc/en/article?id=zm_kb\&sysparm_article=KB0057960)`.

`\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`  
``meeting_summary:read`,`meeting_summary:read:admin``

`\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`  
``meeting:read:summary`,`meeting:read:summary:admin``

`\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* `LIGHT``

### #### Responses

##### Status: 200 `\*\*HTTP Status Code:\*\* `200`` Meeting summary object returned.

##### Content-Type: application/json

- `\*\*`edited_summary`\*\*`  
``object`` — The edited summary content.
- `\*\*`next_steps`\*\*`  
``array`` — The user edited next steps.  
`\*\*Items:\*\*`  
``string`` — The user edited next step.
- `\*\*`summary_details`\*\*`  
``string`` — The user edited summary details.
- `\*\*`summary_overview`\*\*`  
``string`` — The user edited summary overview.
- `\*\*`meeting_end_time`\*\*`  
``string``, format: ``date-time`` — The meeting's end date and time.
- `\*\*`meeting_host_email`\*\*`  
``string``, format: ``email`` — The meeting host's email address.
- `\*\*`meeting_host_id`\*\*`  
``string`` — The ID of the user who is set as the meeting host.
- `\*\*`meeting_id`\*\*`  
``integer``, format: ``int64`` — `\[The meeting ID](https://support.zoom.us/hc/en-us/articles/201362373-What-is-a-Meeting-ID-)` The meeting's unique identifier in `\*\*`long`\*\*` format, represented as int64 data type in JSON. Also known as the meeting number.

```

- meeting_start_time

 `string`, format: `date-time` — The meeting's start date and time.

- meeting_topic

 `string` — The meeting topic.

- meeting_uuid

 `string` — The unique meeting ID. Each meeting instance generates its own meeting UUID. After a meeting ends, a new UUID is generated for the next instance of the meeting. Use the [/docs/api-reference/zoom-api/methods#operation/pastMeetings] API to retrieve a list of UUIDs from past meeting instances. [Double encode] [/docs/api/rest/using-zoom-apis/#meeting-id-and-uuid] your UUID when using it for API calls if the UUID begins with a [/] or contains [/] in it.

- next_steps

 `array` — The next steps.

 Items:

 `string` — The next step.

- summary_content

 `string` — The complete meeting summary in Markdown format. This unified field is used for all summaries. For compatibility, the legacy fields summary_overview, summary_details, next_steps, and edited_summary are still returned, but are deprecated and will not be supported in the future.

- summary_created_time

 `string`, format: `date-time` — The date and time when the meeting summary was created.

- summary_details

 `array` — The summary content details.

 Items:

 - label

 `string` — The summary label.

 - summary

 `string` — The summary content.

- summary_doc_url

 `string`, format: `uri` — The URL to view the full summary document in Zoom Docs.

- summary_end_time

 `string`, format: `date-time` — The summary's end date and time.

- summary_last_modified_time

 `string`, format: `date-time` — The date and time when the meeting summary was last modified.

- summary_last_modified_user_email

 `string` — The user email of the user who last modified the meeting summary.

- summary_last_modified_user_id

 `string` — The user ID of the user who last modified the meeting summary.

- summary_overview

 `string` — The summary overview.

- summary_start_time

 `string`, format: `date-time` — The summary's start date and time.

- summary_title

 `string` — The summary title.

```



**\*\*Example:\*\***

```
```json
```

```
{
  "meeting_host_id": "30R7kT7bTIKSNUFEuH_Qlg",
  "meeting_host_email": "jchill@example.com",
  "meeting_uuid": "aDYlohSHRtCd4iiluC2+hA==",
  "meeting_id": 97763643886,
  "meeting_topic": "My Meeting",
  "meeting_start_time": "2019-07-15T23:24:52Z",
  "meeting_end_time": "2020-07-15T23:30:19Z",
  "summary_start_time": "2019-07-15T23:24:52Z",
  "summary_end_time": "2020-07-15T23:30:19Z",
  "summary_created_time": "2019-07-15T23:24:52Z",
  "summary_last_modified_time": "2020-07-15T23:30:19Z",
  "summary_last_modified_user_id": "Lfi0BlBQTM-bbktE9BRUvA",
  "summary_last_modified_user_email": "user@example.com",
  "summary_title": "Meeting summary for my meeting",
  "summary_content": "## Key takeaways\n- Mobile app performance issues are affecting user retention.\n- New onboarding flow received positive feedback from beta testers.\n- Need to prioritize accessibility improvements.\n- Customer support response time has improved by 25%.\n\n## Discussed topics\n### Mobile App Performance\nDiscussion of recent performance metrics and user complaints\n- **Details**\n  - Sarah (Product): Reports of app crashes increased 15% this month\n  - Mike (Engineering): Memory optimization needed in latest release\n  - Tom (QA): Identified memory leak in photo upload feature\n- **Conclusion**\n  - Implement performance monitoring tools\n  - Prioritize memory optimization in next sprint\n\n### Onboarding Flow\nReview of beta testing results for new user onboarding\n- **Details**\n  - Rachel (UX): 90% completion rate in beta testing\n  - David (Product): Positive feedback on simplified registration\n- **Conclusion**\n  - Ready for full rollout next month\n  - Need to monitor analytics post-launch\n\n### Accessibility Compliance\nDiscussion of current accessibility status and needed improvements\n- **Details**\n  - Lisa (Design): Screen reader compatibility issues identified\n  - John (Engineering): WCAG compliance at 80%\n- **Conclusion**\n  - Create accessibility improvement roadmap\n  - Schedule external audit\n\n### Challenges\n* Resource constraints for performance optimization\n* Integration testing environment stability issues\n* Lack of accessibility expertise in the team\n\n### Action items\n- **Sarah**\n  - Prepare performance monitoring implementation plan\n  - Schedule follow-up meeting with engineering team\n- **Mike**\n  - Investigate memory leak fix\n  - Document performance optimization guidelines\n- **Lisa**\n  - Create accessibility improvement proposal\n  - Research accessibility testing tools\n- **Rachel**\n  - Prepare onboarding analytics dashboard\n  - Document beta testing findings",
  "summary_doc_url": "https://docs.zoom.us/doc/1aBcDeFgHiJkLmNoPqRsTu"
}
```

Status: 400 ****HTTP Status Code:**** 400 ****Error Code:**** 200 ****Only available for Paid account. Error Code: 300 Invalid meeting ID.**

Status: 403 ****HTTP Status Code:**** 403 ****Error Code:**** 2305 ****Access to meeting summaries is restricted by account settings. To use this feature, disable the Only share meeting summaries by email setting in the Account Settings page of the Zoom web portal. Error Code: 2305 Access to meeting summaries is restricted to specific IP address ranges. To allow access, go to the Settings page in the Zoom web portal and update the IP address access control setting. Error Code: 2305 The meeting summary has been moved to Trash and cannot be accessed.**

Status: 404 ****HTTP Status Code:**** 404 ****Error Code:**** 3001 ****Meeting does not exist: {meetingId}.**

Status: 429 ****HTTP Status Code:**** 429 ****Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).**

Delete a meeting or webinar summary

```
- **Method:** DELETE
- **Path:** /meetings/{meetingId}/meeting_summary
- **Tags:** Summaries
```

Delete the summary of a meeting or webinar.

****Prerequisites****

- The host must have a Pro, Business, or higher subscription plan.
- For meetings - the host's ****Meeting Summary with AI Companion**** user setting must be enabled.
- For webinars - the host's ****Webinar Summary with AI Companion**** user setting must be enabled.
- End-to-End Encrypted (E2EE) meetings do not support summaries.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`meeting\_summary:write`, `meeting\_summary:write:admin`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`meeting:delete:summary`, `meeting:delete:summary:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** LIGHT

Responses

Status: 204 `HTTP Status Code: 204` Meeting summary deleted.

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` Only available for Paid account. `Error Code: 300` Invalid meeting ID. `Error Code: 2313` Failed to delete meeting summary.

Status: 403 `HTTP Status Code: 403` `Forbidden` `Error Code: 2305` Access to meeting summaries is restricted by account settings. To use this feature, disable the `Only share meeting summaries by email` setting in the `Account Settings` page of the Zoom web portal. `Error Code: 2305` Access to meeting summaries is restricted to specific IP address ranges. To allow access, go to the `Settings` page in the Zoom web portal and update the `IP address access control` setting. `Error Code: 2305` The meeting summary has been moved to Trash and cannot be accessed.

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` Meeting does not exist: {meetingId}.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits](/docs/api/rate-limits/)`.

Get a meeting survey

- `Method: GET`
 - `Path: /meetings/{meetingId}/survey`
 - `Tags: Surveys`

Display information about a [meeting survey](https://support.zoom.us/hc/en-us/articles/4404969060621-Post-meeting-survey-and-reporting). `Prerequisites:` `The host has a Pro license.` `The [Meeting Survey](https://support.zoom.us/hc/en-us/articles/4404939095053-Enabling-meeting-surveys) feature is enabled on the host's account.` `The meeting must be a scheduled meeting.` Instant meetings do not have survey features enabled.

`[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):` `meeting:read, meeting:read:admin`

`[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):` `meeting:read:survey, meeting:read:survey:admin`

`[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):` `LIGHT`

Responses

Status: 200 `HTTP Status Code: 200` Meeting survey object returned.

Content-Type: application/json

- `custom_survey`

`object` — Information about the customized meeting survey.

- `anonymous`

`boolean`, default: `false` — Allow participants to anonymously answer survey questions. This value defaults to `true`.

- `feedback`

`string` — The survey's feedback, up to 320 characters. This value defaults to `Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.`

- `numbered_questions`

`boolean`, default: `false` — Whether to display the number in the question name. This value defaults to `true`.

- `questions`

`array` — Information about the meeting survey's questions.

`Items:`

- `answer_max_character`

`integer` — The allowed maximum number of characters. This field only applies to `short_answer` and `long_answer` questions. `For short_answer question, a maximum of 500 characters.` `For long_answer question, a maximum of 2,000 characters.`

```

- answer_min_character

  integer — The allowed minimum number of characters. This field only applies to short_answer and long_answer questions. You must provide at least a one character minimum value.

- answer_required

  boolean, default: false — Whether participants must answer the question. true - The participant must answer the question. false - The participant does not need to answer the question. This value defaults to false.

- answers

  array — The survey question's available answers. This field requires a minimum of two answers. For single and multiple questions, you can only provide a maximum of 50 answers. For matching polls, you can only provide a maximum of 16 answers. For rank_order polls, you can only provide a maximum of seven answers.

  Items:

  string

- name

  string — The survey question, up to 420 characters.

- prompts

  array — Information about the prompt questions. This field only applies to matching and rank_order questions. You must provide a minimum of two prompts, up to a maximum of 10 prompts.

  Items:

  - prompt_question

    string — The question prompt's title.

- rating_max_label

  string — The high score label used for the rating_max_value field, up to 50 characters. This field only applies to the rating_scale survey.

- rating_max_value

  integer — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the rating_scale survey.

- rating_min_label

  string — The low score label used for the rating_min_value field, up to 50 characters. This field only applies to the rating_scale survey.

- rating_min_value

  integer — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the rating_scale survey.

- show_as_dropdown

  boolean, default: false — Whether to display the radio selection as a drop-down box. true - Show as a drop-down box. false - Do not show as a drop-down box. This value defaults to false.

- type

  string, possible values: "single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale" — The survey's question and answer type. single - Single choice. multiple - Multiple choice. matching - Matching. rank_order - Rank order. short_answer - Short answer. long_answer - Long answer. fill_in_the_blank - Fill in the blank. rating_scale - Rating scale.

- show_question_type

  boolean, default: false — Whether to display the question type in the question name. This value defaults to false.

- title

  string — The survey's title, up to 64 characters.

- show_in_the_browser

```

`boolean`, default: `true` — Whether the `Show in the browser when the meeting ends` option is enabled. `true` - Enabled. `false` - Disabled. This value defaults to `true`.

- **third_party_survey**

`string` — The link to the third party meeting survey.

Example:

```
```json
{
 "custom_survey": {
 "title": "Learn something new",
 "anonymous": false,
 "numbered_questions": false,
 "show_question_type": false,
 "feedback": "Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.",
 "questions": [
 {
 "name": "How useful was this meeting?",
 "type": "single",
 "answer_required": false,
 "show_as_dropdown": false,
 "answers": [
 "Extremely useful"
],
 "prompts": [
 {
 "prompt_question": "How are you?"
 }
],
 "answer_min_character": 1,
 "answer_max_character": 200,
 "rating_min_value": 1,
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_max_label": "Extremely Likely"
 }
]
 },
 "show_in_the_browser": true,
 "third_party_survey": "https://example.com"
}
```
```

Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300 Invalid meeting ID. Error Code: 3000 Cannot access webinar information. Error Code: 3000 Meeting survey disabled. To enable this feature, enable the "Meeting Survey" setting in the Zoom web portal's "Settings" interface. Error Code: 3161 Meeting hosting and scheduling capabilities are not allowed for your user account.

Status: 404 HTTP Status Code: 404 Not Found Error Code: 300 Meeting ID does not exist. Error Code: 3001 Meeting does not exist: {meetingId}.

Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](/docs/api/rest/rate-limits/).

Delete a meeting survey

- **Method:** DELETE
 - **Path:** /meetings/{meetingId}/survey
 - **Tags:** Surveys

Delete a [meeting survey](https://support.zoom.us/hc/en-us/articles/4404969060621-Post-meeting-survey-and-reporting).

Prerequisites:

- The host must be a **Pro** user type.
- The **Meeting Survey** (https://support.zoom.us/hc/en-us/articles/4404939095053-Enabling-meeting-surveys) feature enabled in the host's account.
- The meeting must be a scheduled meeting. Instant meetings do not have survey features enabled.

Scopes (https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 meeting:write, meeting:write:admin

Granular Scopes (https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):

```
`meeting:delete:survey`,`meeting:delete:survey:admin`
```

```
**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`
```

Responses

```
##### Status: 204 `HTTP Status Code:` `204` Meeting survey deleted.
```

```
##### Status: 400 `HTTP Status Code:` `400`   
 Bad Request `Error Code:` `300`   
 Invalid meeting ID.   
 `Error Code:` `3000`   
 `Cannot access webinar information.   
 Meeting survey disabled. To enable this feature, enable the `Meeting Survey` setting in the Zoom web portal's `Settings` interface.   
 `Error Code:` `3161`   
 Meeting hosting and scheduling capabilities are not allowed for your user account.   

```

```
##### Status: 404 `HTTP Status Code:` `404`   
 Not Found `Error Code:` `300`   
 Meeting ID does not exist.   
 `Error Code:` `3001`   
 Meeting does not exist: {meetingId}.   

```

```
##### Status: 429 `HTTP Status Code:` `429`   
 Too Many Requests. For more information, see   
 [rate limits](/docs/api/rest/rate-limits/).
```

Update a meeting survey

```
- **Method:** `PATCH`  
- **Path:** `/meetings/{meetingId}/survey`  
- **Tags:** Surveys
```

Update a [meeting survey](https://support.zoom.us/hc/en-us/articles/4404969060621-Post-meeting-survey-and-reporting). **Prerequisites:**
 * The host must be a **Pro** user type.
 * The **Meeting Survey** [https://support.zoom.us/hc/en-us/articles/4404939095053-Enabling-meeting-surveys] feature is enabled in the host's account.
 * The meeting must be a scheduled meeting. Instant meetings do not have survey features enabled.

```
**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
`meeting:write`,`meeting:write:admin`
```

```
**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
`meeting:update:survey`,`meeting:update:survey:admin`
```

```
**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`
```

Request Body

```
##### Content-Type: application/json
```

```
- **`custom_survey`**
```

```
  `object` — Information about the customized meeting survey.
```

```
  - **`anonymous`**
```

```
    `boolean`, default: `false` — Allow participants to anonymously answer survey questions. This value defaults to `true`.
```

```
  - **`feedback`**
```

```
    `string` — The survey's feedback, up to 320 characters. This value defaults to `Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.`.
```

```
  - **`numbered_questions`**
```

```
    `boolean`, default: `false` — Whether to display the number in the question name. This value defaults to `true`.
```

```
  - **`questions`**
```

```
    `array` — Information about the meeting survey's questions.
```

```
    **Items:**
```

```
      - **`answer_max_character`**
```

```
        `integer` — The allowed maximum number of characters. This field only applies to `short_answer` and `long_answer` questions.   
 * For `short_answer` question, a maximum of 500 characters.   
 * For `long_answer` question, a maximum of 2,000 characters.
```

```
      - **`answer_min_character`**
```

```
        `integer` — The allowed minimum number of characters. This field only applies to `short_answer` and `long_answer` questions. You must provide at least a one character minimum value.
```

```

- answer_required

  `boolean`, default: `false` — Whether participants must answer the question. `true` - The participant must answer the question. `false` - The participant does not need to answer the question. This value defaults to `false`.

- answers

  `array` — The survey question's available answers. This field requires a minimum of two answers. For single and multiple questions, you can only provide a maximum of 50 answers. For matching polls, you can only provide a maximum of 16 answers. For rank_order polls, you can only provide a maximum of seven answers.

  Items:

  `string`

- name

  `string` — The survey question, up to 420 characters.

- prompts

  `array` — Information about the prompt questions. This field only applies to matching and rank_order questions. You must provide a minimum of two prompts, up to a maximum of 10 prompts.

  Items:

  - prompt_question

    `string` — The question prompt's title.

  - rating_max_label

    `string` — The high score label used for the rating_max_value field, up to 50 characters. This field only applies to the rating_scale survey.

  - rating_max_value

    `integer` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the rating_scale survey.

  - rating_min_label

    `string` — The low score label used for the rating_min_value field, up to 50 characters. This field only applies to the rating_scale survey.

  - rating_min_value

    `integer` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the rating_scale survey.

- show_as_dropdown

  `boolean`, default: `false` — Whether to display the radio selection as a drop-down box. `true` - Show as a drop-down box. `false` - Do not show as a drop-down box. This value defaults to `false`.

- type

  `string`, possible values: "single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale" — The survey's question and answer type. `single` - Single choice. `multiple` - Multiple choice. `matching` - Matching. `rank_order` - Rank order. `short_answer` - Short answer. `long_answer` - Long answer. `fill_in_the_blank` - Fill in the blank. `rating_scale` - Rating scale.

- show_question_type

  `boolean`, default: `false` — Whether to display the question type in the question name. This value defaults to `false`.

- title

  `string` — The survey's title, up to 64 characters.

- show_in_the_browser

  `boolean`, default: `true` — Whether the Show in the browser when the meeting ends option is enabled. `true` - Enabled. `false` - Disabled. This value defaults to `true`.

```

- **third_party_survey**

``string`` — The link to the third party meeting survey.

Example:

````json`

```
{
 "custom_survey": {
 "title": "Learn something new",
 "anonymous": false,
 "numbered_questions": false,
 "show_question_type": false,
 "feedback": "Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.",
 "questions": [
 {
 "name": "How useful was this meeting?",
 "type": "single",
 "answer_required": false,
 "show_as_dropdown": false,
 "answers": [
 "Extremely useful"
],
 "prompts": [
 {
 "prompt_question": "How are you?"
 }
],
 "answer_min_character": 1,
 "answer_max_character": 200,
 "rating_min_value": 1,
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_max_label": "Extremely Likely"
 }
]
 },
 "show_in_the_browser": true,
 "third_party_survey": "https://example.com"
}
```

#### #### Responses

##### Status: 204 `HTTP Status Code: 204` Meeting survey updated.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` Invalid meeting ID. `Error Code: 300` Invalid third party survey: `{third_party_survey}`. `Error Code: 3161` Meeting hosting and scheduling capabilities are not allowed for your user account. `Error Code: 3000` Cannot access Webinar information. `Error Code: 3000` Meeting survey disabled. To enable this feature, enable the `Meeting Survey` setting in the Zoom web portal's `Settings` interface. `Error Code: 3000` Not allowed host to use a 3rd-party survey link. To use this feature, enable the "Allow host to use a 3rd-party survey link" setting in the "Account Settings" page of the Zoom web portal.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 300` Meeting ID does not exist. `Error Code: 3001` Meeting does not exist: `{meetingId}`.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits](/docs/api/rest/rate-limits/)`.

#### ### Get account's TSP information

- **Method:** `GET`  
 - **Path:** `/tsp`  
 - **Tags:** TSP

Get information on Telephony Service Provider (TSP) on an account level.

#### **Prerequisites**

- TSP audio must be enabled on the Zoom account before using this API.
- The Zoom account must have a Pro or higher subscription plan to enable TSP.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:read:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):

``tsp:read:tsp:admin``

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** ``LIGHT``

**#### Responses**

**##### Status:** `200` ``HTTP Status Code:`` `200` TSP account detail returned successfully.

**##### Content-Type:** `application/json`

- **``dial_in_number_unrestricted``**

``boolean`` — Control restriction on account users adding a TSP number outside of account's dial in numbers.

- **``dial_in_numbers``**

``array`` — List of dial in numbers.

**``Items:``**

- **``code``**

``string`` — Country code.

- **``number``**

``string`` — Dial-in number. Length is less than 16.

- **``type``**

``string`` — Dial-in number type.

- **``enable``**

``boolean`` — Enable Telephony Service Provider for account users.

- **``master_account_setting_extended``**

``boolean`` — For master account, extend its TSP setting to all sub accounts. For sub account, extend TSP setting from master account.

- **``modify_credential_forbidden``**

``boolean`` — Control restriction on account users being able to modify their TSP credentials.

- **``tsp_bridge``**

``string``, possible values: ``"US_TSP_TB", "EU_TSP_TB"`` — Telephony bridge zone

- **``tsp_enabled``**

``boolean`` — Enable TSP feature for account. This has to be enabled to use any other tsp settings/features.

- **``tsp_provider``**

``string`` — Telephony service provider.

**``Example:``**

``json``

```
{
 "dial_in_number_unrestricted": false,
 "dial_in_numbers": [
 {
 "code": "1",
 "number": "+1 1000200200",
 "type": "toll"
 }
],
 "enable": true,
 "master_account_setting_extended": true,
 "modify_credential_forbidden": true,
 "tsp_bridge": "US_TSP_TB",
 "tsp_enabled": true,
 "tsp_provider": "someprovidername"
}
```



##### Status: 429 `\**HTTP Status Code:\** \`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(/docs/api/rate-limits/)`.

### ### Update an account's TSP information

```
- **Method:** `PATCH`
- **Path:** `/tsp`
- **Tags:** TSP
```

Update information of the Telephony Service Provider (TSP) set up on an account.

#### **\*\*Prerequisites\*\***

- Enable TSP on the Zoom account before using this API.
- A Pro or higher subscription plan to enable TSP.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*** `tsp:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`tsp:update:tsp:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

### #### Request Body

##### Content-Type: application/json

```
- **`dial_in_number_unrestricted`**
```

`boolean` — Control restriction on account users adding a TSP number outside of account's dial in numbers.

```
- **`enable`**
```

`boolean` — Enable 3rd party audio conferencing for account users

```
- **`master_account_setting_extended`**
```

`boolean` — For master account, extend its TSP setting to all sub accounts. For sub account, extend TSP setting from master account.

```
- **`modify_credential_forbidden`**
```

`boolean` — Control restriction on account users being able to modify their TSP credentials.

```
- **`tsp_bridge`**
```

`string`, possible values: `US\_TSP\_TB`, `EU\_TSP\_TB` — Telephony bridge

```
- **`tsp_enabled`**
```

`boolean` — Enable TSP feature for account. This has to be enabled to use any other tsp settings/features.

```
- **`tsp_provider`**
```

`string` — 3rd party audio conferencing provider

#### **\*\*Example:\*\***

```
``json
```

```
{
 "dial_in_number_unrestricted": true,
 "enable": true,
 "master_account_setting_extended": true,
 "modify_credential_forbidden": true,
 "tsp_bridge": "US_TSP_TB",
 "tsp_enabled": true,
 "tsp_provider": "someprovidername"
}
```

### #### Responses

##### Status: 204 `\**HTTP Status Code:\** \`204\`` `\**No Content\**` TSP Account updated.

##### Status: 400 `\**HTTP Status Code:\** \`400\`` `\<br>` Bad Request `\**Error Code:\** \`300\`` `\<br>` Invalid parameter: `\`tsp_bridge\``. `\<br>`

##### Status: 429 `\**HTTP Status Code:\** \`429\`` `\<br>` Too Many Requests. For more information, see `\`

[rate limits](/docs/api/rate-limits/).

### ### List user's TSP accounts

```
- **Method:** `GET`
- **Path:** `/users/{userId}/tsp`
- **Tags:** TSP
```

List all of a user's TSP accounts. A user can have a maximum of two TSP accounts.

#### \*\*Prerequisites\*\*

- TSP (Telephony Service Provider) audio must be enabled on the Zoom account before using this API.
- The Zoom account must have a Pro or higher subscription plan to enable TSP.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `tsp:read:admin`, `tsp:read`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `tsp:read:list\_tsp\_accounts`, `tsp:read:list\_tsp\_accounts:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `MEDIUM`

### #### Responses

##### Status: 200 `HTTP Status Code: 200 OK` TSP account list returned successfully.

##### Content-Type: application/json

```
- **`tsp_accounts`**
```

`array` — List of the user's TSP accounts.

**Items:**

```
- **`conference_code` (required)**
```

`string` — Conference code: numeric value, length is less than 16.

```
- **`leader_pin` (required)**
```

`string` — Leader PIN. Numeric value, length is less than 16.

```
- **`dial_in_numbers`**
```

`array` — List of dial in numbers.

**Items:**

```
- **`code`**
```

`string` — Country code.

```
- **`country_label`**
```

`string` — Country label, if passed, will display in place of code.

```
- **`number`**
```

`string` — Dial-in number. Length is less than 16.

```
- **`type`**
```

`string`, possible values: `"toll"`, `"tollfree"`, `"media_link"` — Dial-in number types. `"toll"` - Toll number. `"tollfree"` - Toll free number. `"media_link"` - Media link.

```
- **`id`**
```

`string`, possible values: `"1"`, `"2"` — The TSP account's ID.

```
- **`tsp_bridge`**
```

`string`, possible values: `"US_TSP_TB"`, `"EU_TSP_TB"` — Telephony bridge

#### \*\*Example:\*\*

```
```json
{
  "tsp_accounts": [
    {
```

```

    "conference_code": "0125",
    "dial_in_numbers": [
      {
        "code": "1",
        "country_label": "America",
        "number": "+1 1000200200",
        "type": "toll"
      }
    ],
    "id": "1",
    "leader_pin": "11189898",
    "tsp_bridge": "US_TSP_TB"
  }
]
}

```

Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 2024`
Account has not enabled TSP.

Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 1001` User does not exist: `userId`.
`Error Code: 1120` No valid invitation to join the Zoom account was found for this user. This error is thrown if you added a user in your account but the user did not accept the invitation on time and the invitation expired, making the `userId` invalid.

Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

Add a user's TSP account

```

- **Method:** `POST`
- **Path:** `/users/{userId}/tsp`
- **Tags:** TSP

```

Add a user's TSP account.

Prerequisites

- TSP (Telephony Service Provider) audio must be enabled on the Zoom account before using this API.
- The Zoom account must have a Pro or higher subscription plan to enable TSP.

[Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:write:admin`, `tsp:write`

[Granular Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:write:tsp_account`, `tsp:write:tsp_account:admin`

[Rate Limit Label] (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

Request Body

Content-Type: application/json

- ```

- **`conference_code` (required)**

 `string` — Conference code. A numeric value, with a length less than 16.

- **`leader_pin` (required)**

 `string` — Leader PIN: numeric value, length is less than 16.

- **`dial_in_numbers`**

 `array` — List of dial in numbers.

 Items:

 - **`code`**

 `string` — Country code.

 - **`country_label`**

 `string` — Country Label, if passed, will display in place of code.

 - **`number`**

 `string` — Dial-in number: length is less than 16.

 - **`type`**

```

``string``, possible values: ``"toll", "tollfree", "media_link"`` — Dial-in number types: ``\`toll\`` - Toll number. ``\`tollfree\`` -Toll free number. ``\`media\_link\`` - Media link.

- `**`tsp_bridge`**`

``string``, possible values: ``"US_TSP_TB", "EU_TSP_TB"`` — Telephony bridge

**\*\*Example:\*\***

```
```json
{
  "conference_code": "0125",
  "dial_in_numbers": [
    {
      "code": "1",
      "country_label": "America",
      "number": "+1 1000200200",
      "type": "toll"
    }
  ],
  "leader_pin": "US_TSP_TB",
  "tsp_bridge": "US_TSP_TB"
},
```
```

#### Responses

##### Status: 201 `\`*\`HTTP Status Code:\`*\`` `\`201\`` TSP account added.

##### Content-Type: application/json

**\*\*All of:\*\***

- `**`id`**`

``string`` — The ID of the TSP account.

\* `**`conference_code` (required)**`

``string`` — Conference code: numeric value, length is less than 16.

\* `**`leader_pin` (required)**`

``string`` — Leader PIN: numeric value, length is less than 16.

\* `**`dial_in_numbers`**`

``array`` — List of dial in numbers.

**\*\*Items:\*\***

- `**`code`**`

``string`` — Country code.

- `**`country_label`**`

``string`` — Country Label, if passed, will display in place of code.

- `**`number`**`

``string`` — Dial-in number: length is less than 16.

- `**`type`**`

``string``, possible values: ``"toll", "tollfree", "media_link"`` — Dial-in number types: ``\`toll\`` - Toll number. ``\`tollfree\`` -Toll free number. ``\`media\_link\`` - Media link.

\* `**`tsp_bridge`**`

``string``, possible values: ``"US_TSP_TB", "EU_TSP_TB"`` — Telephony bridge

**\*\*Example:\*\***

```
```json
{
  "id": "1",
  "conference_code": "0125",
  "dial_in_numbers": [

```


[rate limits](/docs/api/rate-limits/).

Get a user's TSP account

```
- **Method:** `GET`
- **Path:** `/users/{userId}/tsp/{tspId}`
- **Tags:** TSP
```

Retrieve details of a specific TSP account enabled for a specific user. Each user can have a maximum of two TSP accounts.

Prerequisites

- TSP (Telephony Service Provider) audio must be enabled on the Zoom account before using this API.
- The Zoom account must have a Pro or higher subscription plan to enable TSP.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `tsp:read:admin`, `tsp:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `tsp:read:tsp\_account`, `tsp:read:tsp\_account:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `\*\*HTTP Status Code:\*\*` `200` TSP account retrieved successfully.

Content-Type: application/json

- **`conference\_code` (required)**

``string`` — Conference code: numeric value, length is less than 16.

- **`leader\_pin` (required)**

``string`` — Leader PIN. A numeric value, with a length of less than 16.

- **`dial\_in\_numbers`**

``array`` — List of dial in numbers.

****Items:****

- **`code`**

``string`` — Country code.

- **`country\_label`**

``string`` — Country Label, if passed, will display in place of code.

- **`number`**

``string`` — Dial-in number: length is less than 16.

- **`type`**

``string``, possible values: ``"toll", "tollfree", "media_link"`` — Dial-in number types: ``"toll"`` - Toll number. ``"tollfree"`` - Toll free number. ``"media_link"`` - Media link phone number. This is used for PSTN integration instead of a paid bridge number.

- **`id`**

``string`` — The TSP account's ID.

- **`tsp\_bridge`**

``string``, possible values: ``"US_TSP_TB", "EU_TSP_TB"`` — Telephony bridge

Example:

```
```json
{
 "conference_code": "0125",
 "dial_in_numbers": [
 {
 "code": "1",
 "country_label": "America",
 "number": "+1 1000200200",

```

```

 "type": "toll"
 }
],
"id": "1",
"leader_pin": "11189898",
"tsp_bridge": "US_TSP_TB"
}
},

```

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **The TSP ID provided does not exist.**  
**Error Code:** 300 **TSP config does not exist.**  
**Error Code:** 2024 **Account has not enabled TSP.**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 1001 **User does not exist: \$userId.**  
**Error Code:** 1120 **No valid invitation to join the Zoom account was found for this user.** This error is thrown if you added a user in your account but the user did not accept the invitation on time and the invitation expired, making the `userId` invalid.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Delete a user's TSP account

```

- Method: DELETE
- Path: /users/{userId}/tsp/{tspId}
- Tags: TSP

```

Delete a user's TSP account.

#### Prerequisites

- TSP (Telephony Service Provider) audio must be enabled on the Zoom account before using this API.
- The Zoom account must have a Pro or higher subscription plan to enable TSP.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:write:admin`, `tsp:write`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:delete:tsp_account`, `tsp:delete:tsp_account:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

### Responses

##### Status: 204 **Status Code:** 204 **No Content** TSP account deleted.

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 2024 **This account has not enabled TSP.**  
**Error Code:** 300 **The provided TSP ID does not exist.**  
**Error Code:** 300 **TSP config does not exist.**  
**Error Code:** 300 **At least one TSP config must be available.**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 1001 **User does not exist: \$userId.**  
**Error Code:** 1120 **No valid invitation to join the Zoom account was found for this user.** This error is thrown if you added a user in your account but the user did not accept the invitation on time and the invitation expired, making the `userId` invalid.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Update a TSP account

```

- Method: PATCH
- Path: /users/{userId}/tsp/{tspId}
- Tags: TSP

```

Update a user's Telephony Service Provider (TSP) account.

#### Prerequisites

- TSP audio enabled on the Zoom account before using this API.
- A Pro or higher subscription plan to enable TSP.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:write:admin`, `tsp:write`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `tsp:update:tsp_account`, `tsp:update:tsp_account:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

## #### Request Body

##### Content-Type: application/json

- **conference\_code** (required)\*\*

`string` — Conference code. Numeric value. Length is less than 16.

- **leader\_pin** (required)\*\*

`string` — Leader PIN. Numeric value. Length is less than 16.

- **dial\_in\_numbers**\*\*

`array` — List of dial in numbers.

**Items:**- **code**\*\*

`string` — Country code.

- **country\_label**\*\*

`string` — Country label, if passed, will display in place of code.

- **number**\*\*

`string` — Dial-in number. Length is less than 16.

- **type**\*\*

`string`, possible values: `toll`, `tollfree`, `media\_link` — Dial-in number types. `toll` - Toll number. `tollfree` - Toll free number. `media\_link` - Media Link Phone Number. It is used for PSTN integration instead of paid bridge number.

- **tsp\_bridge**\*\*

`string`, possible values: `US\_TSP\_TB`, `EU\_TSP\_TB` — Telephony bridge.

**Example:**

``json

```
{
 "conference_code": "0125",
 "dial_in_numbers": [
 {
 "code": "1",
 "country_label": "America",
 "number": "+1 1000200200",
 "type": "toll"
 }
],
 "leader_pin": "11189898",
 "tsp_bridge": "US_TSP_TB"
},
```

## #### Responses

##### Status: 204 **HTTP Status Code:** 204 **No Content** TSP account updated.

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 2024 **Account has not enabled TSP.** **Error Code:** 300 **The TSP ID provided does not exist.** **Error Code:** 300 **TSP config does not exist.** **Error Code:** 300 **Media link is required for AT&T TSP accounts.** **Error Code:** 300 **Invalid parameter: tsp\_bridge.**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 1001 **User does not exist: \$userId.** **Error Code:** 1120 **A valid invitation to join the Zoom account was not found for this user.** This error is thrown if you added a user in your account but the user did not accept the invitation on time and the invitation expired - making the `userId` invalid.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rate-limits/\)](#).

## ### List meeting templates

- **Method:** GET- **Path:** /users/{userId}/meeting\_templates



- **Tags:** Templates

List available [meeting templates](https://support.zoom.us/hc/en-us/articles/360036559151-Meeting-templates) for a user. For user-level apps, pass [the `me` value](/docs/api/rest/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter.

**Prerequisites:**

- Host user must have a Zoom Meetings Basic license or higher.

[Learn more about creating and managing meeting templates](https://support.zoom.com/hc/en/article?id=zm\_kb&sysparm\_article=KB0067229).

**Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
`meeting:read`, `meeting:read:admin`

**Granular Scopes**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
`meeting:read:list\_templates`, `meeting:read:list\_templates:admin`

**Rate Limit Label**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **MEDIUM**

#### Responses

##### Status: 200 **HTTP Status Code:** 200 **OK**

##### Content-Type: application/json

- **templates**

array

**Items:**

- **id**

string — The template ID.

- **name**

string — The template name.

- **type**

integer — The template type: 1: Meeting template 2: Admin meeting template

- **total\_records**

integer — Total records found for this request.

**Example:**

```json

```
{
  "templates": [
    {
      "id": "AdxbhxCzKgSiWAw",
      "name": "My meeting template",
      "type": 1
    }
  ],
  "total_records": 1
}
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 3161 **Meeting hosting and scheduling capabilities are not allowed for your user account.**

Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 1001 **User does not exist: {userId}.**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [rate limits](/docs/api/rest/rate-limits/).

Create a meeting template from an existing meeting

- **Method:** POST

- **Path:** /users/{userId}/meeting_templates

- **Tags:** Templates

Create a meeting template from an existing meeting.

****Prerequisites****

- Host user must have a Zoom Meetings Basic license or higher.
- You can only create up to 40 meeting templates.

[Learn more about creating and managing meeting templates](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0067229).

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
 `meeting:write:admin`, `meeting:write`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
 `meeting:write:template`, `meeting:write:template:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** `MEDIUM`

Request Body

Content-Type: application/json

****All of:****

- ****`meeting\_id`****

`integer`, format: `int64` — The meeting ID - the meeting number in long (int64) format.

- ****`name`****

`string` — The template name.

- ****`overwrite`****

`boolean`, default: `false` — Overwrite an existing meeting template if the template is created from same existing meeting.

- ****`save\_recurrence`****

`boolean`, default: `false` — If the field is set to `true`, the recurrence meeting template will be saved as the scheduled meeting.

****Example:****

```
```json
{
 "meeting_id": 96172769962,
 "name": "My Meeting Template",
 "save_recurrence": false,
 "overwrite": false
},
```,
```

Responses

Status: 201 **HTTP Status Code:** 201 Meeting template created.

Content-Type: application/json

****All of:****

- ****`id`****

`string` — The template ID.

- ****`name`****

`string` — The template name.

****Example:****

```
```json
{
 "id": "AdxbhxCzKgSiWAw",
 "name": "My Meeting Template"
},
```,
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **You can only create up to 40 meeting templates.**
Error Code: 3001 **Meeting does not exist:** {meetingId} **Error Code:** 3161 **Meeting hosting and scheduling capabilities are not**

allowed for your user account. \
 Error Code: \`3000\` \
 Cannot access webinar information. \
 Error Code: \`3000\` \
 Meeting template name already exists: {templateName}. \

Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`1001\` \
 User does not exist. \

Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \[rate limits]\(\/docs/api/rest/rate-limits/).

List tracking fields

- **Method:** `GET`
 - **Path:** `/tracking\_fields`
 - **Tags:** Tracking Field

List all the [tracking fields](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields) on your Zoom account. Tracking fields let you analyze usage by various fields within an organization.

Prerequisites:

- A Business, Education, API or higher plan.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `tracking\_fields:read:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `tracking\_field:read:list\_tracking\_fields:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **MEDIUM**

Responses

Status: 200 **HTTP Status Code:** \`200\` List of Tracking Fields returned.

Content-Type: application/json

All of:

- **total_records**
 `integer` — The number of all records available across pages.

- **tracking_fields**
 `array` — Array of tracking fields.

Items:

- **field**
 `string` — Label or name for the tracking field.

- **id**
 `string` — Tracking field's ID.

- **recommended_values**
 `array` — Array of recommended values

Items:

`string`

- **required**
 `boolean` — Tracking field required.

- **visible**
 `boolean` — Tracking field visible.

Example:

```
```json
{
 "total_records": 1,
 "tracking_fields": [
 {
```

```

 "id": "a32CJji-weJ92",
 "field": "field1",
 "recommended_values": [
 "value1"
],
 "required": false,
 "visible": true
 }
]
}

```

##### Status: 429 `\**HTTP Status Code:\** \`429\`` `\<br> Too Many Requests. For more information, see \[rate limits]\(/docs/api/rest/rate-limits/)`.

### ### Create a tracking field

```

- **Method:** `POST`
- **Path:** `/tracking_fields`
- **Tags:** Tracking Field

```

Use this API to create a new [tracking field](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields). Tracking fields let you analyze usage by various fields within an organization. When scheduling a meeting, tracking fields will be included in the meeting options.

#### **\*\*Prerequisites:\*\***

- A Business, Education, API or higher plan.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
``tracking_fields:write:admin``

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
``tracking_field:write:tracking_field:admin``

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** ``LIGHT``

### #### Request Body

##### Content-Type: application/json

```

- **`field`**

 `string` — Label/ Name for the tracking field.

- **`recommended_values`**

 `array` — Array of recommended values

 Items:

 `string`

- **`required`**

 `boolean` — Tracking Field Required

- **`visible`**

 `boolean` — Tracking Field Visible

```

#### **\*\*Example:\*\***

```

```json
{
  "field": "field1",
  "recommended_values": [
    "value1"
  ],
  "required": false,
  "visible": true
}

```

Responses

Status: 201 `\**HTTP Status Code:\** \`201\`` Tracking Field created

Content-Type: application/json

****All of:****

- ****`id`****

`string` — Tracking Field ID

*** **`field`****

`string` — Label/ Name for the tracking field.

*** **`recommended\_values`****

`array` — Array of recommended values

****Items:****

`string`

*** **`required`****

`boolean` — Tracking Field Required

*** **`visible`****

`boolean` — Tracking Field Visible

****Example:****

```json

```
{
 "id": "a32CJji-weJ92",
 "field": "field1",
 "recommended_values": [
 "value1"
],
 "required": false,
 "visible": true
},
{
 "id": "a32CJji-weJ92",
 "field": "field2",
 "recommended_values": [
 "value2"
],
 "required": true,
 "visible": false
}
```

##### Status: 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)."**

### Get a tracking field

- **\*\*Method:\*\*** `GET`

- **\*\*Path:\*\*** `/tracking\_fields/{fieldId}`

- **\*\*Tags:\*\*** Tracking Field

Use this API to return information about a [tracking field](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields).

**\*\*Prerequisites:\*\***

- A Business, Education, API or higher plan.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***

`tracking\_fields:read:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***

`tracking\_field:read:tracking\_field:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

##### Responses

##### Status: 200 **\*\*HTTP Status Code:\*\*** 200 **\*\*Tracking field object returned.**

##### Content-Type: application/json

- **\*\*`field`\*\***

`string` — Label or name for the tracking field.

- **\*\*`id`\*\***

`string` — Tracking field ID.

- **\*\*`recommended\_values`\*\***

`array` — Array of recommended values.

**\*\*Items:\*\***

`string`

- **\*\*`required`\*\***

`boolean` — Tracking field required.

- **\*\*`visible`\*\***

`boolean` — Tracking field visible.

**\*\*Example:\*\***

```
```json
{
  "id": "a32CJji-weJ92",
  "field": "field1",
  "recommended_values": [
    "value1"
  ],
  "required": false,
  "visible": true
},
```,
```

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 5110  
Tracking field does not exist: {fieldId}.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

### Delete a tracking field

- **\*\*Method:\*\*** `DELETE`  
- **\*\*Path:\*\*** `/tracking\_fields/{fieldId}`  
- **\*\*Tags:\*\*** Tracking Field

Delete a [tracking field](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields).

**\*\*Prerequisites:\*\***

- A Business, Education, API or higher plan.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`tracking\_fields:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`tracking\_field:delete:tracking\_field:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

#### Responses

##### Status: 204 **HTTP Status Code:** 204 **Tracking Field deleted.**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 5110  
Tracking field does not exist: {fieldId}.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]\(/docs/api/rest/rate-limits/\)](#).

### Update a tracking field

- **\*\*Method:\*\*** `PATCH`  
- **\*\*Path:\*\*** `/tracking\_fields/{fieldId}`  
- **\*\*Tags:\*\*** Tracking Field

Update a [tracking field](https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields).

**\*\*Prerequisites:\*\***

- A Business, Education, API or higher plan.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`tracking\_fields:write:admin`

```

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`tracking_field:update:tracking_field:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Request Body

Content-Type: application/json

- **`field`**

 `string` — Label or name for the tracking field.

- **`recommended_values`**

 `array` — Array of recommended values.

 Items:

 `string`

- **`required`**

 `boolean` — Tracking field required.

- **`visible`**

 `boolean` — Tracking field visible.

Example:

```json
{
  "field": "field1",
  "recommended_values": [
    "value1"
  ],
  "required": false,
  "visible": true
}
```

Responses

Status: 204 `HTTP Status Code: 204` Tracking field updated.

Status: 400 `HTTP Status Code: 400`
 Bad Request `Error Code: 200`

Tracking field {field} already exists.

Status: 404 `HTTP Status Code: 404`
 Not Found `Error Code: 5110`

Tracking field does not exist: {fieldId}.

Status: 429 `HTTP Status Code: 429`
 Too Many Requests. For more information, see \
[rate limits](/docs/api/rest/rate-limits/).

Delete a live webinar message

- **Method:** `DELETE`
- **Path:** `/live_webinars/{webinarId}/chat/messages/{messageId}`
- **Tags:** Webinars

Deletes a message in a live webinar based on ID.

Prerequisites:

- Have Zoom enable the DLP for the in-meeting chat feature to use this API.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`webinar:write`,`webinar:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`webinar:delete:live_webinar_chat_message`,`webinar:delete:live_webinar_chat_message:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM`

Responses

Status: 204 `HTTP Status Code: 204` Webinar chat message deleted.

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` No permission. `Error Code: 300` DLP is not enabled on this account.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` Webinar does not exist: {webinarId}.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests`. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Get webinar absentees

**Method:** GET  
**Path:** /past\_webinars/{webinarId}/absentees  
**Tags:** Webinars

List absentees of a webinar.

#### Prerequisites

A Pro or higher plan with a [Webinar plan](<https://zoom.us/webinar>) add-on.

**Scopes**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
 `webinar:read:admin`, `webinar:read`

**Granular Scopes**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
 `webinar:read:list\_absentees`, `webinar:read:list\_absentees:admin`

**Rate Limit Label**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **HEAVY**

#### Responses

##### Status: 200 `HTTP Status Code: 200` Success. `Error Code: 200` Webinar plan subscription is missing. Enable webinar for this user once the subscription is added:{userId}.

##### Content-Type: application/json

#### All of:

**next\_page\_token**

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

**page\_count**

`integer` — The number of pages returned for the request made.

**page\_number**

`integer`, default: 1 — `Deprecated.` This field is deprecated. We will no longer support this field in a future release. Instead, use the `next_page_token` for pagination.

**page\_size**

`integer`, default: 30 — The number of records returned with a single API call.

**total\_records**

`integer` — The total number of all the records available across pages.

**registrants**

`array` — List of registrant objects.

**Items:**

**All of:**

**id**

`string` — Registrant ID.

**All of:**

**email** (required)

`string`, format: email — The registrant's email address. See `[Email address display rules]` (<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules>) for return value details.



```

- **`first_name` (required)**

 `string` — The registrant's first name.

- **`address`**

 `string` — The registrant's address.

- **`city`**

 `string` — The registrant's city.

- **`comments`**

 `string` — The registrant's questions and comments.

- **`country`**

 `string` — The registrant's two-letter ISO \[country code]\
(https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

- **`custom_questions`**

 `array` — Information about custom questions.

 Items:

 - **`title`**

 `string` — The title of the custom question.

 - **`value`**

 `string` — The custom question's response value. This has a limit of 128 characters.

- **`industry`**

 `string` — The registrant's industry.

- **`job_title`**

 `string` — The registrant's job title.

- **`last_name`**

 `string` — The registrant's last name.

- **`no_of_employees`**

 `string`, possible values: `""`, "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ * \More than 10,000\

- **`org`**

 `string` — The registrant's organization.

- **`phone`**

 `string` — The registrant's phone number.

- **`purchasing_time_frame`**

 `string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No timeframe" — The registrant's purchasing time frame. * \Within a month\ * \1-3 months\ * \4-6 months\ * \More than 6 months\ * \No timeframe\

- **`role_in_purchase_process`**

 `string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" — The registrant's role in the purchase process. * \Decision Maker\ * \Evaluator/Recommender\ * \Influencer\ * \Not involved\

- **`state`**

 `string` — The registrant's state or province.

- **`status`**

```

`string`, possible values: `"approved", "denied", "pending"` — The registrant's status. `\*` `approved` - Registrant is approved. `\*` `denied` - Registrant is denied. `\*` `pending` - Registrant is waiting for approval.

- **zip**

`string` — The registrant's ZIP or postal code.

**create\_time**

`string`, format: `date-time` — The time when the registrant registered.

**join\_url**

`string`, format: `string` — The URL that an approved registrant can use to join the meeting or webinar.

**status**

`string` — The status of the registrant's registration. `approved` - User has been successfully approved for the webinar. `pending` - The registration is still pending. `denied` - User has been denied from joining the webinar.

**Example:**

```json

```
{
  "next_page_token": "w7587w4eiyfsudgf",
  "page_count": 1,
  "page_size": 30,
  "total_records": 20,
  "registrants": [
    {
      "id": "9tboDiHUQAeOnbmudzWa5g",
      "address": "1800 Amphibious Blvd.",
      "city": "Mountain View",
      "comments": "Looking forward to the discussion.",
      "country": "US",
      "custom_questions": [
        {
          "title": "What do you hope to learn from this?",
          "value": "Look forward to learning how you come up with new recipes and what other services you offer."
        }
      ],
      "email": "jchill@example.com",
      "first_name": "Jill",
      "industry": "Food",
      "job_title": "Chef",
      "last_name": "Chill",
      "no_of_employees": "1-20",
      "org": "Cooking Org",
      "phone": "5550100",
      "purchasing_time_frame": "1-3 months",
      "role_in_purchase_process": "Influencer",
      "state": "CA",
      "status": "approved",
      "zip": "94045",
      "create_time": "2022-03-22T05:59:09Z",
      "join_url": "https://example.com/j/11111"
    }
  ]
}
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **The request could not be completed because you have provided an invalid occurrence ID: {occurrenceId}.**

 Error Code: 1010 **User does not belong to this account: {accountId}.**

 Error Code: 3000 **This webinar doesn't have registration required: {webinarUUID}.**

 Error Code: 200 **No permission.**

Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Webinar {webinarUUID} not found or expired.**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rate-limits/).**

List past webinar instances

```
- **Method:** `GET`
- **Path:** `/past_webinars/{webinarId}/instances`
- **Tags:** Webinars
```

List past webinar instances.

Prerequisites

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

Scopes(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `webinar:read:admin`,`webinar:read`

Granular Scopes(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
 `webinar:read:list\_past\_instances`,`webinar:read:list\_past\_instances:admin`

Rate Limit Label(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

Responses

Status: 200 **HTTP Status Code:** 200 List of past webinar instances returned.

Content-Type: application/json

All of:

- **webinars**

array — List of ended webinar instances.

Items:

All of:

- **start_time**

string, format: `date-time` — Start time.

- **uuid**

string — Webinar UUID.

Example:

```
``json
{
  "webinars": [
    {
      "start_time": "2022-03-26T06:44:14Z",
      "uuid": "Bznyg8KZTdCVbQxvS/oZ7w=="
    }
  ]
}
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 Invalid webinar ID. **Error Code:** 200 No permission.

Status: 404 **HTTP Status Code:** 404 **Not Found**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests**. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

List webinar participants

```
- **Method:** `GET`
- **Path:** `/past_webinars/{webinarId}/participants`
- **Tags:** Webinars
```

Retrieve a list of all the participants who attended a webinar hosted in the past.

Prerequisites:

- A Pro or higher plan with a webinar add-on.

NOTE: After meetings with hundreds of participants, the attendance data takes some time to be generated. If you receive a duration of 0 for users' time in the meeting, you may have called the endpoint before the data is fully processed. Implement a short delay or retry logic before fetching participant data.

Scopes(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):

```
`webinar:read:admin`,`webinar:read`
```

```
**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
`webinar:read:list_past_participants:admin`,`webinar:read:list_past_participants`
```

```
**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `MEDIUM`
```

Responses

```
##### Status: 200 `HTTP Status Code:` `200` `OK` Participants list returned.
```

```
##### Content-Type: application/json
```

```
- **`next_page_token`**
```

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

```
- **`page_count`**
```

`integer` — The number of pages returned for this request.

```
- **`page_size`**
```

`integer`, default: `30` — The total number of records returned from a single API call.

```
- **`participants`**
```

`array` — Array of webinar participant objects.

```
**Items:**
```

```
- **`duration`**
```

`integer` — Participant duration, in seconds, calculated by subtracting the `leave\_time` from the `join\_time` for the `user\_id`. If the participant leaves and rejoins the same meeting, they will be assigned a different `user\_id` and Zoom displays their new duration in a separate object. Note that because of this, the duration may not reflect the total time the user was in the meeting.

```
- **`failover`**
```

`boolean` — Whether failover occurred during the webinar.

```
- **`id`**
```

`string` — The participant's unique identifier.

```
- **`internal_user`**
```

`boolean`, default: `false` — Whether the webinar participant is an internal user.

```
- **`join_time`**
```

`string`, format: `date-time` — The participant's join time.

```
- **`leave_time`**
```

`string`, format: `date-time` — The participant's leave time.

```
- **`name`**
```

`string` — The participant's name.

```
- **`registrant_id`**
```

`string` — The participant's unique registrant ID. This field only returns if you pass the `registrant\_id` value for the `include\_fields` query parameter. This field does not return if the `type` query parameter is the `live` value.

```
- **`status`**
```

`string`, possible values: `in\_meeting`, `in\_waiting\_room` — The participant's status. `in\_meeting` - In a meeting. `in\_waiting\_room` - In a waiting room.

```
- **`user_email`**
```

`string`, format: `email` — Email address of the participant. If the participant is `not` part of the host's account, this returns an empty string value, with some exceptions. See [Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for details.

- ****`user\_id`****

`string` — The participant's ID. This ID is assigned to the participant upon joining the webinar and is only valid for that webinar.

- ****`total\_records`****

`integer` — The total number of records available across all pages.

****Example:****

```
```json
{
 "next_page_token": "Tva2CuIdTgsv8wAnhyAdU3m06Y2HuLQt1h3",
 "page_count": 1,
 "page_size": 30,
 "participants": [
 {
 "id": "30R7kT7bTIKSNUFEuH_Qlg",
 "name": "Jill Chill",
 "user_id": "ABCDEF123456",
 "registrant_id": "_f08HhPJS82MIVLuuFaJPg",
 "user_email": "jchill@example.com",
 "join_time": "2019-02-01T12:34:12.66Z",
 "leave_time": "2019-02-01T12:54:12.66Z",
 "duration": 20,
 "failover": false,
 "status": "in_meeting",
 "internal_user": false
 }
],
 "total_records": 1
},
```
```

Status: 400 **`HTTP Status Code`**: **`400`** **`Bad Request`** **`Error Code`**: **`200`** **`No permission.`** **`Error Code`**: **`300`** **`The next page token is invalid or expired.`** **`Error Code`**: **`200`** **`Only available for Paid or ZMP account: {accountId}.`**

Status: 404 **`HTTP Status Code`**: **`404`** **`Not Found`** **`Error Code`**: **`3001`** **`Webinar does not exist.`**

Status: 429 **`HTTP Status Code`**: **`429`** **`Too Many Requests.`** For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

List past webinar poll results

- ****Method:**** **`GET`**
 - ****Path:**** **`/past\_webinars/{webinarId}/polls`**
 - ****Tags:**** **Webinars**

The polling feature for webinar lets you create single-choice or multiple-choice polling questions for your webinars. This API endpoint retrieves the results for webinar polls of a specific webinar.

****Prerequisites:****

- **[Webinar license](https://zoom.us/webinar)**

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`webinar:read:admin`,`webinar:read`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`webinar:read:list\_past\_polls`,`webinar:read:list\_past\_polls:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** **`MEDIUM`**

Responses

Status: 200 **`HTTP Status Code`**: **`200`** **`OK`** **`Polls returned successfully.`**

Content-Type: application/json

- ****`id`****

`integer`, format: **`int64`** — Webinar ID in **`long`** format, represented as int64 data type in JSON, also known as the webinar number.

- ****`questions`****

```

`array`

**Items:**

- **`email`**

  `string` — Email address of the user who submitted answers to the poll. If the participant is
  \**not\** part of the host's account, this returns an empty string value, with some exceptions. See \
  [Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-
  display-rules) for details.

- **`name`**

  `string` — Name of the user who submitted answers to the poll. If the \`anonymous\` option is enabled
  for a poll, the participant's polling information will be kept anonymous and the value of \`name\` field
  will be \`Anonymous Attendee\`.

- **`question_details`**

  `array`

  **Items:**

  - **`answer`**

    `string` — Answer submitted by the user.

  - **`date_time`**

    `string`, format: `date-time` — Date and time when the answer to the poll was submitted.

  - **`polling_id`**

    `string` — Unique identifier of the poll.

  - **`question`**

    `string` — Question asked during the poll.

- **`start_time`**

  `string`, format: `date-time` — The webinar's start time.

- **`uuid`**

  `string` — Webinar UUID.

**Example:**

```json
{
 "id": 95204914252,
 "questions": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "question_details": [
 {
 "answer": "Good",
 "date_time": "2022-03-26T05:37:59Z",
 "polling_id": "QalIoKWLtJehBJ8e1xRrbQ",
 "question": "How are you?"
 }
]
 }
],
 "start_time": "2022-03-26T05:37:59Z",
 "uuid": "Bznyg8KZTdCVbQxvS/oZ7w=="
}
```

#### Status: 400 \**HTTP Status Code:\** \`400\` \<br> Bad Request \**Error Code:\** \`200\` \<br> No
permission. \<br>

#### Status: 404 \**HTTP Status Code:\** \`404\` \<br> Not Found \**Error Code:\** \`3001\` \<br>
Webinar ID is invalid or not end. \<br>

#### Status: 429 \**HTTP Status Code:\** \`429\` \<br> Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

```

List Q&As of a past webinar

```
- **Method:** `GET`
- **Path:** `/past_webinars/{webinarId}/qa`
- **Tags:** Webinars
```

List the Q&A of a specific past webinar.

The [question and answer (Q&A)](<https://support.zoom.us/hc/en-us/articles/203686015-Getting-Started-with-Question-Answer>) feature for webinars lets attendees ask questions during the webinar and for the panelists, co-hosts and host to answer their questions.

Prerequisites

- [Webinar license](<https://zoom.us/webinar>)

[Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):
`webinar:read:admin`,`webinar:read`

[Granular Scopes](<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):
`webinar:read:past\_qa`,`webinar:read:past\_qa:admin`

[Rate Limit Label](<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

Responses

Status: 200 `\*\*HTTP Status Code:\*\* `200` \*\*OK\*\*` Q&A returned successfully.

Content-Type: application/json

```
- **`id`**
```

``integer`, format: `int64`` — Webinar ID in `\*\*long\*\*` format, represented as int64 data type in JSON, also known as the webinar number.

```
- **`questions`**
```

```
  `array`
```

```
  **Items:**
```

```
  - **`email`**
```

``string`` — Email address of the user. If the participant is `\*\*not\*\*` part of the host's account, this returns an empty string value, with some exceptions. See [Email address display rules](<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules>) for details.

```
  - **`name`**
```

``string`` — Name of the user. If `\`anonymous\`` option is enabled for the Q&A, the participant's information will be kept anonymous and the value of `\`name\`` field will be `\`Anonymous Attendee\``.

```
  - **`question_details`**
```

```
    `array`
```

```
    **Items:**
```

```
    - **`answer`**
```

``string`` — Answer submitted for the question. The value will be 'live answered' if this is a live answer.

```
    - **`question`**
```

``string`` — Question asked during the Q&A.

```
- **`start_time`**
```

``string`, format: `date-time`` — The webinar's start time.

```
- **`uuid`**
```

``string`` — Webinar UUID.

Example:

```
```json
{
 "id": 95204914252,
```

```

"questions": [
 {
 "email": "jchill@example.com",
 "name": "Jill Chill",
 "question_details": [
 {
 "answer": "Good",
 "question": "How are you?"
 }
]
 }
],
"start_time": "2022-03-26T06:44:14Z",
"uuid": "Bznyg8KZTdCVbQxvS/oZ7w=="
},
{
 //

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar ID is invalid or not end.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### ### List webinar templates

```

- Method: GET
- Path: /users/{userId}/webinar_templates
- Tags: Webinars

```

Display a list of a user's `[webinar templates]` (<https://support.zoom.us/hc/en-us/articles/115001079746-Webinar-Templates>). For user-level apps, pass `[the 'me' value]` ([/docs/api-reference/using-zoom-apis#mekeyword](https://developers.zoom.us/docs/api-reference/using-zoom-apis#mekeyword)) instead of the `'userId'` parameter. When you schedule a webinar, save the settings for that webinar as a template for scheduling future webinars. To use a template when scheduling a webinar, use the `'id'` value in this API response in the `'template_id'` field of the `[Create a webinar]` ([/docs/api-reference/zoom-api/methods#operation/webinarCreate](https://developers.zoom.us/docs/api-reference/zoom-api/methods#operation/webinarCreate)) API. **Prerequisites:** A Pro or a higher account with the `[Zoom Webinar plan]` (<https://zoom.us/pricing/webinar>).

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read`, `webinar:read:admin`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:list_templates`, `webinar:read:list_templates:admin`

### ### Responses

##### Status: 200 `HTTP Status Code: 200` `OK` List of existing templates returned.

##### Content-Type: application/json

```

- templates
 array — Information about the webinar templates.
 Items:
 - id
 string — The webinar template's ID.
 - name
 string — The webinar template's name.
 - type
 integer — The webinar template type. 1: Webinar template 2: Admin webinar template
- total_records
 integer — The total number of records returned.

```

**Example:**

```

{
 "templates": [
 {

```



```

 "id": "ull6574eur",
 "name": "Weekly Meeting Template",
 "type": 1
 }
],
"total_records": 1
}

```

##### Status: 400 `\*\*HTTP Status Code:\*\* \400\` `\<br> Bad Request \*\*Error Code:\*\* \200\` `\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br> \*\*Error Code:\*\* \200\` `\<br> No permission. \<br> \*\*Error Code:\*\* \300\` `\<br> You can only create up to 40 webinar templates. \<br> \*\*Error Code:\*\* \3000\` `\<br> Webinar template name already exists {name}.` `\<br>`

##### Status: 404 `\*\*HTTP Status Code:\*\* \404\` `\<br> Not Found \*\*Error Code:\*\* \1001\` `\<br> User does not exist: {userId}.` `\<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \429\` `\<br> Too Many Requests For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).`

### ### Create a webinar template

```

- **Method:** `POST`
- **Path:** `/users/{userId}/webinar_templates`
- **Tags:** Webinars

```

Create a webinar template from an existing webinar.

#### \*\*Prerequisites\*\*

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write:admin`, `webinar:write`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write:template`, `webinar:write:template:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

#### #### Request Body

##### Content-Type: application/json

#### \*\*All of:\*\*

- **\*\*`name`\*\***

``string`` — The webinar template's name.

- **\*\*`overwrite`\*\***

``boolean``, default: ``false`` — Overwrite an existing webinar template if the template is created from same existing webinar.

- **\*\*`save\_recurrence`\*\***

``boolean``, default: ``false`` — If the field is set to true, the recurrence webinar template will be saved as the scheduled webinar.

- **\*\*`webinar\_id`\*\***

``integer``, format: ``int64`` — The webinar ID in long (int64) format.

#### \*\*Example:\*\*

```

```json
{
  "webinar_id": 96172769962,
  "name": "Weekly Meeting Template",
  "save_recurrence": false,
  "overwrite": false
}

```

Responses

Status: 201 `\*\*HTTP Status Code:\*\* \201\` Webinar template created.

Content-Type: application/json

****All of:****

- ****`id`****

`string` — The webinar template's ID.

- ****`name`****

`string` — The webinar template's name.

****Example:****

```json

```
{
 "id": "ull6574eur",
 "name": "Weekly Meeting Template"
}
```

##### Status: 400 **\*\*HTTP Status Code:\*\*** `400` **\*\*Error Code:\*\*** `200` **\*\*Error Message:\*\*** Bad Request **\*\*Error Code:\*\*** `200` **\*\*Error Message:\*\*** Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. **\*\*Error Code:\*\*** `300` **\*\*Error Message:\*\*** You can only create up to 40 webinar templates. **\*\*Error Code:\*\*** `3000` **\*\*Error Message:\*\*** Cannot access meeting info. **\*\*Error Code:\*\*** `3000` **\*\*Error Message:\*\*** Webinar template name already exists: {templateName}. **\*\*Error Code:\*\*** `200` **\*\*Error Message:\*\*** No permission.

##### Status: 404 **\*\*HTTP Status Code:\*\*** `404` **\*\*Error Code:\*\*** `1001` **\*\*Error Message:\*\*** Not Found **\*\*Error Code:\*\*** `1001` **\*\*Error Message:\*\*** User does not exist: {userId}.

##### Status: 429 **\*\*HTTP Status Code:\*\*** `429` **\*\*Error Code:\*\*** **\*\*Error Message:\*\*** Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

### List webinars

- **\*\*Method:\*\*** `GET`  
- **\*\*Path:\*\*** `/users/{userId}/webinars`  
- **\*\*Tags:\*\*** Webinars

List all the webinars scheduled by or on behalf a webinar host. For user-level apps, pass [the `me` value](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#the-me-keyword) instead of the `userId` parameter.

Zoom users with a [webinar plan](https://zoom.us/webinar) have access to creating and managing webinars. Webinars let a host broadcast a Zoom meeting to up to 10,000 attendees.

**\*\*Note\*\*** This API only returns a user's [unexpired webinars](https://support.zoom.us/hc/en-us/articles/201362373-Meeting-ID#h\_c73f9b08-c1c0-4a1a-b538-e01ebb98e844).

**\*\*Prerequisites\*\***

- A Pro or higher plan with the webinar add-on.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:read:admin`, `webinar:read`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:read:list\_webinars`, `webinar:read:list\_webinars:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

#### Responses

##### Status: 200 **\*\*HTTP Status Code:\*\*** `200` **\*\*Error Code:\*\*** **\*\*Error Message:\*\*** List of webinar objects returned.

##### Content-Type: application/json

**\*\*All of:\*\***

- **\*\*`next\_page\_token`\*\***

`string` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **\*\*`page\_count`\*\***

`integer` — The number of pages returned for the request made.

- **page\_number**

`integer`, default: `1` — `Deprecated` We will no longer support this field in a future release. Instead, use the `next_page_token` for pagination.

- **page\_size**

`integer`, default: `30` — The number of records returned with a single API call.

- **total\_records**

`integer` — The total number of all the records available across pages.

**webinars**

`array` — List of webinar objects.

**Items:**

**All of:**

- **agenda**

`string` — Webinar description. The agenda length gets truncated to 250 characters when you list all webinars for a user. To view the complete agenda, retrieve details for a single webinar, use the `Get a webinar` API.

- **created\_at**

`string`, format: `date-time` — The webinar's creation time.

- **duration**

`integer` — The webinar's duration, in minutes.

- **host\_id**

`string` — The host's ID.

- **id**

`integer`, format: `int64` — The webinar ID.

- **is\_simulive**

`boolean` — Whether the webinar is `simulive`.

- **join\_url**

`string` — The URL to join the webinar.

- **start\_time**

`string`, format: `date-time` — The webinar's start time.

- **timezone**

`string` — The webinar's `timezone` (<https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#timezones>).

- **topic**

`string` — The webinar's topic.

- **type**

`integer`, possible values: `5`, `6`, `9`, default: `5` — The webinar type. `5` - A webinar. `6` - A recurring webinar without a fixed time. `9` - A recurring webinar with a fixed time.

- **uuid**

`string` — The webinar's universally unique identifier (UUID). Each webinar instance generates a webinar UUID.

**Example:**

`json`

```
{
 "next_page_token": "w7587w4eiyfsudgf",
 "page_count": 1,
```

```

"page_size": 30,
"total_records": 20,
"webinars": [
 {
 "agenda": "Learn more about Zoom APIs",
 "created_at": "2021-07-01T22:00:00Z",
 "duration": 60,
 "host_id": "x1yCzABCDEFg23HiJKl4mN",
 "id": 1234567890,
 "join_url": "https://example.com/j/11111",
 "start_time": "2021-07-13T21:00:00Z",
 "timezone": "America/Los_Angeles",
 "topic": "My Webinar",
 "type": 9,
 "uuid": "4444AAAiAAAAAiAiAiAi==",
 "is_simulive": true
 }
]
},

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 1001` `User does not exist: {userId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests` For more information, see `[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### ### Create a webinar

```

- Method: POST
- Path: /users/{userId}/webinars
- Tags: Webinars

```

Schedule a webinar for a user who is a webinar host. For user-level apps, pass `[the 'me' value](/docs/api/using-zoom-apis/#the-me-keyword)` instead of the `userId` parameter.

Webinars allow a host to broadcast a Zoom meeting to up to 10,000 attendees.

**Rate limit** Up to a maximum of **100** requests per day. The rate limit is applied to the `userId` of the **webinar host** used to make the request.

#### **Prerequisites**

- A Pro or higher plan with a `[Webinar plan](https://zoom.us/webinar)` add-on.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `webinar:write`, `webinar:write:admin`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `webinar:write:webinar`, `webinar:write:webinar:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

### #### Request Body

##### Content-Type: application/json

- **agenda**

`string` — Webinar description.

- **default\_passcode**

`boolean`, default: `true` — Determines whether to automatically generate a passcode for the webinar when no passcode is provided and the user's `Passcode` setting is enabled. Defaults to `true`. When set to `false`, webinars will only have a passcode if one is explicitly provided.

- **duration**

`integer` — Webinar duration, in minutes. Used for scheduled webinars only.

- **is\_simulive**

`boolean` — Whether to set the webinar to simulive.

- **password**

``string`` — The webinar passcode. By default, it can be up to 10 characters in length and may contain alphanumeric characters as well as special characters like !, @, #, and others. ``Note`` - If the account owner or administrator has configured `[Passcode Requirement]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0063160#h\\_a427384b-e383-4f80-864d-794bf0a37604](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0063160#h_a427384b-e383-4f80-864d-794bf0a37604)), the passcode ``must`` meet those requirements. You can retrieve the requirements using the `[Get user settings]` (`/docs/api/users/#tag/users/GET/users/{userId}/settings`) API or the `[Get account settings]` (`/docs/api/accounts/#tag/accounts/GET/accounts/{accountId}/settings`) API. - If the ``Passcode`` user setting is enabled and ``default_passcode`` is not explicitly set to ``false``, a passcode will be automatically generated when one is not provided. - If the ``Passcode`` setting is enabled and `[locked]` (<https://support.zoom.us/hc/en-us/articles/115005269866-Using-Tiered-Settings#locked>) for the user, a passcode will be automatically generated when one is not provided.

- ``record_file_id``

``string`` — The previously recorded file's ID for ``simulive``.

- ``recurrence``

``object`` — Recurrence object. Use this object only for a webinar of type ``9``, a recurring webinar with fixed time.

- ``type`` (required)

``integer``, possible values: ``1, 2, 3`` — Recurrence webinar types. ``1`` - Daily. ``2`` - Weekly. ``3`` - Monthly.

- ``end_date_time``

``string``, format: ``date-time`` — Select a date when the webinar will recur before it is canceled. Should be in UTC time, such as ``2017-11-25T12:00:00Z``. Cannot be used with ``end_times``.

- ``end_times``

``integer``, default: ``1`` — Select how many times the webinar will recur before it is canceled. The maximum number of recurring is 60. Cannot be used with ``end_date_time``.

- ``monthly_day``

``integer`` — Use this field ``only`` if you're scheduling a recurring webinar of type ``3`` to state which day in a month the webinar should recur. The value range is from 1 to 31. For instance, if you would like the webinar to recur on 23rd of each month, provide ``23`` as the value of this field and ``1`` as the value of the ``repeat_interval`` field. Instead, if you would like the webinar to recur once every three months, on 23rd of the month, change the value of the ``repeat_interval`` field to ``3``.

- ``monthly_week``

``integer``, possible values: ``-1, 1, 2, 3, 4`` — Use this field ``only`` if you're scheduling a recurring webinar of type ``3`` to state the week of the month when the webinar should recur. If you use this field, ``you`` must also use the ``monthly_week_day`` field to state the day of the week when the webinar should recur. ``-1`` - Last week of the month. ``1`` - First week of the month. ``2`` - Second week of the month. ``3`` - Third week of the month. ``4`` - Fourth week of the month.

- ``monthly_week_day``

``integer``, possible values: ``1, 2, 3, 4, 5, 6, 7`` — Use this field ``only`` if you're scheduling a recurring webinar of type ``3`` to state a specific day in a week when the monthly webinar should recur. To use this field, you must also use the ``monthly_week`` field. ``1`` - Sunday. ``2`` - Monday. ``3`` - Tuesday. ``4`` - Wednesday. ``5`` - Thursday. ``6`` - Friday. ``7`` - Saturday.

- ``repeat_interval``

``integer`` — Define the interval when the webinar should recur. For instance, to schedule a webinar that recurs every two months, you must set the value of this field as ``2`` and the value of the ``type`` parameter as ``3``. For a daily webinar, the maximum interval you can set is ``90`` days. For a weekly webinar, the maximum interval that you can set is ``12`` weeks. For a monthly webinar, the maximum interval that you can set is ``3`` months.

- ``weekly_days``

``string`` — Use this field ``only`` if you're scheduling a recurring webinar of type ``2`` to state which day(s) of the week the webinar should repeat. The value for this field could be a number between ``1`` to ``7`` in string format. For instance, if the webinar should recur on Sunday, provide ``1`` as the value of this field. ``Note``: If you would like the webinar to occur on multiple days of a week, you should provide comma separated values for this field. For instance, if the webinar should recur on Sundays and Tuesdays, provide ``1,3`` as the value of this field. ``1`` - Sunday. ``2`` - Monday. ``3`` - Tuesday. ``4`` - Wednesday. ``5`` - Thursday. ``6`` - Friday. ``7`` - Saturday.

- ``schedule_for``

``string`` — The email address or user ID of the user to schedule a webinar for.

- `***settings***`

``object`` — Create webinar settings.

- `***add_audio_watermark***`

``boolean`` — Add audio watermark that identifies the participants. Not supported for simulative webinar. If not provided, the default value will be based on the user's setting.

- `***add_watermark***`

``boolean`` — Add watermark that identifies the viewing participant. Not supported for simulative webinar. If not provided, the default value will be based on the user's setting.

- `***additional_data_center_regions***`

``array`` — Add additional webinar `[data center regions]` (<https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars>). Provide this value as an array of `[country codes]` ([/docs/api/references/abbreviations/#countries](https://docs/api/references/abbreviations/#countries)) for the countries available as data center regions in the `[Account Profile]` (<https://zoom.us/account/setting>) interface but have been opted out of in the `[user settings]` (<https://zoom.us/profile>). For example, the data center regions selected in your `[Account Profile]` (<https://zoom.us/account>) are ``Europe``, ``Hong Kong SAR``, ``Australia``, ``India``, ``Japan``, ``China``, ``United States``, and ``Canada``. However, in the `[My Profile]` (<https://zoom.us/profile>) settings, you did ``not`` select ``India`` and ``Japan`` for meeting and webinar traffic routing. To include ``India`` and ``Japan`` as additional data centers, use the `[IN, TY]` value for this field.

`***Items:***`

``string``

- `***allow_host_control_participant_mute_state***`

``boolean`` — Whether to allow the host and cohosts to fully control the mute state of participants. Not supported for simulative webinar. If not provided, the default value will be based on the user's setting. This option cannot be used together with ``request_permission_to_unmute_participants``, only one of the two can be enabled at a time.

- `***allow_multiple_devices***`

``boolean`` — Allow attendees to join from multiple devices.

- `***alternative_host_update_polls***`

``boolean`` — Whether the ``Allow alternative hosts to add or edit polls`` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `***alternative_hosts***`

``string`` — Alternative host emails or IDs. Multiple values separated by comma.

- `***approval_type***`

``integer``, possible values: ``0``, ``1``, ``2``, default: ``2`` — The default value is ``2``. To enable registration required, set the approval type to ``0`` or ``1``. Values include: ``0`` - Automatically approve. ``1`` - Manually approve. ``2`` - No registration required.

- `***attendees_and_panelists_reminder_email_notification***`

``object`` — Send reminder email to attendees and panelists.

- `***enable***`

``boolean`` — ``true`` - Send reminder email to attendees and panelists. ``false`` - Do not send reminder email to attendees and panelists.

- `***type***`

``integer``, possible values: ``0``, ``1``, ``2``, ``3``, ``4``, ``5``, ``6``, ``7`` — ``0`` - No plan. ``1`` - Send 1 hour before webinar. ``2`` - Send 1 day before webinar. ``3`` - Send 1 hour and 1 day before webinar. ``4`` - Send 1 week before webinar. ``5`` - Send 1 hour and 1 week before webinar. ``6`` - Send 1 day and 1 week before webinar. ``7`` - Send 1 hour, 1 day and 1 week before webinar.

- `***audio***`

``string``, possible values: ``both``, ``telephony``, ``voip``, ``thirdParty``, default: ``both`` — Determine how participants can join the audio portion of the meeting.(Not supported for simulative webinar.)

```

- ``audio_conference_info``

`string` — Third party audio conference information.

- ``authentication_domains``

`string` — Meeting authentication domains. This option allows you to specify the rule so that Zoom users whose email address contains a certain domain can join the webinar. You can either provide multiple comma-separated domains, use a wildcard for listing domains, or use both methods.

- ``authentication_option``

`string` — Specify the authentication type for users to join a webinar with \meeting_authentication\ setting set to \true\. The value of this field can be retrieved from the \id\ field within \authentication_options\ array in the response of \[**Get user settings*\] (/docs/api/rest/reference/zoom-api/methods#operation/userSettings) API.

- ``auto_recording``

`string`, possible values: "local", "cloud", "none", default: "none" — Automatic recording. Not supported for simulive webinar. \local\ - Record on local. \cloud\ - Record on cloud. \none\ - Disabled.

- ``close_registration``

`boolean` — Close registration after event date.

- ``contact_email``

`string` — Contact email for registration

- ``contact_name``

`string` — Contact name for registration

- ``email_in_attendee_report``

`boolean` — Whether to include guest's email addresses in webinars' attendee reports.

- ``email_language``

`string` — Set the email language. \en-US\, \de-DE\, \es-ES\, \fr-FR\, \id-ID\, \jp-JP\, \nl-NL\, \pl-PL\, \pt-PT\, \ru-RU\, \tr-TR\, \zh-CN\, \zh-TW\, \ko-KO\, \it-IT\, \vi-VN\.

- ``enable_session_branding``

`boolean` — Whether the **Webinar Session Branding* setting is enabled. This setting lets hosts visually customize a webinar by setting a session background. This also lets hosts set Virtual Background and apply name tags to hosts, alternative hosts, panelists, interpreters, and speakers.

- ``enforce_login``

`boolean` — Only signed-in users can join this meeting. **This field is deprecated and will not be supported in future.** Instead of this field, use the \meeting_authentication\, \authentication_option\, or \authentication_domains\ fields to establish the authentication mechanism for this Webinar.

- ``enforce_login_domains``

`string` — Only signed-in users with specified domains can join meetings. **This field is deprecated and will not be supported in future.** Instead of this field, use the \authentication_domains\ field for this webinar.

- ``follow_up_absentees_email_notification``

`object` — Send follow-up email to absentees.

- ``enable``

`boolean` — * \true\ - Send follow-up email to absentees. * \false\ - Do not send follow-up email to absentees.

- ``type``

`integer`, possible values: \0, 1, 2, 3, 4, 5, 6, 7 — \0\ - No plan. \1\ - Send 1 days after the scheduled end date. \2\ - Send 2 days after the scheduled end date. \3\ - Send 3 days after the scheduled end date. \4\ - Send 4 days after the scheduled end date. \5\ - Send 5 days after the scheduled end date. \6\ - Send 6 days after the scheduled end date. \7\ - Send 7 days after the scheduled end date.

```

```

- follow_up_attendees_email_notification

 `object` — Send follow-up email to attendees.

- enable

 `boolean` — * \true\: Send follow-up email to attendees. * \false\: Do not send follow-up email to attendees.

- type

 `integer`, possible values: \0, 1, 2, 3, 4, 5, 6, 7 — \0\ - No plan. \1\ - Send 1 day after the scheduled end date. \2\ - Send 2 days after the scheduled end date. \3\ - Send 3 days after the scheduled end date. \4\ - Send 4 days after the scheduled end date. \5\ - Send 5 days after the scheduled end date. \6\ - Send 6 days after the scheduled end date. \7\ - Send 7 days after the scheduled end date.

- global_dial_in_countries

 `array` — List of global dial-in countries

 Items:

 `string`

- hd_video

 `boolean`, default: \false\ — Default to HD video. Not supported for simulative webinar.

- hd_video_for_attendees

 `boolean`, default: \false\ — Whether HD video for attendees is enabled. This value defaults to \false\. Not supported for simulative webinar.

- host_video

 `boolean` — Start video when host joins webinar. Not supported for simulative webinar.

- language_interpretation

 `object` — The webinar's \[language interpretation settings]\(https://support.zoom.com/hc/en/article?id=zm\kb\&sysparm_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details. **Note:* This feature is only available for certain Webinar add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will **not* be applied to the webinar. This is not supported for simulative webinars.

 - enable

 `boolean` — Whether to enable \[language interpretation]\(https://support.zoom.com/hc/en/article?id=zm\kb\&sysparm_article=KB0064768) for the webinar. If not provided, the default value will be based on the user's setting.

 - interpreters

 `array` — Information about the webinar's language interpreters.

 Items:

 - email

 `string`, format: \email\ — The interpreter's email address.

 - interpreter_languages

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the \language_interpretation\` object's \languages\` and \custom_languages\` values in the \[**Get user settings**]\(/docs/api/users/#tag/users/GET/users/{userId}/settings) API response. **languages**: System-supported languages include \English\, \Chinese\, \Japanese\, \German\, \French\, \Russian\, \Portuguese\, \Spanish\, and \Korean\. **custom_languages**: User-defined languages added by the user. For example, an interpreter translating between English and French should use \English,French\.

 - languages

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: \US\ (English), \CN\ (Chinese), \JP\ (Japanese), \DE\ (German), \FR\ (French), \RU\ (Russian), \PT\ (Portuguese), \ES\ (Spanish), and \KR\ (Korean). For example, to set an interpreter translating from English to Chinese, use \US,CN\.

 - meeting_authentication

```



``boolean`` — Only `\[Q\&A]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars)` users can join meeting if the value of this field is set to `\`true\``.

- `**`on_demand`**`

``boolean``, default: ``false`` — Make the webinar on-demand. Not supported for simulative webinar.

- `**`panelist_authentication`**`

``boolean`` — Require panelists to authenticate to join. If not provided, the default value will be based on the user's setting.

- `**`panelists_invitation_email_notification`**`

``boolean`` — Send invitation email to panelists. If `\`false\``, do not send invitation email to panelists.

- `**`panelists_video`**`

``boolean`` — Start video when panelists join webinar. Not supported for simulative webinar.

- `**`post_webinar_survey`**`

``boolean`` — Zoom will open a survey page in attendees' browsers after leaving the webinar

- `**`practice_session`**`

``boolean``, default: ``false`` — Enable practice session.

- `**`question_and_answer`**`

``object`` — `\[Q\&A]\(https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.)` for webinar.

- `**`allow_anonymous_questions`**`

``boolean`` — `\* \`true\`` - Allow participants to send questions without providing their name to the host, co-host, and panelists.. `\* \`false\`` - Do not allow anonymous questions.(Not supported for simulative webinar.)

- `**`allow_auto_reply`**`

``boolean`` — If simulative webinar, `\* \`true\`` - allow auto-reply to attendees. `\* \`false\`` - don't allow auto-reply to the attendees.

- `**`allow_submit_questions`**`

``boolean`` — `\* \`true\`` - Allow participants to submit questions. `\* \`false\`` - Do not allow submit questions.

- `**`answer_questions`**`

``string``, possible values: ``"only", "all"`` — Indicate whether you want attendees to be able to view answered questions only or view all questions. `\* \`only\`` - Attendees are able to view answered questions only. `\* \`all\`` - Attendees are able to view all questions submitted in the Q\&A.

- `**`attendees_can_comment`**`

``boolean`` — `\* \`true\`` - Attendees can answer questions or leave a comment in the question thread. `\* \`false\`` - Attendees can not answer questions or leave a comment in the question thread

- `**`attendees_can_upvote`**`

``boolean`` — `\* \`true\`` - Attendees can click the thumbs up button to bring popular questions to the top of the Q\&A window. `\* \`false\`` - Attendees can not click the thumbs up button on questions.

- `**`auto_reply_text`**`

``string`` — If `\allow\_auto\_reply\` = true`, the text to be included in the automatic response.

- `**`enable`**`

``boolean`` — `\* \`true\`` - Enable `\[Q\&A]\(https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.)` for webinar. `\* \`false\`` - Disable Q\&A for webinar. If not provided, the default value will be based on the user's setting.

- `**`registrants_confirmation_email`**`

``boolean`` — Send confirmation email to registrants.

- `**`registrants_email_notification`**`

``boolean`` — Send email notifications to registrants about approval, cancellation, denial of the registration. The value of this field must be set to true in order to use the ``registrants_confirmation_email`` field.

- `**`registrants_restrict_number`**`

``integer``, default: ``0`` — Restrict number of registrants for a webinar. By default, it is set to ``0``. A ``0`` value means that the restriction option is disabled. Provide a number higher than 0 to restrict the webinar registrants by the that number.

- `**`registration_type`**`

``integer``, possible values: ``1, 2, 3``, default: ``1`` — Registration types. Only used for recurring webinars with a fixed time. ``1`` - Attendees register once and can attend any of the webinar sessions. ``2`` - Attendees need to register for each session in order to attend. ``3`` - Attendees register once and can choose one or more sessions to attend.

- `**`request_permission_to_unmute_participants`**`

``boolean``, default: ``false`` — Whether to enable the ``[*]Request permission to unmute participants`` (https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting) setting. Not supported for simulative webinar. This option cannot be used together with ``allow_host_control_participant_mute_state``, only one of the two can be enabled at a time.

- `**`send_1080p_video_to_attendees`**`

``boolean``, default: ``false`` — Whether to always send 1080p video to attendees. This value defaults to ``false``. (Not supported for simulative webinar.)

- `**`show_join_info`**`

``boolean`` — Whether to show the webinar's join information on the registration confirmation page. This setting is only applied to webinars with registration enabled.

- `**`show_share_button`**`

``boolean`` — Show social share buttons on the registration page.

- `**`sign_language_interpretation`**`

``object`` — The webinar's ``[sign language interpretation settings]`` (https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar). Make sure to add the language in the web portal in order to use it in the API. See link for details. ``[*]Note`` If this feature is not enabled on the host's account, this setting will ``[*]not`` be applied to the webinar.

- `**`enable`**`

``boolean`` — Whether to enable ``[sign language interpretation]`` (https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar) for the webinar. If not provided, the default value will be based on the user's setting.

- `**`interpreters`**`

``array`` — Information about the webinar's sign language interpreters.

`**Items**`

- `**`email`**`

``string``, format: ``email`` — The interpreter's email address.

- `**`sign_language`**`

``string`` — The interpreter's sign language. To get this value, use the ``sign_language_interpretation`` object's ``languages`` and ``custom_languages`` values in the ``[*]Get user settings`` (/docs/api/rest/reference/zoom-api/methods#operation/userSettings) API response.

- `**`survey_url`**`

``string`` — Survey URL for post webinar survey.

- `**`simulive_delay_start`**`

``object`` — ``{ "enable": false, "time": 0, "timeunit": "second" }`

- **enable**

`boolean` — Whether simulive need delay playback.

- **time**

`integer` — The time for delayed playback If the time unit is seconds, then the maximum value is 60 and the minimum value is 1. If the time unit is minutes, then the maximum value is 10 and the minimum value is 1.

- **timeunit**

`string`, possible values: `"second"`, `"minute"`, default: `"second"` — The time unit for delayed playback `"second"` - The time unit for delayed playback is seconds. `"minute"` - The time unit for delayed playback is minutes.

- **start\_time**

`string`, format: `date-time` — Webinar start time. We support two formats for `start_time` - local time and GMT. To set time as GMT the format should be `yyyy-MM-dd\T\HH:mm:ssZ`. To set time using a specific timezone, use `yyyy-MM-dd\T\HH:mm:ss\` format and specify the timezone `[ID]` (`/docs/api/references/abbreviations/#timezones`) in the `timezone` field OR leave it blank and the timezone set on your Zoom account will be used. You can also set the time as UTC as the timezone field. The `start_time` should only be used for scheduled and / or recurring webinars with fixed time.

- **template\_id**

`string` — The webinar template ID to schedule a webinar using a `[webinar template]` (<https://support.zoom.us/hc/en-us/articles/115001079746-Webinar-Templates>) or a `[admin webinar template]` (<https://support.zoom.us/hc/en-us/articles/8137753618957-Configuring-admin-webinar-templates>). For a list of webinar templates, use the `[*List webinar templates*]` (`/docs/api/rest/reference/zoom-api/methods#operation/listWebinarTemplates`) API.

- **timezone**

`string` — The timezone to assign to the `start_time` value. This field is only used for scheduled or recurring webinars with a fixed time. For a list of supported timezones and their formats, see our `[timezone list]` (`/docs/api/references/abbreviations/#timezones`).

- **topic**

`string` — The webinar's topic.

- **tracking\_fields**

`array` — Tracking fields.

**Items:**

- **field** (required)

`string` — Tracking fields type.

- **value**

`string` — Tracking fields value.

- **transition\_to\_live**

`boolean` — Whether to transition a simulive webinar to live. The host must be present at the time of transition.

- **type**

`integer`, possible values: `5`, `6`, `9`, default: `5` — Webinar types. `5` - Webinar. `6` - Recurring webinar with no fixed time. `9` - Recurring webinar with a fixed time.

**Example:**

```
```json
{
  "agenda": "My Webinar",
  "duration": 60,
  "password": "123456",
  "default_passcode": true,
  "recurrence": {
    "end_date_time": "2022-04-02T15:59:00Z",
    "end_times": 7,
    "monthly_day": 1,
    "monthly_week": 1,

```

```

    "monthly_week_day": 1,
    "repeat_interval": 1,
    "type": 1,
    "weekly_days": "1"
  },
  "schedule_for": "jchill@example.com",
  "settings": {
    "additional_data_center_regions": [
      "TY"
    ],
    "allow_multiple_devices": true,
    "alternative_hosts": "jchill@example.com;thill@example.com",
    "alternative_host_update_polls": true,
    "approval_type": 0,
    "attendees_and_panelists_reminder_email_notification": {
      "enable": true,
      "type": 0
    },
    "audio": "telephony",
    "audio_conference_info": "test",
    "authentication_domains": "example.com",
    "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
    "auto_recording": "cloud",
    "contact_email": "jchill@example.com",
    "contact_name": "Jill Chill",
    "email_language": "en-US",
    "follow_up_absentees_email_notification": {
      "enable": true,
      "type": 0
    },
    "follow_up_attendees_email_notification": {
      "enable": true,
      "type": 0
    },
    "global_dial_in_countries": [
      "US"
    ],
    "hd_video": false,
    "hd_video_for_attendees": false,
    "host_video": true,
    "language_interpretation": {
      "enable": true,
      "interpreters": [
        {
          "email": "interpreter@example.com",
          "interpreter_languages": "English,French"
        }
      ]
    },
    "sign_language_interpretation": {
      "enable": true,
      "interpreters": [
        {
          "email": "interpreter@example.com",
          "sign_language": "American"
        }
      ]
    },
    "panelist_authentication": true,
    "meeting_authentication": true,
    "add_watermark": true,
    "add_audio_watermark": true,
    "on_demand": false,
    "panelists_invitation_email_notification": true,
    "panelists_video": true,
    "post_webinar_survey": true,
    "practice_session": false,
    "question_and_answer": {
      "allow_submit_questions": true,
      "allow_anonymous_questions": true,
      "answer_questions": "all",
      "attendees_can_comment": true,
      "attendees_can_upvote": true,
      "allow_auto_reply": true,
      "auto_reply_text": "Thank you for your question. We will get back to you shortly.",
      "enable": true
    },
    "registrants_confirmation_email": true,
    "registrants_email_notification": true,
    "registrants_restrict_number": 100,

```

```

    "registration_type": 1,
    "send_1080p_video_to_attendees": false,
    "show_share_button": true,
    "show_join_info": true,
    "survey_url": "https://example.com",
    "enable_session_branding": true,
    "request_permission_to_unmute_participants": true,
    "allow_host_control_participant_mute_state": false,
    "email_in_attendee_report": true
  },
  "start_time": "2022-03-26T06:44:14Z",
  "template_id": "5Cj3ceXoSt06TGOVvIOVPA==",
  "timezone": "America/Los_Angeles",
  "topic": "My Webinar",
  "tracking_fields": [
    {
      "field": "field1",
      "value": "value1"
    }
  ],
  "type": 5,
  "is_simulive": true,
  "record_file_id": "f09340e1-cdc3-4eae-9a74-98f9777ed908",
  "transition_to_live": false,
  "simulive_delay_start": {
    "enable": true,
    "time": 10,
    "timeunit": "second"
  }
}
},

```

Responses

Status: 201 **HTTP Status Code:** \`201\` Webinar created.

Content-Type: application/json

- ***\`agenda\`***

\`string\` — The webinar's agenda.

- ***\`created\_at\`***

\`string\`, format: \`date-time\` — Creation time.

- ***\`creation\_source\`***

\`string\`, possible values: \`"other", "open\_api", "web\_portal"\` — The platform through which the meeting was created. *\`other\` - Created through another platform. *\`open\_api\` - Created through Open API. *\`web\_portal\` - Created through the web portal.

- ***\`duration\`***

\`integer\` — The webinar's duration.

- ***\`encrypted\_passcode\`***

\`string\` — Encrypted passcode for third party endpoints (H323/SIP).

- ***\`h323\_passcode\`***

\`string\` — H.323/SIP room system passcode.

- ***\`host\_email\`***

\`string\`, format: \`email\` — Email address of the meeting host.

- ***\`host\_id\`***

\`string\` — ID of the user set as host of the webinar.

- ***\`id\`***

\`integer\`, format: \`int64\` — Webinar ID in *\`long\`* format, represented as int64 data type in JSON. Also known as the webinar number.

- ***\`is\_simulive\`***

\`boolean\` — Whether the webinar is \`\`simulive\`\`.

- **join_url**

`string` — URL to join the webinar. Only share this URL with the users who should be invited to the webinar.

- **occurrences**

`array` — Array of occurrence objects.

Items:

- **duration**

`integer` — Duration.

- **occurrence_id**

`string` — Occurrence ID: a unique identifier that identifies an occurrence of a recurring webinar. \[Recurring webinars](https://support.zoom.us/hc/en-us/articles/216354763-How-to-Schedule-A-Recurring-Webinar) can have a maximum of 50 occurrences.

- **start_time**

`string`, format: `date-time` — Start time.

- **status**

`string`, possible values: `"available"`, `"deleted"` — Occurrence status. `available` - Available occurrence. `deleted` - Deleted occurrence.

- **password**

`string` — The webinar passcode. By default, it can be up to 10 characters in length and may contain alphanumeric characters as well as special characters such as `!`, `@`, `#`, etc.

- **record_file_id**

`string` — The previously recorded file's ID for `simulive`.

- **recurrence**

`object` — Recurrence object. Use this object only for a webinar of type `9` i.e., a recurring webinar with fixed time.

- **type** (required)

`integer`, possible values: `1`, `2`, `3` — Recurrence webinar types. `1` - Daily. `2` - Weekly. `3` - Monthly.

- **end_date_time**

`string`, format: `date-time` — A date when the webinar will recur before it is canceled. Should be in UTC time, such as `2017-11-25T12:00:00Z`. Can't be used with `end_times`.

- **end_times**

`integer`, default: `1` — How many times the webinar will recur before it is canceled. The maximum number of recurring is 60. Can't be used with `end_date_time`.

- **monthly_day**

`integer` — Use this field `only` if you're scheduling a recurring webinar of type `3` to state which day in a month the webinar should recur. The value range is from 1 to 31. For instance, if you would like the webinar to recur on 23rd of each month, provide `23` as the value of this field and `1` as the value of the `repeat_interval` field. Instead, if you would like the webinar to recur once every three months, on 23rd of the month, change the value of the `repeat_interval` field to `3`.

- **monthly_week**

`integer`, possible values: `-1`, `1`, `2`, `3`, `4` — Use this field `only` if you're scheduling a recurring webinar of type `3` to state the week of the month when the webinar should recur. If you use this field, `you` must also use the `monthly_week_day` field to state the day of the week when the webinar should recur. `-1` - Last week of the month. `1` - First week of the month. `2` - Second week of the month. `3` - Third week of the month. `4` - Fourth week of the month.

- **monthly_week_day**

`integer`, possible values: `1`, `2`, `3`, `4`, `5`, `6`, `7` — Use this field `only` if you're scheduling a recurring webinar of type `3` to state a specific day in a week when the monthly webinar should recur.

To use this field, you must also use the `\`monthly_week\`` field. `\`1\`` - Sunday. `\`2\`` - Monday. `\`3\`` - Tuesday. `\`4\`` - Wednesday. `\`5\`` - Thursday. `\`6\`` - Friday. `\`7\`` - Saturday.

- `**repeat_interval**`

``integer`` — Define the interval when the webinar should recur. For instance, if you would like to schedule a Webinar that recurs every two months, you must set the value of this field as `\`2\`` and the value of the `\`type\`` parameter as `\`3\``. For a daily webinar, the maximum interval you can set is `\`90\`` days. For a weekly webinar, the maximum interval that you can set is `\`12\`` weeks. For a monthly webinar, the maximum interval that you can set is `\`3\`` months.

- `**weekly_days**`

``string`` — Use this field `\`*\`` only if you're scheduling a recurring webinar of type `\`*\`` `\`2\`` to state which day(s) of the week the webinar should repeat. The value for this field could be a number between `\`1\`` to `\`7\`` in string format. For instance, if the Webinar should recur on Sunday, provide `\`1\`` as the value of this field. `\`*\`Note:\`*\`` If you would like the webinar to occur on multiple days of a week, you should provide comma separated values for this field. For instance, if the webinar should recur on Sundays and Tuesdays, provide `\`1,3\`` as the value of this field. `\`1\`` - Sunday. `\`2\`` - Monday. `\`3\`` - Tuesday. `\`4\`` - Wednesday. `\`5\`` - Thursday. `\`6\`` - Friday. `\`7\`` - Saturday.

- `**registration_url**`

``string`` — The URL that registrants can use to register for a webinar. This field is only returned for webinars that have enabled registration.

- `**settings**`

``object`` — Webinar settings.

- `**add_audio_watermark**`

``boolean`` — Add audio watermark that identifies the participants. If not provided, the default value will be based on the user's setting.

- `**add_watermark**`

``boolean`` — Add watermark that identifies the viewing participant. If not provided, the default value will be based on the user's setting.

- `**additional_data_center_regions**`

``array`` — Add additional webinar `\`[data center regions]\``(<https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars>). Provide this value as an array of `\`[country codes]\``([/docs/api/references/abbreviations/#countries](https://docs/api/references/abbreviations/#countries)) for the countries available as data center regions in the `\`[\`*\`Account Profile\`*\`]\``(<https://zoom.us/account/setting>) interface but have been opted out of in the `\`[user settings]\``(<https://zoom.us/profile>). For example, the data center regions selected in your `\`[\`*\`Account Profile\`*\`]\``(<https://zoom.us/account>) are `\`Europe\``, `\`Hong Kong SAR\``, `\`Australia\``, `\`India\``, `\`Japan\``, `\`China\``, `\`United States\``, and `\`Canada\``. However, in the `\`[\`*\`My Profile\`*\`]\``(<https://zoom.us/profile>) settings, you did `\`*\`not\`*\`` select `\`India\`` and `\`Japan\`` for meeting and webinar traffic routing. To include `\`India\`` and `\`Japan\`` as additional data centers, use the `\`[IN, TY]\`` value for this field.

`**Items:**`

``string``

- `**allow_host_control_participant_mute_state**`

``boolean`` — Whether to allow the host and cohosts to fully control the mute state of participants. Not supported for simulative webinar. If not provided, the default value will be based on the user's setting. This option cannot be used together with `\`request_permission_to_unmute_participants\``, only one of the two can be enabled at a time.

- `**allow_multiple_devices**`

``boolean`` — Allow attendees to join from multiple devices.

- `**alternative_host_update_polls**`

``boolean`` — Whether the `\`*\`Allow alternative hosts to add or edit polls\`*\`` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `**alternative_hosts**`

``string`` — Alternative host emails or IDs. Multiple values separated by comma.

- `**approval_type**`

``integer``, possible values: `\`0, 1, 2\``, default: `\`2\`` — `\`0\`` - Automatically approve. `\`1\`` - Manually

approve. `\`2\`` - No registration required.

- `**`attendees_and_panelists_reminder_email_notification`**`

``object`` — Send reminder email to attendees and panelists.

- `**`enable`**`

``boolean`` — `\`*\`true\`` - Send reminder email to attendees and panelists. `\`*\`false\`` - Do not send reminder email to attendees and panelists.

- `**`type`**`

``integer``, possible values: `\`0\``, `\`1\``, `\`2\``, `\`3\``, `\`4\``, `\`5\``, `\`6\``, `\`7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 hour before webinar. `\`2\`` - Send 1 day before webinar. `\`3\`` - Send 1 hour and 1 day before webinar. `\`4\`` - Send 1 week before webinar. `\`5\`` - Send 1 hour and 1 week before webinar. `\`6\`` - Send 1 day and 1 week before webinar. `\`7\`` - Send 1 hour, 1 day and 1 week before webinar.

- `**`audio`**`

``string``, possible values: `\`"both"\``, `\`"telephony"\``, `\`"voip"\``, `\`"thirdParty"\``, default: `\`"both"\`` — Determine how participants can join the audio portion of the webinar.

- `**`audio_conference_info`**`

``string`` — Third party audio conference info.

- `**`authentication_domains`**`

``string`` — If user has configured `\`[\`*\`Sign Into Zoom with Specified Domains\`*\`]\`` ([https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\`\\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f\`](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\`_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f\`)) option, this will list the domains that are authenticated.

- `**`authentication_name`**`

``string`` — Authentication name set in the `\`[authentication profile]\`` ([https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\`\\_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f\`](https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h\`_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f\`)).

- `**`authentication_option`**`

``string`` — Webinar authentication option ID.

- `**`auto_recording`**`

``string``, possible values: `\`"local"\``, `\`"cloud"\``, `\`"none"\``, default: `\`"none"\`` — Automatic recording. `\`local\`` - Record on local. `\`cloud\`` - Record on cloud. `\`none\`` - Disabled.

- `**`close_registration`**`

``boolean`` — Close registration after event date.

- `**`contact_email`**`

``string`` — Contact email for registration

- `**`contact_name`**`

``string`` — Contact name for registration

- `**`email_in_attendee_report`**`

``boolean`` — Whether to include guest's email addresses in attendee reports for webinars.

- `**`email_language`**`

``string`` — Set the email language. `\`en-US\``, `\`de-DE\``, `\`es-ES\``, `\`fr-FR\``, `\`jp-JP\``, `\`pt-PT\``, `\`ru-RU\``, `\`zh-CN\``, `\`zh-TW\``, `\`ko-KO\``, `\`it-IT\``, `\`vi-VN\``.

- `**`enable_session_branding`**`

``boolean`` — Whether the `\`*\`Webinar Session Branding\`*\`` setting is enabled. This setting lets hosts visually customize a webinar by setting a session background. This also lets hosts use `\`[Webinar Session Branding]\`` (<https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding>) to set the Virtual Background for and apply name tags to hosts, alternative hosts, panelists, interpreters, and speakers.

- `**`enforce_login`**`

``boolean`` — Only signed in users can join this meeting. `\`*\``This field is deprecated and will not be

supported in the future. ** As an alternative, use the `\`meeting_authentication\``, `\`authentication\_option\`` and `\`authentication_domains\`` fields to understand the `\[authentication configurations]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars)` set for the webinar.

- **\`enforce\_login\_domains\`**

`\`string\`` — Only signed in users with specified domains can join meetings. \\*\\*This field is deprecated and will not be supported in the future. \\*\\* As an alternative, use the `\`meeting\_authentication\``, `\`authentication_option\`` and `\`authentication\_domains\`` fields to understand the `\[authentication configurations]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars)` set for the webinar.

- **\`follow\_up\_absentees\_email\_notification\`**

`\`object\`` — Send follow-up email to absentees.

- **\`enable\`**

`\`boolean\`` — `\* \`true\`` - Send follow-up email to absentees. `\* \`false\`` - Do not send follow-up email to absentees.

- **\`type\`**

`\`integer\``, possible values: `\`0, 1, 2, 3, 4, 5, 6, 7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 days after the scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- **\`follow\_up\_attendees\_email\_notification\`**

`\`object\`` — Send follow-up email to attendees.

- **\`enable\`**

`\`boolean\`` — `\* \`true\`` - Send follow-up email to attendees. `\* \`false\`` - Do not send follow-up email to attendees.

- **\`type\`**

`\`integer\``, possible values: `\`0, 1, 2, 3, 4, 5, 6, 7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 day after the scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- **\`global\_dial\_in\_countries\`**

`\`array\`` — List of global dial-in countries

****Items:***

`\`string\``

- **\`global\_dial\_in\_numbers\`**

`\`array\`` — A list of available dial-in numbers for different countries or regions.

****Items:***

- **\`city\`**

`\`string\`` — City of the number.

- **\`country\`**

`\`string\`` — The country code.

- **\`country\_name\`**

`\`string\`` — Full name of country.

- **\`number\`**

`\`string\`` — Dial-in phone number.

- **\`type\`**

`\`string\``, possible values: `\`"toll", "tollfree", "premium"\`` — Dial-in number type.

- **hd_video**
 - `boolean`, default: `false` — Default to HD video.
- **hd_video_for_attendees**
 - `boolean`, default: `false` — Whether HD video for attendees is enabled.
- **host_video**
 - `boolean` — Start video when host joins webinar.
- **language_interpretation**
 - `object` — The webinar's `[language interpretation settings]` (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768). Make sure to add the language in the web portal in order to use it in the API. See link for details. **Note:** This feature is only available for certain Webinar add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will **not** be applied to the webinar. This is not supported for simulative webinars.
 - **enable**
 - `boolean` — Whether to enable `[language interpretation]` (https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768) for the webinar. If not provided, the default value will be based on the user's setting.
 - **interpreters**
 - `array` — Information about the webinar's language interpreters.
 - Items:**
 - **email**
 - `string`, format: `email` — The interpreter's email address.
 - **interpreter_languages**
 - `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the `[language interpretation]` object's `languages` and `custom_languages` values in the `[Get user settings]` (`/docs/api/users/#tag/users/{userId}/settings`) API response. **languages:** System-supported languages include `English`, `Chinese`, `Japanese`, `German`, `French`, `Russian`, `Portuguese`, `Spanish`, and `Korean`. **custom_languages:** User-defined languages added by the user. For example, an interpreter translating between English and French should use `English,French`.
 - **languages**
 - `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: `US` (English), `CN` (Chinese), `JP` (Japanese), `DE` (German), `FR` (French), `RU` (Russian), `PT` (Portuguese), `ES` (Spanish), and `KR` (Korean). For example, to set an interpreter translating from English to Chinese, use `US,CN`.
 - **meeting_authentication**
 - `boolean` — Only authenticated users can join Webinar.
 - **on_demand**
 - `boolean`, default: `false` — Make the webinar on demand.
 - **panelist_authentication**
 - `boolean` — Require panelists to authenticate to join. If not provided, the default value will be based on the user's setting.
 - **panelists_invitation_email_notification**
 - `boolean` — Send invitation email to panelists. If `false`, do not send invitation email to panelists.
 - **panelists_video**
 - `boolean` — Start video when panelists join the webinar.
 - **post_webinar_survey**
 - `boolean` — Zoom will open a survey page in attendees' browsers after leaving the webinar.

```

- **`practice_session`**

  `boolean`, default: `false` — Enable practice session.

- **`question_and_answer`**

  `object` — \[Q\&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.) for webinar.

- **`allow_anonymous_questions`**

  `boolean` — \* `true` - Allow participants to send questions without providing their name to the host, co-host, and panelists. \* `false` - Do not allow anonymous questions.

- **`allow_auto_reply`**

  `boolean` — If simulative webinar, \* `true` - allow auto-reply to attendees. \* `false` - don't allow auto-reply to the attendees.

- **`allow_submit_questions`**

  `boolean` — \* `true` - Allow participants to submit questions. \* `false` - Do not allow submit questions.

- **`answer_questions`**

  `string`, possible values: `only`, `all` — Indicate whether you want attendees to be able to view only answered questions, or view all questions. \* `only` - Attendees are able to view answered questions only. \* `all` - Attendees are able to view all questions submitted in the Q\&A.

- **`attendees_can_comment`**

  `boolean` — \* `true` - Attendees can answer questions or leave a comment in the question thread. \* `false` - Attendees can not answer questions or leave a comment in the question thread

- **`attendees_can_upvote`**

  `boolean` — \* `true` - Attendees can click the thumbs up button to bring popular questions to the top of the Q\&A window. \* `false` - Attendees can not click the thumbs up button on questions.

- **`auto_reply_text`**

  `string` — If `allow_auto_reply` = true, the text to be included in the automatic response.

- **`enable`**

  `boolean` — \* `true` - Enable \[Q\&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.) for webinar. \* `false` - Disable Q\&A for webinar. If not provided, the default value will be based on the user's setting.

- **`registrants_confirmation_email`**

  `boolean` — Send confirmation email to registrants.

- **`registrants_email_notification`**

  `boolean` — Send email notifications to registrants about approval, cancellation, denial of the registration. The value of this field must be set to true in order to use the `registrants_confirmation_email` field.

- **`registrants_restrict_number`**

  `integer`, default: `0` — Restrict number of registrants for a webinar. By default, it is set to `0`. A `0` value means that the restriction option is disabled. Provide a number higher than 0 to restrict the webinar registrants by the that number.

- **`registration_type`**

  `integer`, possible values: `1`, `2`, `3`, default: `1` — Registration types. Only used for recurring webinars with a fixed time. `1` - Attendees register once and can attend any of the webinar sessions. `2` - Attendees need to register for each session in order to attend. `3` - Attendees register once and can choose one or more sessions to attend.

- **`request_permission_to_unmute_participants`**

  `boolean`, default: `false` — Whether to enable the \[Request permission to unmute participants](https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting) setting. Not supported for simulative webinar. This option cannot be used together with `allow_host_control_participant_mute_state`, only one of the two can be enabled at a time.

```

```

- send_1080p_video_to_attendees

  `boolean`, default: `false` — Always send 1080p video to attendees.

- show_join_info

  `boolean` — Whether to show the webinar's join information on the registration confirmation page. This setting is only applied to webinars with registration enabled.

- show_share_button

  `boolean` — Show social share buttons on the registration page.

- sign_language_interpretation

  `object` — The webinar's \[sign language interpretation settings]\(https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar). Make sure to add the language in the web portal in order to use it in the API. See link for details. Note: If this feature is not enabled on the host's account, this setting will not be applied to the webinar.

- enable

  `boolean` — Whether to enable \[sign language interpretation]\(https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar) for the webinar. If not provided, the default value will be based on the user's setting.

- interpreters

  `array` — Information about the webinar's sign language interpreters.

  Items:

  - email

    `string`, format: `email` — The interpreter's email address.

  - sign_language

    `string` — The interpreter's sign language. To get this value, use the \sign\_language\_interpretation\` object's \languages\` and \custom\_languages\` values in the \[*\]Get user settings\[*\] (/docs/api/rest/reference/zoom-api/methods#operation/userSettings) API response.

- survey_url

  `string` — Survey url for post webinar survey.

- simulive_delay_start

  `object` — {"enable":false,"time":0,"timeunit":"second"}

- enable

  `boolean` — Whether simulive need delay playback.

- time

  `integer` — The time for delayed playback.

- timeunit

  `string` — The time unit for delayed playback.

- start_time

  `string`, format: `date-time` — Webinar start time in GMT/UTC.

- start_url

  `string` — The \start\_url\` of a webinar is a URL using which a host or an alternative host can start the webinar. This URL should only be used by the host of the meeting and should not be shared with anyone other than the host of the webinar. The expiration time for the \start\_url\` field listed in the response of the \[*\]Create a webinar\[*\] (/docs/api/rest/reference/zoom-api/methods#operation/webinarCreate) API is two hours for all regular users. For users created using the \custCreate\` option via the \[*\]Create users\[*\] (/docs/api/rest/reference/zoom-api/methods#operation/userCreate) API, the expiration time of the \start\_url\` field is 90 days. For security reasons, to retrieve the latest value for the \start\_url\` field programmatically after expiry, call the \[*\]Get a webinar\[*\] (/docs/api/rest/reference/zoom-api/methods#operation/webinar) API and refer to the value of the \start\_url\` field in the response.

- template_id

```

``string`` — The webinar template's unique identifier. Use this field only if you would like to \[schedule the webinar using an existing template]\(https://support.zoom.us/hc/en-us/articles/115001079746-Webinar-Templates#schedule). The value of this field can be retrieved from \[\\`\*\\`List webinar templates\\`*\\]\(/docs/api/rest/reference/zoom-api/methods#operation/listWebinarTemplates) API. You must provide the user ID of the host instead of the email address in the ``userId`` path parameter in order to use a template for scheduling a Webinar.

- `**`timezone`**`

``string`` — Time zone to format ``start`_time``.

- `**`topic`**`

``string`` — The webinar's topic.

- `**`tracking_fields`**`

``array`` — Tracking fields.

`**Items:**`

- `**`field`**`

``string`` — Tracking fields type.

- `**`value`**`

``string`` — Tracking fields value.

- `**`visible`**`

``boolean`` — Whether the \[tracking field]\(https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields) is visible in the webinar scheduling options in the Zoom Web Portal or not. ``true`` - Tracking field is visible. ``false`` - Tracking field is not visible to the users in the webinar options in the Zoom Web Portal but the field was used while scheduling this webinar via API. An invisible tracking field can be used by users while scheduling webinars via API only.

- `**`transition_to_live`**`

``boolean`` — Whether to transition a simulive webinar to live. The host must be present at the time of transition.

- `**`type`**`

``integer``, possible values: ``5``, ``6``, ``9``, default: ``5`` — Webinar types. ``5`` - Webinar. ``6`` - Recurring webinar with no fixed time. ``9`` - Recurring webinar with a fixed time.

- `**`uuid`**`

``string`` — A webinar's unique identifier. Each webinar instance will generate its own UUID. For example, after a webinar ends, a new UUID is generated for the next instance of the webinar. Once a webinar ends, the value of the UUID for the same webinar will be different from when it was scheduled.

`**Example:**`

```
```json
{
 "host_email": "jchill@example.com",
 "host_id": "30R7kT7bTIKSNUFEuH_Qlg",
 "id": 95204914252,
 "template_id": "ull6574eur",
 "uuid": "Bznyg8KZTdCVbQxvS/oZ7w==",
 "agenda": "My Webinar",
 "created_at": "2022-03-26T07:18:32Z",
 "duration": 60,
 "registration_url": "https://example.com/webinar/register/7ksAkRCoEpt1Jm0wa-E6lICLur9e7Lde5oW6",
 "join_url": "https://example.com/j/11111",
 "occurrences": [
 {
 "duration": 60,
 "occurrence_id": "1648194360000",
 "start_time": "2022-03-25T07:46:00Z",
 "status": "available"
 }
],
 "password": "123456",
 "encrypted_passcode": "8pEkRweVXPV30b2KJYgFTRlDt1lgSn.1",
 "h323_passcode": "123456",
 "recurrence": {
```

```

"end_date_time": "2022-04-02T15:59:00Z",
"end_times": 7,
"monthly_day": 1,
"monthly_week": 1,
"monthly_week_day": 1,
"repeat_interval": 1,
"type": 1,
"weekly_days": "1"
},
"settings": {
 "additional_data_center_regions": [
 "TY"
],
 "allow_multiple_devices": true,
 "alternative_hosts": "jchill@example.com",
 "alternative_host_update_polls": true,
 "approval_type": 0,
 "attendees_and_panelists_reminder_email_notification": {
 "enable": true,
 "type": 0
 },
 "audio": "telephony",
 "audio_conference_info": "test",
 "authentication_domains": "example.com",
 "authentication_name": "Sign in to Zoom",
 "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
 "auto_recording": "cloud",
 "contact_email": "jchill@example.com",
 "contact_name": "Jill Chill",
 "email_language": "en-US",
 "follow_up_absentees_email_notification": {
 "enable": true,
 "type": 0
 },
 "follow_up_attendees_email_notification": {
 "enable": true,
 "type": 0
 },
 "global_dial_in_countries": [
 "US"
],
 "global_dial_in_numbers": [
 {
 "city": "New York",
 "country": "US",
 "country_name": "US",
 "number": "+1 1000200200",
 "type": "toll"
 }
],
 "hd_video": false,
 "hd_video_for_attendees": false,
 "host_video": true,
 "language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "interpreter_languages": "English,French"
 }
]
 },
 "sign_language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "sign_language": "American"
 }
]
 },
 "panelist_authentication": true,
 "meeting_authentication": true,
 "add_watermark": true,
 "add_audio_watermark": true,
 "on_demand": false,
 "panelists_invitation_email_notification": true,
 "panelists_video": true,
 "post_webinar_survey": true,
 "practice_session": false,

```

```

"question_and_answer": {
 "allow_submit_questions": true,
 "allow_anonymous_questions": true,
 "answer_questions": "all",
 "attendees_can_comment": true,
 "attendees_can_upvote": true,
 "allow_auto_reply": true,
 "auto_reply_text": "Thank you for your question. We will get back to you shortly.",
 "enable": true
},
"registrants_confirmation_email": true,
"registrants_email_notification": true,
"registrants_restrict_number": 100,
"registration_type": 1,
"send_1080p_video_to_attendees": false,
"show_share_button": true,
"show_join_info": true,
"survey_url": "https://example.com",
"enable_session_branding": true,
"request_permission_to_unmute_participants": true,
"allow_host_control_participant_mute_state": false,
"email_in_attendee_report": true
},
"start_time": "2022-03-26T07:18:32Z",
"start_url": "https://example.com/s/11111",
"timezone": "America/Los_Angeles",
"topic": "My Webinar",
"tracking_fields": [
 {
 "field": "field1",
 "value": "value1",
 "visible": true
 }
],
"type": 5,
"is_simulive": true,
"record_file_id": "f09340e1-cdc3-4eae-9a74-98f9777ed908",
"transition_to_live": false,
"simulive_delay_start": {
 "enable": true,
 "time": 10,
 "timeunit": "second or minute"
},
"creation_source": "open_api"
}

```

##### Status: 400 `HTTP Status Code: 400` Bad Request `Error Code: 200`  
 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for user {userID} in order to perform this action.  
`Error Code: 300` The value that you entered for the `schedule_for` field is invalid. Enter a valid value and try again.  
`Error Code: 300` Can not schedule simulive webinar for others.  
`Error Code: 300` Account hasn't enabled simulive webinar.  
`Error Code: 300` Record file does not exist.  
`Error Code: 3000` You cannot schedule a meeting for {userID}.  
`Error Code: 200` No permission.  
`Error Code: 4505` Simulive can't select `No Fixed Time`.

##### Status: 404 `HTTP Status Code: 404` Not Found `Error Code: 1001` User {userID} does not exist.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rate-limits/).

### Get a webinar

```

- **Method:** `GET`
- **Path:** `/webinars/{webinarId}`
- **Tags:** Webinars

```

Get details for a scheduled Zoom webinar.

#### Prerequisites

- Pro or higher plan with a Webinar add-on.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:admin`, `webinar:read`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:webinar`, `webinar:read:webinar:admin`

```

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `HTTP Status Code:` `200` Success

Content-Type: application/json

- **`agenda`**

 `string` — Webinar agenda.

- **`created_at`**

 `string`, format: `date-time` — Create time.

- **`creation_source`**

 `string`, possible values: `"other", "open_api", "web_portal"` — The platform used when creating the meeting.
 `other` - Created through another platform.
 `open_api` - Created through Open API.
 `web_portal` - Created through the web portal.

- **`duration`**

 `integer` — Webinar duration.

- **`encrypted_passcode`**

 `string` — Encrypted passcode for third party endpoints (H323/SIP).

- **`h323_passcode`**

 `string` — H.323/SIP room system passcode.

- **`host_email`**

 `string`, format: `email` — The meeting host's email address.

- **`host_id`**

 `string` — ID of the user set as host of webinar.

- **`id`**

 `integer`, format: `int64` — The webinar ID in `long` format, represented as int64 data type in JSON, also known as the webinar number.

- **`is_simulive`**

 `boolean` — Whether the webinar is `simulive`.

- **`join_url`**

 `string` — URL to join the webinar. Only share this URL with the users who should be invited to the webinar.

- **`occurrences`**

 `array` — Array of occurrence objects.

 Items:

 - **`duration`**

 `integer` — Duration.

 - **`occurrence_id`**

 `string` — The occurrence ID, a unique identifier that identifies an occurrence of a recurring webinar.
 [Recurring webinars](https://support.zoom.us/hc/en-us/articles/216354763-How-to-Schedule-A-Recurring-Webinar) can have a maximum of 50 occurrences.

 - **`start_time`**

 `string`, format: `date-time` — Start time.

 - **`status`**

 `string`, possible values: `"available", "deleted"` — Occurrence status.
 `available` - Available

```



occurrence. `\`deleted\`` - Deleted occurrence.

- `**`password`**`

``string`` — Webinar passcode. Passcode may only contain the characters `\[a-z A-Z 0-9 @ - _ \* !]`. Maximum of 10 characters. If `\`*\`Webinar Passcode\`*\`` setting has been `\`*\`enabled\`*\` \`*\`and\`*\` \`*\`locked\`*\`` (<https://support.zoom.us/hc/en-us/articles/115005269866-Using-Tiered-Settings#locked>) for the user, the passcode field will be autogenerated for the Webinar in the response even if it is not provided in the API request. `\`*\`Note:\`*\`` If the account owner or the admin has configured `\[minimum passcode requirement settings]\`*\`` ([https://support.zoom.us/hc/en-us/articles/360033559832-Meeting-and-webinar-passwords#h\\_a427384b-e383-4f80-864d-794bf0a37604](https://support.zoom.us/hc/en-us/articles/360033559832-Meeting-and-webinar-passwords#h_a427384b-e383-4f80-864d-794bf0a37604)), the passcode value provided here must meet those requirements. If the requirements are enabled, you can view those requirements by calling the `\`*\`Get account settings\`*\`` (`\`*\`/docs/api/rest/reference/account/methods/#operation/accountSettings\`*\``) API.

- `**`record_file_id`**`

``string`` — The previously recorded file's ID for `\`simulive\``.

- `**`recurrence`**`

``object`` — Recurrence object. Use this object only for a webinar of type `\`9\`` - a recurring webinar with fixed time.

- `**`type` (required)**`

``integer``, possible values: `\`1, 2, 3\`` — Recurrence webinar types. `\`1\`` - Daily. `\`2\`` - Weekly. `\`3\`` - Monthly.

- `**`end_date_time`**`

``string``, format: ``date-time`` — Select a date when the webinar will recur before it is canceled. Should be in UTC time, such as `2017-11-25T12:00:00Z`. Cannot be used with `\`end_times\``.

- `**`end_times`**`

``integer``, default: `\`1\`` — How many times the webinar will recur before it is canceled. The maximum number of recurring is 60. Cannot be used with `\`end_date_time\``.

- `**`monthly_day`**`

``integer`` — Use this field `\`*\`only if you're scheduling a recurring webinar of type\`*\` \`3\`` to state which day in a month, the webinar should recur. The value range is from 1 to 31. For instance, if you would like the webinar to recur on 23rd of each month, provide `\`23\`` as the value of this field and `\`1\`` as the value of the `\`repeat_interval\`` field. Instead, if you would like the webinar to recur once every three months, on 23rd of the month, change the value of the `\`repeat_interval\`` field to `\`3\``.

- `**`monthly_week`**`

``integer``, possible values: `\`-1, 1, 2, 3, 4\`` — Use this field `\`*\`only if you're scheduling a recurring webinar of type\`*\` \`3\`` to state the week of the month when the webinar should recur. If you use this field, `\`*\`you must also use the \`monthly_week_day\` field to state the day of the week when the webinar should recur.\`*\`` `\`-1\`` - Last week of the month. `\`1\`` - First week of the month. `\`2\`` - Second week of the month. `\`3\`` - Third week of the month. `\`4\`` - Fourth week of the month.

- `**`monthly_week_day`**`

``integer``, possible values: `\`1, 2, 3, 4, 5, 6, 7\`` — Use this field `\`*\`only if you're scheduling a recurring webinar of type\`*\` \`3\`` to state a specific day in a week when the monthly webinar should recur. To use this field, you must also use the `\`monthly_week\`` field. `\`1\`` - Sunday. `\`2\`` - Monday. `\`3\`` - Tuesday. `\`4\`` - Wednesday. `\`5\`` - Thursday. `\`6\`` - Friday. `\`7\`` - Saturday.

- `**`repeat_interval`**`

``integer`` — Define the interval when the webinar should recur. For instance, to schedule a webinar that recurs every two months, you must set the value of this field as `\`2\`` and the value of the `\`type\`` parameter as `\`3\``. For a daily webinar, the maximum interval you can set is `\`90\`` days. For a weekly webinar, the maximum interval that you can set is `\`12\`` weeks. For a monthly webinar, the maximum interval that you can set is `\`3\`` months.

- `**`weekly_days`**`

``string`` — Use this field `\`*\`only if you're scheduling a recurring webinar of type\`*\` \`2\`` to state which days of the week the webinar should repeat. The value for this field could be a number between `\`1\`` to `\`7\`` in string format. For instance, if the Webinar should recur on Sunday, provide `\`1\`` as the value of this field. `\`*\`Note:\`*\`` If you would like the webinar to occur on multiple days of a week, you should provide comma separated values for this field. For instance, if the Webinar should recur on Sundays and Tuesdays provide `\`1,3\`` as the value of this field. `\`1\`` - Sunday. `\`2\`` - Monday. `\`3\`` - Tuesday. `\`4\`` - Wednesday. `\`5\`` - Thursday. `\`6\`` - Friday. `\`7\`` - Saturday.

- `**`registration_url`**`

``string`` — The URL that registrants can use to register for a webinar. This field is only returned for webinars that have enabled registration.

- `**`settings`**`

``object`` — Webinar settings.

- `**`add_audio_watermark`**`

``boolean`` — Add audio watermark that identifies the participants.

- `**`add_watermark`**`

``boolean`` — Add watermark that identifies the viewing participant.

- `**`additional_data_center_regions`**`

``array`` — Add more webinar `\[data center regions]\(https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars)`. Provide this value as an array of `\[country codes]\(/docs/api/references/abbreviations/#countries)` for the countries available as data center regions in the `\[*]*Account Profile\[*]*\(\(https://zoom.us/account/setting)` interface but have been opted out of in the `\[user settings]\(https://zoom.us/profile)`. For example, the data center regions selected in your `\[*]*Account Profile\[*]*\(\(https://zoom.us/account)` are `\`Europe\`, \`Hong Kong SAR\`, \`Australia\`, \`India\`, \`Japan\`, \`China\`, \`United States\`, and \`Canada\``. However, in the `\[*]*My Profile\[*]*\(\(https://zoom.us/profile)` settings, you did `\[*]*not\[*]*` select `\`India\`` and `\`Japan\`` for meeting and webinar traffic routing. To include `\`India\`` and `\`Japan\`` as additional data centers, use the `\[IN, TY]\`` value for this field.

`**Items:**`

``string``

- `**`allow_host_control_participant_mute_state`**`

``boolean`` — Whether to allow the host and co-hosts to fully control the mute state of participants. Not supported for simulive webinar. This option cannot be used together with `\request\permission\_to\_unmute\_participants\``, only one of the two can be enabled at a time.

- `**`allow_multiple_devices`**`

``boolean`` — Allow attendees to join from multiple devices.

- `**`alternative_host_update_polls`**`

``boolean`` — Whether the `\[*]*Allow alternative hosts to add or edit polls\[*]*` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `**`alternative_hosts`**`

``string`` — Alternative host emails or IDs. Multiple values separated by comma.

- `**`approval_type`**`

``integer``, possible values: `\`0, 1, 2\``, default: `\`2\`` — `\`0\`` - Automatically approve. `\`1\`` - Manually approve. `\`2\`` - No registration required.

- `**`attendees_and_panelists_reminder_email_notification`**`

``object`` — Send reminder email to attendees and panelists.

- `**`enable`**`

``boolean`` — `\[*]*true\`` - Send reminder email to attendees and panelists. `\[*]*false\`` - Do not send reminder email to attendees and panelists.

- `**`type`**`

``integer``, possible values: `\`0, 1, 2, 3, 4, 5, 6, 7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 hour before webinar. `\`2\`` - Send 1 day before webinar. `\`3\`` - Send 1 hour and 1 day before webinar. `\`4\`` - Send 1 week before webinar. `\`5\`` - Send 1 hour and 1 week before webinar. `\`6\`` - Send 1 day and 1 week before webinar. `\`7\`` - Send 1 hour, 1 day and 1 week before webinar.

- `**`audio`**`

``string``, possible values: `\`"both", "telephony", "voip", "thirdParty"\``, default: `\`"both"\`` — Determine how participants can join the audio portion of the webinar.

- `**`audio_conference_info`**`

```

`string` — Third party audio conference info.

- **`authentication_domains`**

`string` — If user has configured \[**Sign Into Zoom with Specified Domains*\] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f) option, this will list the domains that are authenticated.

- **`authentication_name`**

`string` — Authentication name set in the \[authentication profile\] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h_5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f).

- **`authentication_option`**

`string` — Webinar authentication option ID.

- **`auto_recording`**

`string`, possible values: "local", "cloud", "none", default: "none" — Automatic recording. "local" - Record on local. "cloud" - Record on cloud. "none" - Disabled.

- **`close_registration`**

`boolean` — Close registration after event date.

- **`contact_email`**

`string` — Contact email for registration.

- **`contact_name`**

`string` — Contact name for registration.

- **`email_in_attendee_report`**

`boolean` — Whether to include guest's email addresses in webinars' attendee reports.

- **`email_language`**

`string` — Set the email language. "en-US", "de-DE", "es-ES", "fr-FR", "jp-JP", "pt-PT", "ru-RU", "zh-CN", "zh-TW", "ko-KO", "it-IT", or "vi-VN".

- **`enable_session_branding`**

`boolean` — Whether the \[**Webinar Session Branding*\] setting is enabled. This setting lets hosts visually customize a webinar by setting a session background. This also lets hosts use \[webinar session branding\] (https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding) to set the Virtual Background for and apply name tags to hosts, alternative hosts, panelists, interpreters, and speakers.

- **`enforce_login`**

`boolean` — Only signed in users can join this meeting. \[**This field is deprecated and will not be supported in the future.** As an alternative, use the \meeting_authentication\, \authentication_option\ and \authentication_domains\ fields to understand the \[authentication configurations\] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the webinar.

- **`enforce_login_domains`**

`string` — Only signed in users with specified domains can join meetings. \[**This field is deprecated and will not be supported in the future.** As an alternative, use the \meeting_authentication\, \authentication_option\, and \authentication_domains\ fields to understand the \[authentication configurations\] (https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars) set for the webinar.

- **`follow_up_absentees_email_notification`**

`object` — Send follow-up email to absentees.

- **`enable`**

`boolean` — "true" - Send follow-up email to absentees. "false" - Do not send follow-up email to absentees.

- **`type`**

`integer`, possible values: 0, 1, 2, 3, 4, 5, 6, 7 — 0 - No plan. 1 - Send 1 days after the

```

scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- **`follow_up_attendees_email_notification`**

`object` — Send follow-up email to attendees.

- **`enable`**

`boolean` — `\`true\`` - Send follow-up email to attendees. `\`false\`` - Do not send follow-up email to attendees.

- **`type`**

`integer`, possible values: `\`0\`` - No plan. `\`1\`` - Send 1 day after the scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- **`global_dial_in_countries`**

`array` — List of global dial-in countries.

**`Items`**

`string`

- **`global_dial_in_numbers`**

`array` — A list of available dial-in numbers for different countries or regions.

**`Items`**

- **`city`**

`string` — The number's city.

- **`country`**

`string` — The country code.

- **`country_name`**

`string` — Full name of country.

- **`number`**

`string` — Dial-in phone number.

- **`type`**

`string`, possible values: `\`toll\``, `\`tollfree\``, `\`premium\`` — Dial-in number type.

- **`hd_video`**

`boolean`, default: `\`false\`` — Default to HD video.

- **`hd_video_for_attendees`**

`boolean`, default: `\`false\`` — Whether HD video for attendees is enabled.

- **`host_video`**

`boolean` — Start video when the host joins the webinar.

- **`language_interpretation`**

`object` — The webinar's `[language interpretation settings]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0064768](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768)). Make sure to add the language in the web portal in order to use it in the API. See link for details. `\`*\`Note:\`*\`` This feature is only available for certain Webinar add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will `\`*\`not\`*\`` be applied to the webinar. This is not supported for simulative webinars.

- **`enable`**

`boolean` — Whether to enable `[language interpretation]` ([https://support.zoom.com/hc/en/article?id=zm\\_kb&sysparm\\_article=KB0064768](https://support.zoom.com/hc/en/article?id=zm_kb&sysparm_article=KB0064768)) for the webinar.

```

- ``interpreters``

 `array` — Information about the webinar's language interpreters.

``Items``

- ``email``

 `string`, format: `email` — The interpreter's email address.

- ``interpreter_languages``

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the `language_interpretation` object's `languages` and `custom_languages` values in the `[*Get user settings*]` (/docs/api/users/#tag/users/{userId}/settings) API response. `[*languages*]: System-supported languages include `English`, `Chinese`, `Japanese`, `German`, `French`, `Russian`, `Portuguese`, `Spanish`, and `Korean`. `[*custom_languages*]: User-defined languages added by the user. For example, an interpreter translating between English and French should use `English,French`.

- ``languages``

 `string` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: `US` (English), `CN` (Chinese), `JP` (Japanese), `DE` (German), `FR` (French), `RU` (Russian), `PT` (Portuguese), `ES` (Spanish), and `KR` (Korean). For example, to set an interpreter translating from English to Chinese, use `US,CN`.

- ``meeting_authentication``

 `boolean` — Only authenticated users can join the webinar.

- ``on_demand``

 `boolean`, default: `false` — Make the webinar on-demand.

- ``panelist_authentication``

 `boolean` — Require panelists to authenticate to join.

- ``panelists_invitation_email_notification``

 `boolean` — Send invitation email to panelists. If `false`, do not send invitation email to panelists.

- ``panelists_video``

 `boolean` — Start video when panelists join webinar.

- ``post_webinar_survey``

 `boolean` — Zoom will open a survey page in attendees' browsers after leaving the webinar.

- ``practice_session``

 `boolean`, default: `false` — Enable practice session.

- ``question_and_answer``

 `object` — [Q&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.) for webinar.

- ``allow_anonymous_questions``

 `boolean` — `true` - Allow participants to send questions without providing their name to the host, co-host, and panelists. `false` - Do not allow anonymous questions.

- ``allow_auto_reply``

 `boolean` — If simulative webinar, `true` - allow auto-reply to attendees. `false` - don't allow auto-reply to the attendees.

- ``allow_submit_questions``

 `boolean` — `true` - Allow participants to submit questions. `false` - Do not allow submit questions.

- ``answer_questions``

 `string`, possible values: `only`, `all` — Indicate whether you want attendees to be able to view

```

answered questions only or view all questions. `\* \only\` - Attendees are able to view answered questions only. `\* \all\` - Attendees are able to view all questions submitted in the Q&A.

- `**`attendees_can_comment`**`

``boolean`` — `\* \true\` - Attendees can answer questions or leave a comment in the question thread. `\* \false\` - Attendees can not answer questions or leave a comment in the question thread

- `**`attendees_can_upvote`**`

``boolean`` — `\* \true\` - Attendees can click the thumbs up button to bring popular questions to the top of the Q&A window. `\* \false\` - Attendees can not click the thumbs up button on questions.

- `**`auto_reply_text`**`

``string`` — If `\allow\_auto\_reply\` = true, the text to be included in the automatic response.

- `**`enable`**`

``boolean`` — `\* \true\` - Enable `\[Q&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.)` for webinar. `\* \false\` - Disable Q&A for webinar.

- `**`registrants_confirmation_email`**`

``boolean`` — Send confirmation email to registrants

- `**`registrants_email_notification`**`

``boolean`` — Send email notifications to registrants about approval, cancellation, denial of the registration. The value of this field must be set to true in order to use the `\registrants\_confirmation\_email\` field.

- `**`registrants_restrict_number`**`

``integer``, default: `\0\` — Restrict number of registrants for a webinar. By default, it is set to `\0\`. A `\0\` value means that the restriction option is disabled. Provide a number higher than 0 to restrict the webinar registrants by the that number.

- `**`registration_type`**`

``integer``, possible values: `\1, 2, 3\`, default: `\1\` — Registration types. Only used for recurring webinars with a fixed time. `\1\` - Attendees register once and can attend any of the webinar sessions. `\2\` - Attendees need to register for each session in order to attend. `\3\` - Attendees register once and can choose one or more sessions to attend.

- `**`request_permission_to_unmute_participants`**`

``boolean`` — Whether to enable the `\[*Request permission to unmute participants\*]` (`https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting`) setting. Not supported for simulive webinar. This option cannot be used together with `\allow\_host\_control\_participant\_mute\_state\`, only one of the two can be enabled at a time.

- `**`send_1080p_video_to_attendees`**`

``boolean``, default: `\false\` — Always send 1080p video to attendees.

- `**`show_join_info`**`

``boolean`` — Whether to show the webinar's join information on the registration confirmation page. This setting is only applied to webinars with registration enabled.

- `**`show_share_button`**`

``boolean`` — Show social share buttons on the registration page.

- `**`sign_language_interpretation`**`

``object`` — The webinar's `\[sign language interpretation settings](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)`. Make sure to add the language in the web portal in order to use it in the API. See link for details. `\*Note:\*` If this feature is not enabled on the host's account, this setting will `\*not\*` be applied to the webinar.

- `**`enable`**`

``boolean`` — Whether to enable `\[sign language interpretation](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)` for the webinar.

- `**`interpreters`**`

```

`array` — Information about the webinar's sign language interpreters.

Items:

- **`email`**

 `string`, format: `email` — The interpreter's email address.

- **`sign_language`**

 `string` — The interpreter's sign language. To get this value, use the
 `sign_language_interpretation` object's `languages` and `custom_languages` values in the `[*]Get
 user settings[*]` (/docs/api-reference/zoom-api/methods#operation/userSettings) API response.

- **`survey_url`**

 `string` — Survey URL for post webinar survey.

- **`simulive_delay_start`**

 `object` — {"enable":false,"time":0,"timeunit":"second"}

- **`enable`**

 `boolean` — Whether simulive needs to delay playback.

- **`time`**

 `integer` — The time for delayed playback. If the time unit is seconds, then the maximum value is 60
 and the minimum value is 1. If the time unit is minutes, then the maximum value is 10 and the minimum value
 is 1.

- **`timeunit`**

 `string`, possible values: `second`, `minute`, default: `second` — The time unit for delayed
 playback. `second` - The time unit for delayed playback is seconds. `minute` - The time unit for delayed
 playback is minutes.

- **`start_time`**

 `string`, format: `date-time` — Webinar start time in GMT/UTC.

- **`start_url`**

 `string` — The `start_url` of a webinar is a URL using which a host or an alternative host can start
 the webinar. This URL should only be used by the host of the meeting and should not be shared with anyone
 other than the host of the webinar. The expiration time for the `start_url` field listed in the response
 of the `[*]Create a webinar[*]` (/docs/api-reference/zoom-api/methods#operation/webinarCreate) API is two
 hours for all regular users. For users created using the `custCreate` option via the `[*]Create
 users[*]` (/docs/api-reference/zoom-api/methods#operation/userCreate) API, the expiration time of the
 `start_url` field is 90 days. For security reasons, to retrieve the latest value for the `start_url`
 field programmatically (after expiry), you must call the `[*]Get a webinar[*]` (/docs/api-reference/zoom-
 api/methods#operation/webinar) API and refer to the value of the `start_url` field in the response.

- **`template_id`**

 `string` — The webinar template's unique identifier. Use this field only if you would like to [schedule
 the webinar using an existing template](https://support.zoom.us/hc/en-us/articles/115001079746-Webinar-
 Templates#schedule). The value of this field can be retrieved from `[*]List webinar templates[*]`
 (/docs/api/rest/reference/zoom-api/methods#operation/listWebinarTemplates) API. You must provide the user ID
 of the host instead of the email address in the `userId` path parameter in order to use a template for
 scheduling a webinar.

- **`timezone`**

 `string` — Time zone to format `start_time`.

- **`topic`**

 `string` — Webinar topic.

- **`tracking_fields`**

 `array` — Tracking fields.

 Items:

 - **`field`**

 `string` — Tracking fields type.

```

```

- value

`string` — Tracking fields value.

- visible

`boolean` — Whether the [tracking field] (https://support.zoom.us/hc/en-us/articles/115000293426-Scheduling-Tracking-Fields) is visible in the webinar scheduling options in the Zoom Web Portal or not.
 * `true` - Tracking field is visible.
 * `false` - Tracking field is not visible to the users in the webinar options in the Zoom Web Portal but the field was used while scheduling this webinar via API.
 An invisible tracking field can be used by users while scheduling webinars via API only.

- transition_to_live

`boolean` — Whether to transition a simulive webinar to live. The host must be present at the time of transition.

- type

`integer`, possible values: `5`, `6`, `9`, default: `5` — Webinar types.
 * `5` - Webinar.
 * `6` - Recurring webinar with no fixed time.
 * `9` - Recurring webinar with a fixed time.

- uuid

`string` — Unique webinar ID. Each webinar instance generates its own webinar UUID. After a webinar ends, a new UUID is generated for the next instance of the webinar. Retrieve a list of UUIDs from past webinar instances using the [/*List past webinar instances*/] (/docs/api-reference/zoom-api/methods#operation/pastWebinars) API. [Double encode] (/docs/api/using-zoom-apis/#meeting-id-and-uuid) your UUID when using it for API calls if the UUID begins with a \`/\` or contains \`/\` in it.

Example:

```json
{
  "host_email": "jchill@example.com",
  "host_id": "30R7kT7bTIKSNUFEuH_Qlg",
  "id": "97871060099",
  "template_id": "ull6574eur",
  "uuid": "m3WqMkvuRXyYqH+eKWhk9w==",
  "agenda": "My webinar",
  "created_at": "2022-03-26T07:18:32Z",
  "duration": 60,
  "registration_url": "https://example.com/webinar/register/7ksAkRCoEpt1Jm0wa-E6lICLur9e7Lde5oW6",
  "join_url": "https://example.com/j/11111",
  "occurrences": [
    {
      "duration": 60,
      "occurrence_id": "1648194360000",
      "start_time": "2022-03-25T07:46:00Z",
      "status": "available"
    }
  ],
  "password": "123456",
  "encrypted_passcode": "8pEkRweVXPV30b2KJYgFTRlDt1lgSn.1",
  "h323_passcode": "123456",
  "recurrence": {
    "end_date_time": "2022-04-02T15:59:00Z",
    "end_times": 7,
    "monthly_day": 1,
    "monthly_week": 1,
    "monthly_week_day": 1,
    "repeat_interval": 1,
    "type": 1,
    "weekly_days": "1"
  },
  "settings": {
    "additional_data_center_regions": [
      "TY"
    ],
    "allow_multiple_devices": true,
    "alternative_hosts": "jchill@example.com",
    "alternative_host_update_polls": true,
    "approval_type": 0,
    "attendees_and_panelists_reminder_email_notification": {
      "enable": true,
      "type": 0
    }
  },
  "audio": "telephony",
  "audio_conference_info": "test",

```



```

"authentication_domains": "example.com",
"authentication_name": "Sign in to Zoom",
"authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
"auto_recording": "cloud",
"contact_email": "jchill@example.com",
"contact_name": "Jill Chill",
"email_language": "en-US",
"follow_up_absentees_email_notification": {
  "enable": true,
  "type": 0
},
"follow_up_attendees_email_notification": {
  "enable": true,
  "type": 0
},
"global_dial_in_countries": [
  "US"
],
"global_dial_in_numbers": [
  {
    "city": "New York",
    "country": "US",
    "country_name": "US",
    "number": "+1 1000200200",
    "type": "toll"
  }
],
"hd_video": false,
"hd_video_for_attendees": false,
"host_video": true,
"language_interpretation": {
  "enable": true,
  "interpreters": [
    {
      "email": "interpreter@example.com",
      "interpreter_languages": "English,French"
    }
  ]
},
"sign_language_interpretation": {
  "enable": true,
  "interpreters": [
    {
      "email": "interpreter@example.com",
      "sign_language": "American"
    }
  ]
},
"panelist_authentication": true,
"meeting_authentication": true,
"add_watermark": true,
"add_audio_watermark": true,
"on_demand": false,
"panelists_invitation_email_notification": true,
"panelists_video": true,
"post_webinar_survey": true,
"practice_session": false,
"question_and_answer": {
  "allow_submit_questions": true,
  "allow_anonymous_questions": true,
  "answer_questions": "all",
  "attendees_can_comment": true,
  "attendees_can_upvote": true,
  "allow_auto_reply": true,
  "auto_reply_text": "Thank you for your question. We will get back to you shortly.",
  "enable": true
},
"registrants_confirmation_email": true,
"registrants_email_notification": true,
"registrants_restrict_number": 100,
"registration_type": 1,
"send_1080p_video_to_attendees": false,
"show_share_button": true,
"show_join_info": true,
"survey_url": "https://example.com",
"enable_session_branding": true,
"request_permission_to_unmute_participants": true,
"allow_host_control_participant_mute_state": false,
"email_in_attendee_report": true
},

```

```

"start_time": "2022-03-26T07:18:32Z",
"start_url": "https://example.com/s/11111",
"timezone": "America/Los_Angeles",
"topic": "My Webinar",
"tracking_fields": [
  {
    "field": "field1",
    "value": "value1",
    "visible": true
  }
],
"type": 5,
"is_simulive": true,
"record_file_id": "f09340e1-cdc3-4eae-9a74-98f9777ed908",
"transition_to_live": false,
"simulive_delay_start": {
  "enable": true,
  "time": 10,
  "timeunit": "second"
},
"creation_source": "open_api"
}

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid webinar ID.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for user {userId} to perform this action.` `Error Code: 200` `No permission.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).`

Delete a webinar

```

- **Method:** `DELETE`
- **Path:** `/webinars/{webinarId}`
- **Tags:** Webinars

```

Delete a webinar.

Prerequisites:

- Pro or higher plan with the webinar add-on.

Scopes(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:write:admin`, `webinar:write`

Granular Scopes(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:delete:webinar`, `webinar:delete:webinar:admin`

Rate Limit Label(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

Responses

Status: 204 `HTTP Status Code: 204` `Webinar deleted.`

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3000` `Your request could not be processed because webinars created via event directory can not be updated or deleted using this method.` `Error Code: 3000` `You cannot update or delete simulive webinars that have started using this method.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.` `Error Code: 200` `No permission.` `Error Code: 3000` `Webinar occurrence does not exist.` `Error Code: 300` `Invalid webinar ID.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

Update a webinar

```

- **Method:** `PATCH`
- **Path:** `/webinars/{webinarId}`
- **Tags:** Webinars

```

Make updates to a scheduled webinar.

****100 requests per day****. The rate limit is applied to the `userId` of the ****webinar host**** used to make the request.

****Prerequisites****

- A Pro or higher plan with a webinar add-on.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
 `webinar:write`, `webinar:write:admin`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/)****
 `webinar:update:webinar`, `webinar:update:webinar:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits)**** `LIGHT`

Request Body

Content-Type: application/json

- ****`agenda`****

`string` — Webinar description.

- ****`duration`****

`integer` — Webinar duration, in minutes. Used for scheduled webinar only.

- ****`is\_simulive`****

`boolean` — Whether to set the webinar to simulive.

- ****`password`****

`string` — Webinar passcode. Passcode may only contain the characters `[a-z A-Z 0-9 @ - \_ \ \* !]`. Maximum of 10 characters. If `Webinar Passcode` setting has been `enabled` and `locked` (https://support.zoom.us/hc/en-us/articles/115005269866-Using-Tiered-Settings#locked) for the user, the passcode field will be autogenerated for the Webinar in the response even if it is not provided in the API request. **Note:** If the account owner or the admin has configured [minimum passcode requirement settings](https://support.zoom.us/hc/en-us/articles/360033559832-Meeting-and-webinar-passwords#a427384b-e383-4f80-864d-794bf0a37604), the passcode value provided here must meet those requirements. If the requirements are enabled, you can view those requirements by calling the [Get account settings](https://developers.zoom.us/docs/api/rest/reference/account/methods/#operation/accountSettings) API.

- ****`record\_file\_id`****

`string` — The previously recorded file's ID for `simulive`.

- ****`recurrence`****

`object` — Recurrence object. Use this object only for a meeting with type `8`, a recurring meeting with fixed time.

- ****`type` (required)****

`integer`, possible values: `1, 2, 3` — Recurrence meeting types. `1` - Daily. `2` - Weekly. `3` - Monthly.

- ****`end\_date\_time`****

`string`, format: `date-time` — Select the final date when the meeting will recur before it is canceled. Should be in UTC time, such as 2017-11-25T12:00:00Z. Cannot be used with `end\_times`.

- ****`end\_times`****

`integer`, default: `1` — Select how many times the webinar will recur before it is canceled. The maximum number of recurring is 60. Cannot be used with `end\_date\_time`.

- ****`monthly\_day`****

`integer`, default: `1` — Use this field **only** if you're scheduling a recurring meeting of type `3` to state which day in a month, the meeting should recur. The value range is from 1 to 31. If you would like the meeting to recur on 23rd of each month, provide `23` as the value of this field and `1` as the value of the `repeat\_interval` field. If you would like the meeting to recur every three months, on 23rd of the month, change the value of the `repeat\_interval` field to `3`.

- ****`monthly\_week`****

`integer`, possible values: `-1, 1, 2, 3, 4` — Use this field **only** if you're scheduling a recurring meeting of type `3` to state the week of the month when the meeting should recur. If you use this

field, `\*\*you must also use the \monthly\_week\_day\` field to state the day of the week when the meeting should recur.**` `\-1\`` - Last week of the month. `\1\`` - First week of the month. `\2\`` - Second week of the month. `\3\`` - Third week of the month. `\4\`` - Fourth week of the month.

- `\*\*monthly\_week\_day\*\*`

`\integer\``, possible values: `\1, 2, 3, 4, 5, 6, 7\`` — Use this field `\*\*only if you're scheduling a recurring meeting of type\*\*` `\3\`` to state a specific day in a week when the monthly meeting should recur. To use this field, you must also use the `\monthly\_week\`` field. `\1\`` - Sunday. `\2\`` - Monday. `\3\`` - Tuesday. `\4\`` - Wednesday. `\5\`` - Thursday. `\6\`` - Friday. `\7\`` - Saturday.

- `\*\*repeat\_interval\*\*`

`\integer\`` — Define the interval when the meeting should recur. If you would like to schedule a meeting that recurs every two months, set the value of this field as `\2\`` and the value of the `\type\`` parameter as `\3\``. For a daily meeting, the maximum interval you can set is `\90\`` days. For a weekly meeting the maximum interval that you can set is of `\12\`` weeks. For a monthly meeting, there is a maximum of `\3\`` months.

- `\*\*weekly\_days\*\*`

`\string\``, possible values: `\1, 2, 3, 4, 5, 6, 7\``, default: `\1\`` — This field is required `\*\*if you're scheduling a recurring meeting of type\*\*` `\2\`` to state which day(s) of the week the meeting should repeat. The value for this field could be a number between `\1\`` to `\7\`` in string format. For instance, if the meeting should recur on Sunday, provide `\1\`` as the value of this field. `\*\*Note:\*\*` If you would like the meeting to occur on multiple days of a week, you should provide comma separated values for this field. For instance, if the meeting should recur on Sundays and Tuesdays provide `\1,3\`` as the value of this field. `\1\`` - Sunday. `\2\`` - Monday. `\3\`` - Tuesday. `\4\`` - Wednesday. `\5\`` - Thursday. `\6\`` - Friday. `\7\`` - Saturday.

- `\*\*schedule\_for\*\*`

`\string\`` — The user's email address or `\userId\`` to schedule a webinar for.

- `\*\*settings\*\*`

`\object\`` — Webinar settings.

- `\*\*add\_audio\_watermark\*\*`

`\boolean\`` — Add audio watermark that identifies the participants.

- `\*\*add\_watermark\*\*`

`\boolean\`` — Add watermark that identifies the viewing participant.

- `\*\*additional\_data\_center\_regions\*\*`

`\array\`` — Add more webinar `\[data center regions]\(https://support.zoom.us/hc/en-us/articles/360042411451-Selecting-data-center-regions-for-hosted-meetings-and-webinars)`. Provide this value as an array of `\[country codes]\(/docs/api/references/abbreviations/#countries)` for the countries available as data center regions in the `\[\*\*Account Profile\*\*]\(https://zoom.us/account/setting)` interface but have been opted out of in the `\[user settings]\(https://zoom.us/profile)`. For example, the data center regions selected in your `\[\*\*Account Profile\*\*]\(https://zoom.us/account)` are `\Europe\``, `\Hong Kong SAR\``, `\Australia\``, `\India\``, `\Japan\``, `\China\``, `\United States\``, and `\Canada\``. However, in the `\[\*\*My Profile\*\*]\(https://zoom.us/profile)` settings, you did `\*\*not\*\*` select `\India\`` and `\Japan\`` for meeting and webinar traffic routing. To include `\India\`` and `\Japan\`` as additional data centers, use the `\[IN, TY]\`` value for this field.

`\*\*Items:\*\*`

`\string\``

- `\*\*allow\_host\_control\_participant\_mute\_state\*\*`

`\boolean\`` — Whether to allow the host and co-hosts to fully control the mute state of participants. Not supported for simulive webinar. This option cannot be used together with `\request\_permission\_to\_unmute\_participants\``, only one of the two can be enabled at a time.

- `\*\*allow\_multiple\_devices\*\*`

`\boolean\`` — Allow attendees to join from multiple devices.

- `\*\*alternative\_host\_update\_polls\*\*`

`\boolean\`` — Whether the `\*\*Allow alternative hosts to add or edit polls\*\*` feature is enabled. This requires Zoom version 5.8.0 or higher.

- `\*\*alternative\_hosts\*\*`

``string`` — Alternative host emails or IDs. Separate multiple values by commas.

- `**`approval_type`**`

``integer``, possible values: ``0``, ``1``, ``2``, default: ``2`` — ``0`` — Automatically approve. ``1`` — Manually approve. ``2`` — No registration required.

- `**`attendees_and_panelists_reminder_email_notification`**`

``object`` — Send reminder email to attendees and panelists.

- `**`enable`**`

``boolean`` — ``true`` — Send reminder email to attendees and panelists. ``false`` — Do not send reminder email to attendees and panelists.

- `**`type`**`

``integer``, possible values: ``0``, ``1``, ``2``, ``3``, ``4``, ``5``, ``6``, ``7`` — ``0`` — No plan. ``1`` — Send 1 hour before webinar. ``2`` — Send 1 day before webinar. ``3`` — Send 1 hour and 1 day before webinar. ``4`` — Send 1 week before webinar. ``5`` — Send 1 hour and 1 week before webinar. ``6`` — Send 1 day and 1 week before webinar. ``7`` — Send 1 hour, 1 day and 1 week before webinar.

- `**`audio`**`

``string``, possible values: ``"both"``, ``"telephony"``, ``"voip"``, ``"thirdParty"``, default: ``"both"`` — Determine how participants can join the audio portion of the webinar.

- `**`audio_conference_info`**`

``string`` — Third party audio conference info.

- `**`authentication_domains`**`

``string`` — If user has configured `[/Sign Into Zoom with Specified Domains/]` (<https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars#h5c0df2e1-cfd2-469f-bb4a-c77d7c0cca6f>) option, this will list the domains that are authenticated.

- `**`authentication_option`**`

``string`` — Webinar authentication option ID.

- `**`auto_recording`**`

``string``, possible values: ``"local"``, ``"cloud"``, ``"none"``, default: ``"none"`` — Automatic recording. ``local`` — Record on local. ``cloud`` — Record on cloud. ``none`` — Disabled.

- `**`close_registration`**`

``boolean`` — Close registration after event date.

- `**`contact_email`**`

``string`` — Contact email for registration

- `**`contact_name`**`

``string`` — Contact name for registration

- `**`email_in_attendee_report`**`

``boolean`` — Whether to include guest's email addresses in webinars' attendee reports.

- `**`email_language`**`

``string`` — Set the email language to one of the following. ``en-US``, ``de-DE``, ``es-ES``, ``fr-FR``, ``jp-JP``, ``pt-PT``, ``ru-RU``, ``zh-CN``, ``zh-TW``, ``ko-KO``, ``it-IT``, ``vi-VN``.

- `**`enable_session_branding`**`

``boolean`` — Whether the `[/Webinar Session Branding/]` setting is enabled. This setting lets hosts visually customize a webinar by setting a session background. This also lets hosts use `[/Webinar Session Branding/]` (<https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding>) to set the virtual background for and apply name tags to hosts, alternative hosts, panelists, interpreters, and speakers.

- `**`enforce_login`**`

``boolean`` — Only signed in users can join this meeting. `[/This field is deprecated and will not be supported in the future./]` As an alternative, use the `[/meeting_authentication/]`,

`\`authentication_option\``, and `\`authentication\_domains\`` fields to understand the `\[authentication configurations]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars)` set for the webinar.

- `\*\`enforce_login_domains\`\``

`\`string\`` — Only signed in users with specified domains can join meetings. `\*\`This field is deprecated and will not be supported in the future.\`\`` As an alternative, use the `\`meeting_authentication\``, `\`authentication\_option\``, and `\`authentication_domains\`` fields to understand the `\[authentication configurations]\(https://support.zoom.us/hc/en-us/articles/360037117472-Authentication-Profiles-for-Meetings-and-Webinars)` set for the webinar.

- `\*\`follow_up_absentees_email_notification\`\``

`\`object\`` — Send follow-up email to absentees.

- `\*\`enable\`\``

`\`boolean\`` — `\* \`true\`` - Send follow-up email to absentees. `\* \`false\`` - Do not send follow-up email to absentees.

- `\*\`type\`\``

`\`integer\``, possible values: `\`0, 1, 2, 3, 4, 5, 6, 7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 days after the scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- `\*\`follow_up_attendees_email_notification\`\``

`\`object\`` — Send follow-up email to attendees.

- `\*\`enable\`\``

`\`boolean\`` — `\* \`true\`` - Send follow-up email to attendees. `\* \`false\`` - Do not send follow-up email to attendees.

- `\*\`type\`\``

`\`integer\``, possible values: `\`0, 1, 2, 3, 4, 5, 6, 7\`` — `\`0\`` - No plan. `\`1\`` - Send 1 day after the scheduled end date. `\`2\`` - Send 2 days after the scheduled end date. `\`3\`` - Send 3 days after the scheduled end date. `\`4\`` - Send 4 days after the scheduled end date. `\`5\`` - Send 5 days after the scheduled end date. `\`6\`` - Send 6 days after the scheduled end date. `\`7\`` - Send 7 days after the scheduled end date.

- `\*\`global_dial_in_countries\`\``

`\`array\`` — List of global dial-in countries

`\*\`Items:\`\``

`\`string\``

- `\*\`hd_video\`\``

`\`boolean\``, default: `\`false\`` — Default to HD video.

- `\*\`hd_video_for_attendees\`\``

`\`boolean\``, default: `\`false\`` — Whether HD video for attendees is enabled.

- `\*\`host_video\`\``

`\`boolean\`` — Start video when host joins the webinar.

- `\*\`language_interpretation\`\``

`\`object\`` — The webinar's `\[language interpretation settings]\(https://support.zoom.com/hc/en/article?id=zm\_kb\&sysparm\_article=KB0064768)`. Make sure to add the language in the web portal in order to use it in the API. See link for details. `\*\`Note:\`\`` This feature is only available for certain Webinar add-on, Education, and Business and higher plans. If this feature is not enabled on the host's account, this setting will `\*\`not\`\`` be applied to the webinar. This is not supported for simulative webinars.

- `\*\`enable\`\``

`\`boolean\`` — Whether to enable `\[language interpretation]\(https://support.zoom.com/hc/en/article?id=zm\_kb\&sysparm\_article=KB0064768)` for the webinar.

- `\*\`interpreters\`\``

``array`` — Information about the webinar's language interpreters.

****Items:****

- ****`email`****

``string``, format: ``email`` — The interpreter's email address.

- ****`interpreter\_languages`****

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two languages. To get this value, use the ``language_interpretation`` object's ``languages`` and ``custom_languages`` values in the ``[*Get user settings*]`` (`/docs/api/users/#tag/users/GET/users/{userId}/settings`) API response. ``[*languages*]``: System-supported languages include ``English``, ``Chinese``, ``Japanese``, ``German``, ``French``, ``Russian``, ``Portuguese``, ``Spanish``, and ``Korean``. ``[*custom_languages*]``: User-defined languages added by the user. For example, an interpreter translating between English and French should use ``English,French``.

- ****`languages`****

``string`` — A comma-separated list of the interpreter's languages. The string must contain exactly two country IDs. Only system-supported languages are allowed: ``US`` (English), ``CN`` (Chinese), ``JP`` (Japanese), ``DE`` (German), ``FR`` (French), ``RU`` (Russian), ``PT`` (Portuguese), ``ES`` (Spanish), and ``KR`` (Korean). For example, to set an interpreter translating from English to Chinese, use ``US,CN``.

- ****`meeting\_authentication`****

``boolean`` — Only authenticated users can join the webinar.

- ****`notify\_registrants`****

``boolean`` — Send notification email to registrants when the host updates a webinar.

- ****`on\_demand`****

``boolean``, default: ``false`` — Make the webinar on-demand.

- ****`panelist\_authentication`****

``boolean`` — Require panelists to authenticate to join.

- ****`panelists\_invitation\_email\_notification`****

``boolean`` — Send invitation email to panelists. If ``false``, do not send invitation email to panelists.

- ****`panelists\_video`****

``boolean`` — Start video when panelists join the webinar.

- ****`post\_webinar\_survey`****

``boolean`` — Zoom will open a survey page in attendees' browsers after leaving the webinar.

- ****`practice\_session`****

``boolean``, default: ``false`` — Enable practice session.

- ****`question\_and\_answer`****

``object`` — ``[Q&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.)`` for webinar.

- ****`allow\_anonymous\_questions`****

``boolean`` — ``true`` - Allow participants to send questions without providing their name to the host, co-host, and panelists.. ``false`` - Do not allow anonymous questions.

- ****`allow\_auto\_reply`****

``boolean`` — If simulive webinar, ``true`` - allow auto-reply to attendees. ``false`` - don't allow auto-reply to the attendees.

- ****`allow\_submit\_questions`****

``boolean`` — ``true`` - Allow participants to submit questions. ``false`` - Do not allow submit questions.

- ****`answer\_questions`****

``string``, possible values: ``"only", "all"`` — Indicate whether you want attendees to be able to view answered questions only or view all questions. ``\* `only\`` - Attendees are able to view answered questions only. ``\* `all\`` - Attendees are able to view all questions submitted in the Q&A.

- `**`attendees_can_comment`**`

``boolean`` — ``\* `true\`` - Attendees can answer questions or leave a comment in the question thread. ``\* `false\`` - Attendees can't answer questions or leave a comment in the question thread.

- `**`attendees_can_upvote`**`

``boolean`` — ``\* `true\`` - Attendees can click the thumbs up button to bring popular questions to the top of the Q&A window. ``\* `false\`` - Attendees can't click the thumbs up button on questions.

- `**`auto_reply_text`**`

``string`` — If ``allow\_auto\_reply\`` = true, the text to be included in the automatic response.

- `**`enable`**`

``boolean`` — ``\* `true\`` - Enable ``[Q&A](https://support.zoom.us/hc/en-us/articles/203686015-Using-Q-A-as-the-webinar-host#:~:text=Overview,and%20upvote%20each%20other's%20questions.)`` for webinar. ``\* `false\`` - Disable Q&A for webinar.

- `**`registrants_confirmation_email`**`

``boolean`` — Send confirmation email to registrants

- `**`registrants_email_notification`**`

``boolean`` — Send email notifications to registrants about approval, cancellation, denial of the registration. The value of this field must be set to true in order to use the ``registrants\_confirmation\_email\`` field.

- `**`registrants_restrict_number`**`

``integer``, default: ``0`` — Restrict number of registrants for a webinar. By default, it is set to ``0``. A ``0`` value means that the restriction option is disabled. Provide a number higher than 0 to restrict the webinar registrants by the that number.

- `**`registration_type`**`

``integer``, possible values: ``1, 2, 3``, default: ``1`` — Registration types. Only used for recurring webinars with a fixed time. ``1`` - Attendees register once and can attend any of the webinar sessions. ``2`` - Attendees need to register for each session in order to attend. ``3`` - Attendees register once and can choose one or more sessions to attend.

- `**`request_permission_to_unmute_participants`**`

``boolean`` — Whether to enable the ``[Request permission to unmute participants](https://support.zoom.us/hc/en-us/articles/203435537-Muting-and-unmuting-participants-in-a-meeting)`` setting. Not supported for simulive webinar. This option cannot be used together with ``allow\_host\_control\_participant\_mute\_state\``, only one of the two can be enabled at a time.

- `**`send_1080p_video_to_attendees`**`

``boolean``, default: ``false`` — Always send 1080p video to attendees.

- `**`show_join_info`**`

``boolean`` — Whether to show the webinar's join information on the registration confirmation page. This setting is only applied to webinars with registration enabled.

- `**`show_share_button`**`

``boolean`` — Show social share buttons on the registration page.

- `**`sign_language_interpretation`**`

``object`` — The webinar's ``[sign language interpretation settings](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)``. Make sure to add the language in the web portal in order to use it in the API. See link for details. ``\*Note\*`` If this feature is not enabled on the host's account, this setting will ``\*not\*`` be applied to the webinar.

- `**`enable`**`

``boolean`` — Whether to enable ``[sign language interpretation](https://support.zoom.us/hc/en-us/articles/9644962487309-Using-sign-language-interpretation-in-a-meeting-or-webinar)`` for the webinar.


```

- ``interpreters``

  `array` — Information about the webinar's sign language interpreters.

  Items:

- ``email``

  `string`, format: `email` — The interpreter's email address.

- ``sign_language``

  `string` — The interpreter's sign language. To get this value, use the
  `sign_language_interpretation` object's `languages` and `custom_languages` values in the `[*Get
  user settings*]` (/api-reference/zoom-api/methods#operation/userSettings) API response.

- ``survey_url``

  `string` — Survey url for post webinar survey

- ``simulive_delay_start``

  `object` — {"enable":false,"time":0,"timeunit":"second"}

- ``enable``

  `boolean` — Whether simulive need delay playback.

- ``time``

  `integer` — The time for delayed playback. If the time unit is seconds, then the maximum value is 60
  and the minimum value is 1. If the time unit is minutes, then the maximum value is 10 and the minimum value
  is 1.

- ``timeunit``

  `string`, possible values: `second`, `minute`, default: `second` — The time unit for delayed
  playback. `second` - The time unit for delayed playback is seconds. `minute` - The time unit for delayed
  playback is minutes.

- ``start_time``

  `string`, format: `date-time` — Webinar start time, in the format `yyyy-MM-dd'T'HH:mm:ss'Z'`. Should be
  in GMT time. In the format `yyyy-MM-dd'T'HH:mm:ss`. This should be in local time and the timezone should
  be specified. Only used for scheduled webinars and recurring webinars with a fixed time.

- ``timezone``

  `string` — The timezone to assign to the `start_time` value. This field is only used for scheduled or
  recurring webinars with a fixed time. For a list of supported timezones and their formats, see our
  [timezone list] (/docs/api/references/abbreviations/#timezones).

- ``topic``

  `string` — The webinar topic.

- ``tracking_fields``

  `array` — Tracking fields.

  Items:

- ``field``

  `string` — Tracking fields type.

- ``value``

  `string` — Tracking fields value.

- ``transition_to_live``

  `boolean` — Whether to transition a simulive webinar to live. The host must be present at the time of
  transition.

- ``type``

  `integer`, possible values: `5`, `6`, `9`, default: `5` — Webinar types. `5` - webinar. `6` - Recurring
  webinar with no fixed time. `9` - Recurring webinar with a fixed time.

```

****Example:****

```
```json
{
 "agenda": "My Webinar",
 "duration": 60,
 "password": "123456",
 "schedule_for": "jchill@example.com",
 "recurrence": {
 "end_date_time": "2022-04-02T15:59:00Z",
 "end_times": 7,
 "monthly_day": 1,
 "monthly_week": 1,
 "monthly_week_day": 1,
 "repeat_interval": 1,
 "type": 1,
 "weekly_days": "1"
 },
 "settings": {
 "additional_data_center_regions": [
 "TY"
],
 "allow_multiple_devices": true,
 "alternative_hosts": "jchill@example.com",
 "alternative_host_update_polls": true,
 "approval_type": 0,
 "attendees_and_panelists_reminder_email_notification": {
 "enable": true,
 "type": 0
 },
 "audio": "telephony",
 "audio_conference_info": "test",
 "authentication_domains": "example.com",
 "authentication_option": "signIn_D8cJuqWVQ623CI4Q8yQK0Q",
 "auto_recording": "cloud",
 "contact_email": "jchill@example.com",
 "contact_name": "Jill Chill",
 "email_language": "en-US",
 "follow_up_absentees_email_notification": {
 "enable": true,
 "type": 0
 },
 "follow_up_attendees_email_notification": {
 "enable": true,
 "type": 0
 },
 "global_dial_in_countries": [
 "US"
],
 "hd_video": false,
 "hd_video_for_attendees": false,
 "host_video": true,
 "language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "interpreter_languages": "English,French"
 }
]
 },
 "sign_language_interpretation": {
 "enable": true,
 "interpreters": [
 {
 "email": "interpreter@example.com",
 "sign_language": "American"
 }
]
 },
 "panelist_authentication": true,
 "meeting_authentication": true,
 "add_watermark": true,
 "add_audio_watermark": true,
 "notify_registrants": true,
 "on_demand": false,
 "panelists_invitation_email_notification": true,
 "panelists_video": true,
 "post_webinar_survey": true,
 "practice_session": false,
 }
}
```

```

"question_and_answer": {
 "allow_submit_questions": true,
 "allow_anonymous_questions": true,
 "answer_questions": "all",
 "attendees_can_comment": true,
 "attendees_can_upvote": true,
 "allow_auto_reply": true,
 "auto_reply_text": "Thank you for your question. We will get back to you shortly.",
 "enable": true
},
"registrants_confirmation_email": true,
"registrants_email_notification": true,
"registrants_restrict_number": 100,
"registration_type": 1,
"send_1080p_video_to_attendees": false,
"show_share_button": true,
"show_join_info": true,
"survey_url": "https://example.com",
"enable_session_branding": true,
"request_permission_to_unmute_participants": true,
"allow_host_control_participant_mute_state": false,
"email_in_attendee_report": true
},
"start_time": "2022-03-26T07:18:32Z",
"timezone": "America/Los_Angeles",
"topic": "My webinar",
"tracking_fields": [
 {
 "field": "field1",
 "value": "value1"
 }
],
"type": 5,
"is_simulive": true,
"record_file_id": "f09340e1-cdc3-4eae-9a74-98f9777ed908",
"transition_to_live": false,
"simulive_delay_start": {
 "enable": true,
 "time": 10,
 "timeunit": "second"
}
}
},

```

#### #### Responses

##### Status: 204 `HTTP Status Code: 204` Webinar updated.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3003` `Users in {domains} have been blocked from joining meetings and webinars. To unblock them, go to the Settings page in the Zoom web portal and update the Block users in specific domains from joining meetings and webinars setting.` `Error Code: 3000` `You cannot update or delete simulive webinars that have started using this method.` `Error Code: 300` `The value that you entered for the schedule_for field is invalid. Enter a valid value and try again.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action: {userId}.` `Error Code: 300` `Invalid webinar ID.` `Error Code: 200` `No permission.` `Error Code: 4505` `Simulive can't select No Fixed Time.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](/docs/api/rate-limits/).`

#### ### Perform batch registration

```

- Method: POST
- Path: /webinars/{webinarId}/batch_registrants
- Tags: Webinars

```

Register up to 30 registrants at once for a scheduled webinar that requires [registration] (<https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-webinar-with-registration>).

#### **Prerequisites:**

- The webinar host must be a licensed user.
- The webinar should be type `5`, a scheduled webinar. Other types of webinars are not supported by this API.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write`, `webinar:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write:batch\_registrants`, `webinar:write:batch\_registrants:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `HEAVY`

#### #### Request Body

##### Content-Type: application/json

- **\*\*`auto\_approve`\*\***

`boolean` — If a meeting was scheduled with approval\\_type `1` (manual approval), but you want to automatically approve registrants added via this API, set the value of this field to `true`. You **cannot** use this field to change approval setting for a meeting that was originally scheduled with approval\\_type `0` (automatic approval).

- **\*\*`registrants`\*\***

`array`

**\*\*Items:\*\***

- **\*\*`email` (required)\*\***

`string`, format: `email` — The registrant's email address.

- **\*\*`first\_name` (required)\*\***

`string` — The registrant's first name.

- **\*\*`last\_name`\*\***

`string` — The registrant's last name.

**\*\*Example:\*\***

```
```json
{
  "auto_approve": true,
  "registrants": [
    {
      "email": "jchill@example.com",
      "first_name": "Jill",
      "last_name": "Chill"
    }
  ]
}
```

Responses

Status: 201 ****HTTP Status Code:**** `200` ****OK**** Registrants added.

Content-Type: application/json

- ****`registrants`****

`array`

****Items:****

- ****`email`****

`string` — The registrant's email address.

- ****`join\_url`****

`string` — Unique URL using which registrant can join the webinar.

- ****`registrant\_id`****

`string` — The registrant's unique identifier.

****Example:****

```
```json
{
```

```

"registrants": [
 {
 "email": "jchill@example.com",
 "join_url": "https://example.com/j/11111",
 "registrant_id": "-r0ym-zdTH0dbT3A7u7u5g"
 }
]
}
}

```

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 200   
 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.   
 **Error Code:** 300   
 This API can only be used for scheduled webinars (type 5). Batch registration is not supported for other webinar types.   
 **Error Code:** 3038   
 The webinar is over. You cannot register now. If you have any questions, contact the webinar's host.   
 **Error Code:** 3000   
 You have reached the limit for the number of attendees you can add. Contact Zoom Support for more information.   
 **Error Code:** 3000   
 The Zoom REST API does not support paid registration.   
 **Error Code:** 3043   
 Webinar has reached maximum attendee capacity.   
 **Error Code:** 3000   
 Registration has not been enabled for this webinar: {webinarId}.   
 **Error Code:** 300   
 Invalid webinar ID.   
 **Error Code:** 200   
 No permission.

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001   
 Webinar does not exist: {webinarId}.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests**. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Get webinar's session branding

```

- Method: GET
- Path: /webinars/{webinarId}/branding
- Tags: Webinars

```

Get the webinar's [session branding](https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding) information. Session branding lets hosts visually customize a webinar by setting a webinar wallpaper that displays behind video tiles. Session branding also lets hosts set the virtual background for and apply name tags to hosts, alternative hosts, panelists, interpreters, and speakers.

#### Prerequisites

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.
- Enable the **Webinar Session Branding** setting.

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **webinar:read**, **webinar:read:admin**

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **webinar:read:branding**, **webinar:read:branding:admin**

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

### Responses

##### Status: 200 **HTTP Status Code:** 200 **Webinar session branding returned.**

##### Content-Type: application/json

```

- name_tags
 array — Information about the webinar's name tag.
 items:
 - accent_color
 string — The name tag's accent color.
 - background_color
 string — The name tag's background color.
 - id
 string — The name tag's ID.
 - is_default
 boolean — Whether the file is the default name tag or not.

```

```

- **`name`**

 `string` — The name tag's name.

- **`text_color`**

 `string` — The name tag's text color.

- **`virtual_backgrounds`**

 `array` — Information about the webinar's \[virtual background]\(https://support.zoom.us/hc/en-us/articles/210707503-Virtual-Background) files.

Items:

- **`id`**

 `string` — The virtual background's file ID.

- **`is_default`**

 `boolean` — Whether the file is the default virtual background file.

- **`name`**

 `string` — The virtual background's file name.

- **`wallpaper`**

 `object` — Information about the webinar's \[wallpaper] file.

- **`id`**

 `string` — The wallpaper's file ID.

```

**\*\*Example:\*\***

```

```json
{
  "wallpaper": {
    "id": "zazQjwDuQkS3Q2EprNd7jQ"
  },
  "virtual_backgrounds": [
    {
      "id": "zazQjwDuQkS3Q2EprNd7jQ",
      "name": "beach.jpg",
      "is_default": true
    }
  ],
  "name_tags": [
    {
      "id": "zazQjwDuQkS3Q2EprNd7jQ",
      "name": "name",
      "text_color": "0e72ed",
      "accent_color": "0e72ed",
      "background_color": "0e72ed",
      "is_default": true
    }
  ]
}
```

```

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`3000\` \<br> You cannot enable session branding for this webinar. \<br> \\*\\*Error Code:\\*\\* \`300\` \<br> Invalid webinar ID. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> No permission. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Create a webinar's branding name tag

```

- **Method:** `POST`
- **Path:** `/webinars/{webinarId}/branding/name_tags`
- **Tags:** Webinars

```

Create a webinar's [session branding](https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding) name tag. There's a limit of 20 name tags per webinar. **\*\*Prerequisites:\*\***

- The **\*\*Webinar Session Branding\*\*** setting enabled.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write`, `webinar:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write:branding\_name\_tag`, `webinar:write:branding\_name\_tag:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

#### Request Body

##### Content-Type: application/json

- **\*\*`accent\_color` (required)\*\***

  `string`, format: `Hex color code` — The name tag's accent color.

- **\*\*`background\_color` (required)\*\***

  `string`, format: `Hex color code` — The name tag's background color.

- **\*\*`name` (required)\*\***

  `string` — The name tag's name. **\*\*Note:\*\*** This value cannot exceed more than 50 characters.

- **\*\*`text\_color` (required)\*\***

  `string`, format: `Hex color code` — The name tag's text color.

- **\*\*`is\_default`\*\***

  `boolean`, default: `false` — Whether set the name tag as the default name tag or not.

- **\*\*`set\_default\_for\_all\_panelists`\*\***

  `boolean`, default: `true` — Whether to set the name tag as the new default for all panelists or not. This includes panelists not currently assigned a default name tag.

**\*\*Example:\*\***

```
```json
{
  "name": "name",
  "text_color": "0e72ed",
  "accent_color": "0e72ed",
  "background_color": "0e72ed",
  "is_default": true,
  "set_default_for_all_panelists": true
}
```

Responses

Status: 201 ****HTTP Status Code:**** `201` Name tag created.

Content-Type: application/json

- ****`accent\_color`****

 `string` — The name tag's accent color.

- ****`background\_color`****

 `string` — The name tag's background_color color.

- ****`id`****

 `string` — The name tag's ID.

- ****`is\_default`****

 `boolean` — Whether the name tag is the default name tag or not.

- ****`name`****

 `string` — The name tag's name.

- **text_color**

`string` — The name tag's text color.

Example:

`json`

```
{
  "id": "J0sFXN2PS0CGrqTqLRwgAQ",
  "name": "name",
  "text_color": "0e72ed",
  "accent_color": "0e72ed",
  "background_color": "0e72ed",
  "is_default": true
}
```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.` `Error Code: 3000` `This webinar does not have session branding enabled.` `Error Code: 3000` `You have reached the limit for the number of name tags you can add for this webinar. The limit is 20.` `Error Code: 300` `Invalid webinar ID.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

Delete a webinar's branding name tag

- **Method:** `DELETE`
 - **Path:** `/webinars/{webinarId}/branding/name_tags`
 - **Tags:** Webinars

Delete a webinar's [session branding](https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding) name tag.

Prerequisites:

- The **Webinar Session Branding** setting enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:write`, `webinar:write:admin`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:delete:branding_name_tag`, `webinar:delete:branding_name_tag:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 204 `HTTP Status Code: 204` `No content.` `Name tag(s) deleted.`

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid parameter: {name_tag_ids}.` `Error Code: 3000` `This webinar does not have session branding enabled.` `Error Code: 3000` `Invalid webinar ID.` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

Update a webinar's branding name tag

- **Method:** `PATCH`
 - **Path:** `/webinars/{webinarId}/branding/name_tags/{nameTagId}`
 - **Tags:** Webinars

Update a webinar's [session branding](https://support.zoom.us/hc/en-us/articles/4836268732045-Using-Webinar-Session-Branding) name tag. **Prerequisites:**

- The **Webinar Session Branding** setting enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):


```
`webinar:write`,`webinar:write:admin`
```

```
**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
`webinar:update:branding_name_tag`,`webinar:update:branding_name_tag:admin`
```

```
**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `MEDIUM`
```

```
#### Request Body
```

```
##### Content-Type: application/json
```

```
- **`accent_color`**
```

```
`string`, format: `Hex color code` — The name tag's accent color.
```

```
- **`background_color`**
```

```
`string`, format: `Hex color code` — The name tag's background color.
```

```
- **`is_default`**
```

```
`boolean`, default: `false` — Whether set the name tag as the default name tag or not.
```

```
- **`name`**
```

```
`string` — The name tag's name. \\*\\*Note:\\*\\* This value cannot exceed more than 50 characters.
```

```
- **`set_default_for_all_panelists`**
```

```
`boolean`, default: `true` — Whether to set the name tag as the new default for all panelists or not, including panelists not currently assigned a default name tag.
```

```
- **`text_color`**
```

```
`string`, format: `Hex color code` — The name tag's text color.
```

```
**Example:**
```

```
```json  
{
 "name": "name",
 "text_color": "0e72ed",
 "accent_color": "0e72ed",
 "background_color": "0e72ed",
 "is_default": true,
 "set_default_for_all_panelists": true
}
```
```

```
#### Responses
```

```
##### Status: 204 \\*\\*HTTP Status Code:\\*\\* \\204\\` \\* No content. \\* Name tag updated.
```

```
##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \\400\\` \\<br> Bad Request \\*\\*Error Code:\\*\\* \\3000\\` \\<br>  
This webinar does not have session branding enabled. \\<br> \\*\\*Error Code:\\*\\* \\300\\` \\<br> Invalid webinar  
ID. \\<br> \\*\\*Error Code:\\*\\* \\200\\` \\<br> No permission. \\<br> \\*\\*Error Code:\\*\\* \\200\\` \\<br> Webinar  
plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to  
perform this action. \\<br> \\*\\*Error Code:\\*\\* \\300\\` \\<br> Name Tag does not exist. \\<br>
```

```
##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \\404\\` \\<br> Not Found \\*\\*Error Code:\\*\\* \\3001\\` \\<br>  
Webinar does not exist: {webinarId}. \\<br>
```

```
##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \\429\\` \\<br> Too Many Requests. For more information, see \\  
[rate limits]\\(https://developers.zoom.us/docs/api/rest/rate-limits/).
```

```
### Upload a webinar's branding virtual background
```

```
- **Method:** `POST`
```

```
- **Path:** /webinars/{webinarId}/branding/virtual_backgrounds`
```

```
- **Tags:** Webinars
```

Upload a webinar's session branding [virtual background](https://support.zoom.us/hc/en-us/articles/210707503-Virtual-Background). Hosts and panelists can select and use these virtual backgrounds during the webinar. Branding virtual background files have these restrictions:

- A webinar cannot exceed more than 10 virtual background files.
- You can only upload image files that are in JPG/JPEG, GIF or PNG format.
- The virtual background file size cannot exceed 15 megabytes (MB).

```
**Prerequisites:**
```

- The **Webinar Session Branding** setting enabled.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:write` , `webinar:write:admin``

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:write:branding_virtual_background` , `webinar:write:branding_virtual_background:admin``

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `MEDIUM``

Request Body

Content-Type: multipart/form-data

- **file** (required)

`string`` — The virtual background's file path, in binary format.

- **default**

`boolean``, default: `false`` — Whether set the file as the default virtual background file.

- **set_default_for_all_panelists**

`boolean``, default: `true`` — Whether to set the virtual background file as the new default for all panelists. This includes panelists not currently assigned a default virtual background.

Example:

```
```json
{
 "file":
"Vm0wd2QyUXlVWGxXYTJoV1YwZG9WVl13Wkc5a1JsWjBUVlpPV0Zac2JETlhMUpUVmpGYWMySkVUbGhoTWsweFZqQmFTMk15U2tWVWJHaG9U
VmhDVVZadGVGWmxSbGw1Vkd0c2FsSnRhRz1VVjNOM1pVWmFkR05GZEZSTlZUVkpWbTEwYTfkSFNrZGpSVGxhWWxoU1RGWnNXbUZR1pFWlNubFpY
ZHpGV2EyUXdZekpHVjF0dVVsWmhlbXhoVm1wT2IyRkdjRmRYYlVaclVqRmFTVnBGV2x0VWJGcFZWbXhzVjFaNlFYaFdSRXBIVWpGT2RWVnNXbWx
TTW1odlZtMXdUMk15UmtkWGJHUL1ZbGhTV0ZSV2FFTlRiR3QzV2tSU1ZrMXJjRmhWTWSoelZqRmF0bEZZYUZkU1JWcDZWbXBHVDJSV1ZuUmhSazVz
WWxob1dGWnRNSGhPUjFGM1RVaG9hbEp0VWxsWmJHaFRWMPFpTVjFkdFJteFdiVko1VmpKNFQyRkdXbk5qU0d4WFRWZG9NMVpxUmtwbGJWVWk1ZVp
vVjJKV1NrbFdiWEJIVkRGA1YyTkZaR2hTTW5oVZGY3hiMWRzV1hoWGJYUk9VbTE0V0ZVeGFHOWhiRXBYVjJ4U1dtSkdXbWhaTVZwelkYeHdSMVJy
TlZ0aWEwcElWbXBLTkZReFdsFRhMlJxVWtWYVYxWnFUa05YUmxweFVtdHdiR0pWV2tsWlZWchJZVWRGZUd0SE9WZFdSVXBvVmtSS1QyUkdUbkhk
UmXKcFZqTm9kbFpHVM05Uk1XULhWMWhvWVZKR1NtRlpha1pIVGtaWmVHRkhPVMRpVlhCSlZsZDRjMWR0U2tkWGGJXaFhUVVp3ZWxreWVIZFNNV
kowWlVaa2FWSXpZM2hXTW5oWFZqRlJlRmRZWkU1WFJYQl1XVmR6TVZsV1VsWlhibVJYVW14d2VGvNrNWRXTURGeVRsVm9WMUo2Umt0V1ZFWkxWakp
PUmxac1pHbFNNVYyZVmxU1IxbFdXbkpOVmxwWFlYcFdWRlZyVmtaT1VUMDk=",
 "default": true,
 "set_default_for_all_panelists": true
}
```
```

Responses

Status: 201 `*`HTTP Status Code: `*` `201` Virtual background uploaded.`

Content-Type: application/json

- **id**

`string`` — The virtual background file's ID.

- **is_default**

`boolean`` — Whether the file is the default virtual background file.

- **name**

`string`` — The virtual background file's name.

- **size**

`integer`` — The virtual background file's size, in bytes.

- **type**

`string``, possible values: `"image"`` — The virtual background file's file type. `*`image`` - An image file.

Example:

```
```json
{
 "id": "J0sFXN2PSOCGrqTqLRwgAQ",

```

```

 "name": "beach.jpg",
 "is_default": true,
 "size": 524288,
 "type": "image"
 },
 \,

```

```

Status: 400 **HTTP Status Code:** `400` \
 Bad Request **Error Code:** `3000` \

This webinar does not have session branding enabled. \
 Error Code: `120` \
 You may only
upload JPG/JPEG, GIF, or PNG image files. \
 Error Code: `120` \
 No file uploaded. Verify
that a file has been uploaded. \
 Error Code: `120` \
 File size cannot exceed 15M. \

Error Code: `120` \
 A maximum of 10 files are allowed for a webinar. \
 Error Code:
`300` \
 Invalid webinar ID. \
 Error Code: `200` \
 No permission. \
 **Error
Code:** `200` \
 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars
for this user in order to perform this action. \


```

```

Status: 404 **HTTP Status Code:** `404` \
 Not Found **Error Code:** `3001` \

Webinar does not exist: {webinarId}. \


```

```

Status: 429 **HTTP Status Code:** `429` \
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

```

### Delete a webinar's branding virtual backgrounds

```

- **Method:** `DELETE`
- **Path:** `/webinars/{webinarId}/branding/virtual_backgrounds`
- **Tags:** Webinars

```

Delete a webinar's session branding [virtual background](https://support.zoom.us/hc/en-us/articles/210707503-Virtual-Background).

**\*\*Prerequisites:\*\***

- The **\*\*Webinar Session Branding\*\*** setting enabled.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:write`, `webinar:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:delete:branding\_virtual\_background`, `webinar:delete:branding\_virtual\_background:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

#### Responses

```

Status: 204 **HTTP Status Code:** `204` \
 \
 No content. \
 \
 Virtual background file(s) deleted.

```

```

Status: 400 **HTTP Status Code:** `400` \
 Bad Request **Error Code:** `300` \

Invalid parameter: `ids`. \
 Error Code: `3000` \
 This webinar does not have session
branding enabled. \
 Error Code: `300` \
 Invalid webinar ID. \
 Error Code:
`200` \
 No permission. \
 Error Code: `200` \
 Webinar plan is missing. You must
subscribe to the webinar plan and enable webinars for this user in order to perform this action. \


```

```

Status: 404 **HTTP Status Code:** `404` \
 Not Found **Error Code:** `3001` \

Webinar does not exist: {webinarId}. \


```

```

Status: 429 **HTTP Status Code:** `429` \
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

```

### Set webinar's default branding virtual background

```

- **Method:** `PATCH`
- **Path:** `/webinars/{webinarId}/branding/virtual_backgrounds`
- **Tags:** Webinars

```

Set a webinar's default session branding [virtual background](https://support.zoom.us/hc/en-us/articles/210707503-Virtual-Background).

**\*\*Prerequisites:\*\***

- The **\*\*Webinar Session Branding\*\*** setting enabled.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:write`, `webinar:write:admin`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:update:branding\_virtual\_background`, `webinar:update:branding\_virtual\_background:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

## #### Responses

##### Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` `\* No content. \* Virtual background updated.`

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br> Bad Request \*\*Error Code:\*\* \`300\`` `\<br> Invalid parameter: {id} \<br> \*\*Error Code:\*\* \`3000\`` `\<br> This webinar does not have session branding enabled. \<br> \*\*Error Code:\*\* \`300\`` `\<br> Invalid webinar ID. \<br> \*\*Error Code:\*\* \`200\`` `\<br> No permission. \<br> \*\*Error Code:\*\* \`200\`` `\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>`

##### Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br> Not Found \*\*Error Code:\*\* \`3001\`` `\<br> Webinar does not exist: {webinarId}. \<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).`

## ### Upload a webinar's branding wallpaper

- `**Method:** \`POST\``  
 - `**Path:** \`/webinars/{webinarId}/branding/wallpaper\``  
 - `**Tags:** Webinars`

Upload a webinar's session branding wallpaper file. Webinar branding wallpaper files have these requirements:

- A webinar can only have one wallpaper file.
- You can only upload image files that are in JPG/JPEG, GIF, or PNG format.
- Image files must be 16:9 ratio. The recommended image size is 1920 x 1080 pixels.
- The wallpaper file size cannot exceed 15 megabytes.

`**Prerequisites:**`

- The `**Webinar Session Branding**` setting enabled.

`**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**`  
`\`webinar:write\`,`webinar:write:admin\``

`**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**`  
`\`webinar:write:branding_wallpaper\`,`webinar:write:branding_wallpaper:admin\``

`**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**` `\`MEDIUM\``

## #### Request Body

##### Content-Type: multipart/form-data

- `**\`file\` (required)**`  
`\`string\`` — The wallpaper's file path, in binary format.

`**Example:**`

```
``json
{
 "file": ""
},
,
```

## #### Responses

##### Status: 201 `\*\*HTTP Status Code:\*\* \`201\`` `Webinar wallpaper uploaded.`

##### Content-Type: application/json

- `**\`id\`**`  
`\`string\`` — The wallpaper file's ID.
- `**\`name\`**`  
`\`string\`` — The wallpaper file's name.
- `**\`size\`**`  
`\`integer\`` — The wallpaper file's size, in bytes.
- `**\`type\`**`  
`\`string\``, possible values: `\`"image"\`` — The wallpaper file's file type. `\*\`image\`` - An image file.

**\*\*Example:\*\***

```
```json
{
  "id": "zazQjwDuQkS3Q2EprNd7jQ",
  "name": "logo.jpg",
  "size": 262144,
  "type": "image"
}
```
```

##### Status: 400 **\*\*HTTP Status Code:\*\*** 400 **\*\*Error Code:\*\*** 3000 **\*\*Message:\*\*** Bad Request  
This webinar does not have session branding enabled. **\*\*Error Code:\*\*** 120 **\*\*Message:\*\*** No file uploaded. Verify that a file has been uploaded. **\*\*Error Code:\*\*** 120 **\*\*Message:\*\*** File size cannot exceed 15M. **\*\*Error Code:\*\*** 120 **\*\*Message:\*\*** You can only upload JPG/JPEG, GIF, or PNG image files. **\*\*Error Code:\*\*** 300 **\*\*Message:\*\*** Invalid webinar ID. **\*\*Error Code:\*\*** 200 **\*\*Message:\*\*** No permission. **\*\*Error Code:\*\*** 200 **\*\*Message:\*\*** Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

##### Status: 404 **\*\*HTTP Status Code:\*\*** 404 **\*\*Error Code:\*\*** 3001 **\*\*Message:\*\*** Not Found  
Webinar does not exist: {webinarId}.

##### Status: 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Message:\*\*** Too Many Requests. For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Delete a webinar's branding wallpaper

```
- **Method:** DELETE
- **Path:** /webinars/{webinarId}/branding/wallpaper
- **Tags:** Webinars
```

Delete a webinar's session branding wallpaper file.

**\*\*Prerequisites:\*\***

- The **\*\*Webinar Session Branding\*\*** setting enabled.

**\*\*[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **\*\*webinar:write, webinar:write:admin\*\***

**\*\*[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **\*\*webinar:delete:branding\_wallpaper, webinar:delete:branding\_wallpaper:admin\*\***

**\*\*[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **\*\*LIGHT\*\***

#### Responses

##### Status: 204 **\*\*HTTP Status Code:\*\*** 204 **\*\*Message:\*\*** No content. **\*\*Message:\*\*** Webinar wallpaper deleted.

##### Status: 400 **\*\*HTTP Status Code:\*\*** 400 **\*\*Error Code:\*\*** 300 **\*\*Message:\*\*** Bad Request  
Invalid webinar ID. **\*\*Error Code:\*\*** 3000 **\*\*Message:\*\*** This webinar does not have session branding enabled. **\*\*Error Code:\*\*** 200 **\*\*Message:\*\*** No permission. **\*\*Error Code:\*\*** 200 **\*\*Message:\*\*** Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

##### Status: 404 **\*\*HTTP Status Code:\*\*** 404 **\*\*Error Code:\*\*** 3001 **\*\*Message:\*\*** Not Found  
Webinar does not exist: {webinarId}.

##### Status: 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Message:\*\*** Too Many Requests For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Create webinar's invite links

```
- **Method:** POST
- **Path:** /webinars/{webinarId}/invite_links
- **Tags:** Webinars
```

Create a batch of invitation links for a webinar.

**\*\*Prerequisites:\*\***

- Business, Education or API Plan with the Webinar add-on.

**\*\*[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **\*\*webinar:write:admin, webinar:write\*\***

**\*\*[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): **\*\*webinar:write:invite\_links, webinar:write:invite\_links:admin\*\***

**\*\*[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **\*\*LIGHT\*\***

## #### Request Body

##### Content-Type: application/json

- **attendees**

`array` — The attendees list.

**Items:**- **name** (required)

`string` — User display name.

- **disable\_audio****boolean**, default: `false` — Whether to disable participant audio when joining the meeting. If not provided or set to `false`, the participant audio will follow the meeting's default settings.- **disable\_video****boolean**, default: `false` — Whether to disable participant video when joining the meeting. If not provided or set to `false`, the participant video will follow the meeting's default settings.- **ttl****integer**, format: `int64`, default: `7200` — The invite link's expiration time, in seconds. This value defaults to `7200`.**Example:**

``json

```
{
 "attendees": [
 {
 "name": "Jill Chill",
 "disable_video": false,
 "disable_audio": false
 }
],
 "ttl": 1000
}
```

## #### Responses

##### Status: 201 **HTTP Status Code:** `201` Webinar Invite Links Created

##### Content-Type: application/json

- **attendees**

`array` — The attendee list.

**Items:**- **join\_url**

`string` — The URL to join the meeting.

- **name**

`string` — The user's display name.

**Example:**

``json

```
{
 "attendees": [
 {
 "join_url": "https://example.com/j/11111",
 "name": "Jill Chill"
 }
]
}
```

##### Status: 400 **HTTP Status Code:** `400` **Bad Request** **Error Code:** `300` **Invalid Webinar Id.**  
**Error Code:** `200` **No permission.** **Error Code:** `200`

\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Get a webinar's join token for live streaming

```
- **Method:** `GET`
- **Path:** `/webinars/{webinarId}/jointoken/live_streaming`
- **Tags:** Webinars
```

Retrieve a webinar's archive token to allow live streaming. The join token lets a recording bot implemented using Zoom meeting SDK connect to a Zoom meeting **hosted by the issuer of the token**, and can call the streaming method automatically. It supports both regular live streaming and raw streaming.

**Prerequisites:**

- A Pro or higher plan with a Webinar add-on.
- The **Allow livestreaming of webinars** user setting enabled in the Zoom web portal.

**[Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
`webinar\_token:read:admin:live\_streaming`,`webinar\_token:read:live\_streaming`

**[Granular Scopes]**(https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):  
`webinar:read:live\_streaming\_token`,`webinar:read:live\_streaming\_token:admin`

**[Rate Limit Label]**(https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): **LIGHT**

##### Responses

##### Status: 200 \\*\\*HTTP Status Code:\\*\\* \`200\` Webinar live streaming token returned.

##### Content-Type: application/json

```
- **`expire_in`**
```

`integer`, format: `int64`, possible values: `120` — The number of seconds the join token is valid for before it expires. This value always returns `120`.

```
- **`token`**
```

`string` — The join token.

**Example:**

```
```json
{
  "expire_in": 120,
  "token": "2njt50mj"
}
```
```

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`300\` \<br> Invalid webinar ID. \<br> \\*\\*Error Code:\\*\\* \`124\` \<br> This API only supports OAuth2 authorization. \<br> \\*\\*Error Code:\\*\\* \`3000\` \<br> Not allowed to start live streaming. To use this feature, enable the \\*\\*Allow livestreaming of webinars\\*\\* setting in the \\*\\*Settings\\*\\* page of the Zoom web portal. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> No permission. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### Get a webinar's archive token for local archiving

```
- **Method:** `GET`
- **Path:** `/webinars/{webinarId}/jointoken/local_archiving`
- **Tags:** Webinars
```

Use this API to get a webinar's archive token to allow local archiving. The archive token allows a meeting SDK app or bot to get archive permission to access the webinar's raw audio and video media stream in real-time.

**\*\*Prerequisites:\*\***

- A Pro or higher plan with a Webinar Add-on.
- The **\*\*Archive meetings and webinars\*\*** account setting enabled in the Zoom web portal.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar\_token:read:admin:local\_archiving`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:read:local\_archiving\_token:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

**#### Responses**

**##### Status:** 200 `HTTP Status Code:` `200` Webinar local archiving token returned.

**##### Content-Type:** application/json

- **\*\*`expire\_in`\*\***

integer, format: `int64`, possible values: `120` — The number of seconds the archive token is valid for before it expires. This value always returns `120`.

- **\*\*`token`\*\***

string — The archive token.

**\*\*Example:\*\***

```
``json
{
 "expire_in": 120,
 "token": "2njt50mj"
},
```

**##### Status:** 400 `HTTP Status Code:` `400`   
 Bad Request **\*\*Error Code:\*\*** `300`   
 Invalid webinar ID.   
 **\*\*Error Code:\*\*** `124`   
 This API only supports OAuth2 authorization.   
 **\*\*Error Code:\*\*** `3000`   
 Not allowed to start local archiving. To use this feature, enable the **\*\*Archive meetings and webinars\*\*** setting in the **\*\*Settings\*\*** page of the Zoom web portal.   
 **\*\*Error Code:\*\*** `200`   
 No permission.   
 **\*\*Error Code:\*\*** `200`   
 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

**##### Status:** 404 `HTTP Status Code:` `404`   
 Not Found **\*\*Error Code:\*\*** `3001`   
 Webinar does not exist: {webinarId}.

**##### Status:** 429 `HTTP Status Code:` `429`   
 Too Many Requests For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

**### Get a webinar's join token for local recording**

- **\*\*Method:\*\*** `GET`  
 - **\*\*Path:\*\*** `/webinars/{webinarId}/jointoken/local\_recording`  
 - **\*\*Tags:\*\*** Webinars

Retrieve a webinar's join token to allow for local recording. The join token lets a recording bot implemented using Zoom Meeting SDK connect to a Zoom webinar. The recording bot can then automatically start locally recording. This supports both regular and raw local recording.

**\*\*Prerequisites:\*\***

- A Pro or higher plan with a Webinar add-on.
- The **\*\*Local recording\*\*** user setting enabled in the Zoom web portal.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar\_token:read:admin:local\_recording`, `webinar\_token:read:local\_recording`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:read:local\_recording\_token`, `webinar:read:local\_recording\_token:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

**#### Responses**

**##### Status:** 200 `HTTP Status Code:` `200` Webinar local recording token returned.

**##### Content-Type:** application/json



- **expire\_in**

`integer`, format: `int64`, possible values: `120` — The number of seconds the join token is valid for before it expires. This value always returns `120`.

- **token**

`string` — The join token.

**Example:**

`json`

```
{
 "expire_in": 120,
 "token": "2njt50mj"
}
```

#### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid webinar ID.` `Error Code: 124` `This API only supports OAuth2 authorization.` `Error Code: 3000` `Not allowed to start local recording. To use this feature, enable the Local Recording setting in the Settings page of the Zoom web portal.` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

#### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

#### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### Get live stream details

- **Method:** `GET`  
 - **Path:** `/webinars/{webinarId}/livestream`  
 - **Tags:** Webinars

Get a webinar's live stream configuration details, such as Stream URL, Stream Key and Page URL.

Zoom allows users to `[live stream a webinar](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service)` to a custom platform.

**Prerequisites:**

- Pro or higher plan with the webinar add-on.  
 - Live streaming details must have been `[configured](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h_01589a6f-a40a-4e18-a448-cb746e52ebc5)` for the webinar.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `webinar:read:admin`, `webinar:read`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `webinar:read:livestream`, `webinar:read:livestream:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

#### Responses

#### Status: 200 `HTTP Status Code: 200` `OK` Live stream details returned.

##### Content-Type: `application/json`

- **page\_url**

`string` — Live streaming page URL. This is the URL using which anyone can view the live stream of the webinar.

- **resolution**

`string` — The number of pixels in each dimension that the video camera can display.

- **stream\_key**

`string` — Stream key.

- **stream\_url**

`string` — Stream URL.

**\*\*Example:\*\***

```
```json
{
  "page_url": "https://example.com/livestream/123",
  "stream_key": "contact-it@example.com",
  "stream_url": "https://example.com/livestream",
  "resolution": "720p"
}
```
```

##### Status: 400 **\*\*HTTP Status Code:\*\*** 400 **\*\*Error Code:\*\*** Bad Request **\*\*Error Code:\*\*** 300 **\*\*Error Code:\*\*** Invalid webinar ID. **\*\*Error Code:\*\*** 200 **\*\*Error Code:\*\*** Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. **\*\*Error Code:\*\*** 200 **\*\*Error Code:\*\*** No permission. **\*\*Error Code:\*\*** 200 **\*\*Error Code:\*\*** The current user has not enabled the custom live streaming feature of the webinar.

##### Status: 404 **\*\*HTTP Status Code:\*\*** 404 **\*\*Error Code:\*\*** Not Found **\*\*Error Code:\*\*** 3001 **\*\*Error Code:\*\*** Webinar does not exist: {webinarId}.

##### Status: 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Error Code:\*\*** Too Many Requests For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

### Update a live stream

- **\*\*Method:\*\*** PATCH  
- **\*\*Path:\*\*** /webinars/{webinarId}/livestream  
- **\*\*Tags:\*\*** Webinars

Update a webinar's live stream information.

**\*\*Prerequisites:\*\***

- Pro or higher plan with the webinar add-on.
- Live streaming details must be [configured](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h_01589a6f-a40a-4e18-a448-cb746e52ebc5) ([https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h\\_01589a6f-a40a-4e18-a448-cb746e52ebc5](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h_01589a6f-a40a-4e18-a448-cb746e52ebc5)) for the webinar.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
webinar:write:admin, webinar:write

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
webinar:update:livestream, webinar:update:livestream:admin

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** LIGHT

#### Request Body

##### Content-Type: application/json

- **\*\*page\_url** (required)  
string, format: uri — The webinar live stream page's URL.
- **\*\*stream\_key** (required)  
string — The webinar live stream name and key.
- **\*\*stream\_url** (required)  
string — The webinar live stream URL.
- **\*\*resolution**  
string — The number of pixels in each dimension that the video camera can display, required when a user enables 1080p. Use a value of 720p or 1080p

**\*\*Example:\*\***

```
```json
{
  "page_url": "https://example.com/livestream/123",
  "stream_key": "contact-it@example.com",
  "stream_url": "https://example.com/livestream",
  "resolution": "720p"
}
```
```

## #### Responses

##### Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` Meeting live stream updated.

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br> Bad Request \*\*Error Code:\*\* \`300\`` `\<br> Invalid webinar ID. \<br> \*\*Error Code:\*\* \`200\`` `\<br> The current user has not enabled the custom live streaming feature of the webinar. \<br> \*\*Error Code:\*\* \`200\`` `\<br> No permission. \<br> \*\*Error Code:\*\* \`200\`` `\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>`

##### Status: 404 `\*\*HTTP Status Code:\*\* \`404\`` `\<br> Not Found \*\*Error Code:\*\* \`3001\`` `\<br> Webinar does not exist: {webinarId}. \<br>`

##### Status: 429 `\*\*HTTP Status Code:\*\* \`429\`` `\<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

## ### Update live stream status

- `\*\*Method:\*\* \`PATCH\``  
 - `\*\*Path:\*\* \`/webinars/{webinarId}/livestream/status\``  
 - `\*\*Tags:\*\* Webinars`

Let users [live stream a webinar](<https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service>) to a custom platform. Update the status of a webinar's live stream.

`\*\*Prerequisites:\*\*`

- Pro or higher plan with a Webinar Add-on.

- Live streaming details must be [configured]([https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h\\_01589a6f-a40a-4e18-a448-cb746e52ebc5](https://support.zoom.us/hc/en-us/articles/115001777826-Live-Streaming-Meetings-or-Webinars-Using-a-Custom-Service#h_01589a6f-a40a-4e18-a448-cb746e52ebc5)) for the webinar.

`\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`  
`\`webinar:write:admin\`,`webinar:write\``

`\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*`  
`\`webinar:update:livestream_status\`,`webinar:update:livestream_status:admin\``

`\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* \`LIGHT\``

## #### Request Body

##### Content-Type: application/json

- `\*\`action\`\*\*`

`\`string\``, possible values: `\`"start", "stop"\`` — Update the live stream's status. `\*\`start\`\`` - Start a webinar live stream. `\*\`stop\`\`` - Stop an ongoing webinar live stream.

- `\*\`settings\`\*\*`

`\`object\`` — Update the live stream session's settings. `\*\*Only\*\*` settings for a stopped live stream can be updated.

- `\*\`active_speaker_name\`\*\*`

`\`boolean\`` — Display the name of the active speaker during a live stream.

- `\*\`display_name\`\*\*`

`\`string\`` — Display the live stream's name.

`\*\*Example:\*\*`

```
``json
{
 "action": "start",
 "settings": {
 "active_speaker_name": true,
 "display_name": "Jill Chill"
 }
}
```

## #### Responses

##### Status: 204 `\*\*HTTP Status Code:\*\* \`204\`` Meeting live stream updated.

```
Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`300\` \

Invalid webinar ID. \
 Error Code: \`1001\` \
 User does not exist: {userId}. \
 **Error
Code:** \`200\` \
 No permission. \
 Error Code: \`3000\` \
 The current webinar is not
configured with a custom streaming service. \
 Error Code: \`200\` \
 Webinar plan is missing.
You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \

 Error Code: \`200\` \
 Webinar {webinarId} has not started. \
 Error Code:
\`3000\` \
 The current webinar is not configured with a custom streaming service. \

```

```
Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \

Webinar does not exist: {webinarId}. \

```

```
Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests. For more information, see \
[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).
```

### ### List panelists

```
- **Method:** `GET`
- **Path:** `/webinars/{webinarId}/panelists`
- **Tags:** Webinars
```

List all of a webinar's panelists.

Webinar panelists can view and send video, screen share, annotate, and do much more compared to webinar attendees.

**\*\*Prerequisites:\*\***

- Pro or a higher plan with [Webinar Add-on](https://zoom.us/webinar).

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:read:admin`, `webinar:read`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:read:list\_panelists`, `webinar:read:list\_panelists:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `MEDIUM`

### #### Responses

```
Status: 200 **HTTP Status Code:** \`200\` Webinar plan subscription missing. Enable webinar for
this user once the subscription is added.
```

```
Content-Type: application/json
```

**\*\*All of:\*\***

- **\*\*`panelists`\*\***

`array` — List of panelist objects.

**\*\*Items:\*\***

**\*\*All of:\*\***

- **\*\*`id`\*\***

`string` — Panelist's ID.

\* **\*\*`email`\*\***

`string`, format: `email` — Panelist's email. See [Email address display rules](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value details.

\* **\*\*`name`\*\***

`string` — The panelist's full name. \\*\\*Note\\*\\* This value cannot exceed more than 12 Chinese characters.

- **\*\*`join\_url`\*\***

`string` — Join URL.

\* **\*\*`name\_tag\_description`\*\***

`string` — The description for the name tag, such as the person's title.

\* **\*\*`name\_tag\_id`\*\***

`string` — The name tag ID to bind.

```

* **`name_tag_name`**

`string` — The panelist's name to display in the name tag.

* **`name_tag_pronouns`**

`string` — The pronouns to display in the name tag.

* **`virtual_background_id`**

`string` — The virtual background's ID.

- **`total_records`**

`integer` — Total records.

Example:

```json
{
  "panelists": [
    {
      "id": "Tg2b6GhcQKKbV7nSCbDKug",
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "join_url": "https://example.com/j/11111",
      "virtual_background_id": "xHhPyb8ERMCmiC5nPjFdQ",
      "name_tag_id": "xHhPyb8ERMCmiC5nPjFdQ",
      "name_tag_name": "name",
      "name_tag_pronouns": "pronouns",
      "name_tag_description": "description"
    }
  ],
  "total_records": 1
}
```

Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300 Invalid webinar ID. Error Code: 200 No permission. Error Code: 200 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

Status: 404 HTTP Status Code: 404 Not Found Error Code: 3001 Webinar does not exist: {webinarId}.

Status: 429 HTTP Status Code: 429 Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

Add panelists

- Method: POST
- Path: /webinars/{webinarId}/panelists
- Tags: Webinars

Panelists in a webinar can view and send video, screen share, annotate, and do much more compared to attendees in a webinar. [Add panelists](https://support.zoom.us/hc/en-us/articles/115005657826-Inviting-Panelists-to-a-Webinar#h_7550d59e-23f5-4703-9e22-e76bded1ed70) to a scheduled webinar.

Prerequisites:

- Pro or a higher plan with the [Webinar Add-on](https://zoom.us/webinar).

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): webinar:write:admin, webinar:write

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): webinar:write:panelist, webinar:write:panelist:admin

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): MEDIUM

Request Body

Content-Type: application/json

- panelists

`array` — List of panelist objects.

```

```

Items:

All of:

- **`email`**

 `string`, format: `email` — Panelist's email. See the \[email address display rules]\
 (https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value
 details.

- **`name`**

 `string` — The panelist's full name. **Note:** This value cannot exceed more than 12 Chinese
 characters.

* **`name_tag_description`**

 `string` — The description for the name tag, such the person's title.

* **`name_tag_id`**

 `string` — The name tag ID to bind.

* **`name_tag_name`**

 `string` — The panelist's name to display in the name tag.

* **`name_tag_pronouns`**

 `string` — The pronouns to display in the name tag.

* **`virtual_background_id`**

 `string` — The virtual background ID to bind.

```

**\*\*Example:\*\***

```

```json
{
  "panelists": [
    {
      "email": "jchill@example.com",
      "name": "Jill Chill",
      "virtual_background_id": "xHhPyb8ERMCmiC5njPjFdQ",
      "name_tag_id": "xHhPyb8ERMCmiC5njPjFdQ",
      "name_tag_name": "xHhPyb8ERMCmiC5njPjFdQ",
      "name_tag_pronouns": "pronouns",
      "name_tag_description": "description"
    }
  ]
}
```

```

**#### Responses**

```

Status: 201 **HTTP Status Code:** \`201\` Panelist created.

```

```

Content-Type: application/json

```

```

- **`id`**

 `string` — Webinar ID.

- **`updated_at`**

 `string`, format: `date-time` — The time when the panelist was added.

```

**\*\*Example:\*\***

```

```json
{
  "id": "95204914252",
  "updated_at": "2022-03-26T07:30:16Z"
}
```

```

```

Status: 400 **HTTP Status Code:** \`400\` \
 Bad Request **Error Code:** \`3000\` \
 You
have reached the limit for the number of panelists you can add. Contact Zoom Support for more information. \

 Error Code: \`200\` \
 No permission. \
 Error Code: \`200\` \
 Webinar plan
is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform

```

this action. \<br> \\*\\*Error Code:\\*\\* \`300\` \<br> Invalid webinar ID. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Remove all panelists

```
- **Method:** `DELETE`
- **Path:** `/webinars/{webinarId}/panelists`
- **Tags:** Webinars
```

Remove all the panelists from a webinar.

**\*\*Prerequisites:\*\***

- Pro or a higher plan with the [webinar add-on](https://zoom.us/webinar).

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:write:admin`, `webinar:write`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:delete:panelist`, `webinar:delete:panelist:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

### #### Responses

##### Status: 204 \\*\\*HTTP Status Code:\\*\\* \`204\` Panelists removed.

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`300\` \<br> Invalid webinar ID. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> No permission. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Remove a panelist

```
- **Method:** `DELETE`
- **Path:** `/webinars/{webinarId}/panelists/{panelistId}`
- **Tags:** Webinars
```

[Remove](https://support.zoom.us/hc/en-us/articles/115005657826-Inviting-Panelists-to-a-Webinar#h\_de31f237-a91c-4fb2-912b-ecfba8ec5ffb) a single panelist from a webinar.  
Retrieve the `panelistId` by calling **\*\*List Panelists API\*\***.

**\*\*Prerequisites:\*\***

- Pro or a higher plan with the [webinar add-on](https://zoom.us/webinar).

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:write:admin`, `webinar:write`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
`webinar:delete:panelist`, `webinar:delete:panelist:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** `LIGHT`

### #### Responses

##### Status: 204 \\*\\*HTTP Status Code:\\*\\* \`204\` Panelist removed.

##### Status: 400 \\*\\*HTTP Status Code:\\*\\* \`400\` \<br> Bad Request \\*\\*Error Code:\\*\\* \`300\` \<br> Invalid webinar ID. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> No permission. \<br> \\*\\*Error Code:\\*\\* \`200\` \<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>

##### Status: 404 \\*\\*HTTP Status Code:\\*\\* \`404\` \<br> Not Found \\*\\*Error Code:\\*\\* \`3001\` \<br> Webinar does not exist: {webinarId}. \<br>

##### Status: 429 \\*\\*HTTP Status Code:\\*\\* \`429\` \<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### List a webinar's polls

```
- **Method:** `GET`
- **Path:** `/webinars/{webinarId}/polls`
- **Tags:** Webinars
```

Lists all the [polls](https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars) of a webinar.

#### \*\*Prerequisites\*\*

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:read:admin`, `webinar:read`

\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:read:list\_polls`, `webinar:read:list\_polls:admin`

\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* `LIGHT`

#### #### Responses

##### Status: 200 `HTTP Status Code:\`\*\`200\` List polls of a Webinar returned

##### Content-Type: application/json

#### \*\*All of:\*\*

- \*\*`polls`\*\*

`array` — An array of polls.

#### \*\*Items:\*\*

#### \*\*All of:\*\*

- \*\*`id`\*\*

`string` — The poll ID.

- \*\*`status`\*\*

`string`, possible values: `notstart`, `started`, `ended`, `sharing`, `deactivated` — The status of the webinar poll: `notstart` - Poll not started `started` - Poll started `ended` - Poll ended `sharing` - Sharing poll results `deactivated` - Poll deactivated

\* \*\*`anonymous`\*\*

`boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value defaults to `false`.

\* \*\*`poll\_type`\*\*

`integer`, possible values: `1`, `2`, `3` — The type of poll: `1` — Poll. `2` — Advanced Poll. This feature must be enabled in your Zoom account. `3` — Quiz. This feature must be enabled in your Zoom account. This value defaults to `1`.

\* \*\*`questions`\*\*

`array` — The information about the poll's questions.

#### \*\*Items:\*\*

- \*\*`answer\_max\_character`\*\*

`integer` — The allowed maximum number of characters. This field only applies to `short\_answer` and `long\_answer` polls: `1` For `short\_answer` polls, a maximum of 500 characters. `2` For `long\_answer` polls, a maximum of 2,000 characters.

- \*\*`answer\_min\_character`\*\*

`integer` — The allowed minimum number of characters. This field only applies to `short\_answer` and `long\_answer` polls. You must provide at least a `1` character minimum value.

- \*\*`answer\_required`\*\*

`boolean`, default: `false` — Whether participants must answer the question: `true` — The participant must answer the question. `false` — The participant does not need to answer the question. `Note:\`\*\` When the poll's `type` value is `1` (Poll), this value defaults to `true`.



\`type\` value is the \`2\` (Advanced Poll) or \`3\` (Quiz) values, this value defaults to \`false\`.

- **\`answers\`**

\`array\` — The poll question's available answers. This field requires a **\`minimum\`** of two answers. \\* For \`single\` and \`multiple\` polls, you can only provide a maximum of 10 answers. \\* For \`matching\` polls, you can only provide a maximum of 16 answers. \\* For \`rank\_order\` polls, you can only provide a maximum of seven answers.

**\`Items:\`**

\`string\`

- **\`case\_sensitive\`**

\`boolean\`, default: \`false\` — Whether the correct answer is case sensitive. This field only applies to \`fill\_in\_the\_blank\` polls: \\* \`true\` — The answer is case-sensitive. \\* \`false\` — The answer is not case-sensitive. This value defaults to \`false\`.

- **\`name\`**

\`string\` — The poll question, up to 1024 characters. For \`fill\_in\_the\_blank\` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of \`right\_answers\` values.

- **\`prompts\`**

\`array\` — The information about the prompt questions. This field only applies to \`matching\` and \`rank\_order\` polls. You **\`must\`** provide a minimum of two prompts, up to a maximum of 10 prompts.

**\`Items:\`**

- **\`prompt\_question\`**

\`string\` — The question prompt's title.

- **\`prompt\_right\_answers\`**

\`array\` — The question prompt's correct answers: \\* For \`matching\` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. \\* For \`rank\_order\` polls, you can only provide one correct answer.

**\`Items:\`**

\`string\`

- **\`rating\_max\_label\`**

\`string\` — The high score label for the \`rating\_max\_value\` field. This field only applies to the \`rating\_scale\` poll.

- **\`rating\_max\_value\`**

\`integer\` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the \`rating\_scale\` poll.

- **\`rating\_min\_label\`**

\`string\` — The low score label for the \`rating\_min\_value\` field. This field only applies to the \`rating\_scale\` poll.

- **\`rating\_min\_value\`**

\`integer\` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the \`rating\_scale\` poll.

- **\`right\_answers\`**

\`array\` — The poll question's correct answer(s). This field is **\`required\`** if the poll's \`type\` value is \`3\` (Quiz). For \`single\` and \`matching\` polls, this field only accepts one answer.

**\`Items:\`**

\`string\`

- **\`show\_as\_dropdown\`**

\`boolean\`, default: \`false\` — Whether to display the radio selection as a drop-down box: \\* \`true\` — Show as a drop-down box. \\* \`false\` — Do not show as a drop-down box. This value defaults

to `false`.

- **type**

`string`, possible values: "single", "multiple", "matching", "rank\_order", "short\_answer", "long\_answer", "fill\_in\_the\_blank", "rating\_scale" — The poll's question and answer type:   
 \* `single` — Single choice.   
 \* `multiple` — Multiple choice.   
 \* `matching` — Matching.   
 \* `rank\_order` — Rank order.   
 \* `short\_answer` — Short answer.   
 \* `long\_answer` — Long answer.   
 \* `fill\_in\_the\_blank` — Fill in the blank.   
 \* `rating\_scale` — Rating scale.

**title**

`string` — The poll's title, up to 64 characters.

- **total\_records**

`integer` — The number of all records available across pages.

**Example:**

```json

```
{
  "polls": [
    {
      "id": "QalIoKWLtJehBJ8e1xRrbQ",
      "status": "notstart",
      "anonymous": true,
      "poll_type": 2,
      "questions": [
        {
          "answer_max_character": 200,
          "answer_min_character": 1,
          "answer_required": false,
          "answers": [
            "Extremely useful"
          ],
          "case_sensitive": false,
          "name": "How useful was this meeting?",
          "prompts": [
            {
              "prompt_question": "How are you?",
              "prompt_right_answers": [
                "Good"
              ]
            }
          ],
          "rating_max_label": "Extremely Likely",
          "rating_max_value": 4,
          "rating_min_label": "Not likely",
          "rating_min_value": 0,
          "right_answers": [
            "Good"
          ],
          "show_as_dropdown": false,
          "type": "single"
        }
      ],
      "title": "Learn something new"
    }
  ],
  "total_records": 1
}
```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 4400 **Webinar polls disabled. To enable this feature, enable the Webinar Polls/Quizzes setting in the Zoom web portal's Settings interface.**
Error Code: 300 **Invalid webinar ID.**
Error Code: 200 **No permission.**
Error Code: 200 **Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.**

Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Webinar does not exist: {webinarId}.**

Status: 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).**

Create a webinar's poll

```
- **Method:** `POST`
- **Path:** `/webinars/{webinarId}/polls`
- **Tags:** Webinars
```

Creates a [poll](https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars) for a webinar.

****Prerequisites****

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

****[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`webinar:write:admin`, `webinar:write`

****[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):****
`webinar:write:poll`, `webinar:write:poll:admin`

****[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):**** `LIGHT`

Request Body

Content-Type: application/json

****All of:****

- ****`anonymous`****

`boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value defaults to `false`.

- ****`poll\_type`****

`integer`, possible values: `1, 2, 3` — The type of poll. `1` - Poll. `2` - Advanced Poll. This feature must be enabled in your Zoom account. `3` - Quiz. This feature must be enabled in your Zoom account. This value defaults to `1`.

- ****`questions`****

`array` — The information about the poll's questions.

****Items:****

- ****`answer\_max\_character`****

`integer` — The allowed maximum number of characters. This field only applies to `short\_answer` and `long\_answer` polls: `For short\_answer` polls, a maximum of 500 characters. `For long\_answer` polls, a maximum of 2,000 characters.

- ****`answer\_min\_character`****

`integer` — The allowed minimum number of characters. This field only applies to `short\_answer` and `long\_answer` polls. You must provide at least a `one` character minimum value.

- ****`answer\_required`****

`boolean`, default: `false` — Whether participants must answer the question. `true` - The participant must answer the question. `false` - The participant does not need to answer the question. **Note:** When the poll's `type` value is `1` (Poll), this value defaults to `true`. When the poll's `type` value is the `2` (Advanced Poll) or `3` (Quiz) values, this value defaults to `false`.

- ****`answers`****

`array` — The poll question's available answers. This field requires a **minimum** of two answers. `For single` and `multiple` polls, you can only provide a maximum of 10 answers. `For matching` polls, you can only provide a maximum of 16 answers. `For rank\_order` polls, you can only provide a maximum of seven answers.

****Items:****

`string`

- ****`case\_sensitive`****

`boolean`, default: `false` — Whether the correct answer is case sensitive. This field only applies to `fill\_in\_the\_blank` polls. `true` - The answer is case-sensitive. `false` - The answer is not case-sensitive. This value defaults to `false`.

- ****`name`****

`string` — The poll question, up to 1024 characters. For `fill\_in\_the\_blank` polls, this field is

the poll's question. For each value that the user must fill in, ensure that there are the same number of `\`right_answers\`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to `\`matching\`` and `\`rank\_order\`` polls. You `\`*\`must\`*` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: `\`*\`For \`matching\` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. \`*\`For \`rank_order\` polls, you can only provide one correct answer.`

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the `\`rating_max_value\`` field. This field only applies to the `\`rating\_scale\`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the `\`rating_scale\`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the `\`rating_min_value\`` field. This field only applies to the `\`rating\_scale\`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the `\`rating_scale\`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is `\`*\`required\`*` if the poll's `\`type\`` value is `\`3\`` (Quiz). For `\`single\`` and `\`matching\`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box. `\`*\`true\`` - Show as a drop-down box. `\`*\`false\`` - Do not show as a drop-down box. This value defaults to `\`false\``.

- `**`type`**`

``string``, possible values: `\`"single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale"\`` — The poll's question and answer type. `\`*\`single\`` - Single choice. `\`*\`multiple\`` - Multiple choice. `\`*\`matching\`` - Matching. `\`*\`rank_order\`` - Rank order. `\`*\`short\_answer\`` - Short answer. `\`*\`long_answer\`` - Long answer. `\`*\`fill\_in\_the\_blank\`` - Fill in the blank. `\`*\`rating_scale\`` - Rating scale.

- `**`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

```
``json
{
  "anonymous": true,
  "poll_type": 2,
  "questions": [
    {
      "answer_max_character": 200,
      "answer_min_character": 1,
```

```

    "answer_required": false,
    "answers": [
      "Extremely useful"
    ],
    "case_sensitive": false,
    "name": "How useful was this meeting?",
    "prompts": [
      {
        "prompt_question": "How are you?",
        "prompt_right_answers": [
          "Good"
        ]
      }
    ],
    "rating_max_label": "Extremely Likely",
    "rating_max_value": 4,
    "rating_min_label": "Not likely",
    "rating_min_value": 0,
    "right_answers": [
      "Good"
    ],
    "show_as_dropdown": false,
    "type": "single"
  }
],
"title": "Learn something new"
}
},
}

```

Responses

Status: 201 **HTTP Status Code:** \`201\` Webinar Poll Created

Content-Type: application/json

****All of:****

- ****`id`****

`string` — The webinar poll ID.

- ****`status`****

`string`, possible values: **`"notstart", "started", "ended", "sharing"`** — The status of the webinar poll:
`notstart` - Poll not started **`started`** - Poll started **`ended`** - Poll ended **`sharing`** - Sharing poll results

*** **`anonymous`****

`boolean`, default: **`false`** — Whether meeting participants answer poll questions anonymously. This value defaults to **`false`**.

*** **`poll\_type`****

`integer`, possible values: **`1, 2, 3`** — The type of poll. **`1`** - Poll. **`2`** - Advanced Poll. This feature must be enabled in your Zoom account. **`3`** - Quiz. This feature must be enabled in your Zoom account. This value defaults to **`1`**.

*** **`questions`****

`array` — The information about the poll's questions.

****Items:****

- ****`answer\_max\_character`****

`integer` — The allowed maximum number of characters. This field only applies to **`short\_answer`** and **`long\_answer`** polls: **`1`** For **`short\_answer`** polls, a maximum of 500 characters. **`2`** For **`long\_answer`** polls, a maximum of 2,000 characters.

- ****`answer\_min\_character`****

`integer` — The allowed minimum number of characters. This field only applies to **`short\_answer`** and **`long\_answer`** polls. You must provide at least a **`one`** character minimum value.

- ****`answer\_required`****

`boolean`, default: **`false`** — Whether participants must answer the question. **`true`** - The participant must answer the question. **`false`** - The participant does not need to answer the question.
`Note`: **`1`** When the poll's **`type`** value is **`1`** (Poll), this value defaults to **`true`**. **`2`** When

the poll's `\`type\`` value is the `\`2\`` (Advanced Poll) or `\`3\`` (Quiz) values, this value defaults to `\`false\``.

- `**`answers`**`

``array`` — The poll question's available answers. This field requires a `\`*\`minimum\`*\`` of two answers. `\`*\` For \`single\` and \`multiple\` polls, you can only provide a maximum of 10 answers. \`*\` For \`matching\` polls, you can only provide a maximum of 16 answers. \`*\` For \`rank_order\` polls, you can only provide a maximum of seven answers.`

`**Items:**`

``string``

- `**`case_sensitive`**`

``boolean``, default: ``false`` — Whether the correct answer is case sensitive. This field only applies to `\`fill_in_the_blank\`` polls. `\`*\` \`true\` - The answer is case-sensitive. \`*\` \`false\` - The answer is not case-sensitive. This value defaults to \`false\`.`

- `**`name`**`

``string`` — The poll question, up to 1024 characters. For `\`fill_in_the_blank\`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of `\`right_answers\`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to `\`matching\`` and `\`rank_order\`` polls. You `\`*\`must\`*\`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: `\`*\` For \`matching\` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. \`*\` For \`rank_order\` polls, you can only provide one correct answer.`

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the `\`rating_max_value\`` field. This field only applies to the `\`rating_scale\`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the `\`rating_scale\`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the `\`rating_min_value\`` field. This field only applies to the `\`rating_scale\`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the `\`rating_scale\`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is `\`*\`required\`*\`` if the poll's `\`type\`` value is `\`3\`` (Quiz). For `\`single\`` and `\`matching\`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box. `\`*\` \`true\` - Show as a drop-down box. \`*\` \`false\` - Do not show as a drop-down box. This value defaults to \`false\`.`

- ****`type`****

`string`, possible values: `"single", "multiple", "matching", "rank\_order", "short\_answer", "long\_answer", "fill\_in\_the\_blank", "rating\_scale"` — The poll's question and answer type. `\* \single\` - Single choice. `\* \multiple\` - Multiple choice. `\* \matching\` - Matching. `\* \rank_order\` - Rank order. `\* \short_answer\` - Short answer. `\* \long_answer\` - Long answer. `\* \fill_in_the_blank\` - Fill in the blank. `\* \rating_scale\` - Rating scale.

****`title`****

`string` — The poll's title, up to 64 characters.

****Example:****

```
```json
{
 "id": "QaIioKwLTJehBJ8e1xRrbQ",
 "status": "notstart",
 "anonymous": true,
 "poll_type": 2,
 "questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
 }
],
 "title": "Learn something new"
}
```

##### Status: 400 `\* \HTTP Status Code: \* \400\` `\<br> Bad Request \* \Error Code: \* \4400\` `\<br> Webinar polls disabled. To enable this feature, enable the \* \Webinar Polls/Quizzes\* \ setting in the Zoom web portal's \* \Settings\* \ interface. \<br> \* \Error Code: \* \300\` `\<br> Invalid webinar ID. \<br> \* \Error Code: \* \200\` `\<br> No permission. \<br> \* \Error Code: \* \200\` `\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br>`

##### Status: 404 `\* \HTTP Status Code: \* \404\` `\<br> Not Found \* \Error Code: \* \3001\` `\<br> Webinar does not exist: {webinarId}. \<br>`

##### Status: 429 `\* \HTTP Status Code: \* \429\` `\<br> Too Many Requests. For more information, see \[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).`

### Get a webinar poll

- **\*\*Method:\*\*** `GET`  
 - **\*\*Path:\*\*** `/webinars/{webinarId}/polls/{pollId}`  
 - **\*\*Tags:\*\*** Webinars

Returns a webinar's [poll](https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars) details.

**\*\*Prerequisites\*\***

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

```

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`webinar:read:admin`,`webinar:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
`webinar:read:poll`,`webinar:read:poll:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `HTTP Status Code:200` Webinar Poll object returned

Content-Type: application/json

All of:

- **`id`**

 `string` — The webinar poll ID.

- **`status`**

 `string`, possible values: `"notstart", "started", "ended", "sharing", "deactivated"` — The status of the
 webinar poll: `notstart` - Poll not started `started` - Poll started `ended` - Poll ended `sharing` -
 Sharing poll results `deactivated` - Poll deactivated

* **`anonymous`**

 `boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value
 defaults to `false`.

* **`poll_type`**

 `integer`, possible values: `1, 2, 3` — The type of poll: `1` — Poll. `2` — Advanced Poll. This feature must be enabled in your Zoom account. `3` — Quiz. This feature must
 be enabled in your Zoom account. This value defaults to `1`.

* **`questions`**

 `array` — The information about the poll's questions.

 Items:

 - **`answer_max_character`**

 `integer` — The allowed maximum number of characters. This field only applies to `short_answer` and
 `long_answer` polls: `For short_answer` polls, a maximum of 500 characters. `For long_answer`
 polls, a maximum of 2,000 characters.

 - **`answer_min_character`**

 `integer` — The allowed minimum number of characters. This field only applies to `short_answer` and
 `long_answer` polls. You must provide at least a `one` character minimum value.

 - **`answer_required`**

 `boolean`, default: `false` — Whether participants must answer the question: `true` — The
 participant must answer the question. `false` — The participant does not need to answer the
 question. Note: When the poll's `type` value is `1` (Poll), this value defaults to `true`.
 When the poll's `type` value is the `2` (Advanced Poll) or `3` (Quiz) values, this value defaults
 to `false`.

 - **`answers`**

 `array` — The poll question's available answers. This field requires a minimum of two answers.
 For `single` and `multiple` polls, you can only provide a maximum of 10 answers. For `matching`
 polls, you can only provide a maximum of 16 answers. For `rank_order` polls, you can only provide a
 maximum of seven answers.

 Items:

 `string`

 - **`case_sensitive`**

 `boolean`, default: `false` — Whether the correct answer is case sensitive. This field only applies to
 `fill_in_the_blank` polls: `true` — The answer is case-sensitive. `false` — The
 answer is not case-sensitive. This value defaults to `false`.

 - **`name`**

```



``string`` — The poll question, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You ``**must`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``*`` For ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``*`` For ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating_min_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``**required`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box: ``*`true`` &mdash; Show as a drop-down box. ``*`false`` &mdash; Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``"single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale"`` — The poll's question and answer type: ``*`single`` &mdash; Single choice. ``*`multiple`` &mdash; Multiple choice. ``*`matching`` &mdash; Matching. ``*`rank_order`` &mdash; Rank order. ``*`short_answer`` &mdash; Short answer. ``*`long_answer`` &mdash; Long answer. ``*`fill_in_the_blank`` &mdash; Fill in the blank. ``*`rating_scale`` &mdash; Rating scale.

`* **`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

``json``

```
{
 "id": "QaIioKwLTJehBJ8e1xRrbQ",
 "status": "notstart",
```

```

"anonymous": true,
"poll_type": 2,
"questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
 }
],
"title": "Learn something new"
}

```

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 4400` `Webinar polls disabled. To enable this feature, enable the Webinar Polls/Quizzes setting in the Zoom web portal's Settings interface.` `Error Code: 300` `Invalid webinar ID.` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

### Update a webinar poll

```

- **Method:** `PUT`
- **Path:** `/webinars/{webinarId}/polls/{pollId}`
- **Tags:** Webinars

```

Updates a webinar's [poll](https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars).

#### Prerequisites

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `webinar:write:admin`, `webinar:write`

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):**  
 `webinar:update:poll`, `webinar:update:poll:admin`

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `LIGHT`

#### Request Body

##### Content-Type: application/json

**All of:**

- **anonymous**

`boolean`, default: `false` — Whether meeting participants answer poll questions anonymously. This value defaults to `false`.

- **poll\_type**

``integer``, possible values: ``1, 2, 3`` — The type of poll: ``1`` — Poll. ``2`` — Advanced Poll. This feature must be enabled in your Zoom account. ``3`` — Quiz. This feature must be enabled in your Zoom account. This value defaults to ``1``.

- `**`questions`**`

``array`` — The information about the poll's questions.

`**Items:**`

- `**`answer_max_character`**`

``integer`` — The allowed maximum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls: ``1`` For ``short_answer`` polls, a maximum of 500 characters. ``2`` For ``long_answer`` polls, a maximum of 2,000 characters.

- `**`answer_min_character`**`

``integer`` — The allowed minimum number of characters. This field only applies to ``short_answer`` and ``long_answer`` polls. You must provide at least a ``one`` character minimum value.

- `**`answer_required`**`

``boolean``, default: ``false`` — Whether participants must answer the question: ``true`` — The participant must answer the question. ``false`` — The participant does not need to answer the question. `**Note:**` When the poll's ``type`` value is ``1`` (Poll), this value defaults to ``true``. When the poll's ``type`` value is the ``2`` (Advanced Poll) or ``3`` (Quiz) values, this value defaults to ``false``.

- `**`answers`**`

``array`` — The poll question's available answers. This field requires a ``minimum`` of two answers. ``1`` For ``single`` and ``multiple`` polls, you can only provide a maximum of 10 answers. ``2`` For ``matching`` polls, you can only provide a maximum of 16 answers. ``3`` For ``rank_order`` polls, you can only provide a maximum of seven answers.

`**Items:**`

``string``

- `**`case_sensitive`**`

``boolean``, default: ``false`` — Whether the correct answer is case sensitive. This field only applies to ``fill_in_the_blank`` polls: ``true`` — The answer is case-sensitive. ``false`` — The answer is not case-sensitive. This value defaults to ``false``.

- `**`name`**`

``string`` — The poll question, up to 1024 characters. For ``fill_in_the_blank`` polls, this field is the poll's question. For each value that the user must fill in, ensure that there are the same number of ``right_answers`` values.

- `**`prompts`**`

``array`` — The information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` polls. You ``must`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`prompt_right_answers`**`

``array`` — The question prompt's correct answers: ``1`` For ``matching`` polls, you must provide a minimum of two correct answers, up to a maximum of 10 correct answers. ``2`` For ``rank_order`` polls, you can only provide one correct answer.

`**Items:**`

``string``

- `**`rating_max_label`**`

``string`` — The high score label for the ``rating_max_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_label`**`

``string`` — The low score label for the ``rating_min_value`` field. This field only applies to the ``rating_scale`` poll.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the ``rating_scale`` poll.

- `**`right_answers`**`

``array`` — The poll question's correct answer(s). This field is ``**required`` if the poll's ``type`` value is ``3`` (Quiz). For ``single`` and ``matching`` polls, this field only accepts one answer.

`**Items:**`

``string``

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box: ``true`` &mdash; Show as a drop-down box. ``false`` &mdash; Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``"single"`, "multiple"`, "matching"`, "rank_order"`, "short_answer"`, "long_answer"`, "fill_in_the_blank"`, "rating_scale" — The poll's question and answer type: `single` &mdash; Single choice. `multiple` &mdash; Multiple choice. `matching` &mdash; Matching. `rank_order` &mdash; Rank order. `short_answer` &mdash; Short answer. `long_answer` &mdash; Long answer. `fill_in_the_blank` &mdash; Fill in the blank. `rating_scale` &mdash; Rating scale.`

- `**`title`**`

``string`` — The poll's title, up to 64 characters.

`**Example:**`

``json``

```
{
 "anonymous": true,
 "poll_type": 2,
 "questions": [
 {
 "answer_max_character": 200,
 "answer_min_character": 1,
 "answer_required": false,
 "answers": [
 "Extremely useful"
],
 "case_sensitive": false,
 "name": "How useful was this meeting?",
 "prompts": [
 {
 "prompt_question": "How are you?",
 "prompt_right_answers": [
 "Good"
]
 }
],
 "rating_max_label": "Extremely Likely",
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_min_value": 0,
 "right_answers": [
 "Good"
],
 "show_as_dropdown": false,
 "type": "single"
 }
],
 "title": "Learn something new"
},
{
 ..
```

## #### Responses

##### Status: 204 `HTTP Status Code: 204` Webinar Poll Updated

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 4400` Webinar polls disabled. To enable this feature, enable the `Webinar Polls/Quizzes` setting in the Zoom web portal's `Settings` interface. `Error Code: 300` Invalid webinar ID. `Error Code: 200` No permission. `Error Code: 200` Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` Webinar does not exist: {webinarId}.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

## ### Delete a webinar poll

- `Method: DELETE`  
 - `Path: /webinars/{webinarId}/polls/{pollId}`  
 - `Tags: Webinars`

Delete a webinar's [poll] (<https://support.zoom.us/hc/en-us/articles/203749865-Polling-for-Webinars>).

## \*\*Prerequisites\*\*

- A Pro or higher plan with a [Webinar plan] (<https://zoom.us/webinar>) add-on.

`[Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:write:admin`, `webinar:write`

`[Granular Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:delete:poll`, `webinar:delete:poll:admin`

`[Rate Limit Label]` (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

## #### Responses

##### Status: 204 `HTTP Status Code: 204` Webinar Poll deleted

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 4400` Webinar polls disabled. To enable this feature, enable the `Webinar Polls/Quizzes` setting in the Zoom web portal's `Settings` interface. `Error Code: 200` No permission. `Error Code: 200` Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. `Error Code: 4400` Invalid poll IDs. `Error Code: 4400` Cannot update or delete the poll within the Survey Library. `Error Code: 300` Invalid webinar ID.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` Webinar does not exist: {webinarId}.

##### Status: 429 `HTTP Status Code: 429` Too Many Requests. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

## ### List webinar registrants

- `Method: GET`  
 - `Path: /webinars/{webinarId}/registrants`  
 - `Tags: Webinars`

List all users that have registered for a given webinar. Zoom users with a [webinar plan] (<https://zoom.us/webinar>) have access to creating and managing webinars. The webinar functionality lets a host broadcast a Zoom meeting to up to 10,000 attendees. Scheduling a [webinar with registration] (<https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-Webinar-with-Registration>) requires your registrants to complete a brief form before receiving the link to join the webinar.

## \*\*Prerequisites\*\*

- Pro or higher plan with a Webinar add-on.

`[Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:admin`, `webinar:read`

`[Granular Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:list_registrants`, `webinar:read:list_registrants:admin`

`[Rate Limit Label]` (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `MEDIUM`

## #### Responses

##### Status: 200 \\*\\*HTTP Status Code:\\*\\* \`200\` Webinar plan subscription is missing. Enable webinar for this user once the subscription is added:{userId}.

##### Content-Type: application/json

**\*\*All of:\*\***

- **\*\*`next\_page\_token`\*\***

``string`` — Use the next page token to paginate through large result sets. A next page token is returned whenever the set of available results exceeds the current page size. This token's expiration period is 15 minutes.

- **\*\*`page\_count`\*\***

``integer`` — The number of pages returned for the request made.

- **\*\*`page\_number`\*\***

``integer``, default: ``1`` — \\*\\*Deprecated\\*\\* This field will be deprecated. We will no longer support this field in a future release. Instead, use ``next_page_token`` for pagination.

- **\*\*`page\_size`\*\***

``integer``, default: ``30`` — The number of records returned with a single API call.

- **\*\*`total\_records`\*\***

``integer`` — The total number of all the records available across pages.

**\* \*\*`registrants`\*\***

``array`` — List of registrant objects.

**\*\*Items:\*\***

**\*\*All of:\*\***

- **\*\*`id`\*\***

``string`` — Registrant ID.

**\*\*All of:\*\***

- **\*\*`email` (required)\*\***

``string``, format: ``email`` — The registrant's email address. See [\\[Email address display rules\]\](https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) (https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules) for return value details.

- **\*\*`first\_name` (required)\*\***

``string`` — The registrant's first name.

- **\*\*`address`\*\***

``string`` — The registrant's address.

- **\*\*`city`\*\***

``string`` — The registrant's city.

- **\*\*`comments`\*\***

``string`` — The registrant's questions and comments.

- **\*\*`country`\*\***

``string`` — The registrant's two-letter ISO [\\[country code\]\](https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries) (https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

- **\*\*`custom\_questions`\*\***

``array`` — Information about custom questions.

**\*\*Items:\*\***

- **\*\*`title`\*\***

```

 `string` — The title of the custom question.

- **`value`**

 `string` — The custom question's response value. This has a limit of 128 characters.

- **`industry`**

 `string` — The registrant's industry.

- **`job_title`**

 `string` — The registrant's job title.

- **`last_name`**

 `string` — The registrant's last name.

- **`no_of_employees`**

 `string`, possible values: `""`, "1-20", "21-50", "51-100", "101-250", "251-500", "501-1,000", "1,001-5,000", "5,001-10,000", "More than 10,000" — The registrant's number of employees. * \1-20\ * \21-50\ * \51-100\ * \101-250\ * \251-500\ * \501-1,000\ * \1,001-5,000\ * \5,001-10,000\ * \More than 10,000\

- **`org`**

 `string` — The registrant's organization.

- **`phone`**

 `string` — The registrant's phone number.

- **`purchasing_time_frame`**

 `string`, possible values: `""`, "Within a month", "1-3 months", "4-6 months", "More than 6 months", "No timeframe" — The registrant's purchasing time frame. * \Within a month.\ * \1-3 months.\ * \4-6 months.\ * \More than 6 months.\ * \No timeframe.\

- **`role_in_purchase_process`**

 `string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved" — The registrant's role in the purchase process. * \Decision maker\ * \Evaluator/Recommender.\ * \Influencer.\ * \Not involved.\

- **`state`**

 `string` — The registrant's state or province.

- **`status`**

 `string`, possible values: "approved", "denied", "pending" — The registrant's status. * \approved\ - Registrant is approved. * \denied\ - Registrant is denied. * \pending\ - Registrant is waiting for approval.

- **`zip`**

 `string` — The registrant's ZIP or postal code.

* **`create_time`**

 `string`, format: `date-time` — The time when the registrant registered.

* **`join_url`**

 `string`, format: `string` — The URL that an approved registrant can use to join the meeting or webinar.

* **`status`**

 `string` — The status of the registrant's registration. \approved\ - User has been successfully approved for the webinar. \pending\ - The registration is still pending. \denied\ - User has been denied from joining the webinar.

Example:

```json
{
  "next_page_token": "w7587w4eiysudgf",

```

```

"page_count": 1,
"page_size": 30,
"total_records": 20,
"registrants": [
  {
    "id": "9tboDiHUQAeOnbmudzWa5g",
    "address": "1800 Amphibious Blvd.",
    "city": "Mountain View",
    "comments": "Looking forward to the discussion.",
    "country": "US",
    "custom_questions": [
      {
        "title": "What do you hope to learn from this?",
        "value": "Look forward to learning how you come up with new recipes and what other services you
offer."
      }
    ],
    "email": "jchill@example.com",
    "first_name": "Jill",
    "industry": "Food",
    "job_title": "Chef",
    "last_name": "Chill",
    "no_of_employees": "1-20",
    "org": "Cooking Org",
    "phone": "5550100",
    "purchasing_time_frame": "1-3 months",
    "role_in_purchase_process": "Influencer",
    "state": "CA",
    "status": "approved",
    "zip": "94045",
    "create_time": "2022-03-22T05:59:09Z",
    "join_url": "https://example.com/j/11111"
  }
]
}
}
}

```

Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/)`.

Add a webinar registrant

```

- Method: POST
- Path: /webinars/{webinarId}/registrants
- Tags: Webinars

```

Create and submit a user's registration for a webinar. Zoom users with a [Webinar plan] (<https://zoom.us/webinar>) have access to creating and managing webinars. Webinars allow hosts to broadcast a Zoom meeting to up to 10,000 attendees. Scheduling a [webinar with registration] (<https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-Webinar-with-Registration>) requires your registrants to complete a brief form before receiving the link to join the webinar.

Prerequisites:

- A Pro or higher plan with the Webinar add-on.

[Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:write:admin`, `webinar:write`

[Granular Scopes] (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:write:registrant`, `webinar:write:registrant:admin`

[Rate Limit Label] (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

Request Body

Content-Type: application/json

- **email** (required)

string, format: email — The registrant's email address.

- **first_name** (required)


```

`string` — The registrant's first name.

- **`address`**

  `string` — The registrant's address.

- **`city`**

  `string` — The registrant's city.

- **`comments`**

  `string` — The registrant's questions and comments.

- **`country`**

  `string` — The registrant's two-letter \[country code]\(https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries).

- **`custom_questions`**

  `array` — Information about custom questions.

  **Items:**

  - **`title`**

    `string` — The custom question's title.

  - **`value`**

    `string` — The custom question's response value. This has a limit of 128 characters.

- **`industry`**

  `string` — The registrant's industry.

- **`job_title`**

  `string` — The registrant's job title.

- **`language`**

  `string`, possible values: `en-US`, `de-DE`, `es-ES`, `fr-FR`, `jp-JP`, `pt-PT`, `ru-RU`, `zh-CN`, `zh-TW`, `ko-KO`, `it-IT`, `vi-VN`, `pl-PL`, `Tr-TR` — Specifies the registrant's preferred language for the confirmation email sent upon successful registration. \*\*Note\*\* This field is only effective if the webinar's 'Select Email Language' setting is set to 'Same as recipients' default language' in the Zoom web portal. If a fixed language is selected, this value will be ignored. \*\*Supported values\*\* \* `en-US` - English (US) \* `de-DE` - German (Germany) \* `es-ES` - Spanish (Spain) \* `fr-FR` - French (France) \* `jp-JP` - Japanese \* `pt-PT` - Portuguese (Portugal) \* `ru-RU` - Russian \* `zh-CN` - Chinese (PRC) \* `zh-TW` - Chinese (Taiwan) \* `ko-KO` - Korean \* `it-IT` - Italian (Italy) \* `vi-VN` - Vietnamese \* `pl-PL` - Polish \* `Tr-TR` - Turkish

- **`last_name`**

  `string` — The registrant's last name.

- **`no_of_employees`**

  `string`, possible values: ``, `1-20`, `21-50`, `51-100`, `101-500`, `500-1,000`, `1,001-5,000`, `5,001-10,000`, `More than 10,000` — The registrant's number of employees: \* `1-20` \* `21-50` \* `51-100` \* `101-500` \* `500-1,000` \* `1,001-5,000` \* `5,001-10,000` \* `More than 10,000`

- **`org`**

  `string` — The registrant's organization.

- **`phone`**

  `string` — The registrant's phone number.

- **`purchasing_time_frame`**

  `string`, possible values: ``, `Within a month`, `1-3 months`, `4-6 months`, `More than 6 months`, `No timeframe` — The registrant's purchasing time frame: \* `Within a month` \* `1-3 months` \* `4-6 months` \* `More than 6 months` \* `No timeframe`

- **`role_in_purchase_process`**

```

`string`, possible values: `""`, "Decision Maker", "Evaluator/Recommender", "Influencer", "Not involved"
 — The registrant's role in the purchase process: `\*` `Decision Maker` `\*` `Evaluator/Recommender` `\*`
 `Influencer` `\*` `Not involved`

- **source_id**

`string` — The tracking source's unique identifier.

- **state**

`string` — The registrant's state or province.

- **zip**

`string` — The registrant's ZIP or postal code.

Example:

``json

```
{
  "first_name": "Jill",
  "last_name": "Chill",
  "email": "jchill@example.com",
  "address": "1800 Amphibious Blvd.",
  "city": "Mountain View",
  "state": "CA",
  "zip": "94045",
  "country": "US",
  "phone": "5550100",
  "comments": "Looking forward to the discussion.",
  "custom_questions": [
    {
      "title": "What do you hope to learn from this?",
      "value": "Look forward to learning how you come up with new recipes and what other services you
offer."
    }
  ],
  "industry": "Food",
  "job_title": "Chef",
  "no_of_employees": "1-20",
  "org": "Cooking Org",
  "purchasing_time_frame": "1-3 months",
  "role_in_purchase_process": "Influencer",
  "language": "en-US",
  "source_id": "4816766181770"
}
```

Responses

Status: 201 `\*`HTTP Status Code:`\*` `201` Webinar registration created.

Content-Type: application/json

- **id**

`integer`, format: `int64` — The webinar's ID.

- **join_url**

`string` — The URL the registrant can use to join the webinar.

- **occurrences**

`array` — Array of occurrence objects.

Items:

- **duration**

`integer` — Duration.

- **occurrence_id**

`string` — Occurrence ID: Unique identifier that identifies an occurrence of a recurring webinar. \[Recurring webinars]\(https://support.zoom.us/hc/en-us/articles/216354763-How-to-Schedule-A-Recurring-Webinar) can have a maximum of 50 occurrences.

- **start_time**

```

`string`, format: `date-time` — Start time.

- status

`string` — Occurrence status.

- registrant_id

`string` — The registrant's ID.

- start_time

`string`, format: `date-time` — The webinar's start time.

- topic

`string` — The webinar's topic.

```

Example:

```

```json
{
 "id": 92674392836,
 "join_url": "https://example.com/j/22222",
 "registrant_id": "fdgsfh2ey82fuh",
 "start_time": "2021-07-13T21:44:51Z",
 "topic": "My Webinar",
 "occurrences": [
 {
 "duration": 60,
 "occurrence_id": "1648194360000",
 "start_time": "2022-03-25T07:46:00Z",
 "status": "available"
 }
]
}
```

```

Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 3000
 This webinar does not have registration as required: {webinarId}.
Error Code: 3027
 Host cannot register.
Error Code: 3034
 If you have been invited, please input your work email address.
Error Code: 3038
 Webinar is over, you cannot register now. If you have any questions, contact the webinar host.
Error Code: 3000
 You have reached the limit for the number of attendees you can add. Contact Zoom Support for more information.
Error Code: 3000
 The Zoom REST API does not support paid registration.
Error Code: 3000
 You have been invited as a panelist for the webinar, please check your email to find more information about this webinar.
Error Code: 200
 No permission.
Error Code: 200
 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.
Error Code: 300
 Invalid webinar ID.

Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001
 Webinar does not exist: {webinarId}.

Status: 429 **HTTP Status Code:** 429 **Too Many Requests**. For more information, see [\[rate limits\]\(https://developers.zoom.us/docs/api/rest/rate-limits/\)](https://developers.zoom.us/docs/api/rest/rate-limits/).

List registration questions

```

- Method: GET
- Path: /webinars/{webinarId}/registrants/questions
- Tags: Webinars

```

List registration questions and fields that are to be answered by users while registering for a webinar.

Scheduling a [webinar with registration](https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-Webinar-with-Registration) requires your registrants to complete a brief form with fields and questions before they can receive the link to join the webinar.

Prerequisites:

- Pro or higher plan with the webinar add-on.

[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:read:admin`, `webinar:read`

[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/): `webinar:read:list_registration_questions`, `webinar:read:list_registration_questions:admin`

[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): `LIGHT`

Responses

Status: 200 `\*\*HTTP Status Code:\*\* \`200\`` Webinar registrant question object returned.

Content-Type: application/json

****All of:****

- ****`custom\_questions`****

``array`` — Array of Registrant Custom Questions.

****Items:****

- ****`answers`****

``array`` — An array of answer choices. Can't be used for short answer type.

****Items:****

``string``

- ****`required`****

``boolean`` — State whether or not the custom question is required to be answered by a registrant.

- ****`title`****

``string`` — Custom question.

- ****`type`****

``string``, possible values: ``"short", "single_radio", "single_dropdown", "multiple"`` — The question-answer type.

- ****`questions`****

``array`` — Array of registration fields whose values should be provided by registrants during registration.

****Items:****

- ****`field\_name`****

``string``, possible values: ``"last_name", "address", "city", "country", "zip", "state", "phone", "industry", "org", "job_title", "purchasing_time_frame", "role_in_purchase_process", "no_of_employees", "comments"`` — Field name

- ****`required`****

``boolean`` — State whether the selected fields are required or optional.

****Example:****

```json`

```
{
 "custom_questions": [
 {
 "answers": [
 "Good"
],
 "required": true,
 "title": "How are you?",
 "type": "short"
 }
],
 "questions": [
 {
 "field_name": "last_name",
 "required": true
 }
]
}
```

##### Status: 400 `\*\*HTTP Status Code:\*\* \`400\`` `\<br> Bad Request \*\*Error Code:\*\* \`300\`` `\<br> Invalid webinar ID. \<br> \*\*Error Code:\*\* \`200\`` `\<br> Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. \<br> \*\*Error Code:\*\* \`3000\`` `\<br> Registration has not been enabled for this webinar: {webinarId}. \<br>`

```
Status: 404 **HTTP Status Code:** \`404\` \
 Not Found **Error Code:** \`3001\` \

Webinar does not exist: {webinarId}. \

```

```
Status: 429 **HTTP Status Code:** \`429\` \
 Too Many Requests For more information, see \[rate
limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/).
```

### ### Update registration questions

```
- **Method:** \`PATCH\`
- **Path:** \`/webinars/{webinarId}/registrants/questions\`
- **Tags:** Webinars
```

Update registration questions and fields of a scheduled webinar for users to answer during webinar registration. Scheduling a [webinar with registration](https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-Webinar-with-Registration) requires your registrants to complete a brief form with fields and questions before they can receive the link to join the webinar.

#### \*\*Prerequisites:\*\*

- Pro or higher plan with a Webinar Add-on.
- Registration option for Webinar should be set as required to use this API.

```
[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
\`webinar:write:admin\`, \`webinar:write\`
```

```
[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):
\`webinar:update:registration_question\`, \`webinar:update:registration_question:admin\`
```

```
[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits): \`LIGHT\`
```

### #### Request Body

```
Content-Type: application/json
```

#### \*\*All of:\*\*

```
- **\`custom_questions\`**
```

```
\`array\` — Array of custom questions for registrants.
```

#### \*\*Items:\*\*

```
- **\`answers\`**
```

```
\`array\` — An array of answer choices. Can't be used for short answer type.
```

#### \*\*Items:\*\*

```
\`string\`
```

```
- **\`required\`**
```

```
\`boolean\` — State whether or not a registrant is required to answer the custom question.
```

```
- **\`title\`**
```

```
\`string\` — Custom question.
```

```
- **\`type\`**
```

```
\`string\`, possible values: \`"short", "single_radio", "single_dropdown", "multiple"\` — The question-
answer type.
```

```
- **\`questions\`**
```

```
\`array\` — Array of registration fields whose values should be provided by registrants.
```

#### \*\*Items:\*\*

```
- **\`field_name\`**
```

```
\`string\`, possible values: \`"last_name", "address", "city", "country", "zip", "state", "phone",
"industry", "org", "job_title", "purchasing_time_frame", "role_in_purchase_process", "no_of_employees",
"comments"\` — Field name
```

```
- **\`required\`**
```

```
\`boolean\` — State whether the selected fields are required or optional.
```

**\*\*Example:\*\***

```

```json
{
  "custom_questions": [
    {
      "answers": [
        "Good"
      ],
      "required": true,
      "title": "How are you?",
      "type": "short"
    }
  ],
  "questions": [
    {
      "field_name": "last_name",
      "required": true
    }
  ]
}
```

```

**#### Responses**

**##### Status:** 204 **\*\*HTTP Status Code:\*\*** 204 Webinar registrant questions updated.

**##### Status:** 400 **\*\*HTTP Status Code:\*\*** 400 **\*\*Error Code:\*\*** 300 Bad Request **\*\*Error Code:\*\*** 200 Invalid webinar ID. **\*\*Error Code:\*\*** 200 No permission. **\*\*Error Code:\*\*** 200 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. **\*\*Error Code:\*\*** 300 Registration has not been enabled for this webinar: {webinarId}.

**##### Status:** 404 **\*\*HTTP Status Code:\*\*** 404 **\*\*Error Code:\*\*** 301 Not Found **\*\*Error Code:\*\*** 301 Webinar does not exist: {webinarId}.

**##### Status:** 429 **\*\*HTTP Status Code:\*\*** 429 **\*\*Error Code:\*\*** Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

**### Update registrant's status**

- **\*\*Method:\*\*** PUT  
 - **\*\*Path:\*\*** /webinars/{webinarId}/registrants/status  
 - **\*\*Tags:\*\*** Webinars

Update webinar registrants' registration status. You can approve or deny a registrant, or revoke a registrant's approval.

**\*\*Prerequisites\*\***

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

This API has an additional rate limit of requests per registrant, per 24-hour period. [See the Rate Limits page](/docs/api/rate-limits/) for more information.

**\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:write:admin`, `webinar:write`

**\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\***  
 `webinar:update:registrant\_status`, `webinar:update:registrant\_status:admin`

**\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\*** MEDIUM

**#### Request Body**

**##### Content-Type:** application/json

- **\*\*`action` (required)\*\***

**`string`**, possible values: "approve", "deny", "cancel" — The registration action to perform. **`approve`** - Approve the registrant. **`deny`** - Reject the registrant. **`cancel`** - Cancel the registrant's approval.

- **\*\*`registrants`\*\***

**`array`** — The registrant information.

**\*\*Items:\*\***

- **\*\*`email`\*\***

``string``, format: ``email`` — The registrant's email address.

- `**id**`

``string`` — The registrant's ID.

**Example:**

```
```json
{
  "action": "approve",
  "registrants": [
    {
      "email": "jchill@example.com",
      "id": "9tboDiHUQAeOnbmudzWa5g"
    }
  ]
},
```,
```

#### Responses

**Status: 204** `HTTP Status Code: 204` `<br>` Registrant status updated.

**Status: 400** `HTTP Status Code: 400` `<br>` Bad Request `Error Code: 3035` `<br>` Webinar has reached maximum attendee capacity. `<br>` `Error Code: 300` `<br>` Invalid webinar ID. `<br>` `Error Code: 200` `<br>` No permission. `<br>` `Error Code: 200` `<br>` Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action. `<br>` `Error Code: 300` `<br>` Registration has not been enabled for this meeting: {webinarId}. `<br>`

**Status: 404** `HTTP Status Code: 404` `<br>` Not Found `Error Code: 3001` `<br>` Webinar does not exist: {webinarId}. `<br>`

**Status: 429** `HTTP Status Code: 429` `<br>` Too Many Requests. For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

#### Get a webinar registrant

- **Method:** `GET`  
 - **Path:** `/webinars/{webinarId}/registrants/{registrantId}`  
 - **Tags:** Webinars

Zoom users with a `[webinar plan]` (<https://zoom.us/webinar>) have access to creating and managing webinars. The webinar feature lets a host broadcast a Zoom meeting to up to 10,000 attendees. Scheduling a `[webinar with registration]` (<https://support.zoom.us/hc/en-us/articles/204619915-Scheduling-a-Webinar-with-Registration>) requires your registrants to complete a brief form before receiving the link to join the webinar. Use this API to get details on a specific user who has registered for the webinar.

**Prerequisites:**

- The account must have a webinar plan.

**[Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:admin`, `webinar:read`

**[Granular Scopes]** (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:registrant`, `webinar:read:registrant:admin`

**[Rate Limit Label]** (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

#### Responses

**Status: 200** Success.

**Content-Type:** `application/json`

**All of:**

- `**id**`

``string``

**All of:**

- `**email` (required)**`

``string``, format: ``email`` — The registrant's email address. See `[Email address display rules]` (<https://developers.zoom.us/docs/api/rest/using-zoom-apis/#email-address-display-rules>) for return value

details.

- **first\_name** (required)

`string` — The registrant's first name.

- **address**

`string` — The registrant's address.

- **city**

`string` — The registrant's city.

- **comments**

`string` — The registrant's questions and comments.

- **country**

`string` — The registrant's two-letter ISO [country code]  
(<https://developers.zoom.us/docs/api/rest/other-references/abbreviation-lists/#countries>).

- **custom\_questions**

`array` — Information about custom questions.

**Items:**

- **title**

`string` — The title of the custom question.

- **value**

`string` — The custom question's response value. This has a limit of 128 characters.

- **industry**

`string` — The registrant's industry.

- **job\_title**

`string` — The registrant's job title.

- **last\_name**

`string` — The registrant's last name.

- **no\_of\_employees**

`string`, possible values: `""`, `"1-20"`, `"21-50"`, `"51-100"`, `"101-250"`, `"251-500"`, `"501-1,000"`, `"1,001-5,000"`, `"5,001-10,000"`, `"More than 10,000"` — The registrant's number of employees: `* 1-20 * 21-50 * 51-100 * 101-250 * 251-500 * 501-1,000 * 1,001-5,000 * 5,001-10,000 * More than 10,000`

- **org**

`string` — The registrant's organization.

- **phone**

`string` — The registrant's phone number.

- **purchasing\_time\_frame**

`string`, possible values: `""`, `"Within a month"`, `"1-3 months"`, `"4-6 months"`, `"More than 6 months"`, `"No timeframe"` — The registrant's purchasing time frame: `* Within a month * 1-3 months * 4-6 months * More than 6 months * No timeframe`

- **role\_in\_purchase\_process**

`string`, possible values: `""`, `"Decision Maker"`, `"Evaluator/Recommender"`, `"Influencer"`, `"Not involved"` — The registrant's role in the purchase process: `* Decision Maker * Evaluator/Recommender * Influencer * Not involved`

- **state**

`string` — The registrant's state or province.



- **status**

string, possible values: "approved", "denied", "pending" — The registrant's status:   
 — Registrant is approved.   
 — Registrant is denied.   
 Registrant is waiting for approval.

- **zip**

string — The registrant's ZIP or postal code.

**language**

string, possible values: "en-US", "de-DE", "es-ES", "fr-FR", "jp-JP", "pt-PT", "ru-RU", "zh-CN", "zh-TW", "ko-KO", "it-IT", "vi-VN", "pl-PL", "tr-TR" — The registrant's language preference for confirmation emails:   
 — English (US)   
 — German (Germany)   
 — Spanish (Spain)   
 — French (France)   
 — Japanese   
 — Portuguese (Portugal)   
 — Russian   
 — Chinese (PRC)   
 — Chinese (Taiwan)   
 — Korean   
 — Italian (Italy)   
 — Vietnamese   
 — Polish   
 — Turkish

- **create\_time**

string, format: date-time

- **join\_url**

string, format: string

- **status**

string

**Example:**

json

```
{
 "id": "95204914252",
 "address": "1800 Amphibious Blvd.",
 "city": "Mountain View",
 "comments": "Looking forward to the discussion.",
 "country": "US",
 "custom_questions": [
 {
 "title": "What do you hope to learn from this?",
 "value": "Look forward to learning how you come up with new recipes and what other services you offer."
 }
],
 "email": "jchill@example.com",
 "first_name": "Jill",
 "industry": "Food",
 "job_title": "Chef",
 "last_name": "Chill",
 "no_of_employees": "1-20",
 "org": "Cooking Org",
 "phone": "5550100",
 "purchasing_time_frame": "1-3 months",
 "role_in_purchase_process": "Influencer",
 "state": "CA",
 "status": "approved",
 "zip": "94045",
 "language": "en-US",
 "create_time": "2022-03-26T06:44:14Z",
 "join_url": "https://example.com/j/11111"
}
```

#### Status: 400 HTTP Status Code: 400 Bad Request Error Code: 300   
 Invalid webinar ID.   
 Error Code: 200 No permission.   
 Error Code: 200 Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.   
 Error Code: 3000 Registration has not been enabled for this webinar: {webinarId}.   
 Error Code: 3079 This registrant does not exist: {registrantId}.

#### Status: 404 HTTP Status Code: 404 Not Found Error Code: 3001 Webinar does not exist: {webinarId}.

#### Status: 429 HTTP Status Code: 429 Too Many Requests For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).

### ### Delete a webinar registrant

```
- **Method:** `DELETE`
- **Path:** `/webinars/{webinarId}/registrants/{registrantId}`
- **Tags:** Webinars
```

Delete a webinar registrant.

#### \*\*Prerequisites\*\*

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:write:admin`,`webinar:write`

\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:delete:registrant`,`webinar:delete:registrant:admin`

\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* `LIGHT`

#### #### Responses

##### Status: 204 `HTTP status code: 204 OK`

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.` `Error Code: 300` `The value that you entered for the Registrant ID field is invalid. Enter a valid value and try again.` `Error Code: 3000` `Registration has not been enabled for this webinar: {webinarId}.` `Error Code: 3000` `Registrant {registrantId} was not found.` `Error Code: 200` `No permission.` `Error Code: 300` `Invalid webinar ID.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).`

### ### Get a webinar SIP URI with passcode

```
- **Method:** `POST`
- **Path:** `/webinars/{webinarId}/sip_dialing`
- **Tags:** Webinars
```

Get a webinar's SIP URI. The URI consists of the webinar ID, an optional user-supplied passcode, and participant identifier code. The API return data also includes additional fields to indicate whether the API caller has a valid Cloud Room Connector subscription, the participant identifier code from the URI, and the SIP URI validity period in seconds.

#### \*\*Prerequisites\*\*

- A Pro or higher plan with a [Webinar plan](https://zoom.us/webinar) add-on.

\*\*[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:write:sip\_dialing`,`webinar:write:admin:sip\_dialing`

\*\*[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):\*\*  
`webinar:write:sip\_dialing`,`webinar:write:sip\_dialing:admin`

\*\*[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):\*\* `LIGHT`

#### #### Request Body

##### Content-Type: application/json

```
- **`passcode`**
```

`string` — If customers want a passcode to be embedded in the SIP URI dial string, they must supply the passcode. Zoom will not validate the passcode.

#### \*\*Example:\*\*

```
```json
{
  "passcode": "xxxx"
}
```
```

#### #### Responses

##### Status: 201 `\**\HTTP Status Code:\**\`201\`` Webinar's encoded SIP URI returned.

##### Content-Type: application/json

- `\**\`expire_in\**`

`\integer\`, format: `\int64\`` — The number of seconds the encoded SIP URI is valid before it expires.

- `\**\`paid_crc_plan_participant\**`

`\boolean\`` — Whether the API caller has a Conference Room Connector (CRC) plan.

- `\**\`participant_identifier_code\**`

`\string\`` — This value identifies the webinar participant. It is automatically embedded in the SIP URI if the API caller has a CRC plan.

- `\**\`sip_dialing\**`

`\string\`` — The webinar's encoded SIP URI.

**Example:**

```
```json
{
  "sip_dialing": "9678722567.xxxx...30qonrvgy@zoomcrc.com",
  "paid_crc_plan_participant": true,
  "participant_identifier_code": "30qonrvgy",
  "expire_in": 7200
}
```
```

##### Status: 400 `\**\HTTP Status Code:\**\`400\`` `\<br>` Bad Request `\**\Error Code:\**\`300\`` `\<br>` Invalid webinar ID. `\<br>` `\**\Error Code:\**\`3000\`` `\<br>` Cannot access meeting information. `\<br>` `\**\Error Code:\**\`3000\`` `\<br>` The webinar's SIP URI does not exist: {webinarId}. `\<br>`

##### Status: 429 `\**\HTTP Status Code:\**\`429\`` `\<br>` Too Many Requests. For more information, see `\[rate limits]\(https://developers.zoom.us/docs/api/rest/rate-limits/)`.

### Update webinar status

- **Method:** `\PUT\``

- **Path:** `\{/webinars/{webinarId}/status\``

- **Tags:** Webinars

Update a webinar's status. Use this API to end an ongoing webinar.

**Prerequisites:**

- The account must hold a valid [Webinar plan](https://zoom.us/webinar).

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `\webinar:write:admin\``, `\webinar:write\``

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** `\webinar:update:status\``, `\webinar:update:status:admin\``

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** `\**\`LIGHT\``

##### Request Body

##### Content-Type: application/json

- `\**\`action\**`

`\string\``, possible values: `\"end"\``

**Example:**

```
```json
{
  "action": "end"
}
```
```

##### Responses

##### Status: 200 Webinar plan subscription is missing. Enable webinar for this user once the subscription is added: {userId}.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 3063` `You can not end an on-premise user's meeting: {webinarId} using this API.` `Invalid webinar ID.` `No permission.` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

### Get a webinar survey

- `Method: GET`  
 - `Path: /webinars/{webinarId}/survey`  
 - `Tags: Webinars`

Return information about a `[webinar survey]` (<https://support.zoom.us/hc/en-us/articles/360048745651>).

`Prerequisites:`

- A Pro or higher plan with the Webinar add-on.
- The `[Webinar Survey]` (<https://support.zoom.us/hc/en-us/articles/360061293191-Enabling-webinar-survey>) feature enabled in the host's account.

`[Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:admin`, `webinar:read`

`[Granular Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:read:survey`, `webinar:read:survey:admin`

`[Rate Limit Label]` (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

### Responses

##### Status: 200 `HTTP Status Code: 200` Webinar survey object returned.

##### Content-Type: application/json

- `custom_survey`

`object` — Information about the customized webinar survey.

- `anonymous`

`boolean`, default: `false` — Allow participants to anonymously answer survey questions. `true` - Anonymous survey enabled. `false` - Participants cannot answer survey questions anonymously. This value defaults to `true`.

- `feedback`

`string` — The survey's feedback, up to 320 characters. This value defaults to `Thank you so much for taking the time to complete the survey, your feedback really makes a difference.`

- `numbered_questions`

`boolean`, default: `false` — Whether to display the number in the question name. This value defaults to `true`.

- `questions`

`array` — Information about the webinar survey's questions.

`Items:`

- `answer_max_character`

`integer` — The allowed maximum number of characters. This field only applies to `short_answer` and `long_answer` questions. `For short_answer question, a maximum of 500 characters. For long_answer question, a maximum of 2,000 characters.`

- `answer_min_character`

`integer` — The allowed minimum number of characters. This field only applies to `short_answer` and `long_answer` questions. You must provide at least a `one` character minimum value.

- `answer_required`

`boolean`, default: `false` — Whether participants must answer the question. `true` - The

participant must answer the question. `\* \false\` - The participant does not need to answer the question. This value defaults to `\false\`.

- `\*\answers\*`

`\array\` — The survey question's available answers. This field requires a `\*\minimum\*` of two answers. `\*` For `\single\` and `\multiple\` questions, you can only provide a maximum of 50 answers. `\*` For `\matching\` polls, you can only provide a maximum of 16 answers. `\*` For `\rank_order\` polls, you can only provide a maximum of seven answers.

`\*\Items:\*`

`\string\`

- `\*\name\*`

`\string\` — The survey question, up to 420 characters.

- `\*\prompts\*`

`\array\` — Information about the prompt questions. This field only applies to `\matching\` and `\rank_order\` questions. You `\*\must\*` provide a minimum of two prompts, up to a maximum of 10 prompts.

`\*\Items:\*`

- `\*\prompt_question\*`

`\string\` — The question prompt's title.

- `\*\rating_max_label\*`

`\string\` — The high score label used for the `\rating_max_value\` field, up to 50 characters. This field only applies to the `\rating_scale\` survey.

- `\*\rating_max_value\*`

`\integer\` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the `\rating_scale\` survey.

- `\*\rating_min_label\*`

`\string\` — The low score label used for the `\rating_min_value\` field, up to 50 characters. This field only applies to the `\rating_scale\` survey.

- `\*\rating_min_value\*`

`\integer\` — The rating scale's minimum value. This value cannot be less than zero. This field only applies to the `\rating_scale\` survey.

- `\*\show_as_dropdown\*`

`\boolean\`, default: `\false\` — Whether to display the radio selection as a drop-down box. `\*\true\` - Show as a drop-down box. `\*\false\` - Do not show as a drop-down box. This value defaults to `\false\`.

- `\*\type\*`

`\string\`, possible values: `"single"`, `"multiple"`, `"matching"`, `"rank_order"`, `"short_answer"`, `"long_answer"`, `"fill_in_the_blank"`, `"rating_scale"` — The survey's question and answer type. `\*\single\` - Single choice. `\*\multiple\` - Multiple choice. `\*\matching\` - Matching. `\*\rank_order\` - Rank order. `\*\short_answer\` - Short answer. `\*\long_answer\` - Long answer. `\*\fill_in_the_blank\` - Fill in the blank. `\*\rating_scale\` - Rating scale.

- `\*\show_question_type\*`

`\boolean\`, default: `\false\` — Whether to display the question type in the question name. This value defaults to `\false\`.

- `\*\title\*`

`\string\` — The survey's title, up to 64 characters.

- `\*\show_in_the_browser\*`

`\boolean\`, default: `\true\` — Whether the `\*\Show in the browser when the webinar ends\*` option is enabled. `\*\true\` - Enabled. `\*\false\` - Disabled. This value defaults to `\true\`.

- `\*\show_in_the_follow_up_email\*`

`\boolean\`, default: `\false\` — Whether the `\*\Show the link on the follow-up email\*` option is enabled. `\*\true\` - Enabled. `\*\false\` - Disabled. This value defaults to `\false\`.

- **third\_party\_survey**

**string** — The link to the third party webinar survey.

**Example:**

**json**

```
{
 "custom_survey": {
 "title": "Learn something new",
 "anonymous": false,
 "numbered_questions": false,
 "show_question_type": false,
 "feedback": "Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.",
 "questions": [
 {
 "name": "How useful was this webinar?",
 "type": "single",
 "answer_required": false,
 "show_as_dropdown": false,
 "answers": [
 "Extremely useful"
],
 "prompts": [
 {
 "prompt_question": "How are you?"
 }
],
 "answer_min_character": 1,
 "answer_max_character": 200,
 "rating_min_value": 1,
 "rating_max_value": 4,
 "rating_min_label": "Not likely",
 "rating_max_label": "Extremely Likely"
 }
]
 },
 "show_in_the_browser": true,
 "show_in_the_follow_up_email": false,
 "third_party_survey": "https://example.com"
}
```

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **Invalid webinar ID.** **Error Code:** 300 **Webinar survey disabled. To enable this feature, enable the Webinar Survey setting in the Zoom web portal's Settings interface.** **Error Code:** 200 **No permission.** **Error Code:** 200 **Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.**

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 301 **Webinar does not exist: {webinarId}.**

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).**

**Delete a webinar survey**

**Method:** DELETE  
**Path:** /webinars/{webinarId}/survey  
**Tags:** Webinars

Delete a [webinar survey](https://support.zoom.us/hc/en-us/articles/360048745651).

**Prerequisites:**

- A Pro or higher plan with the Webinar Add-on.
- The [Webinar Survey](https://support.zoom.us/hc/en-us/articles/360061293191-Enabling-webinar-survey) feature enabled in the host's account.

**[Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** webinar:write, webinar:write:admin

**[Granular Scopes](https://developers.zoom.us/docs/integrations/oauth-scopes-overview/):** webinar:delete:survey, webinar:delete:survey:admin

**[Rate Limit Label](https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits):** LIGHT

## #### Responses

##### Status: 204 `HTTP Status Code: 204` Webinar survey deleted.

##### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid webinar ID.` `Error Code: 3000` Webinar survey disabled. To enable this feature, enable the `Webinar Survey` setting in the Zoom web portal's `Settings` interface. `Error Code: 200` `No permission.` `Error Code: 200` Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

##### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` Webinar does not exist: {webinarId}.

##### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).

## ### Update a webinar survey

- `Method: PATCH`  
 - `Path: /webinars/{webinarId}/survey`  
 - `Tags: Webinars`

Update a [webinar survey] (<https://support.zoom.us/hc/en-us/articles/360048745651>). `Prerequisites:` A Pro or higher plan with the Webinar add-on. Enable the `Webinar Survey` (<https://support.zoom.us/hc/en-us/articles/360061293191-Enabling-webinar-survey>) feature in the host's account.

`[Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:write`, `webinar:write:admin`

`[Granular Scopes]` (<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>): `webinar:update:survey`, `webinar:update:survey:admin`

`[Rate Limit Label]` (<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): `LIGHT`

## #### Request Body

##### Content-Type: application/json

`All of:`

- `custom_survey`

`object` — Information about the customized webinar survey.

- `anonymous`

`boolean`, default: `false` — Allow participants to anonymously answer survey questions. `true` - Anonymous survey enabled. `false` - Participants cannot answer survey questions anonymously. This value defaults to `true`.

- `feedback`

`string` — The survey's feedback, up to 320 characters. This value defaults to `Thank you so much for taking the time to complete the survey, your feedback really makes a difference.`

- `numbered_questions`

`boolean`, default: `false` — Whether to display the number in the question name. This value defaults to `true`.

- `questions`

`array` — Information about the webinar survey's questions.

`Items:`

- `answer_max_character`

`integer` — The allowed maximum number of characters. This field only applies to `short_answer` and `long_answer` questions. For `short_answer` question, a maximum of 500 characters. For `long_answer` question, a maximum of 2,000 characters.

- `answer_min_character`

`integer` — The allowed minimum number of characters. This field only applies to `short_answer` and `long_answer` questions. You must provide at least a `one` character minimum value.

- `answer_required`

``boolean``, default: ``false`` — Whether participants must answer the question. ``*` `true`` - The participant must answer the question. ``*` `false`` - The participant does not need to answer the question. This value defaults to ``false``.

- `**`answers`**`

``array`` — The survey question's available answers. This field requires a ``*`minimum`*`` of two answers. ``*` For `single` and `multiple` questions, you can only provide a maximum of 50 answers. `*` For `matching` polls, you can only provide a maximum of 16 answers. `*` For `rank_order` polls, you can only provide a maximum of seven answers.`

`**Items:**`

``string``

- `**`name`**`

``string`` — The survey question, up to 420 characters.

- `**`prompts`**`

``array`` — Information about the prompt questions. This field only applies to ``matching`` and ``rank_order`` questions. You ``*`must`*`` provide a minimum of two prompts, up to a maximum of 10 prompts.

`**Items:**`

- `**`prompt_question`**`

``string`` — The question prompt's title.

- `**`rating_max_label`**`

``string`` — The high score label used for the ``rating_max_value`` field, up to 50 characters. This field only applies to the ``rating_scale`` survey.

- `**`rating_max_value`**`

``integer`` — The rating scale's maximum value, up to a maximum value of 10. This field only applies to the ``rating_scale`` survey.

- `**`rating_min_label`**`

``string`` — The low score label used for the ``rating_min_value`` field, up to 50 characters. This field only applies to the ``rating_scale`` survey.

- `**`rating_min_value`**`

``integer`` — The rating scale's minimum value. This value can't be less than zero. This field only applies to the ``rating_scale`` survey.

- `**`show_as_dropdown`**`

``boolean``, default: ``false`` — Whether to display the radio selection as a drop-down box. ``*` `true`` - Show as a drop-down box. ``*` `false`` - Do not show as a drop-down box. This value defaults to ``false``.

- `**`type`**`

``string``, possible values: ``"single", "multiple", "matching", "rank_order", "short_answer", "long_answer", "fill_in_the_blank", "rating_scale`` — The survey's question and answer type. ``*` `single`` - Single choice. ``*` `multiple`` - Multiple choice. ``*` `matching`` - Matching. ``*` `rank_order`` - Rank order ``*` `short_answer`` - Short answer ``*` `long_answer`` - Long answer. ``*` `fill_in_the_blank`` - Fill in the blank ``*` `rating_scale`` - Rating scale.

- `**`show_question_type`**`

``boolean``, default: ``false`` — Whether to display the question type in the question name. This value defaults to ``false``.

- `**`title`**`

``string`` — The survey's title, up to 64 characters.

- `**`show_in_the_browser`**`

``boolean``, default: ``true`` — Whether the ``*`Show in the browser when the webinar ends`*`` option is enabled. ``*` `true`` - Enabled. ``*` `false`` - Disabled. This value defaults to ``true``.

- `**`show_in_the_follow_up_email`**`



`boolean`, default: `false` — Whether the `Show the link on the follow-up email` option is enabled.  
 `true` - Enabled. `false` - Disabled. This value defaults to `false`.

- **third\_party\_survey**

`string` — The link to the third party webinar survey.

**Example:**

```
```json
{
  "custom_survey": {
    "title": "Learn something new",
    "anonymous": false,
    "numbered_questions": false,
    "show_question_type": false,
    "feedback": "Thank you so much for taking the time to complete the survey. Your feedback really makes a difference.",
    "questions": [
      {
        "name": "How useful was this webinar?",
        "type": "single",
        "answer_required": false,
        "show_as_dropdown": false,
        "answers": [
          "Extremely useful"
        ],
        "prompts": [
          {
            "prompt_question": "How are you?"
          }
        ],
        "answer_min_character": 1,
        "answer_max_character": 200,
        "rating_min_value": 1,
        "rating_max_value": 4,
        "rating_min_label": "Not likely",
        "rating_max_label": "Extremely Likely"
      }
    ]
  },
  "show_in_the_browser": true,
  "show_in_the_follow_up_email": false,
  "third_party_survey": "https://example.com"
},
```
```

#### Responses

##### Status: 204 **HTTP Status Code:** 204 **Webinar survey updated.**

##### Status: 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **Invalid webinar ID.** **Error Code:** 300 **Invalid third party survey:** {third\_party\_survey}. **Error Code:** 300 **Webinar survey disabled.** To use this feature, enable the **Webinar Survey** setting in the Zoom web portal's **Settings** interface. **Error Code:** 300 **The host isn't allowed to use a third party survey link.** To use this feature, enable the "Allow host to use a 3rd-party survey link" setting in the "Account Settings" page of the Zoom web portal. **Error Code:** 200 **No permission.** **Error Code:** 200 **Webinar plan is missing.** You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.

##### Status: 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Webinar does not exist:** {webinarId}.

##### Status: 429 **HTTP Status Code:** 429 **Too Many Requests.** For more information, see [\[rate limits\]](https://developers.zoom.us/docs/api/rest/rate-limits/)(https://developers.zoom.us/docs/api/rest/rate-limits/).

#### Get webinar's token

- **Method:** GET  
 - **Path:** /webinars/{webinarId}/token  
 - **Tags:** Webinars

Use this API to get a webinar's [closed caption token (caption URL)](https://support.zoom.us/hc/en-us/articles/115002212983-Using-a-third-party-closed-captioning-service). This token lets you use a third-party service to stream text to their closed captioning software to the Zoom webinar.

**Prerequisites:**

- A Pro or higher plan with the Webinar add-on.

- The **Closed captioning** setting enabled in the Zoom web portal.
- The **Allow use of caption API Token to integrate with 3rd-party Closed Captioning services** setting enabled.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`webinar:read`,`webinar:read:admin`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`webinar:read:token`,`webinar:read:token:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **LIGHT**

#### Responses

**Status:** 200 **HTTP Status Code:** 200 Webinar token returned.

**Content-Type:** application/json

**token**

**string** — The generated webinar token.

**Example:**

```

{
 "token": "https://example.com/closedcaption?
id=200610693&ns=GZHkEA==&expire=86400&sparams=id%2Cns%2Cexpire&signature=nYtXJqRKCW"
}

```

**Status:** 400 **HTTP Status Code:** 400 **Bad Request** **Error Code:** 300 **Invalid webinar ID.** **Error Code:** 3000 **Closed captioning disabled. To enable this feature, enable the Closed captioning and Allow use of caption API Token to integrate with 3rd-party Closed Captioning services settings in the Zoom web portal's Settings interface.** **Error Code:** 3000 **Webinar {webinarId} has not started.** **Error Code:** 200 **No permission.** **Error Code:** 200 **Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.**

**Status:** 404 **HTTP Status Code:** 404 **Not Found** **Error Code:** 3001 **Webinar does not exist: {webinarId}.**

**Status:** 429 **HTTP Status Code:** 429 **Too Many Requests. For more information, see [Rate limits](https://developers.zoom.us/docs/api/rest/rate-limits/).**

#### Get webinar tracking sources

**Method:** GET  
**Path:** /webinars/{webinarId}/tracking\_sources  
**Tags:** Webinars

**[Webinar Registration Tracking Sources]**(<https://support.zoom.us/hc/en-us/articles/360000315683-Webinar-Registration-Source-Tracking>) allow you to see where your registrants are coming from if you share the webinar registration page in multiple platforms. You can then use the source tracking to see the number of registrants generated from each platform.  
Use this API to list information on all the tracking sources of a Webinar.

**Prerequisites:**

- [Webinar license](<https://zoom.us/webinar>).
- Registration must be required for the Webinar.

**[Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`webinar:read:admin`,`webinar:read`

**[Granular Scopes]**(<https://developers.zoom.us/docs/integrations/oauth-scopes-overview/>):  
`webinar:read:list\_tracking\_sources`,`webinar:read:list\_tracking\_sources:admin`

**[Rate Limit Label]**(<https://marketplace.zoom.us/docs/api-reference/rate-limits#rate-limits>): **MEDIUM**

#### Responses

**Status:** 200 **HTTP Status Code:** 200

**Content-Type:** application/json

**total\_records**

**integer** — The total number of registration records for this Webinar.

- **tracking\_sources**

`array` — Tracking Sources object.

**Items:**

- **id**

`string` — Unique Identifier of the tracking source.

- **registration\_count**

`integer` — Number of registrations made from this source.

- **source\_name**

`string` — Name of the source (platform) where the registration URL was shared.

- **tracking\_url**

`string` — Tracking URL. The URL that was shared for the registration.

- **visitor\_count**

`integer` — Number of visitors who visited the registration page from this source.

**Example:**

`json`

```
{
 "total_records": 1,
 "tracking_sources": [
 {
 "id": "5516482804110",
 "registration_count": 1,
 "source_name": "https://example.com",
 "tracking_url": "https://example.com/webinar/register/5516482804110/WN_juM2BGyLQMyQ_ZrqiGRhLg",
 "visitor_count": 1
 }
]
}
```

#### Status: 400 `HTTP Status Code: 400` `Bad Request` `Error Code: 300` `Invalid webinar ID.` `Error Code: 200` `No permission.` `Error Code: 200` `Webinar plan is missing. You must subscribe to the webinar plan and enable webinars for this user in order to perform this action.`

#### Status: 404 `HTTP Status Code: 404` `Not Found` `Error Code: 3001` `Webinar does not exist: {webinarId}.`

#### Status: 429 `HTTP Status Code: 429` `Too Many Requests.` For more information, see `[rate limits]` (<https://developers.zoom.us/docs/api/rest/rate-limits/>).