



Naïve Bayes' Classifier



Naïve Bayes Classifier

- Naïve Bayes Classifier can be trained **easily** and **fast** and can be used as **benchmark model**.
- When **variable selection** is carried out properly, Naïve Bayes can **perform** as well as or even **better** than other **statistical** models such as logistic regression.
- Naive Bayes requires a **strong assumption of independent predictors**, so when the model has a **bad performance**, the reason leading to that may be the **dependence between predictors**.
- Doesn't require feature scaling

Naïve Bayes' Classifier



Naïve Bayes' Classifier:

- Naive Bayes is the simplest algorithm that you can apply to your data.
- This algorithm assumes all the variables in the dataset “Naive” i.e., not correlated to each other.
- It requires categorical values.
- It uses Bayes' theorem as its base.
- Mostly used to get the base accuracy of the dataset.
- Mostly used with:
 - Real time Prediction.
 - Multi class Prediction.
 - Text classification/ Spam Filtering/ Sentiment Analysis, and Recommendation Systems.



Types

- ⬡ Multinomial Naïve Bayes → for text (word counts).
- ⬡ Bernoulli Naïve Bayes → for binary data (0/1 features).
- ⬡ Gaussian Naïve Bayes → for numerical (continuous) data.

Example:

Priors: احتمال كل كلاس حسب عدد الأمثلة.

Likelihoods: لكل Feature، عدد كم مرة ظهر مع كل كلاس.

LIKELIHOOD
the probability of "B"
being TRUE given that "A" is TRUE

PRIOR
the probability of
"A" being TRUE

$$P(A|B) = \frac{P(B|A) P(A)}{P(B)}$$

POSTERIOR
the probability of "A"
being TRUE given that "B" is TRUE

The probability
of "B" being
TRUE

- **Problem:** Classify whether an email is "spam" or "not spam"
- **Features:** Presence (1) or absence (0) of words "buy", "cheap", "offer".
- **Training Data:**

Email	buy	cheap	offer	Class
1	1	0	1	spam
2	1	1	0	not spam
3	0	1	1	spam
4	1	0	0	not spam
5	0	1	1	spam


Calculate Priors

Prior Probability of Spam ($P(\text{spam})$):

$$P(\text{spam}) = \frac{\text{Number of spam emails}}{\text{Total number of emails}} = \frac{3}{5} = 0.6$$

Prior Probability of Not Spam ($P(\text{not spam})$):

$$P(\text{not spam}) = \frac{\text{Number of not spam emails}}{\text{Total number of emails}} = \frac{2}{5} = 0.4$$



Calculate Likelihoods

- **Likelihoods for "spam" class:(1,3,5)**
 - buy=1 → 1/3 , buy=0 → 2/3
 - cheap=1 → 2/3 , cheap=0 → 1/3
 - offer=1 → 3/3=1 , offer=0 → 0
- **Likelihoods for "not spam" class: (2,4)**
 - buy=1 → 2/2=1 , buy=0 → 0
 - cheap=1 → 1/2 , cheap=0 → 1/2
 - offer=1 → 0 , offer=0 → 2/2=1

New Email to Classify

- New Email: $"buy"=1, "cheap"=1, "offer"=0$
- Objective: Determine whether the new email is "spam" or "not spam".

Calculate Posterior for Spam

1

Posterior Probability of Spam

$$(P(\text{spam} \mid \text{buy} = 1, \text{cheap} = 1, \text{offer} = 0))$$

$$\propto P(\text{buy} = 1 \mid \text{spam}) \cdot P(\text{cheap} = 1 \mid \text{spam}) \cdot P(\text{offer} = 0 \mid \text{spam}) \cdot P(\text{spam})$$

$$= (1/3) * (2/3) * (0) * 0.6 = 0$$

New Email to Classify

- New Email: "*buy*"=1,"*cheap*"=1,"*offer*"=0
- Objective: Determine whether the new email is "spam" or "not spam".

Calculate Posterior for Not Spam

2

Posterior Probability for Not Spam

$$P(\text{notspam} \mid \text{buy} = 1, \text{cheap} = 1, \text{offer} = 0)$$

$$\propto P(\text{buy} = 1 \mid \text{notspam}) \cdot P(\text{cheap} = 1 \mid \text{notspam}) \cdot P(\text{offer} = 0 \mid \text{notspam}) \cdot P(\text{notspam})$$

$$= (1) * (\frac{1}{2}) * (1) * 0.4 = \mathbf{0.2}$$

New Email: *"buy"=1,"cheap"=1,"offer"=0*

Step 5: Final Decision

- Spam = 0
- Not Spam = 0.2

👉 Email classify as : Not Spam ✓

Why Normalize Probabilities?

1. To Compare Probabilities Directly:

- a. When calculating conditional probabilities $P(Y|X)$ using Bayes' Theorem, we need to normalize the probabilities so they can be compared directly.
- b. Without normalization, the probabilities are not on the same scale and cannot be directly compared.

Example: Spam = 0.2, Not Spam = 0.05

→ Without normalization, you could say "Spam is bigger."

→ **But to say Spam = 80% chance and Not Spam = 20% chance, you need normalization.**

2. To Ensure the Probabilities Sum to 1:

- a. After normalization, the sum of the probabilities for all classes (e.g., spam and not spam) should equal 1.
- b. This ensures we have a valid probability distribution that can be used for classification.

⬡ Without smoothing → rare/missing features kill probabilities.

- If a **feature is very rare or never appears** in the training data for a class, then its likelihood becomes **0**.

⬡ With Laplace smoothing → every feature has at least a small chance, making the model more robust.

Laplace Smoothing (Add-1 Smoothing)

- To fix this, we use **Laplace smoothing** (also called **add-1 smoothing**).
- Instead of using raw counts, we add **+1 to every count**:

$$P(\text{feature} \mid \text{class}) = \frac{\text{count}(\text{feature}, \text{class}) + 1}{\text{count}(\text{class}) + k}$$

where:

- k = number of possible feature values (for binary features, $k = 2$).

Example

Suppose in “Spam” emails we never saw the word “offer=0”.

- Without smoothing:

$$P(\text{offer} = 0 \mid \text{Spam}) = 0$$

- With Laplace smoothing:

$$P(\text{offer} = 0 \mid \text{Spam}) = \frac{0 + 1}{3 + 2} = 0.2$$

Now it's a small probability instead of zero.

Supervised machine learning

Algorithm	Needs Feature Scaling?	Reason
KNN (K-Nearest Neighbors)	✅ Yes	Relies on distance between points
SVM (Support Vector Machine)	✅ Yes	Depends on dot product and distances
Linear Regression	✅ (Recommended)	Regularization + Gradient Descent convergence
Logistic Regression	✅ (Recommended)	Regularization + coefficient stability
Decision Tree	❌ No	Works with threshold splits, not distances
Random Forest	❌ No	Based on Decision Trees
Naïve Bayes	⚠️ Sometimes	<ul style="list-style-type: none">- Gaussian NB assumes normally distributed data → scaling helps- Multinomial / Bernoulli NB: handle counts/binary values → scaling not needed