

```

from .layers import *

"""
This code was originally written for CS 231n at Stanford University
(cs231n.stanford.edu). It has been modified in various areas for use in the
ECE 239AS class at UCLA. This includes the descriptions of what code to
implement as well as some slight potential changes in variable names to be
consistent with class nomenclature. We thank Justin Johnson & Serena Yeung for
permission to use this code. To see the original version, please visit
cs231n.stanford.edu.
"""

def affine_relu_forward(x, w, b):
    """
    Convenience layer that performs an affine transform followed by a ReLU

    Inputs:
    - x: Input to the affine layer
    - w, b: Weights for the affine layer

    Returns a tuple of:
    - out: Output from the ReLU
    - cache: Object to give to the backward pass
    """
    a, fc_cache = affine_forward(x, w, b)
    out, relu_cache = relu_forward(a)
    cache = (fc_cache, relu_cache)
    return out, cache

def affine_relu_backward(dout, cache):
    """
    Backward pass for the affine-relu convenience layer
    """
    fc_cache, relu_cache = cache
    da = relu_backward(dout, relu_cache)
    dx, dw, db = affine_backward(da, fc_cache)
    return dx, dw, db

def bn_affine_relu_forward(x, w, b, gamma, beta, bn_param):
    """
    Helper function for batch-norm affine relu forward
    """
    out, fc_cache = affine_forward(x, w, b)
    out, bn_cache = batchnorm_forward(out, gamma, beta, bn_param)
    out, relu_cache = relu_forward(out)
    cache = (fc_cache, bn_cache, relu_cache)

    return out, cache

def bn_affine_relu_backward(dout, cache):
    """
    Helper function for batch-norm affine relu backward
    """

    fc_cache, bn_cache, relu_cache = cache
    # da = relu_backward(dout, relu_cache)
    dout = relu_backward(dout, relu_cache)
    dout, dgamma, dbeta = batchnorm_backward(dout, bn_cache)
    dx, dw, db = affine_backward(dout, fc_cache)

    return dx, dw, db, dgamma, dbeta

```