

# McPhail Trap Main Board v1.0

Collect, analyze, and report back the environmental data.

This is an attempt to reproduce the work of identifying fruit flies from the following papers:

- 2017: [Automated Surveillance of Fruit Flies](#)
- 2015: [Insect Biometrics: Optoacoustic Signal Processing and its Applications to Remote Monitoring](#)
- 2014: [The Electronic McPhail Trap](#)
- 1979: [Optical Tachometer for Measurement of Wingbeat Frequency of Free-Flying Insects](#)

Parallels the European [ENTOMATIC](#) project.

## Hardware Version Notes

- v1.x, proof of concept, collect data on SD card and over USB Fona breakout board supports texting
- v2.x, switch to ARM MSP430 or other ADC-specific chip, collect data on SD card
- v3.x, integrate mesh net or other networking, possibly more sophisticated offboard analysis

## Design Notes

### Physical Housing

Putting the electronics in acrylic separate from the insects so the ultrasonic isn't bothering them. An acrylic housing placed on top of the trap provides protection from the elements as well as protects the insects from any electronics noise.

If all circuitry is on the board at the top, the IR emitters and photodiode detectors can be the only items in the trap with the insects and be connected by a minimum of cabling.

### Security and Connectivity Platforms for reference

- Particle
- Electric Imp

### v1 FONA808 GSM+GPS MODULE

- PS is power status. Check this after toggling KEY. Pin is low when module is off, and high when module is on.
- NS is network status. It pulses to signal current module status
- RST is hard reset to be used only when module is really stuck.
- RX/TX are pins capable of Software Serial. They are auto-baud so whatever baud you send "AT" after reset or boot is the baud rate the module will use.
- RTS is hardware flow control. Optional. Turn it on in module if you want to use it.
- RI is the ring indicator output. Use it as an interrupt. Default high. Pin will pulse low for 120ms when a call or SMS is received.

The GPS is accessible on the Rx/Tx lines so you can query using AT commands and get the values back. No additional pins are necessary.

## RTC

The DS1307 real time clock is out of date, replaced it with a MCP7940N. Needs some adjustment to the circuitry and crystal to minimize ppm (frequency tolerance) to minimize time slipping, which could be up to a few minutes per month in the worst case.

TODO: quantify this deviation, discuss mitigation

## Temperature

TODO: find out how hot a plastic bottle hanging in the sun in Arizona in August could get.

## Capacitors

Mostly ceramic capacitors were chosen for cost and size, with C0G/NP0 and X7R temperature coefficients. Aluminum electrolytic capacitors were chosen where ceramics were cost-prohibitive or where specifically indicated in datasheets.

The temperature coefficients:


X7R means a capacitor is a temperature-stable (EIA Class 2) cap which only varies up to  $\pm 15\%$  from  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ . [ref](#)


C0G/NP0 means a capacitor is temperature-compensating (EIA Class 1) which varies less than  $\pm 0.3\%$  C from  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ . Capacitance drift or hysteresis is less than  $\pm 0.05\%$ . [ref](#)

## Assembly Information

The following layout is only to get a rough idea of how much area the parts would require if they were all on one side of one board. The area is 3 inches x 3 inches, or 9 square inches, and a set of three bare boards would cost \$48.20 for three with a manufacturing turnaround of about ten days.

Rough cost of parts for a single board is about \$50.





## Bill of Materials

Ref	Qty	Description	Digikey PN
BAT1	1	CR1220 BATTERY HOLDER SMT FLATPIN	BK-916-CT-ND
C1	1	CAP ALUM 330UF 20% 16V RADIAL	732-8798-1-ND
C10 C3	2	CAP CER 0.27UF 16V X7R 0603	490-6427-1-ND
C11 C13 C2 C7	4	CAP CER 1.5UF 25V X7R 1206	1276-6873-1-ND
C12 C28 C8	3	CAP CER 0.01UF 50V X7R 0603	490-1512-1-ND
C14 C29 C34 C4 C49 C50 C9	7	CAP CER 1UF 25V X7R 0805	1276-1066-1-ND
C15 C6	2	CAP CER 22UF 25V X7R 1210	1276-3392-1-ND
C16 C17 C19 C22	4	CAP CER 2.2UF 25V X7R 0805	1276-2953-1-ND
C18	1	CAP CER 33PF 16V X7R 0603	478-6211-1-ND
C20 C21 C23 C24 C43-C46	8	CAP CER 4.7UF 50V X7R 1206	587-2994-1-ND
C25	1	CAP CER 10UF 16V X7R 0805	1276-2872-1-ND
C26 C30-C32 C36-C39 C47	9	CAP CER 0.1UF 100V X7R 0603	490-3285-1-ND
C27	1	CAP CER 0.022UF 50V X7R 0603	1276-2004-1-ND
C33 C35	2	CAP CER 22pF 50V NP0 0603	399-9031-1-ND
C40 C42	2	CAP CER 2PF 50V C0G/NP0 0603	490-10713-1-ND
C41	1	CAP CER 100PF 50V C0G/NP0 0603	490-1427-1-ND
C48	1	CAP CER 10PF 50V NP0 0603	1276-2154-1-ND
C5	1	CAP CER 0.039UF 50V X7R 0603	1276-2056-1-ND
D1 D4	2	DIODE SCHOTTKY 20V 1A SMA	SS12-E3/61TGICT-ND
D2 D3	2	VARISTOR ESD PROTECT USB	CG0603MLC-05ECT-ND
F1	1	RESETTABLE FUSE 500mA 15V MF-MSMF	MF-MSMF050-2CT-ND
J1 J2	2	HEADER MALE 2POS TH 1x02 0.1IN	952-2262-ND
J3	1	HEADER MALE 6POS KK100 0.1IN SHROUD TH	WM4204-ND
J4	1	CONN MICRO SD CARD PUSH-PULL	WM9731CT-ND
J5	1	USB MICRO-B RECEPTACLE 5PIN SMT	609-4616-1-ND
J6	1	HEADER MALE 6POS 2x3 0.1IN	952-1921-ND
J8	1	CONN PWR JACK 2.5X5.5MM HIGH CUR	PJ-202BH
J9	1	CONN HEADER PH SIDE 2POS 2MM	455-1719-ND
L1	1	FERRITE BEAD 220 OHM 0402 1LN	240-2554-1-ND
LED1 LED2 LED3	3	LED AMBER DIFFUSED 0603 SMD	475-2712-1-ND
R1	1	RES SMD 220 OHM 5% 1/10W 0603	311-220GRCT-ND

Ref	Qty	Description	Digikey PN
R10	1	RES SMD 732 OHM 1% 1/10W 0603	P732HCT-ND
R11 R8	2	RES SMD 1.43K OHM 1% 1/10W 0603	P1.43KHCT-ND
R12 R16 R23	3	RES SMD 2.26K OHM 1% 1/10W 0603	311-2.26KHRCT-ND
R13 R33 R36	3	RES SMD 10K OHM 1% 1/8W 0603	RNCP0603FTD10K0CT-ND
R14 R39 R40 R41	4	RES SMD 470 OHM 5% 1/4W 0603	RHM470DCT-ND
R15	1	RES SMD 97.6K OHM 1% 1/10W 0603	P97.6KHCT-ND
R17	1	RES SMD 68 OHM 1% 1/10W 0603	P68.0HCT-ND
R18 R19	2	RES SMD 91K OHM 1% 1/10W 0603	P91.0KHCT-ND
R2	1	RES SMD 64.9K OHM 1% 1/10W 0603	P64.9KHCT-ND
R20 R21	2	RES SMD 220K OHM 5% 1/8W 0805	P220KACT-ND
R22 R26	2	RES SMD 2.2K OHM 5% 1/10W 0603	P2.2KGCT-ND
R24 R28	2	RES SMD 22K OHM 5% 1/10W 0603	P22KGCT-ND
R25 R29	2	RES SMD 4.32K OHM 1% 1/10W 0603	P4.32KHCT-ND
R27	1	RES SMD 2.94K OHM 1% 1/10W 0603	P2.94KHCT-ND
R3 R4 R44	3	RES SMD 100K OHM 1% 1/10W 0603	RMCF0603FG100KCT-ND
R30 R6	2	RES SMD 3.83K OHM 1% 1/10W 0603	P3.83KHCT-ND
R31 R32	2	RES 22 OHM 5% 1/10W 0603	311-22GRCT-ND
R34 R35 R43	3	RES SMD 2K OHM 1% 1/8W 0603	RNCP0603FTD2K00CT-ND
R37	1	RES SMD 1K OHM 1% 1/10W 0603	1276-3484-1-ND
R38	1	RES SMD 0.0 OHM JUMPER 1/8W 0603	MCT0603-0.0-ZZCT-ND
R42	1	NTC THERMISTOR 10K OHM 1% 0402	445-2550-1-ND
R45 R47	2	RES SMD 1M OHM 5% 1/10W 0603	P1.0MGCT-ND
R46	1	RES SMD 111K OHM 5% 1/10W 0603	P110GCT-ND
R5	1	RES SMD 1.87K OHM 1% 1/10W 0603	P1.87KHCT-ND
R7	1	RES SMD 10 OHM 1% 1/10W 0603	P10.0HCT-ND
R9	1	RES SMD 470 OHM 5% 1/4W 0603	311-1.02KHRCT-ND
S1	1	SWITCH TACTILE SPST-NO 0.05A 12V	SW1020CT-ND
U1 U2 U4	3	IC OPAMP QUAD GP RRO 1MHZ SOIC14	MCP6004T-I/SLCT-ND
U10	1	IC REG BUCK BOOST ADJ 2A 10WSON	296-30204-1-ND
U11	1	IC REG LDO 3.3V 0.25A MCP1703 SOT23A-3	MCP1703T-3302E/CBCT-ND
U3	1	IC OPAMP GP 3MHZ RRO 14SOIC	296-39258-1-ND
U5	1	IC VOLT-LEVEL TRANSLATOR TXB0104 SOIC14	296-21928-1-ND
U6	1	MCU 8BIT ATMEGA32U4 44TQFP	ATMEGA32U4RC-AU-ND
U7	1	IC EEPROM 1MBIT 400KHZ 24AA1025 SOIC8	24AA1025-I/SN-ND
U8	1	IC RTC CLK/CALENDAR I2C MCP7940N SOIC8	MCP7940N-E/SN-ND
U9	1	IC USB/AC BATT CHRGR MCP73871 20QFN	MCP73871T-2CCI/MLCT-ND
X1	1	CRYSTAL 16MHZ 30PPM 18pF 4SMD	CTX1206CT-ND
X2	1	CRYSTAL 32.768kHz 7pF CFS-20632768DZBYB	300-8842-ND

Ref	Qty	Description	Adafruit PN
B1	1	Lithium Ion Polymer Battery - 3.7v 500mAh	1578
J7	1	ADAFRUIT FONA 808 + GPS	2542

Ref	Qty	Description	Mouser PN
L2	1	FIXED IND 1UH 11A XFL4020-102	994-XFL4020-102MEC