

# Outline

- Explain and discuss the concepts of datamining.
- Explain and discuss the concepts of training versus testing data-sets.
- discuss descriptive models in SSAS.
- Create a descriptive data-mining solution using the Microsoft decision tree algorithm.

# Data Mining: Overview

- What is Data Mining?
  - Recently coined term for confluence of ideas from statistics and computer science (machine learning and database methods) applied to large databases in science, engineering and business.
  - In a state of flux, many definitions, lot of debate about what it is and what it is not. Terminology not standard e.g. bias, classification, prediction, feature = independent variable, target = dependent variable, case = exemplar = row.
  - \* First International workshop on Knowledge Discovery and Data Mining was in 1995
- 1

# Broad and Narrow Definitions

- Broad Definition includes traditional statistical methods, Narrow Definition emphasizes automated and heuristic methods
- Data mining, data dredging, fishing expeditions various terms ppl using to name data mining
- Knowledge Discovery in Databases (KDD)

What is a heuristic approach?



In computer science, artificial intelligence, and mathematical optimization, a **heuristic** (from Greek εὕρισκω "I find, discover") is a technique designed for solving a problem more quickly when classic **methods** are too slow, or for finding an approximate solution when classic **methods** fail to find any exact solution.

# Another definition by Nitin Patel

- “Statistics at scale and speed” Darryl Pregibon
- My extension:
  - – “. . . And simplicity”

# Gartner Group

- “Data mining is the process of discovering meaningful new correlations, patterns and trends by sifting through large amounts of data stored in repositories, using pattern recognition technologies as well as statistical and mathematical techniques.”

# Evolution of data

IBM **Informix** is a product family within IBM's Information Management division that is centered on several relational database management system (RDBMS) offerings. The **Informix** products were originally developed by **Informix** Corporation, whose **Informix** Software subsidiary was acquired by IBM in 2001.

Evolutionary Step	Business Question	Enabling Technologies	Product Providers	Characteristics
Data Collection (1960s)	"What was my total revenue in the last five years?"	Computers, tapes, disks	IBM, CDC	Retrospective, static data delivery
Data Access (1980s)	"What were unit sales in New England last March?"	Relational databases (RDBMS), Structured Query Language (SQL), ODBC	Oracle, Sybase, Informix, IBM, Microsoft	Retrospective, dynamic data delivery at record level
Data Warehousing & Decision Support (1990s)	"What were unit sales in New England last March? Drill down to Boston."	On-line analytic processing (OLAP), multidimensional databases, data warehouses	Pilot, Comshare, Arbor, Cognos, Microstrategy	Retrospective, dynamic data delivery at multiple levels
Data Mining (Emerging Today)	"What's likely to happen to Boston unit sales next month? Why?"	Advanced algorithms, multiprocessor computers, massive databases	Pilot, Lockheed, IBM, SGI, numerous startups (nascent industry)	Prospective, proactive information delivery

Retrospective

Prospective

industries need prediction

Able to access others' data

Lockheed Martin Corporation is an American global aerospace, defense, security and advanced technologies company with worldwide interests. It was formed by the merger of Lockheed Corporation with Martin Marietta in March 1995. It is headquartered in North Bethesda, Maryland, in the Washington, DC, area. [Wikipedia](#)

# Drivers for Data Mining

- Market: From focus on product/service to focus on customer
- IT: From focus on up-to-date balances to focus on patterns in transactions - Data Warehouses -  
shift in focus
- OLAP
- Dramatic drop in storage costs : Huge databases
  - e.g Walmart: 20 million transactions/day, 10 terabyte database, Blockbuster: 36 million households
- Automatic Data Capture of Transactions
  - e.g. Bar Codes , P OS de vices, Mouse clicks, Location data ( GPS, cell phones)
- Internet: Personalized interactions, longitudinal data

# Core Disciplines

- Statistics (adapted for 21st century data sizes and speed requirements). Examples:
  - Descriptive: Visualization
  - Models ( DMD): Regression, Cluster Analysis
- Machine Learning: e.g. Neural Nets
- Data Base Retrieval: e.g. Association Rules
- Parallel developments: e.g. Tree methods, k Nearest Neighbors, OLAP-EDA



# Typical characteristics of mining data

- “Standard” format is spreadsheet:
  - Row=observation unit, Column=variable
- Many rows, many columns
- Many rows moderate number of columns (e.g. tel. calls)
- Many columns, moderate number of rows (e.g. genomics)
- Opportunistic (often by-product of transactions)
  - Not from designed experiments
  - Often has outliers, missing data

# Process – Data mining

1. Develop understanding of application, goals
2. Create dataset for study (often from Data Warehouse)
3. Data Cleaning and Preprocessing
4. Data Reduction and projection
5. Choose Data Mining task
6. Choose Data Mining algorithms
7. Use algorithms to perform task
8. Interpret and iterate thru 1-7 if necessary
9. Deploy: integrate into operational systems.

Data  
Mining

# Data mining as a process of knowledge discovery


- Data cleaning, a process that removes or transforms noise and inconsistent data ETL
- Data integration, where multiple data sources may be combined
- Data selection, where data relevant to the analysis task are retrieved from the database
- Data transformation, where data are transformed or consolidated into forms appropriate for mining
- Data mining, an essential process where intelligent and efficient methods are applied in order to extract patterns
- Pattern evaluation, a process that identifies the truly interesting patterns representing knowledge based on some interestingness measures
- Knowledge presentation, where visualization and knowledge representation techniques are used to present the mined knowledge to the user

# Knowledge Discovery Process flow, according to CRISP-DM

Cross-industry standard process for ...



Cross-industry standard process for data mining, known as CRISP-DM, is an open standard process model that describes common approaches used by data mining experts. It is the most widely-used analytics model.



see

[www.crisp-dm.org](http://www.crisp-dm.org)

for more  
information

Continuous  
monitoring and  
improvement is  
an addition to CRISP

# Training

test question

- Training Partition
- The training partition is typically the largest partition, and contains the data used to build the various models we are examining. The same training partition is generally used to develop multiple models.


# Validation

This partition (sometimes called the “test” partition) is used to assess the performance of each model, so that you can compare models and pick the best one. In some algorithms (e.g. classification and regression trees), the validation partition may be used in automated fashion to tune and improve the model.

# Test


- Test Partition
- This partition (sometimes called the “holdout” or “evaluation” partition) is used if we need to assess the performance of the chosen model with new data.
- Why have both a validation and a test partition? When we use the validation data to assess multiple models and then pick the model that does best with the validation data, we again encounter another (lesser) facet of the overfitting problem — chance aspects of the validation data that happen to match the chosen model better than other models.

# Classification Step 1: Split data into train and test sets






# Classification Step 2: Build a model on a training set




# Classification Step 3: Evaluate on test set (Re-train?)



# Classification:

## Train, Validation, Test split



# SEMMA Methodology (SAS)

- **S**ample from data sets, Partition into
- Training, Validation and Test datasets
- **E**xplore data set statistically and graphically
- **M**odify: Transform variables, Impute missing values
- **M**odel: fit models e.g. regression, classification tree, neural net
- **A**ssess: Compare models using Partition, Test datasets

statistically look at data, to make sure you don't have some crazy anomalies which could throw off your data  
e.g. some random ages 120+ y/o in your data set can skew your models

# Core Concepts

- Types of Data:

- – Numeric

- Continuous – ratio and interval

- Discrete

- Need for Binning

- Categorical – order and unordered

- Binary

- Overfitting and Generalization

- Distance

- Curse of Dimensionality

• What is binning in data mining?

---

**Binning** or discretization is the process of transforming numerical variables into categorical counterparts. An example is to **bin** values for Age into categories such as 20-39, 40-59, and 60-79. Numerical variables are usually discretized in the modeling methods based on frequency tables (e.g., decision trees).

**Variables** can be classified as **categorical** (aka, qualitative) or quantitative (aka, numerical). **Categorical**. **Categorical variables** take on values that are names or labels. The color of a ball (e.g., red, green, blue) or the breed of a dog (e.g., collie, shepherd, terrier) would be **examples of categorical variables**.

The curse of dimensionality refers to various phenomena that arise when analyzing and organizing data in high-dimensional spaces that do not occur in low-dimensional settings such as the three-dimensional physical space of everyday experience. [Wikipedia](#)

things get too complicated with your data model when adding additional dimensions

# Binning

- **Data binning** or **bucketing** is a data pre-processing technique used to reduce the effects of minor observation errors.
- The original data values which fall in a given small interval, a bin, are replaced by a value representative of that interval, often the central value.

# Categorical, Ordered

- A categorical variable (sometimes called a nominal variable) is one that has two or more categories, but there is no ordering to the categories.
- E.g. Hair color is a categorical variable having a number of categories (blonde, grey, black)
- Ordered - suppose you have a variable, economic status, with three categories (low, medium and high). Measures some “degree” within the category.

# Overfitting , Generalization

Overfitting is a general problem that plagues all machine learning methods.

A learning algorithm is said to overfit if it is:

- more accurate in fitting known data (i.e. training data ) (hindsight)
- less accurate in predicting new data (i.e. test data ) (foresight)
- Occurs when a classifier fits the training data too tightly.
- Works well on the training data but not on independent test data.




# Overfitting cont'd

- Overfitting occurs when a model begins to memorize training data rather than learning to generalize from trend.
- The more difficult a criterion is to predict (i.e., the higher its uncertainty), the more noise exists in past information that need to be ignored. The problem is determining which part to ignore.
- Overfitting generally occurs when a model is excessively complex, such as having too many parameters relative to the number of observations.

# Distance

- Used in classification type algorithms
- Measuring the closeness or similarity of objects with a notion of distance.

# Dimensionality – more variables greater performance penalty.



Curse of Dimensionality  
Increases exponentially with # of vars.  
heavy performance penalty if # of vars rises greatly

# Dimensional Reduction

- It reduces the time and storage space required.
- Removal of multi-collinearity ( variables that are related ) improves the performance of the machine learning model.
- It becomes easier to visualize the data when reduced to very low dimensions such as 2D or 3D.

# Types of models

test question

- **Descriptive**  
*Provide insight into what has happened.*
- **Prescriptive**  
*Advice on how to optimize*
- **Predictive**  
*Forecasts provide insight on what could happen in the future.*

# Descriptive Models

- **Decision tree:**

creates a tree based on the attribute values that play an important role in segmentation.

- **Association rule:** e.g. if ppl buy meat, they will likely buy onions; should put these things nearby in the grocery store

identifies the association between attributes.

One of the most common usages of this is to perform a market-basket analysis.

- **Clustering:**

categorizes items in groups with similar attribute values.

- **Naïve Bayes:**

Uses the Bayesian technique for categorization of elements. It is useful for finding attributes that affect the generation of results; for example, finding the prospective buyers of a product.

# Descriptive models cont'd

- **Linear regression:**

Part decision tree that finds linear relationships between variables.

Good option for figuring out the trend between continuous variables, for example, marketing costs and sales.

- **Neural network:**

Works with the state of the input and the predictable variables and generates the possibility of the state's relationships.

Good candidate to answer text mining questions.

- **Logistic regression:**

Version of the neural network algorithm; it calculates the effect of input variables on outputs and generates weights based on calculations. This algorithm can be used to find the weight factor of different inputs to generate the result.

- **Sequence clustering:**

- Identifies the sequence of variables. It can be used to answer the work order or the clicking path on a website.

- **Time Series:**

Used for time-based analysis, for example, predicting sales for the next couple of months.

# Decision Trees

## Decision Trees in Industry

How well does it work?


Many case studies have shown that decision trees are at least as accurate as human experts.

- a study for diagnosing breast cancer

-

-

Predictors				Target
Outlook	Temp.	Humidity	Windy	Play Golf
Rainy	Hot	High	False	No
Rainy	Hot	High	True	No
Overcast	Hot	High	False	Yes
Sunny	Mild	High	False	Yes
Sunny	Cool	Normal	False	Yes
Sunny	Cool	Normal	True	No
Overcast	Cool	Normal	True	Yes
Rainy	Mild	High	False	No
Rainy	Cool	Normal	False	Yes
Sunny	Mild	Normal	False	Yes
Rainy	Mild	Normal	True	Yes
Overcast	Mild	High	True	Yes
Overcast	Hot	Normal	False	Yes
Sunny	Mild	High	True	No






# How does one build a decision tree

- For the root node, select the attribute with the highest entropy
- This is calculated by frequency using the following formula

$$E(S) = \sum_{i=1}^c -p_i \log_2 p_i$$

- e.g:

Play Golf	
Yes	No
9	5



Entropy(PlayGolf) = Entropy (5,9)  
= Entropy (0.36, 0.64)  
= - (0.36 log<sub>2</sub> 0.36) - (0.64 log<sub>2</sub> 0.64)  
= 0.94

- The #'s coming from the frequency counts

# Entropy using the frequency table of two attributes:

$$E(T, X) = \sum_{c \in X} P(c)E(c)$$

		Play Golf		
		Yes	No	
Outlook	Sunny	3	2	5
	Overcast	4	0	4
	Rainy	2	3	5
				14



$$\begin{aligned} E(\text{PlayGolf}, \text{Outlook}) &= P(\text{Sunny}) * E(3,2) + P(\text{Overcast}) * E(4,0) + P(\text{Rainy}) * E(2,3) \\ &= (5/14) * 0.971 + (4/14) * 0.0 + (5/14) * 0.971 \\ &= 0.693 \end{aligned}$$

Find the next attribute based on the information gain computed against the target attribute

*Step 1:* Calculate entropy of the target.

$$\begin{aligned}\text{Entropy}(\text{PlayGolf}) &= \text{Entropy}(5,9) \\ &= \text{Entropy}(0.36, 0.64) \\ &= -(0.36 \log_2 0.36) - (0.64 \log_2 0.64) \\ &= 0.94\end{aligned}$$

For each candidate attribute, calculate the information gain as below

		Play Golf	
		Yes	No
Outlook	Sunny	3	2
	Overcast	4	0
	Rainy	2	3
Gain = 0.247			

		Play Golf	
		Yes	No
Temp.	Hot	2	2
	Mild	4	2
	Cool	3	1
Gain = 0.029			

		Play Golf	
		Yes	No
Humidity	High	3	4
	Normal	6	1
Gain = 0.152			

		Play Golf	
		Yes	No
Windy	False	6	2
	True	3	3
Gain = 0.048			

$$Gain(T, X) = Entropy(T) - Entropy(T, X)$$

Select the attribute ( outlook) with the largest information gain

		Play Golf	
		Yes	No
Outlook	Sunny	3	2
	Overcast	4	0
	Rainy	2	3
Gain = 0.247			

Outlook	Temp	Humidity	Windy	Play Golf
Sunny	Mild	High	FALSE	Yes
Sunny	Cool	Normal	FALSE	Yes
Sunny	Cool	Normal	TRUE	No
Sunny	Mild	Normal	FALSE	Yes
Sunny	Mild	High	TRUE	No
Overcast	Hot	High	FALSE	Yes
Overcast	Cool	Normal	TRUE	Yes
Overcast	Mild	High	TRUE	Yes
Overcast	Hot	Normal	FALSE	Yes
Rainy	Hot	High	FALSE	No
Rainy	Hot	High	TRUE	No
Rainy	Mild	High	FALSE	No
Rainy	Cool	Normal	FALSE	Yes
Rainy	Mild	Normal	TRUE	Yes

# Evaluating classifiers – confusion matrix

- Calculating the accuracy of the classifier

	Predicted Class	
	$C_0$	$C_1$
Actual Class	$n_{0,0}$ = Number of correctly classified $C_0$ cases	$n_{0,1}$ = Number of $C_0$ cases incorrectly classified as $C_1$
	$n_{1,0}$ = Number of $C_1$ cases incorrectly classified as $C_0$	$n_{1,1}$ = Number of correctly classified $C_1$ cases

Table 4.1: Classification Matrix: Meaning of Each Cell

# Confusion matrix

- Summarizes the correct and incorrect classification
- Rows and Columns correspond to the true and predicted classes
- Upper right and lower left diagonal cells give the correct classification
- The other cells give the misclassification
- Total observations  $n = n_{0,0} + n_{0,1} + n_{1,0} + n_{1,1}$
- Accuracy =  $((n_{0,0} + n_{1,1}) / n) \times 100$
- Error =  $((n_{0,1} + n_{1,0}) / n)$

# An example


Classification Confusion Matrix		
	Predicted Class	
Actual Class	1	0
1	201	85
0	25	2689

Figure 4.2: Classification Matrix Based on 3000 Observations and Two Classes


- $\text{Err} = (25 + 85) / 3000 = 3.67\%$
- $\text{Accuracy} = (201 + 2689) / 3000 = 96.3\%$



# Decision Tree SSAS



# Dependency Network – Contribution of variables to decision



Strength of contribution depends on the distance from the target node.