

Learning to Distrust Misleading Text: Preference Optimization for Reducing Text Bias in Vision-Language Models

Anonymous CVPR submission

Paper ID *****

Abstract

Vision-language models (VLMs) often treat textual context as a shortcut, even when that text conflicts with visual evidence. This “blind faith in text” is especially problematic in document and visual question answering, where auxiliary text may be incomplete, stale, adversarial, or automatically retrieved. We study whether preference optimization can reduce this failure mode without sacrificing normal visual question answering performance. The goal is not to teach the model to ignore all text: auxiliary text is often useful when it agrees with the image, and the model usually does not know in advance whether the text is reliable. Starting from corrupted-text evaluations, we mine model-specific text-following errors: cases where the model is wrong and its wrong answer is copied from the corrupted auxiliary text. We then train VLMs with Direct Preference Optimization (DPO), preferring the image-grounded answer over the model’s own text-following error. On DocVQA with Qwen3-VL-8B, text-following span DPO improves corrupted accuracy from 0.715 to 0.915 and reduces the fraction of incorrect answers copied from corrupted text from 89.5% to 47.1%. A multi-condition error-mined extension further improves accuracy to 0.920 and reduces this text-following rate to 43.8%. By contrast, GRPO-style sampled-answer optimization and auxiliary SFT preservation do not improve over DPO. Experiments on VQAv2 and transfer to Qwen2-VL and LLaVA-Next show that the method works best when the base VLM already has sufficient visual and OCR competence. These results suggest that high-precision preference pairs are an effective and practical mechanism for correcting text bias in VLMs, while also revealing clear boundary conditions for the approach.

1. Introduction

Vision-language models (VLMs) are increasingly used in settings where images are accompanied by textual context: document images with OCR, screenshots with metadata, re-

trieved descriptions, captions, or user-provided hints. Such text can be helpful when it is correct, but it can also become a shortcut. When textual context conflicts with the image, a VLM may answer from the text rather than from visual evidence. Deng et al. [2] describe this phenomenon as “blind faith in text”, showing that several VLMs disproportionately trust textual information under conflict.

This failure is not merely a benchmark artifact. In practical systems, auxiliary text is often produced by retrieval, OCR, captioning, or prior model predictions. All of these sources can be noisy. If a VLM over-trusts such text, the model can produce confident but visually ungrounded answers. For document VQA, this is particularly important: the model must decide whether the image or the accompanying text should be trusted when they disagree.

A natural objection is that the model could simply ignore the auxiliary text whenever corruption is possible. This is not a satisfactory solution. First, in real use the system is not told whether the text is corrupted, matched, or irrelevant. Second, auxiliary text is often genuinely useful: when it matches the image, ignoring it can remove information that helps the model answer. Third, blind text removal does not teach conflict resolution; it only changes the input distribution. The desired behavior is conditional trust: use text when it is supported by the image, but reject it when it contradicts visual evidence.

We ask a targeted question: *Can we reduce text-following failures by directly training a VLM to prefer image-grounded answers over its own corrupted-text errors?* Our key observation is that the corrupted-text setting naturally produces preference pairs. If a model answers incorrectly and its prediction appears in the corrupted auxiliary text, then the model has likely followed the misleading text. The ground-truth answer can be used as the preferred response, and the model’s text-following prediction can be used as the dispreferred response. This gives a high-precision preference signal without manual labeling.

We instantiate this idea with Direct Preference Optimization (DPO) [7]. Unlike online reinforcement learning methods such as PPO or GRPO [8], DPO directly optimizes pair-

wise preferences. This is well aligned with our setting: the contrastive pair is already available as {image-grounded answer, text-following wrong answer}. Prior work already showed that supervised fine-tuning (SFT) with text augmentation can mitigate blind faith in text [2]. Our goal is not to deny that result, but to ask whether a more targeted preference signal can address the same failure mode. Instead of training on a broad mixture of text-only, original VQA, match, corruption, and irrelevance samples, we mine the specific cases where the model follows corrupted text and directly contrast that answer with the ground truth. We compare DPO against GRPO-style sampled-answer optimization, auxiliary SFT preservation, model transfer, and dataset transfer.

Our study makes three empirical findings. First, on DocVQA with Qwen3-VL-8B, DPO sharply improves corrupted-text robustness while reducing the rate of text-copying among remaining errors. Second, broadening DPO from corrupted-only text-following errors to multi-condition error-mined pairs yields the strongest result, suggesting that condition-specific error mining can improve stability. Third, the method has an important boundary condition: it works best when the base VLM already has enough visual/OCR competence. Qwen-family models benefit substantially, while LLaVA-Next models under our prompt and template show weak DocVQA base performance and limited benefit.

We summarize our contributions as follows:

- We define an automatic text-following error mining procedure for corrupted-text VQA, requiring both incorrectness and overlap between the wrong prediction and corrupted auxiliary text.
- We show that DPO on these mined pairs substantially reduces text bias on DocVQA and transfers directionally to VQAv2 and Qwen2-VL.
- We position DPO relative to the SFT mitigation studied by Deng et al. [2], and compare it with GRPO, auxiliary SFT preservation, multi-condition error mining, and model transfer.

2. Related Work

Text bias in VLMs. VLMs are trained to fuse visual and textual inputs, but fusion can become asymmetric when textual context is easier to exploit than visual evidence. The most directly related work is Words or Vision [2], which introduces corrupted textual variations and shows that VLMs may trust text over vision when the two conflict. Our work follows this diagnostic setting but focuses on mitigation through preference optimization. Rather than only measuring the degradation under corrupted text, we use the model’s own corrupted-text failures as training signal. Deng et al. [2] also study SFT with text augmentation and show that increasing SFT data reduces reliance on corrupted or

irrelevant text while preserving the ability to use matched text. They further note that text-only data helps prevent models from rejecting text indiscriminately. We build on this insight: the goal is conditional text use, not blanket text removal. Our contribution is to replace broad SFT augmentation with model-specific preference pairs mined from actual text-following failures.

Document and visual question answering. DocVQA [6] evaluates question answering over document images, requiring OCR, layout understanding, and reasoning over visual text. VQAv2 [3] evaluates open-ended visual question answering with reduced language priors compared to earlier VQA datasets. We use DocVQA as the main testbed because conflict between visual document evidence and auxiliary text is central to the task. VQAv2 is used as a transfer check to test whether the mitigation is specific to document images.

Preference optimization. Preference optimization has become a common alternative to supervised fine-tuning for aligning generative models. DPO [7] directly optimizes a policy from chosen/rejected pairs without training an explicit reward model or running online RL. This makes it attractive for our setting because corrupted-text evaluation yields natural preference pairs. GRPO [8] is an online reinforcement learning method that estimates a group-relative baseline from multiple sampled responses. We compare DPO with GRPO-style optimization and find that free-form sampled-answer rewards are less effective for this failure mode.

Modern VLMs. Qwen2-VL [9] and Qwen2.5-VL [1] emphasize dynamic-resolution visual processing and strong document/OCR capability. LLaVA-style models [4, 5] provide a widely used visual instruction tuning framework. Our transfer experiments suggest that these model families differ substantially in the base competence needed for text-bias correction.

3. Method

3.1. Problem Setup

Each example consists of an image x , a question q , auxiliary text t , and a ground-truth answer y . We consider three main textual conditions. In the *match* condition, the auxiliary text is consistent with the image. In the *irrelevant* condition, the text is unrelated. In the *corrupted* condition, the text contains a plausible but wrong answer. The desired behavior is not to ignore text unconditionally. Instead, the model should use text when it is reliable and fall back to visual evidence when text conflicts with the image.

3.2. Mining Text-Following Errors

We first evaluate a base VLM on corrupted examples. Let $\hat{y}$ be the model prediction. We define a *text-following error* when all of the following hold:

1. the model prediction is incorrect;
2. the prediction is non-empty and does not match the ground truth;
3. the prediction appears in the corrupted auxiliary text.

For the third condition, we use normalized string matching. For multi-token answers, we also accept high token overlap with the auxiliary text. This filtering is important: an arbitrary wrong answer is not necessarily a text-bias error, but an incorrect prediction copied from corrupted text is a much stronger signal.

For each mined error, we construct a DPO pair:

$$y^+ = y, \quad y^- = \hat{y}, \quad (1)$$

where y^+ is the image-grounded answer and y^- is the model’s text-following wrong answer. We call this dataset *text-following span DPO*.

3.3. DPO Objective

Given a policy π_θ and a reference policy π_{ref} , DPO optimizes the preference that y^+ should be more likely than y^- under the prompt (x, q, t) :

$$\mathcal{L}_{\text{DPO}} = -\log \sigma \left(\beta \left[\log \pi_\theta(y^+ | x, q, t) - \log \pi_{\text{ref}}(y^+ | x, q, t) - \log \pi_\theta(y^- | x, q, t) + \log \pi_{\text{ref}}(y^- | x, q, t) \right] \right). \quad (2)$$

In our setting, this objective directly encodes the desired correction: the image-grounded answer should be preferred over the corrupted-text answer.

3.4. Multi-Condition Error-Mined DPO

Text-following span DPO uses only corrupted examples. To reduce drift and improve stability, we also test a multi-condition extension. We mine errors from corrupted, match, irrelevant, and no-text evaluations. For corrupted examples, we keep the strict text-following filter: the wrong prediction must appear in corrupted auxiliary text. For match, irrelevant, and no-text examples, we use a broader condition-specific error filter: the prediction must be incorrect, non-empty, and distinct from the ground truth.

We assign lower weights to non-corrupted errors:

$$\begin{aligned} w_{\text{corrupted}} &= 1.0, & w_{\text{match}} &= 0.25, \\ w_{\text{irrelevant}} &= 0.5, & w_{\text{no-text}} &= 0.5. \end{aligned} \quad (3)$$

This preserves the central text-bias signal while adding weak regularization from other conditions.

Table 1. DocVQA corrupted held-out results with Qwen3-VL-8B.

Method	Acc.	Incorrect aux-hit	Corr./Reg.
Base	0.715	89.5%	–
TF-span DPO, r8	0.900	55.0%	37 / 0
TF-span DPO, r16	0.915	47.1%	40 / 0
Multi-cond. error DPO	0.920	43.8%	41 / 0

3.5. GRPO-Style Baselines

We also test GRPO-style optimization. For each prompt, the model samples multiple candidate answers. A reward function gives positive reward for matching the chosen answer and penalties for matching the rejected answer, misleading spans mined from corrupted text, or any answer copied from the auxiliary text. The reward also mildly encourages short answer-like completions. This tests whether online sampled-answer optimization can discover the same correction signal without explicit pairwise DPO.

4. Experiments

4.1. Metrics

We report three complementary metrics. *Corrupted accuracy* measures task performance when auxiliary text is misleading. *Incorrect aux-hit* measures the fraction of incorrect predictions that appear in the corrupted auxiliary text. Lower incorrect aux-hit indicates less text-following among remaining errors, but it is not sufficient by itself: a model could reduce aux-hit by hallucinating unrelated answers. Therefore, we interpret it together with corrupted accuracy and preservation on match/irrelevant conditions. We also report corrected/regressed counts relative to the base model when available.

4.2. DocVQA Main Results

DocVQA is our main testbed. We use Qwen3-VL-8B-Instruct as the primary model and evaluate on a held-out corrupted split. Table 1 shows that text-following span DPO substantially improves both accuracy and text-bias behavior. Increasing LoRA rank from 8 to 16 improves the result further, while the multi-condition error-mined variant gives the best overall performance.

The multi-condition result suggests that the highest-performing variant is not corrupted-only. However, the corrupted filter remains essential: corrupted rows still require the prediction to be copied from corrupted auxiliary text. The additional match, irrelevant, and no-text errors act as weak condition-specific regularizers rather than replacing the text-following signal.

4.3. DPO versus GRPO

We compare DPO with GRPO-only and DPO-to-GRPO variants on the same disjoint DocVQA split. GRPO sam-

Table 2. GRPO-style optimization does not improve over DPO on DocVQA.

Variant	Init	Acc.	Incorrect aux-hit
Base	–	0.715	89.5%
GRPO-only, 100 steps	base	0.710	89.7%
GRPO-only, 300 steps	base	0.705	89.8%
GRPO-only, dense reward	base	0.705	89.8%
TF-span DPO	base	0.900	55.0%
DPO → GRPO	DPO	0.900	60.0%

ples multiple answers per prompt and optimizes a reward that encourages correctness and penalizes copying corrupted text. Despite this denser reward, GRPO does not move the held-out greedy behavior meaningfully. Table 2 shows that DPO is the effective intervention in our setting.

DPO-to-GRPO changes only a few held-out predictions relative to DPO and does not improve accuracy. This supports our hypothesis: when high-precision chosen/rejected pairs are available, direct pairwise optimization provides a clearer learning signal than free-form sampled-answer rewards.

4.4. SFT: Prior Mitigation and Our Ablation

The original Words or Vision study already evaluates SFT with text augmentation as a mitigation strategy [2]. That SFT setting uses a broader training mixture, including original VQA, text-only, match, corruption, and irrelevance samples, and shows that SFT can reduce text reliance while maintaining the ability to benefit from matched text. This is an important baseline and motivates our own mitigation study.

Our experiment is different. We do not reproduce the full augmented SFT recipe from Deng et al. [2]. Instead, we test a narrower question: after constructing text-following DPO pairs, can an auxiliary SFT preservation loss on match/irrelevant examples further stabilize the model? This is a preservation ablation, not a claim that SFT in general is ineffective. SFT is plausible because it directly teaches the model to output correct answers. However, the central error in our setting is not simply that the model does not know the answer; it is that the model prefers a misleading textual answer over visual evidence. SFT provides only a positive target, while DPO explicitly contrasts the image-grounded answer against the text-following wrong answer.

Our SFT experiment uses auxiliary preservation data from match and irrelevant conditions and mixes it with span DPO. As shown in Table 3, this does not improve over pure DPO on VQAv2: corrupted accuracy decreases from 0.645 to 0.635, incorrect aux-hit increases from 40.8% to 42.5%, and match/irrelevant preservation remains unchanged. Thus, in our experiments, auxiliary SFT preservation acts as a negative ablation, while the prior full SFT aug-

Table 3. VQAv2 transfer results with Qwen3-VL-8B.

Variant	Corr. Acc.	Aux-hit	Match	Irr.
Base	0.545	65.9%	0.92	0.77
Span DPO	0.645	40.8%	0.90	0.75
Span DPO + SFT	0.635	42.5%	0.90	0.75

Table 4. Model transfer on DocVQA. DPO helps Qwen2-VL but not LLaVA-Next under our setting.

Model	Setting	Acc.	Aux-hit	Corr./Reg.
Qwen2-VL-7B	base	0.570	93.0%	–
Qwen2-VL-7B	span DPO	0.775	86.7%	41 / 0
LLaVA-N-7B	base	0.105	90.5%	–
LLaVA-N-7B	span DPO	0.100	91.7%	1 / 2
LLaVA-N-13B	base	0.115	92.7%	–
LLaVA-N-13B	span DPO	0.130	95.4%	3 / 0

mentation result remains a valid mitigation baseline from the original work.

4.5. VQAv2 Transfer Check

We repeat the disjoint split protocol on VQAv2. The effect is positive but weaker than on DocVQA. As shown in Table 3, span DPO improves corrupted accuracy by 10 points and reduces incorrect aux-hit, but match and irrelevant preservation drop slightly. Adding auxiliary SFT preservation does not recover this drop and slightly worsens corrupted performance.

4.6. Model Transfer

We test whether the same mitigation extends beyond Qwen3-VL. Table 4 summarizes Qwen2-VL-7B and LLaVA-Next results on DocVQA. Qwen2-VL benefits substantially, improving from 0.570 to 0.775 corrupted accuracy. LLaVA-Next, however, has very low base DocVQA accuracy under our prompt/template, and DPO provides little benefit.

These results show that the method is not simply a universal post-hoc fix. It requires a base model that can already solve the task visually; DPO then teaches the model to resist misleading text.

5. Analysis and Discussion

5.1. Why DPO Fits This Problem

The corrupted-text setting gives unusually clean preference pairs. For many failures, the model’s wrong answer is directly copied from the corrupted auxiliary text. Thus the comparison is explicit: the image-grounded answer should be preferred over the text-following wrong answer. DPO optimizes exactly this comparison. This complements,

rather than invalidates, the SFT mitigation in Words or Vision [2]. SFT with text augmentation teaches the model from a balanced mixture of cases and can reduce broad text reliance. Our DPO variant instead uses a narrower but sharper signal: for each mined failure, it tells the model which specific text-derived answer should lose to the visual answer. In contrast, GRPO must first sample useful candidate answers and then rely on a hand-designed reward. If the sampled candidates rarely contain the correct answer, or if most candidates are similar text-following errors, the relative reward signal is weak. This explains why GRPO logs can show diagnostic reward events while greedy held-out predictions barely change.

5.2. Why Not Simply Ignore the Text?

Ignoring auxiliary text is an appealing but incomplete baseline. It would avoid some corrupted-text failures, but it does not solve the actual decision problem faced by a VLM. At inference time, the model is not given a label saying whether the text is matched, irrelevant, or corrupted. If the model learns to discard text wholesale, it can lose useful information in match cases and may fail to exploit reliable OCR or retrieved context.

Our objective is therefore not “use less text” but “use text conditionally”. The model should keep using textual context when it is visually supported and reject it when it conflicts with the image. DPO is appropriate because it changes the model’s preference in exactly the conflict cases we can identify:

image-grounded answer $\succ$ text-following wrong answer. (4)

This is different from input ablation or prompt-level instruction to ignore text. The latter can reduce exposure to misleading text, but it does not teach the model which answer should be preferred when both visual evidence and misleading text are present. Our use of match and irrelevant preservation metrics is intended to check precisely this point: a successful method should improve corrupted robustness without collapsing into text avoidance.

5.3. Interpreting Incorrect Aux-Hit

Incorrect aux-hit is useful but should not be optimized alone. A lower value means fewer remaining errors are copied from corrupted text, but it does not guarantee better visual grounding. For example, a model could avoid the corrupted text yet hallucinate an unrelated answer. Therefore, successful text-bias correction should satisfy three conditions:

1. corrupted accuracy should increase;
2. incorrect aux-hit should decrease;
3. match and irrelevant performance should be preserved.

Our main DocVQA results satisfy these conditions. Some negative ablations do not: they reduce neither error copy-

ing nor accuracy, or they preserve match performance while failing on corrupted examples.

5.4. Why Multi-Condition Error Mining Helps

Text-following span DPO is the core filtering strategy, but the best result comes from multi-condition error-mined DPO. This does not mean that unfiltered errors are sufficient. Rather, corrupted errors remain strictly filtered for text-following behavior, while other conditions contribute lower-weight stability signals. This helps prevent the model from over-specializing to the corrupted prompt format. The gain is modest because non-corrupted failures are sparse in DocVQA, but it consistently improves the main held-out metric.

5.5. Boundary Conditions

Our transfer experiments reveal a clear boundary condition. The method works when the base VLM already has sufficient visual and OCR competence. Qwen-family models satisfy this condition on DocVQA and improve substantially. LLaVA-Next models, under our prompt/template, have very low base DocVQA accuracy. In this regime, DPO cannot create document-reading ability from scratch; it can only alter preferences among answers the model can already represent.

TextVQA experiments lead to a related conclusion. DocVQA-trained DPO transfers weakly to TextVQA and does not reliably fix LLaVA-specific TextVQA conflict failures. Even after mining larger LLaVA-specific TextVQA DPO data and adding strict+preserve pairs, corrupted performance does not improve. This suggests that TextVQA conflict involves different OCR and answer-format dynamics than DocVQA. Therefore, we treat TextVQA and LLaVA results as boundary analyses rather than main success claims.

5.6. Limitations

Our study has several limitations. First, the text-following filter is an operational definition, not a causal proof. If a wrong answer appears in corrupted text, the model likely followed the text, but accidental overlap is possible. Second, most experiments use a single held-out split and a limited number of seeds due to compute constraints. Third, our GRPO implementation uses free-form sampled answers; a candidate-constrained GRPO-style objective may be a stronger comparison. Finally, the method assumes ground-truth answers are available for preference construction. This is suitable for benchmark adaptation and supervised mitigation, but not directly for fully unlabeled deployment.

6. Conclusion

We studied preference optimization as a mitigation for VLM text bias under corrupted auxiliary text. By mining

text-following errors and training with DPO, we convert a diagnostic failure mode into a direct preference-learning signal. On DocVQA, this substantially improves corrupted-text accuracy and reduces the rate at which remaining errors copy misleading text. The strongest variant, multi-condition error-mined DPO, combines strict corrupted-error filtering with lower-weight errors from match, irrelevant, and no-text conditions. GRPO-style sampled-answer optimization and preservation SFT do not improve over DPO in our experiments. These comparisons also clarify why simply ignoring text is not the desired solution: the target behavior is conditional trust, not blanket text removal. The results support a precise conclusion: DPO is effective when the base VLM already has visual/OCR competence and the preference pairs accurately capture text-following failures. When this condition is not met, as in our LLaVA-Next DocVQA setting, preference optimization alone is insufficient.

References

- [1] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2.5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025. 2
- [2] Ailin Deng, Tri Cao, Zhirui Chen, and Bryan Hooi. Words or vision: Do vision-language models have blind faith in text? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025. 1, 2, 4, 5
- [3] Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017. 2
- [4] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in Neural Information Processing Systems*, 2023. 2
- [5] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge. *LLaVA project blog*, 2024. 2
- [6] Minesh Mathew, Dimosthenis Karatzas, and C. V. Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2021. 2
- [7] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, 2023. 1, 2
- [8] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. 1, 2
- [9] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin

Ge, et al. Qwen2-vl: Enhancing vision-language model’s perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*, 2024. 2

481
482
483