

# Multi-step RL: Unifying Algorithm

Kirill Bobyrev

November 6, 2017

# Plan

- 1 Introduction
- 2 From MC and one-step TD to multi-step Bootstrapping
- 3  $n$ -step methods
  - 1-step into  $n$ -steps transition
  - Backups overview
  - Off-policy learning
- 4  $Q(\sigma)$  algorithm
  - Relation to other algorithms
  - Backups
  - Off-policy learning
  - Algorithm details
- 5 Experiments
- 6 Conclusion

# Results

Introducing algorithm  $Q(\sigma)$  with following properties

- Model-free
- Can be trained both off- and on-policy
- Uses  $n$ -step backup rule
- Generalizes a huge number of existing algorithms while subsuming them as special cases
- Performs better given a reasonable choice of hyperparameter  $\sigma$

# Monte Carlo methods

- Sample many episodes
- MC every-visit backup:  $V(S_t) \leftarrow V(S_t) + \alpha[G_t - V(S_t)]$
- Does not need environment model

# TD methods

- Combines Monte Carlo and Dynamic Programming
- Does not need environment model
- Uses bootstrapping for updates
- Sample many steps instead of methods
- One-step TD backup:  $V(S_t) \leftarrow V(S_t) + \alpha[R_t - \gamma V(S_t)]$

# From 1-step to $n$ -step

Define multi-step return for TD:

$$G_{t:t+n} \doteq R_{t+1} + \gamma R_{t+2} + \dots + \gamma^{n-1} R_{t+n} + \gamma^n V_{t+n-1}(S_{t+n})$$


Using this multi-step return:

- Monte Carlo backup uses  $G_{t:T}$
- One-step TD backup uses  $G_{t:t+1}$

$n$ -step TD:  $V_{t+n}(S_t) \doteq V_{t+n-1}(S_t) + \alpha[G_{t:t+n} - V_{t+n-1}(S_t)]$

$Q(\sigma)$  is based on  $n$ -step Sarsa and  $n$ -step Tree Backup

# Backups: From one-step TD to MC




# n-step Sarsa

$$\delta_t^S = R_{t+1} + \gamma Q(S_{t+1}, A_{t+1}) - Q(S_t, A_t)$$

$$\delta_t^{ES} = R_{t+1} + \gamma \sum_a \pi(a|S_{t+1}) Q_t(S_{t+1}, a) - Q_{t-1}(S_t, A_t)$$



# n-step Sarsa and Expected Sarsa backup mechanisms



# Tree Backup

Tree Backup is the multi-step generalization of Expected Sarsa backup

$$G_{t:t+1} \doteq R_{t+1} + \gamma \sum_a \pi(a|S_{t+1}) Q_t(S_{t+1}, a) = \delta_t^{ES} + Q_{t-1}(S_{t+1}, a)$$


Hence  $n$ -step return of Tree Backup is a sum of TD errors:

$$G_{t:t+n} \doteq Q_{t-1}(S_t, A_t) + \sum_{k=t}^{\min t+n-1, T-1} \delta'_k \prod_{i=t+1}^k \gamma \pi(A_i|S_i)$$

Taking update rule from  $n$ -step Sarsa:

$$Q_{t+n}(S_t, A_t) \doteq Q_{t+n-1}(S_t, A_t) + \alpha [G_{t:t+n} - Q_{t+n-1}(S_t, A_t)]$$

# Tree Backup backup mechanism



# Sarsa and Tree Backup off-policy learning

**Sarsa** | **Tree Backup**

# Relation to other algorithms

Two families of multi-step algorithms:

- Algorithms that backup their actions and samples (Sarsa and Expected Sarsa)
- Algorithms that consider an expectation over all actions in their backup (Expected Sarsa and Tree Backup)

New parameter  $\sigma \in [0, 1]$ , which controls the degree of sampling at each step of the backup, unifies both families

# Details


Error modification:

$$\begin{aligned}\delta_t^\sigma &= \sigma_{t+1}\delta_t^S + (1 - \sigma_{t+1})\delta_t^{ES} \\ &= R_{t+1} + \gamma[\sigma_{t+1}Q_t(S_{t+1}, A_{t+1}) + (1 - \sigma_{t+1})V_{t+1}] - Q_{t-1}(S_t, A_t)\end{aligned}$$

Resulting return:

$$G_t^{(n)} = Q_{t-1}(S_t, A_t) + \sum_{k=t}^{\min t+n-1, T-1} \delta_k^\sigma \prod_{i=t+1}^k \gamma[(1 - \sigma_i)\pi(A_i|S) + \sigma_i]$$

# Backup comparisons



# Q( $\sigma$ ) off-policy learning

Q( $\sigma$ ) importance sampling for off-policy learning combines the off-policy learning ideas for base algorithms:

$$\rho_{t+1}^{t+n} = \prod_{k=t+1}^{\min t+n-1, T-1} \left( \sigma_k \frac{\pi(A_k|S_k)}{\mu(A_k|S_k)} + 1 - \sigma_k \right)$$



# $\sigma$ choosing strategies

- Constant  $\sigma = C$
- Altering  $\sigma(t) = 1, 0, 1, 0, \dots = [t \bmod 2 = 0]$
- Random  $\sigma(t) \sim \mathcal{U}[0, 1]$
- Decreasing or increasing over  $t$  (between 0 and 1)

# Algorithm description

```

1: Initialize  $S_0 \neq S_T$ ; select  $A_0$  according to  $\pi(\cdot|S_0)$ 
2: Store  $S_0$ ,  $A_0$  and  $Q(S_0, A_0)$ 
3: for  $t \leftarrow 0, T + n - 1$  do
4:   if  $t < T$  then
5:     Take action  $A_t$ , get  $R$ , observe and store  $S_{t+1}$ 
6:     if  $S_{t+1}$  is  $S_T$  then
7:       Store  $\delta_t^\sigma = R - Q(S_t, A_t)$ 
8:     else
9:       Select and store  $A_{t+1}$  according to  $\pi(\cdot|S_{t+1})$ 
10:      Store  $Q(S_{t+1}, A_{t+1})$ ,  $\sigma_{t+1}$ ,  $\pi(A_{t+1}|S_{t+1})$ 
11:      Calculate and store  $\delta_t^\sigma$ 
12:    end if
13:  end if
14:  if  $t \geq n$  then
15:    Calculate and store  $G_t^{(n)}$ 
16:    Perform backup:  $Q(S_t, A_t) \leftarrow S(t, A_t) + \alpha[G_t^{(n)} - Q(S_t, A_t)]$ 
17:  end if
18: end for

```

# Stochastic Windy Gridworld Environment

o	o	o	o	o	o	o	o	o	o
o	o	o	o	o	o	o	o	o	o
o	o	o	o	o	o	o	o	o	o
S	o	o	o	o	o	o	G	o	o
o	o	o	o	o	o	o	o	o	o
o	o	o	o	o	o	o	o	o	o
o	o	o	o	o	o	o	o	o	o
0	0	0	1	1	1	2	2	1	0

- Tabular navigation environment, agent is moved by upward "wind" by  $x$  cells specified below each corresponding column at the end of its turn
- Environment gives reward of  $-1$  after each step
- Agent returns to the closest valid state upon exiting the world
- Stochastic modification: agent ends up in one of 8 adjacent states with  $p = 0.1$

# Comparing Sarsa, Tree Backup, $Q(0.5)$ and dynamic $\sigma$

# Synopsis

- $n$ -step algorithms are derived from MC and one-step TD methods
- $Q(\sigma)$  unifies  $n$ -step Sarsa and Tree-backup
- $Q(\sigma)|_{\sigma=0}$  is Tree Backup
- $Q(\sigma)|_{\sigma=1}$  is  $n$ -step Sarsa

# References



Kristopher De Asis, J. Fernando Hernandez-Garcia, G. Zacharias Holland, Richard S. Sutton.

*Multi-step Reinforcement Learning: A Unifying Algorithm.*  
arXiv, 3 Mar 2017.



Richard S. Sutton, Andrew G. Barto.

*Reinforcement Learning: An Introduction.*  
MIT Press, Cambridge, MA, 19 Jun 2017 Draft.

# Materials

Presentation, code and other materials are available in the GitHub  
[repository](#)